

Package ‘ABHgenotypeR’

May 6, 2026

Type Package

Title Easy Visualization of ABH Genotypes

Version 1.0.1

Date 2016-02-04

Description Easy to use functions to visualize marker data from biparental populations. Useful for both analyzing and presenting genotypes in the ABH format.

License GPL-3

URL <http://github.com/StefanReuscher/ABHgenotypeR>

BugReports <http://github.com/StefanReuscher/ABHgenotypeR/issues>

LazyData TRUE

Imports ggplot2, reshape2, utils

RoxygenNote 5.0.1

Suggests knitr, rmarkdown

VignetteBuilder knitr

NeedsCompilation no

Author Stefan Reuscher [aut, cre],
Tomoyuki Furuta [aut]

Maintainer Stefan Reuscher <reuscher.stefan@gmail.com>

Repository CRAN

Date/Publication 2016-02-04 11:27:29

Contents

ABHgenotypeR	2
correctStretches	2
correctUndercalledHets	3
imputeByFlanks	3
plotAlleleFreq	4

plotCompareGenos	4
plotGenos	5
plotMarkerDensity	6
readABHgenotypes	7
reportGenos	8
writeABHgenotypes	8
Index	9

ABHgenotypeR	<i>ABHgenotypeR: A package for easy visualization and manipulating of ABH genotypes.</i>
--------------	--

Description

The ABHgenotypeR packages is meant as a companion packages in between the TASSEL GBS pipeline and R/qtl. It allows easy visualization of ABH-encoded genotypes in a .csv format as ouptut by the TASSEL ABHGenosPlugin which is also the format necessary for R/qtl input.

correctStretches	<i>Correct short miscalled stretches based on flanking alleles.</i>
------------------	---

Description

Correct short miscalled stretches based on flanking alleles.

Usage

```
correctStretches(inputGenos = "genotypes", maxHapLength = 1)
```

Arguments

inputGenos	A genotypes list object.
maxHapLength	The maximum length of stretches flanked by non-heterzygous sites that are changed. If set to 1 (default) only AXA or BXB will be corrected. If set to 2, both AXA and AXYA (or BXB and BXYB) will be corrected.

Value

A genotype object in which short miscalled stretches are corrected if both flanking alleles match.

Examples

```
## Not run: corrStretchGenos <- correctStretches(genotypes, maxHapLength = 3)
```

`correctUndercalledHets`*Correct undercalled heterozygous sites based on flanking alleles.*

Description

Correct undercalled heterozygous sites based on flanking alleles.

Usage

```
correctUndercalledHets(inputGenos = "genotypes", maxHapLength = 1)
```

Arguments

<code>inputGenos</code>	A genotypes list object.
<code>maxHapLength</code>	The maximum length of not heterozygous stretches flanked by heterzygous sites that are changed to heterozygous. If set to 1 (default) only HAH or HBH will be corrected. If set to 2, both HAH and HAAH (or HBH and HBBH) will be corrected.

Value

A genotype object in which undercalled heterozygous sites are corrected if both flanking alleles match.

Examples

```
## Not run: corrUndHetsGenos <- correctUndercalledHets(genotypes, maxHapLength = 3)
```

`imputeByFlanks`*Impute missing genotypes based on flanking alleles*

Description

Impute missing genotypes based on flanking alleles

Usage

```
imputeByFlanks(inputGenos = "genotypes")
```

Arguments

<code>inputGenos</code>	A genotypes list object.
-------------------------	--------------------------

Value

A genotype object in which missing data is imputed based on flanking alleles. Any number of N is replaced by either A, B or N if the alleles which flank the N match

Examples

```
## Not run: imputedGenos <- imputeByFlanks(genotypes)
```

plotAlleleFreq	<i>Plot the parental allele frequencies along the chromosomes.</i>
----------------	--

Description

Plot the parental allele frequencies along the chromosomes.

Usage

```
plotAlleleFreq(genos = "genotypes")
```

Arguments

genos The output of readABHgenotypes

Value

A plot of parental allele frequencies along the chromosomes. If the output is assigned a name a ggplot2 object is returned for further manipulation.

Examples

```
## Not run: plotAlleleFreq(genotypes)
## Not run: p <- plotAlleleFreq(genotypes)
```

plotCompareGenos	<i>Compare to genotype matrices</i>
------------------	-------------------------------------

Description

Compare to genotype matrices

Usage

```
plotCompareGenos(genos_1 = "genotypes_1", genos_2 = "genotypes_2",
  markerToPlot = "all", individualsToPlot = "all", chromToPlot = "all",
  CompColors = c("#000000", "#E69F00"), textSize = 12,
  showMarkerNames = FALSE, showIndividualNames = FALSE)
```

Arguments

genos_1	Output of readABHgenotypes
genos_2	Output of readABHgenotypes. Note that both genos object need to have identical numbers of marker x individuals.
markerToPlot	A character vector of marker names which appear in the plot. Defaults to all.
individualsToPlot	A character vector of individual names which appear in the plot. Defaults to all.
chromToPlot	A character vector of chromosome names which appear in the plot. Defaults to all.
CompColors	A character vector of length 2 giving the color names or values to use for different and identical markers. Defaults to black and orange.
textSize	The size of all text elements in the plot. Useful for making a nice plot. Defaults to 12.
showMarkerNames	Show the marker names along the x axis. This and showIndividualNames are useful when you display only a few markers and want them labeled. Defaults to FALSE.
showIndividualNames	Show individual names along the y axis.

Value

A graphical comparison of genotypes.

Examples

```
## Not run: plotCompareGenos(preImpGenotypes,postImpGenotypes)
## Not run: #for more examples see plotGenos()
```

plotGenos	<i>Plot graphical genotypes.</i>
-----------	----------------------------------

Description

Plot graphical genotypes.

Usage

```
plotGenos(genos = "genotypes", markerToPlot = "all",
  individualsToPlot = "all", chromToPlot = "all",
  alleleColors = c("#56B4E9", "#E69F00", "#009E73", "#000000"),
  textSize = 12, showMarkerNames = FALSE, showIndividualNames = FALSE)
```

Arguments

genos	The output of readABHgenotypes
markerToPlot	A character vector of marker names which appear in the plot. Defaults to all.
individualsToPlot	A character vector of individual names which appear in the plot. Defaults to all.
chromToPlot	A character vector of chromosome names which appear in the plot. Defaults to all.
alleleColors	A character vector of length 4 giving the color names or values to use for the A,B,H and n.d genotypes. Defaults to orange, blue, green and black.
textSize	The size of all text elements in the plot. Useful for making a nice plot. Defaults to 12.
showMarkerNames	Show the marker names along the x axis. This and showIndividualNames are useful when you display only a few markers and want them labeled. Defaults to FALSE.
showIndividualNames	Show individual names along the y axis.

Value

Graphical genotypes.

Examples

```
## Not run: plotGenos(genotypes)
markerNames <- c("marker1", "marker2", "marker3")
individualNames <- c("F2_100", "F2_101", "F2_102", "F2_103")
someColors <- c("black", "red", "gold", "white")
## Not run: plotgenos(genotypes, markerNames, individualNames, 1:3, someColors)

## Not run: p <- plotGenos(genotypes)
```

plotMarkerDensity *Plot the marker density along the chromosomes.*

Description

Plot the marker density along the chromosomes.

Usage

```
plotMarkerDensity(genos = "genotypes")
```

Arguments

genos	The output of readABHgenotypes
-------	--------------------------------

Value

A plot of marker densities along the chromosomes. If the output is assigned a name a ggplot2 object is returned for further manipulation.

Examples

```
## Not run: plotMarkerDensity(genotypes)
## Not run: p <- plotMarkerDensity(genotypes)
```

readABHgenotypes *Read in the output of the genosToABH plugin.*

Description

Read in the output of the genosToABH plugin.

Usage

```
readABHgenotypes(pathToABH, nameA = "A", nameB = "B", readPos = TRUE)
```

Arguments

pathToABH	The path and filename of the input file.
nameA	Name of the parent represented by "A" in the input file.
nameB	Name of the parent represented by "B" in the input file.
readPos	Should the function attempt read the physical position of markers from the input ?

Details

The input files should be a .csv file holding genotypes as specified by the qtl package and its "csvs" format. All characters in the genotype matrix which are not either A,B or H will be set to N. If readPos = TRUE (default) marker names must conform to S1_123456 meaning 123456 bp on chromosome 1. If FALSE, pos is set to NULL and needs to be manually constructed as shown in the examples. Note that this might throw off some plotting function.

Value

A genotype list object which holds the information from the input file. This list is the fundamental datastructure used by the other functions in this package. See the vignette for what each item in the list is.

Examples

```
## Not run: genotypes <- readABHgenotypes("./genotypes.csv", "NB", "OL")

## Not run: otherGenotypes <- readABHgenotypes("./otherGenotypes.csv", readPos = FALSE)
#arbitrary position to keep marker order intact
## Not run: therGenotypes$pos <- 1:length(otherGenotypes$marker_names)
```

reportGenos	<i>Report the total and relative number of each allele in a genotype object.</i>
-------------	--

Description

Report the total and relative number of each allele in a genotype object.

Usage

```
reportGenos(genos1)
```

Arguments

genos1 A genotypes list object.

Value

Console output of the total an relative number of each allele.

Examples

```
## Not run: reportGenos(preImputation)
```

writeABHgenotypes	<i>Export a genotype list to a .csv file.</i>
-------------------	---

Description

Export a genotype list to a .csv file.

Usage

```
writeABHgenotypes(genos = "genotypes", outfile = "./outfile.csv")
```

Arguments

genos The output of readABHgenotypes or one of the imputation/error correction functions.

outfile The path and filename of the output file.

Value

A file which can be used in R/qtl or elsewhere.

Examples

```
## Not run: writeABHgenotypes(genotypes, outfile = "./outfile_name.csv")
```

Index

ABHgenotypeR, [2](#)
ABHgenotypeR-package (ABHgenotypeR), [2](#)

correctStretches, [2](#)
correctUndercalledHets, [3](#)

imputeByFlanks, [3](#)

plotAlleleFreq, [4](#)
plotCompareGenos, [4](#)
plotGenos, [5](#)
plotMarkerDensity, [6](#)

readABHgenotypes, [7](#)
reportGenos, [8](#)

writeABHgenotypes, [8](#)