

Package ‘ActiSleep’

May 6, 2026

Type Package

Title Sleep Duration Estimate Algorithm

Version 0.2.2

Date 2024-06-17

Description Provides sleep duration estimates using a Pruned Dynamic Programming (PDP) algorithm that efficiently identifies change-points. PDP applied to physical activity data can identify transitions from wakefulness to sleep and vice versa. Baek, Jonggyu, Banker, Margaret, Jansen, Erica C., She, Xichen, Peterson, Karen E., Pitchford, E. Andrew, Song, Peter X. K. (2021) An Efficient Segmentation Algorithm to Estimate Sleep Duration from Actigraphy Data <[doi:10.1007/s12561-021-09309-3](https://doi.org/10.1007/s12561-021-09309-3)>.

License GPL-3

Imports dplyr, stringr, lubridate, accelerometry, DBI, RSQLite, lazyeval, methods, utils, tibble

Depends R (>= 3.5)

NeedsCompilation yes

Encoding UTF-8

RoxygenNote 7.3.1

Author Jonggyu Baek [aut],
Margaret Banker [aut],
Nathan Szeto [aut, cre],
Alice Cleynen [aut],
Guillem Rigail [aut],
Michel Koskas [aut]

Maintainer Nathan Szeto <nszeto@umich.edu>

Repository CRAN

Date/Publication 2024-06-19 09:10:14 UTC

Contents

AccelData	2
---------------------	---

aggregate_dat	3
cal_mean_idx	3
ChangeTimeVar	4
GetDiary_subj	4
GetEstSleepInterval_subj	5
read_agd	6
SearchSleepSeg	6
Segmentor-class	7
SleepDiary1Day	8
SleepDiary1Week	8
SleepEstEachDay	9

Index	12
--------------	-----------

AccelData	<i>Accelerometry Data</i>
-----------	---------------------------

Description

A dataset containing accelerometry data for a single subject in 1-minute epochs, includes vector magnitude and other measurements.

- date: Time and date of a single measurement.
- axis1: X-axis movement.
- axis2: Y-axis movement.
- axis3: Z-axis movement.
- steps: Steps taken by the subject.
- lux: Amount of light present, measured in lux.
- inclineOff: Incline off.
- inclineStanding: Incline standing.
- inclineSitting: Incline sitting.
- inclineLying: Incline lying.
- VM: Vector magnitude, calculated from x-, y-, and z-axis measurements.

Usage

```
data("AccelData")
```

Format

A data frame with 1351 rows and 11 variables.

aggregate_dat	<i>Aggregate Accelerometer Data</i>
---------------	-------------------------------------

Description

Obtain table from raw accelerometer table in 1-min intervals

Usage

```
aggregate_dat(datain, cutnum = 1, unit = c("min", "sec"), tz = "GMT")
```

Arguments

datain	raw ActiGraph GT3X data
cutnum	quantity of unit to serve as interval, default is 1
unit	time unit to use
tz	timezone, default is GMT

Value

data frame of accelerometer data aggregated by intervals

cal_mean_idx	<i>Calculate Mean Index</i>
--------------	-----------------------------

Description

Calculate the mean index of a segment

Usage

```
cal_mean_idx(i, datain, idx_start, idx_end)
```

Arguments

i	segment index
datain	activity data, must be a data frame
idx_start	array of segment start indices
idx_end	array of segment end indices

Value

mean value of segment indices

ChangeTimeVar *Reformat Time Variable*

Description

Reformat the time variable to match analysis-ready format

Usage

```
ChangeTimeVar(datain, col_idx, format = "%Y-%m-%d %H:%M:%S")
```

Arguments

datain	input dataset, must be a data frame
col_idx	index of column to convert to date object
format	format of input date data, default is YYYY-MM-DD HH:MM:SS

Value

dataframe with formatted time values

Examples

```
data("SleepDiary1Week")

ChangeTimeVar(
  SleepDiary1Week,
  col_idx = c(5:18),
  format = "%Y-%m-%d %H:%M:%S")
```

GetDiary_subj *Diary In/Out-bed Times*

Description

Obtain table of in-bed and out-bed times from sleep diary data

Usage

```
GetDiary_subj(datain, subj_idx, idx_bed, idx_wake, tz = "GMT")
```

Arguments

datain	input dataset, must be a data frame
subj_idx	index indicating subject
idx_bed	array specifying indices for in-bed time data
idx_wake	array specifying indices for out-bed time data
tz	timezone, default is GMT

Value

dataframe with in-bed and out-bed times

Examples

```
data("SleepDiary1Week")

SleepDiary1Week <-
ChangeTimeVar(SleepDiary1Week, c(5:18), format = "%m/%d/%Y %H:%M")

colIdx_diary_bed <- c(1:7) * 2 - 2 + 5
colIdx_diary_wake <- c(1:7) * 2 - 1 + 5

GetDiary_subj(
  SleepDiary1Week,
  1,
  colIdx_diary_bed,
  colIdx_diary_wake,
  tz = "GMT")
```

GetEstSleepInterval_subj

Estimated sleep interval

Description

Obtain in-bed and out-bed times from diary data

Usage

```
GetEstSleepInterval_subj(
  datain,
  bed = "22:00:00",
  wake = "8:00:00",
  tz = "GMT"
)
```

Arguments

datain	diary data
bed	default in-bed time
wake	default out-bed time
tz	timezone, default is GMT

Value

data frame containing in-bed and out-bed times based on sleep diary

read_agd	<i>Read in AGD filedata</i>
----------	-----------------------------

Description

Obtain a list of AGD filenames and data

Usage

```
read_agd(file, tz = "GMT", sec = 10)
```

Arguments

file	AGD data file
tz	timezone, default is GMT
sec	time interval used to set date

Value

list of AGD filenames and data

SearchSleepSeg	<i>Find specific sleep segment</i>
----------------	------------------------------------

Description

Obtain specific sleep segment based on day, indices, etc.

Usage

```
SearchSleepSeg(  
  date,  
  Y,  
  idx_start,  
  idx_end,  
  NoPA_cut = 0.7,  
  sleep_mins = 30,  
  SI_i,  
  tz = "GMT"  
)
```

Arguments

date	date of interest
Y	vector containing validated sleep counts
idx_start	start index of sleep segment
idx_end	end index of sleep segment
NoPA_cut	percent of 0 counts to define NoPA segments
sleep_mins	threshold number of minutes to define sleep segment
SI_i	estimated sleep intervals based on sleep diary data
tz	timezone, default is GMT

Value

list of validated sleep segments

Segmentor-class	<i>This code was written by Alice Cleynen, Guillem Rigaiill, and Michel Koskas as part of the Segmentor3IsBack package, which is no longer in CRAN. It has been imported into the ActiSleep package to ensure this package's longevity.</i>
-----------------	---

Description

This code was written by Alice Cleynen, Guillem Rigaiill, and Michel Koskas as part of the Segmentor3IsBack package, which is no longer in CRAN. It has been imported into the ActiSleep package to ensure this package's longevity.

SleepDiary1Day	<i>Sleep Diary 1-Day Data</i>
----------------	-------------------------------

Description

A small dataset containing sleep diary data for a single day and single subject

- bed. time at which the subject reported going to sleep on day 1
- wake. time at which the subject reported waking up on day 1

Usage

```
data("SleepDiary1Day")
```

Format

a data frame with 1 row and 2 variables

SleepDiary1Week	<i>Sleep Diary 1-Week Data</i>
-----------------	--------------------------------

Description

A small dataset containing sleep diary data for a single week and single subject

- FOLIOCC. unique subject id
- etapa.
- stage.
- start_day. first day of measurement
- time_bed1. time at which the subject reported going to sleep on day 1
- time_wake1. time at which the subject reported waking up on day 1
- time_bed2. time at which the subject reported going to sleep on day 2
- time_wake2. time at which the subject reported waking up on day 2
- time_bed3. time at which the subject reported going to sleep on day 3
- time_wake3. time at which the subject reported waking up on day 3
- time_bed4. time at which the subject reported going to sleep on day 4
- time_wake4. time at which the subject reported waking up on day 4
- time_bed5. time at which the subject reported going to sleep on day 5
- time_wake5. time at which the subject reported waking up on day 5
- time_bed6. time at which the subject reported going to sleep on day 6
- time_wake6. time at which the subject reported waking up on day 6
- time_bed7. time at which the subject reported going to sleep on day 7
- time_wake7. time at which the subject reported waking up on day 7

Usage

```
data("SleepDiary1Week")
```

Format

a data frame with 1 row and 18 variables

SleepEstEachDay	<i>Daily sleep estimate</i>
-----------------	-----------------------------

Description

Obtain sleep data from accelerometer data

Usage

```
SleepEstEachDay(
  datain,
  f = 1,
  id = NA,
  Y_name = "max_count",
  T = 0.4,
  nonwear_detect = FALSE,
  wear_mins = 120,
  S = 3,
  NoPA_cut = 0.7,
  sleep_mins = 20,
  wake_mins = 180,
  nap_mins = 20,
  UseDiary = FALSE,
  diary_data = c(),
  CommonBedTime = "22:00:00",
  CommonWakeTime = "8:00:00",
  tz = "GMT"
)
```

Arguments

datain	input accelerometry dataset, must be tibble, data frame, etc.
f	cost function indicator
id	subject id
Y_name	column name of the activity count data to be used in analysis, for example max count of x, y, z axes or vector magnitude
T	threshold percentile of activity level
nonwear_detect	flag indicating use of nonwear detection algorithm, default is FALSE

wear_mins	threshold number of minutes to define wear segment
S	number of segments per hour
NoPA_cut	percent of 0 counts to define NoPA segments
sleep_mins	threshold number of minutes to define sleep segment
wake_mins	threshold number of minutes to define wake segment
nap_mins	threshold number of minutes to define nap segment
UseDiary	flag indicating if diary data to be used, default is FALSE
diary_data	diary data, must be a data frame
CommonBedTime	in-bed time if no diary data, default is "22:00:00"
CommonWakeTime	out-bed time if no diary data, default is "8:00:00"
tz	timezone, default is GMT

Value

list containing a data frame of summary sleep data

Examples

```

data("AccelData")

AccelData <-
ChangeTimeVar(AccelData, col_idx = 1, format = "%m/%d/%Y %H:%M")

SleepEstEachDay(AccelData, Y_name = "VM")

data("AccelData")

AccelData <-
ChangeTimeVar(AccelData, col_idx = 1, format = "%m/%d/%Y %H:%M")

SleepEstEachDay(AccelData, Y_name = "VM", nonwear_detect = TRUE)

data("AccelData")
data("SleepDiary1Day")

SleepDiary1Day <-
ChangeTimeVar(
SleepDiary1Day,
col_idx = c(1,2),
format = "%m/%d/%Y %H:%M")

AccelData <-
ChangeTimeVar(AccelData, col_idx = 1, format = "%m/%d/%Y %H:%M")

SleepEstEachDay(
AccelData,
f = 2,
Y_name = "VM",

```

```
T = 0,  
nonwear_detect = TRUE,  
S = 2,  
NoPA_cut = 0.45,  
sleep_mins = 5,  
UseDiary = TRUE,  
diary_data = SleepDiary1Day  
)
```

Index

* datasets

AccelData, [2](#)

SleepDiary1Day, [8](#)

SleepDiary1Week, [8](#)

AccelData, [2](#)

aggregate_dat, [3](#)

cal_mean_idx, [3](#)

ChangeTimeVar, [4](#)

GetDiary_subj, [4](#)

GetEstSleepInterval_subj, [5](#)

read_agd, [6](#)

SearchSleepSeg, [6](#)

Segmentor-class, [7](#)

SleepDiary1Day, [8](#)

SleepDiary1Week, [8](#)

SleepEstEachDay, [9](#)