

Package ‘BERTopic’

May 6, 2026

Type Package

Title Topic Modeling with 'BERTopic'

Version 0.1.0

Description Interface to the Python package 'BERTopic' <<https://maartengr.github.io/BERTopic/index.html>> for transformer-based topic modeling. Provides R wrappers to fit BERTopic models, transform new documents, update and reduce topics, extract topic- and document-level information, and generate interactive visualizations. 'Python' backends and dependencies are managed via the 'reticulate' package.

License MIT + file LICENSE

Encoding UTF-8

Depends R (>= 3.5)

Imports reticulate, rlang, tibble, utils

Suggests Matrix, htmltools, testthat (>= 3.1.0)

LazyData true

RoxygenNote 7.3.3

Config/testthat/edition 3

URL <https://github.com/Feng-Ji-Lab/BERTopic>

BugReports <https://github.com/Feng-Ji-Lab/BERTopic/issues>

Language en-US

NeedsCompilation no

Author Biying Zhou [aut, cre]

Maintainer Biying Zhou <biying.zhou@psu.edu>

Repository CRAN

Date/Publication 2026-01-26 16:50:14 UTC

Contents

as.data.frame.bertopic_r	3
bertopic_as_document_topic_matrix	3
bertopic_available	4
bertopic_find_topics	4
bertopic_fit	5
bertopic_get_document_info	5
bertopic_get_representative_docs	6
bertopic_has_embedding_model	6
bertopic_load	7
bertopic_reduce_topics	7
bertopic_save	8
bertopic_self_check	9
bertopic_session_info	9
bertopic_set_embedding_model	10
bertopic_set_topic_labels	11
bertopic_topics	11
bertopic_topics_over_time	12
bertopic_topic_terms	12
bertopic_transform	13
bertopic_update_topics	13
bertopic_visualize_barchart	14
bertopic_visualize_distribution	14
bertopic_visualize_documents	15
bertopic_visualize_heatmap	16
bertopic_visualize_hierarchical_documents	16
bertopic_visualize_hierarchy	18
bertopic_visualize_term_rank	18
bertopic_visualize_topics	19
bertopic_visualize_topics_over_time	19
bertopic_visualize_topics_per_class	20
coef.bertopic_r	21
fortify.bertopic_r	21
install_py_deps	22
install_py_deps_conda	22
install_py_deps_venv	23
predict.bertopic_r	24
print.bertopic_r	25
set_bertopic_seed	25
sms_spam	26
summary.bertopic_r	26
use_bertopic	27
use_bertopic_condaenv	27
use_bertopic_virtualenv	28

```
as.data.frame.bertopic_r
  Coerce to data.frame
```

Description

Coerce to data.frame

Usage

```
## S3 method for class 'bertopic_r'
as.data.frame(x, ...)
```

Arguments

x	A "bertopic_r" model.
...	Unused.

Value

A data.frame equal to [bertopic_topics\(\)](#).

```
bertopic_as_document_topic_matrix
  Coerce to a document-topic probability matrix
```

Description

Extract the document-topic probabilities as a matrix. If probabilities were not computed during fitting, returns NULL (with a warning).

Usage

```
bertopic_as_document_topic_matrix(model, sparse = TRUE, prefix = TRUE)
```

Arguments

model	A "bertopic_r" model object.
sparse	Logical; if TRUE and Matrix is available, returns a sparse matrix.
prefix	Logical; if TRUE, prefix columns as topic ids.

Value

A matrix or sparse Matrix of size n_docs x n_topics, or NULL.

bertopic_available *Is Python + BERTopic available?*

Description

Checks whether the active Python (as initialized by **reticulate**) can import the key modules needed for BERTopic.

Usage

```
bertopic_available()
```

Value

Logical scalar.

Examples

```
## Not run:  
bertopic_available()  
  
## End(Not run)
```

bertopic_find_topics *Find nearest topics for a query string*

Description

Use `BERTopic.find_topics()` to retrieve the closest topics for a query string. Augments topic IDs/scores with topic labels when available.

Usage

```
bertopic_find_topics(model, query_text, top_n = 5L)
```

Arguments

model	A "bertopic_r" model.
query_text	A length-1 character query.
top_n	Number of nearest topics to return.

Value

A tibble with columns `topic`, `score`, and `label`.

bertopic_fit	<i>Fit BERTopic from R</i>
--------------	----------------------------

Description

A high-level wrapper around Python 'BERTopic'. Python dependencies are checked at runtime.

Usage

```
bertopic_fit(text, embeddings = NULL, ...)
```

Arguments

text	Character vector of documents.
embeddings	Optional numeric matrix (n_docs x dim). If supplied, passed through to Python.
...	Additional arguments forwarded to bertopic.BERTopic(...).

Value

An S3 object of class "bertopic_r" containing:

- .py: the underlying Python model (reticulate object)
- topics: integer vector of topic assignments
- probs: numeric matrix/data frame of topic probabilities (if available)

Examples

```
## Not run:
if (reticulate::py_module_available("bertopic")) {
  m <- bertopic_fit(c("a doc", "another doc"))
  print(class(m))
}

## End(Not run)
```

bertopic_get_document_info	<i>Document-level information</i>
----------------------------	-----------------------------------

Description

Retrieve document-level information for the provided documents.

Usage

```
bertopic_get_document_info(model, docs)
```

Arguments

model	A "bertopic_r" model.
docs	Character vector of documents to query (required).

Value

A tibble with document-level information.

bertopic_get_representative_docs
Representative documents for a topic

Description

Retrieve representative documents for a given topic using `BERTopic.get_representative_docs()`. Falls back across signature variants.

Usage

```
bertopic_get_representative_docs(model, topic_id, top_n = 5L)
```

Arguments

model	A "bertopic_r" model.
topic_id	Integer topic id.
top_n	Number of representative documents to return.

Value

A tibble with columns rank and document. If scores are available in the current BERTopic version, a score column is included.

bertopic_has_embedding_model
Does the model have a usable embedding model?

Description

Does the model have a usable embedding model?

Usage

```
bertopic_has_embedding_model(model)
```

Arguments

model A "bertopic_r" model.

Value

Logical; TRUE if embedding_model is present and not None.

bertopic_load *Load a BERTopic model*

Description

Load a BERTopic model from disk that was saved with [bertopic_save\(\)](#).

Usage

```
bertopic_load(path)
```

Arguments

path Path used in [bertopic_save\(\)](#) (file or directory).

Value

A "bertopic_r" object with the loaded Python model.

bertopic_reduce_topics *Reduce/merge topics*

Description

Wrapper over Python reduce_topics, compatible with multiple signatures.

Usage

```
bertopic_reduce_topics(  
  model,  
  nr_topics = "auto",  
  representation_model = NULL,  
  docs = NULL  
)
```

Arguments

model	A "bertopic_r" model.
nr_topics	Target number (integer) or "auto".
representation_model	Optional Python representation model.
docs	Optional character vector of training docs (used if required by backend).

Value

The input model (invisibly).

bertopic_save	<i>Save a BERTopic model</i>
---------------	------------------------------

Description

Save a fitted BERTopic model to disk. Depending on the serialization method, this may produce either a single file (e.g., *.pkl / *.pt / *.safetensors) or a directory bundle. The function does not pre-create the target path; it only ensures the parent directory exists and lets BERTopic decide the layout.

Usage

```
bertopic_save(
  model,
  path,
  serialization = c("pickle", "safetensors", "pt"),
  save_embedding_model = FALSE,
  overwrite = FALSE
)
```

Arguments

model	A "bertopic_r" model.
path	Destination path (file or directory, as required by BERTopic).
serialization	One of "pickle", "safetensors", or "pt". Default "pickle".
save_embedding_model	Logical; whether to include the embedding model. Default FALSE.
overwrite	Logical; if TRUE and the target exists, it will be replaced.

Value

Invisibly returns the normalized path.

bertopic_self_check *Quick self-check for the BERTopic R interface*

Description

Runs a quick end-to-end smoke test:

- Report Python path/version.
- Verify that bertopic is importable and report its version.
- Minimal round trip: fit -> transform -> save -> load.

Usage

```
bertopic_self_check()
```

Value

A named list with fields:

python_ok Logical.

bertopic_ok Logical.

roundtrip_ok Logical.

details Character vector of diagnostic messages.

Examples

```
## Not run:  
bertopic_self_check()  
  
## End(Not run)
```

bertopic_session_info *Summarize Python/BERTopic session info*

Description

Summarize Python/BERTopic session info

Usage

```
bertopic_session_info()
```

Value

A named list containing paths, versions, and module availability:

python Path of the active Python.

libpython Path to libpython, if any.

version Python version string.

numpy Whether NumPy is available.

numpy_version NumPy version string (if available).

modules A data.frame with availability for key modules.

Examples

```
## Not run:  
bertopic_session_info()  
  
## End(Not run)
```

bertopic_set_embedding_model

Replace or set the embedding model

Description

Set a new embedding model on a fitted BERTopic instance. This enables transform() after loading when the embedding model was not saved.

Usage

```
bertopic_set_embedding_model(model, embedding_model)
```

Arguments

model A "bertopic_r" model.

embedding_model

Either a character identifier (e.g., "all-MiniLM-L6-v2") or a Python embedding model object (e.g., a SentenceTransformer instance).

Value

The input model (invisibly).

bertopic_set_topic_labels
Relabel topics

Description

Set custom labels for topics. Accepts a named character vector or a data.frame with columns topic and label.

Usage

```
bertopic_set_topic_labels(model, labels)
```

Arguments

model	A "bertopic_r" model.
labels	A named character vector (names are topic ids) or a data.frame.

Value

The input model (invisibly).

bertopic_topics *Get topic info as a tibble*

Description

Get topic info as a tibble

Usage

```
bertopic_topics(model)
```

Arguments

model	A "bertopic_r" object returned by bertopic_fit() .
-------	--

Value

A tibble with topic-level information from Python `get_topic_info()`.

bertopic_topics_over_time
Compute topics over time

Description

Wrapper for Python `BERTopic.topics_over_time()`. Returns a tibble and attaches the original Python dataframe in the `"_py"` attribute for use in visualization.

Usage

```
bertopic_topics_over_time(
  model,
  docs,
  timestamps,
  nr_bins = NULL,
  datetime_format = NULL
)
```

Arguments

<code>model</code>	A "bertopic_r" model.
<code>docs</code>	Character vector of documents.
<code>timestamps</code>	A vector of timestamps (Date, POSIXt, or character).
<code>nr_bins</code>	Optional number of temporal bins.
<code>datetime_format</code>	Optional strftime-style format if timestamps are strings.

Value

A tibble with topics-over-time data; attribute `"_py"` stores the original Python dataframe.

bertopic_topic_terms *Get top terms for a topic*

Description

Get top terms for a topic

Usage

```
bertopic_topic_terms(model, topic_id, top_n = 10L)
```

Arguments

model	A "bertopic_r" model
topic_id	Integer topic id
top_n	Number of top terms to return

Value

A tibble with columns term and weight

bertopic_transform	<i>Transform new documents with a fitted BERTopic model</i>
--------------------	---

Description

Transform new documents with a fitted BERTopic model

Usage

```
bertopic_transform(model, new_text, embeddings = NULL)
```

Arguments

model	A "bertopic_r" model from bertopic_fit() .
new_text	Character vector of new documents.
embeddings	Optional numeric matrix for new documents.

Value

A list with topics and probs for the new documents.

bertopic_update_topics	<i>Update topic representations</i>
------------------------	-------------------------------------

Description

Call Python `BERTopic.update_topics()` to recompute topic representations.

Usage

```
bertopic_update_topics(model, text)
```

Arguments

model	A "bertopic_r" model.
text	Character vector of training documents used in fit.

Value

The input model (invisibly), updated in place on the Python side.

bertopic_visualize_barchart
Visualize a topic barchart

Description

Visualize a topic barchart

Usage

```
bertopic_visualize_barchart(model, topic_id = NULL, file = NULL)
```

Arguments

model	A "bertopic_r" model.
topic_id	Integer topic id. If NULL, a set of top topics is shown.
file	Optional HTML output path.

Value

A barchart.

bertopic_visualize_distribution
Visualize topic probability distribution

Description

Wrapper around Python `BERTopic.visualize_distribution()`. This function takes a single document's topic probability vector (e.g., one row from `probs`) and returns an interactive Plotly figure as HTML or writes it to disk.

Usage

```
bertopic_visualize_distribution(
    model,
    probs,
    min_probability = NULL,
    custom_labels = FALSE,
    title = NULL,
    width = NULL,
    height = NULL,
    file = NULL
)
```

Arguments

<code>model</code>	A "bertopic_r" model.
<code>probs</code>	Numeric vector of topic probabilities for a single document.
<code>min_probability</code>	Optional numeric scalar. If provided, only probabilities greater than this value are visualized (forwarded to <code>min_probability</code> in Python).
<code>custom_labels</code>	Logical or character scalar. If logical, whether to use custom topic labels as set via <code>set_topic_labels()</code> . If character, selects labels from other aspects (e.g., "Aspect1").
<code>title</code>	Optional character plot title.
<code>width, height</code>	Optional integer figure width/height in pixels.
<code>file</code>	Optional HTML output path. If NULL, an <code>htmltools::HTML</code> object is returned.

Value

If `file` is NULL, an `htmltools::HTML` object. Otherwise, the normalized file path is returned invisibly.

`bertopic_visualize_documents`
Visualize embedded documents

Description

Visualize embedded documents

Usage

```
bertopic_visualize_documents(model, docs = NULL, file = NULL)
```

Arguments

model	A "bertopic_r" model.
docs	Optional character vector of documents to visualize.
file	Optional HTML output path.

Value

An html file.

bertopic_visualize_heatmap
Visualize topic similarity heatmap

Description

Visualize topic similarity heatmap

Usage

```
bertopic_visualize_heatmap(model, file = NULL)
```

Arguments

model	A "bertopic_r" model.
file	Optional HTML output path.

Value

An html file output.

bertopic_visualize_hierarchical_documents
Visualize hierarchical documents and topics

Description

Wrapper around Python `BERTopic.visualize_hierarchical_documents()`. This function visualizes documents and their topics in 2D at different levels of a hierarchical topic structure.

Usage

```

bertopic_visualize_hierarchical_documents(
  model,
  docs,
  hierarchical_topics,
  topics = NULL,
  embeddings = NULL,
  reduced_embeddings = NULL,
  sample = NULL,
  hide_annotations = FALSE,
  hide_document_hover = TRUE,
  nr_levels = 10L,
  level_scale = c("linear", "log"),
  custom_labels = FALSE,
  title = NULL,
  width = NULL,
  height = NULL,
  file = NULL
)

```

Arguments

model	A "bertopic_r" model.
docs	Character vector of documents used in <code>fit / fit_transform</code> .
hierarchical_topics	A data frame or Python object as returned by <code>BERTopic.hierarchical_topics(docs, ...)</code> .
topics	Optional integer vector of topic IDs to visualize.
embeddings	Optional numeric matrix of document embeddings.
reduced_embeddings	Optional numeric matrix of 2D reduced embeddings.
sample	Optional numeric (0–1) or integer controlling subsampling of documents per topic (forwarded to Python).
hide_annotations	Logical; if TRUE, hide cluster labels in the plot.
hide_document_hover	Logical; if TRUE, hide document text on hover to speed up rendering.
nr_levels	Integer; number of hierarchy levels to display.
level_scale	Character, either "linear" or "log", controlling how hierarchy distances are scaled across levels.
custom_labels	Logical or character scalar controlling label behavior (forwarded to Python).
title	Optional character plot title.
width, height	Optional integer figure width/height in pixels.
file	Optional HTML output path. If NULL, an <code>htmltools::HTML</code> object is returned.

Value

If file is NULL, an `htmltools::HTML` object. Otherwise, the normalized file path is returned invisibly.

`bertopic_visualize_hierarchy`*Visualize hierarchical clustering of topics*

Description

Visualize hierarchical clustering of topics

Usage

```
bertopic_visualize_hierarchy(model, file = NULL)
```

Arguments

<code>model</code>	A "bertopic_r" model.
<code>file</code>	Optional HTML output path.

Value

An html file output.

`bertopic_visualize_term_rank`*Visualize term rank evolution*

Description

Visualize term rank evolution

Usage

```
bertopic_visualize_term_rank(model, file = NULL)
```

Arguments

<code>model</code>	A "bertopic_r" model.
<code>file</code>	Optional HTML output path.

Value

No output. An HTML file will be saved.

bertopic_visualize_topics
Visualize topic map

Description

Visualize topic map

Usage

```
bertopic_visualize_topics(model, file = NULL)
```

Arguments

model	A "bertopic_r" model.
file	Optional HTML output path. If NULL, returns htmltools::HTML.

Value

An HTML file.

bertopic_visualize_topics_over_time
Visualize topics over time

Description

Visualize topics over time

Usage

```
bertopic_visualize_topics_over_time(  
  model,  
  topics_over_time,  
  top_n = 10L,  
  file = NULL  
)
```

Arguments

model	A "bertopic_r" model.
topics_over_time	A tibble returned by bertopic_topics_over_time() , or a Python dataframe compatible with visualize_topics_over_time() .
top_n	Number of topics to display.
file	Optional HTML output path.

Value

An HTML object.

bertopic_visualize_topics_per_class
Visualize topics per class

Description

Wrapper around Python `BERTopic.visualize_topics_per_class()`. This visualizes how topics are distributed across a set of classes, using the output of Python `topics_per_class(docs, classes)`.

Usage

```
bertopic_visualize_topics_per_class(
    model,
    topics_per_class,
    top_n_topics = 10L,
    topics = NULL,
    normalize_frequency = FALSE,
    custom_labels = FALSE,
    title = NULL,
    width = NULL,
    height = NULL,
    file = NULL
)
```

Arguments

<code>model</code>	A "bertopic_r" model.
<code>topics_per_class</code>	A data frame or Python object as returned by <code>BERTopic.topics_per_class(docs, classes)</code> .
<code>top_n_topics</code>	Integer; number of most frequent topics to display.
<code>topics</code>	Optional integer vector of topic IDs to include.
<code>normalize_frequency</code>	Logical; whether to normalize each topic's frequency within classes.
<code>custom_labels</code>	Logical or character scalar controlling label behavior (forwarded to Python).
<code>title</code>	Optional character plot title.
<code>width, height</code>	Optional integer figure width/height in pixels.
<code>file</code>	Optional HTML output path. If NULL, an <code>htmltools::HTML</code> object is returned.

Value

If file is NULL, an `htmltools::HTML` object. Otherwise, the normalized file path is returned invisibly.

coef.bertopic_r	<i>Coefficients (top terms) for BERTopic</i>
-----------------	--

Description

Coefficients (top terms) for BERTopic

Usage

```
## S3 method for class 'bertopic_r'
coef(object, top_n = 10L, ...)
```

Arguments

object	A "bertopic_r" model.
top_n	Number of terms per topic.
...	Unused.

Value

A data.frame with columns topic, term, weight.

fortify.bertopic_r	<i>Fortify method for ggplot2</i>
--------------------	-----------------------------------

Description

Fortify method for ggplot2

Usage

```
fortify.bertopic_r(model, data, ...)
```

Arguments

model	A "bertopic_r" model.
data	Ignored.
...	Unused.

Value

A data.frame of document-topic assignments.

install_py_deps	<i>Install Python dependencies for BERTopic (auto route)</i>
-----------------	--

Description

Tries Conda first (recommended). If Conda is unavailable, falls back to virtualenv. On success, prints which route was used.

Usage

```
install_py_deps(
    envname = "r-bertopic",
    python_version = "3.10",
    python = NULL,
    reinstall = FALSE,
    validate = TRUE,
    verbose = TRUE
)
```

Arguments

envname	Character. Environment name (both routes). Default "r-bertopic".
python_version	Character. Python version for Conda route, e.g. "3.10".
python	Optional path to python for virtualenv route.
reinstall	Logical. Recreate the environment if it exists (route-specific).
validate	Logical. Attempt to validate imports if reticulate is not already initialized to another Python.
verbose	Logical. Print progress.

Value

Invisibly, the path to the selected Python interpreter.

install_py_deps_conda	<i>Install Python dependencies for BERTopic (Conda route)</i>
-----------------------	---

Description

Creates (or reuses) a Conda environment with a pinned Python toolchain, installs the scientific stack + PyTorch (CPU) + sentence-transformers, then installs bertopic==0.16.0 via pip. Optionally validates imports.

Usage

```
install_py_deps_conda(
    envname = "r-bertopic",
    python_version = "3.10",
    reinstall = FALSE,
    validate = TRUE,
    verbose = TRUE
)
```

Arguments

envname	Character. Conda environment name. Default "r-bertopic".
python_version	Character. Python version to use, e.g. "3.10".
reinstall	Logical. If TRUE, delete any existing env and recreate.
validate	Logical. If TRUE, bind and validate imports (will skip if reticulate is already initialized to another Python).
verbose	Logical. Print progress messages.

Value

Invisibly returns the path to the Python executable inside the env.

Examples

```
## Not run:
install_py_deps_conda(envname = "r-bertopic", python_version = "3.10")

## End(Not run)
```

install_py_deps_venv *Install Python dependencies for BERTopic (virtualenv route)*

Description

Creates (or reuses) a virtualenv and installs bertopic==0.16.0 plus required dependencies via pip. Optionally validates imports.

Usage

```
install_py_deps_venv(
    envname = "r-bertopic",
    python = NULL,
    reinstall = FALSE,
    validate = TRUE,
    verbose = TRUE
)
```

Arguments

envname	Character. Virtualenv name. Default "r-bertopic".
python	Character. Path to a Python executable to create the venv with. If NULL, tries to find python / python3 on PATH.
reinstall	Logical. If TRUE, delete existing venv and recreate.
validate	Logical. If TRUE, bind and validate imports (will skip if reticulate is already initialized to another Python).
verbose	Logical. Print progress messages.

Value

Invisibly returns the path to the Python executable inside the venv.

Examples

```
## Not run:
install_py_deps_venv(envname = "r-bertopic")

## End(Not run)
```

predict.bertopic_r *Predict method for BERTopic models*

Description

Predict method for BERTopic models

Usage

```
## S3 method for class 'bertopic_r'
predict(
  object,
  newdata,
  type = c("both", "class", "prob"),
  embeddings = NULL,
  ...
)
```

Arguments

object	A "bertopic_r" model.
newdata	Character vector of new documents.
type	One of "class", "prob", or "both".
embeddings	Optional numeric matrix of embeddings.
...	Reserved for future arguments.

Value

Depending on type, an integer vector, a matrix/data frame, or a list.

print.bertopic_r *Print method for bertopic_r*

Description

Print method for bertopic_r

Usage

```
## S3 method for class 'bertopic_r'  
print(x, ...)
```

Arguments

x A "bertopic_r" object.
... Unused.

Value

No return value. Output will be printed.

set_bertopic_seed *Set random seed for R and Python backends*

Description

Set random seed for R and Python backends

Usage

```
set_bertopic_seed(seed)
```

Arguments

seed Integer seed

Value

No return value. The seed will be changed.

`sms_spam`*SMS Spam Collection (UCI) - subset for examples*

Description

A cleaned subset of the UCI SMS Spam Collection, suitable for quick examples and tests in this package. Each row is an SMS message labeled as "ham" or "spam".

Usage

```
sms_spam
```

Format

A data frame with two columns:

label Character, either "ham" or "spam".

text Character, the SMS message content (UTF-8).

Note

This dataset is included for educational/demo purposes. If you use it in publications, please cite the original authors and the UCI repository page.

Source

UCI Machine Learning Repository: SMS Spam Collection. Dataset page: <https://archive.ics.uci.edu/dataset/228/sms+spam+collection> Original citation: Almeida, T.A., Hidalgo, J.M.G., & Yamakami, A. (2011). Contributions to the Study of SMS Spam Filtering: New Collection and Results.

Examples

```
data(sms_spam)
head(sms_spam)
```

`summary.bertopic_r`*Summary for BERTopic models*

Description

Summary for BERTopic models

Usage

```
## S3 method for class 'bertopic_r'
summary(object, ...)
```

Arguments

object A "bertopic_r" model.
 ... Unused.

Value

Invisibly returns a named list of summary fields.

use_bertopic *Bind current R session to the BERTopic environment (auto route)*

Description

If a Conda env with the given name exists, prefer Conda; otherwise try a virtualenv with the same name. Stops if neither exists.

Usage

```
use_bertopic(envname = "r-bertopic")
```

Arguments

envname Character. Environment name. Default "r-bertopic".

Value

Invisibly, the Python executable path.

use_bertopic_condaenv *Bind current R session to a BERTopic Conda environment*

Description

Sets RETICULATE_PYTHON to the environment's Python and initializes **reticulate**. If **reticulate** is already initialized to a different Python, this stops with an informative error.

Usage

```
use_bertopic_condaenv(envname = "r-bertopic", required = TRUE)
```

Arguments

envname Character. Conda env name (default "r-bertopic").
 required Logical. Kept for API symmetry; unused.

Value

Invisibly returns the Python executable path in the env.

Examples

```
## Not run:  
use_bertopic_condaenv("r-bertopic")  
  
## End(Not run)
```

```
use_bertopic_virtualenv
```

Bind current R session to a BERTopic virtualenv

Description

Sets RETICULATE_PYTHON to the Python inside the given virtualenv and initializes **reticulate**. If **reticulate** is already initialized to a different Python, this stops with an informative error.

Usage

```
use_bertopic_virtualenv(envname = "r-bertopic", required = TRUE)
```

Arguments

envname	Character. Virtualenv name (default "r-bertopic").
required	Logical. Kept for API symmetry; unused.

Value

Invisibly returns the Python executable path in the venv.

Examples

```
## Not run:  
use_bertopic_virtualenv("r-bertopic")  
  
## End(Not run)
```

Index

* datasets

sms_spam, 26

as.data.frame.bertopic_r, 3

bertopic_as_document_topic_matrix, 3

bertopic_available, 4

bertopic_find_topics, 4

bertopic_fit, 5

bertopic_fit(), 11, 13

bertopic_get_document_info, 5

bertopic_get_representative_docs, 6

bertopic_has_embedding_model, 6

bertopic_load, 7

bertopic_reduce_topics, 7

bertopic_save, 8

bertopic_save(), 7

bertopic_self_check, 9

bertopic_session_info, 9

bertopic_set_embedding_model, 10

bertopic_set_topic_labels, 11

bertopic_topic_terms, 12

bertopic_topics, 11

bertopic_topics(), 3

bertopic_topics_over_time, 12

bertopic_topics_over_time(), 19

bertopic_transform, 13

bertopic_update_topics, 13

bertopic_visualize_barchart, 14

bertopic_visualize_distribution, 14

bertopic_visualize_documents, 15

bertopic_visualize_heatmap, 16

bertopic_visualize_hierarchical_documents,
16

bertopic_visualize_hierarchy, 18

bertopic_visualize_term_rank, 18

bertopic_visualize_topics, 19

bertopic_visualize_topics_over_time,
19

bertopic_visualize_topics_per_class,
20

coef.bertopic_r, 21

fortify.bertopic_r, 21

install_py_deps, 22

install_py_deps_conda, 22

install_py_deps_venv, 23

predict.bertopic_r, 24

print.bertopic_r, 25

set_bertopic_seed, 25

sms_spam, 26

summary.bertopic_r, 26

use_bertopic, 27

use_bertopic_condaenv, 27

use_bertopic_virtualenv, 28