

Package ‘CKAT’

May 7, 2026

Type Package

Title Composite Kernel Association Test for Pharmacogenetics Studies

Version 0.1.0

Author Hong Zhang and Judong Shen

Maintainer Hong Zhang <hzhang@wpi.edu>

Description Composite Kernel Association Test (CKAT) is a flexible and robust kernel machine based approach to jointly test the genetic main effect and gene-treatment interaction effect for a set of single-nucleotide polymorphisms (SNPs) in pharmacogenetics (PGx) assessments embedded within randomized clinical trials.

License GPL-2

Imports stats, CompQuadForm

Encoding UTF-8

LazyData true

RoxygenNote 6.1.0

NeedsCompilation no

Repository CRAN

Date/Publication 2019-10-09 09:20:02 UTC

Contents

CKAT	2
Index	3

CKAT *Composite kernel association test for SNP-set analysis in pharmacogenetics (PGx) studies.*

Description

Composite kernel association test for SNP-set analysis in pharmacogenetics (PGx) studies.

Usage

```
CKAT(G, Tr, X, y, trait = "continuous", ker = "linear", grids = c(0,
  0.5, 1), n_a = 1000, method = "liu", subdiv = 10^6)
```

Arguments

G - genotype matrix.

Tr - treatment vector, 0 indicates placebo, 1 indicates treatment.

X - non-genetic covariates data matrix.

y - response vector. Currently continuous and binary responses are supported. Survival response will be added soon.

trait - response indicator. trait = "continuous" or "binary".

ker - kernel. ker = "linear", "IBS", "Inter" (interaction kernel) and "RBF" (radial basis function kernel).

grids - grids of the candidate weights.

n_a - the number of intervals for manual integration (when integrate function fails). Default n_a = 1000.

method - method for getting density of A (see details in the reference). Default method is Liu's method.

subdiv - parameter of Davies' method. Default value is 1E6.

Value

pvals - p-values of each individual association test.

finalp - final p-value of the CKAT test.

Examples

```
nsamples = 500; nsnps = 10
X = rnorm(nsamples,0,1)
Tr = sample(0:1,nsamples,replace=TRUE)
G = matrix(rbinom(nsamples*nsnps, 1, 0.05), nrow = nsamples, ncol = nsnps)
GxT = G*Tr
Y0 = 0.5*X + Tr + rnorm(nsamples)
CKAT(G, Tr, X, Y0, grids=c(0,0.5,1))
```

Index

CKAT, [2](#)