Package ‘CLA’

May 7, 2026

Version 0.96-3

Date 2024-07-29

Title Critical Line Algorithm in Pure R

Depends R (>= 3.6.0)

Imports stats, grDevices, graphics, utils

Suggests fGarch, FRAPO, Matrix, sfsmisc

Description Implements 'Markowitz' Critical Line Algorithm ('CLA') for classical mean-variance portfolio optimization, see Markowitz (1952) <doi:10.2307/2975974>. Care has been taken for correctness in light of previous buggy implementations.

License GPL (>= 3) | file LICENSE

Encoding UTF-8

URL https://gitlab.math.ethz.ch/maechler/CLA/

NeedsCompilation no

Author Yanhao Shi [aut],
Martin Maechler [aut, cre] (ORCID:
<https://orcid.org/0000-0002-8685-9910>)

Maintainer Martin Maechler <maechler@stat.math.ethz.ch>

Repository CRAN

Date/Publication 2024-07-29 15:50:09 UTC

Contents

CLA 2
findMu 4
findSig 5
MS 7
muS.10ex 8
muS.sp500 9
muSigmaGarch 10
plot.CLA 11

Index **13**

CLA *Critical Line Algorithm for mean-variance optimal portfolio*

Description

The Critical Line Algorithm was first proposed by Markowitz(1987) to solve the mean-variance optimal portfolio problem.

We solve the problem with "box" constraints, i.e., allow to specify lower and upper bounds (via `lB` and `uB`) for each asset weight.

Here we provide a pure R implementation, quite fine tuned and debugged compared to earlier ones.

Usage

```
CLA(mu, covar, lB, uB,
    check.cov = TRUE, check.f = TRUE,
    tol.lambda = 1e-07,
    give.MS = TRUE, keep.names = TRUE, trace = 0)
```

Arguments

`mu`	numeric vector of length `n` containing the expected return $E[R_i]$ for $1 = 1, 2, \ldots, n$.
`covar`	the $n \times n$ covariance matrix of the returns, must be positive definite.
`lB`, `uB`	vectors of length `n` with lower and upper bounds for the asset weights.
`check.cov`	`logical` indicating if the `covar` matrix should be checked to be positive definite.
`check.f`	`logical` indicating if a warning should be produced when the algorithm cannot produce a new (smaller) lambda even though there are still **f**ree weights to be chosen.
`tol.lambda`	the tolerance when checking for lambda changes or being zero.
`give.MS`	`logical` indicating if `MS()` should be computed (and returned) as well.
`keep.names`	`logical` indicating if the `weights_set` matrix should keep the (asset) `names(mu)`.
`trace`	an integer (or `logical`) indicating if and how much diagnostic or progress output should be produced.

Details

The current implementation of the CLA is based (via Norring's) on Bailey et al.(2013). We have found buglets in that implementation which lead them to introduce their "purge" routines (`purgeNumErr`, `purgeExcess`), which are no longer necessary.

Even though this is a pure R implementation, the algorithm is quite fast also when the number of assets n is large (1000s), though that depends quite a bit on the exact problem.

Value

an object of `class` "CLA" which is a `list` with components

`weights_set`	a $n \times m$ matrix of asset weights, corresponding to the m steps that the CLA has completed or the m "turning points" it has computed.
`free_indices`	a `list` of length `m`, the k-th component with the indices in $1, \ldots, n$ of those assets whose weights were not at the boundary after ...
`gammas`	numeric vector of length m of the values γ_k for CLA step k, $k = 1, \ldots, n$.
`lambdas`	numeric vector of length m of the Lagrange parameters λ_k for CLA step k, $k = 1, \ldots, n$.
`MS_weights`	the $\mu(W)$ and $\sigma(W)$ corresponding to the asset weights `weights_set`, i.e., simply the same as `MS(weights_set = weights_set, mu = mu, covar = covar)`.

Note

The exact results of the algorithm, e.g., the assets with non-zero weights, may slightly depend on the (computer) platform, e.g., for the S&P 500 example, differences between 64-bit or 32-bit, version of BLAS or Lapack libraries etc, do have an influence, see the R script '`tests/SP500-ex.R`' in the package sources.

Author(s)

Alexander Norring did the very first version (unpublished master thesis). Current implementation: Yanhao Shi and Martin Maechler

References

Markowitz, H. (1952) Portfolio selection, *The Journal of Finance* **7**, 77–91; doi:10.2307/2975974.

Markowitz, H. M. (1987, 1st ed.) and Markowitz, H. M. and Todd, P. G. (2000) *Mean-Variance Analysis in Portfolio Choice and Capital Markets*; chapters 7 and 13.

Niedermayer, A. and Niedermayer, D. (2010) Applying Markowitz's Critical Line Algorithm, in J. B. Guerard (ed.), Handbook of Portfolio Construction, Springer; chapter 12, 383–400; doi:10.1007/9780387774398_12.

Bailey, D. H. and López de Prado, M. (2013) An open-source implementation of the critical-line algorithm for portfolio optimization, *Algorithms* **6**(1), 169–196; doi:10.3390/a6010169,

Yanhao Shi (2017) Implementation and applications of critical line algorithm for portfolio optimization; unpublished Master's thesis, ETH Zurich.

See Also

`MS`; for plotting `CLA` results: `plot.CLA`.

Examples

```
data(muS.sp500)
## Full data taking too much time for example
set.seed(47)
iS <- sample.int(length(muS.sp500$mu), 24)

CLsp.24 <- CLA(muS.sp500$mu[iS], muS.sp500$covar[iS, iS], lB=0, uB=1/10)
CLsp.24 # using the print() method for class "CLA"

plot(CLsp.24)

if(require(Matrix)) { ## visualize how weights change "along turning points"
  show(image(Matrix(CLsp.24$weights_set, sparse=TRUE),
             main = "CLA(muS.sp500 <random_sample(size=24)>) $ weights_set",
             xlab = "turning point", ylab = "asset number"))
}

## A 3x3 example (from real data) where CLA()'s original version failed
## and  'check.f = TRUE' produces a warning :
mc3 <- list(
    mu = c(0.0408, 0.102, -0.023),
    cv = matrix(c(0.00648, 0.00792, 0.00473,
                  0.00792, 0.0334,  0.0121,
                  0.00473, 0.0121, 0.0793), 3, 3,
           dimnames = list(NULL,
                           paste0(c("TLT", "VTI","GLD"), ".Adjusted"))))

rc3 <- with(mc3,  CLA(mu=mu, covar=cv, lB=0, uB=1, trace=TRUE))
```

`findMu` *Find mu(W) and W, given sigma(W) and CLA result*

Description

Find $\mu(W)$ and W, given $\sigma(W)$ and `CLA` result.

Usage

```
findMu(Sig0, result, covar, tol.unir = 1e-06, equal.tol = 1e-06)
```

Arguments

`Sig0`	numeric vector of $\sigma(W)$ values.
`result`	a `list` with components `MS_weight` and `weights_set` as resulting from `CLA()`.
`covar`	the same $n \times n$ covariance matrix (of asset returns) as the argument of `CLA()`.
`tol.unir`	numeric tolerance passed to `uniroot`.
`equal.tol`	numeric tolerance to be used in `all.equal(.., tolerance = equal.tol)` in the check to see if the μ of two neighbouring turning points are equal.

Value

a list with components

Mu	numeric vector of same length, say M, as Sig0.
weight	numeric $n \times M$ matrix of weights.

References

Master thesis, p.33

See Also

findSig, CLA, MS.

Examples

```
data(muS.sp500)
## Full data taking too much time for example
if(getRversion() >= "3.6") .Rk <- RNGversion("3.5.0") # for back compatibility & warning
set.seed(2016)
iS <- sample.int(length(muS.sp500$mu), 17)
if(getRversion() >= "3.6") do.call(RNGkind, as.list(.Rk)) # revert
cov17 <- muS.sp500$covar[iS, iS]
CLsp.17 <- CLA(muS.sp500$mu[iS], covar=cov17, lB=0, uB = 1/2)
CLsp.17 # 16 turning points
summary(tpS <- CLsp.17$MS_weights[,"Sig"])
str(s0 <- seq(0.0186, 0.0477, by = 0.0001))
mu.. <- findMu(s0, result=CLsp.17, covar=cov17)
str(mu..)
stopifnot(dim(mu..$weight) == c(17, length(s0)))
plot(s0, mu..$Mu, xlab=quote(sigma), ylab = quote(mu),
     type = "o", cex = 1/4)
points(CLsp.17$MS_weights, col = "tomato", cex = 1.5)
```

---

findSig *Find sigma(W) and W, given mu(W) and CLA result*

Description

Find $\sigma(W)$ and W, given $\mu(W)$ and CLA result.

Usage

```
findSig(Mu0, result, covar, equal.tol)
```

Arguments

`Mu0`	numeric vector of $\mu(W)$ values.
`result`	a `list` with components `MS_weight` and `weights_set` as resulting from `CLA()`.
`covar`	the same $n \times n$ covariance matrix (of asset returns) as the argument of `CLA()`.
`equal.tol`	numeric tolerance to be used in `all.equal(.., tolerance = equal.tol)` in the check to see if the μ of two neighbouring turning points are equal.

Value

a `list` with components

`Sig`	numeric vector of same length, say M, as `Mu0`.
`weight`	numeric $n \times M$ matrix of weights.

References

Master thesis, p.33

See Also

`findMu`, `CLA`, `MS`.

Examples

```
data(muS.sp500)
## Full data taking too much time for example: Subset of n=21:
if(getRversion() >= "3.6") .Rk <- RNGversion("3.5.0") # for back compatibility & warning
set.seed(2018)
iS <- sample.int(length(muS.sp500$mu), 21)
if(getRversion() >= "3.6") do.call(RNGkind, as.list(.Rk)) # revert
cov21 <- muS.sp500$covar[iS, iS]
CLsp.21 <- CLA(muS.sp500$mu[iS], covar=cov21, lB=0, uB = 1/2)
CLsp.21 # 14 turning points
summary(tpM <- CLsp.21$MS_weights[,"Mu"])
str(m0 <- c(min(tpM),seq(0.00205, 0.00525, by = 0.00005), max(tpM)))
sig. <- findSig(m0, result=CLsp.21, covar=cov21)
str(sig.)
stopifnot(dim(sig.$weight) == c(21, length(m0)))
plot(sig.$Sig, m0, xlab=quote(sigma), ylab = quote(mu),
     type = "o", cex = 1/4)
points(CLsp.21$MS_weights, col = "tomato", cex = 1.5)
title("Efficient Frontier from CLA()")
mtext("findSig() to interpolate between turning points", side=3)
```

MS — *Means (Mu) and Standard Deviations (Sigma) of the "Turning Points" from CLA*

Description

Compute the vectors of means (μ_i) and standard deviations ($sigma_i$), for all the turning points of a CLA result.

Usage

```
MS(weights_set, mu, covar)
```

Arguments

weights_set	numeric matrix ($n \times m$) of optimal asset weights $W = (w_1, w_2, \ldots, w_m)$, as resulting from CLA().
mu	expected (log) returns (identical to *argument* of CLA()).
covar	covariance matrix of (log) returns (identical to *argument* of CLA()).

Details

These are trivially computable from the CLA()'s result. To correctly *interpolate* this, "hyperbolic" interpolation is needed, provided by the findSig and findMu functions.

Value

a list with components

Sig	numeric vector of length m of standard deviations, $\sigma(W)$.
Mu	numeric vector of length m of means $\mu(W)$.

Author(s)

Yanhao Shi

See Also

CLA.

Examples

```
## The function is quite simply
MS
## and really an auxiliary function for CLA().

## TODO:  add small (~12 assets) example
```

muS.10ex *10 Assets Example Data from Markowitz & Todd*

Description

The simple example Data of Markowitz and Todd (2000); used for illustrating the CLA; reused in Bailey and López de Prado (2013).

Usage

```
data("muS.10ex")
```

Format

A list with two components,

mu Named num [1:10] 1.175 1.19 0.396 1.12 0.346 ...
names : chr [1:10] "X1" "X2" "X3" "X4" ...

covar num [1:10, 1:10] 0.4076 0.0318 0.0518 0.0566 0.033 ...

Source

From '`http://www.quantresearch.info/CLA_Data.csv.txt`' (URL no longer working, Aug.2020!) by López de Prado.

References

Markowitz, H. M. (1987, 1st ed.) and Markowitz, H. M. and Todd, P. G. (2000) *Mean-Variance Analysis in Portfolio Choice and Capital Markets*, page 335.

Bailey, D. H. and López de Prado, M. (2013) An open-source implementation of the critical-line algorithm for portfolio optimization, *Algorithms* **6**(1), 169–196; doi:10.3390/a6010169, p. 16f.

Examples

```
data(muS.10ex)
str(muS.10ex)

CLA.10ex <- with(muS.10ex, CLA(mu, covar, lB=0, uB=1))
if(require("Matrix"))
  drop0(zapsmall(CLA.10ex$weights_set))
## The results, summarized, as in Bayley and López de Prado (Table 2, p.18) :
with(CLA.10ex, round(cbind(MS_weights[,2:1], lambda=lambdas, t(weights_set)), 3))

CLA.10ex.1c <- with(muS.10ex, CLA(mu, covar, lB=1/100, uB=1))
round(CLA.10ex.1c$weights_set, 3)
```

muS.sp500 *Return Expectation and Covariance for "FRAPO"s SP500 data*

Description

If $R_{j,t}$ are the basically the scale standardized log returns for $j = 1, 2, \ldots, 476$ of 476 stocks from S&P 500, as from SP500, then $mu_j = E[R_{j,*}]$ somehow averaged over time; actually as predicted by muSigma() at the end of the time period, and $\Sigma_{j,k} = Cov(R_j, R_k)$ are estimated covariances.

These are the main "inputs" needed for the CLA algorithm, see CLA.

Usage

```
data("muS.sp500")
```

Format

A list with two components,

mu Named num [1:476] 0.00233 0.0035 0.01209 0.00322 0.00249 ...
names : chr [1:476] "A" "AA" "AAPL" "ABC" ...

covar num [1:476, 1:476] 0.001498 0.000531 0.000536 ...

Source

It is as simple as this:

```
data(SP500, package="FRAPO")
system.time(muS.sp500 <- muSigmaGarch(SP500))   #   26 sec. (lynne, 2017)
```

See Also

muSigmaGarch() which was used to construct it.

Examples

```
data(muS.sp500)
str(muS.sp500)
```

muSigmaGarch *Compute (mu, Sigma) for a Set of Assets via GARCH fit*

Description

Compute (mu, Sigma) for a set of assets via a GARCH fit to each individual asset, using package **fGarch**'s `garchFit()`.

Usage

```
muSigmaGarch(x, formula = ~garch(1, 1), cond.dist = "std", trace = FALSE,
             ...)
```

Arguments

`x`	numeric matrix or data frame ($T \times d$) of log returns of d assets, observed on a common set of T time points.
`formula`	optional formula for `garchFit`.
`cond.dist`	the conditional distribution to be used for the garch process.
`trace`	logical indicating if some progress of `garchFit()` should printed to the console.
`...`	optional arguments to `cor`, i.e., `use` or `method`.

Value

a list with components

`mu`	numeric vector of length n of mean returns ($= E[R_i]$).
`covar`	covariance matrix ($n \times n$) of the returns.

See Also

`muS.sp500` which has been produced via `muSigmaGarch`. `CLA` which needs `(mu, covar)` as crucial input.

Examples

```
if(requireNamespace("FRAPO")) {
  data(NASDAQ, package = "FRAPO")
  ## 12 randomly picked stocks from NASDAQ data
  iS <- if(FALSE) {  ## created (w/ warning, in new R)  by
    RNGversion("3.5.0"); set.seed(17); iS <- sample(ncol(NASDAQ), 12)
  } else c(341L, 2126L, 1028L, 1704L, 895L, 1181L, 454L, 410L, 1707L, 425L, 950L, 5L)
  X. <- NASDAQ[, iS]
  muSig <- muSigmaGarch(X.)
  stopifnot(identical(names(muSig$mu), names(NASDAQ)[iS]),
            identical(dim(muSig$covar), c(12L,12L)),
     all.equal(unname(muSig$mu),
```

```
                c(  7.97, -4.05, -14,     21.5, -5.36, -15.3,
                  -15.9,  11.8,   -1.64, -14,    3.13, 121) / 10000,
                tol = 0.0015))
}
```

---

plot.CLA *Plotting CLA() results including Efficient Frontier*

Description

A partly experimental `plot()` method for `CLA()` objects.

It draws the efficient frontier in the μ_w, σ_w aka (mean, std.dev.) plane.

Currently, this is quite rudimentary.
Future improvements would allow - to add the/some single asset points, - to correctly ('hyperbolically') interpolate between turning points - add text about the number of (unique) critical points - add option `add = FALSE` which when TRUE would use `lines` instead `plot`.

Usage

```
## S3 method for class 'CLA'
plot(x, type = "o", main = "Efficient Frontier",
     xlab = expression(sigma(w)),
     ylab = expression(mu(w)),
     col = adjustcolor("blue", alpha.f = 0.5),
     pch = 16, ...)
```

Arguments

`x`	a named `list` as resulting from `CLA()`.
`type`	the `lines`/`points` types used for the efficient frontier. This will become more sophisticated, i.e., *may change non-compatibly!!*
`main`	main `title`.
`xlab, ylab`	x- and y- axis labels, passed to `plot.default`.
`col, pch`	color and point type, passed to `plot.default`, but with differing defaults in this method.
`...`	potentially further arguments passed to `plot`, i.e., `plot.default`.

Author(s)

Martin Maechler.

See Also

`CLA`, `plot.default`.

Examples

```
## TODO %% Add A. Norring's small 12-asset example see --> ../TODO
## ---- one example is in help(CLA)
```

Index

∗ **arith**
- CLA, 2
- findMu, 4
- findSig, 5
- MS, 7

∗ **datasets**
- muS.10ex, 8
- muS.sp500, 9

∗ **dplot**
- findSig, 5

∗ **hplot**
- plot.CLA, 11

∗ **multivariate**
- muSigmaGarch, 10

∗ **optimize**
- CLA, 2
- findMu, 4

all.equal, *4*, *6*

CLA, 2, *4–7*, *9–11*
class, *3*
cor, *10*

findMu, 4, *6, 7*
findSig, *5*, 5, *7*

garchFit, *10*

lines, *11*
list, *3–7*, *11*
logical, *2*

MS, *2, 3*, *5, 6*, 7
muS.10ex, 8
muS.sp500, 9, *10*
muSigmaGarch, *9*, 10

plot, *11*
plot.CLA, *3*, 11
plot.default, *11*
points, *11*

SP500, *9*

title, *11*

uniroot, *4*