

Package ‘DOEM’

May 7, 2026

Title The Distributed Online Expectation Maximization Algorithms to Solve Parameters of Poisson Mixture Models

Version 0.0.0.1

Description The distributed online expectation maximization algorithms are used to solve parameters of Poisson mixture models. The philosophy of the package is described in Guo, G. (2022) <[doi:10.1080/02664763.2022.2053949](https://doi.org/10.1080/02664763.2022.2053949)>.

License MIT + file LICENSE

Encoding UTF-8

LazyData true

RoxygenNote 7.1.2

Imports stats

Suggests testthat (>= 3.0.0)

Config/testthat/edition 3

NeedsCompilation no

Author Qian Wang [aut, cre],
Guangbao Guo [aut],
Guoqi Qian [aut]

Maintainer Qian Wang <waqian0715@163.com>

Depends R (>= 3.5.0)

Repository CRAN

Date/Publication 2022-03-30 07:20:13 UTC

Contents

DE_OEM	2
DMOEM	3
DM_OEM	5
E_OEM	6
M_OEM	7
PeMSD3	8
PeMSD7	9

PeMSD7_weekend	11
PeMSD7_workday	12

Index	14
--------------	-----------

DE_OEM	<i>The DE-OEM algorithm replaces E-step with stochastic step in distributed manner, which is used to solve the parameter estimation of Poisson mixture model.</i>
--------	---

Description

The DE-OEM algorithm replaces E-step with stochastic step in distributed manner, which is used to solve the parameter estimation of Poisson mixture model.

Usage

```
DE_OEM(y, M, K, seed, alpha0, lambda0, a, b)
```

Arguments

y	is a vector
M	is the number of subsets
K	is the number of Poisson distribution
seed	is the recommended way to specify seeds
alpha0	is the initial value of the mixing weight
lambda0	is the initial value of the mean
a	represents the power of the reciprocal of the step size
b	indicates that the M-step is not implemented for the first b data points

Value

DE_OEMtime, DE_OEMalpha, DE_OEMlambda

Examples

```
library(stats)
set.seed(637351)
K=5
alpha1=c(rep(1/K,K))
lambda1=c(1,2,3,4,5)
n=300
U=sample(c(1:n),n,replace=FALSE)
y= c(rep(0,n))
for(i in 1:n){
  if(U[i]<=0.2*n){
    y[i] = rpois(1,lambda1[1])}
  else if(U[i]>0.2*n & U[i]<=0.4*n){
```

```

y[i] = rpois(1,lambda1[2])}
else if(U[i]>0.4*n & U[i]<=0.6*n){
y[i] = rpois(1,lambda1[3])}
else if(U[i]>0.6*n & U[i]<=0.8*n){
y[i] = rpois(1,lambda1[4])}
else if(U[i]>0.8*n ){
y[i] = rpois(1,lambda1[5])}
}
M=5
seed=637351
set.seed(123)
e=sample(c(1:n),K)
alpha0=e/sum(e)
lambda0=c(1.5,2.5,3.5,4.5,5.5)
a=1
b=5
DE_OEM(y,M,K,seed,alpha0,lambda0,a,b)

```

DMOEM

The DMOEM is an overrelaxation algorithm in distributed manner, which is used to solve the parameter estimation of Poisson mixture model.

Description

The DMOEM is an overrelaxation algorithm in distributed manner, which is used to solve the parameter estimation of Poisson mixture model.

Usage

```

DMOEM(
  y,
  M,
  K,
  seed,
  alpha0,
  lambda0,
  MOEMalpha0,
  MOEMlambda0,
  omega,
  T,
  epsilon
)

```

Arguments

y is a data matrix
M is the number of subsets

K	is the number of Poisson distribution
seed	is the recommended way to specify seeds
alpha0	is the initial value of the mixing weight under the EM algorithm
lambda0	is the initial value of the mean under the EM algorithm
MOEMalpha0	is the initial value of the mixing weight under the monotonically overrelaxed EM algorithm
MOEMlambda0	is the initial value of the mean under the monotonically overrelaxed EM algorithm
omega	is the overrelaxation factor
T	is the number of iterations
epsilon	is the threshold value

Value

DMOEMtime,DMOEMalpha,DMOEMlambda

Examples

```

library(stats)
set.seed(637351)
K=5
alpha1=c(rep(1/K,K))
lambda1=c(1,2,3,4,5)
n=300
U=sample(c(1:n),n,replace=FALSE)
y= c(rep(0,n))
for(i in 1:n){
  if(U[i]<=0.2*n){
    y[i] = rpois(1,lambda1[1])}
  else if(U[i]>0.2*n & U[i]<=0.4*n){
    y[i] = rpois(1,lambda1[2])}
  else if(U[i]>0.4*n & U[i]<=0.6*n){
    y[i] = rpois(1,lambda1[3])}
  else if(U[i]>0.6*n & U[i]<=0.8*n){
    y[i] = rpois(1,lambda1[4])}
  else if(U[i]>0.8*n ){
    y[i] = rpois(1,lambda1[5])}
  }
M=5
seed=637351
set.seed(123)
e=sample(c(1:n),K)
alpha0= MOEMalpha0=e/sum(e)
lambda0= MOEMlambda0=c(1.5,2.5,3.5,4.5,5.5)
omega=0.8
T=10
epsilon=0.005
DMOEM(y,M,K,seed,alpha0,lambda0,MOEMalpha0,MOEMlambda0,omega,T,epsilon)

```

DM_OEM	<i>The DM-OEM algorithm replaces M-step with stochastic step in distributed manner, which is used to solve the parameter estimation of Poisson mixture model.</i>
--------	---

Description

The DM-OEM algorithm replaces M-step with stochastic step in distributed manner, which is used to solve the parameter estimation of Poisson mixture model.

Usage

```
DM_OEM(y, M, K, seed, alpha0, lambda0, a, b)
```

Arguments

y	is a vector
M	is the number of subsets
K	is the number of Poisson distribution
seed	is the recommended way to specify seeds
alpha0	is the initial value of the mixing weight
lambda0	is the initial value of the mean
a	represents the power of the reciprocal of the step size
b	indicates that the M-step is not implemented for the first b data points

Value

DM_OEMtime,DM_OEMalpha,DM_OEMlambda

Examples

```
library(stats)
set.seed(637351)
K=5
alpha1=c(rep(1/K,K))
lambda1=c(1,2,3,4,5)
n=300
U=sample(c(1:n),n,replace=FALSE)
y= c(rep(0,n))
for(i in 1:n){
  if(U[i]<=0.2*n){
    y[i] = rpois(1,lambda1[1])}
  else if(U[i]>0.2*n & U[i]<=0.4*n){
    y[i] = rpois(1,lambda1[2])}
  else if(U[i]>0.4*n & U[i]<=0.6*n){
    y[i] = rpois(1,lambda1[3])}
  else if(U[i]>0.6*n & U[i]<=0.8*n){
```

```

y[i] = rpois(1,lambda1[4])}
else if(U[i]>0.8*n ){
y[i] = rpois(1,lambda1[5])}
}
M=5
seed=637351
set.seed(123)
e=sample(c(1:n),K)
alpha0=e/sum(e)
lambda0=c(1.5,2.5,3.5,4.5,5.5)
a=1
b=5
DM_OEM(y,M,K,seed,alpha0,lambda0,a,b)

```

E_OEM

The E-OEM algorithm replaces E-step with stochastic step, which is used to solve the parameter estimation of Poisson mixture model.

Description

The E-OEM algorithm replaces E-step with stochastic step, which is used to solve the parameter estimation of Poisson mixture model.

Usage

```
E_OEM(y, K, alpha0, lambda0, a, b)
```

Arguments

y	is a data vector
K	is the number of Poisson distribution
alpha0	is the initial value of the mixing weight
lambda0	is the initial value of the mean
a	represents the power of the reciprocal of the step size
b	indicates that the M-step is not implemented for the first b data points

Value

E_OEMtime,E_OEMalpha,E_OEMlambda

Examples

```

library(stats)
set.seed(637351)
K=5
alpha1=c(rep(1/K,K))
lambda1=c(1,2,3,4,5)
n=300

```

```

U=sample(c(1:n),n,replace=FALSE)
y= c(rep(0,n))
for(i in 1:n){
  if(U[i]<=0.2*n){
    y[i] = rpois(1,lambda1[1])}
  else if(U[i]>0.2*n & U[i]<=0.4*n){
    y[i] = rpois(1,lambda1[2])}
  else if(U[i]>0.4*n & U[i]<=0.6*n){
    y[i] = rpois(1,lambda1[3])}
  else if(U[i]>0.6*n & U[i]<=0.8*n){
    y[i] = rpois(1,lambda1[4])}
  else if(U[i]>0.8*n ){
    y[i] = rpois(1,lambda1[5])}
  }
M=5
seed=637351
set.seed(123)
e=sample(c(1:n),K)
alpha0=e/sum(e)
lambda0=c(1.5,2.5,3.5,4.5,5.5)
a=0.75
b=5
E_OEM(y,K,alpha0,lambda0,a,b)

```

M_OEM

The M-OEM algorithm replaces M-step with stochastic step, which is used to solve the parameter estimation of Poisson mixture model.

Description

The M-OEM algorithm replaces M-step with stochastic step, which is used to solve the parameter estimation of Poisson mixture model.

Usage

M_OEM(y, K, alpha0, lambda0, a, b)

Arguments

y	is a data vector
K	is the number of Poisson distribution
alpha0	is the initial value of the mixing weight
lambda0	is the initial value of the mean
a	represents the power of the reciprocal of the step size
b	indicates that the M-step is not implemented for the first b data points

Value

M_OEMtime,M_OEMalpha,M_OEMlambda

Examples

```

library(stats)
set.seed(637351)
K=5
alpha1=c(rep(1/K,K))
lambda1=c(1,2,3,4,5)
n=300
U=sample(c(1:n),n,replace=FALSE)
y= c(rep(0,n))
for(i in 1:n){
  if(U[i]<=0.2*n){
    y[i] = rpois(1,lambda1[1])}
  else if(U[i]>0.2*n & U[i]<=0.4*n){
    y[i] = rpois(1,lambda1[2])}
  else if(U[i]>0.4*n & U[i]<=0.6*n){
    y[i] = rpois(1,lambda1[3])}
  else if(U[i]>0.6*n & U[i]<=0.8*n){
    y[i] = rpois(1,lambda1[4])}
  else if(U[i]>0.8*n ){
    y[i] = rpois(1,lambda1[5])}
  }
M=5
seed=637351
set.seed(123)
e=sample(c(1:n),K)
alpha0=e/sum(e)
lambda0=c(1.5,2.5,3.5,4.5,5.5)
a=0.75
b=5
M_OEM(y,K,alpha0,lambda0,a,b)

```

PeMSD3

PeMSD3

Description

The PeMSD3 data

Usage

```
data("PeMSD3")
```

Format

A data frame with 26208 observations on the following 12 variables.

X315836 a numeric vector

X315837 a numeric vector

X315838 a numeric vector

X315841 a numeric vector
X315842 a numeric vector
X315839 a numeric vector
X315843 a numeric vector
X315846 a numeric vector
X315847 a numeric vector
X317895 a numeric vector
X315849 a numeric vector
X315850 a numeric vector

Details

It is the traffic data of Sacramento in California, the United States.

Source

Song, C., Lin, Y., Guo, S., Wan, H. Spatial-temporal synchronous graph convolutional networks: a new framework for spatial-temporal network data forecasting[C]. Proceedings of the AAAI Conference on Artificial Intelligence, 34(1), 914-921.

References

Song, C., Lin, Y., Guo, S., Wan, H. Spatial-temporal synchronous graph convolutional networks: a new framework for spatial-temporal network data forecasting[C]. Proceedings of the AAAI Conference on Artificial Intelligence, 34(1), 914-921.

Examples

```
data(PeMSD3)
## maybe str(PeMSD3) ; plot(PeMSD3) ...
```

PeMSD7

PeMSD7

Description

The PeMSD7 data

Usage

```
data("PeMSD7")
```

Format

A data frame with 17568 observations on the following 20 variables.

X773656 a numeric vector
X760074 a numeric vector
X760080 a numeric vector
X716414 a numeric vector
X760101 a numeric vector
X760112 a numeric vector
X716419 a numeric vector
X716421 a numeric vector
X716424 a numeric vector
X765476 a numeric vector
X760167 a numeric vector
X716427 a numeric vector
X716431 a numeric vector
X716433 a numeric vector
X760187 a numeric vector
X760196 a numeric vector
X716440 a numeric vector
X760226 a numeric vector
X760236 a numeric vector
X716449 a numeric vector

Details

It is the traffic data of Los Angeles in California, the United States.

Source

Xu, D., Wei, C., Peng, P., Xuan, Q., Guo, H. Ge-gan: a novel deep learning framework for road traffic state estimation[J]. Transportation Research Part C Emerging Technologies, 2020, 117, 102635.

References

Xu, D., Wei, C., Peng, P., Xuan, Q., Guo, H. Ge-gan: a novel deep learning framework for road traffic state estimation[J]. Transportation Research Part C Emerging Technologies, 2020, 117, 102635.

Examples

```
data(PeMSD7)  
## maybe str(PeMSD7) ; plot(PeMSD7) ...
```

PeMSD7_weekend	<i>PeMSD7 on weekend</i>
----------------	--------------------------

Description

The weekend data in PeMSD7

Usage

```
data("PeMSD7_weekend")
```

Format

A data frame with 5184 observations on the following 20 variables.

X773656 a numeric vector
X760074 a numeric vector
X760080 a numeric vector
X716414 a numeric vector
X760101 a numeric vector
X760112 a numeric vector
X716419 a numeric vector
X716421 a numeric vector
X716424 a numeric vector
X765476 a numeric vector
X760167 a numeric vector
X716427 a numeric vector
X716431 a numeric vector
X716433 a numeric vector
X760187 a numeric vector
X760196 a numeric vector
X716440 a numeric vector
X760226 a numeric vector
X760236 a numeric vector
X716449 a numeric vector

Details

The weekend data set only records traffic flow data on weekends.

Source

Xu, D., Wei, C., Peng, P., Xuan, Q., Guo, H. Ge-gan: a novel deep learning framework for road traffic state estimation[J]. Transportation Research Part C Emerging Technologies, 2020, 117, 102635.

References

Xu, D., Wei, C., Peng, P., Xuan, Q., Guo, H. Ge-gan: a novel deep learning framework for road traffic state estimation[J]. Transportation Research Part C Emerging Technologies, 2020, 117, 102635.

Examples

```
data(PeMSD7_weekend)
## maybe str(PeMSD7_weekend) ; plot(PeMSD7_weekend) ...
```

PeMSD7_workday	<i>PeMSD7 on workday</i>
----------------	--------------------------

Description

The workday data in PeMSD7

Usage

```
data("PeMSD7_workday")
```

Format

A data frame with 12384 observations on the following 20 variables.

X773656 a numeric vector
 X760074 a numeric vector
 X760080 a numeric vector
 X716414 a numeric vector
 X760101 a numeric vector
 X760112 a numeric vector
 X716419 a numeric vector
 X716421 a numeric vector
 X716424 a numeric vector
 X765476 a numeric vector
 X760167 a numeric vector
 X716427 a numeric vector
 X716431 a numeric vector
 X716433 a numeric vector

X760187 a numeric vector
X760196 a numeric vector
X716440 a numeric vector
X760226 a numeric vector
X760236 a numeric vector
X716449 a numeric vector

Details

The workday data set only records traffic flow data on workdays.

Source

Xu, D., Wei, C., Peng, P., Xuan, Q., Guo, H. Ge-gan: a novel deep learning framework for road traffic state estimation[J]. Transportation Research Part C Emerging Technologies, 2020, 117, 102635.

References

Xu, D., Wei, C., Peng, P., Xuan, Q., Guo, H. Ge-gan: a novel deep learning framework for road traffic state estimation[J]. Transportation Research Part C Emerging Technologies, 2020, 117, 102635.

Examples

```
data(PeMSD7_workday)  
## maybe str(PeMSD7_workday) ; plot(PeMSD7_workday) ...
```

Index

* datasets

PeMSD3, [8](#)

PeMSD7, [9](#)

PeMSD7_weekend, [11](#)

PeMSD7_workday, [12](#)

DE_OEM, [2](#)

DM_OEM, [5](#)

DMOEM, [3](#)

E_OEM, [6](#)

M_OEM, [7](#)

PeMSD3, [8](#)

PeMSD7, [9](#)

PeMSD7_weekend, [11](#)

PeMSD7_workday, [12](#)