Package ‘DepLogo’

May 7, 2026

Type Package

Title Dependency Logo

Version 1.2.2

Maintainer Jan Grau <grau@informatik.uni-halle.de>

Description Plots dependency logos from a set of aligned input sequences.

License GPL-3

NeedsCompilation no

RoxygenNote 7.3.1

Encoding UTF-8

VignetteBuilder knitr

Suggests knitr, rmarkdown, testthat

Author Jan Grau [aut, cre],
Jens Keilwagen [aut],
Martin Nettling [aut]

Repository CRAN

Date/Publication 2025-10-09 22:10:02 UTC

Contents

Alphabet 2
alphabet.dna 3
alphabet.dna.gap 3
alphabet.protein 3
alphabet.protein.gap 4
alphabet.rna 4
alphabet.rna.gap 4
colorchart 5
deprects 6
DLData 7
filter.by.conservation 8
filter.by.dependencies 9

filter.by.gaps 10
filterColumns 10
getDeps 11
getPWM 12
logo 13
partition 14
plotBlocks 15
plotDeparcs 17
plotDeplogo 18
plotDepmatrix 21
replaceColors 22
revcom 23
subBoxes 23
subLines 24
suggestColors 25
summary.DLData 26

Index **27**

`Alphabet` *built alphabet*

Description

builts an object of class Alphabet from the given set of symbols and colors

Usage

```
Alphabet(chars, cols)
```

Arguments

`chars`	set of symbols
`cols`	set of colors; one for each symbol

Value

the Alphabet object

Author(s)

Martin Nettling

Examples

```
DNA <- Alphabet(c("A", "C", "G", "T"), c("green4", "blue", "orange", "red"))
```

alphabet.dna *DNA alphabet*

Description

DNA alphabet

Usage

```
alphabet.dna
```

Format

An object of class `list` of length 2.

alphabet.dna.gap *DNA alphabet with gaps*

Description

DNA alphabet with gaps

Usage

```
alphabet.dna.gap
```

Format

An object of class `list` of length 2.

alphabet.protein *Amino acid alphabet*

Description

Amino acid alphabet

Usage

```
alphabet.protein
```

Format

An object of class `list` of length 2.

alphabet.protein.gap *Amino acid alphabet with gaps*

Description

Amino acid alphabet with gaps

Usage

```
alphabet.protein.gap
```

Format

An object of class `list` of length 2.

alphabet.rna *RNA alphabet*

Description

RNA alphabet

Usage

```
alphabet.rna
```

Format

An object of class `list` of length 2.

alphabet.rna.gap *RNA alphabet with gaps*

Description

RNA alphabet with gaps

Usage

```
alphabet.rna.gap
```

Format

An object of class `list` of length 2.

colorchart *Plots a colorchart representation of a set of sequences*

Description

This function is a low-level plotting function (using image with add=TRUE, internally).

Usage

```
colorchart(part, yoff, ic.scale = TRUE)
```

Arguments

part	the set of sequences as DLData object
yoff	the offset in y-direction within the current plot
ic.scale	ignored for colorcharts

Value

the vertical (y) offset after this plot

Author(s)

Jan Grau <grau@informatik.uni-halle.de>

Examples

```
# read data and create DLData object
seqs <- read.table(system.file("extdata", "cjun.txt", package = "DepLogo"),
    stringsAsFactors = FALSE)
data <- DLData(sequences = seqs[,1], weights = log1p(seqs[, 2]) )

# create high-level plot
plot(NULL, xlim = c(1, ncol(data$data) - 1), ylim = c(0, nrow(data$data)),
    ylab = nrow(data$data), axes = FALSE)
# and add colorchart and axis
colorchart(data, yoff = nrow(data$data))
axis(1)
```

deprects *Rectangles of averaged colors*

Description

Plots a representation of a set of sequences by rectangles of (scaled) averaged color values of the symbols at each position

Usage

```
deprects(part, yoff, ic.scale = TRUE)
```

Arguments

part	the set of sequences as DLData object
yoff	the offset in y-direction within the current plot
ic.scale	if TRUE, alpha values of colors will be assigned based on "information content" of the distribution at each position

Details

This function is a low-level plotting function (using rect, internally).

Value

the vertical (y) offset after this plot

Author(s)

Jan Grau <grau@informatik.uni-halle.de>

Examples

```
# read data and create DLData object
seqs <- read.table(system.file("extdata", "cjun.txt", package = "DepLogo"),
   stringsAsFactors = FALSE)
data <- DLData(sequences = seqs[, 1],weights = log1p(seqs[, 2]) )

# create high-level plot
plot(NULL, xlim = c(1, ncol(data$data) - 1), ylim = c(0, nrow(data$data)),
    ylab = nrow(data$data), axes = FALSE)
# and add deprects and axis
deprects(data, yoff = nrow(data$data))
axis(1)
```

DLData *Create* DLData *object*

Description

Creates a new DLData object from a set of input sequences.

Usage

```
DLData(
  sequences,
  weights = NULL,
  symbols = alphabet.dna$alphabet,
  colors = alphabet.dna$colors,
  delim = "",
  sortByWeights = !is.null(weights),
  axis.labels = NULL
)
```

Arguments

sequences	the input sequences, may be provided as i) character vector or ii) a data.frame with sequences organized in rows and one symbol per column
weights	weights associated with the sequences, numeric vector of the same length as sequences has sequences
symbols	the symbols (alphabet) over which the sequences are defined
colors	colors for each of the symbols, not necessarily unique
delim	delimiter between the symbols in the input sequences, ignored if sequences as a data.frame
sortByWeights	if TRUE, sequences will be ordered by their weight in decreasing order
axis.labels	the labels of the individual sequence positions; if NULL, indexes from 1 to to total number of positions will be used

Details

Sequences may either be provided as a character vector or as a data.frame. All symbols occurring in these sequences need to be defined and assigned to colors, which are used for plotting later. Colors do not need to be unique, but symbols with identical colors may become indistinguishable in subsequent plots (which might even be desired, for instance, when visualizing protein properties instead of amino acids). Sequences may have an associated weight, which is used to order sequences, e.g., for creating chunks/blocks of sequences in subsequent plots (see chunks parameter of plotDeplogo).

Value

the DLData object

Author(s)

Jan Grau <grau@informatik.uni-halle.de>

See Also

plotDeplogo

Examples

```
# creating a DLData object using default (DNA) alphabet and colors
# from a character vector with two entries
data <- DLData(c("ACGT", "ATTA"))

# creating a DLData object using a custom, binary alphabet and custom colors
data2 <- DLData(c("A,B,B,A,B", "A,B,B,A,A", "A,B,A,A,B"),
    symbols = c("A", "B"), colors = c("red","green"), delim = ",")

# creating a DLData object from a data frame
# (created from a character vector, in this case)
vec <- c("A,B,B,A,B", "A,B,B,A,A", "A,B,A,A,B")
df <- as.data.frame(t(sapply(vec, function(a){strsplit(a, ",")[[1]]})))
data.df <- DLData(df, symbols = c("A", "B"), colors = c("red", "green"))

# creating a DLData object from sequences and weights, read from a tabular file
seqs <- read.table(system.file("extdata", "cjun.txt", package = "DepLogo"),
    stringsAsFactors = FALSE)
data3 <- DLData(sequences = seqs[, 1], weights = log1p(seqs[, 2]) )
```

---

filter.by.conservation

Filters columns (sequence positions) by conservation

Description

Filters columns based on the relative information content of each column which is the standard information content normalized to the interval [0,1], where 0 corresponds to uniform distribution and 1 to perfect conservation of one nucleotide or amino acid, respectively.

Usage

```
filter.by.conservation(relative.ic)
```

Arguments

`relative.ic`	the maximum relative information content allowed to retain a position

Value

function that, given a DLData object, returns `TRUE` for every column that does not exceed the specified relative information content

Author(s)

Jan Grau <grau@informatik.uni-halle.de>

Examples

```
fun <- filter.by.conservation(relative.ic = 0.9)
```

---

filter.by.dependencies

Filters columns (sequence positions) by dependency

Description

Filters columns based on the average or maximum mutual information of a column to all other columns. Mutual information is normalized to to interval [0,1], where 0 corresponds to independence and 1 to perfect dependence.

Usage

```
filter.by.dependencies(mi.threshold, use.max = FALSE)
```

Arguments

`mi.threshold`	the minimum average or maximum mutual information required
`use.max`	if `TRUE`, the maximum and otherwise the average mutual information will be considered

Value

function that, given a DLData object, returns `TRUE` for every column that does exceed the specified average mutual information

Author(s)

Jan Grau <grau@informatik.uni-halle.de>

Examples

```
fun <- filter.by.dependencies(mi.threshold = 0.3)
```

filter.by.gaps *Filters columns (sequence positions) by gaps*

Description

Filters columns (sequence positions) by gaps

Usage

```
filter.by.gaps(percent.gap)
```

Arguments

percent.gap	the maximum fraction of gaps allowed to retain a column

Value

function that, given a DLData object, returns TRUE for every column that does not exceed the specified number of gaps

Author(s)

Jan Grau <grau@informatik.uni-halle.de>

Examples

```
fun <- filter.by.gaps(percent.gap = 0.1)
```

filterColumns *Filters data columns by some filter function*

Description

Filters the columns of the input data, i.e., positions of input sequences, by a filter function that, given a DLData object, returns a list containing i) as element $selected a vector with entries TRUE for every column that should be retained in the filtered data and ii) as element $range the range of values obtained for the filtering criterion.

Usage

```
filterColumns(data, filter.fun)
```

Arguments

data	the data as DLData object
filter.fun	the filter function

Value

a DLData object containing the filtered columns and the indexes of the remaining in its `axis.labels` field

Author(s)

Jan Grau <grau@informatik.uni-halle.de>

See Also

filter.by.gaps

filter.by.dependencies

filter.by.conservation

Examples

```
# read data and create DLData object
seqs <- read.table(system.file("extdata", "cjun.txt", package = "DepLogo"),
    stringsAsFactors = FALSE)
data <- DLData(sequences = seqs[, 1], weights = log1p(seqs[, 2]) )

# create a filter function based on the percentage of gap symbols (at most 10%)
fun <- filter.by.gaps(percent.gap = 0.1)
data2 <- filterColumns(data, fun)
```

---

getDeps — *Compute dependencies between positions*

Description

Computes the dependencies (as measures by mutual information) between all positions (columns) of discrete data. Specifically, it returns for each pair of positions (i,j) the mutual information I(X_i,X_j) multiplied by the number N of sequences (rows), which may also be used for testing the statistical significance of mutual information values, as for large N, 2*N*I(X_i,X_j) is approximately chi squared.

Usage

```
getDeps(data, ...)

## S3 method for class 'DLData'
getDeps(data, ...)

## S3 method for class 'data.frame'
getDeps(data, alphabet, ...)
```

Arguments

`data`	the data for computing mutual information. Either a DLData object or a data.frame; In the latter case, the symbols of the alphabet must be provided as a second parameter
`...`	the symbols of the alphabet as character vector, only if data is a data.frame
`alphabet`	only required when called on a data.frame

Value

a matrix of the mutual information values, where the diagonal is fixed to zero

Author(s)

Jan Grau <grau@informatik.uni-halle.de>

Examples

```
data <- DLData(c("ACGT", "ATTA"))
deps <- getDeps(data)
```

`getPWM` *Position weight matrix from DLData object*

Description

Determines the position weight matrix from a DLData object as relative frequency of symbols in each column of the data slot.

Usage

```
getPWM(part)

## S3 method for class 'DLData'
getPWM(part)
```

Arguments

`part`	the DLData object

Value

the position weight matrix, where columns correspond to positions (columns of the DLData$data slot) and rows to symbols

Author(s)

Jan Grau <grau@informatik.uni-halle.de>

Examples

```
data <- DLData(c("ACGT", "ATTA"))
getPWM(data)
```

---

logo *Sequence logo*

Description

Plots a representation of a set of sequences as a sequence logo

Usage

```
logo(part, yoff, ic.scale = TRUE)
```

Arguments

part	the set of sequences as DLData object
yoff	the offset in y-direction within the current plot
ic.scale	if TRUE, symbols are scaled by "information content" of the distribution at each position

Details

This function is a low-level plotting function (using polygon, internally).

Value

the vertical (y) offset after this plot

Author(s)

Jan Grau <grau@informatik.uni-halle.de>

Examples

```
# read data and create DLData object
seqs <- read.table(system.file("extdata", "cjun.txt", package = "DepLogo"),
    stringsAsFactors = FALSE)
data <- DLData(sequences = seqs[, 1], weights = log1p(seqs[,2]) )

# create high-level plot
plot(NULL, xlim = c(1, ncol(data$data) - 1), ylim = c(0, nrow(data$data)),
   ylab = nrow(data$data), axes = FALSE)
```

```
# and add sequence logo and axis
logo(data, yoff = nrow(data$data))
axis(1)
```

---

partition *Paritions data by most inter-dependent positions*

Description

Partitions `data` by the nucleotides at the most inter-dependent positions as measures by pairwise mutual information. Paritioning is performed recursively on the resulting subsets until i) the number of sequences in a partition is less then `minElements`, ii) the average pairwise dependency between the current position and `numBestForSorting` other positions with the largest mutual information value drops below `threshold`, or iii) `maxNum` recursive splits have already been performed. If splitting results in smaller partitions than `minElements`, these are added to the smallest partition with more than `minElements` sequences.

Usage

```
partition(
  data,
  minElements = 10,
  threshold = 0.1,
  numBestForSorting = 3,
  maxNum = 6,
  sortByWeights = NULL,
  partition.by = NULL
)

## S3 method for class 'DLData'
partition(
  data,
  minElements = 10,
  threshold = 0.1,
  numBestForSorting = 3,
  maxNum = 6,
  sortByWeights = NULL,
  partition.by = NULL
)
```

Arguments

`data`	the data as DLData object
`minElements`	the minimum number of elements to perform a further split
`threshold`	the threshold on the average mutual information value
`numBestForSorting`	the number of dependencies to other positions considered

maxNum	the maximum number of recursive splits
sortByWeights	if TRUE, partitions are ordered by their average weight value, if false by frequency of symbols at the partitioning position otherwise. If NULL, the $sortByWeights value of the DLData object is used
partition.by	specify fixed positions to partition by

Value

the partitions as list of DLData objects

Author(s)

Jan Grau <grau@informatik.uni-halle.de>

Examples

```
# create DLData object
seqs <- read.table(system.file("extdata", "cjun.txt", package = "DepLogo"),
    stringsAsFactors = FALSE)
data <- DLData(sequences = seqs[, 1], weights = log1p(seqs[,2]) )

# partition data using default parameters
partitions <- partition(data)

# partition data using a threshold of 0.3 on the mutual
# information value to the most dependent position,
# sorting the resulting partitions by weight
partitions2 <- partition(data = data, threshold = 0.3, numBestForSorting = 1, sortByWeights = TRUE)
```

---

plotBlocks *Plots blocks of data*

Description

Plots the blocks of data in data by successive, vertically arranged sub-plots of the function provided as block.fun. If data is a single DLData object, one block is plotted. Further arguments are provided to block.fun.

Usage

```
plotBlocks(
  data,
  show.number = TRUE,
  block.fun = deprects,
  ic.scale = TRUE,
  add = FALSE,
  ...
)
```

```
## S3 method for class 'DLData'
plotBlocks(
  data,
  show.number = TRUE,
  block.fun = deprects,
  ic.scale = TRUE,
  add = FALSE,
  ...
)

## S3 method for class 'list'
plotBlocks(
  data,
  show.number = TRUE,
  block.fun = deprects,
  ic.scale = TRUE,
  add = FALSE,
  ...
)
```

Arguments

`data`	the data, a single DLData object or a list of `DLData` objects
`show.number`	if `true`, the number of sequences (in total) in data is displayed on the left side of the plot
`block.fun`	the function called for each of the blocks
`ic.scale`	if `TRUE`, output of `block.fun` may be scaled by "information content"
`add`	if `TRUE`, the plot is added to an existing plot
`...`	if `add=FALSE` forwarded to the internal call to plot

Author(s)

Jan Grau <grau@informatik.uni-halle.de>

See Also

deprects

logo

colorchart

Examples

```
# read data and create DLData object
seqs <- read.table(system.file("extdata", "cjun.txt", package = "DepLogo"),
    stringsAsFactors = FALSE)
data <- DLData(sequences = seqs[, 1], weights = log1p(seqs[, 2]) )
```

```
# plot all data
plotBlocks(data)

# partition data
partitions <- partition(data, threshold = 0.3)
# and plot partitions
plotBlocks(partitions)

# or plot partitions as sequence logos
plotBlocks(partitions, block.fun = logo)
```

`plotDeparcs` *Plots a graph representation of dependency values*

Description

Plots a representation of dependency values as arcs between the sequence positions. Internally, dependency values are computed using getDeps on the `data` object.

Usage

```
plotDeparcs(
  data,
  axis.at.bottom = TRUE,
  add.legend = TRUE,
  show.pvals = FALSE,
  axis.labels = NULL,
  threshold = 0.1
)
```

Arguments

`data`	the DLData object containing the data
`axis.at.bottom`	if `TRUE`, the x-axis is shown at the bottom (side=1) of the plot, and at the top (side=3) otherwise
`add.legend`	if `TRUE` a legend of the color scale is added to the plot
`show.pvals`	if `TRUE`, -log10 p-values (computed by pchisq) are shown instead of mutual information values
`axis.labels`	the labels of the x-axis
`threshold`	threshold in mutual information values, edges below this value are not shown; ignored in `show.pvals=TRUE`

Author(s)

Jan Grau <grau@informatik.uni-halle.de>

Examples

```
# create DLData object
seqs <- read.table(system.file("extdata", "cjun.txt", package = "DepLogo"),
    stringsAsFactors = FALSE)
data <- DLData(sequences = seqs[,1], weights = log1p(seqs[, 2]) )

# plot using default parameters
plotDeparcs(data)

# plot with axis at top, without a legend (color scale), and using p-values
plotDeparcs(data, axis.at.bottom = FALSE, add.legend = FALSE, show.pvals = TRUE)
```

---

plotDeplogo *Plot a dependency logo*

Description

Plots a dependency logo

Usage

```
plotDeplogo(
  data,
  dep.fun = plotDeparcs,
  block.fun = deprects,
  summary.fun = logo,
  weight.fun = NULL,
  chunks = NULL,
  chunk.height = 800,
  summary.height = 100,
  minPercent = 0.03,
  threshold = 0.1,
  numBestForSorting = 3,
  maxNum = 6,
  sortByWeights = NULL,
  dep.fun.legend = TRUE,
  show.dependency.pvals = FALSE,
  axis.labels = NULL,
  weight.ratio = 5,
  partition.by = NULL,
  ...
)

## S3 method for class 'DLData'
plotDeplogo(
  data,
  dep.fun = plotDeparcs,
```

```
  block.fun = deprects,
  summary.fun = logo,
  weight.fun = NULL,
  chunks = NULL,
  chunk.height = 800,
  summary.height = 100,
  minPercent = 0.03,
  threshold = 0.1,
  numBestForSorting = 3,
  maxNum = 6,
  sortByWeights = NULL,
  dep.fun.legend = TRUE,
  show.dependency.pvals = FALSE,
  axis.labels = NULL,
  weight.ratio = 5,
  partition.by = NULL,
  ...
)
```

Arguments

`data`	the data, currently implemented for DLData objects
`dep.fun`	the function for plotting the representation of dependency values (as computed by getDeps)
`block.fun`	the function for plotting a representation of the individual partitions of the data generated in dependency logos.
`summary.fun`	the function for plotting a representation of the summary plot for (one chunk of) the data
`weight.fun`	the function for plotting a representation of the `weights` values of the sequences within one partition
`chunks`	the size of chunks the data is split into. The sum of the chunk sizes must not be greater than the number of data points in data; The default value of NULL corresponds to one chunk containing all data points
`chunk.height`	the (relative) height of the parts of the plot representing each of the chunks, one height for each chunk
`summary.height`	the (relative) height of the block summaries in the plot
`minPercent`	the minimum percentage of the (sub) data set that may constitute its own partition in the dependency logo
`threshold`	the threshold on the dependency value for further splits
`numBestForSorting`	the number of dependencies between position i and all other positions when computing the dependency value of position i
`maxNum`	the maximum number of splits allowed
`sortByWeights`	are partitions sorted by their average weight (descending)

dep.fun.legend	if TRUE, a legend of the color scale used for plotting the dependency values in dep.fun is added to the plot
show.dependency.pvals	is TRUE, p-values are used for plotting dependency values in dep.fun instead of mutual information values
axis.labels	labels for the x-axis, vector of the same length as the individual sequences
weight.ratio	the factor by which the plotting width for the main plot is larger than for weight.fun
partition.by	specify fixed positions to partition by
...	forwarded to the high-level plot that contains the blocks plotted by block.fun

Details

The function dep.fun provided for plotting the representation of dependencies is currently implemented in plotDeparcs and plotDepmatrix. Custom implementations must have the same signature as these functions and create a single plot without using layout (or similar).

The functions block.fun and summary.fun provided for plotting the representation of individual partitions of the data generated in dependency logos are currently implemented in deprects, colorchart, and logo. Custom implementations must have the same signature as these functions and create a single plot without using layout (or similar).

The function weight.fun for plotting a representation of the weights values of the sequences within one partition is currently implemented in subLines and subBoxes. Custom implementations must have the same signature as these functions and create a single plot without using layout (or similar).

Value

a list of DLData objects with the partitions created for the dependency logo

Author(s)

Jan Grau <grau@informatik.uni-halle.de>

Examples

```
# read data and create DLData object
seqs <- read.table(system.file("extdata", "cjun.txt", package = "DepLogo"),
    stringsAsFactors = FALSE)
data <- DLData(sequences = seqs[, 1],weights = log1p(seqs[, 2]) )

# plot default dependency logo
plotDeplogo(data)

# refine threshold for clearer picture
plotDeplogo(data, threshold = 0.3)

# customize different parts of the plot
plotDeplogo(data, threshold = 0.3, dep.fun = plotDepmatrix, block.fun = colorchart)

# add plots of the weights
```

```
plotDeplogo(data, weight.fun = subBoxes)
```

---

plotDepmatrix *Plots a matrix representation of dependency values*

Description

Plots a representation of dependency values as a triangular matrix rotated by 45 degrees. Internally, dependency values are computed using getDeps on the `data` object.

Usage

```
plotDepmatrix(
  data,
  axis.at.bottom = TRUE,
  add.legend = TRUE,
  show.pvals = FALSE,
  axis.labels = NULL,
  threshold = 0.1
)
```

Arguments

`data`	the DLData object containing the data
`axis.at.bottom`	if `TRUE`, the x-axis is shown at the bottom (side=1) of the plot, and at the top (side=3) otherwise
`add.legend`	if `TRUE` a legend of the color scale is added to the plot
`show.pvals`	if `TRUE`, -log10 p-values (computed by pchisq) are shown instead of mutual information values
`axis.labels`	the labels of the x-axis
`threshold`	ignored

Author(s)

Jan Grau <grau@informatik.uni-halle.de>

Examples

```
# create DLData object
seqs <- read.table(system.file("extdata", "cjun.txt", package = "DepLogo"),
    stringsAsFactors = FALSE)
data <- DLData(sequences = seqs[, 1], weights = log1p(seqs[, 2]) )

# plot using default parameters
plotDepmatrix(data)

# plot with axis at top, without a legend (color scale), and using p-values
plotDepmatrix(data, axis.at.bottom = FALSE, add.legend = FALSE, show.pvals = TRUE)
```

`replaceColors` *Replaces colors in DLData object*

Description

Replaces colors in DLData object

Usage

```
replaceColors(data, colors)

## S3 method for class 'DLData'
replaceColors(data, colors)
```

Arguments

`data`	the data
`colors`	the new colors

Value

the modified DLData object

Author(s)

Jan Grau <grau@informatik.uni-halle.de>

See Also

replaceColors

Examples

```
# read data and create DLData object
seqs <- read.table(system.file("extdata", "cjun.txt", package = "DepLogo"),
    stringsAsFactors = FALSE)
data <- DLData(sequences = seqs[, 1], weights = log1p(seqs[, 2]) )

replaceColors(data, c("red", "green", "blue", "yellow"))
```

revcom — *Reverse complement*

Description

Determine the reverse complementary DLData object. Only works for DNA or RNA. Data may include gap symbols.

Usage

```
revcom(data)

## S3 method for class 'DLData'
revcom(data)
```

Arguments

data	the data

Value

the reverse complement

Author(s)

Jan Grau <grau@informatik.uni-halle.de>

Examples

```
data <- DLData(c("ACGT", "ATTA"))
revcom(data)
```

subBoxes — *Plots weights as boxplots*

Description

Plots a representation of the weights of a list of DLData objects. Each entry of the list is shown as an independent boxplot.

Usage

```
subBoxes(sub.parts, range, axis.above = TRUE, axis.below = TRUE)
```

Arguments

sub.parts	a list of DLData objects
range	the range of values shown in the plot (i.e., the xlim value of the call to plot)
axis.above	if TRUE, an axis at the top of the plot (side=3) is shown
axis.below	if TRUE, an axis at the bottom of the plot (side=1) is shown

Author(s)

Jan Grau <grau@informatik.uni-halle.de>

Examples

```
# read data and create DLData object
seqs <- read.table(system.file("extdata", "nrsf.txt", package = "DepLogo"),
    stringsAsFactors = FALSE)
data <- DLData(sequences = seqs[, 1], weights = log1p(seqs[, 2]) )

# create dependency logo with plotted weights
plotDeplogo(data, threshold = 0.03, weight.fun = subBoxes)
```

---

subLines *Plots weights as lines*

Description

Plots a representation of the weights of a list of DLData objects. Each entry of the list is shown as an independent line with the median value shown as a red vertical line. Plots of list entries are separated by horizontal grey lines.

Usage

```
subLines(sub.parts, range, axis.above = TRUE, axis.below = TRUE)
```

Arguments

sub.parts	a list of DLData objects
range	the range of values shown in the plot (i.e., the xlim value of the call to plot)
axis.above	if TRUE, an axis at the top of the plot (side=3) is shown
axis.below	if TRUE, an axis at the bottom of the plot (side=1) is shown

Author(s)

Jan Grau <grau@informatik.uni-halle.de>

Examples

```
# read data and create DLData object
seqs <- read.table(system.file("extdata", "nrsf.txt", package = "DepLogo"),
    stringsAsFactors = FALSE)
data <- DLData(sequences = seqs[, 1], weights = log1p(seqs[, 2]) )

# create dependency logo with plotted weights
plotDeplogo(data, threshold = 0.03, weight.fun = subLines)
```

`suggestColors` *Suggests colors for symbols*

Description

Suggests colors for the symbols in `data` based on the co-occurrence of symbols at common positions, weighted by the dependency values at those positions. The idea is to assign similar colors only to symbols that either mostly occur at different positions or that are present at positions with low inter-dependencies to other positions.

Usage

```
suggestColors(data)

## S3 method for class 'DLData'
suggestColors(data)
```

Arguments

`data`	the data

Value

the colors

Author(s)

Jan Grau <grau@informatik.uni-halle.de>

See Also

replaceColors

Examples

```
# read data and create DLData object
seqs <- read.table(system.file("extdata", "cjun.txt", package = "DepLogo"),
    stringsAsFactors = FALSE)
data <- DLData(sequences = seqs[, 1] ,weights = log1p(seqs[, 2]) )

suggestColors(data)
```

summary.DLData *Summarizing DLData objects*

Description

summary method for class "DLData". The summary includes the number of sequences, the consensus sequence and the number of sequences in object that match the consensus.

Usage

```
## S3 method for class 'DLData'
summary(object, delete.gaps = FALSE, ...)
```

Arguments

object	an object of class "DLData"
delete.gaps	if gaps should be removed from the consensus
...	further arguments passed to or from other methods

Value

a list with elements members containing the number of sequences, consensus containing the consensus sequences, and equal.consensus containing the number of sequences in object that are identical to consensus

Author(s)

Jens Keilwagen, Jan Grau <grau@informatik.uni-halle.de>

Examples

```
seqs <- read.table(system.file("extdata", "cjun.txt", package = "DepLogo"),
    stringsAsFactors = FALSE)
data <- DLData(sequences = seqs[, 1], weights = log1p(seqs[, 2]) )
summary(data)
```

Index

∗ **datasets**
    alphabet.dna, 3
    alphabet.dna.gap, 3
    alphabet.protein, 3
    alphabet.protein.gap, 4
    alphabet.rna, 4
    alphabet.rna.gap, 4

Alphabet, 2
alphabet.dna, 3
alphabet.dna.gap, 3
alphabet.protein, 3
alphabet.protein.gap, 4
alphabet.rna, 4
alphabet.rna.gap, 4

colorchart, 5, *16*, *20*

deprects, 6, *16*, *20*
DLData, *5*, *6*, 7, *8–11*, *13–17*, *19–24*

filter.by.conservation, 8, *11*
filter.by.dependencies, 9, *11*
filter.by.gaps, 10, *11*
filterColumns, 10

getDeps, 11, *17*, *19*, *21*
getPWM, 12

image, *5*

layout, *20*
logo, 13, *16*, *20*

partition, 14
pchisq, *17*, *21*
plot, *16*, *24*
plotBlocks, 15
plotDeparcs, 17, *20*
plotDeplogo, *8*, 18
plotDepmatrix, *20*, 21
polygon, *13*

rect, *6*
replaceColors, *22*, 22, *25*
revcom, 23

subBoxes, *20*, 23
subLines, *20*, 24
suggestColors, 25
summary.DLData, 26