Package ‘DoubleML’

May 7, 2026

Type Package

Title Double Machine Learning in R

Version 1.0.2

Description Implementation of the double/debiased machine learning framework of Chernozhukov et al. (2018) <doi:10.1111/ectj.12097> for partially linear regression models, partially linear instrumental variable regression models, interactive regression models and interactive instrumental variable regression models. 'DoubleML' allows estimation of the nuisance parts in these models by machine learning methods and computation of the Neyman orthogonal score functions. 'DoubleML' is built on top of 'mlr3' and the 'mlr3' ecosystem. The object-oriented implementation of 'DoubleML' based on the 'R6' package is very flexible. More information available in the publication in the Journal of Statistical Software: <doi:10.18637/jss.v108.i03>.

License MIT + file LICENSE

URL https://docs.doubleml.org/stable/index.html, https://github.com/DoubleML/doubleml-for-r/

BugReports https://github.com/DoubleML/doubleml-for-r/issues

Encoding UTF-8

Depends R (>= 3.5.0)

Imports R6 (>= 2.4.1), data.table (>= 1.12.8), stats, checkmate, mlr3 (>= 0.5.0), mlr3tuning (>= 0.3.0), mvtnorm, utils, clusterGeneration, readstata13, mlr3learners (>= 0.3.0), mlr3misc

RoxygenNote 7.3.2

Suggests knitr, rmarkdown, testthat, covr, patrick (>= 0.1.0), paradox (>= 0.4.0), dplyr, glmnet, lgr, ranger, sandwich, AER, rpart, bbotk, mlr3pipelines

VignetteBuilder knitr

Collate 'double_ml.R' 'double_ml_data.R' 'double_ml_ssm.R' 'double_ml_iivm.R' 'double_ml_irm.R' 'double_ml_pliv.R' 'double_ml_plr.R' 'helper.R' 'datasets.R' 'zzz.R'

NeedsCompilation no

Author Philipp Bach [aut, cre],
Victor Chernozhukov [aut],
Malte S. Kurz [aut],
Martin Spindler [aut],
Klaassen Sven [aut]

Maintainer Philipp Bach <philipp.bach@uni-hamburg.de>

Repository CRAN

Date/Publication 2025-04-11 10:20:07 UTC

Contents

DoubleML . . . 2
DoubleMLClusterData . . . 10
DoubleMLData . . . 12
DoubleMLIIVM . . . 14
DoubleMLIRM . . . 18
DoubleMLPLIV . . . 21
DoubleMLPLR . . . 27
DoubleMLSSM . . . 31
double_ml_data_from_data_frame . . . 36
double_ml_data_from_matrix . . . 38
fetch_401k . . . 39
fetch_bonus . . . 40
make_iivm_data . . . 42
make_irm_data . . . 44
make_pliv_CHS2015 . . . 45
make_pliv_multiway_cluster_CKMS2021 . . . 46
make_plr_CCDDHNR2018 . . . 48
make_plr_turrell2018 . . . 49
make_ssm_data . . . 50

Index **52**

`DoubleML` *Abstract class DoubleML*

Description

Abstract base class that can't be initialized.

Format

R6::R6Class object.

Active bindings

`all_coef` (`matrix()`)
Estimates of the causal parameter(s) for the `n_rep` different sample splits after calling `fit()`.

`all_dml1_coef` (`array()`)
Estimates of the causal parameter(s) for the `n_rep` different sample splits after calling `fit()` with `dml_procedure = "dml1"`.

`all_se` (`matrix()`)
Standard errors of the causal parameter(s) for the `n_rep` different sample splits after calling `fit()`.

`apply_cross_fitting` (`logical(1)`)
Indicates whether cross-fitting should be applied. Default is `TRUE`.

`boot_coef` (`matrix()`)
Bootstrapped coefficients for the causal parameter(s) after calling `fit()` and `bootstrap()`.

`boot_t_stat` (`matrix()`)
Bootstrapped t-statistics for the causal parameter(s) after calling `fit()` and `bootstrap()`.

`coef` (`numeric()`)
Estimates for the causal parameter(s) after calling `fit()`.

`data` (`data.table`)
Data object.

`dml_procedure` (`character(1)`)
A `character()` (`"dml1"` or `"dml2"`) specifying the double machine learning algorithm. Default is `"dml2"`.

`draw_sample_splitting` (`logical(1)`)
Indicates whether the sample splitting should be drawn during initialization of the object. Default is `TRUE`.

`learner` (named `list()`)
The machine learners for the nuisance functions.

`n_folds` (`integer(1)`)
Number of folds. Default is `5`.

`n_rep` (`integer(1)`)
Number of repetitions for the sample splitting. Default is `1`.

`params` (named `list()`)
The hyperparameters of the learners.

`psi` (`array()`)
Value of the score function $\psi(W;\theta,\eta) = \psi_a(W;\eta)\theta + \psi_b(W;\eta)$ after calling `fit()`.

`psi_a` (`array()`)
Value of the score function component $\psi_a(W;\eta)$ after calling `fit()`.

`psi_b` (`array()`)
Value of the score function component $\psi_b(W;\eta)$ after calling `fit()`.

`predictions` (`array()`)
Predictions of the nuisance models after calling `fit(store_predictions=TRUE)`.

`models` (`array()`)
The fitted nuisance models after calling `fit(store_models=TRUE)`.

`pval` (`numeric()`)
: p-values for the causal parameter(s) after calling `fit()`.

`score` (`character(1)`, `function()`)
: A `character(1)` or `function()` specifying the score function.

`se` (`numeric()`)
: Standard errors for the causal parameter(s) after calling `fit()`.

`smpls` (`list()`)
: The partition used for cross-fitting.

`smpls_cluster` (`list()`)
: The partition of clusters used for cross-fitting.

`t_stat` (`numeric()`)
: t-statistics for the causal parameter(s) after calling `fit()`.

`tuning_res` (named `list()`)
: Results from hyperparameter tuning.

Methods

Public methods:

- `DoubleML$new()`
- `DoubleML$print()`
- `DoubleML$fit()`
- `DoubleML$bootstrap()`
- `DoubleML$split_samples()`
- `DoubleML$set_sample_splitting()`
- `DoubleML$tune()`
- `DoubleML$summary()`
- `DoubleML$confint()`
- `DoubleML$learner_names()`
- `DoubleML$params_names()`
- `DoubleML$set_ml_nuisance_params()`
- `DoubleML$p_adjust()`
- `DoubleML$get_params()`
- `DoubleML$clone()`

Method `new()`**:** DoubleML is an abstract class that can't be initialized.

Usage:

```
DoubleML$new()
```

Method `print()`**:** Print DoubleML objects.

Usage:

```
DoubleML$print()
```

Method `fit()`**:** Estimate DoubleML models.

Usage:

```
DoubleML$fit(store_predictions = FALSE, store_models = FALSE)
```

Arguments:

`store_predictions (logical(1))`
: Indicates whether the predictions for the nuisance functions should be stored in field `predictions`. Default is `FALSE`.

`store_models (logical(1))`
: Indicates whether the fitted models for the nuisance functions should be stored in field `models` if you want to analyze the models or extract information like variable importance. Default is `FALSE`.

Returns: self

Method `bootstrap()`**:** Multiplier bootstrap for DoubleML models.

Usage:

```
DoubleML$bootstrap(method = "normal", n_rep_boot = 500)
```

Arguments:

`method (character(1))`
: A `character(1)` (`"Bayes"`, `"normal"` or `"wild"`) specifying the multiplier bootstrap method.

`n_rep_boot (integer(1))`
: The number of bootstrap replications.

Returns: self

Method `split_samples()`**:** Draw sample splitting for DoubleML models.

The samples are drawn according to the attributes `n_folds`, `n_rep` and `apply_cross_fitting`.

Usage:

```
DoubleML$split_samples()
```

Returns: self

Method `set_sample_splitting()`**:** Set the sample splitting for DoubleML models.

The attributes `n_folds` and `n_rep` are derived from the provided partition.

Usage:

```
DoubleML$set_sample_splitting(smpls)
```

Arguments:

`smpls (list())`
: A nested `list()`. The outer lists needs to provide an entry per repeated sample splitting (length of the list is set as `n_rep`). The inner list is a named `list()` with names `train_ids` and `test_ids`. The entries in `train_ids` and `test_ids` must be partitions per fold (length of `train_ids` and `test_ids` is set as `n_folds`).

Returns: self

Examples:

```
library(DoubleML)
library(mlr3)
set.seed(2)
obj_dml_data = make_plr_CCDDHNR2018(n_obs=10)
```

```
dml_plr_obj = DoubleMLPLR$new(obj_dml_data,
                              lrn("regr.rpart"), lrn("regr.rpart"))

# simple sample splitting with two folds and without cross-fitting
smpls = list(list(train_ids = list(c(1, 2, 3, 4, 5)),
                  test_ids = list(c(6, 7, 8, 9, 10))))
dml_plr_obj$set_sample_splitting(smpls)

# sample splitting with two folds and cross-fitting but no repeated cross-fitting
smpls = list(list(train_ids = list(c(1, 2, 3, 4, 5), c(6, 7, 8, 9, 10)),
                  test_ids = list(c(6, 7, 8, 9, 10), c(1, 2, 3, 4, 5))))
dml_plr_obj$set_sample_splitting(smpls)

# sample splitting with two folds and repeated cross-fitting with n_rep = 2
smpls = list(list(train_ids = list(c(1, 2, 3, 4, 5), c(6, 7, 8, 9, 10)),
                  test_ids = list(c(6, 7, 8, 9, 10), c(1, 2, 3, 4, 5))),
             list(train_ids = list(c(1, 3, 5, 7, 9), c(2, 4, 6, 8, 10)),
                  test_ids = list(c(2, 4, 6, 8, 10), c(1, 3, 5, 7, 9))))
dml_plr_obj$set_sample_splitting(smpls)
```

Method `tune()`**:** Hyperparameter-tuning for DoubleML models.

The hyperparameter-tuning is performed using the tuning methods provided in the mlr3tuning package. For more information on tuning in mlr3, we refer to the section on parameter tuning in the mlr3 book.

Usage:

```
DoubleML$tune(
  param_set,
  tune_settings = list(n_folds_tune = 5, rsmp_tune = mlr3::rsmp("cv", folds = 5), measure
    = NULL, terminator = mlr3tuning::trm("evals", n_evals = 20), algorithm =
    mlr3tuning::tnr("grid_search"), resolution = 5),
  tune_on_folds = FALSE
)
```

Arguments:

`param_set` (named `list()`)
: A named `list` with a parameter grid for each nuisance model/learner (see method `learner_names()`). The parameter grid must be an object of class ParamSet.

`tune_settings` (named `list()`)
: A named `list()` with arguments passed to the hyperparameter-tuning with mlr3tuning to set up TuningInstance objects. `tune_settings` has entries

- `terminator` (Terminator)
  A Terminator object. Specification of `terminator` is required to perform tuning.
- `algorithm` (Tuner or `character(1)`)
  A Tuner object (recommended) or key passed to the respective dictionary to specify the tuning algorithm used in tnr(). `algorithm` is passed as an argument to tnr(). If `algorithm` is not specified by the users, default is set to `"grid_search"`. If set to `"grid_search"`, then additional argument `"resolution"` is required.

- `rsmp_tune` (Resampling or `character(1)`)
  A Resampling object (recommended) or option passed to rsmp() to initialize a Resampling for parameter tuning in `mlr3`. If not specified by the user, default is set to `"cv"` (cross-validation).
- `n_folds_tune` (`integer(1)`, optional)
  If `rsmp_tune = "cv"`, number of folds used for cross-validation. If not specified by the user, default is set to `5`.
- `measure` (`NULL`, named `list()`, optional)
  Named list containing the measures used for parameter tuning. Entries in list must either be Measure objects or keys to be passed to passed to msr(). The names of the entries must match the learner names (see method `learner_names()`). If set to `NULL`, default measures are used, i.e., `"regr.mse"` for continuous outcome variables and `"classif.ce"` for binary outcomes.
- `resolution` (`character(1)`)
  The key passed to the respective dictionary to specify the tuning algorithm used in tnr(). `resolution` is passed as an argument to tnr().

`tune_on_folds (logical(1))`
Indicates whether the tuning should be done fold-specific or globally. Default is `FALSE`.

Returns: self

Method `summary()`**:** Summary for DoubleML models after calling `fit()`.

Usage:

```
DoubleML$summary(digits = max(3L, getOption("digits") - 3L))
```

Arguments:

`digits (integer(1))`
The number of significant digits to use when printing.

Method `confint()`**:** Confidence intervals for DoubleML models.

Usage:

```
DoubleML$confint(parm, joint = FALSE, level = 0.95)
```

Arguments:

`parm (numeric() or character())`
A specification of which parameters are to be given confidence intervals among the variables for which inference was done, either a vector of numbers or a vector of names. If missing, all parameters are considered (default).

`joint (logical(1))`
Indicates whether joint confidence intervals are computed. Default is `FALSE`.

`level (numeric(1))`
The confidence level. Default is `0.95`.

Returns: A `matrix()` with the confidence interval(s).

Method `learner_names()`**:** Returns the names of the learners.

Usage:

```
DoubleML$learner_names()
```

Returns: `character()` with names of learners.

Method `params_names()`**:** Returns the names of the nuisance models with hyperparameters.

Usage:

```
DoubleML$params_names()
```

Returns: `character()` with names of nuisance models with hyperparameters.

Method `set_ml_nuisance_params()`**:** Set hyperparameters for the nuisance models of DoubleML models.

Note that in the current implementation, either all parameters have to be set globally or all parameters have to be provided fold-specific.

Usage:

```
DoubleML$set_ml_nuisance_params(
  learner = NULL,
  treat_var = NULL,
  params,
  set_fold_specific = FALSE
)
```

Arguments:

`learner (character(1))`
: The nuisance model/learner (see method `params_names`).

`treat_var (character(1))`
: The treatment varaible (hyperparameters can be set treatment-variable specific).

`params (named list())`
: A named `list()` with estimator parameters. Parameters are used for all folds by default. Alternatively, parameters can be passed in a fold-specific way if option `fold_specific`is `TRUE`. In this case, the outer list needs to be of length `n_rep` and the inner list of length `n_folds`.

`set_fold_specific (logical(1))`
: Indicates if the parameters passed in `params` should be passed in fold-specific way. Default is `FALSE`. If `TRUE`, the outer list needs to be of length `n_rep` and the inner list of length `n_folds`. Note that in the current implementation, either all parameters have to be set globally or all parameters have to be provided fold-specific.

Returns: self

Method `p_adjust()`**:** Multiple testing adjustment for DoubleML models.

Usage:

```
DoubleML$p_adjust(method = "romano-wolf", return_matrix = TRUE)
```

Arguments:

`method (character(1))`
: A `character(1)`(`"romano-wolf"`, `"bonferroni"`, `"holm"`, etc) specifying the adjustment method. In addition to `"romano-wolf"`, all methods implemented in p.adjust() can be applied. Default is `"romano-wolf"`.

`return_matrix (logical(1))`
: Indicates if the output is returned as a matrix with corresponding coefficient names.

Returns: `numeric()` with adjusted p-values. If `return_matrix = TRUE`, a `matrix()` with adjusted p_values.

Method `get_params()`**:** Get hyperparameters for the nuisance model of DoubleML models.

Usage:

```
DoubleML$get_params(learner)
```

Arguments:

`learner (character(1))`
: The nuisance model/learner (see method `params_names()`)

Returns: named `list()`with paramers for the nuisance model/learner.

Method `clone()`**:** The objects of this class are cloneable with this method.

Usage:

```
DoubleML$clone(deep = FALSE)
```

Arguments:

`deep` Whether to make a deep clone.

See Also

Other DoubleML: `DoubleMLIIVM`, `DoubleMLIRM`, `DoubleMLPLIV`, `DoubleMLPLR`, `DoubleMLSSM`

Examples

```
## ------------------------------------------------
## Method `DoubleML$set_sample_splitting`
## ------------------------------------------------

library(DoubleML)
library(mlr3)
set.seed(2)
obj_dml_data = make_plr_CCDDHNR2018(n_obs=10)
dml_plr_obj = DoubleMLPLR$new(obj_dml_data,
                              lrn("regr.rpart"), lrn("regr.rpart"))

# simple sample splitting with two folds and without cross-fitting
smpls = list(list(train_ids = list(c(1, 2, 3, 4, 5)),
                  test_ids = list(c(6, 7, 8, 9, 10))))
dml_plr_obj$set_sample_splitting(smpls)

# sample splitting with two folds and cross-fitting but no repeated cross-fitting
smpls = list(list(train_ids = list(c(1, 2, 3, 4, 5), c(6, 7, 8, 9, 10)),
                  test_ids = list(c(6, 7, 8, 9, 10), c(1, 2, 3, 4, 5))))
dml_plr_obj$set_sample_splitting(smpls)

# sample splitting with two folds and repeated cross-fitting with n_rep = 2
smpls = list(list(train_ids = list(c(1, 2, 3, 4, 5), c(6, 7, 8, 9, 10)),
                  test_ids = list(c(6, 7, 8, 9, 10), c(1, 2, 3, 4, 5))),
             list(train_ids = list(c(1, 3, 5, 7, 9), c(2, 4, 6, 8, 10)),
                  test_ids = list(c(2, 4, 6, 8, 10), c(1, 3, 5, 7, 9))))
dml_plr_obj$set_sample_splitting(smpls)
```

DoubleMLClusterData *Double machine learning data-backend for data with cluster variables*

Description

Double machine learning data-backend for data with cluster variables.

DoubleMLClusterData objects can be initialized from a data.table. Alternatively DoubleML provides functions to initialize from a collection of matrix objects or a data.frame. The following functions can be used to create a new instance of DoubleMLClusterData.

- DoubleMLClusterData$new() for initialization from a data.table.
- double_ml_data_from_matrix() for initialization from matrix objects,
- double_ml_data_from_data_frame() for initialization from a data.frame.

Super class

DoubleML::DoubleMLData -> DoubleMLClusterData

Active bindings

cluster_cols (character())
: The cluster variable(s).

x_cols (NULL, character())
: The covariates. If NULL, all variables (columns of data) which are neither specified as outcome variable y_col, nor as treatment variables d_cols, nor as instrumental variables z_cols, nor as cluster variables cluster_cols are used as covariates. Default is NULL.

n_cluster_vars (integer(1))
: The number of cluster variables.

Methods

Public methods:

- DoubleMLClusterData$new()
- DoubleMLClusterData$print()
- DoubleMLClusterData$set_data_model()
- DoubleMLClusterData$clone()

Method new(): Creates a new instance of this R6 class.

Usage:

```
DoubleMLClusterData$new(
  data = NULL,
  x_cols = NULL,
  y_col = NULL,
  d_cols = NULL,
  cluster_cols = NULL,
```

```
  z_cols = NULL,
  s_col = NULL,
  use_other_treat_as_covariate = TRUE
)
```

Arguments:

`data` (`data.table`, `data.frame()`)
: Data object.

`x_cols` (`NULL`, `character()`)
: The covariates. If `NULL`, all variables (columns of `data`) which are neither specified as outcome variable `y_col`, nor as treatment variables `d_cols`, nor as instrumental variables `z_cols` are used as covariates. Default is `NULL`.

`y_col` (`character(1)`)
: The outcome variable.

`d_cols` (`character()`)
: The treatment variable(s).

`cluster_cols` (`character()`)
: The cluster variable(s).

`z_cols` (`NULL`, `character()`)
: The instrumental variables. Default is `NULL`.

`s_col` (`NULL`, `character()`)
: The score or selection variable (only relevant/used for SSM Estimators). Default is `NULL`.

`use_other_treat_as_covariate` (`logical(1)`)
: Indicates whether in the multiple-treatment case the other treatment variables should be added as covariates. Default is `TRUE`.

Method `print()`**:** Print DoubleMLClusterData objects.

Usage:

```
DoubleMLClusterData$print()
```

Method `set_data_model()`**:** Setter function for `data_model`. The function implements the causal model as specified by the user via `y_col`, `d_cols`, `x_cols`, `z_cols` and `cluster_cols` and assigns the role for the treatment variables in the multiple-treatment case.

Usage:

```
DoubleMLClusterData$set_data_model(treatment_var)
```

Arguments:

`treatment_var` (`character()`)
: Active treatment variable that will be set to `treat_col`.

Method `clone()`**:** The objects of this class are cloneable with this method.

Usage:

```
DoubleMLClusterData$clone(deep = FALSE)
```

Arguments:

`deep` Whether to make a deep clone.

Examples

```
library(DoubleML)
dt = make_pliv_multiway_cluster_CKMS2021(return_type = "data.table")
obj_dml_data = DoubleMLClusterData$new(dt,
  y_col = "Y",
  d_cols = "D",
  z_cols = "Z",
  cluster_cols = c("cluster_var_i", "cluster_var_j"))
```

DoubleMLData *Double machine learning data-backend*

Description

Double machine learning data-backend.

DoubleMLData objects can be initialized from a data.table. Alternatively DoubleML provides functions to initialize from a collection of matrix objects or a data.frame. The following functions can be used to create a new instance of DoubleMLData.

- DoubleMLData$new() for initialization from a data.table.
- double_ml_data_from_matrix() for initialization from matrix objects,
- double_ml_data_from_data_frame() for initialization from a data.frame.

Active bindings

all_variables (character())
: All variables available in the dataset.

d_cols (character())
: The treatment variable(s).

data (data.table)
: Data object.

data_model (data.table)
: Internal data object that implements the causal model as specified by the user via y_col, d_cols, x_cols and z_cols.

n_instr (NULL, integer(1))
: The number of instruments.

n_obs (integer(1))
: The number of observations.

n_treat (integer(1))
: The number of treatment variables.

other_treat_cols (NULL, character())
: If use_other_treat_as_covariate is TRUE, other_treat_cols are the treatment variables that are not "active" in the multiple-treatment case. These variables then are internally added to the covariates x_cols during the fitting stage. If use_other_treat_as_covariate is FALSE, other_treat_cols is NULL.

`treat_col` (`character(1)`)
: "Active" treatment variable in the multiple-treatment case.

`use_other_treat_as_covariate` (`logical(1)`)
: Indicates whether in the multiple-treatment case the other treatment variables should be added as covariates. Default is `TRUE`.

`x_cols` (`NULL`, `character()`)
: The covariates. If `NULL`, all variables (columns of `data`) which are neither specified as outcome variable `y_col`, nor as treatment variables `d_cols`, nor as instrumental variables `z_cols` are used as covariates. Default is `NULL`.

`y_col` (`character(1)`)
: The outcome variable.

`z_cols` (`NULL`, `character()`)
: The instrumental variables. Default is `NULL`.

`s_col` (`NULL`, `character()`)
: The score or selection variable (only relevant/used for SSM Estimators). Default is `NULL`.

Methods

Public methods:

- `DoubleMLData$new()`
- `DoubleMLData$print()`
- `DoubleMLData$set_data_model()`
- `DoubleMLData$clone()`

Method `new()`**:** Creates a new instance of this R6 class.

Usage:

```
DoubleMLData$new(
  data = NULL,
  x_cols = NULL,
  y_col = NULL,
  d_cols = NULL,
  z_cols = NULL,
  s_col = NULL,
  use_other_treat_as_covariate = TRUE
)
```

Arguments:

`data` (`data.table`, `data.frame()`)
: Data object.

`x_cols` (`NULL`, `character()`)
: The covariates. If `NULL`, all variables (columns of `data`) which are neither specified as outcome variable `y_col`, nor as treatment variables `d_cols`, nor as instrumental variables `z_cols` are used as covariates. Default is `NULL`.

`y_col` (`character(1)`)
: The outcome variable.

`d_cols` (`character()`)
: The treatment variable(s).

`z_cols` (`NULL`, `character()`)
The instrumental variables. Default is `NULL`.

`s_col` (`NULL`, `character()`)
The score or selection variable (only relevant/used for SSM Estimators). Default is `NULL`.

`use_other_treat_as_covariate` (`logical(1)`)
Indicates whether in the multiple-treatment case the other treatment variables should be added as covariates. Default is `TRUE`.

Method `print()`**:** Print DoubleMLData objects.

Usage:

```
DoubleMLData$print()
```

Method `set_data_model()`**:** Setter function for `data_model`. The function implements the causal model as specified by the user via `y_col`, `d_cols`, `x_cols` and `z_cols` and assigns the role for the treatment variables in the multiple-treatment case.

Usage:

```
DoubleMLData$set_data_model(treatment_var)
```

Arguments:

`treatment_var` (`character()`)
Active treatment variable that will be set to `treat_col`.

Method `clone()`**:** The objects of this class are cloneable with this method.

Usage:

```
DoubleMLData$clone(deep = FALSE)
```

Arguments:

`deep` Whether to make a deep clone.

Examples

```
library(DoubleML)
df = make_plr_CCDDHNR2018(return_type = "data.table")
obj_dml_data = DoubleMLData$new(df,
  y_col = "y",
  d_cols = "d")
```

`DoubleMLIIVM` *Double machine learning for interactive IV regression models*

Description

Double machine learning for interactive IV regression models.

Format

R6::R6Class object inheriting from DoubleML.

Details

Interactive IV regression (IIVM) models take the form

$Y = \ell_0(D, X) + \zeta,$

$Z = m_0(X) + V,$

with $E[\zeta|X, Z] = 0$ and $E[V|X] = 0$. Y is the outcome variable, $D \in \{0, 1\}$ is the binary treatment variable and $Z \in \{0, 1\}$ is a binary instrumental variable. Consider the functions g_0, r_0 and m_0, where g_0 maps the support of (Z, X) to R and r_0 and m_0, respectively, map the support of (Z, X) and X to $(\epsilon, 1 - \epsilon)$ for some $\epsilon \in (1, 1/2)$, such that

$Y = g_0(Z, X) + \nu,$

$D = r_0(Z, X) + U,$

$Z = m_0(X) + V,$

with $E[\nu|Z, X] = 0$, $E[U|Z, X] = 0$ and $E[V|X] = 0$. The target parameter of interest in this model is the local average treatment effect (LATE),

$\theta_0 = \frac{E[g_0(1,X)] - E[g_0(0,X)]}{E[r_0(1,X)] - E[r_0(0,X)]}.$

Super class

`DoubleML::DoubleML` -> `DoubleMLIIVM`

Active bindings

`subgroups` (named `list(2)`)
: Named `list(2)` with options to adapt to cases with and without the subgroups of always-takers and never-takes. The entry `always_takers(logical(1))` speficies whether there are always takers in the sample. The entry `never_takers` (`logical(1)`) speficies whether there are never takers in the sample.

`trimming_rule (character(1))`
: A `character(1)` specifying the trimming approach.

`trimming_threshold (numeric(1))`
: The threshold used for timming.

Methods

Public methods:

- `DoubleMLIIVM$new()`
- `DoubleMLIIVM$clone()`

Method `new()`**:** Creates a new instance of this R6 class.

Usage:

```
DoubleMLIIVM$new(
  data,
  ml_g,
  ml_m,
  ml_r,
```

```
  n_folds = 5,
  n_rep = 1,
  score = "LATE",
  subgroups = list(always_takers = TRUE, never_takers = TRUE),
  dml_procedure = "dml2",
  trimming_rule = "truncate",
  trimming_threshold = 1e-12,
  draw_sample_splitting = TRUE,
  apply_cross_fitting = TRUE
)
```

Arguments:

`data` (`DoubleMLData`)
: The `DoubleMLData` object providing the data and specifying the variables of the causal model.

`ml_g` (`LearnerRegr`, `LearnerClassif`, `Learner`, `character(1)`)
: A learner of the class `LearnerRegr`, which is available from mlr3 or its extension packages mlr3learners or mlr3extralearners. For binary treatment outcomes, an object of the class `LearnerClassif` can be passed, for example `lrn("classif.cv_glmnet", s = "lambda.min")`. Alternatively, a `Learner` object with public field `task_type = "regr"` or `task_type = "classif"` can be passed, respectively, for example of class `GraphLearner`.
`ml_g` refers to the nuisance function $g_0(Z, X) = E[Y|X, Z]$.

`ml_m` (`LearnerClassif`, `Learner`, `character(1)`)
: A learner of the class `LearnerClassif`, which is available from mlr3 or its extension packages mlr3learners or mlr3extralearners. Alternatively, a `Learner` object with public field `task_type = "classif"` can be passed, for example of class `GraphLearner`. The learner can possibly be passed with specified parameters, for example `lrn("classif.cv_glmnet", s = "lambda.min")`.
`ml_m` refers to the nuisance function $m_0(X) = E[Z|X]$.

`ml_r` (`LearnerClassif`, `Learner`, `character(1)`)
: A learner of the class `LearnerClassif`, which is available from mlr3 or its extension packages mlr3learners or mlr3extralearners. Alternatively, a `Learner` object with public field `task_type = "classif"` can be passed, for example of class `GraphLearner`. The learner can possibly be passed with specified parameters, for example `lrn("classif.cv_glmnet", s = "lambda.min")`.
`ml_r` refers to the nuisance function $r_0(Z, X) = E[D|X, Z]$.

`n_folds` (`integer(1)`)
: Number of folds. Default is `5`.

`n_rep` (`integer(1)`)
: Number of repetitions for the sample splitting. Default is `1`.

`score` (`character(1)`, `function()`)
: A `character(1)` (`"LATE"` is the only choice) specifying the score function. If a `function()` is provided, it must be of the form `function(y, z, d, g0_hat, g1_hat, m_hat, r0_hat, r1_hat, smpls)` and the returned output must be a named `list()` with elements `psi_a` and `psi_b`. Default is `"LATE"`.

`subgroups` (named `list(2)`)
: Named `list(2)` with options to adapt to cases with and without the subgroups of always-takers and never-takes. The entry `always_takers(logical(1))` speficies whether there are

always takers in the sample. The entry `never_takers` (`logical(1)`) speficies whether there are never takers in the sample. Default is `list(always_takers = TRUE, never_takers = TRUE)`.

`dml_procedure` (`character(1)`)
: A `character(1)` (`"dml1"` or `"dml2"`) specifying the double machine learning algorithm. Default is `"dml2"`.

`trimming_rule` (`character(1)`)
: A `character(1)` (`"truncate"` is the only choice) specifying the trimming approach. Default is `"truncate"`.

`trimming_threshold` (`numeric(1)`)
: The threshold used for timming. Default is `1e-12`.

`draw_sample_splitting` (`logical(1)`)
: Indicates whether the sample splitting should be drawn during initialization of the object. Default is `TRUE`.

`apply_cross_fitting` (`logical(1)`)
: Indicates whether cross-fitting should be applied. Default is `TRUE`.

Method `clone()`**:** The objects of this class are cloneable with this method.

Usage:

```
DoubleMLIIVM$clone(deep = FALSE)
```

Arguments:

`deep` Whether to make a deep clone.

See Also

Other DoubleML: `DoubleML`, `DoubleMLIRM`, `DoubleMLPLIV`, `DoubleMLPLR`, `DoubleMLSSM`

Examples

```
library(DoubleML)
library(mlr3)
library(mlr3learners)
library(data.table)
set.seed(2)
ml_g = lrn("regr.ranger",
  num.trees = 100, mtry = 20,
  min.node.size = 2, max.depth = 5)
ml_m = lrn("classif.ranger",
  num.trees = 100, mtry = 20,
  min.node.size = 2, max.depth = 5)
ml_r = ml_m$clone()
obj_dml_data = make_iivm_data(
  theta = 0.5, n_obs = 1000,
  alpha_x = 1, dim_x = 20)
dml_iivm_obj = DoubleMLIIVM$new(obj_dml_data, ml_g, ml_m, ml_r)
dml_iivm_obj$fit()
dml_iivm_obj$summary()
```

```
## Not run:
library(DoubleML)
library(mlr3)
library(mlr3learners)
library(mlr3tuning)
library(data.table)
set.seed(2)
ml_g = lrn("regr.rpart")
ml_m = lrn("classif.rpart")
ml_r = ml_m$clone()
obj_dml_data = make_iivm_data(
  theta = 0.5, n_obs = 1000,
  alpha_x = 1, dim_x = 20)
dml_iivm_obj = DoubleMLIIVM$new(obj_dml_data, ml_g, ml_m, ml_r)
param_grid = list(
  "ml_g" = paradox::ps(
    cp = paradox::p_dbl(lower = 0.01, upper = 0.02),
    minsplit = paradox::p_int(lower = 1, upper = 2)),
  "ml_m" = paradox::ps(
    cp = paradox::p_dbl(lower = 0.01, upper = 0.02),
    minsplit = paradox::p_int(lower = 1, upper = 2)),
  "ml_r" = paradox::ps(
    cp = paradox::p_dbl(lower = 0.01, upper = 0.02),
    minsplit = paradox::p_int(lower = 1, upper = 2)))
# minimum requirements for tune_settings
tune_settings = list(
  terminator = mlr3tuning::trm("evals", n_evals = 5),
  algorithm = mlr3tuning::tnr("grid_search", resolution = 5))
dml_iivm_obj$tune(param_set = param_grid, tune_settings = tune_settings)
dml_iivm_obj$fit()
dml_iivm_obj$summary()

## End(Not run)
```

DoubleMLIRM *Double machine learning for interactive regression models*

Description

Double machine learning for interactive regression models.

Format

R6::R6Class object inheriting from DoubleML.

Details

Interactive regression (IRM) models take the form

$Y = g_0(D, X) + U,$

$D = m_0(X) + V$,

with $E[U|X, D] = 0$ and $E[V|X] = 0$. Y is the outcome variable and $D \in \{0, 1\}$ is the binary treatment variable. We consider estimation of the average treamtent effects when treatment effects are fully heterogeneous. Target parameters of interest in this model are the average treatment effect (ATE),

$\theta_0 = E[g_0(1, X) - g_0(0, X)]$

and the average treament effect on the treated (ATTE),

$\theta_0 = E[g_0(1, X) - g_0(0, X)|D = 1]$.

Super class

`DoubleML::DoubleML` -> `DoubleMLIRM`

Active bindings

`trimming_rule (character(1))`
: A `character(1)` specifying the trimming approach.

`trimming_threshold (numeric(1))`
: The threshold used for timming.

Methods

Public methods:

- `DoubleMLIRM$new()`
- `DoubleMLIRM$clone()`

Method `new()`**:** Creates a new instance of this R6 class.

Usage:

```
DoubleMLIRM$new(
  data,
  ml_g,
  ml_m,
  n_folds = 5,
  n_rep = 1,
  score = "ATE",
  trimming_rule = "truncate",
  trimming_threshold = 1e-12,
  dml_procedure = "dml2",
  draw_sample_splitting = TRUE,
  apply_cross_fitting = TRUE
)
```

Arguments:

`data (DoubleMLData)`
: The `DoubleMLData` object providing the data and specifying the variables of the causal model.

`ml_g` (`LearnerRegr`, `LearnerClassif`, `Learner`, `character(1)`)
A learner of the class `LearnerRegr`, which is available from mlr3 or its extension packages mlr3learners or mlr3extralearners. For binary treatment outcomes, an object of the class `LearnerClassif` can be passed, for example `lrn("classif.cv_glmnet", s = "lambda.min")`. Alternatively, a `Learner` object with public field `task_type = "regr"` or `task_type = "classif"` can be passed, respectively, for example of class `GraphLearner`.
`ml_g` refers to the nuisance function $g_0(X) = E[Y|X, D]$.

`ml_m` (`LearnerClassif`, `Learner`, `character(1)`)
A learner of the class `LearnerClassif`, which is available from mlr3 or its extension packages mlr3learners or mlr3extralearners. Alternatively, a `Learner` object with public field `task_type = "classif"` can be passed, for example of class `GraphLearner`. The learner can possibly be passed with specified parameters, for example `lrn("classif.cv_glmnet", s = "lambda.min")`.
`ml_m` refers to the nuisance function $m_0(X) = E[D|X]$.

`n_folds (integer(1))`
Number of folds. Default is `5`.

`n_rep (integer(1))`
Number of repetitions for the sample splitting. Default is `1`.

`score (character(1), function())`
A `character(1)` (`"ATE"` or `ATTE`) or a `function()` specifying the score function. If a `function()` is provided, it must be of the form `function(y, d, g0_hat, g1_hat, m_hat, smpls)` and the returned output must be a named `list()` with elements `psi_a` and `psi_b`. Default is `"ATE"`.

`trimming_rule (character(1))`
A `character(1)` (`"truncate"` is the only choice) specifying the trimming approach. Default is `"truncate"`.

`trimming_threshold (numeric(1))`
The threshold used for timming. Default is `1e-12`.

`dml_procedure (character(1))`
A `character(1)` (`"dml1"` or `"dml2"`) specifying the double machine learning algorithm. Default is `"dml2"`.

`draw_sample_splitting (logical(1))`
Indicates whether the sample splitting should be drawn during initialization of the object. Default is `TRUE`.

`apply_cross_fitting (logical(1))`
Indicates whether cross-fitting should be applied. Default is `TRUE`.

Method `clone()`**:** The objects of this class are cloneable with this method.

Usage:

```
DoubleMLIRM$clone(deep = FALSE)
```

Arguments:

`deep` Whether to make a deep clone.

See Also

Other DoubleML: `DoubleML`, `DoubleMLIIVM`, `DoubleMLPLIV`, `DoubleMLPLR`, `DoubleMLSSM`

Examples

```
library(DoubleML)
library(mlr3)
library(mlr3learners)
library(data.table)
set.seed(2)
ml_g = lrn("regr.ranger",
  num.trees = 100, mtry = 20,
  min.node.size = 2, max.depth = 5)
ml_m = lrn("classif.ranger",
  num.trees = 100, mtry = 20,
  min.node.size = 2, max.depth = 5)
obj_dml_data = make_irm_data(theta = 0.5)
dml_irm_obj = DoubleMLIRM$new(obj_dml_data, ml_g, ml_m)
dml_irm_obj$fit()
dml_irm_obj$summary()

## Not run:
library(DoubleML)
library(mlr3)
library(mlr3learners)
library(mlr3tuning)
library(data.table)
set.seed(2)
ml_g = lrn("regr.rpart")
ml_m = lrn("classif.rpart")
obj_dml_data = make_irm_data(theta = 0.5)
dml_irm_obj = DoubleMLIRM$new(obj_dml_data, ml_g, ml_m)

param_grid = list(
  "ml_g" = paradox::ps(
    cp = paradox::p_dbl(lower = 0.01, upper = 0.02),
    minsplit = paradox::p_int(lower = 1, upper = 2)),
  "ml_m" = paradox::ps(
    cp = paradox::p_dbl(lower = 0.01, upper = 0.02),
    minsplit = paradox::p_int(lower = 1, upper = 2)))

# minimum requirements for tune_settings
tune_settings = list(
  terminator = mlr3tuning::trm("evals", n_evals = 5),
  algorithm = mlr3tuning::tnr("grid_search", resolution = 5))
dml_irm_obj$tune(param_set = param_grid, tune_settings = tune_settings)
dml_irm_obj$fit()
dml_irm_obj$summary()

## End(Not run)
```

DoubleMLPLIV *Double machine learning for partially linear IV regression models*

Description

Double machine learning for partially linear IV regression models.

Format

R6::R6Class object inheriting from DoubleML.

Details

Partially linear IV regression (PLIV) models take the form

$Y - D\theta_0 = g_0(X) + \zeta,$

$Z = m_0(X) + V,$

with $E[\zeta|Z, X] = 0$ and $E[V|X] = 0$. Y is the outcome variable variable, D is the policy variable of interest and Z denotes one or multiple instrumental variables. The high-dimensional vector $X = (X_1, \ldots, X_p)$ consists of other confounding covariates, and ζ and V are stochastic errors.

Super class

`DoubleML::DoubleML` -> `DoubleMLPLIV`

Active bindings

`partialX (logical(1))`
: Indicates whether covariates X should be partialled out.

`partialZ (logical(1))`
: Indicates whether instruments Z should be partialled out.

Methods

Public methods:

- `DoubleMLPLIV$new()`
- `DoubleMLPLIV$set_ml_nuisance_params()`
- `DoubleMLPLIV$tune()`
- `DoubleMLPLIV$clone()`

Method `new()`**:** Creates a new instance of this R6 class.

Usage:

```
DoubleMLPLIV$new(
  data,
  ml_l,
  ml_m,
  ml_r,
  ml_g = NULL,
  partialX = TRUE,
  partialZ = FALSE,
  n_folds = 5,
  n_rep = 1,
```

```
  score = "partialling out",
  dml_procedure = "dml2",
  draw_sample_splitting = TRUE,
  apply_cross_fitting = TRUE
)
```

Arguments:

`data` (`DoubleMLData`)
: The `DoubleMLData` object providing the data and specifying the variables of the causal model.

`ml_l` (`LearnerRegr`, `Learner`, `character(1)`)
: A learner of the class `LearnerRegr`, which is available from mlr3 or its extension packages mlr3learners or mlr3extralearners. Alternatively, a `Learner` object with public field `task_type = "regr"` can be passed, for example of class `GraphLearner`. The learner can possibly be passed with specified parameters, for example `lrn("regr.cv_glmnet", s = "lambda.min")`.
`ml_l` refers to the nuisance function $l_0(X) = E[Y|X]$.

`ml_m` (`LearnerRegr`, `Learner`, `character(1)`)
: A learner of the class `LearnerRegr`, which is available from mlr3 or its extension packages mlr3learners or mlr3extralearners. Alternatively, a `Learner` object with public field `task_type = "regr"` can be passed, for example of class `GraphLearner`. The learner can possibly be passed with specified parameters, for example `lrn("regr.cv_glmnet", s = "lambda.min")`.
`ml_m` refers to the nuisance function $m_0(X) = E[Z|X]$.

`ml_r` (`LearnerRegr`, `Learner`, `character(1)`)
: A learner of the class `LearnerRegr`, which is available from mlr3 or its extension packages mlr3learners or mlr3extralearners. Alternatively, a `Learner` object with public field `task_type = "regr"` can be passed, for example of class `GraphLearner`. The learner can possibly be passed with specified parameters, for example `lrn("regr.cv_glmnet", s = "lambda.min")`.
`ml_r` refers to the nuisance function $r_0(X) = E[D|X]$.

`ml_g` (`LearnerRegr`, `Learner`, `character(1)`)
: A learner of the class `LearnerRegr`, which is available from mlr3 or its extension packages mlr3learners or mlr3extralearners. Alternatively, a `Learner` object with public field `task_type = "regr"` can be passed, for example of class `GraphLearner`. The learner can possibly be passed with specified parameters, for example `lrn("regr.cv_glmnet", s = "lambda.min")`.
`ml_g` refers to the nuisance function $g_0(X) = E[Y - D\theta_0|X]$. Note: The learner `ml_g` is only required for the score `'IV-type'`. Optionally, it can be specified and estimated for callable scores.

`partialX` (`logical(1)`)
: Indicates whether covariates X should be partialled out. Default is `TRUE`.

`partialZ` (`logical(1)`)
: Indicates whether instruments Z should be partialled out. Default is `FALSE`.

`n_folds` (`integer(1)`)
: Number of folds. Default is `5`.

`n_rep` (`integer(1)`)
: Number of repetitions for the sample splitting. Default is `1`.

score (character(1), function())
: A character(1) ("partialling out" or "IV-type") or a function() specifying the score function. If a function() is provided, it must be of the form function(y, z, d, l_hat, m_hat, r_hat, g_ha and the returned output must be a named list() with elements psi_a and psi_b. Default is "partialling out".

dml_procedure (character(1))
: A character(1) ("dml1" or "dml2") specifying the double machine learning algorithm. Default is "dml2".

draw_sample_splitting (logical(1))
: Indicates whether the sample splitting should be drawn during initialization of the object. Default is TRUE.

apply_cross_fitting (logical(1))
: Indicates whether cross-fitting should be applied. Default is TRUE.

Method set_ml_nuisance_params(): Set hyperparameters for the nuisance models of DoubleML models.

Note that in the current implementation, either all parameters have to be set globally or all parameters have to be provided fold-specific.

Usage:

```
DoubleMLPLIV$set_ml_nuisance_params(
  learner = NULL,
  treat_var = NULL,
  params,
  set_fold_specific = FALSE
)
```

Arguments:

learner (character(1))
: The nuisance model/learner (see method params_names).

treat_var (character(1))
: The treatment varaible (hyperparameters can be set treatment-variable specific).

params (named list())
: A named list() with estimator parameters. Parameters are used for all folds by default. Alternatively, parameters can be passed in a fold-specific way if option fold_specificis TRUE. In this case, the outer list needs to be of length n_rep and the inner list of length n_folds.

set_fold_specific (logical(1))
: Indicates if the parameters passed in params should be passed in fold-specific way. Default is FALSE. If TRUE, the outer list needs to be of length n_rep and the inner list of length n_folds. Note that in the current implementation, either all parameters have to be set globally or all parameters have to be provided fold-specific.

Returns: self

Method tune(): Hyperparameter-tuning for DoubleML models.

The hyperparameter-tuning is performed using the tuning methods provided in the mlr3tuning package. For more information on tuning in mlr3, we refer to the section on parameter tuning in the mlr3 book.

Usage:

```
DoubleMLPLIV$tune(
  param_set,
  tune_settings = list(n_folds_tune = 5, rsmp_tune = mlr3::rsmp("cv", folds = 5), measure
    = NULL, terminator = mlr3tuning::trm("evals", n_evals = 20), algorithm =
    mlr3tuning::tnr("grid_search"), resolution = 5),
  tune_on_folds = FALSE
)
```

Arguments:

`param_set` (named `list()`)
: A named `list` with a parameter grid for each nuisance model/learner (see method `learner_names()`). The parameter grid must be an object of class ParamSet.

`tune_settings` (named `list()`)
: A named `list()` with arguments passed to the hyperparameter-tuning with mlr3tuning to set up TuningInstance objects. `tune_settings` has entries

- `terminator` (Terminator)
  A Terminator object. Specification of `terminator` is required to perform tuning.
- `algorithm` (Tuner or `character(1)`)
  A Tuner object (recommended) or key passed to the respective dictionary to specify the tuning algorithm used in tnr(). `algorithm` is passed as an argument to tnr(). If `algorithm` is not specified by the users, default is set to `"grid_search"`. If set to `"grid_search"`, then additional argument `"resolution"` is required.
- `rsmp_tune` (Resampling or `character(1)`)
  A Resampling object (recommended) or option passed to rsmp() to initialize a Resampling for parameter tuning in `mlr3`. If not specified by the user, default is set to `"cv"` (cross-validation).
- `n_folds_tune` (`integer(1)`, optional)
  If `rsmp_tune = "cv"`, number of folds used for cross-validation. If not specified by the user, default is set to `5`.
- `measure` (`NULL`, named `list()`, optional)
  Named list containing the measures used for parameter tuning. Entries in list must either be Measure objects or keys to be passed to passed to msr(). The names of the entries must match the learner names (see method `learner_names()`). If set to `NULL`, default measures are used, i.e., `"regr.mse"` for continuous outcome variables and `"classif.ce"` for binary outcomes.
- `resolution` (`character(1)`)
  The key passed to the respective dictionary to specify the tuning algorithm used in tnr(). `resolution` is passed as an argument to tnr().

`tune_on_folds` (`logical(1)`)
: Indicates whether the tuning should be done fold-specific or globally. Default is `FALSE`.

Returns: self

Method `clone()`**:** The objects of this class are cloneable with this method.

Usage:

```
DoubleMLPLIV$clone(deep = FALSE)
```

Arguments:

`deep` Whether to make a deep clone.

See Also

Other DoubleML: DoubleML, DoubleMLIIVM, DoubleMLIRM, DoubleMLPLR, DoubleMLSSM

Examples

```
library(DoubleML)
library(mlr3)
library(mlr3learners)
library(data.table)
set.seed(2)
ml_l = lrn("regr.ranger", num.trees = 100, mtry = 20, min.node.size = 2, max.depth = 5)
ml_m = ml_l$clone()
ml_r = ml_l$clone()
obj_dml_data = make_pliv_CHS2015(alpha = 1, n_obs = 500, dim_x = 20, dim_z = 1)
dml_pliv_obj = DoubleMLPLIV$new(obj_dml_data, ml_l, ml_m, ml_r)
dml_pliv_obj$fit()
dml_pliv_obj$summary()


## Not run:
library(DoubleML)
library(mlr3)
library(mlr3learners)
library(mlr3tuning)
library(data.table)
set.seed(2)
ml_l = lrn("regr.rpart")
ml_m = ml_l$clone()
ml_r = ml_l$clone()
obj_dml_data = make_pliv_CHS2015(
  alpha = 1, n_obs = 500, dim_x = 20,
  dim_z = 1)
dml_pliv_obj = DoubleMLPLIV$new(obj_dml_data, ml_l, ml_m, ml_r)
param_grid = list(
  "ml_l" = paradox::ps(
    cp = paradox::p_dbl(lower = 0.01, upper = 0.02),
    minsplit = paradox::p_int(lower = 1, upper = 2)),
  "ml_m" = paradox::ps(
    cp = paradox::p_dbl(lower = 0.01, upper = 0.02),
    minsplit = paradox::p_int(lower = 1, upper = 2)),
  "ml_r" = paradox::ps(
    cp = paradox::p_dbl(lower = 0.01, upper = 0.02),
    minsplit = paradox::p_int(lower = 1, upper = 2)))

# minimum requirements for tune_settings
tune_settings = list(
  terminator = mlr3tuning::trm("evals", n_evals = 5),
  algorithm = mlr3tuning::tnr("grid_search", resolution = 5))
dml_pliv_obj$tune(param_set = param_grid, tune_settings = tune_settings)
dml_pliv_obj$fit()
dml_pliv_obj$summary()
```

```
## End(Not run)
```

DoubleMLPLR *Double machine learning for partially linear regression models*

Description

Double machine learning for partially linear regression models.

Format

R6::R6Class object inheriting from DoubleML.

Details

Partially linear regression (PLR) models take the form

$Y = D\theta_0 + g_0(X) + \zeta$,

$D = m_0(X) + V$,

with $E[\zeta|D, X] = 0$ and $E[V|X] = 0$. Y is the outcome variable variable and D is the policy variable of interest. The high-dimensional vector $X = (X_1, \ldots, X_p)$ consists of other confounding covariates, and ζ and V are stochastic errors.

Super class

DoubleML::DoubleML -> DoubleMLPLR

Methods

Public methods:

- DoubleMLPLR$new()
- DoubleMLPLR$set_ml_nuisance_params()
- DoubleMLPLR$tune()
- DoubleMLPLR$clone()

Method new(): Creates a new instance of this R6 class.

Usage:

```
DoubleMLPLR$new(
  data,
  ml_l,
  ml_m,
  ml_g = NULL,
  n_folds = 5,
  n_rep = 1,
  score = "partialling out",
  dml_procedure = "dml2",
  draw_sample_splitting = TRUE,
```

```
  apply_cross_fitting = TRUE
)
```

Arguments:

`data` (`DoubleMLData`)
: The `DoubleMLData` object providing the data and specifying the variables of the causal model.

`ml_l` (`LearnerRegr`, `Learner`, `character(1)`)
: A learner of the class `LearnerRegr`, which is available from mlr3 or its extension packages mlr3learners or mlr3extralearners. Alternatively, a `Learner` object with public field `task_type = "regr"` can be passed, for example of class `GraphLearner`. The learner can possibly be passed with specified parameters, for example `lrn("regr.cv_glmnet", s = "lambda.min")`.
`ml_l` refers to the nuisance function $l_0(X) = E[Y|X]$.

`ml_m` (`LearnerRegr`, `LearnerClassif`, `Learner`, `character(1)`)
: A learner of the class `LearnerRegr`, which is available from mlr3 or its extension packages mlr3learners or mlr3extralearners. For binary treatment variables, an object of the class `LearnerClassif` can be passed, for example `lrn("classif.cv_glmnet", s = "lambda.min")`. Alternatively, a `Learner` object with public field `task_type = "regr"` or `task_type = "classif"` can be passed, respectively, for example of class `GraphLearner`.
`ml_m` refers to the nuisance function $m_0(X) = E[D|X]$.

`ml_g` (`LearnerRegr`, `Learner`, `character(1)`)
: A learner of the class `LearnerRegr`, which is available from mlr3 or its extension packages mlr3learners or mlr3extralearners. Alternatively, a `Learner` object with public field `task_type = "regr"` can be passed, for example of class `GraphLearner`. The learner can possibly be passed with specified parameters, for example `lrn("regr.cv_glmnet", s = "lambda.min")`.
`ml_g` refers to the nuisance function $g_0(X) = E[Y - D\theta_0|X]$. Note: The learner `ml_g` is only required for the score `'IV-type'`. Optionally, it can be specified and estimated for callable scores.

`n_folds` (`integer(1)`)
: Number of folds. Default is `5`.

`n_rep` (`integer(1)`)
: Number of repetitions for the sample splitting. Default is `1`.

`score` (`character(1)`, `function()`)
: A `character(1)` (`"partialling out"` or `"IV-type"`) or a `function()` specifying the score function. If a `function()` is provided, it must be of the form `function(y, d, l_hat, m_hat, g_hat, smpls)` and the returned output must be a named `list()` with elements `psi_a` and `psi_b`. Default is `"partialling out"`.

`dml_procedure` (`character(1)`)
: A `character(1)` (`"dml1"` or `"dml2"`) specifying the double machine learning algorithm. Default is `"dml2"`.

`draw_sample_splitting` (`logical(1)`)
: Indicates whether the sample splitting should be drawn during initialization of the object. Default is `TRUE`.

`apply_cross_fitting` (`logical(1)`)
: Indicates whether cross-fitting should be applied. Default is `TRUE`.

Method `set_ml_nuisance_params()`**:** Set hyperparameters for the nuisance models of DoubleML models.

Note that in the current implementation, either all parameters have to be set globally or all parameters have to be provided fold-specific.

Usage:

```
DoubleMLPLR$set_ml_nuisance_params(
  learner = NULL,
  treat_var = NULL,
  params,
  set_fold_specific = FALSE
)
```

Arguments:

`learner` (`character(1)`)
: The nuisance model/learner (see method `params_names`).

`treat_var` (`character(1)`)
: The treatment varaible (hyperparameters can be set treatment-variable specific).

`params` (named `list()`)
: A named `list()` with estimator parameters. Parameters are used for all folds by default. Alternatively, parameters can be passed in a fold-specific way if option `fold_specificis` `TRUE`. In this case, the outer list needs to be of length `n_rep` and the inner list of length `n_folds`.

`set_fold_specific` (`logical(1)`)
: Indicates if the parameters passed in `params` should be passed in fold-specific way. Default is `FALSE`. If `TRUE`, the outer list needs to be of length `n_rep` and the inner list of length `n_folds`. Note that in the current implementation, either all parameters have to be set globally or all parameters have to be provided fold-specific.

Returns: self

Method `tune()`**:** Hyperparameter-tuning for DoubleML models.

The hyperparameter-tuning is performed using the tuning methods provided in the mlr3tuning package. For more information on tuning in mlr3, we refer to the section on parameter tuning in the mlr3 book.

Usage:

```
DoubleMLPLR$tune(
  param_set,
 tune_settings = list(n_folds_tune = 5, rsmp_tune = mlr3::rsmp("cv", folds = 5), measure
    = NULL, terminator = mlr3tuning::trm("evals", n_evals = 20), algorithm =
    mlr3tuning::tnr("grid_search"), resolution = 5),
  tune_on_folds = FALSE
)
```

Arguments:

`param_set` (named `list()`)
: A named `list` with a parameter grid for each nuisance model/learner (see method `learner_names()`). The parameter grid must be an object of class ParamSet.

`tune_settings` (named `list()`)
A named `list()` with arguments passed to the hyperparameter-tuning with mlr3tuning to set up TuningInstance objects. `tune_settings` has entries

- `terminator` (Terminator)
  A Terminator object. Specification of `terminator` is required to perform tuning.
- `algorithm` (Tuner or `character(1)`)
  A Tuner object (recommended) or key passed to the respective dictionary to specify the tuning algorithm used in tnr(). `algorithm` is passed as an argument to tnr(). If `algorithm` is not specified by the users, default is set to `"grid_search"`. If set to `"grid_search"`, then additional argument `"resolution"` is required.
- `rsmp_tune` (Resampling or `character(1)`)
  A Resampling object (recommended) or option passed to rsmp() to initialize a Resampling for parameter tuning in `mlr3`. If not specified by the user, default is set to `"cv"` (cross-validation).
- `n_folds_tune` (`integer(1)`, optional)
  If `rsmp_tune = "cv"`, number of folds used for cross-validation. If not specified by the user, default is set to `5`.
- `measure` (`NULL`, named `list()`, optional)
  Named list containing the measures used for parameter tuning. Entries in list must either be Measure objects or keys to be passed to passed to msr(). The names of the entries must match the learner names (see method `learner_names()`). If set to `NULL`, default measures are used, i.e., `"regr.mse"` for continuous outcome variables and `"classif.ce"` for binary outcomes.
- `resolution` (`character(1)`)
  The key passed to the respective dictionary to specify the tuning algorithm used in tnr(). `resolution` is passed as an argument to tnr().

`tune_on_folds` (`logical(1)`)
Indicates whether the tuning should be done fold-specific or globally. Default is `FALSE`.

Returns: self

Method `clone()`**:** The objects of this class are cloneable with this method.

Usage:

```
DoubleMLPLR$clone(deep = FALSE)
```

Arguments:

`deep` Whether to make a deep clone.

See Also

Other DoubleML: `DoubleML`, `DoubleMLIIVM`, `DoubleMLIRM`, `DoubleMLPLIV`, `DoubleMLSSM`

Examples

```
library(DoubleML)
library(mlr3)
library(mlr3learners)
library(data.table)
set.seed(2)
```

```
ml_g = lrn("regr.ranger", num.trees = 10, max.depth = 2)
ml_m = ml_g$clone()
obj_dml_data = make_plr_CCDDHNR2018(alpha = 0.5)
dml_plr_obj = DoubleMLPLR$new(obj_dml_data, ml_g, ml_m)
dml_plr_obj$fit()
dml_plr_obj$summary()


## Not run:
library(DoubleML)
library(mlr3)
library(mlr3learners)
library(mlr3tuning)
library(data.table)
set.seed(2)
ml_l = lrn("regr.rpart")
ml_m = ml_l$clone()
obj_dml_data = make_plr_CCDDHNR2018(alpha = 0.5)
dml_plr_obj = DoubleMLPLR$new(obj_dml_data, ml_l, ml_m)

param_grid = list(
  "ml_l" = paradox::ps(
    cp = paradox::p_dbl(lower = 0.01, upper = 0.02),
    minsplit = paradox::p_int(lower = 1, upper = 2)),
  "ml_m" = paradox::ps(
    cp = paradox::p_dbl(lower = 0.01, upper = 0.02),
    minsplit = paradox::p_int(lower = 1, upper = 2)))

# minimum requirements for tune_settings
tune_settings = list(
  terminator = mlr3tuning::trm("evals", n_evals = 5),
  algorithm = mlr3tuning::tnr("grid_search", resolution = 5))
dml_plr_obj$tune(param_set = param_grid, tune_settings = tune_settings)
dml_plr_obj$fit()
dml_plr_obj$summary()

## End(Not run)
```

DoubleMLSSM *Double machine learning for sample selection models*

Description

Double machine learning for sample selection models.

Format

R6::R6Class object inheriting from DoubleML.

Super class

DoubleML::DoubleML -> DoubleMLSSM

Active bindings

trimming_rule (character(1))
: A character(1) specifying the trimming approach.

trimming_threshold (numeric(1))
: The threshold used for timming.

Methods

Public methods:

- DoubleMLSSM$new()
- DoubleMLSSM$set_ml_nuisance_params()
- DoubleMLSSM$tune()
- DoubleMLSSM$clone()

Method new(): Creates a new instance of this R6 class.

Usage:

```
DoubleMLSSM$new(
  data,
  ml_g,
  ml_pi,
  ml_m,
  n_folds = 5,
  n_rep = 1,
  score = "missing-at-random",
  normalize_ipw = FALSE,
  trimming_rule = "truncate",
  trimming_threshold = 1e-12,
  dml_procedure = "dml2",
  draw_sample_splitting = TRUE,
  apply_cross_fitting = TRUE
)
```

Arguments:

data (DoubleMLData)
: The DoubleMLData object providing the data and specifying the variables of the causal model.

ml_g (LearnerRegr, Learner, character(1))
: A learner of the class LearnerRegr, which is available from mlr3 or its extension packages mlr3learners or mlr3extralearners. Alternatively, a Learner object with public field task_type = "regr" can be passed, for example of class GraphLearner. The learner can possibly be passed with specified parameters, for example lrn("regr.cv_glmnet", s = "lambda.min").
ml_g refers to the nuisance function $g_0(S, D, X) = E[Y|S, D, X]$.

`ml_pi` (`LearnerClassif`, `Learner`, `character(1)`)
: A learner of the class `LearnerClassif`, which is available from mlr3 or its extension packages mlr3learners or mlr3extralearners. Alternatively, a `Learner` object with public field `task_type = "classif"` can be passed, for example of class `GraphLearner`. The learner can possibly be passed with specified parameters, for example `lrn("classif.cv_glmnet", s = "lambda.min")`.
`ml_pi` refers to the nuisance function $pi_0(D, X) = Pr[S = 1|D, X]$.

`ml_m` (`LearnerRegr`, `LearnerClassif`, `Learner`, `character(1)`)
: A learner of the class `LearnerClassif`, which is available from mlr3 or its extension packages mlr3learners or mlr3extralearners. Alternatively, a `Learner` object with public field `task_type = "classif"` can be passed, for example of class `GraphLearner`. The learner can possibly be passed with specified parameters, for example `lrn("classif.cv_glmnet", s = "lambda.min")`.
`ml_m` refers to the nuisance function $m_0(X) = Pr[D = 1|X]$.

`n_folds` (`integer(1)`)
: Number of folds. Default is `5`.

`n_rep` (`integer(1)`)
: Number of repetitions for the sample splitting. Default is `1`.

`score` (`character(1)`, `function()`)
: A `character(1)` (`"missing-at-random"` or `"nonignorable"`) specifying the score function. Default is `"missing-at-random"`.

`normalize_ipw` (`logical(1)`)
: Indicates whether the inverse probability weights are normalized. Default is `FALSE`.

`trimming_rule` (`character(1)`)
: A `character(1)` (`"truncate"` is the only choice) specifying the trimming approach. Default is `"truncate"`.

`trimming_threshold` (`numeric(1)`)
: The threshold used for timming. Default is `1e-12`.

`dml_procedure` (`character(1)`)
: A `character(1)` (`"dml1"` or `"dml2"`) specifying the double machine learning algorithm. Default is `"dml2"`.

`draw_sample_splitting` (`logical(1)`)
: Indicates whether the sample splitting should be drawn during initialization of the object. Default is `TRUE`.

`apply_cross_fitting` (`logical(1)`)
: Indicates whether cross-fitting should be applied. Default is `TRUE`.

Method `set_ml_nuisance_params()`**:** Set hyperparameters for the nuisance models of DoubleML models.

Note that in the current implementation, either all parameters have to be set globally or all parameters have to be provided fold-specific.

Usage:

```
DoubleMLSSM$set_ml_nuisance_params(
  learner = NULL,
  treat_var = NULL,
  params,
  set_fold_specific = FALSE
```

```
)
```

Arguments:

`learner` (`character(1)`)
: The nuisance model/learner (see method `params_names`).

`treat_var` (`character(1)`)
: The treatment varaible (hyperparameters can be set treatment-variable specific).

`params` (named `list()`)
: A named `list()` with estimator parameters. Parameters are used for all folds by default. Alternatively, parameters can be passed in a fold-specific way if option `fold_specificis` `TRUE`. In this case, the outer list needs to be of length `n_rep` and the inner list of length `n_folds`.

`set_fold_specific` (`logical(1)`)
: Indicates if the parameters passed in `params` should be passed in fold-specific way. Default is `FALSE`. If `TRUE`, the outer list needs to be of length `n_rep` and the inner list of length `n_folds`. Note that in the current implementation, either all parameters have to be set globally or all parameters have to be provided fold-specific.

Returns: self

Method `tune()`**:** Hyperparameter-tuning for DoubleML models.

The hyperparameter-tuning is performed using the tuning methods provided in the mlr3tuning package. For more information on tuning in mlr3, we refer to the section on parameter tuning in the mlr3 book.

Usage:

```
DoubleMLSSM$tune(
  param_set,
  tune_settings = list(n_folds_tune = 5, rsmp_tune = mlr3::rsmp("cv", folds = 5), measure
    = NULL, terminator = mlr3tuning::trm("evals", n_evals = 20), algorithm =
    mlr3tuning::tnr("grid_search"), resolution = 5),
  tune_on_folds = FALSE
)
```

Arguments:

`param_set` (named `list()`)
: A named `list` with a parameter grid for each nuisance model/learner (see method `learner_names()`). The parameter grid must be an object of class ParamSet.

`tune_settings` (named `list()`)
: A named `list()` with arguments passed to the hyperparameter-tuning with mlr3tuning to set up TuningInstance objects. `tune_settings` has entries

- `terminator` (Terminator)
  A Terminator object. Specification of `terminator` is required to perform tuning.
- `algorithm` (Tuner or `character(1)`)
  A Tuner object (recommended) or key passed to the respective dictionary to specify the tuning algorithm used in tnr(). `algorithm` is passed as an argument to tnr(). If `algorithm` is not specified by the users, default is set to `"grid_search"`. If set to `"grid_search"`, then additional argument `"resolution"` is required.

- `rsmp_tune` (Resampling or `character(1)`)
  A Resampling object (recommended) or option passed to rsmp() to initialize a Resampling for parameter tuning in `mlr3`. If not specified by the user, default is set to `"cv"` (cross-validation).
- `n_folds_tune` (`integer(1)`, optional)
  If `rsmp_tune = "cv"`, number of folds used for cross-validation. If not specified by the user, default is set to `5`.
- `measure` (`NULL`, named `list()`, optional)
  Named list containing the measures used for parameter tuning. Entries in list must either be Measure objects or keys to be passed to passed to msr(). The names of the entries must match the learner names (see method `learner_names()`). If set to `NULL`, default measures are used, i.e., `"regr.mse"` for continuous outcome variables and `"classif.ce"` for binary outcomes.
- `resolution` (`character(1)`)
  The key passed to the respective dictionary to specify the tuning algorithm used in tnr(). `resolution` is passed as an argument to tnr().

`tune_on_folds (logical(1))`
Indicates whether the tuning should be done fold-specific or globally. Default is `FALSE`.

Returns: self

Method `clone()`**:** The objects of this class are cloneable with this method.

Usage:

```
DoubleMLSSM$clone(deep = FALSE)
```

Arguments:

`deep` Whether to make a deep clone.

See Also

Other DoubleML: `DoubleML`, `DoubleMLIIVM`, `DoubleMLIRM`, `DoubleMLPLIV`, `DoubleMLPLR`

Examples

```
library(DoubleML)
library(mlr3)
library(mlr3learners)
library(data.table)
set.seed(2)
ml_g = lrn("regr.ranger",
  num.trees = 100, mtry = 20,
  min.node.size = 2, max.depth = 5)
ml_m = lrn("classif.ranger",
  num.trees = 100, mtry = 20,
  min.node.size = 2, max.depth = 5)
ml_pi = lrn("classif.ranger",
  num.trees = 100, mtry = 20,
  min.node.size = 2, max.depth = 5)

n_obs = 2000
df = make_ssm_data(n_obs = n_obs, mar = TRUE, return_type = "data.table")
```

```
dml_data = DoubleMLData$new(df, y_col = "y", d_cols = "d", s_col = "s")
dml_ssm = DoubleMLSSM$new(dml_data, ml_g, ml_m, ml_pi, score = "missing-at-random")
dml_ssm$fit()
print(dml_ssm)

## Not run:
library(DoubleML)
library(mlr3)
library(mlr3learners)
library(mlr3tuning)
library(data.table)
set.seed(2)
ml_g = lrn("regr.rpart")
ml_m = lrn("classif.rpart")
ml_pi = lrn("classif.rpart")
dml_data = make_ssm_data(n_obs = n_obs, mar = TRUE)
dml_ssm = DoubleMLSSM$new(dml_data, ml_g = ml_g, ml_m = ml_m, ml_pi = ml_pi,
  score = "missing-at-random")

param_grid = list(
 "ml_g" = paradox::ps(
   cp = paradox::p_dbl(lower = 0.01, upper = 0.02),
   minsplit = paradox::p_int(lower = 1, upper = 2)),
"ml_m" = paradox::ps(
  cp = paradox::p_dbl(lower = 0.01, upper = 0.02),
  minsplit = paradox::p_int(lower = 1, upper = 2)),
  "ml_pi" = paradox::ps(
  cp = paradox::p_dbl(lower = 0.01, upper = 0.02),
  minsplit = paradox::p_int(lower = 1, upper = 2)))

# minimum requirements for tune_settings
tune_settings = list(
  terminator = mlr3tuning::trm("evals", n_evals = 5),
  algorithm = mlr3tuning::tnr("grid_search", resolution = 5))

dml_ssm$tune(param_set = param_grid, tune_settings = tune_settings)
dml_ssm$fit()
dml_ssm$summary()

## End(Not run)
```

`double_ml_data_from_data_frame`

Wrapper for Double machine learning data-backend initialization from data.frame.

Description

Initalization of DoubleMLData from `data.frame`.

Usage

```
double_ml_data_from_data_frame(
  df,
  x_cols = NULL,
  y_col = NULL,
  d_cols = NULL,
  z_cols = NULL,
  s_col = NULL,
  cluster_cols = NULL,
  use_other_treat_as_covariate = TRUE
)
```

Arguments

`df` (`data.frame()`)
Data object.

`x_cols` (`NULL`, `character()`)
The covariates. If `NULL`, all variables (columns of `data`) which are neither specified as outcome variable `y_col`, nor as treatment variables `d_cols`, nor as instrumental variables `z_cols` are used as covariates. Default is `NULL`.

`y_col` (`character(1)`)
The outcome variable.

`d_cols` (`character()`)
The treatment variable(s).

`z_cols` (`NULL`, `character()`)
The instrumental variables. Default is `NULL`.

`s_col` (`NULL`, `character()`)
The score or selection variable (only relevant/used for SSM Estimators). Default is `NULL`.

`cluster_cols` (`NULL`, `character()`)
The cluster variables. Default is `NULL`.

`use_other_treat_as_covariate` (`logical(1)`)
Indicates whether in the multiple-treatment case the other treatment variables should be added as covariates. Default is `TRUE`.

Value

Creates a new instance of class `DoubleMLData`.

Examples

```
df = make_plr_CCDDHNR2018(return_type = "data.frame")
x_names = names(df)[grepl("X", names(df))]
obj_dml_data = double_ml_data_from_data_frame(
  df = df, x_cols = x_names,
  y_col = "y", d_cols = "d")
# Input: Data frame, Output: DoubleMLData object
```

double_ml_data_from_matrix

Wrapper for Double machine learning data-backend initialization from matrix.

Description

Initalization of DoubleMLData from `matrix()` objects.

Usage

```
double_ml_data_from_matrix(
  X = NULL,
  y,
  d,
  z = NULL,
  s = NULL,
  cluster_vars = NULL,
  data_class = "DoubleMLData",
  use_other_treat_as_covariate = TRUE
)
```

Arguments

`X` (`matrix()`)
Matrix of covariates.

`y` (`numeric()`)
Vector of outcome variable.

`d` (`matrix()`)
Matrix of treatment variables.

`z` (`matrix()`)
Matrix of instruments.

`s` (`numeric()`)
Vector of the score or selection variable (only relevant for SSM models).

`cluster_vars` (`matrix()`)
Matrix of cluster variables.

`data_class` (`character(1)`)
Class of returned object. By default, an object of class `DoubleMLData` is returned. Setting `data_class = "data.table"` returns an object of class `data.table`.

`use_other_treat_as_covariate`
(`logical(1)`)
Indicates whether in the multiple-treatment case the other treatment variables should be added as covariates. Default is `TRUE`.

Value

Creates a new instance of class DoubleMLData.

Examples

```
matrix_list = make_plr_CCDDHNR2018(return_type = "matrix")
obj_dml_data = double_ml_data_from_matrix(
  X = matrix_list$X,
  y = matrix_list$y,
  d = matrix_list$d)
```

---

fetch_401k *Data set on financial wealth and 401(k) plan participation.*

Description

Preprocessed data set on financial wealth and 401(k) plan participation. The raw data files are preprocessed to reproduce the examples in Chernozhukov et al. (2020). An internet connection is required to sucessfully download the data set.

Usage

```
fetch_401k(
  return_type = "DoubleMLData",
  polynomial_features = FALSE,
  instrument = FALSE
)
```

Arguments

`return_type` (character(1))
If "DoubleMLData", returns a DoubleMLData object. If "data.frame" returns a data.frame(). If "data.table" returns a data.table(). Default is "DoubleMLData".

`polynomial_features` (logical(1))
If TRUE polynomial freatures are added (see replication file of Chernozhukov et al. (2018)).

`instrument` (logical(1))
If TRUE, the returned data object contains the variables e401 and p401. If return_type = "DoubleMLData", the variable e401 is used as an instrument for the endogenous treatment variable p401. If FALSE, p401 is removed from the data set.

Details

Variable description, based on the supplementary material of Chernozhukov et al. (2020):

- net_tfa: net total financial assets
- e401: = 1 if employer offers 401(k)
- p401: = 1 if individual participates in a 401(k) plan
- age: age
- inc: income
- fsize: family size
- educ: years of education
- db: = 1 if individual has defined benefit pension
- marr: = 1 if married
- twoearn: = 1 if two-earner household
- pira: = 1 if individual participates in IRA plan
- hown: = 1 if home owner

The supplementary data of the study by Chernozhukov et al. (2018) is available at https://academic.oup.com/ectj/article/21/1/C1/5056401#supplementary-data.

Value

A data object according to the choice of `return_type`.

References

Abadie, A. (2003), Semiparametric instrumental variable estimation of treatment response models. Journal of Econometrics, 113(2): 231-263.

Chernozhukov, V., Chetverikov, D., Demirer, M., Duflo, E., Hansen, C., Newey, W. and Robins, J. (2018), Double/debiased machine learning for treatment and structural parameters. The Econometrics Journal, 21: C1-C68. doi:10.1111/ectj.12097.

---

fetch_bonus *Data set on the Pennsylvania Reemployment Bonus experiment.*

Description

Preprocessed data set on the Pennsylvania Reemploymnent Bonus experiment. The raw data files are preprocessed to reproduce the examples in Chernozhukov et al. (2020). An internet connection is required to sucessfully download the data set.

Usage

```
fetch_bonus(return_type = "DoubleMLData", polynomial_features = FALSE)
```

Arguments

`return_type` (`character(1)`)
If `"DoubleMLData"`, returns a `DoubleMLData` object. If `"data.frame"` returns a `data.frame()`. If `"data.table"` returns a `data.table()`. Default is `"DoubleMLData"`.

`polynomial_features` (`logical(1)`)
If `TRUE` polynomial freatures are added (see replication file of Chernozhukov et al. (2018)).

Details

Variable description, based on the supplementary material of Chernozhukov et al. (2020):

- abdt: chronological time of enrollment of each claimant in the Pennsylvania reemployment bonus experiment.
- tg: indicates the treatment group (bonus amount - qualification period) of each claimant.
- inuidur1: a measure of length (in weeks) of the first spell of unemployment
- inuidur2: a second measure for the length (in weeks) of
- female: dummy variable; it indicates if the claimant's sex is female (=1) or male (=0).
- black: dummy variable; it indicates a person of black race (=1).
- hispanic: dummy variable; it indicates a person of hispanic race (=1).
- othrace: dummy variable; it indicates a non-white, non-black, not-hispanic person (=1).
- dep1: dummy variable; indicates if the number of dependents of each claimant is equal to 1 (=1).
- dep2: dummy variable; indicates if the number of dependents of each claimant is equal to 2 (=1).
- q1-q6: six dummy variables indicating the quarter of experiment during which each claimant enrolled.
- recall: takes the value of 1 if the claimant answered "yes" when was asked if he/she had any expectation to be recalled
- agelt35: takes the value of 1 if the claimant's age is less than 35 and 0 otherwise.
- agegt54: takes the value of 1 if the claimant's age is more than 54 and 0 otherwise.
- durable: it takes the value of 1 if the occupation of the claimant was in the sector of durable manufacturing and 0 otherwise.
- nondurable: it takes the value of 1 if the occupation of the claimant was in the sector of nondurable manufacturing and 0 otherwise.
- lusd: it takes the value of 1 if the claimant filed in Coatesville, Reading, or Lancaster and 0 otherwise.
- These three sites were considered to be located in areas characterized by low unemployment rate and short duration of unemployment.
- husd: it takes the value of 1 if the claimant filed in Lewistown, Pittston, or Scranton and 0 otherwise.

- These three sites were considered to be located in areas characterized by high unemployment rate and short duration of unemployment.
- muld: it takes the value of 1 if the claimant filed in Philadelphia-North, Philadelphia-Uptown, McKeesport, Erie, or Butler and 0 otherwise.
- These three sites were considered to be located in areas characterized by moderate unemployment rate and long duration of unemployment."

The supplementary data of the study by Chernozhukov et al. (2018) is available at https://academic.oup.com/ectj/article/21/1/C1/5056401#supplementary-data.

The supplementary data of the study by Bilias (2000) is available at https://www.journaldata.zbw.eu/dataset/sequential-testing-of-duration-data-the-case-of-the-pennsylvania-reemployment-bonus

Value

A data object according to the choice of `return_type`.

References

Bilias Y. (2000), Sequential Testing of Duration Data: The Case of Pennsylvania 'Reemployment Bonus' Experiment. Journal of Applied Econometrics, 15(6): 575-594.

Chernozhukov, V., Chetverikov, D., Demirer, M., Duflo, E., Hansen, C., Newey, W. and Robins, J. (2018), Double/debiased machine learning for treatment and structural parameters. The Econometrics Journal, 21: C1-C68. doi:10.1111/ectj.12097.

Examples

```
library(DoubleML)
df_bonus = fetch_bonus(return_type = "data.table")
obj_dml_data_bonus = DoubleMLData$new(df_bonus,
  y_col = "inuidur1",
  d_cols = "tg",
  x_cols = c(
    "female", "black", "othrace", "dep1", "dep2",
    "q2", "q3", "q4", "q5", "q6", "agelt35", "agegt54",
    "durable", "lusd", "husd"
  )
)
obj_dml_data_bonus
```

`make_iivm_data` *Generates data from a interactive IV regression (IIVM) model.*

Description

Generates data from a interactive IV regression (IIVM) model. The data generating process is defined as

$d_i = 1\left\{\alpha_x Z + v_i > 0\right\},$

$y_i = \theta d_i + x_i'\beta + u_i,$

$Z \sim Bernoulli(0.5)$ and

$\left(\begin{array}{c} u_i \\ v_i \end{array}\right) \sim \mathcal{N}\left(0, \left(\begin{array}{cc} 1 & 0.3 \\ 0.3 & 1 \end{array}\right)\right).$

The covariates :$x_i \sim \mathcal{N}(0, \Sigma)$, where Σ is a matrix with entries $\Sigma_{kj} = 0.5^{|j-k|}$ and β is a `dim_x`-vector with entries $\beta_j = \frac{1}{j^2}$.

The data generating process is inspired by a process used in the simulation experiment of Farbmacher, Gruber and Klaaßen (2020).

Usage

```
make_iivm_data(
  n_obs = 500,
  dim_x = 20,
  theta = 1,
  alpha_x = 0.2,
  return_type = "DoubleMLData"
)
```

Arguments

`n_obs`	(`integer(1)`) The number of observations to simulate.
`dim_x`	(`integer(1)`) The number of covariates.
`theta`	(`numeric(1)`) The value of the causal parameter.
`alpha_x`	(`numeric(1)`) The value of the parameter α_x.
`return_type`	(`character(1)`) If `"DoubleMLData"`, returns a `DoubleMLData` object. If `"data.frame"` returns a `data.frame()`. If `"data.table"` returns a `data.table()`. If `"matrix"` a named `list()` with entries `X`, `y`, `d` and `z` is returned. Every entry in the list is a `matrix()` object. Default is `"DoubleMLData"`.

References

Farbmacher, H., Guber, R. and Klaaßen, S. (2020). Instrument Validity Tests with Causal Forests. MEA Discussion Paper No. 13-2020. Available at SSRN:doi:10.2139/ssrn.3619201.

`make_irm_data` *Generates data from a interactive regression (IRM) model.*

Description

Generates data from a interactive regression (IRM) model. The data generating process is defined as

$d_i = 1\left\{\frac{\exp(c_d x_i'\beta)}{1+\exp(c_d x_i'\beta)} > v_i\right\}$,

$y_i = \theta d_i + c_y x_i'\beta d_i + \zeta_i$,

with $v_i \sim \mathcal{U}(0,1)$, $\zeta_i \sim \mathcal{N}(0,1)$ and covariates $x_i \sim \mathcal{N}(0,\Sigma)$, where Σ is a matrix with entries $\Sigma_{kj} = 0.5^{|j-k|}$. β is a `dim_x`-vector with entries $\beta_j = \frac{1}{j^2}$ and the constancts c_y and c_d are given by

$c_y = \sqrt{\frac{R_y^2}{(1-R_y^2)\beta'\Sigma\beta}}$,

$c_d = \sqrt{\frac{(\pi^2/3)R_d^2}{(1-R_d^2)\beta'\Sigma\beta}}$.

The data generating process is inspired by a process used in the simulation experiment (see Appendix P) of Belloni et al. (2017).

Usage

```
make_irm_data(
  n_obs = 500,
  dim_x = 20,
  theta = 0,
  R2_d = 0.5,
  R2_y = 0.5,
  return_type = "DoubleMLData"
)
```

Arguments

`n_obs`	(`integer(1)`) The number of observations to simulate.
`dim_x`	(`integer(1)`) The number of covariates.
`theta`	(`numeric(1)`) The value of the causal parameter.
`R2_d`	(`numeric(1)`) The value of the parameter R_d^2.
`R2_y`	(`numeric(1)`) The value of the parameter R_y^2.

`return_type` (character(1))
If "DoubleMLData", returns a DoubleMLData object. If "data.frame" returns a data.frame(). If "data.table" returns a data.table(). If "matrix" a named list() with entries X, y, d and z is returned. Every entry in the list is a matrix() object. Default is "DoubleMLData".

References

Belloni, A., Chernozhukov, V., Fernández-Val, I. and Hansen, C. (2017). Program Evaluation and Causal Inference With High-Dimensional Data. Econometrica, 85: 233-298.

`make_pliv_CHS2015` *Generates data from a partially linear IV regression model used in Chernozhukov, Hansen and Spindler (2015).*

Description

Generates data from a partially linear IV regression model used in Chernozhukov, Hansen and Spindler (2015). The data generating process is defined as

$z_i = \Pi x_i + \zeta_i,$

$d_i = x_i' \gamma + z_i' \delta + u_i,$

$y_i = \alpha d_i + x_i' \beta + \epsilon_i,$

with

$$\begin{pmatrix} \varepsilon_i \\ u_i \\ \zeta_i \\ x_i \end{pmatrix} \sim \mathcal{N}\left(0, \begin{pmatrix} 1 & 0.6 & 0 & 0 \\ 0.6 & 1 & 0 & 0 \\ 0 & 0 & 0.25 I_{p_n^z} & 0 \\ 0 & 0 & 0 & \Sigma \end{pmatrix}\right)$$

where Σ is a $p_n^x \times p_n^x$ matrix with entries $\Sigma_{kj} = 0.5^{|j-k|}$ and $I_{p_n^z}$ is the $p_n^z \times p_n^z$ identity matrix. $\beta = \gamma$ iis a p_n^x-vector with entries $\beta_j = \frac{1}{j^2}$, δ is a p_n^z-vector with entries $\delta_j = \frac{1}{j^2}$ and $\Pi = (I_{p_n^z}, O_{p_n^z \times (p_n^x - p_n^z)})$.

Usage

```
make_pliv_CHS2015(
  n_obs,
  alpha = 1,
  dim_x = 200,
  dim_z = 150,
  return_type = "DoubleMLData"
)
```

Arguments

`n_obs`	(`integer(1)`) The number of observations to simulate.
`alpha`	(`numeric(1)`) The value of the causal parameter.
`dim_x`	(`integer(1)`) The number of covariates.
`dim_z`	(`integer(1)`) The number of instruments.
`return_type`	(`character(1)`) If `"DoubleMLData"`, returns a `DoubleMLData` object. If `"data.frame"` returns a `data.frame()`. If `"data.table"` returns a `data.table()`. If `"matrix"` a named `list()` with entries `X`, `y`, `d` and `z` is returned. Every entry in the list is a `matrix()` object. Default is `"DoubleMLData"`.

Value

A data object according to the choice of `return_type`.

References

Chernozhukov, V., Hansen, C. and Spindler, M. (2015), Post-Selection and Post-Regularization Inference in Linear Models with Many Controls and Instruments. American Economic Review: Papers and Proceedings, 105 (5): 486-90.

`make_pliv_multiway_cluster_CKMS2021`

Generates data from a partially linear IV regression model with multiway cluster sample used in Chiang et al. (2021).

Description

Generates data from a partially linear IV regression model with multiway cluster sample used in Chiang et al. (2021). The data generating process is defined as

$Z_{ij} = X_{ij}'\xi_0 + V_{ij},$

$D_{ij} = Z_{ij}'\pi_{10} + X_{ij}'\pi_{20} + v_{ij},$

$Y_{ij} = D_{ij}\theta + X_{ij}'\zeta_0 + \varepsilon_{ij},$

with

$X_{ij} = (1 - \omega_1^X - \omega_2^X)\alpha_{ij}^X + \omega_1^X\alpha_i^X + \omega_2^X\alpha_j^X,$

$\varepsilon_{ij} = (1 - \omega_1^\varepsilon - \omega_2^\varepsilon)\alpha_{ij}^\varepsilon + \omega_1^\varepsilon\alpha_i^\varepsilon + \omega_2^\varepsilon\alpha_j^\varepsilon,$

$v_{ij} = (1 - \omega_1^v - \omega_2^v)\alpha_{ij}^v + \omega_1^v\alpha_i^v + \omega_2^v\alpha_j^v,$

$V_{ij} = (1 - \omega_1^V - \omega_2^V)\alpha_{ij}^V + \omega_1^V\alpha_i^V + \omega_2^V\alpha_j^V,$

and $\alpha_{ij}^X, \alpha_i^X, \alpha_j^X \sim \mathcal{N}(0, \Sigma)$ where Σ is a $p_x \times p_x$ matrix with entries $\Sigma_{kj} = s_X^{|j-k|}$.
Further
$\begin{pmatrix} \alpha_{ij}^\varepsilon \\ \alpha_{ij}^v \end{pmatrix}, \begin{pmatrix} \alpha_i^\varepsilon \\ \alpha_i^v \end{pmatrix}, \begin{pmatrix} \alpha_j^\varepsilon \\ \alpha_j^v \end{pmatrix} \sim \mathcal{N}\left(0, \begin{pmatrix} 1 & s_{\varepsilon v} \\ s_{\varepsilon v} & 1 \end{pmatrix}\right)$
and $\alpha_{ij}^V, \alpha_i^V, \alpha_j^V \sim \mathcal{N}(0, 1)$.

Usage

```
make_pliv_multiway_cluster_CKMS2021(
  N = 25,
  M = 25,
  dim_X = 100,
  theta = 1,
  return_type = "DoubleMLClusterData",
  ...
)
```

Arguments

`N`	(`integer(1)`) The number of observations (first dimension).
`M`	(`integer(1)`) The number of observations (second dimension).
`dim_X`	(`integer(1)`) The number of covariates.
`theta`	(`numeric(1)`) The value of the causal parameter.
`return_type`	(`character(1)`) If `"DoubleMLClusterData"`, returns a `DoubleMLClusterData` object. If `"data.frame"` returns a `data.frame()`. If `"data.table"` returns a `data.table()`. If `"matrix"` a named `list()` with entries `X`, `y`, `d`, `z` and `cluster_vars` is returned. Every entry in the list is a `matrix()` object. Default is `"DoubleMLClusterData"`.
`...`	Additional keyword arguments to set non-default values for the parameters $\pi_{10} = 1.0$, $\omega_X = \omega_\varepsilon = \omega_V = \omega_v = (0.25, 0.25)$, $s_X = s_{\varepsilon v} = 0.25$, or the p_x-vectors $\zeta_0 = \pi_{20} = \xi_0$ with default entries $\zeta_0)_j = 0.5^j$.

Value

A data object according to the choice of `return_type`.

References

Chiang, H. D., Kato K., Ma, Y. and Sasaki, Y. (2021), Multiway Cluster Robust Double/Debiased Machine Learning, Journal of Business & Economic Statistics, doi:10.1080/07350015.2021.1895815, https://arxiv.org/abs/1909.03489.

`make_plr_CCDDHNR2018` *Generates data from a partially linear regression model used in Chernozhukov et al. (2018)*

Description

Generates data from a partially linear regression model used in Chernozhukov et al. (2018) for Figure 1. The data generating process is defined as

$d_i = m_0(x_i) + s_1 v_i,$

$y_i = \alpha d_i + g_0(x_i) + s_2 \zeta_i,$

with $v_i \sim \mathcal{N}(0,1)$ and $\zeta_i \sim \mathcal{N}(0,1)$,. The covariates are distributed as $x_i \sim \mathcal{N}(0, \Sigma)$, where Σ is a matrix with entries $\Sigma_{kj} = 0.7^{|j-k|}$. The nuisance functions are given by

$m_0(x_i) = a_0 x_{i,1} + a_1 \frac{\exp(x_{i,3})}{1+\exp(x_{i,3})},$

$g_0(x_i) = b_0 \frac{\exp(x_{i,1})}{1+\exp(x_{i,1})} + b_1 x_{i,3},$

with $a_0 = 1$, $a_1 = 0.25$, $s_1 = 1$, $b_0 = 1$, $b_1 = 0.25$, $s_2 = 1$.

Usage

```
make_plr_CCDDHNR2018(
  n_obs = 500,
  dim_x = 20,
  alpha = 0.5,
  return_type = "DoubleMLData"
)
```

Arguments

`n_obs`	(`integer(1)`) The number of observations to simulate.
`dim_x`	(`integer(1)`) The number of covariates.
`alpha`	(`numeric(1)`) The value of the causal parameter.
`return_type`	(`character(1)`) If `"DoubleMLData"`, returns a `DoubleMLData` object. If `"data.frame"` returns a `data.frame()`. If `"data.table"` returns a `data.table()`. If `"matrix"` a named `list()` with entries `X`, `y` and `d` is returned. Every entry in the list is a `matrix()` object. Default is `"DoubleMLData"`.

Value

A data object according to the choice of `return_type`.

References

Chernozhukov, V., Chetverikov, D., Demirer, M., Duflo, E., Hansen, C., Newey, W. and Robins, J. (2018), Double/debiased machine learning for treatment and structural parameters. The Econometrics Journal, 21: C1-C68. doi:10.1111/ectj.12097.

`make_plr_turrell2018` *Generates data from a partially linear regression model used in a blog article by Turrell (2018).*

Description

Generates data from a partially linear regression model used in a blog article by Turrell (2018). The data generating process is defined as

$d_i = m_0(x_i'b) + v_i,$

$y_i = \theta d_i + g_0(x_i'b) + u_i,$

with $v_i \sim \mathcal{N}(0,1)$, $u_i \sim \mathcal{N}(0,1)$, and covariates $x_i \sim \mathcal{N}(0,\Sigma)$, where Σ is a random symmetric, positive-definite matrix generated with `clusterGeneration::genPositiveDefMat()`. b is a vector with entries $b_j = \frac{1}{j}$ and the nuisance functions are given by

$m_0(x_i) = \frac{1}{2\pi}\frac{\sinh(\gamma)}{\cosh(\gamma)-\cos(x_i-\nu)},$

$g_0(x_i) = \sin(x_i)^2.$

Usage

```
make_plr_turrell2018(
  n_obs = 100,
  dim_x = 20,
  theta = 0.5,
  return_type = "DoubleMLData",
  nu = 0,
  gamma = 1
)
```

Arguments

`n_obs`	`(integer(1))` The number of observations to simulate.
`dim_x`	`(integer(1))` The number of covariates.
`theta`	`(numeric(1))` The value of the causal parameter.
`return_type`	`(character(1))` If `"DoubleMLData"`, returns a `DoubleMLData` object. If `"data.frame"` returns a `data.frame()`. If `"data.table"` returns a `data.table()`. If `"matrix"` a named `list()` with entries `X`, `y` and `d` is returned. Every entry in the list is a `matrix()` object. Default is `"DoubleMLData"`.

nu (numeric(1))
The value of the parameter ν. Default is 0.

gamma (numeric(1))
The value of the parameter γ. Default is 1.

Value

A data object according to the choice of return_type.

References

Turrell, A. (2018), Econometrics in Python part I - Double machine learning, Markov Wanderer: A blog on economics, science, coding and data. https://aeturrell.com/blog/posts/econometrics-in-python-parti-m

---

make_ssm_data *Generates data from a sample selection model (SSM).*

Description

The data generating process is defined as:

Usage

```
make_ssm_data(
  n_obs = 8000,
  dim_x = 100,
  theta = 1,
  mar = TRUE,
  return_type = "DoubleMLData"
)
```

Arguments

n_obs (integer(1))
The number of observations to simulate.

dim_x (integer(1))
The number of covariates.

theta (numeric(1))
The value of the causal parameter.

mar (logical(1))
Indicates whether missingness at random holds.

return_type (character(1))
If "DoubleMLData", returns a DoubleMLData object. If "data.frame" returns a data.frame(). If "data.table" returns a data.table(). Default is "DoubleMLData".

Details

$$y_i = \theta d_i + x_i'\beta + u_i,$$

$$s_i = 1\{d_i + \gamma z_i + x_i'\beta + v_i > 0\},$$

$$d_i = 1\{x_i'\beta + w_i > 0\},$$

with y_i being observed if $s_i = 1$ and covariates $x_i \sim \mathcal{N}(0, \Sigma_x^2)$, where Σ_x^2 is a matrix with entries $\Sigma_{kj} = 0.5^{|j-k|}$. β is a `dim_x`-vector with entries $\beta_j = \frac{0.4}{j^2}$ $z_i \sim \mathcal{N}(0,1)$, $(u_i, v_i) \sim \mathcal{N}(0, \Sigma_{u,v}^2)$, $w_i \sim \mathcal{N}(0,1)$.

The data generating process is inspired by a process used in the simulation study (see Appendix E) of Bia, Huber and Lafférs (2023).

Value

Depending on the `return_type`, returns an object or set of objects as specified.

References

Michela Bia, Martin Huber & Lukáš Lafférs (2023) Double Machine Learning for Sample Selection Models, Journal of Business & Economic Statistics, DOI: 10.1080/07350015.2023.2271071

Index

∗ **DoubleML**
DoubleML, 2
DoubleMLIIVM, 14
DoubleMLIRM, 18
DoubleMLPLIV, 21
DoubleMLPLR, 27
DoubleMLSSM, 31

clusterGeneration::genPositiveDefMat(), *49*

data.table, *3*, *10–13*
double_ml_data_from_data_frame, 36
double_ml_data_from_data_frame(), *10*, *12*
double_ml_data_from_matrix, 38
double_ml_data_from_matrix(), *10*, *12*
DoubleML, 2, *14*, *17*, *18*, *20*, *22*, *26*, *27*, *30*, *31*, *35*
DoubleML::DoubleML, *15*, *19*, *22*, *27*, *32*
DoubleML::DoubleMLData, *10*
DoubleMLClusterData, 10
DoubleMLData, 12
DoubleMLIIVM, *9*, 14, *20*, *26*, *30*, *35*
DoubleMLIRM, *9*, *17*, 18, *26*, *30*, *35*
DoubleMLPLIV, *9*, *17*, *20*, 21, *30*, *35*
DoubleMLPLR, *9*, *17*, *20*, *26*, 27, *35*
DoubleMLSSM, *9*, *17*, *20*, *26*, *30*, 31

fetch_401k, 39
fetch_bonus, 40

GraphLearner, *16*, *20*, *23*, *28*, *32*, *33*

Learner, *16*, *20*, *23*, *28*, *32*, *33*
LearnerClassif, *16*, *20*, *28*, *33*
LearnerRegr, *16*, *20*, *23*, *28*, *32*, *33*

make_iivm_data, 42
make_irm_data, 44
make_pliv_CHS2015, 45
make_pliv_multiway_cluster_CKMS2021, 46
make_plr_CCDDHNR2018, 48
make_plr_turrell2018, 49
make_ssm_data, 50
Measure, *7*, *25*, *30*, *35*
msr(), *7*, *25*, *30*, *35*

p.adjust(), *8*
ParamSet, *6*, *25*, *29*, *34*

R6, *10*, *13*
R6::R6Class, *2*, *14*, *18*, *22*, *27*, *31*
Resampling, *7*, *25*, *30*, *35*
rsmp(), *7*, *25*, *30*, *35*

Terminator, *6*, *25*, *30*, *34*
tnr(), *6*, *7*, *25*, *30*, *34*, *35*
Tuner, *6*, *25*, *30*, *34*
TuningInstance, *6*, *25*, *30*, *34*