

Package ‘EcoNiche’

May 7, 2026

Type Package

Title Community Niche Position and Width Estimation Tools

Version 1.0.2

Description Provides methods for estimating species niche position and niche breadth under continuous environmental gradients. The package implements canonical correspondence analysis (CCA), partial CCA (pCCA), generalized additive models (GAM), and Levins' niche breadth metrics for species-level and community-level analyses. Methods are based on ter Braak (1986) <[doi:10.2307/1938672](https://doi.org/10.2307/1938672)>, Okie et al. (2015) <[doi:10.1098/rspb.2014.2630](https://doi.org/10.1098/rspb.2014.2630)>, Feng et al. (2020) <[doi:10.1111/mec.15441](https://doi.org/10.1111/mec.15441)>, Wood (2017) <[doi:10.1201/9781315370279](https://doi.org/10.1201/9781315370279)>, and Levins (1968, ISBN:978-0691080628).

License MIT + file LICENSE

Encoding UTF-8

Imports ggplot2, mgcv, vegan,

Suggests testthat (>= 3.0.0), knitr, rmarkdown, viridisLite

Config/testthat/edition 3

VignetteBuilder knitr

RoxygenNote 7.3.3

URL <https://github.com/yedeng-lab/EcoNiche>

BugReports <https://github.com/yedeng-lab/EcoNiche/issues>

NeedsCompilation no

Author Shuotao Zhou [aut, cre],
Kai Feng [aut],
Ye Deng [aut]

Maintainer Shuotao Zhou <zhoushuotao@stu.hunau.edu.cn>

Repository CRAN

Date/Publication 2026-03-10 12:10:02 UTC

Contents

cca_calc_gradient	2
cca_calc_group	3
cca_calc_species	3
cca_fit_ordination	4
cca_plot_group_env	5
cca_prep_env	6
cca_workflow	7
cca_workflow_gradient	8
cca_workflow_group	9
gam_calc_sitewidth	10
gam_fit_model	11
gam_plot_species	12
levins_calc_binned	14
levins_calc_group	15
levins_plot_pos_width	16
niche_width_calc	17
Index	19

cca_calc_gradient *Plot Site Niche Position vs Environmental Gradient (Step 4)*

Description

Evaluates the relationship between the environmental gradient and the aggregated niche position of sites.

Usage

```
cca_calc_gradient(env, site_pos, var, make_plot = TRUE, galaxy_colnum = TRUE)
```

Arguments

env	A sample-by-environment data.frame (rows = samples).
site_pos	Named numeric vector of site scores on the position axis.
var	Environmental variable to plot against (name or index).
make_plot	Logical; if TRUE, returns a ggplot object.
galaxy_colnum	Logical; for numeric indices, whether to treat them as 1-based indices.

Value

A list containing:

data Data frame used for plotting (ENV, NichePosition).

plot The ggplot object.

cca_calc_group	<i>Calculate Niche Width Summary by Group (Step 5)</i>
----------------	--

Description

Computes aggregated niche width statistics at the sample level and group level. Supports two calculation modes via choice: "all" (global context) or group-specific context.

Usage

```
cca_calc_group(otu, site_width, group, choice = "all")
```

Arguments

otu	OTU/species matrix (rows = taxa, columns = samples).
site_width	Site scores for width axis (usually matrix).
group	A named vector or factor defining groups. Names must match sample IDs.
choice	Calculation mode. If "all", computes niche width using all samples. Otherwise, computes within-group niche widths.

Value

A list containing:

sample_summary Data frame of sample-level statistics (ID, AverageValue, StandardDeviation/Error).

group_summary Data frame of group-level statistics.

cca_calc_species	<i>Calculate Species Niche Width and Position (Step 3)</i>
------------------	--

Description

Computes the niche width and niche position for each species using the site scores from Step 2. Generates a plot of Niche Width vs. Niche Position.

Usage

```
cca_calc_species(
  otu,
  site_width,
  site_pos,
  method = c("lm", "loess"),
  make_plot = TRUE,
  top_node = 10000
)
```

Arguments

otu	OTU/species matrix (rows = taxa, columns = samples).
site_width	Site scores for width axis (usually matrix from partial CCA).
site_pos	Site scores for position axis (usually vector from CCA axis 1).
method	Smoothing method for the plot ("lm" or "loess").
make_plot	Logical; if TRUE, returns a ggplot object.
top_node	Integer; maximum number of most abundant species to use for loess smoothing calculation (default 10000). Points are plotted for all valid species.

Value

A list containing:

species Data frame of species traits (NichePosition, NicheWidth).

plot The ggplot object (if make_plot = TRUE).

cca_fit_ordination *Fit CCA and Partial-CCA Ordination (Step 2)*

Description

Performs Constrained Correspondence Analysis (CCA) and Partial CCA to obtain site scores for niche position and niche width calculations.

Usage

```
cca_fit_ordination(
  otu,
  env,
  sel,
  covariates,
  standardize = TRUE,
  galaxy_colnum = TRUE
)
```

Arguments

otu	An OTU/species matrix or data frame (rows = taxa, columns = samples).
env	A data.frame of environmental variables (rows = samples).
sel	Variables (names or indices) defining the width axis (used in partial CCA).
covariates	Variables (names or indices) defining the position axis (used in CCA and as covariates in partial CCA).
standardize	Logical; if TRUE, environmental variables are standardized. Default is TRUE.
galaxy_colnum	Logical; for numeric indices, whether to treat them as Galaxy-style 1-based indices (skipping column 1).

Value

A list containing:

site_width Matrix of site scores from the partial CCA (width axes).

site_pos Named vector of site scores from the first axis of the CCA (position axis).

site_pos_mat Matrix of all site scores from the CCA.

cca The CCA model object.

pcca The Partial CCA model object.

cca_plot_group_env *Plot Sample/Group Niche Width vs Environmental Gradient (Step 6)*

Description

Visualizes the relationship between environmental gradients and niche width at the sample or group level.

Usage

```
cca_plot_group_env(
  env,
  sample_summary,
  var,
  group = NULL,
  plot_type = c("sample", "group", "both"),
  method = c("lm", "loess"),
  make_plot = TRUE,
  galaxy_colnum = TRUE,
  show_ci = TRUE,
  annotate_stats = TRUE
)
```

Arguments

env	A sample-by-environment data.frame.
sample_summary	Output from cca_calc_group (step 5).
var	Environmental variable to plot against (name or index).
group	Named vector/factor of group labels (required for group plots).
plot_type	Type of plot: "sample", "group", or "both".
method	Smoothing method ("lm" or "loess").
make_plot	Logical; if TRUE, returns ggplot object(s).
galaxy_colnum	Logical; for numeric indices, whether to treat them as 1-based indices.
show_ci	Logical; whether to show confidence intervals on the smooth line.
annotate_stats	Logical; whether to annotate R-squared and P-value on the plot.

Value

A list containing data frames and ggplot objects for samples and/or groups.

cca_prep_env	<i>Prepare Environmental Data for CCA (Step 1)</i>
--------------	--

Description

Performs standardization and Principal Component Analysis (PCA) on environmental variables. This step assists in selecting constrained variables and covariates for downstream CCA or partial-CCA.

Usage

```
cca_prep_env(
  env,
  sel,
  constrain = NULL,
  standardize = TRUE,
  galaxy_colnum = TRUE
)
```

Arguments

env	A data.frame of environmental variables. Rows must be sample IDs and columns must be environmental variables.
sel	A vector of variable names or column indices to be used as constrained variables.
constrain	Optional. A vector of variable names or column indices to be used as covariates. (Note: in the legacy workflow this parameter corresponds to 'covariates').
standardize	Logical; if TRUE, environmental variables are standardized (centered and scaled) column-wise. Default is TRUE.
galaxy_colnum	Logical; if TRUE and numeric indices are provided, they are treated as 1-based indices where column 1 is assumed to be SampleID (and thus indices are decremented by 1). Default is TRUE.

Value

A list containing:

env_sd The standardized environmental data frame.

sel_idx Indices of selected variables.

con_idx Indices of constrained covariates.

pca The PCA result object (from [prcomp](#)).

combined A data frame combining SampleID, PCA axes, and constrained variables.

cor_res A matrix/table of correlations between PCA axes and original variables, including significance levels.

`cca_workflow`*CCA-Based Niche Analysis Workflow Controller*

Description

A controller function that orchestrates the CCA-based niche analysis workflow. It dispatches the execution to either the gradient workflow (Steps 1-4) or the group workflow (Steps 1-2, 5-6) based on the specified mode.

Usage

```
cca_workflow(mode = c("gradient", "group"), ...)
```

Arguments

<code>mode</code>	A character string specifying the analysis mode. Must be one of "gradient" or "group".
<code>...</code>	Additional arguments passed to the specific workflow functions (cca_workflow_gradient or cca_workflow_group).

Value

A list containing the results of the executed workflow steps. See [cca_workflow_gradient](#) or [cca_workflow_group](#) for structure details.

Examples

```
set.seed(1)
otu <- matrix(rpois(20*25, 5), nrow = 20)
rownames(otu) <- paste0("OTU", 1:20)
colnames(otu) <- paste0("S", 1:25)
env <- data.frame(
  Temp = rnorm(25, 15, 3),
  pH = rnorm(25, 6.5, 0.4),
  SOC = rlnorm(25, 2, 0.3)
)
rownames(env) <- colnames(otu)
res <- cca_workflow(
  mode = "gradient",
  otu = otu, env = env,
  sel = c("Temp", "pH"),
  covariates = "SOC",
  make_plot = FALSE,
  top_node = 20
)
str(res, max.level = 1)
```

cca_workflow_gradient *Execute Gradient-Based Workflow (Steps 1-4)*

Description

Runs the complete environmental gradient analysis pipeline: 1. Prepare env data (PCA) 2. Fit CCA/Partial-CCA 3. Calculate species niche traits 4. Analyze gradient vs niche position

Usage

```
cca_workflow_gradient(
  otu,
  env,
  sel,
  covariates,
  standardize = TRUE,
  method = c("lm", "loess"),
  var = sel[1],
  galaxy_colnum = TRUE,
  make_plot = TRUE,
  top_node = 10000
)
```

Arguments

otu	An OTU/species matrix or data frame (rows = taxa, columns = samples).
env	A data.frame of environmental variables. Rows must be sample IDs and columns must be environmental variables.
sel	A vector of variable names or column indices to be used as constrained variables.
covariates	Variables (names or indices) defining the position axis (used in CCA and as covariates in partial CCA).
standardize	Logical; if TRUE, environmental variables are standardized (centered and scaled) column-wise. Default is TRUE.
method	Smoothing method for the plot ("lm" or "loess").
var	Environmental variable for gradient plotting (passed to Step 4).
galaxy_colnum	Logical; if TRUE and numeric indices are provided, they are treated as 1-based indices where column 1 is assumed to be SampleID (and thus indices are decremented by 1). Default is TRUE.
make_plot	Logical; if TRUE, returns a ggplot object.
top_node	Integer; maximum number of most abundant species to use for loess smoothing calculation (default 10000). Points are plotted for all valid species.

Value

A named list containing outputs of steps 1 through 4.

cca_workflow_group *Execute Group-Based Workflow (Steps 1-2, 5-6)*

Description

Runs the complete group-based analysis pipeline: 1. Prepare env data (PCA) 2. Fit CCA/Partial-CCA 5. Calculate group niche widths 6. Plot group/sample niche width vs gradient

Usage

```
cca_workflow_group(
  otu,
  env,
  sel,
  group,
  covariates,
  standardize = TRUE,
  method = c("lm", "loess"),
  var = sel[1],
  choice = "all",
  galaxy_colnum = TRUE,
  make_plot = TRUE,
  plot_type = c("sample", "group", "both"),
  show_ci = TRUE,
  annotate_stats = TRUE
)
```

Arguments

otu	An OTU/species matrix or data frame (rows = taxa, columns = samples).
env	A data.frame of environmental variables. Rows must be sample IDs and columns must be environmental variables.
sel	A vector of variable names or column indices to be used as constrained variables.
group	A named vector or factor defining groups. Names must match sample IDs.
covariates	Variables (names or indices) defining the position axis (used in CCA and as covariates in partial CCA).
standardize	Logical; if TRUE, environmental variables are standardized (centered and scaled) column-wise. Default is TRUE.
method	Smoothing method ("lm" or "loess").
var	Environmental variable for gradient plotting (passed to Step 6).
choice	Calculation mode. If "all", computes niche width using all samples. Otherwise, computes within-group niche widths.
galaxy_colnum	Logical; if TRUE and numeric indices are provided, they are treated as 1-based indices where column 1 is assumed to be SampleID (and thus indices are decremented by 1). Default is TRUE.

make_plot	Logical; if TRUE, returns ggplot object(s).
plot_type	Type of plot: "sample", "group", or "both".
show_ci	Logical; whether to show confidence intervals on the smooth line.
annotate_stats	Logical; whether to annotate R-squared and P-value on the plot.

Value

A named list containing outputs of steps 1, 2, 5, and 6.

gam_calc_sitewidth	<i>Calculate Sample-Level Niche Width Weighted by Abundance</i>
--------------------	---

Description

Computes the abundance-weighted mean niche breadth for each sample, given an OTU-by-sample table and OTU-level niche breadth estimates (e.g., from `gam_fit_model`). The formula is:

$$B_j = \sum_i (abundance_{ij} \times breadth_{50i}) / \sum_i abundance_{ij}$$

Usage

```
gam_calc_sitewidth(
  otu,
  niche_df,
  otu_col = "OTU",
  width_col = "breadth50",
  weight_mode = c("auto", "counts", "relative")
)
```

Arguments

otu	An OTU-by-sample matrix or data frame.
niche_df	A data frame containing at least columns for OTU IDs and niche width values.
otu_col	Character string; the column name in <code>niche_df</code> containing OTU IDs. Default is "OTU".
width_col	Character string; the column name in <code>niche_df</code> containing niche width values. Default is "breadth50".
weight_mode	Character string; how to handle abundance weights. One of "auto", "counts", or "relative".

Value

A data frame with columns `sample` and `Bw50_abundance_weighted`.

gam_fit_model

*Fit GAM-Based Niche Curves for All OTUs***Description**

Fits a Generalized Additive Model (GAM) response curve for each OTU along a single environmental gradient. This function handles both count data (using Negative Binomial or Poisson families) and relative abundance data (using logit-transformed Gaussian models). It estimates the niche optimum and the 50% niche breadth (breadth50) for each taxon.

Usage

```
gam_fit_model(
  otu,
  env,
  env_var,
  data_type = c("auto", "count", "relative"),
  count_family = c("nb", "poisson"),
  use_offset = TRUE,
  lib_size = NULL,
  min_prev = 0.1,
  min_total = 100,
  min_mean = 1e-05,
  k_spline = 5,
  n_grid = 200,
  verbose = TRUE
)
```

Arguments

otu	An OTU-by-sample matrix or data frame. Rows should be OTUs/taxa and columns should be samples. Values can be counts or relative abundances.
env	A sample-by-environment data frame. Rows must be samples and columns must be environmental variables.
env_var	A character string specifying the column name in env to use as the environmental gradient.
data_type	Character string specifying the data type. One of "auto" (heuristic detection), "count", or "relative".
count_family	Character string specifying the error distribution family for count data. One of "nb" (Negative Binomial, default) or "poisson".
use_offset	Logical; whether to use an offset term (log library size) in the GAM for count data. Default is TRUE.
lib_size	Optional named numeric vector of library sizes (sequencing depth) for each sample. If NULL and data_type="count", column sums of otu are used.

min_prev	Minimum prevalence threshold (proportion of samples with abundance > 0). OTUs below this threshold are skipped. Default is 0.10.
min_total	Minimum total abundance threshold. Relevant for count data. Default is 100.
min_mean	Minimum mean abundance threshold. Relevant for relative abundance data. Default is 1e-5.
k_spline	Integer; the upper limit on the spline basis dimension for the smooth term $s(\text{env}, k = \dots)$. Default is 5.
n_grid	Integer; number of grid points along the gradient used to estimate optimum and niche breadth. Default is 200.
verbose	Logical; whether to print progress messages. Default is TRUE.

Value

A data frame with one row per OTU and the following columns:

OTU OTU identifier.

n_nonzero Number of samples with non-zero abundance.

prevalence Proportion of samples with non-zero abundance.

total_counts Total counts (for count data) or NA.

r2 Adjusted R-squared (for relative abundance models) or NA.

dev_expl Proportion of deviance explained.

edf Effective degrees of freedom of the smooth term.

F_stat Test statistic (F or Chi-sq) for the smooth term.

p_value Approximate p-value for the smooth term.

optimum_env Environmental value at the peak of the fitted curve.

env50_min Lower environmental bound where fitted abundance $\geq 50\%$ of peak.

env50_max Upper environmental bound where fitted abundance $\geq 50\%$ of peak.

breadth50 Niche breadth ($\text{env50_max} - \text{env50_min}$).

gam_plot_species

Plot GAM-Based Niche Curve for a Single OTU

Description

Fits a GAM response curve for a specific OTU and plots the results. Includes options for confidence intervals and different color palettes.

Usage

```
gam_plot_species(
  otu,
  env,
  env_var,
  otu_id,
  data_type = c("auto", "count", "relative"),
  count_family = c("nb", "poisson"),
  use_offset = TRUE,
  lib_size = NULL,
  min_mean = 1e-05,
  min_prev = 0.1,
  k_spline = 5,
  n_grid = 200,
  add_ci = TRUE,
  palette = c("blue", "orange", "green", "purple", "viridis"),
  point_alpha = 0.85
)
```

Arguments

otu	An OTU-by-sample matrix or data frame.
env	A sample-by-environment data frame.
env_var	Character string; the environmental variable to use as the gradient.
otu_id	Character string; the ID of the OTU to plot (must exist in otu).
data_type	Character string; "auto", "count", or "relative".
count_family	Character string; "nb" or "poisson".
use_offset	Logical; whether to use library size offset for count data.
lib_size	Optional named vector of library sizes.
min_mean	Minimum mean abundance filter (for relative mode).
min_prev	Minimum prevalence filter.
k_spline	Spline basis dimension.
n_grid	Number of grid points for prediction.
add_ci	Logical; whether to plot the 95% confidence interval.
palette	Character string; color palette name ("blue", "orange", "green", "purple", or "viridis").
point_alpha	Numeric; transparency alpha for observed data points.

Value

A list containing:

data Data frame of observed values (env, y).

grid Data frame of fitted values along the gradient.

fit The GAM model object.
optimum_env Estimated niche optimum.
env50_min Lower bound of 50% niche breadth.
env50_max Upper bound of 50% niche breadth.
breadth50 Niche breadth.
plot The ggplot object.

levins_calc_binned *Calculate Levins Niche Width Along a Gradient (Binned States)*

Description

Computes OTU-level Levins niche breadth along a continuous composite axis (e.g., CCA1) by discretizing the axis into bins (states). Abundance is first aggregated within bins (mean or sum), converted to within-bin proportions p_{ij} , and then used to compute:

$$B_i = 1 / \sum_j p_{ij}^2$$

A standardized breadth is also reported:

$$B'_i = (B_i - 1) / (K - 1)$$

where K is the number of bins.

Usage

```
levins_calc_binned(
  otu,
  env,
  axis_var,
  nbin = 8L,
  bin_method = c("equal_freq", "equal_width"),
  agg_fun = c("mean", "sum"),
  otu_mode = c("auto", "count", "relative"),
  min_occ = 3L,
  min_abund = 5
)
```

Arguments

otu	An OTU-by-sample matrix or data frame.
env	A sample-by-environment data frame with row names as sample IDs.
axis_var	Character string; column name in env containing the axis values.
nbin	Integer; number of bins used to discretize the axis. Default is 8.

bin_method	Character string; binning strategy. "equal_freq" (quantile-based) or "equal_width".
agg_fun	Character string; aggregation method within bins. "mean" (recommended) or "sum".
otu_mode	Character string; input data type. "auto" (detect), "count", or "relative". If "count", columns are normalized to relative abundance before aggregation to reduce sequencing depth bias.
min_occ	Minimum number of samples with abundance > 0 required to keep an OTU.
min_abund	Minimum total abundance required to keep an OTU.

Value

A data frame with one row per OTU and the following columns:

OTU OTU identifier.

axis Name of the gradient axis used.

n_states Number of bins (K).

levins_B Raw Levins niche breadth.

levins_Bstd Standardized Levins niche breadth.

n_samples Number of samples where the OTU is present.

total_abund Total abundance of the OTU.

levins_calc_group	<i>Calculate Community-Mean Levins Niche Width Along a Gradient</i>
-------------------	---

Description

Computes the abundance-weighted mean Levins width for each sample, using OTU-level Levins widths and sample-level OTU abundances. Optionally plots the relationship between this community metric and an environmental gradient.

Usage

```
levins_calc_group(
  otu,
  env,
  levins_df,
  grad,
  width_col = "levins_Bstd",
  method = c("lm", "loess"),
  make_plot = TRUE
)
```

Arguments

otu	An OTU-by-sample matrix or data frame.
env	A sample-by-environment data frame.
levins_df	A data frame of OTU-level Levins results containing at least columns OTU and width_col.
grad	The environmental gradient to plot against (column name or index in env).
width_col	Character string; column name in levins_df to use as the width metric. Default is "levins_Bstd".
method	Character string; smoothing method for the trend line. "lm" or "loess".
make_plot	Logical; whether to return a ggplot object.

Details

The community-mean width for sample s is:

$$B_s = \sum_i Q_{is} B'_i$$

where Q_{is} is the relative abundance of OTU i in sample s and B'_i is the standardized Levins width (levins_Bstd).

Value

A list containing:

data Data frame with columns Sample, ENV, and CommLevinsWidth.

plot The ggplot object (if make_plot=TRUE).

levins_plot_pos_width *Plot Species Niche Position vs Levins Width*

Description

Merges species niche optima (from any method such as CCA, GAM, or weighted average) with standardized Levins niche width, and plots the position-width relationship showing the correlation (R-squared) and P-value.

Usage

```
levins_plot_pos_width(
  pos_df,
  levins_df,
  id_col,
  pos_col = "NichePosition",
  width_col = "levins_Bstd",
  method = c("lm", "loess"),
  make_plot = TRUE
)
```

Arguments

pos_df	A data frame containing species niche positions. Must include id_col and pos_col.
levins_df	A data frame containing Levins widths. Must include id_col and width_col.
id_col	Character string; column name of the species/OTU ID shared by both tables (e.g., "OTU").
pos_col	Character string; column name of the niche position in pos_df. Default "NichePosition".
width_col	Character string; column name of the Levins width in levins_df. Default "levins_Bstd".
method	Character string; fitting method for the trend line. "lm" or "loess".
make_plot	Logical; whether to return a ggplot object.

Value

A list containing:

data Merged data frame used for plotting.

plot The ggplot object (if make_plot=TRUE).

niche_width_calc *Calculate Niche Width (Samples as States)*

Description

Computes OTU-level niche breadth by treating each sample as a discrete state. For OTU i , let p_{is} be the proportional abundance of OTU i in sample s (i.e., abundance of OTU i normalized to sum to 1 across all samples).

Usage

```
niche_width_calc(
  otu,
  env = NULL,
  min_occ = 3L,
  min_abund = 5,
  standardize = TRUE,
  method = c("levins", "shannon", "both")
)
```

Arguments

otu	An OTU-by-sample matrix or data frame (rows = OTUs, columns = samples). Values should be non-negative (counts or relative abundance).
env	Optional sample metadata data frame with row names as sample IDs. If provided, samples are aligned by the intersection of <code>colnames(otu)</code> and <code>rownames(env)</code> .
min_occ	Minimum number of samples with abundance > 0 required to keep an OTU. Default is 3.
min_abund	Minimum total abundance required to keep an OTU (sum across samples). Default is 5.
standardize	Logical; if TRUE and method includes "levins", returns the standardized breadth <code>levins_Bstd</code> in addition to the raw Levins breadth. Default is TRUE.
method	Character; which niche width index to compute. One of "levins", "shannon", or "both". Default is "levins".

Details

Two niche-width indices are supported via method:

- **Levins breadth (Levins):**

$$B_i = 1 / \sum_s p_{is}^2$$

Optionally, a standardized breadth ranging from 0 to 1 is returned:

$$B'_i = (B_i - 1) / (K - 1)$$

where K is the total number of samples (states).

- **Shannon breadth (Shannon):**

$$H_i = - \sum_s p_{is} \log(p_{is})$$

Terms with $p_{is} = 0$ are excluded from the sum to avoid $\log(0)$.

Value

A data frame with one row per OTU. Columns include:

OTU OTU identifier.

n_states Number of states (samples) used in calculation.

n_samples Number of samples where the OTU is present.

total_abund Total abundance of the OTU across samples.

levins_B Raw Levins niche breadth. Present if method is "levins" or "both".

levins_Bstd Standardized Levins niche breadth (if `standardize=TRUE`). Present if method is "levins" or "both".

shannon_H Shannon niche breadth (entropy). Present if method is "shannon" or "both".

Index

cca_calc_gradient, 2
cca_calc_group, 3, 5
cca_calc_species, 3
cca_fit_ordination, 4
cca_plot_group_env, 5
cca_prep_env, 6
cca_workflow, 7
cca_workflow_gradient, 7, 8
cca_workflow_group, 7, 9

gam_calc_sitewidth, 10
gam_fit_model, 11
gam_plot_species, 12

levins_calc_binned, 14
levins_calc_group, 15
levins_plot_pos_width, 16

niche_width_calc, 17

prcomp, 6