

Package ‘FILEST’

May 7, 2026

Type Package

Title Fine-Level Structure Simulator

Version 1.1.2

Description A population genetic simulator, which is able to generate synthetic datasets for single-nucleotide polymorphisms (SNP) for multiple populations. The genetic distances among populations can be set according to the Fixation Index (Fst) as explained in Balding and Nichols (1995) <[doi:10.1007/BF01441146](https://doi.org/10.1007/BF01441146)>. This tool is able to simulate outlying individuals and missing SNPs can be specified. For Genome-wide association study (GWAS), disease status can be set in desired level according risk ratio.

Depends R (>= 3.2.4)

License MIT + file LICENSE

Encoding UTF-8

LazyData true

RoxygenNote 7.1.1

Imports KRIS (>= 1.1.1),rARPACK,grDevices,stats,utils

Suggests testthat

BugReports <https://gitlab.com/kris.ccp/filest/-/issues>

URL <https://gitlab.com/kris.ccp/filest>

NeedsCompilation no

Author Kridsakorn Chaichoompu [aut, cre],
Kristel Van Steen [aut],
Fentaw Abegaz [aut]

Maintainer Kridsakorn Chaichoompu <kridsakorn@biostatgen.org>

Repository CRAN

Date/Publication 2021-01-25 12:50:06 UTC

Contents

cbind_bigmatrix	2
create.template.setting	3
demo.filest	3
filest	4
rbind_bigmatrix	5
Index	7

cbind_bigmatrix	<i>Combine two matrices by column for big data, internally used for parallelization</i>
-----------------	---

Description

Combine two matrices by column for big data, internally used for parallelization

Usage

```
cbind_bigmatrix(a, b)
```

Arguments

a	The first matrix
b	The second matrix

Value

The combined matrix by column

See Also

[rbind_bigmatrix](#)

Examples

```
X <- matrix(c(1,2,0,1,2,2,1,2,0,0,1,2,1,2,2,2),ncol=4)
Y <- matrix(c(2,1,1,0,1,0,0,1,1,2,2,0,0,1,1,0),ncol=4)
Z <- cbind_bigmatrix(X,Y)
print(Z)
```

`create.template.setting`*Create a template for a setting file of function filest*

Description

Create a template for a setting file of function filest

Usage

```
create.template.setting(out.file, no.setting = 1)
```

Arguments

<code>out.file</code>	An absolute path to a new setting file
<code>no.setting</code>	A number of simulated settings

Value

An output directory if successfully created. Null if a setting file can't be created.

Examples

```
#Create 2 simulated settings

output <- file.path(tempdir(), "example_setting.txt")
res <- create.template.setting(out.file = output, no.setting = 2)
print(res)
```

`demo.filest`*Demonstration the filest function*

Description

This function generates the setting file and demonstrate how to use [filest](#).

Usage

```
demo.filest()
```

Value

The output directory

Examples

```
#To run this function, simply call demo.filest()
demo.filest()
```

filest	<i>Simulate data for multiple populations</i>
--------	---

Description

The output files are saved to the specified directory according to out.

Usage

```
filest(setting, out, thread = 1)
```

Arguments

setting	An absolute path to a setting file
out	An absolute path for output files
thread	A number to specify a maximum thread to be run in parallel

Details

This function takes the specific input file containing the settings for simulations. It allows multiple settings for several simulation within one file. The simulation-setting file must be a text file. The line started with "-" indicates the parameters for simulation, and the line started with "#" are comments. Empty lines are allowed in the setting file. The parameters in the setting file are listed below:

- --setting A name of setting
- --population A list that indicates the numbers of population separated by comma
- --fst A list that indicates the Fst values separated by comma. Each Fst value represents a genetic distance of that particular population and the first population. The Fst values for the first population and the second population should be the same values, otherwise they will be summed up and divided by two.
- --case A list that indicates the ratio values of cases separated by comma
- --outlier A list that indicates the logical values (0/1) whether that population are outliers, separated by comma
- --marker A number of SNPs
- --replicate A number of replicates
- --riskratio A number of replicates
- --no.case.snp A number of case SNPs
- --pc A logical value (TRUE/FALSE) whether PCs will be calculated.
- --fulloutput A logical value (TRUE/FALSE) whether all information will be exported.

Value

NULL if done successfully. NA if output directory can't be created.

Examples

```
#Check and run the demo from demo.filest()
demo.filest()

#Here is the code for demo.filest()
txt <- "--setting=example1\n"
txt <- paste0(txt, "--population=100,100\n")
txt <- paste0(txt, "--fst=0.01,0.01\n")
txt <- paste0(txt, "--case=0,0\n")
txt <- paste0(txt, "--outlier=0,0\n")
txt <- paste0(txt, "--marker=1000\n")
txt <- paste0(txt, "--replicate=1\n")
txt <- paste0(txt, "--riskratio=1\n")
txt <- paste0(txt, "--no.case.snp=0\n")
txt <- paste0(txt, "--pc=TRUE\n")
txt <- paste0(txt, "--missing=0\n")
txt <- paste0(txt, "--fulloutput=TRUE\n")

outdir <- file.path(tempdir())

settingfile <- file.path(outdir, "example1.txt")
fo <- file(settingfile,"w")
for (i in txt){ write(i,fo)}
close(fo)

filest(setting = settingfile, out = outdir, thread = 1)
```

rbind_bigmatrix	<i>Combine two matrices by row for big data, internally used for parallelization</i>
-----------------	--

Description

Combine two matrices by row for big data, internally used for parallelization

Usage

```
rbind_bigmatrix(a, b)
```

Arguments

a	The first matrix
b	The second matrix

Value

The combined matrix by row

See Also

[cbind_bigmatrix](#)

Examples

```
X <- matrix(c(1,2,0,1,2,2,1,2,0,0,1,2,1,2,2,2),ncol=4)
Y <- matrix(c(2,1,1,0,1,0,0,1,1,2,2,0,0,1,1,0),ncol=4)
Z <- rbind_bigmatrix(X,Y)
print(Z)
```

Index

`cbind_bigmatrix`, [2](#), [6](#)
`create.template.setting`, [3](#)
`demo.filest`, [3](#)
`filest`, [3](#), [4](#)
`rbind_bigmatrix`, [2](#), [5](#)