

Package ‘GRNNs’

May 7, 2026

Title General Regression Neural Networks Package

Version 0.1.0

Description This General Regression Neural Networks Package uses various distance functions. It was motivated by Specht (1991, ISBN:1045-9227), and updated from previous published paper Li et al. (2016) <doi:10.1016/j.palaeo.2015.11.005>. This package includes various functions, although “euclidean” distance is used traditionally.

License GPL (>= 3)

Encoding UTF-8

LazyData true

RoxygenNote 7.1.1

Imports cvTools, rdist, scales, stats, vegan

Depends R (>= 3.5.0)

Suggests rmarkdown, knitr, testthat (>= 3.0.0)

Config/testthat/edition 3

VignetteBuilder knitr

NeedsCompilation no

Author Shufeng LI [aut, cre] (ORCID: <<https://orcid.org/0000-0002-5144-4432>>)

Maintainer Shufeng LI <lif@xtbg.org.cn>

Repository CRAN

Date/Publication 2021-09-08 09:30:04 UTC

Contents

findSpread	2
findSpreadRdist	2
findSpreadVegan	3
grnn	4
grnn.distance	5
grnn.kfold	5
met	6
physg	7
veg.distance	8

Index**9**

findSpread	<i>Find best spread</i>
------------	-------------------------

Description

Find best spread

Usage

```
findSpread(p_train, v_train, k, fun, scale = TRUE)
```

Arguments

p_train	The dataframe of training predictor dataset
v_train	The dataframe of training response variables
k	The numeric number of k folds
fun	The distance function
scale	The logic statements (TRUE/FALSE)

Value

Best spread

Examples

```
data("met")  
data("physg")  
## Not run: best.spread<-findSpread(physg,met,10,"bray",scale=TRUE)
```

findSpreadRdist	<i>find best spreads using Rdist</i>
-----------------	--------------------------------------

Description

find best spreads using Rdist

Usage

```
findSpreadRdist(x, y, k, fun, scale = TRUE)
```

Arguments

x	The dataframe of training predictor dataset
y	The dataframe of training response variables
k	The numeric number of k folds
fun	The distance function
scale	The logic statements (TRUE/FALSE)

Value

The vector of best spreads

<i>findSpreadVegan</i>	<i>Find best spread using vegan function</i>
------------------------	--

Description

Find best spread using vegan function

Usage

```
findSpreadVegan(x, y, k, fun, scale = TRUE)
```

Arguments

x	The dataframe of training predictor dataset
y	The dataframe of training response variables
k	The numeric number of k folds
fun	The distance function
scale	The logic statements (TRUE/FALSE)

Value

The vector of best spreads

 grnn

General Regression Neural Networks (GRNNs)

Description

This GRNNs uses various distance functions including: "euclidean", "minkowski", "manhattan", "maximum", "canberra", "angular", "correlation", "absolute_correlation", "hamming", "jaccard", "bray", "kulczynski", "gower", "altGower", "morisita", "horn", "mountford", "raup", "binomial", "chao", "cao", "mahalanobis".

Usage

```
grnn(p_input, p_train, v_train, fun = "euclidean", best.spread, scale = TRUE)
```

Arguments

p_input	The dataframe of input predictors
p_train	The dataframe of training predictor dataset
v_train	The dataframe of training response variables
fun	The distance function
best.spread	The vector of best spreads
scale	The logic statements (TRUE/FALSE)

Value

The predictions

Examples

```
data("met")
data("physg")
best.spread<-c(0.33,0.33,0.31,0.34,0.35,0.35,0.32,0.31,0.29,0.35,0.35)
predict<-physg[1,]
physg.train<-physg[-1,]
met.train<-met[-1,]
prediction<-grnn(predict,physg.train,met.train,fun="euclidean",best.spread,scale=TRUE)
```

grnn.distance	<i>grnn distance</i>
---------------	----------------------

Description

grnn distance

Usage

grnn.distance(x, y, fun)

Arguments

x	The dataframe of training predictor dataset
y	The dataframe of training response variables
fun	The distance function

Value

The matrix of distance between a and b

Examples

```
data("physg")
physg.train<-physg[1:10,]
physg.test<-physg[11:30,]
distance<-grnn.distance(physg.test,physg.train,"bray")
```

grnn.kfold	<i>General Regression Neural Networks (GRNNs)</i>
------------	---

Description

General Regression Neural Networks (GRNNs)

Usage

grnn.kfold(x, y, k, fun, scale = TRUE)

Arguments

x	The dataframe of training predictor dataset
y	The dataframe of training response variables
k	The numeric number of k folds
fun	The distance function
scale	The logic statements (TRUE/FALSE)

Value

rmse,stdae,stdev,mae,r,pvalue,best spread

Examples

```
data("met")
data("physg")
results_kfold<-grnn.kfold(physg,met,10,"euclidean",scale=TRUE)
```

met	<i>meteorological dataset</i>
-----	-------------------------------

Description

Data from a global collection by Robert A. Spicer. It include 11 climate variables from 378 sites.

Usage

```
met
```

Format

A data frame with 378 rows and 11 variables:

```
MAT double COLUMN_DESCRIPTION
WMT double COLUMN_DESCRIPTION
CMT double COLUMN_DESCRIPTION
GROWSEAS double COLUMN_DESCRIPTION
GSP double COLUMN_DESCRIPTION
MMGSP double COLUMN_DESCRIPTION
Three_WET double COLUMN_DESCRIPTION
Three_DRY double COLUMN_DESCRIPTION
RH double COLUMN_DESCRIPTION
SH double COLUMN_DESCRIPTION
ENTHAL double COLUMN_DESCRIPTION
```

Details

DETAILS

 physg

physiognomy dataset

Description

Data from a global collection by Robert A. Spicer. It include 31 leaf physiognomies variables from 378 sites.

Usage

physg

Format

A data frame with 378 rows and 31 variables:

Lobed double COLUMN_DESCRIPTION
 No.Teeth double COLUMN_DESCRIPTION
 Regular.teeth double COLUMN_DESCRIPTION
 Close.teeth double COLUMN_DESCRIPTION
 Round.teeth double COLUMN_DESCRIPTION
 Acute.teeth double COLUMN_DESCRIPTION
 Compound.teeth double COLUMN_DESCRIPTION
 Nanophyll double COLUMN_DESCRIPTION
 Leptophyll.1 double COLUMN_DESCRIPTION
 Leptophyll.2 double COLUMN_DESCRIPTION
 Microphyll.1 double COLUMN_DESCRIPTION
 Microphyll.2 double COLUMN_DESCRIPTION
 Microphyll.3 double COLUMN_DESCRIPTION
 Mesophyll.1 double COLUMN_DESCRIPTION
 Mesophyll.2 double COLUMN_DESCRIPTION
 Mesophyll.3 double COLUMN_DESCRIPTION
 Emarginate.apex double COLUMN_DESCRIPTION
 Round.apex double COLUMN_DESCRIPTION
 Acute.apex double COLUMN_DESCRIPTION
 Attenuate.apex double COLUMN_DESCRIPTION
 Cordate.base double COLUMN_DESCRIPTION
 Round.base double COLUMN_DESCRIPTION
 Acute.base double COLUMN_DESCRIPTION
 L.W..1.1 double COLUMN_DESCRIPTION

L.W.1.2.1 double COLUMN_DESCRIPTION
 L.W.2.3.1 double COLUMN_DESCRIPTION
 L.W.3.4.1 double COLUMN_DESCRIPTION
 L.W..4.1 double COLUMN_DESCRIPTION
 Obovate double COLUMN_DESCRIPTION
 Elliptic double COLUMN_DESCRIPTION
 Ovate double COLUMN_DESCRIPTION

Details

DETAILS

veg.distance	<i>distance using vegdist</i>
--------------	-------------------------------

Description

distance using vegdist

Usage

```
veg.distance(a, b, fun = "bray")
```

Arguments

a	The dataframe of training predictor dataset
b	The dataframe of validation predictor dataset
fun	The distance function

Value

The matrix of distance between a and b

Examples

```
data("physg")
physg.train<-physg[1:10,]
physg.test<-physg[11:30,]
distance<-veg.distance(physg.test,physg.train,"bray")
```


Index

* datasets

met, [6](#)

physg, [7](#)

findSpread, [2](#)

findSpreadRdist, [2](#)

findSpreadVegan, [3](#)

grnn, [4](#)

grnn.distance, [5](#)

grnn.kfold, [5](#)

met, [6](#)

physg, [7](#)

veg.distance, [8](#)