

Package ‘GregoryQuadrature’

May 7, 2026

Title Gregory Weights for Function Integration

Version 1.0.0

Description Computes Gregory weights for a given number nodes and function order. Anthony Ralston and Philip Rabinowitz (2001) <ISBN:9780486414546>.

License GPL-3

Encoding UTF-8

RoxygenNote 7.3.1

Imports pracma

Suggests knitr, rmarkdown, testthat (>= 3.0.0)

Config/testthat/edition 3

VignetteBuilder knitr

URL <https://github.com/dhetting/GregoryQuadrature>

BugReports <https://github.com/dhetting/GregoryQuadrature/issues>

NeedsCompilation no

Author Dylan Hettinger [aut, cre, cph] (ORCID:
<<https://orcid.org/0009-0000-5769-2333>>),
Bengt Fornberg [aut] (ORCID: <<https://orcid.org/0000-0003-0014-6985>>)

Maintainer Dylan Hettinger <dhettinger@mines.edu>

Repository CRAN

Date/Publication 2024-04-23 08:40:02 UTC

Contents

Gregory_weights	2
Index	3

Gregory_weights	<i>Calculate the Gregory quadrature weights for equispaced integration. If f is a row vector containing the function values, the integral is approximated by the statement $f \%* \% t(w)$ where w are the returned weights. Translated from https://www.colorado.edu/amath/sites/default/files/attached-files/gregory.pdf.</i>
-----------------	--

Description

Calculate the Gregory quadrature weights for equispaced integration. If f is a row vector containing the function values, the integral is approximated by the statement $f \%* \% t(w)$ where w are the returned weights. Translated from <https://www.colorado.edu/amath/sites/default/files/attached-files/gregory.pdf>.

Usage

```
Gregory_weights(n_nodes, h, order)
```

Arguments

n_nodes	Total number of nodes
h	Step size
order	Order of accuracy desired. 2, 3, 4, ... (with 2 giving the trapezoidal rule). The value must satisfy $2 \leq \text{order} \leq n_nodes$

Value

The weights to be used for the successive function values

Examples

```
n_nodes = 11
order = 8
h = 2/(n_nodes-1)
x = pracma::linspace(-1, 1, n_nodes)
f = exp(x)

w = GregoryQuadrature::Gregory_weights(n_nodes, h, order)
int = f \%* \% w
# Exact value for integral
exact = exp(1) - exp(-1)

error = int - exact
```

Index

Gregory_weights, [2](#)