

Package ‘MN’

May 7, 2026

Type Package

Title Matrix Normal Distribution

Version 1.1

Date 2026-03-27

Author Michail Tsagris [aut, cre],
Alzeley Omar [ctb]

Maintainer Michail Tsagris <mtsagris@uoc.gr>

Depends R (>= 4.0)

Imports rangen, Rfast

Description Density computation, random matrix generation and maximum likelihood estimation of the matrix normal distribution. References: Pocuca N., Gal-
laugher M. P., Clark K. M. & McNicholas P. D. (2019). Assessing and Visualizing Matrix Vari-
ate Normality. <doi:10.48550/arXiv.1910.02859> and the relevant wikipedia page.

License GPL (>= 2)

NeedsCompilation no

Repository CRAN

Date/Publication 2026-03-27 17:40:23 UTC

Contents

MN-package	2
Density of the matrix normal distribution	2
Distance-Distance Plot	4
Kolmogorov-Smirnov test for matrix normality	5
Maximum likelihood estimation of the the matrix normal distribution	6
Random matrices simulation from the matrix normal distribution	7

Index	9
--------------	----------

MN-package

Matrix Normal Distribution

Description

Density computation, random matrix generation and maximum likelihood estimation of the matrix normal distribution. For references see: Pocuca N., Gallagher M. P., Clark K. M. & McNicholas P. D. (2019). Assessing and Visualizing Matrix Variate Normality. arXiv:1910.02859 and the relevant wikipedia page.

Details

Package: MN
Type: Package
Version: 1.1
Date: 2026-03-27

Maintainers

Michail Tsagris <mtsagris@uoc.gr>.

Author(s)

Michail Tsagris <mtsagris@uoc.gr> and Omar Alzeley <oazeley@uqu.edu.sa>

References

Pocuca, N., Gallagher, M. P., Clark, K. M., & McNicholas, P. D. (2019). Assessing and Visualizing Matrix Variate Normality. arXiv:1910.02859.

Density of the matrix normal distribution

Density of the matrix normal distribution

Description

Density of the matrix normal distribution.

Usage

`dmn(X, M, U, V, logged = FALSE)`

Arguments

X	A list with k elements, k matrices of dimension $n \times p$ each. In the case of one matrix only, this may be given as a numerical matrix and not as an element in a list.
M	The mean matrix of the distribution, a numerical matrix of dimensions $n \times p$.
U	The covariance matrix associated with the rows, a numerical matrix of dimensions $n \times n$.
V	The covariance matrix associated with the columns, a numerical matrix of dimensions $p \times p$.
logged	Should the logarithm of the density be computed?

Value

A numeric vector with the (logged) density values.

Author(s)

Omar Alzeley.

R implementation and documentation: Omar Alzeley <oazeley@uqu.edu.sa>.

References

https://en.wikipedia.org/wiki/Matrix_normal_distribution#Definition

Pocuca, N., Gallagher, M. P., Clark, K. M., & McNicholas, P. D. (2019). Assessing and Visualizing Matrix Variate Normality. arXiv:1910.02859.

See Also

[rmn](#), [mn.mle](#), [ddplot](#)

Examples

```
M <- as.matrix(iris[1:8, 1:4])
U <- cov( matrix( rnorm(100 * 8), ncol = 8 ) )
V <- cov( iris[1:50, 1:4] )
X <- rmn(10, M, U, V)
dmn(X, M, U, V, TRUE)
```

Distance-Distance Plot*Distance-Distance Plot*

Description

Distance-Distance Plot

Usage`ddplot(X, M, U, V)`**Arguments**

X	A list with k elements, k matrices of dimension $n \times p$ each. In the case of one matrix only, this may be given as a numerical matrix and not as an element in a list.
M	The mean matrix of the distribution, a numerical matrix of dimensions $n \times p$.
U	The covariance matrix associated with the rows, a numerical matrix of dimensions $n \times n$.
V	The covariance matrix associated with the columns, a numerical matrix of dimensions $p \times p$.

Details

The distance-distance plot is produced. This is a scatter plot of the Mahalanobis distances computed using the estimated parameters from the multivariate normal and matrix normal distribution. See Pocuca et al. (2019) for more details.

Value

A scatter plot of the Mahalanobis distances.

Author(s)

Michail Tsagris and Omar Alzeley.

R implementation and documentation: Michail Tsagris <mtsagris@uoc.gr> and Omar Alzeley <oazeley@uqu.edu.sa>.

References

Pocuca N., Gallagher M. P., Clark K. M. & McNicholas P. D. (2019). Assessing and Visualizing Matrix Variate Normality. arXiv:1910.02859.

See Also

[rmn](#), [mn.mle](#), [dmn](#), [ddkstest](#)

Examples

```
M <- as.matrix(iris[1:8, 1:4])
U <- cov( matrix( rnorm(100 * 8), ncol = 8 ) )
V <- cov( iris[1:50, 1:4] )
X <- rmn(100, M, U, V)
ddplot(X, M, U, V)
```

Kolmogorov-Smirnov test for matrix normality

Kolmogorov-Smirnov test for matrix normality

Description

Kolmogorov-Smirnov test for matrix normality

Usage

```
ddkstest(X, M, U, V, alpha = 0.05)
```

Arguments

X	A list with k elements, k matrices of dimension $n \times p$ each. In the case of one matrix only, this may be given as a numerical matrix and not as an element in a list.
M	The mean matrix of the distribution, a numerical matrix of dimensions $n \times p$.
U	The covariance matrix associated with the rows, a numerical matrix of dimensions $n \times n$.
V	The covariance matrix associated with the columns, a numerical matrix of dimensions $p \times p$.
alpha	The significance level for the test, set by default equal to 0.05.

Details

The Kolmogorov-Smirnov test for matrix normality is performed. See Pocuca (2019) for more details.

Value

A message. If the Kronecker product covariance structure is not present, the message reads "Reject" and "Not reject otherwise".

Author(s)

Michail Tsagris.

R implementation and documentation: Michail Tsagris <mtsagris@uoc.gr>.

References

Pocuca N., Gallagher M. P., Clark K. M. & McNicholas P. D. (2019). Assessing and Visualizing Matrix Variate Normality. arXiv:1910.02859.

See Also

[rmn](#), [mn.mle](#), [dmn](#), [ddplot](#)

Examples

```
M <- as.matrix(iris[1:8, 1:4])
U <- cov( matrix( rnorm(100 * 8), ncol = 8 ) )
V <- cov( iris[1:50, 1:4] )
X <- rmn(200, M, U, V)
ddkstest(X, M, U, V)
```

Maximum likelihood estimation of the the matrix normal distribution

Maximum likelihood estimation of the the matrix normal distribution

Description

Maximum likelihood estimation of the the matrix normal distribution.

Usage

```
mn.mle(X)
```

Arguments

X A list with k elements (k is the sample size), k matrices of dimension $n \times p$ each.

Value

A list including:

<code>runtime</code>	The runtime required for the whole fitting procedure.
<code>iters</code>	The number of iterations required for the estimation of the U and V matrices.
<code>M</code>	The estimated mean matrix of the distribution, a numerical matrix of dimensions $n \times p$.
<code>U</code>	The estimated covariance matrix associated with the rows, a numerical matrix of dimensions $n \times n$.
<code>V</code>	The estimated covariance matrix associated with the columns, a numerical matrix of dimensions $p \times p$.

Author(s)

Michail Tsagris.

R implementation and documentation: Michail Tsagris <mtsagris@uoc.gr>.

References

https://en.wikipedia.org/wiki/Matrix_normal_distribution#Definition

Pocuca N., Gallagher M. P., Clark K. M. & McNicholas P. D. (2019). Assessing and Visualizing Matrix Variate Normality. arXiv:1910.02859.

See Also

[dmn](#), [rmn](#), [ddplot](#)

Examples

```
M <- as.matrix(iris[1:8, 1:4])
U <- cov( matrix( rnorm(100 * 8), ncol = 8 ) )
V <- cov( iris[1:50, 1:4] )
X <- rmn(200, M, U, V)
mod <- mn.mle(X)
```

Random matrices simulation from the matrix normal distribution

Random matrices simulation from the matrix normal distribution

Description

Random matrices simulation from the matrix normal distribution.

Usage

```
rmn(k, M, U, V)
```

Arguments

k	The sample size, the number of matrices to simulate.
M	The mean matrix of the distribution, a numerical matrix of dimensions $n \times p$.
U	The covariance matrix associated with the rows, a numerical matrix of dimensions $n \times n$.
V	The covariance matrix associated with the columns, a numerical matrix of dimensions $p \times p$.

Value

A list with k elements, k matrices of dimension $n \times p$ each. These are the random matrices drawn from a matrix normal distribution.

Author(s)

Michail Tsagris.

R implementation and documentation: Michail Tsagris <mtsagris@uoc.gr>.

References

https://en.wikipedia.org/wiki/Matrix_normal_distribution#Definition

See Also

[dmn](#), [mn.mle](#), [ddplot](#)

Examples

```
M <- as.matrix(iris[1:8, 1:4])
U <- cov( matrix( rnorm(100 * 8), ncol = 8 ) )
V <- cov( iris[1:50, 1:4] )
X <- rmn(10, M, U, V)
```

Index

ddkstest, [4](#)
ddkstest (Kolmogorov-Smirnov test for matrix normality), [5](#)
ddplot, [3, 6–8](#)
ddplot (Distance-Distance Plot), [4](#)
Density of the matrix normal distribution, [2](#)
Distance-Distance Plot, [4](#)
dmn, [4, 6–8](#)
dmn (Density of the matrix normal distribution), [2](#)

Kolmogorov-Smirnov test for matrix normality, [5](#)

Maximum likelihood estimation of the the matrix normal distribution, [6](#)

MN-package, [2](#)
mn.mle, [3, 4, 6, 8](#)
mn.mle (Maximum likelihood estimation of the the matrix normal distribution), [6](#)

Random matrices simulation from the matrix normal distribution, [7](#)
rmn, [3, 4, 6, 7](#)
rmn (Random matrices simulation from the matrix normal distribution), [7](#)