

Package ‘MODISTools’

May 7, 2026

Title Interface to the 'MODIS Land Products Subsets' Web Services

Version 1.1.6

Description Programmatic interface to the Oak Ridge National Laboratories 'MODIS Land Products Subsets' web services (<https://modis.ornl.gov/data/modis_webservice.html>). Allows for easy downloads of 'MODIS' time series directly to your R workspace or your computer.

URL <https://github.com/bluegreen-labs/MODISTools>,
<https://bluegreen-labs.github.io/MODISTools/>

BugReports <https://github.com/bluegreen-labs/MODISTools/issues>

Depends R (>= 3.4)

Imports httr, utils, sf, terra, stats, memoise, jsonlite

License AGPL-3

Encoding UTF-8

LazyData true

ByteCompile true

RoxygenNote 7.3.2

Suggests knitr, markdown, covr, testthat, ggplot2, dplyr

VignetteBuilder knitr

NeedsCompilation no

Author Koen Hufkens [aut, cre] (ORCID:
<<https://orcid.org/0000-0002-5070-8109>>),
BlueGreen Labs [cph, fnd]

Maintainer Koen Hufkens <koen.hufkens@gmail.com>

Repository CRAN

Date/Publication 2026-01-14 14:50:07 UTC

Contents

| | |
|---------------------------|----|
| arcachon_lai | 2 |
| arcachon_lc | 2 |
| mt_bands | 3 |
| mt_batch_subset | 3 |
| mt_bbox | 5 |
| mt_dates | 6 |
| mt_products | 7 |
| mt_sites | 8 |
| mt_subset | 9 |
| mt_to_terra | 10 |
| sin_to_ll | 11 |

| | |
|--------------|-----------|
| Index | 13 |
|--------------|-----------|

| | |
|--------------|---------------------|
| arcachon_lai | <i>arcachon_lai</i> |
|--------------|---------------------|

Description

MODIS leaf area index (LAI) around the French town of Arcachon derived from the MODIS MOD15A2H product (band Lai_500m).

Usage

arcachon_lai

Format

A MODISTools tidy data frame

| | |
|-------------|--------------------|
| arcachon_lc | <i>arcachon_lc</i> |
|-------------|--------------------|

Description

MODIS land cover (IGBP) around the French town of Arcachon derived from the MODIS MCD12Q2 product (band LC_Type1).

Usage

arcachon_lc

Format

A MODISTools tidy data frame

| | |
|----------|-------------------------------------|
| mt_bands | <i>Download all available bands</i> |
|----------|-------------------------------------|

Description

Lists all available bands for a MODIS Land Products Subset product.

Usage

```
mt_bands(product)
```

Arguments

product a valid MODIS product name

Value

A data frame of all available bands for a MODIS Land Products Subsets products

See Also

[mt_products](#) [mt_sites](#) [mt_dates](#)

Examples

```
# list all available MODIS Land Products Subsets products
bands <- mt_bands(product = "MCD12Q2")
head(bands)
```

| | |
|-----------------|---|
| mt_batch_subset | <i>Batch download MODIS Land Products subsets</i> |
|-----------------|---|

Description

Lists all available dates for a MODIS Land Products Subset product at a particular location.

Usage

```
mt_batch_subset(
  df,
  product,
  band,
  start = "2000-01-01",
  end = format(Sys.time(), "%Y-%m-%d"),
  km_lr = 0,
  km_ab = 0,
  out_dir = tempdir(),
  internal = TRUE
)
```

Arguments

| | |
|----------|---|
| df | a CSV file or data frame holding locations and their sitenames to batch process with column names site_name, lat, lon holding the respective sitenames, latitude and longitude. When providing a CSV make sure that the data are comma separated. |
| product | a valid MODIS product name |
| band | band to download |
| start | start date |
| end | end date |
| km_lr | km left-right to sample |
| km_ab | km above-below to sample |
| out_dir | location where to store all data |
| internal | should the data be returned as an internal data structure TRUE or FALSE (default = TRUE) |

Value

A data frame combining meta-data and actual data values, data from different sites is concatenated into one large dataframe. Subsets can be created by searching on sitename.

See Also

[mt_sites](#) [mt_dates](#) [mt_bands](#) [mt_products](#) [mt_subset](#)

Examples

```
## Not run:
# create data frame with a site_name, lat and lon column
# holding the respective names of sites and their location
df <- data.frame("site_name" = paste("test",1:2))
df$lat <- 40
df$lon <- -110
```

```

print(df)

# test batch download
subsets <- mt_batch_subset(df = df,
                           product = "MOD11A2",
                           band = "LST_Day_1km",
                           internal = TRUE,
                           start = "2004-01-01",
                           end = "2004-03-31")

# the same can be done using a CSV file with
# a data structure similar to the dataframe above

write.table(df, file.path(tempdir(), "my_sites.csv"),
            quote = FALSE,
            row.names = FALSE,
            col.names = TRUE,
            sep = ",")

# test batch download form CSV
subsets <- mt_batch_subset(df = file.path(tempdir(), "my_sites.csv"),
                           product = "MOD11A2",
                           band = "LST_Day_1km",
                           internal = TRUE,
                           start = "2004-01-01",
                           end = "2004-03-31"
                           )

head(subsets)

## End(Not run)

```

mt_bbox

Converts lower-left sinusoidal coordinates to lat-lon sf bounding box

Description

Converts lower-left sinusoidal coordinates to lat-lon sf bounding box

Usage

```
mt_bbox(xllcorner, yllcorner, cellsize, nrows, ncols, transform = TRUE)
```

Arguments

| | |
|-----------|--|
| xllcorner | lower left x coordinate as provided by mt_subset |
| yllcorner | lower left y coordinate as provided by mt_subset |
| cellsize | cell size provided by mt_subset |
| nrows | cell size provided by mt_subset |

ncols cell size provided by [mt_subset](#)
 transform transform the bounding box from sin to lat long coordinates, TRUE or FALSE
 (default = TRUE)

See Also

[sin_to_ll](#), [mt_subset](#)

Examples

```
# Download some test data
subset <- mt_subset(product = "MOD11A2",
                    lat = 40,
                    lon = -110,
                    band = "LST_Day_1km",
                    start = "2004-01-01",
                    end = "2004-03-31",
                    progress = FALSE)

# convert sinusoidal to lat / lon
lat_lon <- sin_to_ll(subset$xllcorner, subset$yllcorner)

# bind with the original dataframe
subset <- cbind(subset, lat_lon)

# convert to bounding box
bb <- apply(subset, 1, function(x){
  mt_bbox(xllcorner = x['xllcorner'],
          yllcorner = x['yllcorner'],
          cellsize = x['cellsize'],
          nrows = x['nrows'],
          ncols = x['ncols'])
})

head(bb)
```

mt_dates

Download all available dates

Description

Lists all available dates for a MODIS Land Products Subset product at a particular location.

Usage

```
mt_dates(product, lat, lon, site_id, network)
```

Arguments

| | |
|---------|--|
| product | a valid MODIS product name |
| lat | latitude in decimal degrees |
| lon | longitude in decimal degrees |
| site_id | site id (overrides lat / lon) |
| network | the network for which to generate the site list, when not provided the complete list is provided |

Value

A data frame of all available dates for a MODIS Land Products Subsets products at the given location.

See Also

[mt_products](#) [mt_sites](#) [mt_bands](#)

Examples

```
# list all available MODIS Land Products Subsets products
bands <- mt_dates(product = "MOD11A2", lat = 40, lon = -110)
head(bands)
```

| | |
|-------------|--|
| mt_products | <i>Download all available products</i> |
|-------------|--|

Description

Lists all available MODIS Land Products Subset products.

Usage

```
mt_products()
```

Value

A data frame of all available MODIS Land Products Subsets products

See Also

[mt_bands](#) [mt_sites](#) [mt_dates](#)

Examples

```
# list all available MODIS Land Products Subsets products
products <- mt_products()
head(products)
```

mt_sites

Download all available fixed sites

Description

Lists all available MODIS Land Products Subset pre-processed sites

Usage

```
mt_sites(network)
```

Arguments

network the network for which to generate the site list, when not provided the complete list is provided

Value

A data frame of all available MODIS Land Products Subsets pre-processed sites

See Also

[mt_products](#) [mt_bands](#) [mt_dates](#)

Examples

```
# list all available MODIS Land Products Subsets products
sites <- mt_sites()
print(head(sites))
```

mt_subset

Download MODIS Land Products subsets

Description

Download a MODIS Land Products Subset product for a given point location buffered with a given amount of kilometers left-right, top-bottom for a given location (provided as latitude and longitude values).

Usage

```
mt_subset(
  product,
  band,
  lat,
  lon,
  start = "2000-01-01",
  end = format(Sys.time(), "%Y-%m-%d"),
  km_lr = 0,
  km_ab = 0,
  site_id,
  network,
  site_name = "sitename",
  out_dir = tempdir(),
  internal = TRUE,
  progress = TRUE
)
```

Arguments

| | |
|-----------|--|
| product | a valid MODIS product name |
| band | band or bands (as a character vector) to download |
| lat | latitude in decimal degrees |
| lon | longitude in decimal degrees |
| start | start date |
| end | end date |
| km_lr | km left-right to sample (rounded to the nearest integer) |
| km_ab | km above-below to sample (rounded to the nearest integer) |
| site_id | site id (overrides lat / lon) |
| network | the network for which to generate the site list, when not provided the complete list is provided |
| site_name | arbitrary site name used in writing data to file (default = sitename) |
| out_dir | path where to store the data if writing to disk (default = tempdir()) |

| | |
|----------|--|
| internal | should the data be returned as an internal data structure TRUE or FALSE (default = TRUE) |
| progress | show download progress |

Value

A data frame combining meta-data and actual data values.

See Also

[mt_sites](#) [mt_dates](#) [mt_bands](#) [mt_products](#) [mt_batch_subset](#)

Examples

```
# list all available MODIS Land Products Subsets products
# download data
subset <- mt_subset(product = "MOD11A2",
                    lat = 40,
                    lon = -110,
                    band = "LST_Day_1km",
                    start = "2004-01-01",
                    end = "2004-03-31",
                    progress = FALSE)

head(subset)
```

mt_to_terra

Convert tidy MODISTools data to terra SpatRaster

Description

Convert tidy MODISTools data to a terra SpatRaster for easy spatial processing and plotting.

Usage

```
mt_to_terra(df, reproject = FALSE, method = "bilinear")
```

Arguments

| | |
|-----------|--|
| df | a valid MODISTools data frame with a single band (filter for a particular band using the <code>dplyr filter()</code> function or base <code>subset()</code>) |
| reproject | reproject output to lat / long (default = FALSE) |
| method | character. Method used for estimating the new cell values of a SpatRaster. One of: near: nearest neighbor. This method is fast, and it can be the preferred method if the cell values represent classes. It is not a good choice for continuous values. This is used by default if the first layer of x is categorical. bilinear: bilinear interpolation. This is the default if the first layer of x is numeric (not categorical). cubic: cubic interpolation. cubicspline: cubic spline interpolation. |

Value

A terra SpatRaster populated with the tidy dataframe values

See Also

[mt_subset](#) [mt_batch_subset](#)

Examples

```
# list all available MODIS Land Products Subsets products
# download data
LC <- mt_subset(product = "MCD12Q1",
  lat = 48.383662,
  lon = 2.610250,
  band = "LC_Type1",
  start = "2005-01-01",
  end = "2005-12-30",
  km_lr = 2,
  km_ab = 2,
  site_name = "testsite",
  internal = TRUE,
  progress = FALSE)

head(LC)

# convert to raster
LC_r <- mt_to_terra(df = LC)
```

sin_to_ll

Convert sinusoidal coordinates to lat / lon

Description

A full description of the sinusoidal projection is provided on the lpdaac page: https://lpdaac.usgs.gov/dataset_discovery/modis and wikipedia: https://en.wikipedia.org/wiki/Sinusoidal_projection

Usage

```
sin_to_ll(x, y)
```

Arguments

| | |
|---|----------------------------------|
| x | sinusoidal x coordinate (vector) |
| y | sinusoidal y coordinate (vector) |

See Also[mt_bbox](#)**Examples**

```
# Download some test data
subset <- mt_subset(product = "MOD11A2",
                   lat = 40,
                   lon = -110,
                   band = "LST_Day_1km",
                   start = "2004-01-01",
                   end = "2004-03-31",
                   progress = FALSE)

# convert sinusoidal to lat / lon
lat_lon <- sin_to_ll(subset$xllcorner, subset$yllcorner)

# bind with the original dataframe
subset <- cbind(subset, lat_lon)
head(subset)
```

Index

* datasets

arcachon_lai, [2](#)

arcachon_lc, [2](#)

arcachon_lai, [2](#)

arcachon_lc, [2](#)

mt_bands, [3](#), [4](#), [7](#), [8](#), [10](#)

mt_batch_subset, [3](#), [10](#), [11](#)

mt_bbox, [5](#), [12](#)

mt_dates, [3](#), [4](#), [6](#), [7](#), [8](#), [10](#)

mt_products, [3](#), [4](#), [7](#), [7](#), [8](#), [10](#)

mt_sites, [3](#), [4](#), [7](#), [8](#), [10](#)

mt_subset, [4-6](#), [9](#), [11](#)

mt_to_terra, [10](#)

sin_to_ll, [6](#), [11](#)