

Package ‘MetSizeR’

May 7, 2026

Title A Shiny App for Sample Size Estimation in Metabolomic Experiments

Version 2.0.0

Date 2021-08-20

Description Provides a Shiny application to estimate the sample size required for a metabolomic experiment to achieve a desired statistical power. Estimation is possible with or without available data from a pilot study.

License GPL (≥ 3)

Encoding UTF-8

RoxygenNote 7.1.1

Imports dplyr, ggplot2, MetabolAnalyze, Rfast, shiny, shinythemes, stats, tools, utils, vroom

Suggests rmarkdown, knitr

VignetteBuilder knitr

NeedsCompilation no

Author Kate Finucane [aut, cre],
Gift Nyamundanda [aut],
Isobel Claire Gormley [aut],
Yue Fan [aut],
William M Gallagher [aut],
Lorraine Brennan [aut]

Maintainer Kate Finucane <kate.finucane@ucdconnect.ie>

Repository CRAN

Date/Publication 2021-08-20 13:20:02 UTC

Contents

metsize	2
MetSizeR	3
Index	4

metsize

*Metsize***Description**

Function to estimate sample size required to achieve a desired statistical power.

Usage

```
metsize(
  pilot = pilot,
  n1 = 4,
  n2 = 4,
  p = 200,
  prop = 0.25,
  covars = covars,
  ncovar = 0,
  model = "PPCA",
  plot.prop = FALSE,
  target.fdr = 0.05,
  Targeted = FALSE
)
```

Arguments

<code>pilot</code>	A matrix containing pilot data, if available.
<code>n1</code>	Sample group 1 minimum sample size to consider.
<code>n2</code>	Sample group 2 minimum sample size to consider.
<code>p</code>	Number of bins in the data.
<code>prop</code>	Expected proportion of significant bins.
<code>covars</code>	Matrix of covariates, if available. Categorical covariates should be included as X-1 dummy variables for a covariate with X levels.
<code>ncovar</code>	The number of covariates present. For Z numeric covariates and Y categorical covariates with X total levels, this should be Z + X - Y.
<code>model</code>	The chosen model.
<code>plot.prop</code>	TRUE/FALSE should sample size be calculated for varying proportions of significant bins?
<code>target.fdr</code>	The desired false discovery rate.
<code>Targeted</code>	TRUE/FALSE is the experiment intended as targeted analysis?

Value

List containing the estimated sample size with the per-group sample size breakdown, results of FDR calculations for each sample size tested, results for varying the proportion of significant metabolites, the number of bins input, the number of covariates input, the model type used, the input minimum sample sizes for group 1 and group 2, and the desired FDR.

References

G. Nyamundanda, I. C. Gormley, Y. Fan, W. M. Gallagher and L. Brennan, BMC Bioinformatics, 2013, 14, 338.

Examples

```
metsize(pilot = NULL, n1 = 4, n2 = 4, p = 200, prop = 0.2, covars = NULL,  
        ncovar = 0, model = "PPCA", plot.prop = FALSE, target.fdr = 0.10,  
        Targeted = FALSE)  
metsize(pilot = NULL, n1 = 6, n2 = 4, p = 100, prop = 0.1, covars = NULL,  
        ncovar = 2, model = "PPCCA", plot.prop = FALSE, target.fdr = 0.05,  
        Targeted = TRUE)
```

MetSizeR

MetsizeR Launcher

Description

Launches the Shiny application for the MetsizeR functionality. The interactive application allows estimation of the sample size required for a metabolomic experiment to achieve a desired statistical power.

Usage

```
MetSizeR()
```

References

G. Nyamundanda, I. C. Gormley, Y. Fan, W. M. Gallagher and L. Brennan, BMC Bioinformatics, 2013, 14, 338.

Index

metsize, [2](#)
MetSizeR, [3](#)