

Package ‘MolgenisAuth’

May 7, 2026

Title 'OpenID Connect' Discovery and Authentication

Description Discover 'OpenID Connect' endpoints and authenticate using device flow. Used by 'MOLGENIS' packages.

Version 1.0.0

Maintainer Mariska Slofstra <m.k.slofstra@umcg.nl>

Imports urltools (>= 1.7.0), httr2(>= 1.0.1), assertthat

Depends R (>= 4.1.0)

URL <https://github.com/molgenis/molgenis-r-auth/>,
<https://molgenis.github.io/molgenis-r-auth/>

BugReports <https://github.com/molgenis/molgenis-r-auth/issues/>

License GPL-3

Encoding UTF-8

RoxygenNote 7.3.2

Suggests testthat (>= 3.2.0), mockery

NeedsCompilation no

Author Fleur Kelpin [aut] (ORCID: <<https://orcid.org/0000-0003-1527-5130>>),
Tommy de Boer [aut] (ORCID: <<https://orcid.org/0000-0002-4492-7225>>),
Sido Haakma [aut] (ORCID: <<https://orcid.org/0000-0003-1278-9144>>),
Mariska Slofstra [aut, cre] (ORCID:
<<https://orcid.org/0000-0002-0400-0468>>),
Tim Cadman [aut] (ORCID: <<https://orcid.org/0000-0002-7682-5645>>),
MOLGENIS org [cph, fnd]

Repository CRAN

Date/Publication 2025-07-21 13:52:08 UTC

Contents

device_flow_auth	2
discover	2

Index	4
--------------	----------

device_flow_auth *Authenticate using device flow*

Description

Get an ID token using the [OpenIDConnect Device Flow](#).

Usage

```
device_flow_auth(endpoint, client_id, scopes = c("openid", "offline_access"))
```

Arguments

endpoint	An list with a device endpoint specified in it
client_id	The client ID for which the token should be obtained
scopes	the requested scopes, default to c("openid", "offline_access")

Value

The credentials retrieved from the token endpoint

Examples

```
## Not run:
endpoint <- discover("https://auth.molgenis.org")
device_flow_auth(endpoint, "b396233b-cdb2-449e-ac5c-a0d28b38f791")

## End(Not run)
```

discover *Discover OpenID Connect Endpoints*

Description

Performs OpenID Connect discovery on an ID Provider.

Usage

```
discover(auth_server)
```

Arguments

auth_server	the server
-------------	------------

Value

An list with the discovered endpoints.

Examples

```
## Not run:  
discover("https://auth.molgenis.org")  
discover("https://accounts.google.com")  
  
## End(Not run)
```

Index

`device_flow_auth`, [2](#)
`discover`, [2](#)