

Package ‘PKPDsim’

May 7, 2026

Type Package

Title Tools for Performing Pharmacokinetic-Pharmacodynamic Simulations

Version 1.4.1

Date 2025-04-09

Depends R (>= 4.0.0)

Imports Rcpp (>= 1.0.13), BH, data.table, stringr, MASS, randtoolbox,
jsonlite, stats, parallel, magrittr

Suggests httr, testthat (>= 3.0.0), mockery, knitr, rmarkdown

LinkingTo BH, Rcpp (>= 1.0.13)

Description Simulate dose regimens for pharmacokinetic-pharmacodynamic (PK-PD) models described by differential equation (DE) systems. Simulation using ADVAN-style analytical equations is also supported (Abuhelwa et al. (2015) <[doi:10.1016/j.vascn.2015.03.004](https://doi.org/10.1016/j.vascn.2015.03.004)>).

License MIT + file LICENSE

URL <https://github.com/InsightRX/PKPDsim>,
<https://insightrx.github.io/PKPDsim/>

Language en-US

LazyData TRUE

RoxygenNote 7.3.2

Config/testthat/edition 3

Config/Needs/website tidyverse, nlmixr2

Encoding UTF-8

VignetteBuilder knitr

NeedsCompilation yes

Author Ron Keizer [aut, cre],
Jasmine Hughes [aut],
Dominic Tong [aut],
Kara Woo [aut],
Jordan Brooks [aut],
InsightRX [cph, fnd]

Maintainer Ron Keizer <ron@insight-rx.com>

Repository CRAN

Date/Publication 2025-04-17 06:40:05 UTC

Contents

add_quotes	3
add_ruv	4
add_ruv_to_quantile	4
adherence_binomial	5
adherence_markov	5
advan	6
advan_create_data	6
advan_parse_output	7
advan_process_infusion_doses	7
apply_duration_scale	8
apply_lagtime	9
available_default_literature_models	9
calculate_parameters	10
calc_auc_analytic	11
calc_dydP	12
calc_ss_analytic	12
check_obs_input	13
compile_sim_cpp	14
covariates_table_to_list	15
covariate_last_obs_only	16
cv_to_omega	16
detect_ode_syntax	17
f_cov	17
get_fixed_parameters	18
get_model_info	18
get_ode_model_size	19
get_parameters_from_code	20
get_var_y	20
ifelse0	22
install_default_literature_model	22
is_positive_definite	23
join_cov_and_par	23
join_regimen	24
lower_triangle_mat_size	24
merge_regimen	25
model_from_api	25
model_library	26
mvrnorm2	27
na_locf	27
new_adherence	28
new_covariate	28

new_covariate_model	29
new_ode_model	30
new_regimen	33
nlmixr_parse_parameters	34
nm_to_regimen	35
pkdata	35
pkpdsim_to_nlmixr	36
pop_regimen	37
print_list	37
read_model_json	38
regimen_to_nm	38
reparametrize	39
search_replace_in_file	39
shift_regimen	40
sim	40
sim_core	44
sim_ode	44
sim_ode_shiny	45
table_to_list	45
test_model	46
test_pointer	46
translate_ode	47
triangle_to_full	47
Index	48

add_quotes	<i>Put vector values in quotes</i>
------------	------------------------------------

Description

Put vector values in quotes

Usage

```
add_quotes(x, quote = "double")
```

Arguments

x	vector of string / numeric
quote	what type of quotes (double or single)

Value

Character vector of input with quotation marks around each value

add_ruv	<i>Add residual variability to the dependent variable</i>
---------	---

Description

Add residual variability to the dependent variable

Usage

```
add_ruv(x, ruv = list(), obs_type = 1)
```

Arguments

x	dependent value without residual variability
ruv	list specifying proportional, additive and/or exponential errors (prop, add, exp)
obs_type	vector of observation types

Value

Input vector with residual variability added

add_ruv_to_quantile	<i>Calculate the increase in a specific quantile for a distribution on y when residual variability is added</i>
---------------------	---

Description

Calculate the increase in a specific quantile for a distribution on y when residual variability is added

Usage

```
add_ruv_to_quantile(y, sd_y, log_scale = FALSE, q = NULL, ruv = list(), ...)
```

Arguments

y	y with
sd_y	standard deviation of y without residual variability added. Will add normally distributed variability (potentially on log-scale).
log_scale	add variability on log scale (FALSE by default, DEPRECATED!).
q	quantile
ruv	list of residual variability (prop and add)
...	passed arguments

Value

Numeric vector of y values with residual variability

adherence_binomial	<i>Binomial adherence</i>
--------------------	---------------------------

Description

Model adherence as a binomial probability at the time of each occasion.

Usage

```
adherence_binomial(n = 100, prob)
```

Arguments

n	number of occasions
prob	binomial probability

Value

Returns a vector of length n containing values 0 (non-adherent) or 1 (adherent).

Numeric vector of length n

adherence_markov	<i>Markov adherence model</i>
------------------	-------------------------------

Description

Model adherence as a markov chain model, based on the probability of staying adherent and of becoming adherent once non-adherent. Assumes all patients start adherent.

Usage

```
adherence_markov(n = 100, p11 = 0.9, p01 = 0.7)
```

Arguments

n	number of occasions
p11	probability of staying adherent
p01	probability of going from non-adherent to adherent state

Value

Returns a vector of length n containing values 0 (non-adherent) or 1 (adherent).

Numeric vector of length n

advan	<i>ADVAN-style functions to calculate linear PK systems</i>
-------	---

Description

ADVAN-style functions to calculate linear PK systems

Usage

```
advan(model, cpp = TRUE)
```

Arguments

model	Standard linear PK model, e.g. 1cmt_iv_bolus.
cpp	use C++-versions of model (~50x faster than R implementations)

Value

Model function

advan_create_data	<i>Create ADVAN-style dataset</i>
-------------------	-----------------------------------

Description

Create ADVAN-style dataset

Usage

```
advan_create_data(
  regimen,
  parameters,
  cmts = 5,
  t_obs = NULL,
  covariates = NULL,
  covariate_model = NULL
)
```

Arguments

regimen	PKPDsim regimen
parameters	list of parameters
cmts	number of compartments, minimum is 1. Default is 5, which is enough for most linear PK models. It is OK to have more compartments available than are actually being used.

t_obs add observation timepoints to dataset
 covariates covariate list
 covariate_model covariate model equations, written in C

Value

Data frame of ADVAN-style data

advan_parse_output *Internal function to parse the raw output from ADVAN-style functions*

Description

Internal function to parse the raw output from ADVAN-style functions

Usage

advan_parse_output(data, cmts = 1, t_obs, extra_t_obs = TRUE, regimen)

Arguments

data simulation output data
 cmts number of compartments
 t_obs observation times
 extra_t_obs leave extra added dose times in dataset?
 regimen PKPDsim regimen

Value

Data frame containing parsed simulation data

advan_process_infusion_doses *Add column RATEALL to ADVAN-style dataset to handle infusions*

Description

Function adapted from code from Abuhelwa, Foster, Upton JPET 2015. cleaned up and somewhat optimized. Can potentially be optimized more.

Usage

advan_process_infusion_doses(data)

Arguments

data ADVAN-style dataset, e.g. created using `advan_create_data`.

Value

Data frame containing additional RATEALL column.

References

Abuhelwa, A. Y., Foster, D. J. R., Upton, R. N. (2015) ADVAN-style analytical solutions for common pharmacokinetic models. *J Pharmacol Toxicol Methods* 73:42-8. DOI: 10.1016/j.vascn.2015.03.004

apply_duration_scale *Apply infusion duration scale to a regimen*

Description

E.g. see Centanni et al. *Clin Pharmacokinet* 2024. An estimated scaling factor for the length of the infusion was applied there in a model for vincristine. This is likely most relevant for very short infusions.

Usage

```
apply_duration_scale(
  regimen,
  duration_scale = NULL,
  parameters = NULL,
  cmt_mapping = NULL
)
```

Arguments

regimen PKPDsim regimen
duration_scale infusion length scale.
parameters parameter list, required if the duration scale is specified as a parameter.
cmt_mapping map of administration types to compartments, e.g. `list("oral" = 1, "infusion" = 2, "bolus" = 2)`.

Details

Implementation is similar to handling of `lagtime`, i.e. the regimen that is the input for the simulation function is updated.

Value

Original regimen with infusion lengths scaled by a factor

apply_lagtime	<i>Apply lagtime to a regimen</i>
---------------	-----------------------------------

Description

Apply lagtime to a regimen

Usage

```
apply_lagtime(regimen, lagtime, parameters, cmt_mapping = NULL)
```

Arguments

regimen	PKPDsim regimen
lagtime	lagtime object, either single value / parameter name or vector of values/parameter names for all compartments.
parameters	parameter list, required if parameters are specified.
cmt_mapping	map of administration types to compartments, e.g. <code>list("oral" = 1, "infusion" = 2, "bolus" = 2)</code> .

Value

Original regimen with lagtime added to dose times

available_default_literature_models	<i>See models from the literature available for installation</i>
-------------------------------------	--

Description

See models from the literature available for installation

Usage

```
available_default_literature_models()
```

Value

Returns a character vector of models available for installation

Examples

```
available_default_literature_models()
```

calculate_parameters *Calculate model-specific variables using a dummy call to sim_ode()*

Description

This is a convenience function for PKPDsim users, it is not used inside the `sim_ode()` function in any way. This function is $CL * (WT/70) * (1/CR)$ it can be used to calculate CL_i without having to write that function a second time in R.

Usage

```
calculate_parameters(
  ode = NULL,
  parameters = NULL,
  covariates = NULL,
  include_parameters = TRUE,
  include_variables = TRUE,
  regimen = NULL,
  t_obs = NULL,
  ...
)
```

Arguments

ode	PKPDsim model object
parameters	parameter list
covariates	covariate list. Make sure to include covariates at the right time point, since only last observed covariate values are used.
include_parameters	boolean, include parameters?
include_variables	boolean, include variables?
regimen	optional, provide a regimen object for the computation of the effective parameters. This is only relevant for models for which parameters depend on the dose or administration type, which is rare.
t_obs	optional, provide timepoint(s) at which to compute effective parameters. This is only relevant for models with time-varying fixed-effects. If unspecified, will evaluate parameters at $t=0$.
...	arguments to pass on to simulation function

Value

List of model-specific variables

calc_auc_analytic	<i>Convenience function to calculate the AUC based on PK model parameters at any given moment, for linear iv models.</i>
-------------------	--

Description

Convenience function to calculate the AUC based on PK model parameters at any given moment, for linear iv models.

Usage

```
calc_auc_analytic(
  f = c("1cmt_iv_infusion", "2cmt_iv_infusion", "3cmt_iv_infusion", "1cmt_iv_bolus",
        "2cmt_iv_bolus", "3cmt_iv_bolus"),
  parameters,
  regimen = NULL,
  dose = NULL,
  interval = NULL,
  t_inf = NULL,
  t_obs = c(0, 24, 48, 72),
  ...
)
```

Arguments

f	analytic model to use, show available models using <code>advan()</code>
parameters	list of parameter estimates. Requires CL/V for 1-compartment models, CL/V/Q/V2 for 2-compartment models, and CL/V/Q/V2/Q2/V3 for 3-compartment models.
regimen	PKPDsim regimen created using <code>new_regimen</code> . Not required, regimen can also be specified using <code>dose</code> , <code>interval</code> , and <code>t_inf</code> .
dose	dosing amount for regimen (single value). Only used if no regimen supplied.
interval	dosing interval for regimen (single value). Only used if no . regimen supplied.
t_inf	infusion length for regimen (single value). Only used if no regimen supplied.
t_obs	vector of observation times for AUC
...	optional arguments passed to <code>advanc_create_data()</code>

Value

a data.frame with t and auc

Examples

```
dat <- calc_auc_analytic(
  f = "2cmt_iv_infusion",
  regimen = new_regimen(
```

```

    amt = 1000, n = 10, type = "infusion",
    t_inf = 1, interval = 24
  ),
  parameters = list(CL = 5, V = 50, Q = 8, V2 = 150)
)

```

calc_dydp

Calculate derivative

Description

Calculate derivative

Usage

```
calc_dydp(dy, y, rel_delta, log_y)
```

Arguments

dy	dy
y	dependent value
rel_delta	relative delta
log_y	logical indicating if the dependent variable is log transformed

calc_ss_analytic

Returns the state of a linear PK system at steady state (trough) using analytics equations (so for linear PK systems only).

Description

Basically it performs a PK simulation using analytic equations instead of ODEs to steady state (n=45 days, increased if needed).

Usage

```

calc_ss_analytic(
  f = "1cmt_oral",
  dose,
  interval,
  t_inf = NULL,
  model,
  parameters,
  covariates = NULL,
  map = NULL,
)

```

```

    n_days = 45,
    n_transit_compartments = 0,
    auc = FALSE
  )

```

Arguments

f	analytic equation to use, must be one of names(advan_funcs)
dose	dose
interval	interval
t_inf	infusion time
model	PKPDsim model
parameters	parameters list
covariates	covariates list
map	list for remapping parameters, ex: <code>list(CL = "CL", V = "V")</code>
n_days	number of days at which to assume steady state. Default is 45.
n_transit_compartments	number of transit compartments, will insert n compartments between the first (dose) compartment and the second (central) compartment.
auc	add (empty) AUC compartment at end of state vector?

Details

It can also be used for models with transit compartments, however, the assumption is made that at the end of the dosing interval the amount in the transit compartments is negligible (0).

Value

State vector of a linear pharmacokinetic system at steady state

check_obs_input	<i>Checks obs input for valid combinations of cmt, var, scale</i>
-----------------	---

Description

Checks obs input for valid combinations of cmt, var, scale

Usage

```
check_obs_input(obs)
```

Arguments

obs	specified observation object including at least a description of which variable(s) are associated with a particular compartment, e.g. <code>list(variable="CONC", scale="1")</code> .
-----	---

 compile_sim_cpp

Compile ODE model to c++ function

Description

Compile ODE model to c++ function

Usage

```

compile_sim_cpp(
  code,
  dose_code,
  pk_code,
  size,
  p,
  cpp_show_code,
  code_init = NULL,
  state_init = NULL,
  declare_variables = NULL,
  variables = NULL,
  covariates = NULL,
  obs = NULL,
  dose = NULL,
  iov = NULL,
  compile = TRUE,
  verbose = FALSE,
  as_is = FALSE
)

```

Arguments

code	C++ code ODE system
dose_code	C++ code per dose event
pk_code	C++ code per any event (similar to \$PK)
size	size of ODE system
p	parameters (list)
cpp_show_code	show output c++ function?
code_init	code for initialization of state
state_init	state init vector
declare_variables	variable declaration for all required variables (including user-specified)
variables	only the user-specified variables
covariates	covariates specification
obs	observation specification

dose	dose specification
iov	iov specification
compile	compile or not?
verbose	show more output
as_is	use C-code as-is, don't substitute line-endings or shift indices

Value

List containing ODE definition in C++ code and simulation function

```
covariates_table_to_list
      Convert covariate table specified as data.frame
```

Description

Can handle time-varying data too, if t or time is specified as column

Usage

```
covariates_table_to_list(covariates_table, covariates_implementation = list())
```

Arguments

```
covariates_table
      data.frame`` with covariates in columns. Potentially with idandt'
      columns
covariates_implementation
      list with implementation method per covariate
```

Value

List of covariates

covariate_last_obs_only
Use only last observed covariate values

Description

Use only last observed covariate values

Usage

covariate_last_obs_only(covariates)

Arguments

covariates covariates object

Value

List containing same elements as input covariate object but including only the last value for each covariate

cv_to_omega *Create lower-diagonal omega matrix from CV for parameter estimates*

Description

Create lower-diagonal omega matrix from CV for parameter estimates

Usage

cv_to_omega(par_cv = NULL, parameters = NULL)

Arguments

par_cv list of parameter CVs
parameters list of parameters

Value

a vector describing the lower triangle of the omega (between-subject variability) matrix

See Also

[sim_ode](#)

detect_ode_syntax	<i>Auto-detect the syntax for the ODE code</i>
-------------------	--

Description

Either PKPDsim or RxODE

Usage

```
detect_ode_syntax(code)
```

Arguments

code character string with ODE code

Value

List with elements from and to indicating the syntax for the ODE code

f_cov	<i>covariate function builder</i>
-------	-----------------------------------

Description

covariate function builder

Usage

```
f_cov(...)
```

Arguments

... parameters to pass to cov

Value

Covariate function

get_fixed_parameters *Get fixed parameters from model definition.*

Description

Get fixed parameters listed in model definition. This function is used when parsing model specifications before the model has been compiled. Please see [get_model_fixed_parameters] for accessing fixed parameters from a model that has already been built.

Usage

```
get_fixed_parameters(def)
```

Arguments

def Model definition as output by [read_model_json\(\)](#)

get_model_info *Functions for getting information about a model*

Description

PKPDsim models encode information about using the model that can be helpful for working with the model. This family of functions provides an easier API for accessing useful information. See also `attributes(model)` for less commonly used model metadata. Functions will return NULL if the requested field is not available.

Usage

```
get_model_parameters(model)
get_model_covariates(model)
get_model_fixed_parameters(model)
get_model_structure(model)
get_model_linearity(model)
get_model_auc_compartment(model)
get_model_iov(model)
```

Arguments

model PKPDsim model

Value

get_model_parameters: returns a vector of PK parameter names

get_model_covariates: returns a vector of covariate names

get_model_fixed_parameters: returns a vector of names of parameters that are not associated with inter-individual or inter-occasion variability.

get_model_structure: returns a single string indicating model structure. E.g., "1cmt_iv", "2cmt_oral".

get_model_linearity: returns a single string indicating model linearity. E.g., "linear" or "nonlinear".

get_model_auc_compartment: returns the index of the final compartment, which is conventionally the AUC compartment. Note: will not detect if the final compartment is actually encoded to describe AUC.

get_model_iov: returns information about the IOV structure. For models without IOV, returns a single field (`list(n_bins = 1)`). Models with IOV will return additional fields: `n_bins`, `bin durations`, and `CV` associated with each PK parameter.

get_ode_model_size	<i>Get the number of states in the ODE from the code code C++ code for model</i>
--------------------	--

Description

Get the number of states in the ODE from the code code C++ code for model

Usage

```
get_ode_model_size(code)
```

Arguments

code	C++ code
------	----------

Value

Number of states in the ODE model

get_parameters_from_code
Get model parameters from code

Description

Get model parameters from code

Usage

```
get_parameters_from_code(code, state_init, declare_variables = NULL)
```

Arguments

code	code
state_init	state init vector
declare_variables	declared variables

Value

Vector of parameter names

get_var_y
Get expected variance/sd/ci of dependent variable based on PKPDsim model, parameters, and regimen

Description

Get expected variance/sd/ci of dependent variable based on PKPDsim model, parameters, and regimen

Usage

```
get_var_y(
  model = NULL,
  parameters = list(),
  regimen = list(),
  t_obs = c(1:48),
  obs_comp = NULL,
  obs_variable = NULL,
  omega = c(0.1, 0.05, 0.1),
  omega_full = NULL,
  n_ind = NULL,
  ruv = NULL,
```

```

y = NULL,
rel_delta = 1e-04,
method = "delta",
sequence = NULL,
auc = FALSE,
sd = TRUE,
q = NULL,
in_parallel = FALSE,
n_cores = 3,
return_all = FALSE,
...
)

```

Arguments

model	model, created using <code>PKPDsim::new_ode_model()</code>
parameters	parameters list
regimen	regimen, as created using <code>PKPDsim::new_regimen()</code>
t_obs	vector of observation times
obs_comp	observation compartment. If NULL will be "obs" (default)
obs_variable	observation variable. If NULL, will be ignored, otherwise will override obs_comp.
omega	triangle omega block
omega_full	full omega block
n_ind	number of individuals to simulate with sim method
ruv	residual variability, supplied as a named list, ex: <code>list(prop = 0, add = 0, exp = 0)</code>
y	vector of observations. If NULL, then a new simulation will be performed.
rel_delta	rel_delta
method	method, delta or sim
sequence	for simulations, if not NULL the pseudo-random sequence to use, e.g. "halton" or "sobol". See <code>mvrnorm2</code> for more details.
auc	is AUC?
sd	return as standard deviation (TRUE) or variance (FALSE)
q	return vector of quantiles instead of sd/var. Will return parametric quantiles when delta-method is used, non-parametric for simulation-based methods.
in_parallel	run simulations in parallel?
n_cores	if run in parallel, on how many cores?
return_all	return object with all relevant information?
...	passed on to <code>sim_ode()</code>

Value

Vector of standard deviations or variances (or quantiles thereof) for dependent value variable

ifelse0	<i>ifelse function but then based on whether value is NULL or not</i>
---------	---

Description

ifelse function but then based on whether value is NULL or not

Usage

```
ifelse0(value = NULL, alternative = NULL, allow_null = FALSE)
```

Arguments

value	metadata list object
alternative	alternative value
allow_null	can the alternative be NULL?

Value

value if non-NULL; alternative otherwise

install_default_literature_model	<i>Install default literature model</i>
----------------------------------	---

Description

A very lightweight wrapper for `model_from_api` that installs previously published models packaged within PKPDSim.

Usage

```
install_default_literature_model(model, ...)
```

Arguments

model	Name of model, e.g., "pk_busulfan_mccune". See available_default_literature_models()
...	arguments passed onto <code>model_from_api</code> . For fine-grain control, it is better to install models directly from model_from_api() or new_ode_model() .

Examples

```
## Not run:
install_default_literature_model("pk_busulfan_mccune")

## End(Not run)
```

is_positive_definite *Is matrix positive definite*

Description

Is matrix positive definite

Usage

```
is_positive_definite(x)
```

Arguments

x matrix, specified either as vector of lower triangle, or full matrix (as matrix class)

Value

TRUE if x is positive definite; FALSE otherwise.

join_cov_and_par *Combines covariates and parameters into a single list, useful for reparametrization of the model.*

Description

Combines covariates and parameters into a single list, useful for reparametrization of the model.

Usage

```
join_cov_and_par(covs, pars)
```

Arguments

covs covariates object
pars model parameters, such as the output of the parameters() call from a model library.

Value

List containing covariates and parameters

join_regimen	<i>Join two dosing regimens</i>
--------------	---------------------------------

Description

Join two dosing regimens

Usage

```
join_regimen(
  regimen1 = NULL,
  regimen2 = NULL,
  interval = NULL,
  dose_update = NULL,
  t_dose_update = NULL,
  continuous = FALSE
)
```

Arguments

regimen1	first regimen
regimen2	second regimen
interval	interval between regimen1 and regimen2 (if dose_update not specified)
dose_update	dose number at which to override regimen1 with regimen 2 (if interval not specified)
t_dose_update	dose time from which to update regimen
continuous	for joining continuous infusions

Value

Joined regimen

lower_triangle_mat_size	<i>Size of the lower triangle of the matrix</i>
-------------------------	---

Description

Size of the lower triangle of the matrix

Usage

```
lower_triangle_mat_size(mat)
```

Arguments

mat omega matrix as a vector

merge_regimen *Merge two regimens together.*

Description

In contrast to `join_regimen`, which joins two consecutive regimens together, `merge_regimen` merges two or more regimens given at the same time. This can e.g. be used to define regimens for multi-drug models.

Usage

```
merge_regimen(regimens)
```

Arguments

regimens List of PKPDsim regimens created with `new_regimen`.

Value

Merged regimens

model_from_api *Load model definition from API, and compile to R library*

Description

Load model definition from API, and compile to R library

Usage

```
model_from_api(
  url,
  model = NULL,
  nonmem = NULL,
  verbose = TRUE,
  get_definition = FALSE,
  to_package = FALSE,
  force = FALSE,
  install_all = FALSE,
  ...
)
```

Arguments

url	URL or file path to JSON representation of model
model	model id (used in messages)
nonmem	URL or file path to NONMEM file
verbose	verbosity (T/F)
get_definition	return only the model definition, do not compile
to_package	compile to package?
force	force install even if same version number of model already installed.
install_all	force install all, even if model inactive
...	arguments passed to <code>new_ode_model()</code> function

Value

Model object created with `new_ode_model()`

model_library	<i>Model library</i>
---------------	----------------------

Description

Model library

Usage

```
model_library(name = NULL)
```

Arguments

name	name of model in library. If none specified, will show list of available models.
------	--

Value

List containing information about the named model

mvrnorm2 *More powerful multivariate normal sampling function*

Description

Besides standard multivariate normal sampling (mvrnorm), allows exponential multivariate normal and quasi-random multivariate normal (using the randtoolbox) all using the same interface.

Usage

```
mvrnorm2(n, mu, Sigma, exponential = FALSE, sequence = NULL, ...)
```

Arguments

n	number of samples
mu	mean
Sigma	covariance matrix
exponential	exponential distribution (i.e. multiply mu by exponential of sampled numbers)
sequence	any sequence available in the randtoolbox, e.g. halton, or sobol
...	parameters passed to mvrnorm or randtoolbox sequence generator

Value

Multivariate normal samples

na_locf *Fill in NAs with the previous non-missing value*

Description

Inspired by zoo::na.locf0

Usage

```
na_locf(object, fromLast = FALSE)
```

Arguments

object	an object
fromLast	logical. Causes observations to be carried backward rather than forward. Default is FALSE.

Value

Original object with NAs filled in

new_adherence	<i>Probabilistically model adherence</i>
---------------	--

Description

Model the drug adherence using either a binomial probability distribution or a markov chain model based on the probability of staying adherent and of becoming adherent once non-adherent.

Usage

```
new_adherence(  
  n = 100,  
  type = c("markov", "binomial"),  
  p_markov_remain_ad = 0.75,  
  p_markov_become_ad = 0.75,  
  p_binom = 0.7  
)
```

Arguments

n	number of occasions to simulate
type	type of adherence simulation, either "markov" or "binomial"
p_markov_remain_ad	markov probability of staying adherent
p_markov_become_ad	markov probability of going from non-adherent to adherent state
p_binom	binomial probability of being adherent

Value

Returns a vector of length n containing values 0 (non-adherent) or 1 (adherent).

Numeric vector of length n

new_covariate	<i>New covariate</i>
---------------	----------------------

Description

Describe data for a covariate, either fixed or time-variant

Usage

```

new_covariate(
  value = NULL,
  times = NULL,
  implementation = c("interpolate", "locf"),
  unit = NULL,
  interpolation_join_limit = 1,
  remove_negative_times = TRUE,
  round_times = NULL,
  comments = NULL,
  verbose = TRUE
)

```

Arguments

value	a numeric vector
times	NULL for time-invariant covariate or a numeric vector specifying the update times for the covariate
implementation	for time-varying covariates either 'locf' (last observation carried forward) or 'interpolate' (default). Non-numeric covariate values are assumed to be locf.
unit	specify covariate unit (optional, for documentation purposes only)
interpolation_join_limit	for interpolate option, if covariate timepoints are spaced too close together, the ODE solver sometimes chokes. This argument sets a lower limit on the space between timepoints. It will create average values on joint timepoints instead. If undesired set to NULL or 0.
remove_negative_times	should times before zero be discarded (with value at time zero determined based on implementation argument), TRUE or FALSE.
round_times	round times to specified number of digits. If NULL, will not round.
comments	NULL, or vector of length equal to value specifying comments to each observation (optional, for documentation only)
verbose	verbosity

Value

Object of class "covariate"

new_covariate_model *covariate model function*

Description

covariate model function

Usage

```
new_covariate_model(model = list())
```

Arguments

model covariate model specified as list

Value

List containing model function(s)

new_ode_model	<i>Create new ODE model</i>
---------------	-----------------------------

Description

Create new ODE model

Usage

```
new_ode_model(  
  model = NULL,  
  code = NULL,  
  pk_code = NULL,  
  dose_code = NULL,  
  file = NULL,  
  func = NULL,  
  state_init = NULL,  
  parameters = NULL,  
  reparametrization = NULL,  
  mixture = NULL,  
  units = NULL,  
  size = NULL,  
  lagtime = NULL,  
  obs = list(cmt = 1, scale = 1),  
  dose = list(cmt = 1),  
  covariates = NULL,  
  declare_variables = NULL,  
  iiv = NULL,  
  iov = NULL,  
  development = NULL,  
  omega_matrix = NULL,  
  ruv = NULL,  
  ltbs = NULL,  
  misc = NULL,  
  cmt_mapping = NULL,  
  int_step_size = NULL,
```

```

    default_parameters = NULL,
    fixed = NULL,
    cpp_show_code = FALSE,
    package = NULL,
    test_file = NULL,
    install = TRUE,
    folder = NULL,
    lib_location = NULL,
    verbose = FALSE,
    as_is = FALSE,
    nonmem = NULL,
    comments = NULL,
    version = "0.1.0",
    quiet = "",
    definition = NULL
)

```

Arguments

model	model name from model library
code	C++ code specifying ODE system
pk_code	C++ code called at any event
dose_code	C++ code called at dose event only
file	file containing C++ code
func	R function to be used with deSolve library
state_init	vector of state init
parameters	list or vector of parameter values
reparametrization	list of parameters with definitions that reparametrize the linear PK model to a 1-, 2- or 3-compartment PK with standardized parametrization.
mixture	for mixture models, provide a list of the parameter associated with the mixture and it's possible values and probabilities (of the first value), e.g. <code>list(CL = list(value = c(10, 20), p</code>
units	list or vector of parameter units
size	size of state vector for model. Size will be extracted automatically from supplied code, use this argument to override.
lagtime	lag time
obs	list with "scale": character string with definition for scale, e.g. "V" or "V*(WT/70)". If NULL, scale defaults to 1., and "cmt" the observation compartment
dose	specify default dose compartment, e.g. <code>list(cmt = 1)</code>
covariates	specify covariates, either as a character vector or a list. if specified as list, it allows use of timevarying covariates (see <code>new_covariate()</code> function for more info)
declare_variables	declare variables

<code>iiv</code>	inter-individual variability, can optionally be added to library
<code>iov</code>	inter-occasion variability, can optionally be added to library
<code>development</code>	Information about the model development population, can optionally be added to library
<code>omega_matrix</code>	variance-covariance matrix for inter-individual variability, can optionally be added to library
<code>ruv</code>	residual variability, can optionally be added to library
<code>ltbs</code>	log-transform both sides. Not used in simulations, only for fitting (sets attribute <code>ltbs</code>).
<code>misc</code>	a list of miscellaneous model metadata
<code>cmt_mapping</code>	list indicating which administration routes apply to which compartments. Example: <code>list("oral" = 1, "infusion" = 2)</code>
<code>int_step_size</code>	step size for integrator. Can be pre-specified for model, to override default for <code>sim_ode()</code>
<code>default_parameters</code>	population or specific patient values, can optionally be added to library
<code>fixed</code>	parameters that should not have <code>iiv</code> added.
<code>cpp_show_code</code>	show generated C++ code
<code>package</code>	package name when saving as package
<code>test_file</code>	optional test file to be included with package
<code>install</code>	install package after compilation?
<code>folder</code>	base folder name to create package in
<code>lib_location</code>	install into folder (<code>--library</code> argument)
<code>verbose</code>	show more output
<code>as_is</code>	use C-code as-is, don't substitute line-endings or shift indices
<code>nonmem</code>	add NONMEM code as attribute to model object
<code>comments</code>	comments for model
<code>version</code>	number of library
<code>quiet</code>	passed on to <code>system2</code> as setting for <code>stderr</code> and <code>stdout</code> ; how to output cmd line output. Default (<code>""</code>) is R console, <code>NULL</code> or <code>FALSE</code> discards. <code>TRUE</code> captures the output and saves as a file.
<code>definition</code>	optional, filename for the JSON file the full definition for the model. The definition file will be stored as <code>definition.json</code> in the resulting package.

Value

If package name is `NULL`, returns the model object. Otherwise has no return value.

 new_regimen

Dose regimen for sim_ode

Description

Create a dosing regimen for use with sim_ode

Usage

```
new_regimen(
  amt = 100,
  interval = NULL,
  n = 3,
  times = NULL,
  type = NULL,
  t_inf = NULL,
  rate = NULL,
  t_lag = NULL,
  cmt = NULL,
  checks = TRUE,
  ss = FALSE,
  n_ss = NULL,
  first_dose_time = now_utc()
)
```

Arguments

amt	dosing amount, either a single value (which will be repeated for multiple doses), or a vector with doses for each administration
interval	dosing interval (requires n as argument)
n	number of doses (requires interval as argument)
times	vector describing dosing times. Overrides specified times using interval and n arguments
type	either "infusion", "bolus", "oral", "sc" (subcutaneous), or "im" (intramuscular).
t_inf	infusion time (if type==infusion)
rate	infusion rate (if type==infusion). NULL by default. If specified, overrides t_inf
t_lag	lag time (can be applied to any dose type, not only oral). Will just be added to times
cmt	vector of dosing compartments (optional, if NULL will dosing compartment defined in model will be used)
checks	input checks. Remove to increase speed (e.g. for population-level estimation or optimal design)

ss	steady state? boolean value whether to simulate out to steady state first (steady state will be based on specified amt and interval, times will be ignored).
n_ss	how many doses to simulate before assumed steady state. Default is $4 * 24 / \text{interval}$.
first_dose_time	datetime stamp of first dose (of class POSIXct). Default is current date time.

Value

a list containing calculated VPC information, and a ggplot2 object

See Also

[sim_ode](#)

Examples

```
r1 <- new_regimen(amt=50, interval=12, n=20) # dose 50mg, q12hrs for 10 days
r2 <- new_regimen(amt=50, times=c(0:19)*12) # same, but using explicit times
r3 <- new_regimen(amt=c(rep(100,4), rep(50,16)), times=c(0:19)*12) # first 4 doses higher dose
```

nlmixr_parse_parameters

Function to parse parameters for a model into a structure used by nlmixr

Description

Function to parse parameters for a model into a structure used by nlmixr

Usage

```
nlmixr_parse_parameters(
  parameters = list(CL = 5, V = 50),
  omega = c(0.1, 0.05, 0.1),
  res_var = list(prop = 0.1, add = 1),
  fixed = c(),
  log_transform = TRUE,
  ...
)
```

Arguments

parameters	list of parameters
omega	vector describing the lower-diagonal of the between-subject variability matrix
res_var	residual variability. Expected a list with arguments prop, add, and/or exp. NULL by default.

fixed	vector of fixed parameters
log_transform	log-transform estimated parameters in nlmixr?
...	passed on

Value

List of parameters that can be used by nlmixr

nm_to_regimen	<i>Create a regimen from NONMEM data</i>
---------------	--

Description

Create a regimen based on a NONMEM, or NONMEM-like dataset

Usage

```
nm_to_regimen(data, reset_time = TRUE, first_only = FALSE)
```

Arguments

data	NONMEM-type dataset
reset_time	start time for each simulated patient at 0, irrespective of design in dataset
first_only	use only design from first individual in dataset

Value

Regimen object

pkdata	<i>PK dataset</i>
--------	-------------------

Description

Example PK dataset

Usage

```
pkdata
```

Format

A data frame with 624 rows and 12 variables in NONMEM format

pkpdsim_to_nlmixr *Convert a model generated with PKPDSim to an object for nlmixr*

Description

Convert a model generated with PKPDSim to an object for nlmixr

Usage

```
pkpdsim_to_nlmixr(
  model = NULL,
  parameters = NULL,
  omega = NULL,
  res_var = NULL,
  fixed = c(),
  ini_code = NULL,
  model_code = NULL,
  model_par_code = NULL,
  verbose = FALSE,
  ...
)
```

Arguments

model	PKPDSim model
parameters	list of parameters
omega	vector describing the lower-diagonal of the between-subject variability matrix
res_var	residual variability. Expected a list with arguments prop, add, and/or exp. NULL by default.
fixed	vector of fixed (not estimated) parameter names
ini_code	manually specify the ini block for nlmixr
model_code	manually specify the model block for nlmixr
model_par_code	manually specify the parameters section inside the model block for nlmixr
verbose	verbose, TRUE or FALSE
...	passed on

Value

nlmixr function

pop_regimen	<i>Remove n doses (from tail) of PKPDsim regimen</i>
-------------	--

Description

Opposite of shift_regimen()

Usage

```
pop_regimen(regimen, n = 1)
```

Arguments

regimen	PKPDsim regimen created using new_regimen()
n	number of doses to pop from regimen

Value

Input regiment minus selected number of doses

See Also

shift_regimen

print_list	<i>Return a list in R syntax</i>
------------	----------------------------------

Description

Return a list in R syntax

Usage

```
print_list(x, wrapper = TRUE)
```

Arguments

x	list to be printed
wrapper	wrap in list object?

Value

Original list in R syntax

read_model_json	<i>Read model definition from JSON</i>
-----------------	--

Description

Does some substitution of escaped characters in strings in the JSON file, then converts to a list with `jsonlite::fromJSON()`

Usage

```
read_model_json(path)
```

Arguments

path	Path to JSON file
------	-------------------

Value

List containing contents of original JSON file

regimen_to_nm	<i>Convert PKPDsim regimen to NONMEM table (doses only)</i>
---------------	---

Description

Convert PKPDsim regimen to NONMEM table (doses only)

Usage

```
regimen_to_nm(
  reg = NULL,
  dose_cmt = 1,
  n_ind = 1,
  t_obs = NULL,
  obs_cmt = 1,
  bioav = NULL
)
```

Arguments

reg	PKPDsim regimen, created using <code>new_regimen()</code> function
dose_cmt	dosing compartment, if not specified in reg object
n_ind	repeat for n_ind subjects
t_obs	add observation time(s)
obs_cmt	observation compartment for added observation time(s)
bioav	bioavailability (numeric vector, can not be a parameter)

Value

Data frame containing doses

reparametrize	<i>Reparametrize model parameters using a reparametrization defined within the model.</i>
---------------	---

Description

Mostly useful for reparametrizing models into standard parametrizations, e.g. to NONMEM TRANS or clinPK parametrizations.

Usage

```
reparametrize(model, parameters, covariates)
```

Arguments

model	PKPDsim model, compiled using reparametrization argument or in metadata object.
parameters	list of model parameters
covariates	covariates list, specified as PKPDsim covariates

Value

Reparameterized model parameters

search_replace_in_file	<i>Find string and replace in file</i>
------------------------	--

Description

Find string and replace in file

Usage

```
search_replace_in_file(files = c(), find = NULL, replacement = NULL)
```

Arguments

files	vector of files
find	find what string, vector of character
replacement	replace with what, vector of character, should be equal in length to find

Value

Function does not return a value but edits files on disk

shift_regimen	<i>Remove n doses (from start) of PKPDsim regimen</i>
---------------	---

Description

Opposite of pop_regimen()

Usage

```
shift_regimen(regimen, n = 1, reset_time = TRUE)
```

Arguments

regimen	PKPDsim regimen created using new_regimen()
n	number of doses to shift regimen
reset_time	reset the remaining doses to start at t=0?

Value

Regimen with selected number of doses removed from start

See Also

pop_regimen

sim	<i>Simulate ODE or analytical equation</i>
-----	--

Description

Simulates a specified regimen using ODE system or analytical equation

Usage

```
sim(
  ode = NULL,
  analytical = NULL,
  parameters = NULL,
  parameters_table = NULL,
  mixture_group = NULL,
  omega = NULL,
  omega_type = "exponential",
  res_var = NULL,
  iov_bins = NULL,
  seed = NULL,
```

```

sequence = NULL,
n_ind = 1,
event_table = NULL,
regimen = NULL,
lagtime = NULL,
covariates = NULL,
covariates_table = NULL,
covariates_implementation = list(),
covariate_model = NULL,
A_init = NULL,
only_obs = FALSE,
obs_step_size = NULL,
int_step_size = 0.01,
t_max = NULL,
t_obs = NULL,
t_tte = NULL,
t_init = 0,
obs_type = NULL,
duplicate_t_obs = FALSE,
extra_t_obs = TRUE,
rtte = FALSE,
checks = TRUE,
verbose = FALSE,
return_event_table = FALSE,
return_design = FALSE,
output_include = list(parameters = FALSE, covariates = FALSE),
...
)

```

Arguments

ode	function describing the ODE system
analytical	string specifying analytical equation model to use (similar to ADVAN1-5 in NONMEM). If specified, will not use ODEs.
parameters	model parameters
parameters_table	dataframe of parameters (with parameters as columns) containing parameter estimates for individuals to simulate. Formats accepted: data.frame, data.table, or list of lists.
mixture_group	mixture group for models containing mixtures. Should be either 1 or 2, since only two groups are currently allowed.
omega	vector describing the lower-diagonal of the between-subject variability matrix
omega_type	exponential or normal, specified as vector
res_var	residual variability. Expected a list with arguments prop, add, and/or exp. NULL by default.
iov_bins	allow override of the default IOV bins for a model. Specified as a vector of time-points specifying the bin separators, e.g. iov_bins = c(0, 24, 48, 72, 9999).

	A warning will be thrown when less bins are requested than was defined for the model during compilation. When the number of bins is higher than defined for the model an error will be thrown.
seed	set seed for reproducible results
sequence	if not NULL specifies the pseudo-random sequence to use, e.g. "halton" or "sobol". See <code>mvrnorm2</code> for more details.
n_ind	number of individuals to simulate
event_table	use a previously created design object used for ODE simulation instead of calling <code>create_event_table()</code> to create a new one. Especially useful for repeated calling of <code>sim()</code> , such as in optimizations or optimal design analysis. Also see <code>sim_core()</code> for even faster simulations using precalculated design objects.
regimen	a regimen object created using the <code>regimen()</code> function
lagtime	either a value (numeric) or a parameter (character) or NULL.
covariates	list of covariates (for single individual) created using <code>new_covariate()</code> function
covariates_table	data.frame (or unnamed list of named lists per individual) with covariate values
covariates_implementation	used only for <code>covariates_table</code> , a named list of covariate implementation methods per covariate, e.g. <code>list(WT = "interpolate", BIN = "locf")</code>
covariate_model	R code used to pre-calculate effective parameters for use in ADVAN-style analytical equations. Not used in ODE simulations.
A_init	vector with the initial state of the ODE system
only_obs	only return the observations
obs_step_size	the step size between the observations
int_step_size	the step size for the numerical integrator
t_max	maximum simulation time, if not specified will pick the end of the regimen as maximum
t_obs	vector of observation times, only output these values (only used when <code>t_obs==NULL</code>)
t_tte	vector of observation times for time-to-event simulation
t_init	initialization time before first dose, default 0.
obs_type	vector of observation types. Only valid in combination with equal length vector <code>t_obs</code> .
duplicate_t_obs	allow duplicate <code>t_obs</code> in output? E.g. for optimal design calculations when <code>t_obs = c(0,1,2,2,3)</code> . Default is FALSE.
extra_t_obs	include extra <code>t_obs</code> in output for bolus doses? This is only activated when <code>t_obs</code> is not specified manually. E.g. for a bolus dose at <code>t=24</code> , if FALSE, <code>PKPDsim</code> will output only the trough, so for bolus doses you might want to switch this setting to TRUE. When set to "auto" (default), it will be TRUE by default, but will switch to FALSE whenever <code>t_obs</code> is specified manually.

rtte	should repeated events be allowed (FALSE by default)
checks	perform input checks? Default is TRUE. For calculations where <code>sim_ode</code> is invoked many times (e.g. population estimation, optimal design) it makes sense to switch this to FALSE (after confirming the input is correct) to improve speed.
verbose	show more output
return_event_table	return the event table for the simulation only, does not run the actual simulation. Useful for iterative use of <code>sim()</code> .
return_design	returns the design (event table and several other details) for the simulation, does not run the actual simulation. Useful for iterative functions like estimation in combination with <code>sim_core()</code> , e.g. for estimation and optimal design.
output_include	list specifying what to include in output table, with keys parameters and covariates. Both are FALSE by default.
...	extra parameters

Value

a data frame of compartments with associated concentrations at requested times
 Simulated regimen

See Also

[sim_ode_shiny](#)

Examples

```
p <- list(
  CL = 38.48,
  V = 7.4,
  Q = 7.844,
  V2 = 5.19,
  Q2 = 9.324,
  V3 = 111
)

omega <- c(0.3,      # IIV CL
          0.1, 0.3) # IIV V

r1 <- new_regimen(
  amt = 100,
  times = c(0, 24, 36),
  type = "infusion"
)

mod <- new_ode_model("pk_3cmt_iv")
dat <- sim(
  ode = mod,
  parameters = p,
  omega = omega,
```

```

    n_ind = 20,
    regimen = r1
  )

```

sim_core	<i>Only core function of the simulation function, always just returns observations. Mostly useful for estimations / optimal design. Has no checks (for speed)!</i>
----------	--

Description

Only core function of the simulation function, always just returns observations. Mostly useful for estimations / optimal design. Has no checks (for speed)!

Usage

```
sim_core(sim_object = NULL, ode, duplicate_t_obs = FALSE, t_init = 0)
```

Arguments

sim_object	list with design and simulation parameters
ode	ode
duplicate_t_obs	allow duplicate t_obs in output? E.g. for optimal design calculations when t_obs = c(0,1,2,2,3). Default is FALSE.
t_init	time of initialization of the ODE system. Usually 0.

Value

Data frame with simulation results

sim_ode	<i>Deprecated function, renamed to sim()</i>
---------	--

Description

Deprecated function, renamed to sim()

Usage

```
sim_ode(...)
```

Arguments

...	parameters passed to sim() function
-----	-------------------------------------

Value

Output from `sim()`

See Also

`sim`

sim_ode_shiny	<i>Simulate ODE and create a Shiny app</i>
---------------	--

Description

This function has been deprecated and moved to a separate package at <https://github.com/ronkeizer/PKPDsimshiny>.

Usage

```
sim_ode_shiny(...)
```

Arguments

... arguments passed to `PKPDsimShiny::sim_ode_shiny()`

Value

No return value

See Also

`sim_ode`

table_to_list	<i>Convert a table to a list</i>
---------------	----------------------------------

Description

Convert a table to a list

Usage

```
table_to_list(table)
```

Arguments

table data.frame

Value

List containing original table contents

test_model	<i>Test a model</i>
------------	---------------------

Description

Test a model

Usage

```
test_model(url, test_file, package, force = FALSE)
```

Arguments

url	URL or file path to JSON representation of model
test_file	Path to a .R file containing tests to run
package	Package name
force	Run tests even if model is not flagged for building? Defaults to FALSE

Value

Runs test file for a model but does not return a value

test_pointer	<i>Test if model still in memory</i>
--------------	--------------------------------------

Description

Test if model still in memory

Usage

```
test_pointer(model)
```

Arguments

model	pointer to model
-------	------------------

Value

No return value

translate_ode	<i>Translate a model from/to various PKPD simulators</i>
---------------	--

Description

Currently only supports PKDPsim \leftrightarrow RxODE

Usage

```
translate_ode(code, auto = TRUE, from = NULL, to = NULL, verbose = TRUE)
```

Arguments

code	character string with ODE code
auto	is auto-detect syntax (from)
from	from syntax
to	to syntax
verbose	verbose, TRUE or FALSE

Value

Translated PKDPsim or RxODE model

triangle_to_full	<i>Convert triangle omega matrix to full omega matrix</i>
------------------	---

Description

Convert triangle omega matrix to full omega matrix

Usage

```
triangle_to_full(vect)
```

Arguments

vect	vector specifying triangle omega matrix
------	---

Value

Omega matrix

Index

- * **datasets**
 - pkdata, 35
- add_quotes, 3
- add_ruv, 4
- add_ruv_to_quantile, 4
- adherence_binomial, 5
- adherence_markov, 5
- advan, 6
- advan_create_data, 6
- advan_parse_output, 7
- advan_process_infusion_doses, 7
- apply_duration_scale, 8
- apply_lagtime, 9
- available_default_literature_models, 9
- available_default_literature_models(), 22

- calc_auc_analytic, 11
- calc_dydp, 12
- calc_ss_analytic, 12
- calculate_parameters, 10
- check_obs_input, 13
- compile_sim_cpp, 14
- covariate_last_obs_only, 16
- covariates_table_to_list, 15
- cv_to_omega, 16

- detect_ode_syntax, 17

- f_cov, 17

- get_fixed_parameters, 18
- get_model_auc_compartment (get_model_info), 18
- get_model_covariates (get_model_info), 18
- get_model_fixed_parameters (get_model_info), 18
- get_model_info, 18
- get_model_iov (get_model_info), 18

- get_model_linearity (get_model_info), 18
- get_model_parameters (get_model_info), 18
- get_model_structure (get_model_info), 18
- get_ode_model_size, 19
- get_parameters_from_code, 20
- get_var_y, 20

- ifelse0, 22
- install_default_literature_model, 22
- is_positive_definite, 23

- join_cov_and_par, 23
- join_regimen, 24
- jsonlite::fromJSON(), 38

- lower_triangle_mat_size, 24

- merge_regimen, 25
- model_from_api, 25
- model_from_api(), 22
- model_library, 26
- mvnorm2, 27

- na_locf, 27
- new_adherence, 28
- new_covariate, 28
- new_covariate_model, 29
- new_ode_model, 30
- new_ode_model(), 22, 26
- new_regimen, 33
- nlmixr_parse_parameters, 34
- nm_to_regimen, 35

- pkdata, 35
- pkpdsim_to_nlmixr, 36
- pop_regimen, 37
- print_list, 37

- read_model_json, 38
- read_model_json(), 18

regimen_to_nm, [38](#)
reparametrize, [39](#)

search_replace_in_file, [39](#)
shift_regimen, [40](#)
sim, [40](#)
sim(), [45](#)
sim_core, [44](#)
sim_ode, [16](#), [34](#), [44](#), [45](#)
sim_ode_shiny, [43](#), [45](#)

table_to_list, [45](#)
test_model, [46](#)
test_pointer, [46](#)
translate_ode, [47](#)
triangle_to_full, [47](#)