

Package ‘PLORN’

May 7, 2026

Type Package

Title Prediction with Less Overfitting and Robust to Noise

Version 0.1.1

Author Takahiko Koizumi, Kenta Suzuki, Yasunori Ichihashi

Maintainer Takahiko Koizumi <takahiko.koizumi@riken.jp>

Description A method for the quantitative prediction with much predictors.
This package provides functions to construct the quantitative prediction model with less overfitting and robust to noise.

Depends R (>= 3.5.0)

License MIT + file LICENSE

Language en-US

Encoding UTF-8

LazyData true

RoxygenNote 7.1.2

Suggests knitr, rmarkdown, testthat (>= 3.0.0)

URL <https://github.com/takakoizumi/PLORN>

VignetteBuilder knitr

Config/testthat/edition 3

Imports ggplot2, kernlab

NeedsCompilation no

Repository CRAN

Date/Publication 2022-03-21 08:00:11 UTC

Contents

p.clean	2
p.opt	3
p.pca	4
p.rank	5

p.sort	6
Pinus	7
plorn	7
Index	9

p.clean	<i>Clean data by eliminating predictors with many missing values</i>
---------	--

Description

Clean data by eliminating predictors with many missing values

Usage

```
p.clean(x, missing = 0.1, lowest = 10)
```

Arguments

x	A data matrix (row: samples, col: predictors).
missing	A ratio of missing values in each column allowed to be remained in the data.
lowest	The lowest value recognized in the data.

Value

A data matrix (row: samples, col: qualified predictors)

Author(s)

Takahiko Koizumi

Examples

```
data(Pinus)
train.raw <- Pinus$train
ncol(train.raw)

train <- p.clean(train.raw)
ncol(train)
```

p.opt *Estimate the optimal number of predictors to construct PLORN model*

Description

Estimate the optimal number of predictors to construct PLORN model

Usage

```
p.opt(x, y, range = 5:50, method = "linear", rep = 1)
```

Arguments

x	A data matrix (row: samples, col: predictors).
y	A vector of an environment in which the samples were collected.
range	A sequence of numbers of predictors to be tested for MAE calculation (default: 5:50).
method	A string to specify the method of regression for calculating R-squared values. "linear" (default), "quadratic" or "cubic" regression model can be specified.
rep	The number of replications for each case set by range (default: 1).

Value

A sample-MAE curve

Author(s)

Takahiko Koizumi

Examples

```
data(Pinus)
train <- p.clean(Pinus$train)
target <- Pinus$target
p.opt(train[1:10, ], target[1:10], range = 5:15)
```

p.pca

Visualize predictors using principal coordinate analysis

Description

Visualize predictors using principal coordinate analysis

Usage

```
p.pca(x, y, method = "linear", lower.thr = 0, n.pred = ncol(x), size = 1)
```

Arguments

x	A data matrix (row: samples, col: predictors).
y	A vector of an environment in which the samples were collected.
method	A string to specify the method of regression for calculating R-squared values. "linear" (default), "quadratic" or "cubic" regression model can be specified.
lower.thr	The lower threshold of R-squared value to be indicated in a PCA plot (default: 0).
n.pred	The number of candidate predictors for PLORN model to be indicated in a PCA plot (default: ncol(x)).
size	The size of symbols in a PCA plot (default: 1).

Value

A PCA plot

Author(s)

Takahiko Koizumi

Examples

```
data(Pinus)
train <- p.clean(Pinus$train)
target <- Pinus$target
p.pca(train, target)
```

p.rank	<i>Visualize R-squared value distribution in predictor-environment interaction</i>
--------	--

Description

Visualize R-squared value distribution in predictor-environment interaction

Usage

```
p.rank(  
  x,  
  y,  
  method = "linear",  
  lower.thr = 0,  
  n.pred = ncol(x),  
  upper.xlim = ncol(x)  
)
```

Arguments

x	A data matrix (row: samples, col: predictors).
y	A vector of an environment in which the samples were collected.
method	A string to specify the method of regression for calculating R-squared values. "linear" (default), "quadratic" or "cubic" regression model can be specified.
lower.thr	The lower threshold of R-squared value to be included in PLORN model (default: 0).
n.pred	The number of predictors to be included in PLORN model (default: ncol(x)).
upper.xlim	The upper limitation of x axis (i.e., the number of predictors) in the resulted figure (default: ncol(x)).

Value

A rank order plot

Author(s)

Takahiko Koizumi

Examples

```
data(Pinus)  
train <- p.clean(Pinus$train)  
target <- Pinus$target  
train <- p.sort(train, target)  
p.rank(train, target)
```

p.sort	<i>Sort and truncate predictors according to the strength of predictor-environment interaction</i>
--------	--

Description

Sort and truncate predictors according to the strength of predictor-environment interaction

Usage

```
p.sort(x, y, method = "linear", n.pred = ncol(x), trunc = 1)
```

Arguments

x	A data matrix (raw: samples, col: predictors).
y	A vector of an environment in which the samples were collected.
method	A string to specify the method of regression for calculating R-squared values. "linear" (default), "quadratic" or "cubic" regression model can be specified.
n.pred	The number of predictors to be included in PLORN model (default: ncol(x)).
trunc	a threshold to be truncated (default: 1).

Value

A data matrix (raw: samples, col: sorted predictors)

Author(s)

Takahiko Koizumi

Examples

```
data(Pinus)
train <- p.clean(Pinus$train)
target <- Pinus$target
cor(target, train[, 1])

train <- p.sort(train, target, trunc = 0.5)
cor(target, train[, 1])
```

Pinus

Transcriptomes of Pinus roots under a Temperature Gradient

Description

This dataset gives the TPM values of 200 selected genes obtained from 60 Pinus root samples (30 samples each for training and test data) under a temperature gradient, generated by RNA-seq.

Usage

Pinus

Details

A gene expression data matrix of 30 root samples of *P. thunbergii* under five temperature conditions (8, 13, 18, 23, 28 °C) with six biological replicates is in the first element of the list.

A gene expression data matrix of another 30 root samples of *P. thunbergii* under the same condition is in the second one.

Temperature conditions where 30 root samples in each data matrix were generated are in the third one.

Gene expressions are normalized in the TPM value.

Source

original (not published)

References

original (not published)

plorn

Construct and apply the PLORN model with your own data

Description

Construct and apply the PLORN model with your own data

Usage

```
plorn(x, y, newx = x, method = "linear", lower.thr = 0, n.pred = 0)
```

Arguments

x	A data matrix (row: samples, col: predictors).
y	A vector of an environment in which the samples were collected.
newx	A data matrix (row: samples, col: predictors).
method	A string to specify the method of regression for calculating R-squared values. "linear" (default), "quadratic" or "cubic" regression model can be specified.
lower.thr	The lower threshold of R-squared value to be used in PLORN model (default: 0).
n.pred	The number of candidate predictors to be used in PLORN model (default: 30).

Value

A vector of the environment in which the samples of newx were collected

Author(s)

Takahiko Koizumi

Examples

```
data(Pinus)
train <- p.clean(Pinus$train)
test <- Pinus$test
test <- test[, colnames(train)]
target <- Pinus$target
cor(target, plorn(train, target, newx = test, method = "cubic"))
```

Index

* **dataset**
 Pinus, 7

p.clean, 2
p.opt, 3
p.pca, 4
p.rank, 5
p.sort, 6
Pinus, 7
plorn, 7