

Package ‘QuESTr’

May 7, 2026

Type Package

Title Constructing Quantitative Environment Sensor using
Transcriptomes

Version 0.1.1

Author Takahiko Koizumi, Kenta Suzuki, Yasunori Ichihashi

Maintainer Takahiko Koizumi <takahiko.koizumi@riken.jp>

Description A method for prediction of environmental conditions based on transcriptome data linked with the environmental gradients. This package provides functions to overview gene-environment relationships, to construct the prediction model, and to predict environmental conditions where the transcriptomes were generated. This package can quest for candidate genes for the model construction even in non-model organisms' transcriptomes without any genetic information.

Depends R (>= 3.5.0)

License MIT + file LICENSE

Language en-US

Encoding UTF-8

LazyData true

RoxygenNote 7.1.2

Suggests knitr, rmarkdown, testthat (>= 3.0.0)

URL <https://github.com/takakoizumi/QuESTr>

VignetteBuilder knitr

Config/testthat/edition 3

Imports ggplot2, kernlab

NeedsCompilation no

Repository CRAN

Date/Publication 2022-02-15 20:00:04 UTC

Contents

Pinus	2
q.clean	3
q.opt	3
q.pca	4
q.rank	5
q.sort	6
quest	7
Index	8

Pinus

Transcriptomes of Pinus roots under a Temperature Gradient

Description

This dataset gives the TPM values of 200 selected genes obtained from 60 Pinus root samples (30 samples each for training and test data) under a temperature gradient, generated by RNA-seq.

Usage

Pinus

Details

A gene expression data matrix of 30 root samples of *P. thunbergii* under five temperature conditions (8, 13, 18, 23, 28 °C) with six biological replicates is in the first element of the list.

A gene expression data matrix of another 30 root samples of *P. thunbergii* under the same condition is in the second one.

Temperature conditions where 30 root samples in each data matrix were generated are in the third one.

Gene expressions are normalized in the TPM value.

Source

original (not published)

References

original (not published)

q.clean	<i>Clean data by eliminating genes with many missing values</i>
---------	---

Description

Clean data by eliminating genes with many missing values

Usage

```
q.clean(x, missing = 0.1, lowest = 10)
```

Arguments

x	A data matrix (raw: samples, col: genes).
missing	A ratio of missing values in each column allowed to be remained in the data.
lowest	The lowest value recognized in the data (e.g., TPM, FPKM, or raw read counts).

Value

A data matrix (raw: samples, col: qualified genes)

Author(s)

Takahiko Koizumi

Examples

```
data(Pinus)
train.raw <- Pinus$train
ncol(train.raw)

train <- q.clean(train.raw)
ncol(train)
```

q.opt	<i>Estimate the optimal number of genes to construct QuEST model</i>
-------	--

Description

Estimate the optimal number of genes to construct QuEST model

Usage

```
q.opt(x, y, range = 5:50, method = "linear", rep = 1)
```

Arguments

x	A data matrix (row: samples, col: genes).
y	A vector of an environment in which the samples were collected.
range	A sequence of numbers of genes to be tested for MAE calculation (default: 5:50).
method	A string to specify the method of regression for calculating R-squared values. "linear" (default), "quadratic" or "cubic" regression model can be specified.
rep	The number of replications for each case set by range (default: 1).

Value

A sample-MAE curve

Author(s)

Takahiko Koizumi

Examples

```
data(Pinus)
train <- q.clean(Pinus$train)
target <- Pinus$target
q.opt(train[1:10, ], target[1:10], range = 5:15)
```

q.pca	<i>Visualize gene expression similarity using principal coordinate analysis</i>
-------	---

Description

Visualize gene expression similarity using principal coordinate analysis

Usage

```
q.pca(x, y, method = "linear", lower.thr = 0, n.gene = ncol(x), size = 1)
```

Arguments

x	A data matrix (row: samples, col: genes).
y	A vector of an environment in which the samples were collected.
method	A string to specify the method of regression for calculating R-squared values. "linear" (default), "quadratic" or "cubic" regression model can be specified.
lower.thr	The lower threshold of R-squared value to be indicated in a PCA plot (default: 0).
n.gene	The number of candidate genes for QuEST model to be indicated in a PCA plot (default: ncol(x)).
size	The size of symbols in a PCA plot (default: 1).

Value

A PCA plot

Author(s)

Takahiko Koizumi

Examples

```
data(Pinus)
train <- q.clean(Pinus$train)
target <- Pinus$target
q.pca(train, target)
```

q.rank	<i>Visualize R-squared value distribution in gene-environment interaction</i>
--------	---

Description

Visualize R-squared value distribution in gene-environment interaction

Usage

```
q.rank(
  x,
  y,
  method = "linear",
  lower.thr = 0,
  n.gene = ncol(x),
  upper.xlim = ncol(x)
)
```

Arguments

x	A data matrix (row: samples, col: genes).
y	A vector of an environment in which the samples were collected.
method	A string to specify the method of regression for calculating R-squared values. "linear" (default), "quadratic" or "cubic" regression model can be specified.
lower.thr	The lower threshold of R-squared value to be included in QuEST model (default: 0).
n.gene	The number of genes to be included in QuEST model (default: ncol(x)).
upper.xlim	The upper limitation of x axis (i.e., the number of genes) in the resulted figure (default: ncol(x)).

Value

A rank order plot

Author(s)

Takahiko Koizumi

Examples

```
data(Pinus)
train <- q.clean(Pinus$train)
target <- Pinus$target
train <- q.sort(train, target)
q.rank(train, target)
```

q.sort	<i>Sort and truncate genes according to the strength of gene-environment interaction</i>
--------	--

Description

Sort and truncate genes according to the strength of gene-environment interaction

Usage

```
q.sort(x, y, method = "linear", n.gene = ncol(x), trunc = 1)
```

Arguments

x	A data matrix (raw: samples, col: genes).
y	A vector of an environment in which the samples were collected.
method	A string to specify the method of regression for calculating R-squared values. "linear" (default), "quadratic" or "cubic" regression model can be specified.
n.gene	The number of genes to be included in QuEST model (default: ncol(x)).
trunc	a threshold to be truncated (default: 1).

Value

A data matrix (raw: samples, col: sorted genes)

Author(s)

Takahiko Koizumi

Examples

```

data(Pinus)
train <- q.clean(Pinus$train)
target <- Pinus$target
cor(target, train[, 1])

train <- q.sort(train, target, trunc = 0.5)
cor(target, train[, 1])

```

quest

*Construct and apply the QuEST model with your own data***Description**

Construct and apply the QuEST model with your own data

Usage

```
quest(x, y, newx = x, method = "linear", lower.thr = 0, n.gene = 0)
```

Arguments

x	A data matrix (row: samples, col: genes).
y	A vector of an environment in which the samples were collected.
newx	A data matrix (row: samples, col: genes).
method	A string to specify the method of regression for calculating R-squared values. "linear" (default), "quadratic" or "cubic" regression model can be specified.
lower.thr	The lower threshold of R-squared value to be used in QuEST model (default: 0).
n.gene	The number of candidate genes to be used in QuEST model (default: 30).

Value

A vector of the environment in which the samples of newx were collected

Author(s)

Takahiko Koizumi

Examples

```

data(Pinus)
train <- q.clean(Pinus$train)
test <- Pinus$test
test <- test[, colnames(train)]
target <- Pinus$target
cor(target, quest(train, target, newx = test, method = "cubic"))

```

Index

* **dataset**
Pinus, 2

Pinus, 2

q.clean, 3
q.opt, 3
q.pca, 4
q.rank, 5
q.sort, 6
quest, 7