

Package ‘RCognito’

May 7, 2026

Type Package

Title A Simplified Interface for 'Amazon Cognito'

Version 0.1.0

Maintainer Sanjaya J Shetty <shettysanjaya01@gmail.com>

Description Simplifies integration with 'Amazon Cognito' (<<https://aws.amazon.com/cognito/>>) for R developers, enabling easy management of user authentication, registration, and password flows.

License MIT + file LICENSE

Encoding UTF-8

RoxygenNote 7.3.2

Imports paws

Suggests testthat (>= 3.0.0), mockery

Config/testthat/edition 3

NeedsCompilation no

Author Sanjaya J Shetty [aut, cre]

Repository CRAN

Date/Publication 2024-11-13 14:20:02 UTC

Contents

change_password	2
confirm_forgot_password	2
confirm_sign_up_user	3
forgot_password	3
get_user_list_from_cognito	4
is_valid_email	4
is_valid_token	5
sign_in	5
sign_up_user	6

Index	7
--------------	----------

change_password *Change User Password*

Description

Change User Password

Usage

```
change_password(old_password, new_password, token)
```

Arguments

old_password	A character string representing the user's current password.
new_password	A character string representing the user's new password.
token	A character string representing the user's access token.

Value

A message indicating the success of the password change, or an error if it fails.

confirm_forgot_password
Confirm Forgot Password

Description

This function confirms the forgot password process by setting a new password for a user.

Usage

```
confirm_forgot_password(client_id, username, confirmation_code, new_password)
```

Arguments

client_id	A character string representing the app client ID.
username	A character string for the user's username.
confirmation_code	A character string for the confirmation code sent to the user.
new_password	A character string for the user's new password.

Value

Nothing (displays a message on success or raises an error if it fails).

confirm_sign_up_user *Confirm User Sign Up*

Description

This function confirms the sign-up process for a user in AWS Cognito.

Usage

```
confirm_sign_up_user(client_id, userpool, username, verification_code)
```

Arguments

client_id	A character string representing the app client ID.
userpool	A character string representing the user pool ID.
username	A character string for the user's username.
verification_code	A character string for the verification code sent to the user.

Value

Nothing (displays a message on success or raises an error if it fails).

forgot_password *Initiate Forgot Password Request*

Description

Initiate Forgot Password Request

Usage

```
forgot_password(client_id, username)
```

Arguments

client_id	A character string representing the app client ID.
username	A character string for the user's username.

Value

Nothing (displays a message on success or raises an error if it fails).

`get_user_list_from_cognito`*Get User List from Cognito*

Description

Retrieve the list of usernames and email addresses from Cognito.

Usage

```
get_user_list_from_cognito(cognito_client, userpool)
```

Arguments

`cognito_client` The Cognito client.

`userpool` A character string representing the user pool ID.

Value

A list containing usernames and email addresses.

`is_valid_email`*Check if an email address is valid.*

Description

This function validates the format of an email address.

Usage

```
is_valid_email(email)
```

Arguments

`email` The email address to be validated.

Value

TRUE if the email is valid, otherwise an error is thrown.

is_valid_token	<i>Check if an access token is valid.</i>
----------------	---

Description

This function validates the format of an access token.

Usage

```
is_valid_token(token)
```

Arguments

token	The access token to be validated.
-------	-----------------------------------

Value

TRUE if the token is valid, otherwise an error is thrown.

sign_in	<i>Sign in to AWS Cognito</i>
---------	-------------------------------

Description

Sign in to AWS Cognito

Usage

```
sign_in(client_id, username, password, authflow = "USER_PASSWORD_AUTH")
```

Arguments

client_id	A character string representing the app client ID.
username	A character string for the user's username.
password	A character string for the user's password.
authflow	A character string specifying the authentication flow (default: "USER_PASSWORD_AUTH").

Value

A list with user information and tokens if successful; throws an error otherwise.

`sign_up_user`*Sign up a new user to AWS Cognito*

Description

Sign up a new user to AWS Cognito

Usage

```
sign_up_user(client_id, email, username, password, ...)
```

Arguments

<code>client_id</code>	A character string representing the app client ID.
<code>email</code>	A character string for the user's email address.
<code>username</code>	A character string for the user's username.
<code>password</code>	A character string for the user's password.
<code>...</code>	Additional named user attributes for Cognito (e.g., 'phone_number').

Value

A list with sign-up confirmation details if successful; throws an error otherwise.

Index

`change_password`, 2

`confirm_forgot_password`, 2

`confirm_sign_up_user`, 3

`forgot_password`, 3

`get_user_list_from_cognito`, 4

`is_valid_email`, 4

`is_valid_token`, 5

`sign_in`, 5

`sign_up_user`, 6