

Package ‘RECA’

May 7, 2026

Title Relevant Component Analysis for Supervised Distance Metric Learning

Version 1.7.1

Description Relevant Component Analysis (RCA) tries to find a linear transformation of the feature space such that the effect of irrelevant variability is reduced in the transformed space.

License GPL (>= 3)

URL <https://nanx.me/RECA/>, <https://github.com/nanxstats/RECA>

BugReports <https://github.com/nanxstats/RECA/issues>

Suggests MASS

Encoding UTF-8

RoxygenNote 7.3.2

NeedsCompilation no

Author Nan Xiao [aut, cre, cph] (ORCID:
<<https://orcid.org/0000-0002-0250-5673>>)

Maintainer Nan Xiao <me@nanx.me>

Repository CRAN

Date/Publication 2025-07-28 04:40:02 UTC

Contents

rca	2
Index	5

Description

Performs relevant component analysis (RCA) for the given data. It takes a data set and a set of positive constraints as arguments and returns a linear transformation of the data space into better representation, alternatively, a Mahalanobis metric over the data space.

The new representation is known to be optimal in an information theoretic sense under a constraint of keeping equivalent data points close to each other.

Usage

```
rca(x, chunks, useD = NULL)
```

Arguments

x	A $n * d$ matrix or data frame of original data.
chunks	A vector of size N describing the chunklets: -1 in the i-th place says that point i does not belong to any chunklet; integer j in place i says that point i belongs to chunklet j; The chunklets indexes should be 1:number-of-chunklets.
useD	Optional. Default is NULL: RCA is done in the original dimension and B is full rank. When useD is given, RCA is preceded by constraints based LDA which reduces the dimension to useD. B in this case is of rank useD.

Details

The three returned objects are just different forms of the same output. If one is interested in a Mahalanobis metric over the original data space, the first argument is all she/he needs. If a transformation into another space (where one can use the Euclidean metric) is preferred, the second returned argument is sufficient. Using A and B are equivalent in the following sense:

if $y1 = A * x1$, $y2 = A * x2$, then

$$(x2 - x1)^T * B * (x2 - x1) = (y2 - y1)^T * (y2 - y1)$$

Value

A list of the RCA results:

- B: The RCA suggested Mahalanobis matrix. Distances between data points $x1$, $x2$ should be computed by $(x2 - x1)^T * B * (x2 - x1)$.
- RCA: The RCA suggested transformation of the data. The data should be transformed by $RCA * data$.
- newX: The data after the RCA transformation. $newX = data * RCA$.

Note

Note that any different sets of instances (chunklets), for example, {1, 3, 7} and {4, 6}, might belong to the same class and might belong to different classes.

References

Aharon Bar-Hillel, Tomer Hertz, Noam Shental, and Daphna Weinshall (2003). Learning Distance Functions using Equivalence Relations. *Proceedings of 20th International Conference on Machine Learning (ICML2003)*.

Examples

```
library("MASS")

# Generate synthetic multivariate normal data
set.seed(42)
k <- 100L # Sample size of each class
n <- 3L # Specify how many classes
N <- k * n # Total sample size
x1 <- mvrnorm(k, mu = c(-16, 8), matrix(c(15, 1, 2, 10), ncol = 2))
x2 <- mvrnorm(k, mu = c(0, 0), matrix(c(15, 1, 2, 10), ncol = 2))
x3 <- mvrnorm(k, mu = c(16, -8), matrix(c(15, 1, 2, 10), ncol = 2))
x <- as.data.frame(rbind(x1, x2, x3)) # Predictors
y <- gl(n, k) # Response

# Fully labeled data set with 3 classes,
# need to use a line in 2D to classify.
plot(x[, 1L], x[, 2L],
     bg = c("#E41A1C", "#377EB8", "#4DAF4A")[y],
     pch = rep(c(22, 21, 25), each = k)
)
abline(a = -10, b = 1, lty = 2)
abline(a = 12, b = 1, lty = 2)

# Generate synthetic chunklets
chunks <- vector("list", 300)
for (i in 1:100) chunks[[i]] <- sample(1L:100L, 10L)
for (i in 101:200) chunks[[i]] <- sample(101L:200L, 10L)
for (i in 201:300) chunks[[i]] <- sample(201L:300L, 10L)

chks <- x[unlist(chunks), ]

# Make "chunklet" vector to feed the chunks argument
chunksvec <- rep(-1L, nrow(x))
for (i in 1L:length(chunks)) {
  for (j in 1L:length(chunks[[i]])) {
    chunksvec[chunks[[i]][j]] <- i
  }
}

# Relevant component analysis
rca <- rca(x, chunksvec)
```

```
# Learned transformation of the data
rcs$RCA

# Learned Mahalanobis distance metric
rcs$B

# Whitening transformation applied to the chunklets
chkTransformed <- as.matrix(chks) %*% rcs$RCA

# Original data after applying RCA transformation,
# easier to classify - using only horizontal lines.
xnew <- rcs$newX
plot(xnew[, 1L], xnew[, 2L],
     bg = c("#E41A1C", "#377EB8", "#4DAF4A")[gl(n, k)],
     pch = c(rep(22, k), rep(21, k), rep(25, k))
)
abline(a = -15, b = 0, lty = 2)
abline(a = 16, b = 0, lty = 2)
```

Index

rca, [2](#)