

# Package ‘ROI.plugin.quadprog’

May 7, 2026

**Version** 1.0-1

**Title** 'quadprog' Plug-in for the 'R' Optimization Infrastructure

**Description** Enhances the R Optimization Infrastructure ('ROI') package by registering the 'quadprog' solver. It allows for solving quadratic programming (QP) problems.

**Imports** methods, quadprog, ROI (>= 0.3-0), slam

**License** GPL-3

**URL** <http://roi.r-forge.r-project.org/>,  
<https://r-forge.r-project.org/projects/roi/>

**NeedsCompilation** no

**Author** Stefan Theussl [aut, cre] (ORCID:  
<<https://orcid.org/0000-0002-6523-4620>>)

**Maintainer** Stefan Theussl <Stefan.Theussl@R-Project.org>

**Repository** CRAN

**Date/Publication** 2023-07-12 22:40:06 UTC

## Contents

Example-1 . . . . .	1
<b>Index</b>	<b>3</b>

---

Example-1	<i>Quadratic Problem 1</i>
-----------	----------------------------

---

**Description**

$$\text{maximize } x_1^2 + x_2^2 + x_3^2 - 5x_2$$

subject to :

$$-4x_1 - 3x_2 + \phantom{x_3} \geq -8$$

$$2x_1 + x_2 + \phantom{x_3} \geq 2$$

$$-2x_2 + x_3 \geq 0$$

$$x_1, x_2, x_3 \geq 0$$

**Examples**

```
require("ROI")
A <- cbind(c(-4, -3, 0),
          c( 2,  1, 0),
          c( 0, -2, 1))
x <- OP(Q_objective(diag(3), L = c(0, -5, 0)),
        L_constraint(L = t(A),
                    dir = rep(">=", 3),
                    rhs = c(-8, 2, 0)))

opt <- ROI_solve(x, solver="quadprog")
opt
## Optimal solution found.
## The objective value is: -2.380952e+00
solution(opt)
## [1] 0.4761905 1.0476190 2.0952381
```

# Index

Example-1, [1](#)

ROI.plugin.quadprog\_Example\_1  
(Example-1), [1](#)