

Package ‘Rwofost’

May 7, 2026

Description An implementation of the WOFOST (“World Food Studies”) crop growth model. WOFOST is a dynamic simulation model that uses daily weather data, and crop, soil and management parameters to simulate crop growth and development. See De Wit et al. (2019) <[doi:10.1016/j.agsy.2018.06.018](https://doi.org/10.1016/j.agsy.2018.06.018)> for a recent review of the history and use of the model.

Type Package

Title WOFOST Crop Growth Simulation Model

Version 0.8-7

Date 2025-12-06

LinkingTo Rcpp

Imports meteor, methods (>= 0.2-2), Rcpp (>= 0.12.4)

Suggests terra, raster

Depends R (>= 3.5.0)

URL <https://CRAN.R-project.org/package=Rwofost>

BugReports <https://github.com/cropmodels/Rwofost/issues>

Maintainer Robert J. Hijmans <r.hijmans@gmail.com>

License GPL (>= 3)

NeedsCompilation yes

Author Robert J. Hijmans [cre, aut],
Huang Fang [ctb],
C.A. van Diepen [ctb],
Allard de Wit [ctb],
Daniel van Kraalingen [ctb],
Tamme van der Wal [ctb],
C. Rappoldt [ctb],
Hendrik Boogard [ctb],
I.G.A.M. Noy [ctb],
Alterra, Wageningen-UR [cph]

Repository CRAN

Date/Publication 2025-12-07 06:40:16 UTC

Contents

Rwofost-package	2
predict	2
wofost	3
wofost_control	5
wofost_crop	6
wofost_model	7
wofost_soil	8

Index	10
--------------	-----------

Rwofost-package	<i>WOFOST Crop Growth Simulation Model</i>
-----------------	--

Description

This package provides an R interface to a C++ implementation of the WOFOST crop growth simulation model.

This is the first release. Please consider this version unstable. It needs more work to simplify its use.

More detailed documentation is also forthcoming, but there is ample general documentation available on-line. The documentation for the FORTRAN version 7.1 is most applicable. For example, [this manual](#).

The WOFOST model that this R package uses is written in C++ and it can also be compiled and run as a stand-alone program (see the [github repository](#)). It was derived from the original FORTRAN implementation. It passes the tests cases developed for the PCSE/python version. This suggests that you safely can use the model for "standard" computation of potential and water-limited production.

predict	<i>Spatial WOFOST model predictions</i>
---------	---

Description

Make spatial predictions with a WOFOST model. First create a model, then use the model with a `SpatDataSet` of weather and a `SpatRaster` of soil properties to make spatial predictions.

Usage

```
## S4 method for signature 'Rcpp_WofostModel'
predict(object, weather, mstart, soils=NULL,
        soiltypes=NULL, filename="", overwrite=FALSE, ...)
```

Arguments

object	WOFOST model
weather	SpatRasterDataset with weather data. There must be six sub-datasets with daily weather data for the same days and these names: tmin, tmax, prec, srad, wind and vapr
mstart	Date. The dates to start the model
soils	SpatRaster with one or two layers. Only required when computing water-limited yield. There must be a layer called index, that has positive integers with the ID for the soil type to use for a grid cell (index in the soiltypes list. If there is another layer called "depth", this layer is used to set the soil depth for each grid cell
soiltypes	list of wofost soil types
filename	character. Output filename. Optional
overwrite	logical. If TRUE, filename is overwritten
...	list. Options for writing files as in writeRaster

Value

SpatRaster with a layer for each element in mstart

wofost	<i>WOFOST crop growth model</i>
--------	---------------------------------

Description

Run the WOFOST crop growth model. Through this interface, you provide weather data, and crop, soil and control parameters to run the model once. For multiple runs it might be preferable to use [wofost_model](#) instead.

Usage

```
wofost(crop, weather, soil, control)
```

Arguments

crop	list. Crop parameters
weather	data.frame with weather data
soil	list. Soil parameters
control	list. Model control options

Details

The weather data must be passed as a data.frame with the following variables and units.

variable	description	class / unit
date	"Date" class variable	-
srad	Solar radiation	kJ m-2 day-1
tmin	Minimum temperature	degrees C
tmax	Maximum temperature	degrees C
vapr	Vapor pressure	kPa
wind	Wind speed	m s-1
prec	Precipitation	mm day-1

Note that there should not be any time gaps between the days in the data.frame

Value

matrix

References

Van Diepen, C.A., J. Wolf, and H van Keulen, 1989. WOFOST: a simulation model of crop production. *Soil Use and Management*, 5: 16-24

Van Keulen, H. and J. Wolf, 1986. Modelling of agricultural production : weather, soils and crops. <https://edepot.wur.nl/168025>

See Also

[wofost_model](#)

Examples

```
# weather data
f <- system.file("extdata/Netherlands_Swifterbant.csv", package="meteor")
w <- read.csv(f)
w$date <- as.Date(w$date)
head(w)

# crop and soil parameters
crop <- wofost_crop("barley")
soil <- wofost_soil("ec1")

# "control" parameters
contr <- wofost_control()
contr$modelstart <- as.Date("1980-02-06")
contr$latitude=52.57
contr$elevation=50

# run model
```

```

d <- wofost(crop, w, soil, contr)

# output
head(d)
tail(d)
plot(d[, "step"], d[, "LAI"])

## Another example
crop <- wofost_crop("rapeseed_1001")
soil <- wofost_soil("soil_5")
contr$modelstart <- as.Date("1977-01-01")

rp <- wofost(crop, w, soil, contr)
plot(rp[, "step"], rp[, "LAI"])

# yield
plot(rp[, 1], rp[, "WSO"])

## water limited
contr$water_limited <- TRUE
contr$modelstart <- as.Date("1985-01-01")

crop <- wofost_crop("maize_1")
f <- system.file("extdata/Philippines_IRRI.csv", package="meteor")
wth <- read.csv(f)
wth$date <- as.Date(wth$date)
contr$elevation <- 21
contr$latitude <- 14.18

ma <- wofost(crop, wth, soil, contr)
plot(ma[, "step"], ma[, "LAI"])

```

wofost_control

WOFOST control parameters

Description

This function returns a list of "control" parameters to run the WOFOST model. Either a default list, or from a file. See this manual https://swap.wur.nl/Documents/WCC_WOFOST_717_Manual.pdf for the interpretation of the parameters.

Usage

```
wofost_control(filename='')
```

Arguments

filename character. Filename

Value

list

See Also

[wofost](#)

Examples

```
contr <- wofost_control()
str(contr)
```

wofost_crop

WOFOST crop parameters

Description

This function returns a list of crop parameters for the WOFOST model. See this manual https://swap.wur.nl/Documents/WCC_WOFOST_717_Manual.pdf for their interpretation.

Usage

```
wofost_crop(name="", describe=FALSE)
```

Arguments

name	character. Either the name of a crop that comes with the package (see examples) or a filename of a similarly formatted file
describe	logical. If TRUE available metadata is printed

Value

list

References

van Heemst

See Also

[wofost](#)

Examples

```
wofost_crop('')
crop <- wofost_crop('barley')
str(crop)
```

wofost_model	<i>WOFOST crop growth model</i>
--------------	---------------------------------

Description

Create a WOFOST crop growth model object. Through this interface, you first create a model object and then you run it. The advantage is that you can easily change single parameters of the model and run the model again.

Usage

```
wofost_model(crop, weather, soil, control)
run(x, ...)
crop(x) <- value
soil(x) <- value
control(x) <- value
weather(x) <- value
force(x) <- value
```

Arguments

crop	list. Crop parameters
weather	data.frame with weather data. See Details
soil	list. Soil parameters
control	list. Model control options
value	crop, weather, soil, or control data, as above; or a data.frame for "force"
x	WOFOST model
...	additional arguments. <code>stopError(logical)</code> . If an error occurs and <code>stopError</code> is TRUE, and error message is given. Otherwise, a warning is given and some simulation data (up till when the error occurred) may be returned

Details

The weather data must be passed as a data.frame with the following variables and units.

variable	description	class / unit
date	"Date" class variable	-
srad	Solar radiation	kJ m ⁻² day ⁻¹
tmin	Minimum temperature	degrees C
tmax	Maximum temperature	degrees C
vapr	Vapor pressure	kPa
wind	Wind speed	m s ⁻¹
prec	Precipitation	mm day ⁻¹

Note that there should not be any time gaps between the days in the data.frame

Value

WofostModel object

References

Van Diepen, C.A., J. Wolf, and H van Keulen, 1989. WOFOST: a simulation model of crop production. *Soil Use and Management*, 5: 16-24

Van Keulen, H. and J. Wolf, 1986. Modelling of agricultural production : weather, soils and crops. <https://edepot.wur.nl/168025>

Examples

```
# weather data
f <- system.file("extdata/Netherlands_Swifterbant.csv", package="meteor")
w <- read.csv(f)
w$date <- as.Date(w$date)

crop <- wofost_crop("barley")
soil <- wofost_soil("ec1")
contr <- wofost_control()

contr$modelstart <- as.Date("1980-02-06")
contr$latitude=52.57
contr$elevation=50

# create model
m <- wofost_model(crop, w, soil, contr)

# run model
x <- run(m)
plot(x[, "date"], x[, "LAI"], cex=.5)

# make a change
m$control$modelstart = as.Date("1980-02-20")

# run model again
y <- run(m)
lines(y[, "date"], y[, "LAI"], col="red")

# change the crop
crop(m) <- wofost_crop("potato_704")
p <- run(m)
lines(p[, "date"], p[, "LAI"], col="blue")
```

Description

This function returns a list with soil parameters for the WOFOST model. See this manual https://swap.wur.nl/Documents/WCC_WOFOST_717_Manual.pdf for their interpretation.

Usage

```
wofost_soil(name='')
```

Arguments

name	character. Either the name of a soil that comes with the package (see examples) or a filename of a similarly formatted file
------	---

Value

list

See Also

[wofost](#)

Examples

```
wofost_soil('')  
soil <- wofost_soil('ec1')  
str(soil)
```

Index

`control<- (wofost_model)`, [7](#)
`control<- ,Rcpp_WofostModel`, list-method
 (`wofost_model`), [7](#)
`crop<- (wofost_model)`, [7](#)
`crop<- ,Rcpp_WofostModel`, list-method
 (`wofost_model`), [7](#)

`force<- (wofost_model)`, [7](#)
`force<- ,Rcpp_WofostModel`, data.frame-method
 (`wofost_model`), [7](#)

`predict`, [2](#)
`predict,Rcpp_WofostModel`-method
 (`predict`), [2](#)

`run (wofost_model)`, [7](#)
`run,Rcpp_WofostModel`-method
 (`wofost_model`), [7](#)
`Rwofost (Rwofost-package)`, [2](#)
`Rwofost-package`, [2](#)

`soil<- (wofost_model)`, [7](#)
`soil<- ,Rcpp_WofostModel`, list-method
 (`wofost_model`), [7](#)

`weather<- (wofost_model)`, [7](#)
`weather<- ,Rcpp_WofostModel`, data.frame-method
 (`wofost_model`), [7](#)
`wofost`, [3](#), [6](#), [9](#)
`wofost_control`, [5](#)
`wofost_crop`, [6](#)
`wofost_model`, [3](#), [4](#), [7](#)
`wofost_soil`, [8](#)
`writeRaster`, [3](#)