

Package ‘SAP’

May 7, 2026

Type Package

Date 2022-10-30

Title Statistical Analysis and Programming

Version 1.0

Description The Hypothesis tests for the means of independent or paired groups. This package investigates the normality assumption automatically. Then, it tests the hypothesis tests for two independent or paired group means by using parametric or non-parametric tests. It uses the Shapiro-Wilk test to test the normality assumption. For independent two groups, If data comes from the normal distribution, the package uses the Z or t-test according to whether variances are known. For paired groups, it uses paired t-test under normal data sets. If data does not come from the normal distribution, the package uses the Wilcoxon test for independent and paired cases.

Author Hasan Bulut [aut, cre]

Maintainer Hasan Bulut <hasan.bulut@omu.edu.tr>

License GPL-2

Encoding UTF-8

LazyData true

Depends R (>= 3.5.0)

Imports stats, BSDA

RoxygenNote 7.2.1

NeedsCompilation no

Repository CRAN

Date/Publication 2022-10-31 14:28:36 UTC

Contents

data1	2
TwoSamplesMeans	2
Index	4

data1	<i>data1</i>
-------	--------------

Description

The data set is used in Sample 16.1. The data set consists of 2 variables and 10 observations. This data is imaginary.

Usage

data1

TwoSamplesMeans	<i>Hypothesis tests for two means</i>
-----------------	---------------------------------------

Description

Tests for means of two independent or paired groups.

Usage

```
TwoSamplesMeans(
  x,
  y,
  var.equal = FALSE,
  H1 = "two.sided",
  xvar = NULL,
  yvar = NULL,
  paired = FALSE
)
```

Arguments

x	a numeric vector for the data of the first group.
y	a numeric vector for the data of the second group.
var.equal	a logical variable indicating whether to treat the two variances as being equal
H1	a character string specifying the alternative hypothesis, must be one of "two.sided" (default),
xvar	a numeric value for the variance of the first group
yvar	a numeric value for the variance of the second group
paired	a logical indicating value whether you want

Details

`TwoSamplesMeans` function performs hypothesis tests on means of independent or paired two groups. Moreover, this function can decide whether it will use a parametric or non-parametric test.

Value

a list with 3 elements:

<code>statistic</code>	the value of the test statistic
<code>df</code>	If it is available, the degree of freedom for the test statistic
<code>p.value</code>	the p-value for the test
<code>test</code>	a character string indicating which method was used

Author(s)

Hasan BULUT <hasan.bulut@omu.edu.tr>

Examples

```
x<-c(10, 25, 35, 40, 70, 60, 50, 70, 65, 25)
y<-c(30, 20, 60, 70, 50, 90, 80, 65, 75, 60)
TwoSamplesMeans(x = x,y = y,H1 = "two.sided")
```

Index

* **datasets**

data1, [2](#)

data1, [2](#)

TwoSamplesMeans, [2](#)