

Package ‘SVN’

May 7, 2026

Type Package

Title Statistically Validated Networks

Version 1.0.1

Date 2019-09-23

Author Damien Challet

Maintainer Damien Challet <damien.challet@gmail.com>

Description Determines networks of significant synchronization between the discrete states of nodes; see Tumminello et al <[doi:10.1371/journal.pone.0017994](https://doi.org/10.1371/journal.pone.0017994)>.

License GPL (>= 2.0)

Depends igraph, memoise

Imports data.table

RoxygenNote 6.1.0

Encoding UTF-8

NeedsCompilation no

Repository CRAN

Date/Publication 2019-09-24 08:40:02 UTC

Contents

| | |
|------------------------|---|
| SVN-package | 2 |
| SVN_clusters | 3 |
| SVN_links | 3 |

| | |
|--------------|----------|
| Index | 5 |
|--------------|----------|

Description

Statistically validated networks are built from the states of nodes and from their curious (statistically speaking) synchronization: two nodes are linked if their states are anomalously synchronized. The associated null hypothesis is that the states of nodes are Poissonian processes, i.e., independent from each other.

Details

The main function `SVN_links` expects a matrix/data.frame/data.table of states, the line number being the index and while a given column corresponds to a given node, and outputs the results network in an `igraph` format. A Multiple Hypothesis Testing correction is applied since one performs several (rather, many) tests. It is then up to the user to use some network clustering technique if needed. For the convenience of the user, the function `SVN_clusters` applies the `infoMap` or `Louvain` method to the output of `SVN_links` and returns the resulting clustering. For small enough timeseries, it may be useful to use the options(`svn.memoise=TRUE`) so as to avoid expensive calls to the `phyper` function.

Author(s)

Maintainer: Damien Challet <damien.challet@gmail.com>

References

Tumminello, M., Micciche, S., Lillo, F., Piilo, J., & Mantegna, R. N. (2011). Statistically validated networks in bipartite complex systems. *PloS one*, 6(3), e17994.

See Also

igraph

Examples

```
x=sample(c(1,0),1000,replace = TRUE) # random vector of 0s and 1s
xx=x; x[1]=1-x[1] # one modifies just one element. x and xx are very similar
x_rev=rev(x) # x and x_rev are not
y=sample(c(1,0),1000,replace = TRUE) # y is another random vector of 0s and 1s
M=cbind(x,xx,x_rev,y) # builds the matrix of states
mylinks=SVN_links(M)
print(mylinks)

# one can compute clusters as well
myclusters=SVN_clusters(mylinks)
```

| | |
|--------------|--|
| SVN_clusters | <i>Find clusters in Statistically Validated Networks</i> |
|--------------|--|

Description

Find clusters in Statistically Validated Networks

Usage

```
SVN_clusters(links, cluster.method = "infomap")
```

Arguments

`links` an object obtained from the `SVN_links` function
`cluster.method` a string, either "infomap" or "louvain", that selects the clustering method

Value

an igraph communities object

Examples

```
M=matrix(rbinom(200,size = 1,0.5),nrow=50)
mylinks=SVN_links(M)
# no links, then
print(mylinks)

# another example
x=c(1,0,0,0,0,0,0,1,1,1,1,0,0)
xx=c(1,1,0,0,0,0,0,1,1,1,1,0,0)
xrev=rev(x)
w=sample(x,length(x))
M=rbind(x,xx,xrev,w)
mylinks=SVN_links(M)

## if one wants clusters as well
myclusters=SVN_clusters(mylinks)
```

| | |
|-----------|---------------------------------------|
| SVN_links | <i>Statistical validated networks</i> |
|-----------|---------------------------------------|

Description

Statistical validated networks

Usage

```
SVN_links(states_vs_t, alpha = 0.01, MHT.correction = "bonferroni",
  exclude.states = NULL, states.pair.types = "all",
  alternative = "overexpression")
```

Arguments

| | |
|-------------------|--|
| states_vs_t | a matrix with time in lines and individual states in columns |
| alpha | the family-wise error rate in the case of Bonferroni multiple-hypothesis correction, or the false discovery rate in the case of the FDR multiple hypothesis correction |
| MHT.correction | the type of multiple hypothesis correction |
| exclude.states | a vector of states to remove from states_vs_t |
| states.pair.types | accepted value: "all", "same", "different": selects which kind of state pairs are tested: if there are two states e.g. (1,2), "all" allows (1,1), (2,2) and (1,2); "same" allows (1,1) and (2,2), while "different" allows (1,2) |
| alternative | a string either equal to "overexpression" or "underexpression" |

Value

a data.table object of the node pairs significantly correlated at the alpha level. The columns are: link_id: a unique identifier for links; i and j are the node names; si and sj are their states; pv is the value associated to the link; threshold is the Multiple Hypothesis Testing-adjusted p-value threshold (only links with $pv \leq \text{threshold}$ are kept)

Examples

```
x=sample(c(1,0),1000,replace = TRUE)
xx=x; x[1]=1-x[1] # one modifies just one element
x_rev=rev(x)
y=sample(c(1,0),1000,replace = TRUE)
M=cbind(x,xx,x_rev,y)
mylinks=SVN_links(M)
print(mylinks)
# one can compute clusters as well
myclusters=SVN_clusters(mylinks)
```

Index

* **network**

SVN-package, [2](#)

* **synchronization**

SVN-package, [2](#)

SVN (SVN-package), [2](#)

SVN-package, [2](#)

SVN_clusters, [3](#)

SVN_links, [3](#)