

Package ‘SpaDES.core’

May 8, 2026

Type Package

Title Core Utilities for Developing and Running Spatially Explicit Discrete Event Models

Description Provides the core framework for a discrete event system to implement a complete data-to-decisions, reproducible workflow. The core components facilitate the development of modular pieces, and enable the user to include additional functionality by running user-built modules. Includes conditional scheduling, restart after interruption, packaging of reusable modules, tools for developing arbitrary automated workflows, automated interweaving of modules of different temporal resolution, and tools for visualizing and understanding the within-project dependencies. The suggested package 'NLMR' can be installed from the repository (<<https://PredictiveEcology.r-universe.dev>>).

URL <https://spades-core.predictiveecology.org/>,
<https://github.com/PredictiveEcology/SpaDES.core>

Date 2026-01-09

Version 3.0.4

Depends R (>= 4.3), quickPlot (>= 1.0.2), reproducible (>= 2.1.3.9031)

Imports cli, data.table (>= 1.11.0), fs, igraph (>= 1.0.1), lobstr, methods, qs2, Require (>= 1.0.1), stats, terra (>= 1.7-46), tools, utils, whisker

Suggests archive, CircStats, codetools, covr, DBI, DiagrammeR (>= 0.8.2), future, future.callr, ggplot2, ggplotify, gitcreds, googledrive, httr, httr2, knitr, lattice, lme4, logging, magrittr, NLMR (>= 1.1.1), pkgload, png, RColorBrewer (>= 1.1-2), raster (>= 2.5-8), rmarkdown, roxygen2, RSQLite, rstudioapi, sp, SpaDES.tools (>= 2.0.0), tcltk, testthat (>= 1.0.2), withr

Additional_repositories <https://predictiveecology.r-universe.dev/>

Encoding UTF-8

Language en-CA

License GPL-3

VignetteBuilder knitr, rmarkdown

BugReports <https://github.com/PredictiveEcology/SpaDES.core/issues>

ByteCompile yes

Collate 'module-dependencies-class.R' 'misc-methods.R' 'environment.R'
 'helpers.R' 'simList-class.R' 'times.R' 'simList-accessors.R'
 'Plots.R' 'cache.R' 'check.R' 'priority.R' 'checkpoint.R'
 'code-checking.R' 'convertToPackage.R' 'copy.R'
 'createDESCRIPTIONandDocs.R' 'debugging.R' 'downloadData.R'
 'simulation-parseModule.R' 'simulation-simInit.R' 'load.R'
 'memory-leaks.R' 'memory.R' 'modActiveBinding.R'
 'module-define.R' 'module-dependencies-methods.R'
 'module-param-check.R' 'module-repository.R'
 'module-template.R' 'moduleCoverage.R' 'moduleMetadata.R'
 'objectSynonyms.R' 'options.R' 'paths.R' 'plotting-diagrams.R'
 'plotting.R' 'progress.R' 'project-template.R' 'reexports.R'
 'restart.R' 'save.R' 'saveLoadSimList.R' 'simulation-spades.R'
 'spades-classes.R' 'spades-core-deprecated.R'
 'spades-core-package.R' 'suppliedElsewhere.R' 'zzz.R'

RoxygenNote 7.3.3

NeedsCompilation no

Author Alex M Chubaty [aut] (ORCID: <<https://orcid.org/0000-0001-7146-8135>>),
 Eliot J B McIntire [aut, cre] (ORCID:
 <<https://orcid.org/0000-0002-6914-8316>>),
 Yong Luo [ctb],
 Steve Cumming [ctb],
 Ceres Barros [ctb] (ORCID: <<https://orcid.org/0000-0003-4036-977X>>),
 His Majesty the King in Right of Canada, as represented by the Minister
 of Natural Resources Canada [cph]

Maintainer Eliot J B McIntire <eliot.mcintire@canada.ca>

Repository CRAN

Date/Publication 2026-01-11 06:12:04 UTC

Contents

SpaDES.core-package	5
.addChangedAttr,simList-method	13
.addTagsToOutput,simList-method	14
.cacheMessage,simList-method	15
.checkCacheRepo,list-method	16
.fileExtensions	16
.findSimList	18
.guessPkgFun	19
.parseElems,simList-method	19
.preDigestByClass,simList-method	20
.prepareOutput,simList-method	20

.quickCheck	21
.rndstr	21
.robustDigest,simList-method	23
.tagsByClass,simList-method	24
.wrap,simList	25
all.equal,simList	26
anyPlotting	27
append_attr	27
bindrows	28
checkModule	29
checkModuleLocal	29
checkModulePath	30
checkObject	31
checkParams	32
checkpointFile	33
checksums	34
citation	35
classFilter	36
clearCache,simList-method	37
clearCacheEventsOnly	40
convertToPackage	41
Copy,simList-method	43
copyModule	44
createDESCRIPTIONandDocs	45
createsOutput	48
defineEvent	49
defineModule	50
defineParameter	52
depsEdgeList	54
depsGraph	55
dhour	55
doCallSafe	57
downloadData	57
downloadModule	60
envir	62
eventDiagram	63
events	64
expectsInput	66
extractURL	67
fileName	68
getMapPath	69
getModuleVersion	69
globals	71
initialize,simList-method	72
inputObjects	72
inputs	74
inSeconds	77
loadSimList	78

makeMemoisable.simList	80
maxTimeunit	80
memoryUseThisSession	81
minTimeunit	82
moduleCodeFiles	82
moduleCoverage	83
moduleDefaults	84
moduleDiagram	84
moduleGraph	86
moduleMetadata	87
moduleParams	88
modules	90
moduleVersion	91
newModule	92
newModuleTests	95
newObjectsCreated	96
newProgressBar	97
newProject	97
newProjectCode	98
noEventWarning	99
objectDiagram	99
objectSynonyms	100
objs	101
objSize.simList	103
openModules	104
outputs	105
packages	108
paramCheckOtherMods	109
params	111
paths	113
Plot,simList-method	116
Plots	118
priority	121
progressInterval	122
rasterCreate	124
rasterToMemory	124
remoteFileSize	125
restartR	126
restartSpades	127
savedSimEnv	129
saveFiles	130
saveSimList	131
scheduleConditionalEvent	133
scheduleEvent	135
show,simList-method	136
simFile	137
simInit	137
simInitAndSpades2	144

simList-class	147
spades2	149
spadesClasses	153
spadesOptions	154
suppliedElsewhere	155
times	157
updateList	160
use_gha	160
writeEventInfo	161
writeRNGInfo	161
zipModule	162
zipSimList	163
[,simList,character,ANY-method	164

Index**165**

SpaDES.core-package *Categorized overview of the SpaDES.core package*

Description

This package allows implementation a variety of simulation-type models, with a focus on spatially explicit models. The core simulation components are built upon a discrete event simulation framework that facilitates modularity, and easily enables the user to include additional functionality by running user-built simulation modules. Included are numerous tools to visualize various spatial data formats, as well as non-spatial data. Much work has been done to speed up the core of the DES, with current benchmarking as low as 56 microseconds overhead for each event (including scheduling, sorting event queue, spawning event etc.) or 38 microseconds if there is no sorting (i.e., no sorting occurs under simple conditions). Under most event conditions, therefore, the DES itself will contribute very minimally compared to the content of the events, which may often be milliseconds to many seconds each event.

Bug reports: <https://github.com/PredictiveEcology/SpaDES.core/issues>

Module repository: <https://github.com/PredictiveEcology/SpaDES-modules>

Wiki: <https://github.com/PredictiveEcology/SpaDES/wiki>

Details

1 Spatial discrete event simulation (SpaDES)

A collection of top-level functions for doing spatial discrete event simulation.

1.1 Simulations: There are two workhorse functions that initialize and run a simulation, and third function for doing multiple spades runs:

<code>simInit()</code>	Initialize a new simulation
<code>spades()</code>	Run a discrete event simulation
<code>experiment</code>	In SpaDES.experiment package. Run multiple <code>spades()</code> calls
<code>experiment2</code>	In SpaDES.experiment package. Run multiple <code>spades()</code> calls

1.2 Events: Within a module, important simulation functions include:

<code>scheduleEvent()</code>	Schedule a simulation event
<code>scheduleConditionalEvent()</code>	Schedule a conditional simulation event
<code>removeEvent</code>	Remove an event from the simulation queue (not yet implemented)

2 The simList object class

The principle exported object class is the `simList`. All SpaDES simulations operate on this object class.

`simList()` The `simList` class

3 simList methods

Collections of commonly used functions to retrieve or set slots (and their elements) of a `simList()` object are summarized further below.

3.1 Simulation parameters:

<code>globals()</code>	List of global simulation parameters.
<code>params()</code>	Nested list of all simulation parameter.
<code>P()</code>	Namespaced version of <code>params()</code> (i.e., do not have to specify module name).

3.2 loading from disk, saving to disk:

<code>inputs()</code>	List of loaded objects used in simulation. (advanced)
<code>outputs()</code>	List of objects to save during simulation. (advanced)

3.3 objects in the simList:

<code>ls(), objects()</code>	Names of objects referenced by the simulation environment.
<code>ls.str()</code>	List the structure of the <code>simList</code> objects.

`objs()` List of objects referenced by the simulation environment.

3.4 Simulation paths:

Accessor functions for the `paths` slot and its elements.

`cachePath()` Global simulation cache path.
`modulePath()` Global simulation module path.
`inputPath()` Global simulation input path.
`outputPath()` Global simulation output path.
`rasterPath()` Global simulation temporary raster path.
`paths()` Global simulation paths (cache, modules, inputs, outputs, rasters).

3.5 Simulation times:

Accessor functions for the `simtimes` slot and its elements.

`time()` Current simulation time, in units of longest module.
`start()` Simulation start time, in units of longest module.
`end()` Simulation end time, in units of longest module.
`times()` List of all simulation times (current, start, end), in units of longest module..

3.6 Simulation event queues:

Accessor functions for the `events` and `completed` slots. By default, the event lists are shown when the `simList` object is printed, thus most users will not require direct use of these methods.

`events()` Scheduled simulation events (the event queue). (advanced)
`current()` Currently executing event. (advanced)
`completed()` Completed simulation events. (advanced)
`elapsedTime()` The amount of clock time that modules & events use

3.7 Modules, dependencies, packages:

Accessor functions for the `depends`, `modules`, and `.loadOrder` slots. These are included for advanced users.

`depends()` List of simulation module dependencies. (advanced)
`modules()` List of simulation modules to be loaded. (advanced)
`packages()` Vector of required R libraries of all modules. (advanced)

3.8 simList environment:

The `simList()` has a slot called `.xData` which is an environment. All objects in the `simList` are actually in this environment, i.e., the `simList` is not a list. In R, environments use pass-by-reference semantics, which means that copying a `simList` object using normal R assignment operation (e.g., `sim2 <- sim1`), will not copy the objects contained within the `.xData` slot. The two objects (`sim1` and `sim2`) will share identical objects within that slot. Sometimes, this not desired, and a true copy is required.

`envir()` Access the environment of the `simList` directly (advanced)
`Copy()` Deep copy of a `simList`. (advanced)

3.9 Checkpointing:

Accessor method	Module	Description
<code>checkpointFile()</code>	checkpoint	Name of the checkpoint file. (advanced)
<code>checkpointInterval()</code>	checkpoint	The simulation checkpoint interval. (advanced)

3.10 Progress Bar:

<code>progressType()</code>	.progress	Type of graphical progress bar used. (advanced)
<code>progressInterval()</code>	.progress	Interval for the progress bar. (advanced)

4 Module operations

4.1 Creating, distributing, and downloading modules: Modules are the basic unit of SpaDES. These are generally created and stored locally, or are downloaded from remote repositories, including our [SpaDES-modules](#) repository on GitHub.

<code>checksums()</code>	Verify (and optionally write) checksums for a module's data files.
<code>downloadModule()</code>	Open all modules nested within a base directory.
<code>getModuleVersion()</code>	Get the latest module version # from module repository.
<code>newModule()</code>	Create new module from template.
<code>newModuleDocumentation()</code>	Create empty documentation for a new module.
<code>openModules()</code>	Open all modules nested within a base directory.
<code>moduleMetadata()</code>	Shows the module metadata.
<code>zipModule()</code>	Zip a module and its associated files.

4.2 Module metadata: Each module requires several items to be defined. These comprise the metadata for that module (including default parameter specifications, inputs and outputs), and are currently written at the top of the module's .R file.

<code>defineModule()</code>	Define the module metadata
<code>defineParameter()</code>	Specify a parameter's name, value and set a default
<code>expectsInput()</code>	Specify an input object's name, class, description, sourceURL and other specifications
<code>createsOutput()</code>	Specify an output object's name, class, description and other specifications

There are also accessors for many of the metadata entries:

<code>timeunit()</code>	Accesses metadata of same name
<code>citation()</code>	Accesses metadata of same name
<code>documentation()</code>	Accesses metadata of same name
<code>reqdPkgs()</code>	Accesses metadata of same name
<code>inputObjects()</code>	Accesses metadata of same name
<code>outputObjects()</code>	Accesses metadata of same name

4.3 Module dependencies: Once a set of modules have been chosen, the dependency information is automatically calculated once `simInit` is run. There are several functions to assist with dependency information:

<code>depsEdgeList()</code>	Build edge list for module dependency graph
<code>depsGraph()</code>	Build a module dependency graph using <code>igraph</code>

5 Module functions

A collection of functions that help with making modules can be found in the suggested `SpaDES.tools` package, and are summarized below.

5.1 Spatial spreading/distances methods: Spatial contagion is a key phenomenon for spatially explicit simulation models. Contagion can be modelled using discrete approaches or continuous approaches. Several `SpaDES.tools` functions assist with these:

<code>SpaDES.tools::adj()</code>	An optimized (i.e., faster) version of <code>terra::adjacent()</code>
<code>SpaDES.tools::cir()</code>	Identify pixels in a circle around a <code>SpatialPoints*</code> () object
<code>SpaDES.tools::directionFromEachPoint()</code>	Fast calculation of direction and distance surfaces
<code>SpaDES.tools::distanceFromEachPoint()</code>	Fast calculation of distance surfaces
<code>SpaDES.tools::rings()</code>	Identify rings around focal cells (e.g., buffers and donuts)
<code>SpaDES.tools::spokes()</code>	Identify outward radiating spokes from initial points
<code>SpaDES.tools::spread()</code>	Contagious cellular automata
<code>SpaDES.tools::spread2()</code>	Contagious cellular automata, different algorithm, more robust
<code>SpaDES.tools::wrap()</code>	Create a torus from a grid

5.2 Spatial agent methods: Agents have several methods and functions specific to them:

<code>SpaDES.tools::crw()</code>	Simple correlated random walk function
<code>SpaDES.tools::heading()</code>	Determines the heading between <code>SpatialPoints*</code>
<code>quickPlot::makeLines()</code>	Makes <code>SpatialLines</code> object for, e.g., drawing arrows
<code>SpaDES.tools::move()</code>	A meta function that can currently only take "crw"
<code>SpaDES.tools::specificNumPerPatch()</code>	Initiate a specific number of agents per patch

5.3 GIS operations: In addition to the vast amount of GIS operations available in R (mostly from contributed packages such as `sf`, `terra`, (also `sp`, `raster`), `maps`, `maptools` and many others), we provide the following GIS-related functions:

<code>quickPlot::equalExtent()</code>	Assess whether a list of extents are all equal
---------------------------------------	--

5.4 'Map-reduce'-type operations: These functions convert between reduced and mapped representations of the same data. This allows compact representation of, e.g., rasters that have many individual pixels that share identical information.

<code>SpaDES.tools::rasterizeReduced()</code>	Convert reduced representation to full raster.
---	--

5.5 Colours in Raster* objects: We likely will not want the default colours for every map. Here are several helper functions to add to, set and get colours of Raster* objects:

<code>quickPlot::setColors()</code>	Set colours for plotting Raster* objects
<code>quickPlot::getColors()</code>	Get colours in a Raster* objects
<code>quickPlot::divergentColors()</code>	Create a colour palette with diverging colours around a middle

5.6 Random Map Generation: It is often useful to build dummy maps with which to build simulation models before all data are available. These dummy maps can later be replaced with actual data maps.

<code>SpaDES.tools::neutralLandscapeMap()</code>	Creates a random map using Gaussian random fields
<code>SpaDES.tools::randomPolygons()</code>	Creates a random polygon with specified number of classes

5.7 Checking for the existence of objects: SpaDES modules will often require the existence of objects in the `simList`. These are helpers for assessing this:

<code>checkObject()</code>	Check for a existence of an object within a <code>simList</code>
<code>reproducible::checkPath()</code>	Checks the specified filepath for formatting consistencies

5.8 SELES-type approach to simulation: These functions are essentially skeletons and are not fully implemented. They are intended to make translations from SELES (<https://www.gowlland.ca/>). You must know how to use SELES for these to be useful:

<code>SpaDES.tools::agentLocation()</code>	Agent location
<code>SpaDES.tools::initiateAgents()</code>	Initiate agents into a <code>SpatialPointsDataFrame</code>
<code>SpaDES.tools::numAgents()</code>	Number of agents
<code>SpaDES.tools::probInit()</code>	Probability of initiating an agent or event
<code>SpaDES.tools::transitions()</code>	Transition probability

5.9 Miscellaneous: Functions that may be useful within a SpaDES context:

<code>SpaDES.tools::inRange()</code>	Test whether a number lies within range $[a, b]$
<code>quickPlot::layerNames()</code>	Get layer names for numerous object classes
<code>quickPlot::numLayers()</code>	Return number of layers
<code>reproducible::paddedFloatToChar()</code>	Wrapper for padding (e.g., zeros) floating numbers to character

6 Caching simulations and simulation components

Simulation caching uses the reproducible package.

Caching can be done in a variety of ways, most of which are up to the module developer. However, the one most common usage would be to cache a simulation run. This might be useful if a simulation

is very long, has been run once, and the goal is just to retrieve final results. This would be an alternative to manually saving the outputs.

See example in `spades()`, achieved by using `cache = TRUE` argument.

<code>reproducible::Cache()</code>	Caches a function, but often accessed as argument in <code>spades()</code>
<code>reproducible::showCache()</code>	Shows information about the objects in the cache
<code>reproducible::clearCache()</code>	Removes objects from the cache
<code>reproducible::keepCache()</code>	Keeps only the objects described

A module developer can build caching into their module by creating cached versions of their functions.

7 Plotting

Much of the underlying plotting functionality is provided by `quickPlot`.

There are several user-accessible plotting functions that are optimized for modularity and speed of plotting:

Commonly used:

<code>quickPlot::Plot()</code>	The workhorse plotting function
--------------------------------	---------------------------------

Simulation diagrams:

<code>eventDiagram()</code>	Gantt chart representing the events in a completed simulation.
<code>moduleDiagram()</code>	Network diagram of simplified module (object) dependencies.
<code>objectDiagram()</code>	Sequence diagram of detailed object dependencies.

Other useful plotting functions:

<code>quickPlot::clearPlot()</code>	Helpful for resolving many errors
<code>quickPlot::clickValues()</code>	Extract values from a raster object at the mouse click location(s)
<code>quickPlot::clickExtent()</code>	Zoom into a raster or polygon map that was plotted with <code>quickPlot::Plot()</code>
<code>quickPlot::clickCoordinates()</code>	Get the coordinates, in map units, under mouse click
<code>quickPlot::dev()</code>	Specify which device to plot on, making a non-RStudio one as default
<code>quickPlot::newPlot()</code>	Open a new default plotting device
<code>quickPlot::rePlot()</code>	Re-plots all elements of device for refreshing or moving plot

8 File operations

In addition to R's file operations, we have added several here to aid in bulk loading and saving of files for simulation purposes:

<code>loadFiles()</code>	Load simulation objects according to a file list
<code>rasterToMemory()</code>	Read a raster from file to RAM
<code>saveFiles()</code>	Save simulation objects according to outputs and parameters

9 Sample modules included in package

Several dummy modules are included for testing of functionality. These can be found with `file.path(find.package("SpaDES"), "sampleModules")`.

<code>randomLandscapes</code>	Imports, updates, and plots several raster map layers
<code>caribouMovement</code>	A simple agent-based (a.k.a., individual-based) model
<code>fireSpread</code>	A simple model of a spatial spread process

10 Package options

SpaDES packages use the following `options()` to configure behaviour:

- `spades.browserOnError`: If TRUE, the default, then any error rerun the same event with `debugonce` called on it to allow editing to be done. When that browser is continued (e.g., with 'c'), then it will save it reparse it into the `simList` and rerun the edited version. This may allow a `spades` call to be recovered on error, though in many cases that may not be the correct behaviour. For example, if the `simList` gets updated inside that event in an iterative manner, then each run through the event will cause that iteration to occur. When this option is TRUE, then the event will be run at least 3 times: the first time makes the error, the second time has `debugonce` and the third time is after the error is addressed. TRUE is likely somewhat slower.
- `reproducible.cachePath`: The default local directory in which to cache simulation outputs. Default is a temporary directory (typically `/tmp/RtmpXXX/SpaDES/cache`).
- `spades.inputPath`: The default local directory in which to look for simulation inputs. Default is a temporary directory (typically `/tmp/RtmpXXX/SpaDES/inputs`).
- `spades.debug`: The default debugging value `debug` argument in `spades()`. Default is TRUE.
- `spades.lowMemory`: If true, some functions will use more memory efficient (but slower) algorithms. Default FALSE.
- `spades.moduleCodeChecks`: Should the various code checks be run during `simInit`. These are passed to `codetools::checkUsage()`. Default is given by the function, plus these `:list(suppressParamUnused = FALSE, suppressUndefined = TRUE, suppressPartialMatchArgs = FALSE, suppressNoLocalFun = TRUE, skipWith = TRUE)`.
- `spades.modulePath`: The default local directory where modules and data will be downloaded and stored. Default is a temporary directory (typically `/tmp/RtmpXXX/SpaDES/modules`).
- `spades.moduleRepo`: The default GitHub repository to use when downloading modules via `downloadModule`. Default `"PredictiveEcology/SpaDES-modules"`.
- `spades.nCompleted`: The maximum number of completed events to retain in the completed event queue. Default 1000L.
- `spades.outputPath`: The default local directory in which to save simulation outputs. Default is a temporary directory (typically `/tmp/RtmpXXX/SpaDES/outputs`).

- `spades.recoveryMode`: If this is a numeric greater than 0 or TRUE, then the discrete event simulator will take a snapshot of the objects in the `simList` that might change (based on metadata `outputObjects` for that module), prior to initiating every event. This will allow the user to be able to recover in case of an error or manual interruption (e.g., Esc). If this is numeric, a copy of that number of "most recent events" will be maintained so that the user can recover and restart more than one event in the past, i.e., redo some of the "completed" events. Default is TRUE, i.e., it will keep the state of the `simList` at the start of the current event. This can be recovered with `restartSpades` and the differences can be seen in a hidden object in the stashed `simList`. There is a message which describes how to find that.
- `spades.switchPkgNamespaces`: Should the search path be modified to ensure a module's required packages are listed first? Default FALSE to keep computational overhead down. If TRUE, there should be no name conflicts among package objects, but it is much slower, especially if the events are themselves fast.
- `spades.tolerance`: The default tolerance value used for floating point number comparisons. Default `.Machine$double.eps^0.5`.
- `spades.useragent`: The default user agent to use for downloading modules from GitHub.com. Default `"https://github.com/PredictiveEcology/SpaDES"`.

Author(s)

Maintainer: Eliot J B McIntire <eliot.mcintire@canada.ca> ([ORCID](#))

Authors:

- Alex M Chubaty <achubaty@for-cast.ca> ([ORCID](#))

Other contributors:

- Yong Luo <Yong.Luo@gov.bc.ca> [contributor]
- Steve Cumming <Steve.Cumming@sbf.ulaval.ca> [contributor]
- Ceres Barros <ceres.barros@ubc.ca> ([ORCID](#)) [contributor]
- His Majesty the King in Right of Canada, as represented by the Minister of Natural Resources Canada [copyright holder]

See Also

[spadesOptions\(\)](#)

.addChangedAttr,simList-method
 .addChangedAttr *for simList objects*

Description

This will evaluate which elements in the `simList` object changed following this `Cached` function call. It will add a named character string as an attribute `attr(x, ".Cache")$changed`, indicating which ones changed. When this function is subsequently called again, only these changed objects will be returned. All other `simList` objects will remain unchanged.

Usage

```
## S4 method for signature 'simList'
.addChangedAttr(object, preDigest, origArguments, ...)
```

Arguments

object	Any R object returned from a function
preDigest	The full, element by element hash of the input arguments to that same function, e.g., from <code>.robustDigest</code>
origArguments	These are the actual arguments (i.e., the values, not the names) that were the source for <code>preDigest</code>
...	Anything passed to methods.

Value

returns the object with attribute added

See Also

[reproducible::.addChangedAttr](#)

```
.addTagsToOutput,simList-method
      .addTagsToOutput for simList objects
```

Description

See [reproducible::.addTagsToOutput\(\)](#).

Usage

```
## S4 method for signature 'simList'
.addTagsToOutput(object, outputObjects, FUN, preDigestByClass)
```

Arguments

object	Any R object returned from a function
outputObjects	Optional character vector indicating which objects to return. This is only relevant for list, environment (or similar) objects
FUN	A function
preDigestByClass	A list, usually from <code>.preDigestByClass</code>

Value

modified object, with attributes added

Author(s)

Eliot McIntire

.cacheMessage,simList-method
 .cacheMessage for simList objects

Description

See [reproducible::.cacheMessage\(\)](#).

Usage

```
## S4 method for signature 'simList'  
.cacheMessage(  
  object,  
  functionName,  
  fromMemoise = getOption("reproducible.useMemoise", TRUE),  
  verbose = getOption("reproducible.verbose")  
)
```

Arguments

object	Any R object returned from a function
functionName	A character string indicating the function name
fromMemoise	Logical. If TRUE, the message will be about recovery from memoised copy
verbose	Numeric, -1 silent (where possible), 0 being very quiet, 1 showing more messaging, 2 being more messaging, etc. Default is 1. Above 3 will output much more information about the internals of Caching, which may help diagnose Caching challenges. Can set globally with an option, e.g., <code>options('reproducible.verbose' = 0)</code> to reduce t

See Also

[reproducible::.cacheMessage](#)

```
.checkCacheRepo, list-method  
      .checkCacheRepo for simList objects
```

Description

See [reproducible::.checkCacheRepo\(\)](#).

Usage

```
## S4 method for signature 'list'  
.checkCacheRepo(object, create = FALSE)
```

Arguments

object	Any R object returned from a function
create	Logical. If TRUE, then it will create the path for cache.

Value

character string representing a directory path to the cache repo

See Also

[reproducible::.checkCacheRepo](#)

```
.fileExtensions      File extensions map
```

Description

How to load various types of files in R.

This function has two roles:

1. to proceed with the loading of files that are in a `simList`; or
2. as a shortcut to `simInit(inputs = filelist)`.

A data.frame with information on how to load various types of files in R, containing the columns:

- `exts`: the file extension;
- `fun`: the function to use for files with this file extension;
- `package`: the package from which to load fun.

Usage

```
.fileExtensions()

loadFiles(sim, filelist, ...)

## S4 method for signature 'simList,missing'
loadFiles(sim, filelist, ...)

## S4 method for signature 'missing,ANY'
loadFiles(sim, filelist, ...)

## S4 method for signature 'missing,missing'
loadFiles(sim, filelist, ...)

.saveFileExtensions()
```

Arguments

sim	simList object.
filelist	list or data.frame to call loadFiles directly from the filelist as described in Details
...	Additional arguments.

Value

data.frame of file extension, package, and function mappings
the modified sim, invisibly.
data.frame

Note

Generally not intended to be used by users.

Author(s)

Eliot McIntire and Alex Chubaty

See Also

[inputs\(\)](#)

Examples

```
library(SpaDES.core)

# Load random maps included with package
filelist <- data.frame(
  files = dir(getMapPath(tempdir()), full.names = TRUE),
```

```

    functions = "rasterToMemory",
    package = "SpaDES.core"
  )
sim1 <- loadFiles(filelist = filelist) # loads all the maps to sim1 simList

# Second, more sophisticated. All maps loaded at time = 0, and the last one is reloaded
# at time = 10 and 20 (via "intervals").
# Also, pass the single argument as a list to all functions...
# specifically, when add "native = TRUE" as an argument to the raster function
files <- dir(getMapPath(tempdir()), full.names = TRUE)
arguments <- I(rep(list(lyrs = 1), length(files)))
filelist <- data.frame(
  files = files,
  functions = "terra::rast",
  objectName = NA,
  arguments = arguments,
  loadTime = 0,
  intervals = c(rep(NA, length(files)-1), 10)
)

sim2 <- loadFiles(filelist = filelist) # only does the time = 0 loading; see next
end(sim2) <- 10
sim2 <- spades(sim2) # loads the object at time 10

# if we extend the end time and continue running, it will load an object scheduled
# at time = 10, and it will also schedule a new object loading at 20 because
# interval = 10
end(sim2) <- 20
sim2 <- spades(sim2) # loads the percentPine map 2 more times, once at 10, once at 20

```

.findSimList
Find simList in a nested list

Description

This is recursive, so it will find the all simLists even if they are deeply nested.

Usage

```
.findSimList(x)
```

Arguments

x any object, used here only when it is a list with at least one simList in it

<code>.guessPkgFun</code>	<i>Guess package of a function</i>
---------------------------	------------------------------------

Description

Guess package of a function

Usage

```
.guessPkgFun(bsf)
```

Arguments

`bsf` character. A function name

Value

character. The package and function name as "pkg: :bsf"

<code>.parseElems, simList-method</code>	<i>.parseElems for simList class objects</i>
--	--

Description

See [quickPlot::.parseElems\(\)](#).

Usage

```
## S4 method for signature 'simList'  
.parseElems(tmp, elems, envir)
```

Arguments

`tmp` A evaluated object
`elems` A character string to be parsed
`envir` An environment

Value

An object, parsed from a character string and an environment.

See Also

[quickPlot::.parseElems](#)

```
.preDigestByClass,simList-method
      Pre-digesting method for simList
```

Description

Takes a snapshot of `simList` objects.

Usage

```
## S4 method for signature 'simList'
.preDigestByClass(object)
```

Arguments

`object` Any R object returned from a function

Details

See [reproducible::.preDigestByClass\(\)](#).

Value

character vector corresponding to the names of objects stored in the `.xData` slot

Author(s)

Eliot McIntire

See Also

[reproducible::.preDigestByClass](#)

```
.prepareOutput,simList-method
      .prepareOutput for simList objects
```

Description

See [reproducible::.prepareOutput\(\)](#).

Usage

```
## S4 method for signature 'simList'
.prepareOutput(object, cachePath = getOption("reproducible.cachePath"), ...)
```

Arguments

- object Any R object returned from a function
- cachePath A repository used for storing cached objects. This is optional if Cache is used inside a SpaDES module.
- ... Anything passed to methods.

Value

the modified object

See Also

[reproducible::prepareOutput](#)

.quickCheck	<i>The SpaDES.core variable to switch between quick and robust checking</i>
-------------	---

Description

A variable that can be use by module developers and model users to switch between a quick check of functions like downloadData, Cache . The module developer must actually use this in their code.

Usage

.quickCheck

Format

An object of class logical of length 1.

.rndstr	<i>Generate random strings</i>
---------	--------------------------------

Description

Generate a vector of random alphanumeric strings each of an arbitrary length.

Usage

```
.rndstr(n = 1, len = 8)

rndstr(n, len, characterFirst)

## S4 method for signature 'numeric,numeric,logical'
rndstr(n, len, characterFirst)

## S4 method for signature 'numeric,numeric,missing'
rndstr(n, len)

## S4 method for signature 'numeric,missing,logical'
rndstr(n, characterFirst)

## S4 method for signature 'missing,numeric,logical'
rndstr(len, characterFirst)

## S4 method for signature 'numeric,missing,missing'
rndstr(n)

## S4 method for signature 'missing,numeric,missing'
rndstr(len)

## S4 method for signature 'missing,missing,logical'
rndstr(characterFirst)

## S4 method for signature 'missing,missing,missing'
rndstr(n, len, characterFirst)
```

Arguments

n	Number of strings to generate (default 1). Will attempt to coerce to integer value.
len	Length of strings to generate (default 8). Will attempt to coerce to integer value.
characterFirst	Logical, if TRUE, then a letter will be the first character of the string (useful if being used for object names).

Value

Character vector of random strings.

Author(s)

Alex Chubaty and Eliot McIntire

Examples

```
set.seed(11)
```

```
rndstr()  
rndstr(len = 10)  
rndstr(characterFirst = FALSE)  
rndstr(n = 5, len = 10)  
rndstr(n = 5)  
rndstr(n = 5, characterFirst = TRUE)  
rndstr(len = 10, characterFirst = TRUE)  
rndstr(n = 5, len = 10, characterFirst = TRUE)
```

```
.robustDigest,simList-method  
  .robustDigest for simList objects
```

Description

This is intended to be used within the `Cache` function, but can be used to evaluate what a `simList` would look like once it is converted to a repeatably digestible object.

Usage

```
## S4 method for signature 'simList'  
.robustDigest(object, .objects, length, algo = "xxhash64", quick, classOptions)
```

Arguments

<code>object</code>	an object to digest.
<code>.objects</code>	Character vector of objects to be digested. This is only applicable if there is a list, environment (or similar) with named objects within it. Only this/these objects will be considered for caching, i.e., only use a subset of the list, environment or similar objects. In the case of nested list-type objects, this will only be applied outermost first.
<code>length</code>	Numeric. If the element passed to <code>Cache</code> is a <code>Path</code> class object (from e.g., <code>asPath(filename)</code>) or it is a <code>Raster</code> with file-backing, then this will be passed to <code>digest::digest</code> , essentially limiting the number of bytes to digest (for speed). This will only be used if <code>quick = FALSE</code> . Default is <code>getOption("reproducible.length")</code> , which is set to <code>Inf</code> .
<code>algo</code>	The digest algorithm to use. Default <code>xxhash64</code> (see <code>digest::digest()</code> for others).
<code>quick</code>	Logical or character. If <code>TRUE</code> , no disk-based information will be assessed, i.e., only memory content. See <code>Details</code> section about <code>quick</code> in <code>Cache()</code> .
<code>classOptions</code>	Optional list. This will pass into <code>.robustDigest</code> for specific classes. Should be options that the <code>.robustDigest</code> knows what to do with.

Details

See [reproducible::.robustDigest\(\)](#). This method strips out stuff from a `simList` class object that would make it otherwise not reproducibly digestible between sessions, operating systems, or machines. This will likely still not allow identical digest results across R versions.

Author(s)

Eliot McIntire

See Also

[reproducible::.robustDigest\(\)](#)

`.tagsByClass,simList-method`
.tagsByClass for simList objects

Description

See [reproducible::.tagsByClass\(\)](#). Adds current `moduleName`, `eventType`, `eventTime`, and `function:spades` as `userTags`.

Usage

```
## S4 method for signature 'simList'  
.tagsByClass(object)
```

Arguments

`object` Any R object returned from a function

Author(s)

Eliot McIntire

See Also

[reproducible::.tagsByClass](#)

.wrap.simList *Methods for .wrap and .unwrap*

Description

Methods for `.wrap` and `.unwrap`

Usage

```
## S3 method for class 'simList'
.wrap(
  obj,
  cachePath = getOption("reproducible.cachePath"),
  preDigest,
  drv = getOption("reproducible.drv", NULL),
  conn = getOption("reproducible.conn", NULL),
  verbose = getOption("reproducible.verbose"),
  outputObjects = NULL,
  cacheId = NULL,
  ...
)

## S3 method for class '.simDeps'
.wrap(obj, ...)

## S3 method for class '.simDeps'
.unwrap(obj, ...)

## S3 method for class '.moduleDeps'
.wrap(obj, ...)

## S3 method for class '.moduleDeps'
.unwrap(obj, ...)

## S3 method for class 'simList'
.unwrap(
  obj,
  cachePath = getOption("reproducible.cachePath"),
  cacheId = NULL,
  drv = getOption("reproducible.drv", NULL),
  conn = getOption("reproducible.conn", NULL),
  ...
)
```

Arguments

`obj` Any arbitrary R object.

cachePath	A repository used for storing cached objects. This is optional if Cache is used inside a SpaDES module.
preDigest	The list of preDigest that comes from CacheDigest of an object
drv	an object that inherits from DBIDriver, or an existing DBIConnection object (in order to clone an existing connection).
conn	A DBIConnection object, as returned by dbConnect().
verbose	Numeric, -1 silent (where possible), 0 being very quiet, 1 showing more messaging, 2 being more messaging, etc. Default is 1. Above 3 will output much more information about the internals of Caching, which may help diagnose Caching challenges. Can set globally with an option, e.g., options('reproducible.verbose' = 0) to reduce t
outputObjects	Optional character vector indicating which objects to return. This is only relevant for list, environment (or similar) objects
cacheId	An optional character vector describing the cacheIds to extract. Only entries with this/these cacheIds will be returned. If useDBI(FALSE), this will also be dramatically faster than using userTags, for a large cache.
...	Other arguments. Can be in the form of tagKey = tagValue, such as, class = "numeric" to find all entries that are numerics in the cache. Note: the special cases of cacheId and fun have their own named arguments in these functions. Also can be regexp = xx, where xx is TRUE if the user is passing a regular expression. Otherwise, userTags will need to be exact matches. Default is missing, which is the same as TRUE. If there are errors due to regular expression problem, try FALSE. For cc, it is passed to clearCache, e.g., ask, userTags. For showCache, it can also be sorted = FALSE to return the object unsorted.

Value

The same object as passed into the function, but dealt with so that it can be saved to disk.

all.equal.simList *All equal method for simList objects*

Description

This function removes a few attributes that are added internally by **SpaDES.core** and are not relevant to the all.equal. One key element removed is any time stamps, as these are guaranteed to be different. A possibly very important argument to pass to the ... is check.attributes = FALSE which will allow successful comparisons of many objects that might have pointers.

Usage

```
## S3 method for class 'simList'
all.equal(target, current, ...)
```

Arguments

target	R object.
current	other R object, to be compared with target.
...	further arguments for different methods, notably the following two, for numerical comparison:

Value

See [base::all.equal\(\)](#)

anyPlotting	<i>Test whether there should be any plotting from .plots module parameter</i>
-------------	---

Description

This will do all the various tests needed to determine whether plotting of one sort or another will occur. Testing any of the types as listed in [Plots\(\)](#) argument types. Only the first 3 letters of the type are required.

Usage

```
anyPlotting(.plots)
```

Arguments

.plots	Usually will be the P(sim)\$.plots is used within a module.
--------	--

Value

logical of length 1

append_attr	<i>Append attributes</i>
-------------	--------------------------

Description

Ordinary base lists and vectors do not retain their attributes when subsetted or appended. This function appends items to a list while preserving the attributes of items in the list (but not of the list itself).

Usage

```
append_attr(x, y)
```

```
## S4 method for signature 'list,list'
append_attr(x, y)
```

Arguments

`x, y` A list of items with optional attributes.

Details

Similar to `updateList` but does not require named lists.

Value

An updated list with attributes.

Author(s)

Alex Chubaty and Eliot McIntire

Examples

```
tmp1 <- list("apple", "banana")
tmp1 <- lapply(tmp1, `attributes<-`, list(type = "fruit"))
tmp2 <- list("carrot")
tmp2 <- lapply(tmp2, `attributes<-`, list(type = "vegetable"))
append_attr(tmp1, tmp2)
rm(tmp1, tmp2)
```

bindrows

Simple wrapper around `data.table::rbindlist`

Description

This simply sets defaults to `fill = TRUE`, and `use.names = TRUE`.

Usage

```
bindrows(...)
```

Arguments

`...` one or more `data.frame`, `data.table`, or list objects

Value

a `data.table` object

checkModule	<i>Check for the existence of a remote module</i>
-------------	---

Description

Looks in the remote repo for a module named name.

Usage

```
checkModule(name, repo, token, verbose)

## S4 method for signature 'character,character'
checkModule(name, repo, token, verbose = getOption("reproducible.verbose"))

## S4 method for signature 'character,missing'
checkModule(name, token, verbose = getOption("reproducible.verbose"))
```

Arguments

name	Character string giving the module name.
repo	GitHub repository name. Default is "PredictiveEcology/SpaDES-modules", which is specified by the global option <code>spades.moduleRepo</code> .
token	A github repository token as from <code>gitcreds::gitcreds_get()</code>
verbose	Logical or Numeric, follows <code>reproducible.verbose</code> value by default.

Value

a character vector of module file paths (invisibly).

Author(s)

Eliot McIntire and Alex Chubaty

checkModuleLocal	<i>Check for the existence of a module locally</i>
------------------	--

Description

Looks the module path for a module named name, and checks for existence of all essential module files listed below.

Usage

```

checkModuleLocal(name, path, version)

## S4 method for signature 'character,character,character'
checkModuleLocal(name, path, version)

## S4 method for signature 'character,ANY,ANY'
checkModuleLocal(name, path, version)

```

Arguments

name	Character string giving the module name.
path	Local path to modules directory. Default is specified by the global option <code>spades.modulePath</code> .
version	Character specifying the desired module version.

Details

- 'data/CHECKSUMS.txt'
- 'name.R'

Value

Logical indicating presence of the module (invisibly).

Author(s)

Alex Chubaty

checkModulePath	<i>Check module path</i>
-----------------	--------------------------

Description

Will compare default in `spadesOptions()` (i.e., `spades.modulePath`) to `getPaths()`. Uses "." if `modulePath` not set (e.g., via `setPaths`). If that is the case, then use `getPaths()[["modulePath"]]`.

Usage

```
checkModulePath()
```

checkObject	<i>Check for existence of object(s) referenced by a objects slot of a simList object</i>
-------------	--

Description

Check that a named object exists in the provide simList environment slot, and optionally has desired attributes.

Usage

```
checkObject(sim, name, object, layer, ...)  
  
## S4 method for signature 'simList,ANY,ANY'  
checkObject(sim, name, object, layer, ...)  
  
## S4 method for signature 'simList,character,missing'  
checkObject(sim, name, object, layer, ...)  
  
## S4 method for signature 'missing,ANY,ANY'  
checkObject(sim, name, object, layer, ...)
```

Arguments

sim	A <code>simList()</code> object.
name	A character string specifying the name of an object to be checked.
object	An object. This is mostly used internally, or with layer, because it will fail if the object does not exist.
layer	Character string, specifying a layer name in a Raster, if the name is a Raster* object.
...	Additional arguments. Not implemented.

Value

Invisibly return TRUE indicating object exists; FALSE if not.

Author(s)

Alex Chubaty and Eliot McIntire

See Also

[library\(\)](#).

Examples

```

sim <- simInit()
sim$a <- 1
sim$b <- list(d = 1)
sim$r <- terra::rast(terra::ext(0,2,0,2), res = 1, vals = 2)
sim$s <- c(sim$r, terra::rast(terra::ext(0,2,0,2), res = 1, vals = 3))
names(sim$s) <- c("r1", "r2") # give layer names
(checkObject(sim, name = "a")) # TRUE
(checkObject(sim, name = "b", layer = "d")) # TRUE
(checkObject(sim, name = "d")) # FALSE
(checkObject(sim, name = "r")) # TRUE
(checkObject(sim, object = sim$s)) # TRUE
(checkObject(sim, object = sim$s, layer = "r1")) # TRUE

```

checkParams

Check use and existence of parameters passed to simulation.

Description

Checks that all parameters passed are used in a module, and that all parameters used in a module are passed.

Usage

```

checkParams(sim, coreParams, ...)

## S4 method for signature 'simList,list'
checkParams(sim, coreParams, ...)

```

Arguments

sim	A simList simulation object.
coreParams	List of default core parameters.
...	Additional arguments. Not implemented.

Value

Invisibly return TRUE indicating object exists; FALSE if not. Sensible messages are produced identifying missing parameters.

Author(s)

Alex Chubaty

checkpointFile *Simulation checkpoints*

Description

Save and reload the current state of the simulation, including the state of the random number generator, by scheduling checkpoint events.

Usage

```

checkpointFile(sim)

## S4 method for signature 'simList'
checkpointFile(sim)

checkpointFile(sim) <- value

## S4 replacement method for signature 'simList'
checkpointFile(sim) <- value

checkpointInterval(sim)

## S4 method for signature 'simList'
checkpointInterval(sim)

checkpointInterval(sim) <- value

## S4 replacement method for signature 'simList'
checkpointInterval(sim) <- value

doEvent.checkpoint(sim, eventTime, eventType, debug = FALSE)

checkpointLoad(file)

.checkpointSave(sim, file)

```

Arguments

sim	A simList simulation object.
value	The parameter value to be set (in the corresponding module and param).
eventTime	A numeric specifying the time of the next event.
eventType	A character string specifying the type of event: one of either "init", "load", or "save".
debug	Optional logical flag determines whether sim debug info will be printed (default debug = FALSE).
file	The checkpoint file.

Value

Returns the modified `simList` object.

Note

Checkpoint files are intended to be used locally, and do not invoke the simulation archiving tools to bundle and subsequently extract simulation files (e.g., file-backed rasters).

RNG save code adapted from: http://www.cookbook-r.com/Numbers/Saving_the_state_of_the_random_number_generator/ and <https://stackoverflow.com/q/13997444/1380598>

Author(s)

Alex Chubaty

See Also

[.Random.seed](#).

Other functions to access elements of a 'simList' object: [.addDepends\(\)](#), [envir\(\)](#), [events\(\)](#), [globals\(\)](#), [inputs\(\)](#), [modules\(\)](#), [objs\(\)](#), [packages\(\)](#), [params\(\)](#), [paths\(\)](#), [progressInterval\(\)](#), [times\(\)](#)

checksums

Calculate checksum for a module's data files

Description

Verify (and optionally write) checksums for data files in a module's 'data/' subdirectory. The file 'data/CHECKSUMS.txt' contains the expected checksums for each data file. Checksums are computed using `reproducible:::digest`, which is simply a wrapper around `digest::digest`.

Usage

```
checksums(module, path, ...)
```

Arguments

<code>module</code>	Character string giving the name of the module.
<code>path</code>	Character string giving the path to the module directory.
<code>...</code>	Passed to <code>reproducible::Checksums()</code> , notably, <code>write</code> , <code>quickCheck</code> , <code>checksumFile</code> and <code>files</code> .

Details

Modules may require data that for various reasons cannot be distributed with the module source code. In these cases, the module developer should ensure that the module downloads and extracts the data required. It is useful to not only check that the data files exist locally but that their checksums match those expected.

Note

In version 1.2.0 and earlier, two checksums per file were required because of differences in the checksum hash values on Windows and Unix-like platforms. Recent versions use a different (faster) algorithm and only require one checksum value per file. To update your 'CHECKSUMS.txt' files using the new algorithm:

1. specify your module (`moduleName <- "my_module"`);
2. use a temporary location to ensure all modules get fresh copies of the data (`tmpdir <- file.path(tmpdir(), "SpaDES_modules")`);
3. download your module's data to the temp dir (`downloadData(moduleName, tmpdir)`);
4. initialize a dummy simulation to ensure any 'data prep' steps in the `.inputObjects` section are run (`simInit(modules = moduleName)`);
5. recalculate your checksums and overwrite the file (`checksums(moduleName, tmpdir, write = TRUE)`);
6. copy the new checksums file to your working module directory (the one not in the temp dir) (`file.copy(from = file.path(tmpdir, moduleName, 'data', 'CHECKSUMS.txt'), to = file.path('path/to/moduleName', 'data', 'CHECKSUMS.txt'), overwrite = TRUE)`).

 citation

A citation method for SpaDES modules

Description

This is a wrapper around `utils::citation()` for cases with `package` is a character string. Otherwise, it takes a `simList`.

Usage

```

citation(package, lib.loc = NULL, auto = NULL, module = character())

## S4 method for signature 'simList'
citation(package, lib.loc = NULL, auto = NULL, module = character())

## S4 method for signature 'character'
citation(package, lib.loc = NULL, auto = NULL, module = character())

```

Arguments

<code>package</code>	For compatibility with <code>utils::citation()</code> . This can be a <code>simList</code> or a character string for a package name.
<code>lib.loc</code>	a character vector with path names of R libraries, or the directory containing the source for <code>package</code> , or <code>NULL</code> . The default value of <code>NULL</code> corresponds to all libraries currently known. If the default is used, the loaded packages are searched before the libraries.

auto	a logical indicating whether the default citation auto-generated from the package 'DESCRIPTION' metadata should be used or not, or NULL (default), indicating that a 'CITATION' file is used if it exists, or an object of class " packageDescription " with package metadata (see below).
module	Optional character string indicating which module params should come from.

Value

The citation information for a SpaDES module.

classFilter	<i>Filter objects by class</i>
-------------	--------------------------------

Description

Based on <https://stackoverflow.com/a/5158978/1380598>.

Usage

```
classFilter(x, include, exclude, envir)

## S4 method for signature 'character,character,character,environment'
classFilter(x, include, exclude, envir)

## S4 method for signature 'character,character,character,missing'
classFilter(x, include, exclude)

## S4 method for signature 'character,character,missing,environment'
classFilter(x, include, envir)

## S4 method for signature 'character,character,missing,missing'
classFilter(x, include)
```

Arguments

x	Character vector of object names to filter, possibly from ls.
include	Class(es) to include, as a character vector.
exclude	Optional class(es) to exclude, as a character vector.
envir	The environment ins which to search for objects. Default is the calling environment.

Value

Vector of object names matching the class filter.

Note

`inherits()` is used internally to check the object class, which can, in some cases, return results inconsistent with `is`. See <https://stackoverflow.com/a/27923346/1380598>. These (known) cases are checked manually and corrected.

Author(s)

Alex Chubaty

Examples

```
## from local (e.g., function) environment
local({
  e <- environment()
  a <- list(1:10) # class `list`
  b <- letters # class `character`
  d <- stats::runif(10) # class `numeric`
  f <- sample(1L:10L) # class `numeric`, `integer`
  g <- lm( jitter(d) ~ d ) # class `lm`
  h <- glm( jitter(d) ~ d ) # class `lm`, `glm`
  classFilter(ls(), include=c("character", "list"), envir = e)
  classFilter(ls(), include = "numeric", envir = e)
  classFilter(ls(), include = "numeric", exclude = "integer", envir = e)
  classFilter(ls(), include = "lm", envir = e)
  classFilter(ls(), include = "lm", exclude = "glm", envir = e)
  rm(a, b, d, e, f, g, h)
})

## from another environment (can be omitted if .GlobalEnv)
e = new.env(parent = emptyenv())
e$a <- list(1:10) # class `list`
e$b <- letters # class `character`
e$d <- stats::runif(10) # class `numeric`
e$f <- sample(1L:10L) # class `numeric`, `integer`
e$g <- lm( jitter(e$d) ~ e$d ) # class `lm`
e$h <- glm( jitter(e$d) ~ e$d ) # class `lm`, `glm`
classFilter(ls(e), include=c("character", "list"), envir = e)
classFilter(ls(e), include = "numeric", envir = e)
classFilter(ls(e), include = "numeric", exclude = "integer", envir = e)
classFilter(ls(e), include = "lm", envir = e)
classFilter(ls(e), include = "lm", exclude = "glm", envir = e)
rm(a, b, d, f, g, h, envir = e)
rm(e)
```

clearCache,simList-method

clearCache for simList objects

Description

This will take the `cachePath(object)` and pass

Usage

```
## S4 method for signature 'simList'
clearCache(
  x,
  userTags = character(),
  after = NULL,
  before = NULL,
  fun = NULL,
  cacheId = NULL,
  ask = getOption("reproducible.ask"),
  useCloud = FALSE,
  cloudFolderID = getOption("reproducible.cloudFolderID", NULL),
  drv = getDrv(getOption("reproducible.drv", NULL)),
  conn = getOption("reproducible.conn", NULL),
  verbose = getOption("reproducible.verbose"),
  ...
)

## S4 method for signature 'simList'
showCache(
  x,
  userTags = character(),
  after = NULL,
  before = NULL,
  fun = NULL,
  cacheId = NULL,
  drv = getDrv(getOption("reproducible.drv", NULL)),
  conn = getOption("reproducible.conn", NULL),
  verbose = getOption("reproducible.verbose"),
  ...
)

## S4 method for signature 'simList'
keepCache(
  x,
  userTags = character(),
  after = NULL,
  before = NULL,
  ask = getOption("reproducible.ask"),
  drv = getDrv(getOption("reproducible.drv", NULL)),
  conn = getOption("reproducible.conn", NULL),
  verbose = getOption("reproducible.verbose"),
  ...
)
```

Arguments

x	A simList or a directory containing a valid Cache repository. Note: For compatibility with Cache argument, cachePath can also be used instead of x, though x will take precedence.
userTags	Character vector. If used, this will be used in place of the after and before. Specifying one or more userTag here will clear all objects that match those tags. Matching is via regular expression, meaning partial matches will work unless strict beginning (^) and end (\$) of string characters are used. Matching will be against any of the 3 columns returned by showCache(), i.e., artifact, tagValue or tagName. Also, if length(userTags) > 1, then matching is by and. For or matching, use in a single character string. See examples.
after	A time (POSIX, character understandable by data.table). Objects cached after this time will be shown or deleted.
before	A time (POSIX, character understandable by data.table). Objects cached before this time will be shown or deleted.
fun	An optional character vector describing the function name to extract. Only functions with this/these functions will be returned.
cacheId	An optional character vector describing the cacheIds to extract. Only entries with this/these cacheIds will be returned. If useDBI(FALSE), this will also be dramatically faster than using userTags, for a large cache.
ask	Logical. If FALSE, then it will not ask to confirm deletions using clearCache or keepCache. Default is TRUE
useCloud	Logical. If TRUE, then every object that is deleted locally will also be deleted in the cloudFolderID, if it is non-NULL
cloudFolderID	A googledrive dribble of a folder, e.g., using drive_mkdir(). If left as NULL, the function will create a cloud folder with name from last two folder levels of the cachePath path, : paste0(basename(dirname(cachePath)), "_", basename(cachePath)). This cloudFolderID will be added to options("reproducible.cloudFolder") but this will not persist across sessions. If this is a character string, it will treat this as a folder name to create or use on GoogleDrive.
drv	an object that inherits from DBIDriver, or an existing DBIConnection object (in order to clone an existing connection).
conn	A DBIConnection object, as returned by dbConnect().
verbose	Numeric, -1 silent (where possible), 0 being very quiet, 1 showing more messaging, 2 being more messaging, etc. Default is 1. Above 3 will output much more information about the internals of Caching, which may help diagnose Caching challenges. Can set globally with an option, e.g., options('reproducible.verbose' = 0) to reduce t
...	Other arguments. Can be in the form of tagKey = tagValue, such as, class = "numeric" to find all entries that are numerics in the cache. Note: the special cases of cacheId and fun have their own named arguments in these functions. Also can be regexp = xx, where xx is TRUE if the user is passing a regular expression. Otherwise, userTags will need to be exact matches. Default is missing, which is the same as TRUE. If there are errors due to regular expression problem, try FALSE. For cc, it is passed to clearCache, e.g., ask, userTags. For showCache, it can also be sorted = FALSE to return the object unsorted.

Value

A `data.table` object showing the subset of items in the cache, located at `cachePath` of the `sim` object, if `sim` is provided, or located in `cachePath`. For `clearCache` (invoked for its side effect of clearing objects matching `userTags`, or those between `after` or `before`), the returned `data.table` shows the removed items (invisibly).

`clearCacheEventsOnly` *Convenience wrapper around clearCache for SpaDES events*

Description

This will clear only the event- and module-level caching that is triggered using a module parameter, `.useCache`.

Usage

```
clearCacheEventsOnly(
  ask = TRUE,
  x = getOption("reproducible.cachePath"),
  dryRun = FALSE,
  verbose = getOption("reproducible.verbose")
)
```

Arguments

<code>ask</code>	Logical. If FALSE, then it will not ask to confirm deletions using <code>clearCache</code> or <code>keepCache</code> . Default is TRUE
<code>x</code>	A <code>simList</code> or a directory containing a valid Cache repository. Note: For compatibility with <code>Cache</code> argument, <code>cachePath</code> can also be used instead of <code>x</code> , though <code>x</code> will take precedence.
<code>dryRun</code>	logical. If FALSE, the default, then the function will deleted entries in the Cache. If TRUE, the function will identify which events and <code>.inputObjects</code> will be deleted, without deleting them.
<code>verbose</code>	Numeric, -1 silent (where possible), 0 being very quiet, 1 showing more messaging, 2 being more messaging, etc. Default is 1. Above 3 will output much more information about the internals of Caching, which may help diagnose Caching challenges. Can set globally with an option, e.g., <code>options('reproducible.verbose' = 0)</code> to reduce t

Value

A list of individual `clearCache` outputs, one for each event that was cleared.

convertToPackage	<i>Convert standard module code into an R package</i>
------------------	---

Description

EXPERIMENTAL – USE WITH CAUTION. This function attempts to convert a SpaDES module to the closest rendition of the same functionality, but in an R package. The main change is that instead of SpaDES.core parsing the functions using custom parsing tools, it will use pkgload::load_all on the package functions. These

Usage

```
convertToPackage(
  module = NULL,
  path = getOption("spades.modulePath"),
  buildDocuments = TRUE
)
```

Arguments

module	Character string of module name, without path
path	Character string of modulePath. Defaults to getOption("spades.modulePath").
buildDocuments	A logical. If TRUE, the default, then the documentation will be built, if any exists, using roxygen2::roxygenise.

Details

convertToPackage will:

1. move any functions that were defined within the main module file (moduleName.R) into the R folder, with the same name, but ending with Fns.R;
2. keep the defineModule(...) function call with all the metadata in the same file, moduleName.R, but with all other content removed, i.e., only the defineModule(...) will be here.
3. build documentation from all the **roxygen2** tags
4. places one **roxygen2** tag, @export in front of the doEvent.moduleName function, so that the function can be found by SpaDES.core
5. All other functions will be kept "private", i.e., not exported, unless the user manually adds @export, as per a normal package
6. will make a DESCRIPTION file from the SpaDES module metadata
7. will make a NAMESPACE file from the **roxygen2** tags (e.g., @export)

A user can continue to use the module code as before, i.e., by editing it and putting browser() etc. It will be parsed during simInit. Because the functions are "in a package", they are automatically namespaced with each other, so that when you want to use a function from that package, there is no need to put a prefix with the package name.

This function does not install anything (e.g., `devtools::install`). After running this function, `simInit` will automatically detect that this is now a package and will load the functions (via `pkgload::load_all`) from the source files. This will have the effect that it emulates the "non-package" behaviour of a SpaDES module exactly. After running this function, current tests show no impact on module behaviour, other than event-level and module-level Caching will show changes and will be rerun. Function-level Caching appears unaffected. In other words, this should cause no changes to running the module code via `simInit` and `spades`.

This function will create and fill a minimal DESCRIPTION file. This will leave the `defineModule` function call as the only code in the main module file. This `defineModule` and a `doEvent.xxx` are the only 2 elements that are required for an R package to be considered a SpaDES module. With these changes, the module should still function normally, but will be able to act like an R package, e.g., for writing function documentation with `roxygen2`, using the `testthat` infrastructure, etc.

This function is intended to be run once for a module that was created using the "standard" SpaDES module structure (e.g., from a `newModule` call). There is currently no way to "revert" the changes from R (though it can be done using version control utilities if all files are under version control, e.g., GitHub). Currently `SpaDES.core` identifies a module as being a package if it has a DESCRIPTION file, or if it has been installed to the `.libPaths()` e.g., via `devtools::install` or the like. So one can simply remove the package from `.libPaths` and delete the DESCRIPTION file and `SpaDES.core` will treat it as a normal module.

Value

Invoked for its side effects. There will be a new or modified DESCRIPTION file in the root directory of the module. Any functions that were in the main module script (i.e., the `.R` file whose filename is the name of the module and is in the root directory of the module) will be moved to individual `.R` files in the `R` folder. Any function with a dot prefix will have the dot removed in its respective filename, but the function name is unaffected.

Currently, `SpaDES.core` does not install the package under any circumstances. It will load it via `pkgdown::load_all`, and optionally (`option("spades.moduleDocument" = TRUE)`) build documentation via `roxygen2::roxygenise` within the `simInit` call. This means that any modifications to source code will be read in during the `simInit` call, as is the practice when a module is not a package.

invoked for the side effect of converting a module to a package

Reverting

Currently, this is not a reversible process. We recommend trying one module at a time, running your code. If all seems to work, then great. Commit the changes. If things don't seem to work, then revert the changes and continue on as before. Ideally, file a bug report on the `SpaDES.core` GitHub.com pages.

Currently

Exported functions

The only function that will be exported by default is the `doEvent.xxx`, where `xxx` is the module name. If any other module is to be exported, it must be explicitly exported with e.g., `@export`, and then building the NAMESPACE file, e.g., via `devtools::document(moduleRootPath)`. NOTE: as

long as all the functions are being used inside each other, and they all can be traced back to a call in `doEvent.xxx`, then there is no need to export anything else.

DESCRIPTION

The DESCRIPTION file that is created (destroying any existing DESCRIPTION file) with this function will have several elements that a user may wish to change. Notably, all packages that were in `reqdPkgs` in the SpaDES module metadata will be in the Imports section of the DESCRIPTION. To accommodate the need to see these functions, a new R script, `imports.R` will be created with `@import` for each package in `reqdPkgs` of the module metadata. However, if a module already has used `@importFrom` for importing a function from a package, then the generic `@import` will be omitted for that (those) package(s). So, a user should likely follow standard R package best practices and use `@importFrom` to identify the specific functions that are required within external packages, thereby limiting function name collisions (and the warnings that come with them).

Other elements of a standard DESCRIPTION file that will be missing or possibly inappropriately short are `Title`, `Description`, `URL`, `BugReports`.

Installing as a package

There is no need to "install" the source code as a package because `simInit` will load it on the fly. But, there may be reasons to install it, e.g., to have access to individual functions, help manual, running tests etc. To do this, simply use the `devtools::install(pathToModuleRoot)`. Even if it is installed, `simInit` will nevertheless run `pkgload::load_all` to ensure the `spades` call will be using the current source code.

Examples

```
if (requireNamespace("ggplot2") && requireNamespace("pkgload") ) {
  tmpdir <- tempdir2()
  newModule("test", tmpdir, open = FALSE)
  convertToPackage("test", path = tmpdir)
}
```

Copy, simList-method *Copy for simList class objects*

Description

Because a `simList` works with an environment to hold all objects, all objects within that slot are pass-by-reference. That means it is not possible to simply copy an object with an assignment operator: the two objects will share the same objects. As one `simList` object changes so will the other. When this is not the desired behaviour, use this function.

Usage

```
## S4 method for signature 'simList'
Copy(object, objects, queues, modules, ...)
```

Arguments

object	An R object (likely containing environments) or an environment.
objects	Whether the objects contained within the <code>simList</code> environment should be copied. Default TRUE, which may be slow.
queues	Logical. Should the events queues (events, current, completed) be deep copied via <code>data.table::copy()</code>
modules	Logical. Should list of modules be copied.
...	Only used for custom Methods

Details

`simList` objects can contain a lot of information, much of which could be in pass-by-reference objects (e.g., `data.table` class), and objects that are file-backed, such as some `Raster*`-class objects. For all the objects that are file-backed, it is likely *very* important to give unique file-backed directories. This should be passed here, which gets passed on to the many methods of `reproducible::Copy()`.

Value

a copy of object

Note

uses capital C, to limit confusion with e.g., `data.table::copy()`.

Author(s)

Eliot McIntire

See Also

[reproducible::Copy\(\)](#)

copyModule

Create a copy of an existing module

Description

Create a copy of an existing module

Usage

```
copyModule(from, to, path, ...)

## S4 method for signature 'character,character,character'
copyModule(from, to, path, ...)

## S4 method for signature 'character,character,missing'
copyModule(from, to, path, ...)
```

Arguments

from	The name of the module to copy.
to	The name of the copy.
path	The path to a local module directory. Defaults to the path set by the <code>spades.modulePath</code> option. See setPaths() .
...	Additional arguments to <code>file.copy</code> , e.g., <code>overwrite = TRUE</code> .

Value

Invisible logical indicating success (TRUE) or failure (FALSE).

Author(s)

Alex Chubaty

createDESCRIPTIONandDocs

Convert standard module code into an R package

Description

EXPERIMENTAL – USE WITH CAUTION. This function will create a DESCRIPTION file if one does not exist, based on the module metadata. If one exists, it will update it with any additional information: **it will not remove packages that are removed from the metadata.** It will create, if one does not exist, or update a `.Rbuildignore` file. If `importAll = TRUE` It will create a file named `R/imports.R`, which will import all functions. This function will make no changes to any existing source file of a `SpaDES.module`. If `buildDocumentation = TRUE`, it will build documentation `.Rd` files from `roxygen2` tags.

Usage

```
createDESCRIPTIONandDocs(
  module = NULL,
  path = getOption("spades.modulePath"),
  importAll = TRUE,
  buildDocuments = TRUE,
  verbose = getOption("Require.verbose")
)
```

Arguments

module	Character string of module name, without path
path	Character string of modulePath. Defaults to <code>getOption("spades.modulePath")</code> .
importAll	A logical. If TRUE, then every package named in <code>reqdPkgs</code> will have an <code>@importFrom <pkgName></code> , meaning every function from every package will be imported. If FALSE, then only functions explicitly imported using <code>@importFrom <pkgName> <functionName></code> will be imported.
buildDocuments	A logical. If TRUE, the default, then the documentation will be built, if any exists, using <code>roxygen2::roxygenise</code> .
verbose	Numeric, -1 silent (where possible), 0 being very quiet, 1 showing more messaging, 2 being more messaging, etc. Default is 1. Above 3 will output much more information about the internals of Caching, which may help diagnose Caching challenges. Can set globally with an option, e.g., <code>options('reproducible.verbose' = 0)</code> to reduce t

Details

This function does not install anything (e.g., `devtools::install`). After running this function, `simInit` will automatically detect that this is now a package and will load the functions (via `pkgload::load_all`) from the source files. This will have the effect that it emulates the "non-package" behaviour of a SpaDES module exactly. After running this function, current tests show no impact on module behaviour, other than event-level and module-level Caching will show changes and will be rerun. Function-level Caching appears unaffected. In other words, this should cause no changes to running the module code via `simInit` and `spades`.

This function will create and fill a minimal DESCRIPTION file. This will leave the `defineModule` function call as the only code in the main module file. This `defineModule` and a `doEvent.xxx` are the only 2 elements that are required for an R package to be considered a SpaDES module. With these changes, the module should still function normally, but will be able to act like an R package, e.g., for writing function documentation with `roxygen2`, using the `testthat` infrastructure, etc.

This function is intended to be run once for a module that was created using the "standard" SpaDES module structure (e.g., from a `newModule` call). There is currently no way to "revert" the changes from R (though it can be done using version control utilities if all files are under version control, e.g., GitHub). Currently `SpaDES.core` identifies a module as being a package if it has a DESCRIPTION file, or if it has been installed to the `.libPaths()` e.g., via `devtools::install` or the like. So one can simply remove the package from `.libPaths` and delete the DESCRIPTION file and `SpaDES.core` will treat it as a normal module.

Value

Invoked for its side effects. There will be a new or modified DESCRIPTION file in the root directory of the module. Any functions that were in the main module script (i.e., the .R file whose filename is the name of the module and is in the root directory of the module) will be moved to individual .R files in the R folder. Any function with a dot prefix will have the dot removed in its respective filename, but the function name is unaffected.

Currently, `SpaDES.core` does not install the package under any circumstances. It will load it via `pkgdown::load_all`, and optionally (`option("spades.moduleDocument" = TRUE)`) build documentation via `roxygen2::roxygenise` within the `simInit` call. This means that any modifications

to source code will be read in during the `simInit` call, as is the practice when a module is not a package.

invoked for the side effect of creating DESCRIPTION file, a .Rbuildignore file and possibly building documentation from roxygen2 tags.

Reverting

Currently, this is not a reversible process. We recommend trying one module at a time, running your code. If all seems to work, then great. Commit the changes. If things don't seem to work, then revert the changes and continue on as before. Ideally, file a bug report on the SpaDES.core GitHub.com pages.

Currently

Exported functions

The only function that will be exported by default is the `doEvent.xxx`, where `xxx` is the module name. If any other module is to be exported, it must be explicitly exported with e.g., `@export`, and then building the NAMESPACE file, e.g., via `devtools::document(moduleRootPath)`. NOTE: as long as all the functions are being used inside each other, and they all can be traced back to a call in `doEvent.xxx`, then there is no need to export anything else.

DESCRIPTION

The DESCRIPTION file that is created (destroying any existing DESCRIPTION file) with this function will have several elements that a user may wish to change. Notably, all packages that were in `reqdPkgs` in the SpaDES module metadata will be in the Imports section of the DESCRIPTION. To accommodate the need to see these functions, a new R script, `imports.R` will be created with `@import` for each package in `reqdPkgs` of the module metadata. However, if a module already has used `@importFrom` for importing a function from a package, then the generic `@import` will be omitted for that (those) package(s). So, a user should likely follow standard R package best practices and use `@importFrom` to identify the specific functions that are required within external packages, thereby limiting function name collisions (and the warnings that come with them).

Other elements of a standard DESCRIPTION file that will be missing or possibly inappropriately short are Title, Description, URL, BugReports.

Installing as a package

There is no need to "install" the source code as a package because `simInit` will load it on the fly. But, there may be reasons to install it, e.g., to have access to individual functions, help manual, running tests etc. To do this, simply use the `devtools::install(pathToModuleRoot)`. Even if it is installed, `simInit` will nevertheless run `pkgload::load_all` to ensure the `spades` call will be using the current source code.

Examples

```
if (requireNamespace("ggplot2") && requireNamespace("pkgload") ) {
  tmpdir <- tempdir2()
  newModule("test", tmpdir, open = FALSE)
  createDESCRIPTIONandDocs("test", path = tmpdir)
```

```
}
```

```
createsOutput      Define an output object of a module
```

Description

Used to specify an output object's name, class, description and other specifications.

Usage

```
createsOutput(objectName, objectClass, desc, ...)

## S4 method for signature 'ANY,ANY,ANY'
createsOutput(objectName, objectClass, desc, ...)

## S4 method for signature 'character,character,character'
createsOutput(objectName, objectClass, desc, ...)
```

Arguments

objectName	Character string to define the output object's name.
objectClass	Character string to specify the output object's class.
desc	Text string providing a brief description of the output object. If there are extra spaces or carriage returns, these will be stripped, allowing for multi-line character strings without using paste or multiple quotes.
...	Other specifications of the output object.

Value

A data.frame suitable to be passed to outputObjects in a module's metadata.

Author(s)

Yong Luo

Examples

```
outputObjects <- bindrows(
  createsOutput(objectName = "outputObject1", objectClass = "character",
    desc = "this is for example"),
  createsOutput(objectName = "outputObject2", objectClass = "numeric",
    desc = "this is for example",
    otherInformation = "I am the second output object")
)
```

defineEvent *Alternative way to define events in SpaDES.core*

Description

There are two ways to define what occurs during an event: defining a function called `doEvent.moduleName`, where `moduleName` is the actual module name. This approach is the original approach used in `SpaDES.core`, and it must have an explicit `switch` statement branching on `eventType`. The newer approach (still experimental) uses `defineEvent()`. Instead of creating, `doEvent.moduleName()`, it creates one function for each event, each with the name `doEvent.moduleName.eventName`. This may be a little bit cleaner, but both will still work.

Usage

```
defineEvent(
  sim,
  eventName = "init",
  code,
  moduleName = NULL,
  envir = parent.frame()
)
```

Arguments

<code>sim</code>	A <code>simList</code>
<code>eventName</code>	Character string of the desired event name to define. Default is "init"
<code>code</code>	An expression that defines the code to execute during the event. This will be captured, and pasted into a new function (<code>doEvent.moduleName.eventName</code>), remaining unevaluated until that new function is called.
<code>moduleName</code>	Character string of the name of the module. If this function is used within a module, then it will try to find the module name.
<code>envir</code>	An optional environment to specify where to put the resulting function. The default will place a function called <code>doEvent.moduleName.eventName</code> in the module function location, i.e., <code>sim[[dotMods]][[moduleName]]</code> . However, if this location does not exist, then it will place it in the <code>parent.frame()</code> , with a message. Normally, especially, if used within <code>SpaDES</code> module code, this should be left missing.

See Also

[defineModule\(\)](#), [simInit\(\)](#), [scheduleEvent\(\)](#)

Examples

```

sim <- simInit()

# these put the functions in the parent.frame() which is .GlobalEnv for an interactive user
defineEvent(sim, "init", moduleName = "thisTestModule", code = {
  sim <- Init(sim) # initialize
  # Now schedule some different event for "current time", i.e., will
  # be put in the event queue to run *after* this current event is finished
  sim <- scheduleEvent(sim, time(sim), "thisTestModule", "grow")
}, envir = envir(sim))

defineEvent(sim, "grow", moduleName = "thisTestModule", code = {
  sim <- grow(sim) # grow
  # Now schedule this same event for "current time plus 1", i.e., a "loop"
  sim <- scheduleEvent(sim, time(sim) + 1, "thisTestModule", "grow") # for "time plus 1"
})

Init <- function(sim) {
  sim$messageToWorld <- "Now the sim has an object in it that can be accessed"
  sim$size <- 1 # initializes the size object --> this can be anything, Raster, list, whatever
  message(sim$messageToWorld)
  return(sim) # returns all the things you added to sim as they are in the simList
}

grow <- function(sim) {
  sim$size <- sim$size + 1 # increments the size
  message(sim$size)
  return(sim)
}

# schedule that first "init" event
sim <- scheduleEvent(sim, 0, "thisTestModule", "init")
# Look at event queue
events(sim) # shows the "init" we just added

# this is skipped when running in automated tests; it is fine in interactive use
out <- spades(sim)

```

defineModule

Define a new module.

Description

Specify a new module's metadata as well as object and package dependencies. Packages are loaded during this call. Any or all of these can be missing, with missing values set to defaults

Usage

```
defineModule(sim, x)

## S4 method for signature 'simList,list'
defineModule(sim, x)
```

Arguments

sim	A <code>simList</code> object from which to extract element(s) or in which to replace element(s).
x	A list with a number of named elements, referred to as the metadata. See details.

Value

Updated `simList` object.

Required metadata elements

name	Module name. Must match the filename (without the <code>.R</code> extension). This is currently not parsed by SpaDES.
description	Brief description of the module. This is currently not parsed by SpaDES; it is for human readers only.
keywords	Author-supplied keywords. This is currently not parsed by SpaDES; it is for human readers only.
childModules	If this contains any character vector, then it will be treated as a parent module. If this is a parent module, the
authors	Module author information (as a vector of <code>person()</code> objects. This is currently not parsed by SpaDES; it is
version	Module version number (will be coerced to <code>numeric_version()</code> if a character or numeric are supplied). T
spatialExtent	The spatial extent of the module supplied via <code>terra::ext</code> . This is currently unimplemented. Once implem
timeframe	Vector (length 2) of POSIXt dates specifying the temporal extent of the module. Currently unimplemented.
timeunit	Time scale of the module (e.g., "day", "year"). If this is not specified, then <code>.timeunitDefault()</code> will be us
citation	List of character strings specifying module citation information. Alternatively, a list of filenames of <code>.bib</code> o
documentation	List of filenames referring to module documentation sources. This is currently not parsed by SpaDES; it is
loadOrder	Named list of length 0, 1, or 2, with names being <code>after</code> and <code>before</code> . Each element should be a character st
reqdPkgs	List of R package names required by the module. These packages will be loaded when <code>simInit</code> is called. R
parameters	A <code>data.frame</code> specifying the parameters used in the module. Usually produced by <code>rbind</code> -ing the outputs of
inputObjects	A <code>data.frame</code> specifying the data objects expected as inputs to the module, with columns <code>objectName</code> (cl
outputObjects	A <code>data.frame</code> specifying the data objects output by the module, with columns identical to those in <code>inputO</code>

Author(s)

Alex Chubaty

See Also

[moduleDefaults\(\)](#), [defineEvent\(\)](#)

Examples

```
## a default version of the defineModule is created with a call to newModule
newModule("test", path = tempdir(), open = FALSE)

## view the resulting module file
if (interactive()) file.edit(file.path(tempdir(), "test", "test.R"))
```

defineParameter	<i>Define a parameter used in a module</i>
-----------------	--

Description

Used to specify a parameter's name, value, and set a default. The min and max arguments are ignored by simInit or spades; they are for human use only. To ensure that a user cannot set parameters outside of a range of values, the module developer should use assertions in their module code.

Usage

```
defineParameter(name, class, default, min, max, desc, ...)
```

Arguments

name	Character string giving the parameter name.
class	Character string giving the parameter class.
default	The default value to use when none is specified by the user. Non-standard evaluation is used for the expression.
min	With max, used to define a suitable range of values. Non-standard evaluation is used for the expression. <i>These are not tested by simInit or spades.</i> These are primarily for human use, i.e., to tell a module user what values the module expects.
max	With min, used to define a suitable range of values. Non-standard evaluation is used for the expression. <i>These are not tested by simInit or spades.</i> These are primarily for human use, i.e., to tell a module user what values the module expects.
desc	Text string providing a brief description of the parameter. If there are extra spaces or carriage returns, these will be stripped, allowing for multi-line character strings without using paste or multiple quotes.
...	A convenience that allows writing a long desc without having to use paste; any character strings after desc will be pasted together with desc.

Value

a data.frame

Note

Be sure to use the correct NA type: logical (NA), integer (NA_integer_), real (NA_real_), complex (NA_complex_), or character (NA_character_). See [NA\(\)](#).

Author(s)

Alex Chubaty and Eliot McIntire

See Also

[P\(\)](#), [params\(\)](#) for accessing these parameters in a module.

Examples

```
parameters = rbind(
  defineParameter("lambda", "numeric", 1.23, desc = "intrinsic rate of increase"),
  defineParameter("P", "numeric", 0.2, 0, 1, "probability of attack"),

  # multi-line desc without quotes on each line -- spaces and carriage returns are stripped
  defineParameter("rate", "numeric", 0.2, 0, 1,
    "rate of arrival. This is in individuals
    per day. This can be modified
    by the user"),
  # multi-line desc with quotes on each line
  defineParameter("times", "numeric", 0.2, 0, 1,
    desc = "The times during the year ",
    "that events will occur ",
    "with possibility of random arrival times")
)

# Create a new module, then access parameters using `P`
tmpdir <- file.path(tempdir(), "test")
checkPath(tmpdir, create = TRUE)

# creates a new, "empty" module -- it has defaults for everything that is required
newModule("testModule", tmpdir, open = FALSE)

# Look at new module code -- see defineParameter
if (interactive()) file.edit(file.path(tmpdir, "testModule", "testModule.R"))

# initialize the simList
if (requireNamespace("ggplot2", quietly = TRUE)) {
  # Some things not necessary in this example, if not interactive (like plotting)
  opts <- if (interactive()) list() else
    options(spades.plot = NA, spades.useRequire = FALSE,
      spades.moduleCodeChecks = FALSE)
  mySim <- simInit(modules = "testModule",
    paths = list(modulePath = tmpdir))

  # Access one of the parameters -- because this line is not inside a module
```

```

# function, we must specify the module name. If used within a module,
# we can omit the module name
P(mySim, module = "testModule") # gets all params in a module
P(mySim, ".useCache", "testModule") # just one param
options(opts)
}
unlink(tmpdir, recursive = TRUE)

```

depsEdgeList

Build edge list for module dependency graph

Description

Build edge list for module dependency graph

Usage

```
depsEdgeList(sim, plot, includeOutputs = FALSE)
```

```
## S4 method for signature 'simList,logical'
depsEdgeList(sim, plot, includeOutputs = FALSE)
```

```
## S4 method for signature 'simList,missing'
depsEdgeList(sim, plot)
```

Arguments

sim	A simList object.
plot	Logical indicating whether the edgelist (and subsequent graph) will be used for plotting. If TRUE, duplicated rows (i.e., multiple object dependencies between modules) are removed so that only a single arrow is drawn connecting the modules. Default is FALSE.
includeOutputs	Logical indicating whether objects that are only "outputs" will be kept and labelled as <i>OUTPUTS</i> analogous to <i>INPUTS</i> . This is relevant in the case of objectSynonyms. If an object is not used by another module then it will be removed from this depsEdgeList return; this keeps these so can be determined if they are e.g., suppliedElsewhere.

Value

A data.table whose first two columns give a list of edges and remaining columns the attributes of the dependency objects (object name, class, etc.).

Author(s)

Alex Chubaty

depsGraph	<i>Build a module dependency graph</i>
-----------	--

Description

Build a module dependency graph

Usage

```
depsGraph(sim, plot)

## S4 method for signature 'simList,logical'
depsGraph(sim, plot)

## S4 method for signature 'simList,missing'
depsGraph(sim)
```

Arguments

sim	A simList object.
plot	Logical indicating whether the edgelist (and subsequent graph) will be used for plotting. If TRUE, duplicated rows (i.e., multiple object dependencies between modules) are removed so that only a single arrow is drawn connecting the modules. Default is FALSE.

Value

An igraph() object.

Author(s)

Alex Chubaty

dhour	<i>SpaDES time units</i>
-------	--------------------------

Description

SpaDES modules commonly use approximate durations that divide with no remainder among themselves. For example, models that simulate based on a "week" timestep, will likely want to fall in lock step with a second module that is a "year" timestep. Since, weeks, months, years don't really have this behaviour because of: leap years, leap seconds, not quite 52 weeks in a year, months that are of different duration, etc. We have generated a set of units that work well together that are based on the astronomical or "Julian" year. In an astronomical year, leap years are added within each year with an extra 1/4 day, (i.e., 1 year == 365.25 days); months are defined as year/12, and weeks as year/52.

Usage

```
dhour(x)

dmin(x)

dday(x)

dyears(x)

## S4 method for signature 'numeric'
dyears(x)

dmonths(x)

## S4 method for signature 'numeric'
dmonths(x)

dweeks(x)

## S4 method for signature 'numeric'
dweeks(x)

dweek(x)

dmonth(x)

dyear(x)

dsecond(x)

dNA(x)

## S4 method for signature 'ANY'
dNA(x)
```

Arguments

x numeric. Number of the desired units

Details

When these units are not correct, a module developer can create their own time unit, and create a function to calculate the number of seconds in that unit using the "d" prefix (for duration), following the lubridate package standard: `ddecade <- function(x) lubridate::duration(dyear(10))`. Then the module developer can use "decade" as the module's time unit.

Value

Number of seconds within each unit

Author(s)

Eliot McIntire

doCallSafe *Memory safe alternative to do.call*

Description

doCallSafe is an alternative implementation for do.call that does not evaluate the args prior to running. This means that R does not become unresponsive when there are large objects in the args. This should be used *always* instead of do.call, whenever there are possibly large objects within the args. This is a verbatim copy from package Gmisc at <https://search.r-project.org/CRAN/refmans/Gmisc/html/fastDoCall.html>

Usage

```
doCallSafe(what, args, quote = FALSE, envir = parent.frame())
```

Arguments

what	either a function or a non-empty character string naming the function to be called.
args	a <i>list</i> of arguments to the function call. The names attribute of args gives the argument names.
quote	a logical value indicating whether to quote the arguments.
envir	an environment within which to evaluate the call. This will be most useful if what is a character string and the arguments are symbols or quoted expressions.

Value

Same as do.call, but without the memory inefficiency.

downloadData *Download module data*

Description

Download external data for a module if not already present in the module directory, or if there is a checksum mismatch indicating that the file is not the correct one.

Usage

```
downloadData(  
  module,  
  path,  
  quiet,  
  quickCheck = FALSE,  
  overwrite = FALSE,  
  files = NULL,  
  checked = NULL,  
  urls = NULL,  
  children = NULL,  
  ...  
)  
  
## S4 method for signature 'character,character,logical'  
downloadData(  
  module,  
  path,  
  quiet,  
  quickCheck = FALSE,  
  overwrite = FALSE,  
  files = NULL,  
  checked = NULL,  
  urls = NULL,  
  children = NULL,  
  ...  
)  
  
## S4 method for signature 'character,missing,missing'  
downloadData(module, quickCheck, overwrite, files, checked, urls, children)  
  
## S4 method for signature 'character,missing,logical'  
downloadData(  
  module,  
  quiet,  
  quickCheck,  
  overwrite,  
  files,  
  checked,  
  urls,  
  children  
)  
  
## S4 method for signature 'character,character,missing'  
downloadData(  
  module,  
  path,  
  quickCheck,
```

```

    overwrite,
    files,
    checked,
    urls,
    children
  )

```

Arguments

module	Character string giving the name of the module.
path	Character string giving the path to the module directory.
quiet	Logical. This is passed to <code>download.file</code> . Default is <code>FALSE</code> .
quickCheck	Logical. If <code>TRUE</code> , then the check with local data will only use <code>file.size</code> instead of <code>digest::digest</code> . This is faster, but potentially much less robust.
overwrite	Logical. Should local data files be overwritten in case they exist? Default is <code>FALSE</code> .
files	A character vector of length 1 or more if only a subset of files should be checked in the 'CHECKSUMS.txt' file.
checked	The result of a previous checksums call. This should only be used when there is no possibility that the file has changed, i.e., if <code>downloadData</code> is called from inside another function.
urls	Character vector of urls from which to get the data. This is automatically found from module metadata when this function invoked with <code>SpaDES.core::downloadModule(..., data = TRUE)</code> . See also <code>reproducible::prepInputs()</code> .
children	The character vector of child modules (without path) to also run <code>downloadData</code> on
...	Passed to <code>reproducible::preProcess()</code> , e.g., <code>purge</code>

Details

`downloadData` requires a checksums file to work, as it will only download the files specified therein. Hence, module developers should make sure they have manually downloaded all the necessary data and ran checksums to build a checksums file.

There is an experimental attempt to use the **googledrive** package to download data from a shared (publicly or with individual users) file. To try this, put the Google Drive URL in `sourceURL` argument of `expectsInputs` in the module metadata, and put the filename once downloaded in the `objectName` argument. If using RStudio Server, you may need to use "out of band" authentication by setting `options(httr_oob_default = TRUE)`. To avoid caching of Oauth credentials, set `options(httr_oauth_cache = TRUE)`.

There is also an experimental option for the user to make a new 'CHECKSUMS.txt' file if there is a `sourceURL` but no entry for that file. This is experimental and should be used with caution.

Value

Invisibly, a list of downloaded files.

Author(s)

Alex Chubaty & Eliot McIntire

See Also

[reproducible::prepInputs\(\)](#), [checksums\(\)](#), and [downloadModule\(\)](#) for downloading modules and building a checksums file.

Examples

```
## In metadata, each expectsInput has a sourceURL;
## downloadData will look for that and download if it defined;
## however this sample module has all NAs for sourceURL, so nothing to download.
if (FALSE) {
  modulePath <- getSampleModules(tempdir())
  downloadData("caribouMovement", path = modulePath)
}
```

downloadModule

Download a module from a SpaDES module GitHub repository

Description

Download a .zip file of the module and extract (unzip) it to a user-specified location.

Usage

```
downloadModule(
  name,
  path,
  version,
  repo,
  data,
  quiet,
  quickCheck = FALSE,
  overwrite = FALSE,
  verbose = getOption("reproducible.verbose")
)

## S4 method for signature
## 'character,character,character,character,logical,logical,ANY,logical'
downloadModule(
  name,
  path,
  version,
  repo,
```

```

    data,
    quiet,
    quickCheck = FALSE,
    overwrite = FALSE,
    verbose = getOption("reproducible.verbose")
  )

## S4 method for signature
## 'character,missing,missing,missing,missing,ANY,ANY'
downloadModule(name, quickCheck, overwrite)

## S4 method for signature 'character,ANY,ANY,ANY,ANY,ANY,ANY,ANY,ANY'
downloadModule(name, path, version, repo, data, quiet, quickCheck, overwrite)

```

Arguments

name	Character string giving the module name.
path	Character string giving the location in which to save the downloaded module.
version	The module version to download. (If not specified, or NA, the most recent version will be retrieved.)
repo	GitHub repository name, specified as "username/repo". Default is "PredictiveEcology/SpaDES-modu" which is specified by the global option <code>spades.moduleRepo</code> . Only master/main branches can be used at this point.
data	Logical. If TRUE, then the data that is identified in the module metadata will be downloaded, if possible. Default FALSE.
quiet	Logical. This is passed to <code>download.file</code> (default FALSE).
quickCheck	Logical. If TRUE, then the check with local data will only use <code>file.size</code> instead of <code>digest::digest</code> . This is faster, but potentially much less robust.
overwrite	Logical. Should local module files be overwritten in case they exist? Default FALSE.
verbose	Numeric, -1 silent (where possible), 0 being very quiet, 1 showing more messaging, 2 being more messaging, etc. Default is 1. Above 3 will output much more information about the internals of Caching, which may help diagnose Caching challenges. Can set globally with an option, e.g., <code>options('reproducible.verbose' = 0)</code> to reduce t

Details

Currently only works with GitHub repositories where modules are located in a `modules` directory in the root tree on the master branch. Module `.zip` files' names should contain the version number and be inside their respective module folders (see `zipModule()` for zip compression of modules).

Value

A list of length 2. The first element is a character vector containing a character vector of extracted files for the module. The second element is a `tbl` with details about the data that is relevant for the function, including whether it was downloaded or not, and whether it was renamed (because there was a local copy that had the wrong file name).

Note

downloadModule uses the GITHUB_PAT environment variable if a value is set. This alleviates 403 errors caused by too-frequent downloads. Generate a GitHub personal access token with no additional permissions at <https://github.com/settings/tokens>, and add this key to '.Renviro' as GITHUB_PAT=<your-github-pat-here>.

The default is to overwrite any existing files in the case of a conflict.

Author(s)

Alex Chubaty and Eliot McIntire

See Also

[zipModule\(\)](#) for creating module .zip folders.

 envir

Simulation environment

Description

Accessor functions for the .xData slot, which is the default virtual slot for an S4 class object that inherits from an S3 object (specifically, the simList inherits from environment) in a simList object. These are included for advanced users.

Usage

```
envir(sim)

## S4 method for signature 'simList'
envir(sim)

envir(sim) <- value

## S4 replacement method for signature 'simList'
envir(sim) <- value
```

Arguments

sim	A simList object from which to extract element(s) or in which to replace element(s).
value	The object to be stored at the slot.

Details

Currently, only get and set methods are defined. Subset methods are not.

Value

Returns or sets the value of the slot from the `simList` object.

Author(s)

Alex Chubaty

See Also

[SpaDES.core-package](#), specifically the section 1.2.8 on `simList` environment.

Other functions to access elements of a 'simList' object: [.addDepends\(\)](#), [checkpointFile\(\)](#), [events\(\)](#), [globals\(\)](#), [inputs\(\)](#), [modules\(\)](#), [objs\(\)](#), [packages\(\)](#), [params\(\)](#), [paths\(\)](#), [progressInterval\(\)](#), [times\(\)](#)

eventDiagram

Simulation event diagram

Description

Create a Gantt Chart representing the events in a completed simulation. This event diagram is constructed using the completed event list. To change the number of events shown, provide an `n` argument.

Usage

```
eventDiagram(sim, n, startDate, ...)
```

```
## S4 method for signature 'simList,numeric,character'
```

```
eventDiagram(sim, n, startDate, ...)
```

```
## S4 method for signature 'simList,missing,character'
```

```
eventDiagram(sim, n, startDate, ...)
```

```
## S4 method for signature 'simList,missing,missing'
```

```
eventDiagram(sim, n, startDate, ...)
```

Arguments

<code>sim</code>	A <code>simList</code> object (typically corresponding to a completed simulation).
<code>n</code>	The number of most recently completed events to plot.
<code>startDate</code>	A character representation of date in YYYY-MM-DD format.
<code>...</code>	Additional arguments passed to <code>mermaid</code> . Useful for specifying height and width.

Details

Simulation time is presented on the x-axis, starting at date `startDate`. Each module appears in a colour-coded row, within which each event for that module is displayed corresponding to the sequence of events for that module. Note that only the start time of the event is meaningful in these figures: the width of the bar associated with a particular module's event DOES NOT correspond to an event's "duration".

Based on this Stack Overflow answer: <https://stackoverflow.com/a/29999300/1380598>.

Value

Plots an event diagram as Gantt Chart, invisibly returning a mermaid object.

Note

A red vertical line corresponding to the current date may appear on the figure. This is useful for Gantt Charts generally but can be considered a 'bug' here.

Author(s)

Alex Chubaty

See Also

DiagrammeR::mermaid.

events

Simulation event lists

Description

Accessor functions for the events and completed slots of a `simList` object. These path functions will extract the values that were provided to the `simInit` function in the `path` argument.

Usage

```
events(sim, unit)

## S4 method for signature 'simList,character'
events(sim, unit)

## S4 method for signature 'simList,missing'
events(sim, unit)

events(sim) <- value

## S4 replacement method for signature 'simList'
events(sim) <- value
```

```

conditionalEvents(sim, unit)

## S4 method for signature 'simList,character'
conditionalEvents(sim, unit)

## S4 method for signature 'simList,missing'
conditionalEvents(sim, unit)

current(sim, unit)

## S4 method for signature 'simList,character'
current(sim, unit)

## S4 method for signature 'simList,missing'
current(sim, unit)

current(sim) <- value

## S4 replacement method for signature 'simList'
current(sim) <- value

completed(sim, unit, times = TRUE)

## S4 method for signature 'simList,character'
completed(sim, unit, times = TRUE)

## S4 method for signature 'simList,missing'
completed(sim, unit, times = TRUE)

completed(sim) <- value

## S4 replacement method for signature 'simList'
completed(sim) <- value

```

Arguments

sim	A simList object from which to extract element(s) or in which to replace element(s).
unit	Character. One of the time units used in SpaDES.
value	The object to be stored at the slot.
times	Logical. Should this function report the clockTime.

Details

By default, the event lists are shown when the simList object is printed, thus most users will not require direct use of these methods.

events Scheduled simulation events (the event queue).
 completed Completed simulation events.

Currently, only get and set methods are defined. Subset methods are not.

Value

Returns or sets the value of the slot from the `simList` object.

Note

Each event is represented by a `data.table::data.table()` row consisting of:

- `eventTime`: The time the event is to occur.
- `moduleName`: The module from which the event is taken.
- `eventType`: A character string for the programmer-defined event type.

See Also

[SpaDES.core-package](#), specifically the section 1.2.6 on Simulation event queues.

Other functions to access elements of a 'simList' object: `.addDepends()`, `checkpointFile()`, `envir()`, `globals()`, `inputs()`, `modules()`, `objs()`, `packages()`, `params()`, `paths()`, `progressInterval()`, `times()`

expectsInput

Define an input object that the module expects.

Description

Used to specify an input object's name, class, description, source url and other specifications.

Usage

```
expectsInput(objectName, objectClass, desc, sourceURL, ...)
```

```
## S4 method for signature 'ANY,ANY,ANY,ANY'
```

```
expectsInput(objectName, objectClass, desc, sourceURL, ...)
```

```
## S4 method for signature 'character,character,character,character'
```

```
expectsInput(objectName, objectClass, desc, sourceURL, ...)
```

```
## S4 method for signature 'character,character,character,missing'
```

```
expectsInput(objectName, objectClass, desc, sourceURL, ...)
```

Arguments

objectName	Character string to define the input object's name.
objectClass	Character string to specify the input object's class.
desc	Text string providing a brief description of the input object. If there are extra spaces or carriage returns, these will be stripped, allowing for multi-line character strings without using paste or multiple quotes.
sourceURL	Character string to specify an URL to reach the input object, default is NA.
...	Other specifications of the input object.

Value

A data.frame suitable to be passed to inputObjects in a module's metadata.

Author(s)

Yong Luo

Examples

```
inputObjects <- bindrows(
  expectsInput(objectName = "inputObject1", objectClass = "character",
    desc = "this is for example", sourceURL = "not available"),
  expectsInput(objectName = "inputObject2", objectClass = "numeric",
    desc = "this is for example", sourceURL = "not available",
    otherInformation = "I am the second input object")
)
```

extractURL

Extract a url from module metadata

Description

This will get the sourceURL for the object named.

Usage

```
extractURL(objectName, sim, module)

## S4 method for signature 'character,missing'
extractURL(objectName, sim, module)

## S4 method for signature 'character,simList'
extractURL(objectName, sim, module)
```

Arguments

objectName	A character string of the object name in the metadata.
sim	A simList object from which to extract the sourceURL
module	An optional character string of the module name whose metadata is to be used. If omitted, the function will use the currentModule(sim), if defined.

Value

The url.

Author(s)

Eliot McIntire

fileName	<i>Extract filename (without extension) of a file</i>
----------	---

Description

Extract filename (without extension) of a file

Usage

fileName(x)

Arguments

x	List or character vector
---	--------------------------

Value

A character vector.

Author(s)

Eliot McIntire

getMapPath	<i>Get copies of sample files for examples and tests</i>
------------	--

Description

Get copies of sample files for examples and tests

Usage

```
getMapPath(tmpdir)
getSampleModules(tmpdir)
```

Arguments

tmpdir character specifying the path to a temporary directory (e.g., tempdir())

Value

character vector of filepaths to the copied files

getModuleVersion	<i>Find the latest module version from a SpaDES module repository</i>
------------------	---

Description

Modified from <https://stackoverflow.com/a/25485782/1380598>.

Usage

```
getModuleVersion(
  name,
  repo,
  token,
  moduleFiles = NULL,
  verbose = getOption("reproducible.verbose")
)

## S4 method for signature 'character,character'
getModuleVersion(
  name,
  repo,
  token,
  moduleFiles = NULL,
  verbose = getOption("reproducible.verbose")
)
```

```
## S4 method for signature 'character,missing'
getModuleVersion(
  name,
  token,
  moduleFiles = NULL,
  verbose = getOption("reproducible.verbose")
)
```

Arguments

name	Character string giving the module name.
repo	GitHub repository name, specified as "username/repo". Default is "PredictiveEcology/SpaDES-modules" which is specified by the global option <code>spades.moduleRepo</code> . Only master/main branches can be used at this point.
token	A github repository token as from <code>gitcreds::gitcreds_get()</code>
moduleFiles	Optional. List of files of the name and repo. If not supplied, this function will get that information by using <code>checkModule</code> .
verbose	Numeric, -1 silent (where possible), 0 being very quiet, 1 showing more messaging, 2 being more messaging, etc. Default is 1. Above 3 will output much more information about the internals of Caching, which may help diagnose Caching challenges. Can set globally with an option, e.g., <code>options('reproducible.verbose' = 0)</code> to reduce t

Details

`getModuleVersion` extracts a module's most recent version by looking at the module `.zip` files contained in the module directory. It takes the most recent version, based on the name of the zip file.

See the modules vignette for details of module directory structure (<https://spades-core.predictiveecology.org/articles/ii-modules.html#module-directory-structure-modulename>), and see our SpaDES-modules repo for details of module repository structure (<https://github.com/PredictiveEcology/SpaDES-modules>).

Value

numeric_version

Author(s)

Alex Chubaty

See Also

[zipModule\(\)](#) for creating module `.zip` folders.

`globals`*Get and set global simulation parameters*

Description

`globals`, and the alias `G`, accesses or sets the "globals" in the `simList`. This currently is not an explicit slot in the `simList`, but it is a `.globals` element in the `params` slot of the `simList`.

Usage

```
globals(sim)

## S4 method for signature 'simList'
globals(sim)

globals(sim) <- value

## S4 replacement method for signature 'simList'
globals(sim) <- value

G(sim)

## S4 method for signature 'simList'
G(sim)

G(sim) <- value

## S4 replacement method for signature 'simList'
G(sim) <- value
```

Arguments

<code>sim</code>	A <code>simList</code> object from which to extract element(s) or in which to replace element(s).
<code>value</code>	The parameter value to be set (in the corresponding module and param).

See Also

[SpaDES.core-package](#), specifically the section 1.2.1 on Simulation Parameters.

Other functions to access elements of a 'simList' object: [.addDepends\(\)](#), [checkpointFile\(\)](#), [envir\(\)](#), [events\(\)](#), [inputs\(\)](#), [modules\(\)](#), [objs\(\)](#), [packages\(\)](#), [params\(\)](#), [paths\(\)](#), [progressInterval\(\)](#), [times\(\)](#)

```
initialize,simList-method
      Generate a simList object
```

Description

Given the name or the definition of a class, plus optionally data to be included in the object, new returns an object from that class.

Given the name or the definition of a class, plus optionally data to be included in the object, new returns an object from that class.

Usage

```
## S4 method for signature 'simList'
initialize(.Object, ...)

## S4 method for signature 'simList_'
initialize(.Object, ...)
```

Arguments

.Object	A simList object.
...	Optional Values passed to any or all slot

```
inputObjects      Metadata accessors
```

Description

These accessors extract the metadata for a module (if specified) or all modules in a simList if not specified.

Usage

```
inputObjects(sim, module, path)

## S4 method for signature 'simList'
inputObjects(sim, module, path)

## S4 method for signature 'missing'
inputObjects(sim, module, path)

outputObjects(sim, module, path)

## S4 method for signature 'simList'
```

```

outputObjects(sim, module, path)

## S4 method for signature 'missing'
outputObjects(sim, module, path)

outputObjectNames(sim, module)

## S4 method for signature 'simList'
outputObjectNames(sim, module)

reqdPkgs(sim, module, modulePath)

## S4 method for signature 'simList'
reqdPkgs(sim, module, modulePath)

## S4 method for signature 'missing'
reqdPkgs(sim, module, modulePath)

documentation(sim, module)

## S4 method for signature 'simList'
documentation(sim, module)

sessInfo(sim)

## S4 method for signature 'simList'
sessInfo(sim)

```

Arguments

sim	A simList object from which to extract element(s) or in which to replace element(s).
module	Character vector of module name(s)
path	The path to the module., i.e., the modulePath. Only relevant if sim not supplied.
modulePath	That path where module can be found. If set already using setPaths, it will use that. This will be ignored if sim is supplied and is required if sim not supplied

Examples

```

# set modulePath
setPaths(modulePath = getSampleModules(tempdir()))
# use Require and reqdPkgs
pkgs <- reqdPkgs(module = c("caribouMovement", "randomLandscapes", "fireSpread"))

```

 inputs

Simulation inputs

Description

Accessor functions for the inputs slots in a `simList` object.

Usage

```
inputs(sim)

## S4 method for signature 'simList'
inputs(sim)

inputs(sim) <- value

## S4 replacement method for signature 'simList'
inputs(sim) <- value

inputArgs(sim)

## S4 method for signature 'simList'
inputArgs(sim)

inputArgs(sim) <- value

## S4 replacement method for signature 'simList'
inputArgs(sim) <- value
```

Arguments

<code>sim</code>	A <code>simList</code> object from which to extract element(s) or in which to replace element(s).
<code>value</code>	The object to be stored at the slot. See Details.

Details

These functions are one of three mechanisms to add the information about which input files to load in a `spades` call.

1. As arguments to a `simInit` call. Specifically, `inputs` or `outputs`. See `?simInit`.
2. With the `outputs(simList)` function call.
3. By adding a function called `.inputObjects` inside a module, which will be executed during the `simInit` call. This last way is the most "modular" way to create default data sets for your model.

See below for more details.

Value

Returns or sets the value(s) of the input or output slots in the `simList` object.

inputs function or argument in `simInit`

`inputs` accepts a `data.frame`, with up to 7 columns. Columns are:

<code>file</code>	required, a character string indicating the file path. There is no default.
<code>objectName</code>	optional, character string indicating the name of the object that the loaded file will be assigned to in the <code>simList</code> .
<code>fun</code>	optional, a character string indicating the function to use to load that file. Defaults to the known extensions in <code>SpaDES</code> .
<code>package</code>	optional character string indicating the package in which to find the <code>fun</code> ;
<code>loadTime</code>	optional numeric, indicating when in simulation time the file should be loaded. The default is the highest priority.
<code>interval</code>	optional numeric, indicating at what interval should this same exact file be reloaded from disk, e.g., 10 would mean every 10 simulation time units.
<code>arguments</code>	is a list of lists of named arguments, one list for each <code>fun</code> . For example, if <code>fun="raster"</code> , <code>arguments = list(</code>

Currently, only `file` is required. All others will be filled with defaults if not specified.

See the modules vignette for more details (`browseVignettes("SpaDES.core")`).

`.inputObjects` function placed inside module

Any code placed inside a function called `.inputObjects` will be run during `simInit()` for the purpose of creating any objects required by this module, i.e., objects identified in the `inputObjects` element of `defineModule`. This is useful if there is something required before simulation to produce the module object dependencies, including such things as downloading default datasets, e.g., `downloadData('LCC2005', modulePath(sim))`. Nothing should be created here that does not create a named object in `inputObjects`. Any other initiation procedures should be put in the "init" `eventType` of the `doEvent` function. Note: the module developer can use `sim$.userSuppliedObjNames` inside the function to selectively skip unnecessary steps because the user has provided those `inputObjects` in the `simInit` call. e.g., the following code would look to see if the user had passed `defaultColor` into during `simInit`. If the user had done this, then this function would not override that value with 'red'. If the user has not passed in a value for `defaultColor`, then the module will get it here:

```
if (!('defaultColor' %in% sim$.userSuppliedObjNames)) { sim$defaultColor <- 'red' }
```

See Also

[SpaDES.core-package](#), specifically the section 1.2.2 on loading and saving.

Other functions to access elements of a 'simList' object: `.addDepends()`, `checkpointFile()`, `envir()`, `events()`, `globals()`, `modules()`, `objs()`, `packages()`, `params()`, `paths()`, `progressInterval()`, `times()`

Examples

```
#####
# inputs
#####

# Start with a basic empty simList
```

```

sim <- simInit()

test <- 1:10
tmpdir <- file.path(tempdir(), "inputs") |> checkPath(create = TRUE)
tmpFile <- file.path(tmpdir, "test.rds")
saveRDS(test, file = tmpFile)
inputs(sim) <- data.frame(file = tmpFile) # using only required column, "file"
inputs(sim) # see that it is not yet loaded, but when it is scheduled to be loaded
simOut <- spades(sim)
inputs(simOut) # confirm it was loaded
simOut$test

# can put data.frame for inputs directly inside simInit call
allTifs <- dir(getMapPath(tempdir()), full.names = TRUE)

# next: .objectNames are taken from the filenames (without the extension)
# This will load all 5 tifs in the SpaDES sample directory, using
# the rast fuction in the terra package, all at time = 0
sim <- simInit(
  inputs = data.frame(
    files = allTifs,
    functions = "rast",
    package = "terra",
    loadTime = 0,
    stringsAsFactors = FALSE)
)

#####
# A fully described inputs object, including arguments:
files <- dir(getMapPath(tempdir()), full.names = TRUE)

# arguments must be a list of lists. This may require I() to keep it as a list
# once it gets coerced into the data.frame.
# arguments = I(rep(list(native = TRUE), length(files)))
filelist <- data.frame(
  objectName = paste0("Maps", 1:5),
  files = files,
  functions = "terra::rast",
  # arguments = arguments,
  loadTime = 0,
  intervals = c(rep(NA, length(files) - 1), 10)
)
inputs(sim) <- filelist
spades(sim)

# Example showing loading multiple objects from global environment onto the
# same object in the simList, but at different load times
a1 <- 1
a2 <- 2
# Note arguments must be a list of NROW(inputs), with each element itself being a list,
# which is passed to do.call(fun[x], arguments[[x]]), where x is row number, one at a time
args <- lapply(1:2, function(x) {
  list(x = paste0("a", x),

```

```

      envir = environment()) # may be necessary to specify in which envir a1, a2
      # are located, if not in an interactive session
    })
inputs <- data.frame(objectName = "a", loadTime = 1:2, fun = "base::get", arguments = I(args))
a <- simInit(inputs = inputs, times = list(start = 0, end = 1))
a <- spades(a)
identical(a1, a$a)

end(a) <- 3
a <- spades(a) # different object (a2) loaded onto a$a
identical(a2, a$a)

# Clean up after
unlink(tmpdir, recursive = TRUE)

```

inSeconds

Convert time units

Description

Current pre-defined units are found within the `spadesTimes()` function. The user can define a new unit. The unit name can be anything, but the function definition must be of the form "dunitName", e.g., `dyear` or `dfortnight`. The unit name is the part without the `d` and the function name definition includes the `d`. This new function, e.g., `dfortnight <- function(x) lubridate::duration(dday(14))` can be placed anywhere in the search path or in a module (you will need to declare "lubridate" in your `pkgDeps` in the metadata).

This function takes a numeric with a "unit" attribute and converts it to another numeric with a different time attribute. If the units passed to argument `units` are the same as `attr("time", "unit")`, then it simply returns input time.

Usage

```

inSeconds(unit, envir, skipChecks = FALSE)

convertTimeunit(time, unit, envir, skipChecks = FALSE)

.spadesTimes

spadesTimes()

checkTimeunit(unit, envir)

## S4 method for signature 'character,missing'
checkTimeunit(unit, envir)

## S4 method for signature 'character,environment'
checkTimeunit(unit, envir)

```

Arguments

<code>unit</code>	Character. One of the time units used in SpaDES or user defined time unit, given as the unit name only. See details.
<code>envir</code>	An environment. This is where to look up the function definition for the time unit. See details.
<code>skipChecks</code>	For speed, the internal checks for classes and missingness can be skipped. Default FALSE.
<code>time</code>	Numeric. With a <code>unit</code> attribute, indicating the time unit of the input numeric. See Details.

Format

An object of class `character` of length 12.

Details

Because of R scoping, if `envir` is a `simList` environment, then this function will search there first, then up the current `search()` path. Thus, it will find a user defined or module defined unit before a SpaDES unit. This means that a user can override the `dyear` given in SpaDES, for example, which is 365.25 days, with `dyear <- function(x) lubridate::duration(dday(365))`.

If `time` has no `unit` attribute, then it is assumed to be seconds.

Value

A numeric vector of length 1, with `unit` attribute set to "seconds".

Author(s)

Alex Chubaty & Eliot McIntire

Eliot McIntire

loadSimList

Load a saved simList and ancillary files

Description

Loading a `simList` from file can be problematic as there are non-standard objects that must be rebuilt. See description in [saveSimList\(\)](#) for details.

`unzipSimList` is a convenience wrapper around `unzip` and `loadSimList` where all the files are correctly identified and passed to `loadSimList(..., otherFiles = xxx)`. See [zipSimList](#) for details.

Usage

```
loadSimList(
  filename,
  projectPath = getwd(),
  tempPath = tempdir(),
  paths = NULL,
  otherFiles = "",
  verbose = getOption("reproducible.verbose")
)

unzipSimList(zipfile, load = TRUE, paths = getPaths(), ...)
```

Arguments

filename	Character giving the name of a saved simulation file. Currently, only file types .qs2 or .rds are supported.
projectPath	An optional path for the project within which the simList exists. This is used to identify relative paths for saving and loading the simList.
tempPath	A character string specifying the new base directory for the temporary paths maintained in a simList.
paths	A list of character vectors for all the simList paths. When loading a simList, this will replace the paths of everything to these new paths. Experimental still.
otherFiles	A character vector of (absolute) file names locating each of the existing file-backed Raster* files that are the real paths for the possibly incorrect paths in Filenames(sim) if the the file being read in is from a different computer, path, or drive. This could be the output from unzipSimList (which is calls loadSimList internally, passing the unzipped filenames)
verbose	Numeric, -1 silent (where possible), 0 being very quiet, 1 showing more messaging, 2 being more messaging, etc. Default is 1. Above 3 will output much more information about the internals of Caching, which may help diagnose Caching challenges. Can set globally with an option, e.g., options('reproducible.verbose' = 0) to reduce t
zipfile	Filename of a zipped simList
load	Logical. If TRUE, the default, then the simList will also be loaded into R.
...	passed to unzip

Details

If cache is used, it is likely that it should be trimmed before zipping, to include only cache elements that are relevant.

Value

For `loadSimList()`, a `simList` object. For `unzipSimList()`, either a character vector of file names unzipped (if `load = FALSE`), or a `simList` object.

See Also

[saveSimList\(\)](#), [zipSimList\(\)](#)

makeMemoisable.simList

Make simList correctly work with memoise

Description

Because of the environment slot, `simList` objects don't correctly memoise a `simList`. This method for `simList` converts the object to a `simList_` first.

Usage

```
## S3 method for class 'simList'
makeMemoisable(x)
```

```
## S3 method for class 'simList_'
unmakeMemoisable(x)
```

Arguments

`x` An object to make memoisable. See individual methods in other packages.

Value

A `simList_` object or a `simList`, in the case of `unmakeMemoisable`.

See Also

[reproducible::makeMemoisable\(\)](#)

maxTimeunit

Determine the largest timestep unit in a simulation

Description

Determine the largest timestep unit in a simulation

Usage

```
maxTimeunit(sim)
```

```
## S4 method for signature 'simList'
maxTimeunit(sim)
```

Arguments

`sim` A `simList` simulation object.

Value

The timeunit as a character string. This defaults to NA if none of the modules has explicit units.

Author(s)

Eliot McIntire and Alex Chubaty

`memoryUseThisSession` *Estimate memory used with system("ps")*

Description

This will give a slightly different estimate than `pryr::mem_used`, which uses `gc()` internally. The purpose of this function is to allow continuous monitoring, external to the R session. Normally, this is run in a different session.

This will only work if the user has specified before running the `spades` call, set the interval, in seconds, that `ps` is run. E.g., `options("spades.memoryUseInterval" = 0.5)`, will assess memory use every 0.5 seconds. The default is 0, meaning no interval, "off".

Usage

```
memoryUseThisSession(thisPid)
```

```
memoryUse(sim, max = TRUE)
```

Arguments

`thisPid` Numeric or integer, the PID of the process. If omitted, it will be found with `Sys.getpid()`.

`sim` A completed `simList`

`max` Logical. If TRUE, then the return value will be summarized by module/event, showing the maximum memory used. If FALSE, then the raw memory used during each event will be shown.

Value

estimated memory use in MiB

`data.table` summarizing the estimated memory use (in MiB) for each event type, for each module, during the simulation.

Note

The suggested `future` and `future.callr` packages must be available.

See Also

The vignette("iv-modules")

minTimeunit	<i>Determine the smallest timeunit in a simulation</i>
-------------	--

Description

When modules have different timeunit, SpaDES automatically takes the smallest (e.g., "second") as the unit for a simulation.

Usage

```
minTimeunit(sim)

## S4 method for signature 'simList'
minTimeunit(sim)

## S4 method for signature 'list'
minTimeunit(sim)
```

Arguments

sim A simList simulation object.

Value

The timeunit as a character string. This defaults to "second" if none of the modules has explicit units.

Author(s)

Eliot McIntire

moduleCodeFiles	<i>Extract the full file paths for R source code</i>
-----------------	--

Description

This can be used e.g., for Caching, to identify which files have changed.

Usage

```
moduleCodeFiles(paths, modules)
```

Arguments

paths	An optional named list with up to 4 named elements, modulePath, inputPath, outputPath, and cachePath. See details. NOTE: Experimental feature now allows for multiple modulePaths to be specified in a character vector. The modules will be searched for sequentially in the first modulePath, then if it doesn't find it, in the second etc.
modules	A named list of character strings specifying the names of modules to be loaded for the simulation. Note: the module name should correspond to the R source file from which the module is loaded. Example: a module named "caribou" will be sourced from the file 'caribou.R', located at the specified modulePath(simList) (see below).

Value

character vector of file paths.

moduleCoverage	<i>Calculate module coverage of unit tests</i>
----------------	--

Description

Calculate the test coverage by unit tests for the module and its functions.

Usage

```
moduleCoverage(mod, modulePath = "..")
```

Arguments

mod	Character string. The module's name. Default is basename(getwd())
modulePath	Character string. The path to the module directory (default is "..", i.e., one level up from working directory).

Value

Return a list of two coverage objects and two data.table objects. The two coverage objects are named moduleCoverage and functionCoverage. The moduleCoverage object contains the percent value of unit test coverage for the module. The functionCoverage object contains percentage values for unit test coverage for each function defined in the module. Please use covr::report() to view the coverage information. Two data.tables give the information of all the tested and untested functions in the module.

Note

When running this function, the test files must be strictly placed in the 'tests/testthat/' directory under module path. To automatically generate this folder, please set unitTests = TRUE when creating a new module using newModule(). To accurately test your module, the test filename must follow the format test-functionName.R.

Author(s)

Yong Luo

See Also[newModule\(\)](#).

moduleDefaults	<i>Defaults values used in defineModule</i>
----------------	---

Description

Where individual elements are missing in `defineModule`, these defaults will be used.

Usage

```
moduleDefaults
```

Format

An object of class `list` of length 13.

Value

named list of default module metadata

moduleDiagram	<i>Simulation module dependency diagram</i>
---------------	---

Description

Create a network diagram illustrating the simplified module dependencies of a simulation. Offers a less detailed view of specific objects than does plotting the `depsEdgeList` directly with [objectDiagram\(\)](#).

Usage

```
moduleDiagram(sim, type, showParents = TRUE, ...)
```

```
## S4 method for signature 'simList,character,logical'
moduleDiagram(sim, type = "plot", showParents = TRUE, ...)
```

```
## S4 method for signature 'simList,ANY,ANY'
moduleDiagram(sim, type, showParents = TRUE, ...)
```

Arguments

sim	A simList object (typically corresponding to a completed simulation).
type	Character string, either "rgl" for <code>igraph::rglplot</code> or "tk" for <code>igraph::tkplot</code> , "Plot" to use <code>quickPlot::Plot()</code> or "plot" to use <code>base::plot()</code> , the default.
showParents	Logical. If TRUE, then any children that are grouped into parent modules will be grouped together by coloured blobs. Internally, this is calling <code>moduleGraph()</code> . Default FALSE.
...	Additional arguments passed to plotting function specified by type.

Value

invoked for its side effect of plotting the module dependency diagram.

Author(s)

Alex Chubaty

See Also

[igraph::igraph](#), [moduleGraph\(\)](#) for a version that accounts for parent and children module structure.

Examples

```
if (requireNamespace("SpaDES.tools", quietly = TRUE) &&
    packageVersion("SpaDES.tools") > "3.0.0") {
  library(igraph)
  times <- list(start = 0, end = 6, "month")
  parameters <- list(
    .globals = list(stackName = "landscape"),
    caribouMovement = list(
      .saveObjects = "caribou",
      .saveInitialTime = 1, .saveInterval = 1
    ),
    randomLandscapes = list(.plotInitialTime = NA, nx = 20, ny = 20))

  modules <- list("randomLandscapes", "caribouMovement")
  paths <- list(
    modulePath = getSampleModules(tempdir())
  )

  # Set some options so example runs faster
  opts <- options(spades.moduleCodeChecks = FALSE, spades.loadReqdPkgs = FALSE)
  sim <- simInit(times = times, params = parameters, modules = modules,
                paths = paths)

  options(opts)
  moduleDiagram(sim)
  # Can also use default base::plot
  modDia <- depsGraph(sim, plot = TRUE)
  # See ?plot.igraph
```

```

plot(modDia, layout = layout_as_star)

# Or for more control - here, change the label "_INPUT_" to "DATA"
edgeList <- depsEdgeList(sim)
edgeList <- edgeList[, list(from, to)]
edgeList[from == "_INPUT_", from := "Data"]
edgeList[to == "_INPUT_", to := "Data"]
edgeList <- unique(edgeList)
ig <- graph_from_data_frame(edgeList[, list(from, to)])
plot(ig)
}

```

moduleGraph

Build a module dependency graph

Description

This is still experimental, but this will show the hierarchical structure of parent and children modules and return a list with an igraph object and an igraph communities object, showing the groups. Currently only tested with relatively simple structures.

Usage

```

moduleGraph(sim, plot, ...)

## S4 method for signature 'simList,logical'
moduleGraph(sim, plot, ...)

## S4 method for signature 'simList,missing'
moduleGraph(sim, plot, ...)

```

Arguments

sim	A simList object.
plot	Logical indicating whether the edgelist (and subsequent graph) will be used for plotting. If TRUE, duplicated rows (i.e., multiple object dependencies between modules) are removed so that only a single arrow is drawn connecting the modules. Default is FALSE.
...	Arguments passed to Plot

Value

A list with 2 elements, an [igraph::igraph](#) object and an igraph communities object.

Author(s)

Eliot McIntire

See Also[moduleDiagram\(\)](#)

moduleMetadata	<i>Parse and extract module metadata</i>
----------------	--

Description

Parse and extract module metadata

Usage

```

moduleMetadata(
  sim,
  module,
  path = getOption("spades.modulePath", NULL),
  defineModuleListItems = c("name", "description", "keywords", "childModules", "authors",
    "version", "spatialExtent", "timeframe", "timeunit", "citation", "documentation",
    "reqdPkgs", "parameters", "inputObjects", "outputObjects")
)

## S4 method for signature 'missing,character,character'
moduleMetadata(module, path, defineModuleListItems)

## S4 method for signature 'missing,character,missing'
moduleMetadata(module, defineModuleListItems)

## S4 method for signature 'ANY,ANY,ANY'
moduleMetadata(
  sim,
  module,
  path = getOption("spades.modulePath", NULL),
  defineModuleListItems = c("name", "description", "keywords", "childModules", "authors",
    "version", "spatialExtent", "timeframe", "timeunit", "citation", "documentation",
    "reqdPkgs", "parameters", "inputObjects", "outputObjects")
)

```

Arguments

sim	A simList simulation object, generally produced by simInit.
module	Character string. Your module's name.
path	Character string specifying the file path to modules directory. Default is to use the spades.modulePath option.
defineModuleListItems	A vector of metadata entries to return values about.

Value

A list of module metadata, matching the structure in `defineModule()`.

Author(s)

Alex Chubaty

See Also

`defineModule()`

Examples

```
## turn off code checking -- don't need it here
opts <- options("spades.moduleCodeChecks" = FALSE,
               "spades.useRequire" = FALSE)

path <- getSampleModules(tempdir())
sampleModules <- dir(path)
x <- moduleMetadata(sampleModules[3], path = path)

## using simList
if (require("SpaDES.tools", quietly = TRUE)) {
  mySim <- simInit(
    times = list(start = 2000.0, end = 2001.0, timeunit = "year"),
    params = list(
      .globals = list(stackName = "landscape")
    ),
    modules = list("caribouMovement"),
    paths = list(modulePath = path)
  )
  moduleMetadata(sim = mySim)
}

# turn code checking back on -- don't need it here
options(opts)
```

moduleParams

Extract a module's parameters, inputs, or outputs

Description

These are more or less wrappers around `moduleMetadata`, with the exception that extraneous spaces and End-Of-Line characters will be removed from the desc arguments in `defineParameters`, `defineInputs`, and `defineOutputs`

Usage

```
moduleParams(module, path)

## S4 method for signature 'character,character'
moduleParams(module, path)

moduleInputs(module, path)

## S4 method for signature 'character,character'
moduleInputs(module, path)

moduleOutputs(module, path)

## S4 method for signature 'character,character'
moduleOutputs(module, path)
```

Arguments

module	Character string. Your module's name.
path	Character string specifying the file path to modules directory. Default is to use the <code>spades.modulePath</code> option.

Value

```
data.frame
```

Author(s)

Alex Chubaty

See Also

[moduleMetadata\(\)](#)

Examples

```
## easily include these tables in Rmd files using knitr
path <- getSampleModules(tempdir())
sampleModules <- dir(path)

p <- moduleParams(sampleModules[3], path = path)
i <- moduleInputs(sampleModules[3], path = path)
o <- moduleOutputs(sampleModules[3], path = path)

knitr::kable(p)
knitr::kable(i)
knitr::kable(o)
```

modules

Simulation modules and dependencies

Description

Accessor functions for the depends and modules slots in a simList object. These are included for advanced users.

<code>depends()</code>	List of simulation module dependencies. (advanced)
<code>modules()</code>	List of simulation modules to be loaded. (advanced)
<code>inputs()</code>	List of loaded objects used in simulation. (advanced)

Usage

```
modules(sim, hidden = FALSE)

## S4 method for signature 'simList'
modules(sim, hidden = FALSE)

modules(sim) <- value

## S4 replacement method for signature 'simList'
modules(sim) <- value

depends(sim)

## S4 method for signature 'simList'
depends(sim)

depends(sim) <- value

## S4 replacement method for signature 'simList'
depends(sim) <- value
```

Arguments

<code>sim</code>	A simList object from which to extract element(s) or in which to replace element(s).
<code>hidden</code>	Logical. If TRUE, show the default core modules.
<code>value</code>	The object to be stored at the slot.

Details

Currently, only get and set methods are defined. Subset methods are not.

Value

Returns or sets the value of the slot from the `simList` object.

Author(s)

Alex Chubaty

See Also

[SpaDES.core-package](#), specifically the section 1.2.7 on Modules and dependencies.

Other functions to access elements of a 'simList' object: `.addDepends()`, `checkpointFile()`, `envir()`, `events()`, `globals()`, `inputs()`, `objs()`, `packages()`, `params()`, `paths()`, `progressInterval()`, `times()`

moduleVersion	<i>Parse and extract a module's version</i>
---------------	---

Description

Parse and extract a module's version

Usage

```
moduleVersion(module, path, sim, envir = NULL)

## S4 method for signature 'character,character,missing'
moduleVersion(module, path, envir)

## S4 method for signature 'character,missing,missing'
moduleVersion(module, envir)

## S4 method for signature 'character,missing,simList'
moduleVersion(module, sim, envir)
```

Arguments

module	Character string. Your module's name.
path	Character string specifying the file path to modules directory. Default is to use the <code>spades.modulePath</code> option.
sim	A <code>simList</code> simulation object, generally produced by <code>simInit</code> .
envir	Optional environment in which to store parsed code. This may be useful if the same file is being parsed multiple times. This function will check in that environment for the parsed file before parsing again. If the <code>envir</code> is transient, then this will have no effect.

Value

numeric_version indicating the module's version.

Author(s)

Alex Chubaty

See Also

[moduleMetadata\(\)](#)

Examples

```
# using filepath
path <- getSampleModules(tempdir())
moduleVersion("caribouMovement", path)

# using simList
options("spades.useRequire" = FALSE)
if (require("SpaDES.tools", quietly = TRUE)) {
  mySim <- simInit(
    times = list(start = 2000.0, end = 2002.0, timeunit = "year"),
    params = list(
      .globals = list(stackName = "landscape", burnStats = "nPixelsBurned")
    ),
    modules = list("caribouMovement"),
    paths = list(modulePath = path)
  )
  moduleVersion("caribouMovement", sim = mySim)
}
```

newModule

Create new module from template

Description

Generate a skeleton for a new SpaDES module, a template for a documentation file, a citation file, a license file, a 'README.md' file, and a folder that contains unit tests information. newModule is largely a wrapper around newModuleCode and newModuleDocumentation. newModuleCode will not generate the module code. newModuleDocumentation will create the other files.

Usage

```
newModule(name, path, ..., events = NULL, envir = parent.frame())

## S4 method for signature 'character,character'
newModule(name, path, ..., events = NULL, envir = parent.frame())
```

```
## S4 method for signature 'character,missing'
newModule(name, path, ..., events = NULL, envir = parent.frame())

newModuleCode(name, path, ..., events)

## S4 method for signature 'character,character'
newModuleCode(name, path, ..., events)

newModuleDocumentation(name, path, ...)

## S4 method for signature 'character,character'
newModuleDocumentation(name, path, ...)

## S4 method for signature 'character,missing'
newModuleDocumentation(name, path, ...)
```

Arguments

name	Character string specifying the name of the new module.
path	Character string. Subdirectory in which to place the new module code file. The default is the current working directory.
...	Additional arguments. Currently, these can be either named function definitions (which will be added to the <code>simList</code>) or one or more of the following:
	<p><code>children</code> Required when <code>type = "parent"</code>. A character vector specifying the names of child modules.</p> <p><code>open</code> Logical. Should the new module file be opened after creation? Default <code>TRUE</code>.</p> <p><code>type</code> Character string specifying one of "child" (default), or "parent".</p> <p>For <code>newModule</code> can also be:</p> <p><code>unitTests</code> Logical. Should the new module include unit test files? Default <code>TRUE</code>. Unit testing relies on the testthat package.</p> <p><code>useGitHub</code> Logical. Is module development happening on GitHub? Default <code>TRUE</code>.</p>
events	A list of named expressions, each of which is surrounded by <code>{ }</code> . A user can specify events here, instead of accepting the default <code>doEvent</code> function that comes with the module template. If this is specified, all events must be specified, i.e., it will not inherit partially from the template <code>doEvent.<moduleName></code> . See example.
envir	An environment where objects being passed to <code>newModule</code> can be found. Default <code>parent.frame()</code> , which should be fine for most cases.

Details

All files will be created within a subdirectory named `name` within the path:

```
<path>/
|_ <name>/
|_ R/           # contains additional module R scripts
|_ data/       # directory for all included data
|_ CHECKSUMS.txt # contains checksums for data files
|_ tests/      # contains unit tests for module code
|_ citation.bib # bibtex citation for the module
|_ LICENSE     # describes module's legal usage
|_ README.md   # provide overview of key aspects
|_ <name>.R    # module code file (incl. metadata)
|_ <name>.Rmd  # documentation, usage info, etc.
```

Value

NULL (invisibly). The new module file is created at `'path/name.R'`, as well as ancillary files for documentation, citation, `'LICENSE'`, `'README'`, and `'tests'` directory.

`newModuleCode` is invoked for its side effect of creating new module code files.

`newModuleDocumentation` is invoked for its side effect of creating new module documentation files.

Note

On Windows there is currently a bug in RStudio that prevents the editor from opening when `file.edit` is called. Similarly, in RStudio on macOS, there is an issue opening files where they are opened in an overlaid window rather than a new tab. `file.edit` does work if the user types it at the command prompt. A message with the correct lines to copy and paste is provided.

Author(s)

Alex Chubaty and Eliot McIntire

Eliot McIntire and Alex Chubaty

See Also

Other module creation helpers: [newModuleTests\(\)](#)

Other module creation helpers: [newModuleTests\(\)](#)

Other module creation helpers: [newModuleTests\(\)](#)

Examples

```
tmpdir <- tempdir2("exampleNewModule")
## create a "myModule" module in the "modules" subdirectory.
newModule("myModule", tmpdir)

## create a new parent module in the "modules" subdirectory.
```

```

newModule("myParentModule", tmpdir, type = "parent", children = c("child1", "child2"))
unlink(tmpdir, recursive = TRUE)

if (requireNamespace("ggplot2")) {
  # We can also specify events and functions in `newModule`; it will still get all
  # functions that are not specified from the module template (e.g., plotFun below)
  nm <- "test"
  modulePath <- Require::tmpdir2()
  newModule(nm, path = modulePath, open = FALSE,
    events = list(
      init = {
        sim <- Init(sim) # finds definition below
        sim <- scheduleEvent(sim, start(sim) + 1,
          eventType = "plot")
      },
      plot = {
        plotFun(sim) # finds the templated plotFun
        sim <- scheduleEvent(sim, time(sim) + 1,
          eventType = "plot")
      }
    ),
    Init = function(sim) { # replaces Init definition from template
      sim$a <- 1
      return(sim)
    }
  )
  out <- simInitAndSpades(module = nm, paths = list(modulePath = modulePath))
  # clean up
  unlink(dir(modulePath, pattern = nm, full.names = TRUE), recursive = TRUE)
}

```

newModuleTests

Create template testing structures for new modules

Description

Create template testing structures for new modules

Usage

```
newModuleTests(name, path, open, useGitHub)
```

```
## S4 method for signature 'character,character,logical,logical'
```

```
newModuleTests(name, path, open, useGitHub)
```

Arguments

name	Character string specifying the name of the new module.
path	Character string. Subdirectory in which to place the new module code file. The default is the current working directory.
open	Logical. Should the new module file be opened after creation? Default TRUE in an interactive session.
useGitHub	Logical indicating whether GitHub will be used. If TRUE (default), creates suitable configuration files (e.g., '.gitignore') and configures basic GitHub actions for module code checking.

Value

NULL (invisibly). Invoked for its side effect of creating new module test files.

Author(s)

Eliot McIntire and Alex Chubaty

See Also

Other module creation helpers: [newModule\(\)](#)

newObjectsCreated *Show which objects were first created in a simInit or spades call*

Description

This does an `rbindlist(sim$._objectsCreated)`. This object in the `sim` records the yellow message that reports on when objects are created.

Usage

```
newObjectsCreated(sim)
```

Arguments

sim A `simList` object that contains `data.table` objects

Value

The `data.table` of the objects created, alongside the current (`sim`) at each moment of creation.

newProgressBar	<i>Progress bar</i>
----------------	---------------------

Description

Shows a progress bar that is scaled to simulation end time.

Usage

```
newProgressBar(sim)
```

```
setProgressBar(sim)
```

Arguments

`sim` A `simList` simulation object.

Details

The progress bar object is stored in a separate environment, `#' .pkgEnv`.

Value

invoked for side effect of creating progress bar

Author(s)

Alex Chubaty and Eliot McIntire

newProject	<i>Create new SpaDES project</i>
------------	----------------------------------

Description

Initialize a project with subdirectories 'cache/', 'modules/', 'inputs/', 'outputs/', and `setPaths` accordingly. If invoked from Rstudio, will also create a new Rstudio project file.

Usage

```
newProject(name, path, open)
```

```
## S4 method for signature 'character,character,logical'
newProject(name, path, open)
```

```
## S4 method for signature 'character,character,missing'
newProject(name, path, open)
```

Arguments

name	project name (name of project directory)
path	path to directory in which to create the project directory
open	Logical. Should the new project file be opened after creation? Default TRUE in an interactive session.

Value

invoked for side effect of project file creation

Examples

```
myProjDir <- newProject("myProject", tempdir())

dir.exists(file.path(myProjDir, "cache"))
dir.exists(file.path(myProjDir, "inputs"))
dir.exists(file.path(myProjDir, "modules"))
dir.exists(file.path(myProjDir, "outputs"))
unlink(myProjDir, recursive = TRUE) ## cleanup
```

newProjectCode	<i>Create new module code file</i>
----------------	------------------------------------

Description

Create new module code file

Usage

```
newProjectCode(name, path, open)

## S4 method for signature 'character,character,logical'
newProjectCode(name, path, open = interactive())
```

Arguments

name	project name (name of project directory)
path	path to directory in which to create the project directory
open	Logical. Should the new project file be opened after creation? Default TRUE in an interactive session.

Value

invoked for side effect of project file creation

Author(s)

Alex Chubaty

noEventWarning	<i>Text for no event with that name</i>
----------------	---

Description

Provides the text to be sent to warning in each module as the default switch case.

Usage

```
noEventWarning(sim)
```

Arguments

sim	A simList simulation object, generally produced by simInit.
-----	---

Value

A text string specifying the event name and module for which there is no event

objectDiagram	<i>Simulation object dependency diagram</i>
---------------	---

Description

Create a sequence diagram illustrating the data object dependencies of a simulation. Offers a more detailed view of specific objects than does plotting the `depsEdgeList` directly with `moduleDiagram()`.

Usage

```
objectDiagram(sim, ...)
```

```
## S4 method for signature 'simList'
objectDiagram(sim, ...)
```

Arguments

sim	A simList object (typically corresponding to a completed simulation).
...	Additional arguments passed to <code>DiagrammeR::mermaid</code> . Useful for specifying height and width.

Value

Plots a sequence diagram, invisibly returning a `DiagrammeR::mermaid` object.

Author(s)

Alex Chubaty

See Also

DiagrammeR::mermaid.

Examples

```
if (requireNamespace("DiagrammeR", quietly = TRUE)) {
  sim <- simInit()
  objectDiagram(sim)
  # if there are lots of objects, may need to increase width and/or height
  objectDiagram(sim, height = 3000, width = 3000)
}
```

objectSynonyms

Identify synonyms in a simList

Description

This will create active bindings amongst the synonyms. To minimize copying, the first one that exists in the character vector will become the "canonical" object. All others named in the character vector will be activeBindings to that canonical one. This synonym list will be assigned to the envir, as an object named objectSynonyms. That object will have an attribute called, bindings indicating which one is the canonical one and which is/are the activeBindings. **EXPERIMENTAL:** If the objects are removed during a spades call by, say, a module, then at the end of the event, the spades call will replace the bindings. In other words, if a module deletes the object, it will "come back". This may not always be desired.

Usage

```
objectSynonyms(envir, synonyms)
```

Arguments

envir	An environment, which in the context of SpaDES.core is usually a simList to find and/or place the objectSynonyms object.
synonyms	A list of synonym character vectors, such as <code>list(c("age", "ageMap", "age2"), c("veg", "vegMap"))</code>

Details

This is very experimental and only has minimal tests. Please report if this is not working, and under what circumstances (e.g., please submit a reproducible example to our issues tracker)

This function will append any new objectSynonym to any pre-existing objectSynonym in the envir. Similarly, this function assumes transitivity, i.e., if age and ageMap are synonyms, and ageMap and timeSinceFire are synonyms, then age and timeSinceFire must be synonyms.

Value

Active bindings in the `envir` so that all synonyms point to the same canonical object, e.g., they would be at `envir[[synonym[[1]][1]]]` and `envir[[synonym[[1]][2]]]`, if a list of length one is passed into `synonyms`, with a character vector of length two. See examples.

Examples

```
sim <- simInit()

sim$age <- 1:10;
sim <- objectSynonyms(sim, list(c("age", "ageMap")))

identical(sim$ageMap, sim$age)
sim$age <- 4
identical(sim$ageMap, sim$age)
sim$ageMap <- 2:5
sim$ageMap[3] <- 11
identical(sim$ageMap, sim$age)

# Also works to pass it in as an object
objectSynonyms <- list(c("age", "ageMap"))
sim <- simInit(objects = list(objectSynonyms = objectSynonyms))
identical(sim$ageMap, sim$age) # they are NULL at this point
sim$age <- 1:10
identical(sim$ageMap, sim$age) # they are not NULL at this point

## More complicated, with 'updating' i.e., you can add new synonyms to previous
sim <- simInit()
os <- list(c("age", "ageMap"), c("vegMap", "veg"), c("studyArea", "studyArea2"))
os2 <- list(c("ageMap", "timeSinceFire", "tsf"),
           c("system", "system2"),
           c("vegMap", "veg"))
sim <- objectSynonyms(sim, os)
sim <- objectSynonyms(sim, os2)

# check
sim$.objectSynonyms
```

Description

The `[[` and `$` operators provide "shortcuts" for accessing objects in the simulation environment. I.e., instead of using `envir(sim)$object` or `envir(sim)[["object"]]`, one can simply use `sim$object` or `sim[["object"]]`.

Usage

```

objs(sim, ...)

## S4 method for signature 'simList'
objs(sim, ...)

objs(sim) <- value

## S4 replacement method for signature 'simList'
objs(sim) <- value

moduleObjects(sim, module, path)

findObjects(objects, sim, module, path)

```

Arguments

sim	A simList object from which to extract element(s) or in which to replace element(s).
...	passed to ls
value	objects to assign to the simList
module	Character vector of module name(s)
path	The path to the module., i.e., the modulePath. Only relevant if sim not supplied.
objects	A character vector of length ≥ 1 with name(s) of objects to look for in the metadata. This is used in a grep, meaning it will do partial matching (e.g., "studyArea" will find "studyArea" and "studyAreaLarge"). User can use regular expressions.

Details

objs can take ... arguments passed to ls, allowing, e.g. all.names=TRUE objs<- requires takes a named list of values to be assigned in the simulation environment.

Value

Returns or sets a list of objects in the simList environment.

moduleObjects returns a data.table with 4 columns, module, objectName, type, and desc, pulled directly from the object metadata in the createsOutputs and expectsInputs. These will be determined either from a simList or from the module source code.

findObjects returns a data.table similar to moduleObjects, but with only the objects provided by objects.

See Also

[SpaDES.core-package](#), specifically the section 1.2.1 on Simulation Parameters.

Other functions to access elements of a 'simList' object: `.addDepends()`, `checkpointFile()`, `envir()`, `events()`, `globals()`, `inputs()`, `modules()`, `packages()`, `params()`, `paths()`, `progressInterval()`, `times()`

Examples

```
# findObjects
path <- getSampleModules(tempdir())
findObjects(path = path, module = dir(path), objects = "caribou")
```

objSize.simList	<i>Object size for simList</i>
-----------------	--------------------------------

Description

Recursively, runs `reproducible::objSize()` on the `simList` environment, so it estimates the correct size of functions stored there (e.g., with their enclosing environments) plus, it adds all other "normal" elements of the `simList`, e.g., `objSize(completed(sim))`. The output is structured into 2 elements: the `sim` environment and all its objects, and the other slots in the `simList` (e.g., `events`, `completed`, `modules`, etc.). The returned object also has an attribute, "total", which shows the total size.

Usage

```
## S3 method for class 'simList'
objSize(x, quick = FALSE, recursive = FALSE, ...)
```

Arguments

<code>x</code>	An object
<code>quick</code>	Logical. If FALSE, then an attribute, "objSize" will be added to the returned value, with each of the elements' object size returned also.
<code>recursive</code>	Logical. If TRUE, then, in addition to evaluating the whole object, it will also return the recursive sizes of the elements of a list or environment.
<code>...</code>	Additional arguments (currently unused), enables backwards compatible use.

Value

an estimate of the size of the object, in bytes.

Examples

```
a <- simInit(objects = list(d = 1:10, b = 2:20))
objSize(a)
utils::object.size(a)
```

openModules	<i>Open all modules nested within a base directory</i>
-------------	--

Description

This is just a convenience wrapper for opening several modules at once, recursively. A module is defined as any file that ends in `.R` or `.r` and has a directory name identical to its filename. Thus, this must be case sensitive.

Usage

```
openModules(name, path)

## S4 method for signature 'character,character'
openModules(name, path)

## S4 method for signature 'missing,missing'
openModules()

## S4 method for signature 'missing,character'
openModules(path)

## S4 method for signature 'character,missing'
openModules(name)

## S4 method for signature 'simList,missing'
openModules(name)
```

Arguments

name	Character vector with names of modules to open. If missing, then all modules will be opened within the base directory.
path	Character string of length 1. The base directory within which there are only module subdirectories.

Value

NULL (invisibly). All file are open via `file.edit`.

Note

On Windows there is currently a bug in RStudio that prevents the editor from opening when `file.edit` is called. `file.edit` does work if the user types it at the command prompt. A message with the correct lines to copy and paste is provided.

Author(s)

Eliot McIntire

Examples

```
if (interactive())
  openModules("modules")
```

 outputs

Simulation outputs

Description

Accessor functions for the outputs slots in a `simList` object.

If a module saves a file to disk during events, it can be useful to keep track of the files that are saved e.g., for `saveSimList()` so that all files can be added to the archive. In addition to setting outputs at the `simInit` stage, a module developer can also put this in a using any saving mechanism that is relevant (e.g., `qs2::qs_save`, `saveRDS` etc.). When a module event does this it can be useful to register that saved file. `registerOutputs` offers an additional mechanism to do this. See examples.

Usage

```
outputs(sim)

## S4 method for signature 'simList'
outputs(sim)

outputs(sim) <- value

## S4 replacement method for signature 'simList'
outputs(sim) <- value

registerOutputs(filename, sim, ...)

outputArgs(sim)

## S4 method for signature 'simList'
outputArgs(sim)

outputArgs(sim) <- value

## S4 replacement method for signature 'simList'
outputArgs(sim) <- value
```

Arguments

`sim` A `simList`. If missing, then the function will search in the call stack, so it will find it if it is in a SpaDES module.

value	The object to be stored at the slot. See Details.
filename	The filename to register in the <code>outputs(sim)</code> data.frame. If missing, an attempt will be made to search for either a file or filename argument in the call itself. This means that this function can be used with the pipe, as long as the returned return from the upstream pipe function is a filename or if it is NULL (e.g., <code>saveRDS</code>), then it will find the file argument and use that.
...	Not used.

Details

These functions are one of three mechanisms to add information about which output files to save.

1. As arguments to a `simInit` call. Specifically, `inputs` or `outputs`. See `?simInit`.
2. With the `outputs(simList)` function call.
3. By adding a function called `.inputObjects` inside a module, which will be executed during the `simInit` call. This last way is the most "modular" way to create default data sets for your model.

See below for more details.

Note using `registerOutputs`: a user can pass any other arguments to `registerOutputs` that are in the `outputs(sim)` data.frame, such as `objectName`, `fun`, `package`, though these will not be used to save the files as this function is only about registering an output that has already been saved.

Value

A `simList` which will be the `sim` passed in with a new object registered in the `outputs(sim)`

outputs function or argument in simInit

`outputs` accepts a data.frame similar to the `inputs` data.frame, but with up to 6 columns.

<code>objectName</code>	required, character string indicating the name of the object in the <code>simList</code> that will be saved to disk (without the
<code>file</code>	optional, a character string indicating the file path to save to. The default is to concatenate <code>objectName</code> with the
<code>fun</code>	optional, a character string indicating the function to use to save that file. The default is <code>saveRDS()</code>
<code>package</code>	optional character string indicating the package in which to find the fun);
<code>saveTime</code>	optional numeric, indicating when in simulation time the file should be saved. The default is the lowest priority
<code>arguments</code>	is a list of lists of named arguments, one list for each fun. For example, if <code>fun = "write.csv"</code> , <code>arguments = list</code>

See the modules vignette for more details (`browseVignettes("SpaDES.core")`).

Note

The automatic file type handling only adds the correct extension from a given fun and package. It does not do the inverse, from a given extension find the correct fun and package.

See Also

`registerOutputs()` which enables files that are saved to be added to the `simList` using the `outputs(sim)` mechanism, so the files that are saved during a module event can be tracked at the `simList` level. `saveSimList()` which will optionally add all the outputs that are tracked into an archive.

`Plots()`, `outputs()`

Examples

```
#####
# outputs
#####

tmpdir <- file.path(tmpdir(), "outputs") |> checkPath(create = TRUE)
tmpFile <- file.path(tmpdir, "temp.rds")
tempObj <- 1:10

# Can add data.frame of outputs directly into simInit call
sim <- simInit(objects = c("tempObj"),
               outputs = data.frame(objectName = "tempObj"),
               paths = list(outputPath = tmpdir))
outputs(sim) # To see what will be saved, when, what filename
sim <- spades(sim)
outputs(sim) # To see that it was saved, when, what filename

# Also can add using assignment after a simList object has been made
sim <- simInit(objects = c("tempObj"), paths = list(outputPath = tmpdir))
outputs(sim) <- data.frame(objectName = "tempObj", saveTime = 1:10)
sim <- spades(sim)
outputs(sim) # To see that it was saved, when, what filename.

# can do highly variable saving
tempObj2 <- paste("val", 1:10)
df1 <- data.frame(col1 = tempObj, col2 = tempObj2)
sim <- simInit(objects = c("tempObj", "tempObj2", "df1"),
               paths = list(outputPath = tmpdir))
outputs(sim) <- data.frame(
  objectName = c(rep("tempObj", 2), rep("tempObj2", 3), "df1"),
  saveTime = c(c(1, 4), c(2, 6, 7), end(sim)),
  fun = c(rep("saveRDS", 5), "write.csv"),
  package = c(rep("base", 5), "utils"),
  stringsAsFactors = FALSE)
# since write.csv has a default of adding a column, x, with rownames, must add additional
# argument for 6th row in data.frame (corresponding to the write.csv function)
outputArgs(sim)[[6]] <- list(row.names = FALSE)
sim <- spades(sim)
outputs(sim)

# read one back in just to test it all worked as planned
newObj <- read.csv(dir(tmpdir, pattern = "year10.csv", full.name = TRUE))
newObj
```

```

# using saving with SpaDES-aware methods
# To see current ones SpaDES can do
.saveFileExtensions()

library(terra)
ras <- rast(ncol = 4, nrow = 5)
ras[] <- 1:20

sim <- simInit(objects = c("ras"), paths = list(outputPath = tmpdir))
outputs(sim) <- data.frame(
  file = "test",
  fun = "writeRaster",
  package = "terra",
  objectName = "ras",
  stringsAsFactors = FALSE)

simOut <- spades(sim)
outputs(simOut)
newRas <- rast(dir(tmpdir, full.name = TRUE, pattern = ".tif")[1])
all.equal(newRas, ras) # Should be TRUE
# Clean up after
unlink(tmpdir, recursive = TRUE)
# For `registerOutputs`
sim <- simInit()
# This would normally be a save call, e.g., `writeRaster`
tf <- reproducible::tempfile2(fileext = ".tif")
sim <- registerOutputs(sim, filename = tf)

# Using a pipe
tf <- reproducible::tempfile2(fileext = ".rds")
sim$a <- 1
sim <- saveRDS(sim$a, tf) |> registerOutputs()
# confirm:
outputs(sim) # has object --> saved = TRUE

```

packages

Get module or simulation package dependencies

Description

Get module or simulation package dependencies

Usage

```
packages(sim, modules, paths, filenames, envir, clean = FALSE, ...)
```

```
## S4 method for signature 'ANY'
```

```
packages(sim, modules, paths, filenames, envir, clean = FALSE, ...)
```

Arguments

sim	A simList object.
modules	Character vector, specifying the name or vector of names of module(s)
paths	Character vector, specifying the name or vector of names of paths(s) for those modules. If path not specified, it will be taken from <code>getOption("spades.modulePath")</code> , which is set with <code>setPaths()</code>
filenames	Character vector specifying filenames of modules (i.e. combined path & module. If this is specified, then modules and path are ignored.
envir	Optional environment in which to store parsed code. This may be useful if the same file is being parsed multiple times. This function will check in that environment for the parsed file before parsing again. If the envir is transient, then this will have no effect.
clean	Optional logical. If TRUE, it will scrub any references to GitHub repositories, e.g., "PredictiveEcology/reproducible" will be returned as "reproducible".
...	All simInit parameters.

Value

A sorted character vector of package names.

Author(s)

Alex Chubaty & Eliot McIntire

See Also

Other functions to access elements of a 'simList' object: [.addDepends\(\)](#), [checkpointFile\(\)](#), [envir\(\)](#), [events\(\)](#), [globals\(\)](#), [inputs\(\)](#), [modules\(\)](#), [objs\(\)](#), [params\(\)](#), [paths\(\)](#), [progressInterval\(\)](#), [times\(\)](#)

paramCheckOtherMods *Test and update a parameter against same parameter in other modules*

Description

This function is intended to be part of module code and will test whether the value of a parameter within the current module matches the value of the same parameter in other modules. This is a test for parameters that might expect to be part of a `params = list(.globals = list(someParam = "test"))` passed to [simInit\(\)](#).

Usage

```

paramCheckOtherMods(
  sim,
  paramToCheck,
  moduleToUse = "all",
  ifSetButDifferent = c("error", "warning", "message", "silent"),
  verbose = getOption("reproducible.verbose")
)

```

Arguments

<code>sim</code>	A <code>simList</code> object
<code>paramToCheck</code>	A character string, length one, of a parameter name to check and compare between the current module and one or more or all others
<code>moduleToUse</code>	A character vector of module names to check against. This can be "all" which will compare against all other modules.
<code>ifSetButDifferent</code>	A character string indicating whether to "error" the default, or send a "warning", message or just silently continue (any other value).
<code>verbose</code>	Logical or Numeric, follows <code>reproducible.verbose</code> value by default.

Details

It is considered a "fail" under several conditions:

1. current module has a value that is not NULL or "default" and another module has a different value;
2. there is more than one value for the `paramToCheck` in the other modules, so it is ambiguous which one to return.

Either the current module is different than other modules, unless it is "default" or NULL.

Value

If the value of the `paramToCheck` in the current module is either NULL or "default", and there is only one other value across all modules named in `moduleToUse`, then this will return a character string with the value of the single parameter value in the other module(s). It will return the current value if there are no other modules with the same parameter.

 params

Get and set simulation parameters

Description

params, P and Par (an active binding, like "mod") access the parameter slot in the simList. params has a replace method, so can be used to update a parameter value.

Usage

```

params(sim)

## S4 method for signature 'simList'
params(sim)

params(sim) <- value

## S4 replacement method for signature 'simList'
params(sim) <- value

P(sim, param, module)

P(sim, param, module) <- value

parameters(sim, asDF = FALSE)

## S4 method for signature 'simList'
parameters(sim, asDF = FALSE)

```

Arguments

sim	A simList object from which to extract element(s) or in which to replace element(s).
value	The parameter value to be set (in the corresponding module and param).
param	Optional character string indicating which parameter to choose.
module	Optional character string indicating which module params should come from.
asDF	Logical. For parameters, if TRUE, this will produce a single data.frame of all model parameters. If FALSE, then it will return a data.frame with 1 row for each parameter within nested lists, with the same structure as params.

Details

parameters will extract only the metadata with the metadata defaults, NOT the current values that may be overwritten by a user. See examples.

Value

Returns or sets the value of the slot from the `simList` object.

Note

The differences between `P()`, `params()` and being explicit with passing arguments are mostly a question of speed and code compactness. The computationally fastest way to get a parameter is to specify `moduleName` and parameter name, as in: `P(sim, "paramName", "moduleName")` (replacing `moduleName` and `paramName` with your specific module and parameter names), but it is more verbose than `P(sim)$paramName`. Note: the important part for speed (e.g., 2-4x faster) is specifying the `moduleName`. Specifying the parameter name is <5% faster.

See Also

[SpaDES.core-package](#), specifically the section 1.2.1 on Simulation parameters.

Other functions to access elements of a 'simList' object: [.addDepends\(\)](#), [checkpointFile\(\)](#), [envir\(\)](#), [events\(\)](#), [globals\(\)](#), [inputs\(\)](#), [modules\(\)](#), [objs\(\)](#), [packages\(\)](#), [paths\(\)](#), [progressInterval\(\)](#), [times\(\)](#)

Examples

```
s <- simInit()
# add a parameter to tmp module
params(s)$tmp <- list(a = 1)

# Only work inside a module, inside a function with `sim` is an argument
# P(s, "a") # get "a" parameter inside the current module
# Par$a    # same. Get "a" parameter inside the current module

if (requireNamespace("SpaDES.tools", quietly = TRUE) &&
    packageVersion("SpaDES.tools") > "3.0.0") {
  opts <- options("spades.moduleCodeChecks" = FALSE) # not necessary for example
  modules <- list("randomLandscapes")
  paths <- list(modulePath = getSampleModules(tempdir()))
  mySim <- simInit(modules = modules, paths = paths,
                  params = list(globals = list(stackName = "landscape")))

  # update some parameters using assignment -- currently only params will work
  params(mySim)$randomLandscapes$nx <- 200
  params(mySim)$randomLandscapes$ny <- 200

  parameters(mySim) # Does not contain these user overridden values

  # These next 2 are same here because they are not within a module
  P(mySim)          # Does contain the user overridden values
  params(mySim)     # Does contain the user overridden values

  # NOTE -- deleting a parameter will affect params and P, not parameters
  params(mySim)$randomLandscapes$nx <- NULL
  params(mySim)$randomLandscapes$ny <- NULL
}
```

```

parameters(mySim) # Shows nx and ny

# These next 2 are same here because they are not within a module
P(mySim)          # nx and ny are Gone
params(mySim)     # nx and ny are Gone

options(opts) # reset
}

```

paths

Specify paths for modules, inputs, outputs, and temporary rasters

Description

Accessor functions for the paths slot in a simList object.

dataPath will return file.path(modulePath(sim), currentModule(sim), "data"). dataPath, like currentModule, is namespaced. This means that when it is used inside a module, then it will return *that model-specific* information. For instance, if used inside a module called "movingAgent", then currentModule(sim) will return "movingAgent", and dataPath(sim) will return file.path(modulePath(sim), "movingAgent", "data")

Usage

```

paths(sim)

## S4 method for signature 'simList'
paths(sim)

paths(sim) <- value

## S4 replacement method for signature 'simList'
paths(sim) <- value

cachePath(sim)

## S4 method for signature 'simList'
cachePath(sim)

cachePath(sim) <- value

## S4 replacement method for signature 'simList'
cachePath(sim) <- value

inputPath(sim)

## S4 method for signature 'simList'
inputPath(sim)

```

```
inputPath(sim) <- value

## S4 replacement method for signature 'simList'
inputPath(sim) <- value

outputPath(sim)

## S4 method for signature 'simList'
outputPath(sim)

outputPath(sim) <- value

## S4 replacement method for signature 'simList'
outputPath(sim) <- value

figurePath(sim)

## S4 method for signature 'simList'
figurePath(sim)

logPath(sim)

## S4 method for signature 'simList'
logPath(sim)

modulePath(sim, module)

## S4 method for signature 'simList'
modulePath(sim, module)

modulePath(sim) <- value

## S4 replacement method for signature 'simList'
modulePath(sim) <- value

scratchPath(sim)

## S4 method for signature 'simList'
scratchPath(sim)

scratchPath(sim) <- value

## S4 replacement method for signature 'simList'
scratchPath(sim) <- value

rasterPath(sim)
```

```

## S4 method for signature 'simList'
rasterPath(sim)

rasterPath(sim) <- value

## S4 replacement method for signature 'simList'
rasterPath(sim) <- value

terraPath(sim)

## S4 method for signature 'simList'
terraPath(sim)

terraPath(sim) <- value

## S4 replacement method for signature 'simList'
terraPath(sim) <- value

dataPath(sim)

## S4 method for signature 'simList'
dataPath(sim)

```

Arguments

sim	A simList object from which to extract element(s) or in which to replace element(s).
value	The parameter value to be set (in the corresponding module and param).
module	The optional character string of the module(s) whose paths are desired. If omitted, will return all module paths, if more than one exist.

Details

These are ways to add or access the file paths used by `spades()`. There are five file paths: `cachePath`, `modulePath`, `inputPath`, `outputPath`, and `rasterPath`. Each has a function to get or set the value in a `simList` object. If no paths are specified, the defaults are as follows:

- `cachePath`: `getOption("reproducible.cachePath")`;
- `inputPath`: `getOption("spades.modulePath")`;
- `modulePath`: `getOption("spades.inputPath")`;
- `outputPath`: `getOption("spades.outputPath")`;
- `rasterPath`: `file.path(getOption("spades.scratchPath"), "raster")`;
- `scratchPath`: `getOption("spades.scratchPath")`;
- `terraPath`: `file.path(getOption("spades.scratchPath"), "terra")`

Value

Returns or sets the value of the slot from the `simList` object.

See Also

[SpaDES.core-package](#), specifically the section 1.2.4 on Simulation Paths.

Other functions to access elements of a 'simList' object: [.addDepends\(\)](#), [checkpointFile\(\)](#), [envir\(\)](#), [events\(\)](#), [globals\(\)](#), [inputs\(\)](#), [modules\(\)](#), [objs\(\)](#), [packages\(\)](#), [params\(\)](#), [progressInterval\(\)](#), [times\(\)](#)

Plot, simList-method *Plot method for simList objects*

Description

Extends `quickPlot::Plot` for `simList` objects.

Usage

```
## S4 method for signature 'simList'
Plot(
  ...,
  new = FALSE,
  addTo = NULL,
  gp = gpar(),
  gpText = gpar(),
  gpAxis = gpar(),
  axes = FALSE,
  speedup = 1,
  size = 5,
  cols = NULL,
  col = NULL,
  zoomExtent = NULL,
  visualSqueeze = NULL,
  legend = TRUE,
  legendRange = NULL,
  legendText = NULL,
  pch = 19,
  title = NULL,
  na.color = "#FFFFFF00",
  zero.color = NULL,
  length = NULL,
  arr = NULL,
  plotFn = "plot",
  verbose = getOption("quickPlot.verbose")
)
```

Arguments

...	A combination of spatialObjects or non-spatial objects. For many object classes, there are specific Plot methods. Where there are no specific ones, the base plotting will be used internally. This means that for objects with no specific Plot methods, many arguments, such as addTo, will not work. See details.
new	Logical. If TRUE, then the previous named plot area is wiped and a new one made; if FALSE, then the ... plots will be added to the current device, adding or rearranging the plot layout as necessary. Default is FALSE. This currently works best if there is only one object being plotted in a given Plot call. However, it is possible to pass a list of logicals to this, matching the length of the ... objects. Use clearPlot to clear the whole plotting device. NOTE if TRUE: <i>Everything that was there, including the legend and the end points of the colour palette, will be removed and re-initiated.</i>
addTo	Character vector, with same length as ... This is for overplotting, when the overplot is not to occur on the plot with the same name, such as plotting a SpatialPoints* object on a RasterLayer.
gp	A gpar object, created by gpar(), to change plotting parameters (see grid package).
gpText	A gpar object for the title text. Default gpar(col = "black").
gpAxis	A gpar object for the axes. Default gpar(col = "black").
axes	Logical or "L", representing the left and bottom axes, over all plots.
speedup	Numeric. The factor by which the number of pixels is divided by to plot rasters. See Details.
size	Numeric. The size, in points, for SpatialPoints symbols, if using a scalable symbol.
cols	(also col) Character vector or list of character vectors of colours. See details.
col	(also cols) Alternative to cols to be consistent with plot. cols takes precedence, if both are provided.
zoomExtent	An Extent object. Supplying a single extent that is smaller than the rasters will call a crop statement before plotting. Defaults to NULL. This occurs after any downsampling of rasters, so it may produce very pixelated maps.
visualSqueeze	Numeric. The proportion of the white space to be used for plots. Default is 0.75.
legend	Logical indicating whether a legend should be drawn. Default is TRUE.
legendRange	Numeric vector giving values that, representing the lower and upper bounds of a legend (i.e., 1:10 or c(1, 10) will give same result) that will override the data bounds contained within the grobToPlot.
legendText	Character vector of legend value labels. Defaults to NULL, which results in a pretty numeric representation. If Raster* has a Raster Attribute Table (rat; see raster package), this will be used by default. Currently, only a single vector is accepted. The length of this must match the length of the legend, so this is mostly useful for discrete-valued rasters.
pch	see ?par.

<code>title</code>	Logical or character string. If logical, it indicates whether to print the object name as the title above the plot. If a character string, it will print this above the plot. NOTE: the object name is used with <code>addTo</code> , not the title. Default <code>NULL</code> , which means print the object name as title, if no other already exists on the plot, in which case, keep the previous title.
<code>na.color</code>	Character string indicating the colour for NA values. Default transparent.
<code>zero.color</code>	Character string indicating the colour for zero values, when zero is the minimum value, otherwise, zero is treated as any other colour. Default transparent.
<code>length</code>	Numeric. Optional length, in inches, of the arrow head.
<code>arr</code>	A vector of length 2 indicating a desired arrangement of plot areas indicating number of rows, number of columns. Default <code>NULL</code> , meaning let <code>Plot</code> function do it automatically.
<code>plotFn</code>	An optional function name to do the plotting internally, e.g., <code>"barplot"</code> to get a <code>barplot()</code> call. Default <code>"plot"</code> .
<code>verbose</code>	Numeric or logical. If <code>TRUE</code> or <code>>0</code> , then messages will be shown. If <code>FALSE</code> or <code>0</code> , most messages will be suppressed.

Details

See `quickPlot::Plot`. This method strips out stuff from a `simList` class object that would make it otherwise not reproducibly digestible between sessions, operating systems, or machines. This will likely still not allow identical digest results across R versions.

Value

invoked for side effect of plotting

See Also

`quickPlot::Plot`

Plots

Plot wrapper intended for use in a Spades module

Description

This is a single function call that allows a user to change which format in which the plots will occur. Specifically, the two common formats would be to "screen" or to disk as an image file, such as "png". *This has currently been tested with ggplot2, RasterLayer, and tmap objects.* The default (or change with e.g., `fn = "print"`, `usePlot = FALSE`) uses `Plot` internally, so individual plots may be rearranged. When saved to disk (e.g., via `type = 'png'`), then `Plot` will not be used and the single object that is the result of this `Plots` call will be saved to disk. This function requires at least 2 things: a plotting function and arguments passed to that function (which could include data, but commonly would simply be named arguments required by `fn`). See below and examples.

Usage

```

Plots(
  data,
  fn,
  filename,
  types = quote(params(sim)[[currentModule(sim)]]$.plots),
  path = quote(figurePath(sim)),
  .plotInitialTime = quote(params(sim)[[currentModule(sim)]]$.plotInitialTime),
  ggsaveArgs = list(),
  usePlot = getOption("spades.PlotsUsePlot", FALSE),
  deviceArgs = list(),
  envir = parent.frame(),
  ...
)

```

Arguments

<code>data</code>	An (optional) arbitrary data object. If supplied, it will be passed as the first argument to <code>Plot</code> function, and should contain all the data required for the inner plotting. If passing a <code>RasterLayer</code> , it may be a good idea to set <code>names(RasterLayer)</code> so that multiple layers can be plotted without overlapping each other. When a custom <code>fn</code> is used and all arguments for <code>fn</code> are supplied and named, then this can be omitted. See examples.
<code>fn</code>	An arbitrary plotting function. If not provided, defaults to using <code>quickPlot::Plot</code>
<code>filename</code>	A name that will be the base for the files that will be saved, i.e., do not supply the file extension, as this will be determined based on <code>types</code> . If a user provides this as an absolute path, it will override the <code>path</code> argument.
<code>types</code>	Character vector, zero or more of types. If used within a module, this will be deduced from the <code>P(sim)\$type</code> and can be omitted. See below.
<code>path</code>	Currently a single path for the saved objects on disk. If <code>filename</code> is supplied as an absolute path, <code>path</code> will be set to <code>dirname(filename)</code> , overriding this argument value.
<code>.plotInitialTime</code>	A numeric. If <code>NA</code> then no visual on screen. Anything else will have visuals plotted to screen device. This is here for backwards compatibility. A developer should set in the module to the intended initial plot time and leave it, i.e., <i>not</i> <code>NA</code> .
<code>ggsaveArgs</code>	An optional list of arguments passed to <code>ggplot2::ggsave</code>
<code>usePlot</code>	Logical. If <code>TRUE</code> , the default, then the plot will occur with <code>quickPlot::Plot</code> , so it will be arranged with previously existing plots.
<code>deviceArgs</code>	An optional list of arguments passed to one of <code>png</code> , <code>pdf</code> , <code>tiff</code> , <code>bmp</code> , or <code>jpeg</code> . This is useful when the plotting function is not creating a <code>ggplot</code> object, e.g., plotting a <code>RasterLayer</code> .
<code>envir</code>	The environment where the data argument should be evaluated if it is a call. Normally, this should be left at its default, <code>parent.frame()</code> .
<code>...</code>	Anything needed by <code>fn</code> , all named.

Details

- type
 - "screen" – Will plot to the current device, normally a plot window
 - "object" – Will save the plot object, e.g., ggplot object
 - "raw" – Will save the raw data prior to plotting, e.g., the data argument
 - "png" – or any other type save-able with ggsave

Value

Called for its side effect of plot creation.

Recording of files saved

In cases where files are saved, and where Plots is used within a SpaDES module, the file(s) that is/are saved will be appended to the outputs slot of the simList of the module. This will, therefore, keep a record of figures saved *within* the simList

Note

This is still experimental and could change in the next release.

Plots now has experimental support for "just a Plot call", but with types specified. See examples. The devices to save on disk will have some different behaviours to the screen representation, since "wiping" an individual plot on a device doesn't exist for a file device.

This offers up to 4 different actions for a given plot:

- To screen device
- To disk as raw data (limited testing)
- To disk as a saved plot object (limited testing)
- To disk as a '.png' or other image file, e.g., '.pdf'

To turn off plotting both to screen and disk, set both `.plotInitialTime = NA` and `.plots = NA` or any other value that will not trigger a TRUE with a `grepl` with the `types` argument (e.g., "" will omit all saving).

Examples

```
# Note: if this is used inside a SpaDES module, do not define this
# function inside another function. Put it outside in a normal
# module script. Otherwise, it will cause a memory leak.
if (requireNamespace("ggplot2")) {
  fn <- function(d)
    ggplot2::ggplot(d, ggplot2::aes(a)) +
    ggplot2::geom_histogram()
  sim <- simInit()
  sim$something <- data.frame(a = sample(1:10, replace = TRUE))

  Plots(data = sim$something, fn = fn,
        types = c("png"),
```

```

    path = file.path(tempdir(), "figures"),
    filename = tempfile(),
    .plotInitialTime = 1)

# plot to active device and to png
Plots(
  data = sim$something, fn = fn,
  types = c("png", "screen"),
  path = file.path(tempdir(), "figures"),
  filename = tempfile(),
  .plotInitialTime = 1
)

# Can also be used like quickPlot::Plot, but with control over output type
r <- terra::rast(terra::ext(0,10,0,10),
  vals = sample(1:3, size = 100, replace = TRUE))
Plots(r, types = c("screen", "png"), filename = tempfile(),
  deviceArgs = list(width = 700, height = 500),
  usePlot = TRUE)

# with ggplotify, Plots can also be used to plot/save
# non-ggplot objects:

if (require("ggplotify")) {
  if (!require("lattice")) stop("please install lattice")

  p1 <- densityplot(~mpg|cyl, data=mtcars)
  Plots(data = p1, fn = as.ggplot, filename = tempfile(),
    ggsaveArgs = list(width = 5, height = 4, dpi = 300,
      bg = "white", units = "in"),
    types = c("screen", "png"),
    .plotInitialTime = 1)
}
} # end ggplot
unlink("figures") # clean up
# end of dontrun

```

priority

Event priority

Description

Preset event priorities: 1 = first (highest); 5 = normal; 10 = last (lowest).

Usage

`.first()`

`.highest()`

```
.last()
.lowest()
.normal()
```

Value

numeric of length 1.

Author(s)

Alex Chubaty

progressInterval	<i>Get and set simulation progress bar details</i>
------------------	--

Description

The progress bar can be set in two ways in SpaDES. First, by setting values in the `.progress` list element in the `params` list element passed to `simInit()`. Second, at the `spades()` call itself, which can be simpler. See examples.

Usage

```
progressInterval(sim)

## S4 method for signature 'simList'
progressInterval(sim)

progressInterval(sim) <- value

## S4 replacement method for signature 'simList'
progressInterval(sim) <- value

progressType(sim)

## S4 method for signature 'simList'
progressType(sim)

progressType(sim) <- value

## S4 replacement method for signature 'simList'
progressType(sim) <- value
```

Arguments

sim	A simList object from which to extract element(s) or in which to replace element(s).
value	The parameter value to be set (in the corresponding module and param).

Details

Progress Bar: Progress type can be one of "text", "graphical", or "shiny". Progress interval can be a numeric. These both can get set by passing a `.progress = list(type = "graphical", interval = 1)` into the `simInit` call. See examples.

Value

for `progressInterval`, a numeric corresponding to the progress update interval; for `progressInterval<-`, an updated `simList` object.

See Also

Other functions to access elements of a 'simList' object: [.addDepends\(\)](#), [checkpointFile\(\)](#), [envir\(\)](#), [events\(\)](#), [globals\(\)](#), [inputs\(\)](#), [modules\(\)](#), [objs\(\)](#), [packages\(\)](#), [params\(\)](#), [paths\(\)](#), [times\(\)](#)

Examples

```
if (requireNamespace("SpaDES.tools", quietly = TRUE) &&
    packageVersion("SpaDES.tools") > "3.0.0") {
  opts <- options("spades.moduleCodeChecks" = FALSE) # not necessary for example
  mySim <- simInit(
    times = list(start=0.0, end=100.0),
    params = list(.globals = list(stackName = "landscape"),
      .progress = list(type = "text", interval = 10),
      checkpoint = list(interval = 10, file = "chkpnt.RData")),
    modules = list("randomLandscapes"),
    paths = list(modulePath = getSampleModules(tempdir()))
  )

  # progress bar
  progressType(mySim) # "text"
  progressInterval(mySim) # 10

  # parameters
  params(mySim) # returns all parameters in all modules
                # including .global, .progress, checkpoint
  globals(mySim) # returns only global parameters

  # checkpoint
  checkpointFile(mySim) # returns the name of the checkpoint file
                       # In this example, "chkpnt.RData"
  checkpointInterval(mySim) # 10

  options(opts) # reset
```

```
}
```

rasterCreate	<i>Simple wrapper to load any Raster* object</i>
--------------	--

Description

This wraps either `raster::raster`, `raster::stack`, `raster::brick`, or `terra::rast`, allowing a single function to be used to create a new object of the same class as a template. This works for all `Raster*` and `SpatRaster` class templates.

Usage

```
rasterCreate(x, ...)
```

```
## Default S3 method:
```

```
rasterCreate(x, ...)
```

Arguments

<code>x</code>	An object, notably a <code>Raster*</code> object. All others will simply be passed through with no effect.
<code>...</code>	Passed to <code>raster::raster</code> , <code>raster::stack</code> , or <code>raster::brick</code>

Value

a new (empty) object of same class as the original.

Methods (by class)

- `rasterCreate(default)`: Simply passes through argument with no effect

rasterToMemory	<i>Read raster to memory</i>
----------------	------------------------------

Description

Wrapper to the `raster` function, that creates the raster object in memory, even if it was read in from file. There is the default method which is just a pass through, so this can be safely used on large complex objects, recursively, e.g., a `simList`.

Usage

```
rasterToMemory(x, ...)  
  
## S4 method for signature 'list'  
rasterToMemory(x, ...)  
  
## S4 method for signature 'character'  
rasterToMemory(x, ...)  
  
## S4 method for signature 'ANY'  
rasterToMemory(x, ...)  
  
## S4 method for signature 'simList'  
rasterToMemory(x, ...)
```

Arguments

x	An object passed directly to the function raster (e.g., character string of a file-name).
...	Additional arguments to raster::raster, raster::stack, or raster::brick.

Value

A raster object whose values are stored in memory.

Author(s)

Eliot McIntire and Alex Chubaty

See Also

raster(), [terra::rast\(\)](#).

remoteFileSize	<i>Determine the size of a remotely hosted file</i>
----------------	---

Description

Defunct. Will be removed by mid-2023.

Usage

```
remoteFileSize(url)
```

Arguments

url	The url of the remote file.
-----	-----------------------------

Value

A numeric indicating the size of the remote file in bytes.

Author(s)

Eliot McIntire and Alex Chubaty

 restartR

Restart R programmatically

Description

This will attempt to restart the R session, reloading all packages, and saving and reloading the `simList`. Currently, this is not intended for general use: it has many specialized pieces for using inside a `spades` call. The main purpose for doing this is to clear memory leaks (possibly deep in R <https://github.com/r-lib/fastmap>) that are not fully diagnosed. *This is still very experimental.* This should only be used if there are RAM limitations being hit with long running simulations. It has been tested to work Linux within Rstudio and at a terminal R session. The way to initiate restarting of R is simply setting the `spades.restartRInterval` or setting the equivalent parameter in the `restartR` core module via: `simInit(..., params = list(.restartR = list(.restartRInterval = 1)), ...)` greater than 0, which is the default, e.g., `options("spades.restartRInterval" = 100)`. This is only intended to restart a simulation in exactly the same place as it was (i.e., cannot change machines), and because of the restart, the assignment of the `spades` call will be either to `sim` or the user must make such an assignment manually, e.g., `sim <- savedSimEnv()$.sim`, or perhaps, the safer `sim <- Copy(savedSimEnv()$.sim)`. This is stated in a message.

Usage

```
restartR(
  sim,
  reloadPkgs = TRUE,
  .First = NULL,
  .RDataFile = getOption("spades.restartR.RDataFilename"),
  restartDir = getOption("spades.restartR.restartDir", NULL)
)
```

Arguments

<code>sim</code>	Required. A <code>simList</code> to be retained through the restart.
<code>reloadPkgs</code>	Logical. If <code>TRUE</code> , it will attempt to reload all the packages as they were in previous session, in the same order. If <code>FALSE</code> , it will load no packages beyond normal R startup. Default <code>TRUE</code> .
<code>.First</code>	A function to save to <code>~/ .qs2</code> which will be loaded at restart from <code>~/ .qs2</code> and run. Default is <code>NULL</code> , meaning it will use the non-exported <code>SpaDES.core:::First</code> . If a user wants to make a custom <code>First</code> file, it should built off that one.

<code>.RDataFile</code>	A filename for saving the <code>simList</code> . Defaults to <code>getOption("spades.restartR.filename")</code> , and the directory will be in <code>restartDir</code> . The simulation time will be mid-pended to this name, as in: <code>basename(file), "_time", paddedFloatToChar(time(sim), padL = nchar(</code>
<code>restartDir</code>	A character string indicating root directory to save <code>simList</code> and other ancillary files during restart. Defaults to <code>getOption("spades.restartR.restartDir", NULL)</code> . If <code>NULL</code> , then it will try, in order, <code>outputPath(sim)</code> , <code>modulePath(sim)</code> , <code>inputPath(sim)</code> , <code>cachePath(sim)</code> , taking the first one that is not inside the <code>tempdir()</code> , which will disappear during restart of R. The actual directory for a given spades call that is restarting will be: <code>file.path(restartDir, "restartR", paste0(sim[["_txtStartClockTime"]], "_", .rndString))</code> . The random string is to prevent parallel processes that started at the same clock time from colliding.

Details

The process responds to several options. Though under most cases, the default behaviour should suffice. These are of 3 types: `restartRInterval` the arguments to `restartR` and the arguments to `saveSimList`, these latter two using a dot to separate the function name and its argument. The defaults for two key options are: `options("spades.restartR.restartDir" = NULL, meaning use file.path(restartDir, "restartR", paste0(sim[["_txtStartClockTime"]], "_", .rndString)) and options("spades.saveSimList.fileBackend" = 0), which means don't do anything with raster-backed files. See specific functions for defaults and argument meanings. The only difference from the default function values is with saveSimList argument fileBackend = FALSE during restartR by default, because it is assumed that the file backends will still be intact after a restart, so no need to move them all to memory.`

Value

invoked for side effect of restarting the R session

Note

Because of the restarting, the object name of the original assignment of the spades call can not be preserved. The spades call will be assigned to `sim` in the `.GlobalEnv`.

Because this function is focused on restarting during a spades call, it will remove all objects in the `.GlobalEnv`, emulating `q("no")`. If the user wants to keep those objects, then they should be saved to disk immediately before the spades call. This can then be recovered immediately after the return from the spades call.

To keep the saved `simList`, use `options("spades.restartR.clearFiles" = TRUE)`. The default is to treat these files as temporary files and so will be removed.

Description

This is experimental and has not been thoroughly tested. Use with caution. If there is an error during an event, this function will rewind the simulation to a state `numEvents` prior to the event that led to the error. The developer may then modify the source code of the module that caused the break and resume the simulation.

Usage

```
restartSpades(
  sim = NULL,
  module = NULL,
  numEvents = Inf,
  restart = TRUE,
  verbose = getOption("reproducible.verbose", 1L),
  ...
)

saveState(filename, ...)

restartOrSimInitAndSpades(ll, file, reset = getOption("spades.resetRestart"))
```

Arguments

<code>sim</code>	A <code>simList</code> or a filename that will load a <code>simList</code> , e.g., from <code>saveState</code> or <code>saveSimList</code> . If not supplied (the default), this will take the <code>sim</code> from <code>savedSimEnv()\$.sim</code> , i.e., the one that was interrupted
<code>module</code>	A character string length one naming the module that caused the error and whose source code was fixed. This module will be re-parsed and placed into the <code>simList</code>
<code>numEvents</code>	Numeric. Default is <code>Inf</code> (i.e., all available). The number of events to be rewind. In the <code>simList</code> , if <code>options('spades.recoveryMode')</code> is set to <code>TRUE</code> or a numeric, then there will be a list in the <code>simList</code> called <code>.recoverableObjs</code> . These will be replayed backwards in time to reproduce the initial state of the <code>simList</code> before the event that is <code>numEvents</code> prior to the first event in <code>events(sim)</code> .
<code>restart</code>	Logical. If <code>TRUE</code> , then the call to <code>spades</code> will be made, i.e., restarting the simulation. If <code>FALSE</code> , then it will return a new <code>simList</code> with the module code parsed into the <code>simList</code>
<code>verbose</code>	Logical or Numeric, follows <code>reproducible.verbose</code> value by default.
<code>...</code>	Passed to <code>spades</code> , e.g., <code>debug</code> , <code>.plotInitialTime</code>
<code>filename</code>	The filename to save the sim state. <code>saveState</code> is a wrapper around <code>restartSpades</code> and <code>saveSimList</code> . You can pass arguments to the <code>...</code> that will be passed to <code>saveSimList</code> , such as modules, inputs, outputs.
<code>ll</code>	A list of elements that would be passed to <code>simInit</code> , such as modules.
<code>file</code>	An optional file that has a saved <code>simList</code> , e.g., from <code>saveSimList</code> or <code>saveState</code> .
<code>reset</code>	Logical. If <code>TRUE</code> , then it will force <code>simInitAndSpades</code> to be called even if there is saved <code>sim</code> available.

Details

If `options('spades.recoveryMode')` is set to `TRUE` or a numeric (default 1), then there will be a list in the `simList` called `.recoverableObjs`. These record the elements of `simList` that have changed over a number of events equal to the number chosen for `options('spades.recoveryMode')`. The `restartSpades` function then uses this list to rewind `numEvents` backwards from the first event in `events(sim)` (likely the one that caused the error).

The random number seed will be reset to the state it was at the start of the earliest event recovered, thereby returning to the exact stochastic simulation trajectory.

Value

A `simList` as if `spades` had been called on a `simList`.

A `simList`, that has been "executed" until `end(sim)`, if it does not hit an error.

Note

The `simList` will be in the state it was `numEvents` prior to the event that led to the error (although some objects, e.g., on disk, may have already been modified).

Examples

```
# options("spades.recoveryMode" = 1) # now the default
s <- simInit()
s <- spades(s) # if this is interrupted or fails
## the following line will not work if the previous line didn't fail:

## don't need to specify `sim` if previous line fails;
## will take from savedSimEnv()$.sim automatically
s <- restartSpades(s)
```

savedSimEnv

Retrieve environment for saving interrupted simulations

Description

If the user sets `options(reproducible.memoisePersist = TRUE)`, the global environment will be used, otherwise, a package environment.

Usage

```
savedSimEnv(envir = .GlobalEnv)
```

Arguments

`envir` an environment to use to store the `.sim` (`simList`) object. default is to use the user's global environment (`.GlobalEnv`).

saveFiles	Save objects using .saveObjects in params slot of simInit
-----------	---

Description

In the `simInit()` call, a parameter called `.saveObjects` can be provided in each module. This must be a character string vector of all object names to save. These objects will then be saved whenever a call to `saveFiles` is made.

Usage

```
saveFiles(sim)
```

Arguments

`sim` A `simList` simulation object.

Details

The file names will be equal to the object name plus `time(sim)` is appended at the end. The files are saved as `.rds` files, meaning, only one object gets saved per file.

For objects saved using this function, the module developer must create save events that schedule a call to `saveFiles`.

If this function is used outside of a module, it will save all files in the `outputs(sim)` that are scheduled to be saved at the current time in the `simList`.

There are several ways to save objects using SpaDES.

Value

(invisibly) the modified `sim` object. invoked for side effect of saving the simulation to file.

Model-level saving

Using the `outputs` slot in the `simInit()` call. See example in `simInit()`. This can be convenient because it gives overall control of many modules at a time, and it gets automatically scheduled during the `simInit()` call.

Module-level saving

Using the `saveFiles` function inside a module. This must be accompanied by a `.saveObjects` vector or list element in the `params` slot in the `simList()`. Usually a module developer will create this method for future users of their module.

Custom saving

A module developer can save any object at any time inside their module, using standard R functions for saving R objects (e.g., `save` or `saveRDS`). This is the least modular approach, as it will happen whether a module user wants it or not.

Note

It is not possible to schedule separate saving events for each object that is listed in the `.saveObjects`.

Author(s)

Eliot McIntire and Alex Chubaty

Examples

```

if (requireNamespace("SpaDES.tools", quietly = TRUE) &&
    packageVersion("SpaDES.tools") > "3.0.0") {
## This will save the "caribou" object at the save interval of 1 unit of time
## in the outputPath location
outputPath <- file.path(tempdir(), "test_save")
times <- list(start = 0, end = 1, "month")

modules <- list("randomLandscapes", "caribouMovement")
paths <- list(
  modulePath = getSampleModules(tempdir()),
  outputPath = outputPath
)
opts <- options("spades.moduleCodeChecks" = FALSE,
               "spades.useRequire" = FALSE) # not necessary for example

## save multiple outputs
parameters <- list(
  .globals = list(stackName = "landscape"),
  caribouMovement = list(
    .saveObjects = c("caribou", "habitatQuality"),
    .saveInitialTime = 1, .saveInterval = 1
  ),
  randomLandscapes = list(.plots = NA, nx = 20, ny = 20))

mySim <- simInit(times = times, params = parameters, modules = modules,
                paths = paths)

spades(mySim, .plotInitialTime = NA) # plotting not relevant for this example
dir(outputPath)
# remove the files
file.remove(dir(outputPath, full.names = TRUE))

options(opts) # clean up
}

```

Description

Saving a `simList` may not work using the standard approaches (e.g., `save`, `saveRDS`, and `qs2::qs_save`). There are 2 primary reasons why this doesn't work as expected: the `activeBindings` that are in place within modules (these allow the `mod` and `Par` to exist), and file-backed objects, such as `SpatRaster` and `Raster*`. Because of these, a user should use `saveSimList` and `loadSimList`. These will save the object and recover the object using the filename supplied, if there are no file-backed objects. If there are file-backed objects, then it will save an archive (default is `.tar.gz` using the `archive` package for non-Windows and `zip()` if using Windows, as there is currently an unidentified bug in `archive*` on Windows). The user does not need to specify the filename any differently, as the code will search based on the filename without the file extension.

Usage

```
saveSimList(
  sim,
  filename,
  projectPath = getwd(),
  outputs = TRUE,
  inputs = TRUE,
  cache = FALSE,
  envir,
  files = TRUE,
  ...
)
```

Arguments

<code>sim</code>	Either a <code>simList</code> or a character string of the name of a <code>simList</code> that can be found in <code>envir</code> . Using a character string will assign that object name to the saved <code>simList</code> , so when it is recovered it will be given that name.
<code>filename</code>	Character string with the path for saving <code>simList</code> to or reading the <code>simList</code> from. Currently, only <code>.rds</code> and <code>.qs2</code> file types are supported.
<code>projectPath</code>	Should be the "top level" or project path for the <code>simList</code> . Defaults to <code>getwd()</code> . All other paths will be made relative with respect to this if nested within this.
<code>outputs</code>	Logical. If <code>TRUE</code> , all files identified in <code>outputs(sim)</code> will be included in the zip.
<code>inputs</code>	Logical. If <code>TRUE</code> , all files identified in <code>inputs(sim)</code> will be included in the zip.
<code>cache</code>	Logical. Not yet implemented. If <code>TRUE</code> , all files in <code>cachePath(sim)</code> will be included in the archive. Defaults to <code>FALSE</code> as this could be large, and may include many out of date elements. See Details.
<code>envir</code>	If <code>sim</code> is a character string, then this must be provided. It is the environment where the object named <code>sim</code> can be found.
<code>files</code>	Logical. Should all the files in the optional <code>outputs</code> , <code>inputs</code> , <code>cache</code> be saved. If this is <code>TRUE</code> , then the resulting <code>filename</code> will be silently converted to an archive file with the appropriate extension e.g., <code>.zip</code> or <code>.tar.gz</code> . This will automatically be <code>TRUE</code> if any of the <code>outputs</code> , <code>inputs</code> or <code>cache</code> are <code>TRUE</code> . Setting this to <code>FALSE</code> will turn off the saving of files specified in <code>inputs(sim)</code> , <code>outputs(sim)</code> or the <code>cache</code> .

... Additional arguments. See Details.

Details

There is a family of 2 functions that are mutually useful for saving and loading `simList` objects and their associated files (e.g., file-backed `Raster*`, `inputs`, `outputs`, `cache`) `saveSimList()`, `loadSimList()`.

Additional arguments may be passed via `...`, including:

- `files`: logical indicating whether files should be included in the archive. if `FALSE`, will override `cache`, `inputs`, `outputs`, setting them to `FALSE`.
- `symlinks`: a named list of paths corresponding to symlinks, which will be used to substitute normalized absolute paths of files. Names should correspond to the names in `paths()`; values should be project-relative paths. E.g., `list(cachePath = "cache", inputPath = "inputs", outputPath = "outputs")`.

Value

Invoked for side effects of saving both a `.qs2` (or `.rds`) file, and a compressed archive (one of `.tar.gz` if using non-Windows OS or `.zip` on Windows).

See Also

[loadSimList\(\)](#)

scheduleConditionalEvent

Schedule a conditional simulation event

Description

Adds a new event to the simulation's conditional event queue, updating the simulation object by creating or appending to `sim$._conditionalEvents`. *This is very experimental. Use with caution.*

Usage

```
scheduleConditionalEvent(  
  sim,  
  condition,  
  moduleName,  
  eventType,  
  eventPriority = .normal(),  
  minEventTime = start(sim),  
  maxEventTime = end(sim)  
)
```

Arguments

sim	A simList simulation object.
condition	A string, call or expression that will be assessed for TRUE after each event in the regular event queue. It can access objects in the simList by using functions of sim, e.g., "sim\$page > 1"
moduleName	A character string specifying the module from which to call the event. If missing, it will use currentModule(sim)
eventType	A character string specifying the type of event from within the module.
eventPriority	A numeric specifying the priority of the event. Lower number means higher priority. As a best practice, it is recommended that decimal values are conceptual grouped by their integer values (e.g., 4.0, 4.25, 4.5 are conceptually similar). See priority() .
minEventTime	A numeric specifying the time before which the event should not occur, even if the condition is met. Defaults to start(sim)
maxEventTime	A numeric specifying the time after which the event should not occur, even if the condition is met. Defaults to end(sim)

Details

This conditional event queue will be assessed at every single event in the normal event queue. If there are no conditional events, then spades will proceed as normal. As conditional event conditions are found to be true, then it will trigger a call to `scheduleEvent(...)` with the current time passed to `eventTime` *and* it will remove the conditional event from the conditional queue. If the user would like the triggered conditional event to occur as the very next event, then a possible strategy would be to set `eventPriority` of the conditional event to very low or even negative to ensure it gets inserted at the top of the event queue.

Value

Returns the modified simList object, i.e., `sim$._conditionalEvents`.

Author(s)

Eliot McIntire

References

Matloff, N. (2011). The Art of R Programming (ch. 7.8.3). San Francisco, CA: No Starch Press, Inc.. Retrieved from <https://nostarch.com/artofr.htm>

See Also

[scheduleEvent\(\)](#), [conditionalEvents\(\)](#)

Examples

```

sim <- simInit(times = list(start = 0, end = 2))
condition <- "sim$age > 1" # provide as string
condition <- quote(sim$age > 1) # provide as a call
condition <- expression(sim$age > 1) # provide as an expression
sim <- scheduleConditionalEvent(sim, condition, "firemodule", "burn")
conditionalEvents(sim)
sim <- spades(sim) # no changes to sim$age, i.e., it is absent
events(sim) # nothing scheduled
sim$age <- 2 # change the value
sim <- spades(sim) # Run spades, the condition is now true, so event is
                  # scheduled at current time
events(sim)      # now scheduled in the normal event queue

```

scheduleEvent	<i>Schedule a simulation event</i>
---------------	------------------------------------

Description

Adds a new event to the simulation's event queue, updating the simulation object.

Usage

```

scheduleEvent(
  sim,
  eventTime,
  moduleName,
  eventType,
  eventPriority = .pkgEnv$.normalVal,
  .skipChecks = FALSE
)

```

Arguments

<code>sim</code>	A <code>simList</code> simulation object.
<code>eventTime</code>	A numeric specifying the time of the next event.
<code>moduleName</code>	A character string specifying the module from which to call the event. If missing, it will use <code>currentModule(sim)</code>
<code>eventType</code>	A character string specifying the type of event from within the module.
<code>eventPriority</code>	A numeric specifying the priority of the event. Lower number means higher priority. As a best practice, it is recommended that decimal values are conceptual grouped by their integer values (e.g., 4.0, 4.25, 4.5 are conceptually similar). See priority() .
<code>.skipChecks</code>	Logical. If TRUE, then internal checks that arguments match expected types are skipped. Should only be used if speed is critical.

Details

Here, we implement a simulation in a more modular fashion so it's easier to add submodules to the simulation. We use S4 classes and methods, and use `data.table` instead of `data.frame` to implement the event queue (because it is much faster).

Value

Returns the modified `simList` object.

Author(s)

Alex Chubaty

References

Matloff, N. (2011). *The Art of R Programming* (ch. 7.8.3). San Francisco, CA: No Starch Press, Inc.. Retrieved from <https://nostarch.com/artofr.htm>

See Also

[priority\(\)](#), [scheduleConditionalEvent\(\)](#)

Examples

```
sim <- simInit()
sim <- scheduleEvent(sim, time(sim) + 1.0, "fireSpread", "burn") # default priority
sim <- scheduleEvent(sim, time(sim) + 1.0, "fireSpread", "burn", .normal()) # default priority

sim <- scheduleEvent(sim, time(sim) + 1.0, "fireSpread", "burn", .normal()-1) # higher priority
sim <- scheduleEvent(sim, time(sim) + 1.0, "fireSpread", "burn", .normal()+1) # lower priority

sim <- scheduleEvent(sim, time(sim) + 1.0, "fireSpread", "burn", .highest()) # highest priority
sim <- scheduleEvent(sim, time(sim) + 1.0, "fireSpread", "burn", .lowest()) # lowest priority
events(sim) # shows all scheduled events, with eventTime and priority
```

show,simList-method *Show an Object*

Description

Show an Object

Usage

```
## S4 method for signature 'simList'
show(object)
```

Arguments

object simList

Author(s)

Alex Chubaty

simFile	<i>Generate simulation file name</i>
---------	--------------------------------------

Description

Assists with saving and retrieving simulations (e.g., with saveSimList and loadSimList).

Usage

```
simFile(name, path, time = NULL, ext = "rds")
```

Arguments

name	Object name (e.g., "mySimOut")
path	Directory location in where the file will be located (e.g., an outputPath).
time	Optional simulation time to use as filename suffix. Default NULL.
ext	The file extension to use (default "rds").

Value

character string giving a file path for a simulation file

simInit	<i>Initialize a new simulation</i>
---------	------------------------------------

Description

Create a new simulation object, the sim object (a simList). This object is implemented using an environment where all objects and functions are placed. Since environments in R are pass by reference, "putting" objects in the sim object does no actual copy. The simList also stores all parameters, and other important simulation information, such as times, paths, modules, and module load order. See more details below.

Usage

```
simInit(  
  times,  
  params,  
  modules,  
  objects,  
  paths,  
  inputs,  
  outputs,  
  loadOrder,  
  notOlderThan = NULL,  
  ...  
)  
  
## S4 method for signature  
## 'list,list,list,list,list,data.frame,data.frame,character'  
simInit(  
  times,  
  params,  
  modules,  
  objects,  
  paths,  
  inputs,  
  outputs,  
  loadOrder,  
  notOlderThan = NULL,  
  ...  
)  
  
## S4 method for signature 'ANY,ANY,ANY,character,ANY,ANY,ANY,ANY'  
simInit(  
  times,  
  params,  
  modules,  
  objects,  
  paths,  
  inputs,  
  outputs,  
  loadOrder,  
  notOlderThan = NULL,  
  ...  
)  
  
## S4 method for signature 'ANY,ANY,character,ANY,ANY,ANY,ANY,ANY'  
simInit(  
  times,  
  params,  
  modules,
```

```

    objects,
    paths,
    inputs,
    outputs,
    loadOrder,
    notOlderThan = NULL,
    ...
)

## S4 method for signature 'ANY,ANY,ANY,ANY,ANY,ANY,ANY,ANY'
simInit(
  times,
  params,
  modules,
  objects,
  paths,
  inputs,
  outputs,
  loadOrder,
  notOlderThan = NULL,
  ...
)

simInit2(1)

simInitDefaults()

```

Arguments

times	A named list of numeric simulation start and end times (e.g., <code>times = list(start = 0.0, end = 10.0, timeunit = "year")</code>), with the final optional element, <code>timeunit</code> , overriding the default time unit used in the simulation which is the "smallest time unit" across all modules. See examples.
params	A list of lists of the form <code>list(moduleName=list(param1=value, param2=value))</code> . See details.
modules	A named list of character strings specifying the names of modules to be loaded for the simulation. Note: the module name should correspond to the R source file from which the module is loaded. Example: a module named "caribou" will be sourced from the file 'caribou.R', located at the specified <code>modulePath(simList)</code> (see below).
objects	(optional) A vector of object names (naming objects that are in the calling environment of the <code>simInit</code> , which is often the <code>.GlobalEnv</code> unless used programmatically. NOTE: this mechanism will fail if object name is in a package dependency), or a named list of data objects to be passed into the <code>simList</code> (more reliable). These objects will be accessible from the <code>simList</code> as a normal list, e.g., <code>mySim\$obj</code> .
paths	An optional named list with up to 4 named elements, <code>modulePath</code> , <code>inputPath</code> , <code>outputPath</code> , and <code>cachePath</code> . See details. NOTE: Experimental feature now

	allows for multiple <code>modulePaths</code> to be specified in a character vector. The modules will be searched for sequentially in the first <code>modulePath</code> , then if it doesn't find it, in the second etc.
<code>inputs</code>	A <code>data.frame</code> . Can specify from 1 to 6 columns with following column names: <code>objectName</code> (character, required), <code>file</code> (character), <code>fun</code> (character), <code>package</code> (character), <code>interval</code> (numeric), <code>loadTime</code> (numeric). See <code>inputs()</code> and <code>vignette("ii-modules")</code> section about inputs.
<code>outputs</code>	A <code>data.frame</code> . Can specify from 1 to 5 columns with following column names: <code>objectName</code> (character, required), <code>file</code> (character), <code>fun</code> (character), <code>package</code> (character), <code>saveTime</code> (numeric) and <code>eventPriority</code> (numeric). If <code>eventPriority</code> is not set, it defaults to <code>.last()</code> . If <code>eventPriority</code> is set to a low value, e.g., 0, 1, 2 and <code>saveTime</code> is <code>start(sim)</code> , it should give "initial conditions". See <code>outputs()</code> and <code>vignette("ii-modules")</code> section about outputs.
<code>loadOrder</code>	An optional character vector of module names specifying the order in which to load the modules. If not specified, the module load order will be determined automatically.
<code>notOlderThan</code>	A time, as in from <code>Sys.time()</code> . This is passed into the <code>Cache</code> function that wraps <code>.inputObjects</code> . If the module uses the <code>.useCache</code> parameter and it is set to <code>TRUE</code> or <code>".inputObjects"</code> , then the <code>.inputObjects</code> will be cached. Setting <code>notOlderThan = Sys.time()</code> will cause the cached versions of <code>.inputObjects</code> to be refreshed, i.e., rerun.
<code>...</code>	An alternative way to pass objects, i.e., they can just be named arguments rather than in a <code>objects = list(...)</code> . It can also be any options that begins with spades, <code>reproducible</code> or <code>Require</code> , i.e., those identified in <code>spadesOptions()</code> , <code>reproducibleOptions()</code> or <code>RequireOptions()</code> . These will be assigned to the equivalent option <i>during</i> the <code>simInit</code> and <code>spades</code> calls only, i.e., they will revert after the <code>simInit</code> or <code>spades</code> calls are complete. NOTE: these are not passed to the <code>simList</code> per se, i.e., they are not be available in the <code>simList</code> during either the <code>simInit</code> or <code>spades</code> calls via <code>sim\$xxx</code> , though they will be returned to the <code>simList</code> at the end of each of these calls (so that the next call to e.g., <code>spades</code> can see them). For convenience, these can be supplied without their package prefix, e.g., <code>lowMemory</code> can be specified instead of <code>spades.lowMemory</code> . In cases that share option name (<code>reproducible.verbose</code> and <code>Require.verbose</code> both exist), passing <code>verbose = FALSE</code> will set both. Obviously this may cause unexpected problems if a module is also expecting a value.
1	A list of arguments to passed to <code>simInit</code> .

Details

Calling this `simInit` function does the following::

What

fills `simList` slots
sources all module files
copies objects
loads objects
schedule object loading/copying

Details

places the arguments `times`, `params`, `modules`, `paths` into equivalently named `simList` slots
places all function definitions in the `simList`, specifically, into a sub-environment of the `simList`
from the global environment to the `simList` environment
from disk into the `simList`
Objects can be loaded into the `simList` at any time during a simulation

schedule object saving	Objects can be saved to disk at any arbitrary time during the simulation. If specified here, the
schedules "init" events	from all modules (see <code>events()</code>)
assesses module dependencies	via the inputs and outputs identified in their metadata. This gives the order of the <code>.inputOb</code>
determines time unit	takes time units of modules and how they fit together
runs <code>.inputObjects</code> functions	from every module <i>in the module order as determined above</i>

params can only contain updates to any parameters that are defined in the metadata of modules. Take the example of a module named, `Fire`, which has a parameter named `.plotInitialTime`. In the metadata of that module, it says `TRUE`. Here we can override that default with: `list(Fire=list(.plotInitialTime=NA))` effectively turning off plotting. Since this is a list of lists, one can override the module defaults for multiple parameters from multiple modules all at once, with say: `list(Fire = list(.plotInitialTime = NA, .plotInterval = 2), caribouModule = list(N = 1000))`.

The params list can contain a list (named `.globals`) of named objects e.g., `.globals = list(climateURL = "https:\\something.com")` entry. Any and every module that has a parameter with that name (in this case `climateURL`) will be overridden with this value as passed.

params can be used to set the seed for a specific event in a module. This is done using the normal params argument, specifying `.seed` as a list where the elements are a numeric for the seed and the name is the event. Since parameters must be specific to a module, this creates a module and event specific seed e.g., `params = list(moduleName = list(.seed = list(init = 123)))` will set the `init` event of module named `moduleName` to 123. The RN stream will be reset to its state prior to the `set.seed` call after the event.

We implement a discrete event simulation in a more modular fashion so it is easier to add modules to the simulation. We use S4 classes and methods, and fast lists to manage the event queue.

`paths` specifies the location of the module source files, the data input files, and the saving output files. If no paths are specified the defaults are as follows:

- `cachePath: getOption("reproducible.cachePath");`
- `inputPath: getOption("spades.inputPath");`
- `modulePath: getOption("spades.modulePath");`
- `outputPath: getOption("spades.outputPath").`

Value

A `simList` simulation object, pre-initialized from values specified in the arguments supplied.

Parsing and Checking Code

The `simInit` function will attempt to find usage of `sim$xxx` or `sim[['xxx']]` on either side of the assignment (`<-`) operator. It will compare these to the module metadata, specifically `inputObjects` for cases where objects or "gotten" from the `simList` and `outputObjects` for cases where objects are assigned to the `simList`.

It will also attempt to find potential, common function name conflicts with things like `scale` and `stack` (both in **base** and **raster**), and `Plot` (in **quickPlot** and some modules).

This code checking is young and may get false positives and false negatives, i.e., miss things. It also takes computational time, which may be undesirable in operational code. To turn off checking

(i.e., if there are too many false positives and negatives), set `options(spades.moduleCodeChecks = FALSE)`.

Caching

Using caching with SpaDES is vital when building re-usable and reproducible content. Please see the vignette dedicated to this topic.

Note

Since the objects in the `simList` are passed-by-reference, it is useful to create a copy of the initialized `simList` object prior to running the simulation (e.g., `mySimOut <- spades(Copy(mySim))`). This ensures you retain access to the original objects, which would otherwise be overwritten/modified during the simulation.

The user can opt to run a simpler `simInit` call without inputs, outputs, and times. These can be added later with the accessor methods (See example). These are not required for initializing the simulation via `simInit`. All of modules, paths, params, and objects are needed for successful initialization.

Author(s)

Alex Chubaty and Eliot McIntire

References

Matloff, N. (2011). *The Art of R Programming* (ch. 7.8.3). San Francisco, CA: No Starch Press, Inc.. Retrieved from <https://nostarch.com/artofr.htm>

See Also

[spades\(\)](#), [defineModule\(\)](#) to get help on metadata elements, [times\(\)](#), [params\(\)](#), [objs\(\)](#), [paths\(\)](#), [modules\(\)](#), [inputs\(\)](#), [outputs\(\)](#)

Examples

```
# Tests take several seconds
if (requireNamespace("SpaDES.tools", quietly = TRUE) &&
    packageVersion("SpaDES.tools") > "3.0.0") {
  opts <- options("spades.moduleCodeChecks" = FALSE, "spades.useRequire" = FALSE)
  if (!interactive()) opts <- append(opts, options("spades.plots" = NA,
                                                  "spades.debug" = FALSE))

  mySim <- simInit(
    times = list(start = 0.0, end = 2.0, timeunit = "year"),
    params = list(
      .globals = list(stackName = "landscape", burnStats = "nPixelsBurned")
    ),
    modules = list("randomLandscapes", "fireSpread", "caribouMovement"),
    paths = list(modulePath = getSampleModules(tempdir()))
  )
  spades(mySim) # shows plotting
```

```

# Change more parameters, removing plotting
mySim <- simInit(
  times = list(start = 0.0, end = 2.0, timeunit = "year"),
  params = list(
    .globals = list(stackName = "landscape", burnStats = "nPixelsBurned"),
    fireSpread = list(.plotInitialTime = NA)
  ),
  modules = list("randomLandscapes", "fireSpread", "caribouMovement"),
  paths = list(modulePath = getSampleModules(tempdir()))
)
outSim <- spades(mySim)

# A little more complicated with inputs and outputs
mapPath <- system.file("maps", package = "quickPlot")
mySim <- simInit(
  times = list(start = 0.0, end = 2.0, timeunit = "year"),
  params = list(
    .globals = list(stackName = "landscape", burnStats = "nPixelsBurned")
  ),
  modules = list("randomLandscapes", "fireSpread", "caribouMovement"),
  paths = list(modulePath = getSampleModules(tempdir()),
    outputPath = tempdir()),
  inputs = data.frame(
    files = dir(file.path(mapPath), full.names = TRUE, pattern = "tif")[1:2],
    functions = "rast",
    package = "terra",
    loadTime = 1,
    stringsAsFactors = FALSE),
  outputs = data.frame(
    expand.grid(objectName = c("caribou", "landscape"),
      saveTime = 1:2,
      stringsAsFactors = FALSE)))

# Use accessors for inputs, outputs
mySim2 <- simInit(
  times = list(start = 0.0, end = 2.0, timeunit = "year"),
  modules = list("randomLandscapes", "fireSpread", "caribouMovement"),
  params = list(
    .globals = list(stackName = "landscape", burnStats = "nPixelsBurned"),
    randomLandscapes = list(nx = 10, ny = 10)
  ),
  paths = list(
    modulePath = getSampleModules(tempdir()),
    outputPath = tempdir()
  )
)

# add by accessor is equivalent
inputs(mySim2) <- data.frame(
  files = dir(file.path(mapPath), full.names = TRUE, pattern = "tif")[1:2],
  functions = "rast",
  package = "terra",

```

```

    loadTime = 1,
    stringsAsFactors = FALSE)
outputs(mySim2) <- data.frame(
  expand.grid(objectName = c("caribou", "landscape"),
    saveTime = 1:2,
    stringsAsFactors = FALSE))
all.equal(mySim, mySim2) # TRUE

# Use accessors for times -- does not work as desired because times are
# adjusted to the input timeunit during simInit
mySim2 <- simInit(
  params = list(
    .globals = list(stackName = "landscape", burnStats = "nPixelsBurned")
  ),
  modules = list("randomLandscapes", "fireSpread", "caribouMovement"),
  paths = list(modulePath = getSampleModules(tempdir()),
    outputPath = tempdir()),
  inputs = data.frame(
    files = dir(file.path(mapPath), full.names = TRUE, pattern = "tif")[1:2],
    functions = "rast",
    package = "terra",
    loadTime = 1,
    stringsAsFactors = FALSE),
  outputs = data.frame(
    expand.grid(objectName = c("caribou", "landscape"),
      saveTime = 1:2,
      eventPriority = c(0,10), # eventPriority 0 may give "initial" conditions
      stringsAsFactors = FALSE))
)

# add times by accessor fails all.equal test because "year" was not
# declared during module loading, so month became the default
times(mySim2) <- list(current = 0, start = 0.0, end = 2.0, timeunit = "year")
all.equal(mySim, mySim2) # fails because time units are all different, so
# several parameters that have time units in
# "months" because they were loaded that way
params(mySim)$fireSpread$.plotInitialTime
params(mySim2)$fireSpread$.plotInitialTime
events(mySim) # load event is at time 1 year
events(mySim2) # load event is at time 1 month, reported in years because of
# update to times above
options(opts)
}

```

simInitAndSpades2 *simInitAndSpades2 is a convenience wrapper for do.call(simInitAndSpades, listOfArgs), i.e., a user can pass a list of all the arguments.*

Description

These functions are convenience wrappers that may allow for more efficient caching. Passes all arguments to `simInit()`, then passes the created `simList` to `spades()`.

Usage

```
simInitAndSpades2(l)

simInitAndSpades(
  times,
  params,
  modules,
  objects,
  paths,
  inputs,
  outputs,
  loadOrder,
  notOlderThan,
  debug = getOption("spades.debug"),
  progress,
  cache,
  .plots,
  .plotInitialTime,
  .saveInitialTime,
  events,
  ...
)
```

Arguments

<code>l</code>	A list of arguments to be passed to <code>simInitAndSpades</code> .
<code>times</code>	A named list of numeric simulation start and end times (e.g., <code>times = list(start = 0.0, end = 10.0, timeunit = "year")</code>), with the final optional element, <code>timeunit</code> , overriding the default time unit used in the simulation which is the "smallest time unit" across all modules. See examples.
<code>params</code>	A list of lists of the form <code>list(moduleName=list(param1=value, param2=value))</code> . See details.
<code>modules</code>	A named list of character strings specifying the names of modules to be loaded for the simulation. Note: the module name should correspond to the R source file from which the module is loaded. Example: a module named "caribou" will be sourced from the file 'caribou.R', located at the specified <code>modulePath(simList)</code> (see below).
<code>objects</code>	(optional) A vector of object names (naming objects that are in the calling environment of the <code>simInit</code> , which is often the <code>.GlobalEnv</code> unless used programmatically). NOTE: this mechanism will fail if object name is in a package dependency), or a named list of data objects to be passed into the <code>simList</code> (more reliable). These objects will be accessible from the <code>simList</code> as a normal list, e.g., <code>mySim\$obj</code> .

paths	An optional named list with up to 4 named elements, modulePath, inputPath, outputPath, and cachePath. See details. NOTE: Experimental feature now allows for multiple modulePaths to be specified in a character vector. The modules will be searched for sequentially in the first modulePath, then if it doesn't find it, in the second etc.
inputs	A data.frame. Can specify from 1 to 6 columns with following column names: objectName (character, required), file (character), fun (character), package (character), interval (numeric), loadTime (numeric). See <code>inputs()</code> and vignette("ii-modules") section about inputs.
outputs	A data.frame. Can specify from 1 to 5 columns with following column names: objectName (character, required), file (character), fun (character), package (character), saveTime (numeric) and eventPriority (numeric). If eventPriority is not set, it defaults to <code>.last()</code> . If eventPriority is set to a low value, e.g., 0, 1, 2 and saveTime is <code>start(sim)</code> , it should give "initial conditions". See <code>outputs()</code> and vignette("ii-modules") section about outputs.
loadOrder	An optional character vector of module names specifying the order in which to load the modules. If not specified, the module load order will be determined automatically.
notOlderThan	A time, as in from <code>Sys.time()</code> . This is passed into the Cache function that wraps <code>.inputObjects</code> . If the module uses the <code>.useCache</code> parameter and it is set to TRUE or <code>".inputObjects"</code> , then the <code>.inputObjects</code> will be cached. Setting <code>notOlderThan = Sys.time()</code> will cause the cached versions of <code>.inputObjects</code> to be refreshed, i.e., rerun.
debug	Optional tools for invoking debugging. Supplying a list will invoke the more powerful logging package. See details. Default is to use the value in <code>getOption("spades.debug")</code> .
progress	Logical (TRUE or FALSE show a graphical progress bar), character ("graphical", "text") or numeric indicating the number of update intervals to show in a graphical progress bar.
cache	Logical. If TRUE, then the spades call will be cached. This means that if the call is made again with the same simList, then spades will return the return value from the previous run of that exact same simList. Default FALSE. See Details. See also the vignette on caching for examples.
.plots	Character. Sets the parameter of this name in all modules. See <code>Plots()</code> for possible values. The parameter is intended to slowly take over from <code>.plotInitialTime</code> as a mechanism to turn on or off plotting. For backwards compatibility, if <code>.plotInitialTime</code> is not set in this spades call, but this <code>.plots</code> is used, two things will happen: setting this without "screen" will turn off all plotting; setting this with "screen" will trigger plotting for any modules that use this parameter but will have no effect on other modules. To get plotting, therefore, it may be necessary to also set <code>.plotInitialTime = start(sim)</code> .
.plotInitialTime	Numeric. Temporarily override the <code>.plotInitialTime</code> parameter for all modules. See Details.
.saveInitialTime	Numeric. Temporarily override the <code>.plotInitialTime</code> parameter for all modules. See Details.

events A character vector or a named list of character vectors. If specified, the simulations will only do the events indicated here. If a named list, the names must correspond to the modules and the character vectors can be specific events within each of the named modules. With the list form, all unspecified modules will run *all* their events, including internal spades modules, e.g., `save`, that get invoked with the `outputs` argument in `simInit`. See example.

... Arguments passed to `simInit()` and `spades()`

Value

Same as `spades()` (a `simList`) or

See Also

`simInit()`, `spades()`

simList-class

The simList class

Description

Contains the minimum components of a SpaDES simulation. Various slot accessor methods (i.e., `get` and `set` functions) are provided (see 'Accessor Methods' below).

Details

Based on code from chapter 7.8.3 of Matloff (2011): "Discrete event simulation". Here, we implement a discrete event simulation in a more modular fashion so it's easier to add simulation components (i.e., "simulation modules"). We use S4 classes and methods, and use `data.table::data.table()` instead of `data.frame()` to implement the event queue (because it is much more efficient).

Slots

`modules` List of character names specifying which modules to load.

`params` Named list of potentially other lists specifying simulation parameters.

`events` The list of scheduled events (i.e., event queue), which can be converted to a sorted `data.table` with `events(sim)`. See 'Event Lists' for more information.

`current` The current event, as a `data.table`. See 'Event Lists' for more information..

`completed` An environment consisting of completed events, with each object named a character representation of the order of events. This was converted from a previous version which was a list. This was changed because the list became slow as number of events increased. See 'Event Lists' for more information. It is kept as an environment of individual events for speed. The `completed` method converts it to a sorted `data.table`.

`depends` A `.simDeps` list of `.moduleDeps()` objects containing module object dependency information.

`simtimes` List of numerical values describing the simulation start and end times; as well as the current simulation time.

`inputs` a `data.frame` or `data.table` of files and metadata

`outputs` a `data.frame` or `data.table` of files and metadata

`paths` Named list of paths. See `?paths`. Partial matching is performed.

`.xData` Environment referencing the objects used in the simulation. Several "shortcuts" to accessing objects referenced by this environment are provided, and can be used on the `simList` object directly instead of specifying the `.xData` slot: `$`, `[[`, `ls`, `ls.str`, `objs`. See examples.

`.envir` Deprecated. Please do not use any more.

Accessor Methods

Several slot (and sub-slot) accessor methods are provided for use, and categorized into separate help pages:

<code>simList-accessors-envir()</code>	Simulation environment.
<code>simList-accessors-events()</code>	Scheduled and completed events.
<code>simList-accessors-inout()</code>	Passing data in to / out of simulations.
<code>simList-accessors-modules()</code>	Modules loaded and used; module dependencies.
<code>simList-accessors-objects()</code>	Accessing objects used in the simulation.
<code>simList-accessors-params()</code>	Global and module-specific parameters.
<code>simList-accessors-paths()</code>	File paths for modules, inputs, and outputs.
<code>simList-accessors-times()</code>	Simulation times.

Event Lists

The main event list is a sorted `data.table` (keyed) on `eventTime`, and `eventPriority`. The completed event list is an ordered list in the exact order that the events were executed. Each event is represented by a `data.table::data.table()` row consisting of:

<code>eventTime</code>	The time the event is to occur.
<code>moduleName</code>	The module from which the event is taken.
<code>eventType</code>	A character string for the programmer-defined event type.
<code>eventPriority</code>	The priority given to the event.

Note

The `simList` class extends the `environment`, by adding several slots that provide information about the metadata for a discrete event simulation. The `environment` slot, if accessed directly is `.xData` and this is where input and output objects from modules are placed. The `simList_()` class is similar, but it extends the `list` class. All other slots are the same. Thus, `simList` is identical to `simList_`, except that the former uses an `environment` for objects and the latter uses a `list`. The class `simList_` is only used internally when saving/loading, because saving/loading a `list` behaves more reliably than saving/loading an `environment`.

Author(s)

Alex Chubaty and Eliot McIntire

References

Matloff, N. (2011). The Art of R Programming (ch. 7.8.3). San Francisco, CA: No Starch Press, Inc.. Retrieved from <https://nostarch.com/artofr.htm>

spades2	<i>spades2 is a convenience wrapper for do.call(spades, listOfArgs), i.e., a user can pass a list of all the arguments.</i>
---------	---

Description

Here, we implement a simulation in a more modular fashion so it's easier to add submodules to the simulation. We use S4 classes and methods, and use `data.table` instead of `data.frame` to implement the event queue (because it is much faster).

Usage

```
spades2(1)

spades(
  sim,
  debug = getOption("spades.debug"),
  progress = NA,
  cache,
  .plotInitialTime = NULL,
  .saveInitialTime = NULL,
  notOlderThan = NULL,
  events = NULL,
  .plots = getOption("spades.plots", NULL),
  ...
)

## S4 method for signature 'simList,ANY,ANY,missing'
spades(
  sim,
  debug = getOption("spades.debug"),
  progress = NA,
  cache,
  .plotInitialTime = NULL,
  .saveInitialTime = NULL,
  notOlderThan = NULL,
  events = NULL,
  .plots = getOption("spades.plots", NULL),
  ...
)
```

```

)

## S4 method for signature 'ANY,ANY,ANY,logical'
spades(
  sim,
  debug = getOption("spades.debug"),
  progress = NA,
  cache,
  .plotInitialTime = NULL,
  .saveInitialTime = NULL,
  notOlderThan = NULL,
  events = NULL,
  .plots = getOption("spades.plots", NULL),
  ...
)

```

Arguments

<code>l</code>	A list of arguments to be passed to <code>spades</code> .
<code>sim</code>	A <code>simList</code> simulation object, generally produced by <code>simInit</code> .
<code>debug</code>	Optional tools for invoking debugging. Supplying a list will invoke the more powerful logging package. See details. Default is to use the value in <code>getOption("spades.debug")</code> .
<code>progress</code>	Logical (TRUE or FALSE show a graphical progress bar), character ("graphical", "text") or numeric indicating the number of update intervals to show in a graphical progress bar.
<code>cache</code>	Logical. If TRUE, then the <code>spades</code> call will be cached. This means that if the call is made again with the same <code>simList</code> , then <code>spades</code> will return the return value from the previous run of that exact same <code>simList</code> . Default FALSE. See Details. See also the vignette on caching for examples.
<code>.plotInitialTime</code>	Numeric. Temporarily override the <code>.plotInitialTime</code> parameter for all modules. See Details.
<code>.saveInitialTime</code>	Numeric. Temporarily override the <code>.plotInitialTime</code> parameter for all modules. See Details.
<code>notOlderThan</code>	Date or time. Passed to <code>reproducible::Cache</code> to update the cache. Default is NULL, meaning don't update the cache. If <code>Sys.time()</code> is provided, then it will force a recache, i.e., remove old value and replace with new value. Ignored if cache is FALSE.
<code>events</code>	A character vector or a named list of character vectors. If specified, the simulations will only do the events indicated here. If a named list, the names must correspond to the modules and the character vectors can be specific events within each of the named modules. With the list form, all unspecified modules will run <i>all</i> their events, including internal <code>spades</code> modules, e.g., <code>save</code> , that get invoked with the <code>outputs</code> argument in <code>simInit</code> . See example.
<code>.plots</code>	Character. Sets the parameter of this name in all modules. See <code>Plots()</code> for possible values. The parameter is intended to slowly take over from <code>.plotInitialTime</code>

as a mechanism to turn on or off plotting. For backwards compatibility, if `.plotInitialTime` is not set in this `spades` call, but this `.plots` is used, two things will happen: setting this without "screen" will turn off all plotting; setting this with "screen" will trigger plotting for any modules that use this parameter but will have no effect on other modules. To get plotting, therefore, it may be necessary to also set `.plotInitialTime = start(sim)`.

... Any. Can be used to make a unique cache identity, such as "replicate = 1". This will be included in the Cache call, so will be unique and thus `spades` will not use a cached copy as long as anything passed in ... is unique, i.e., not cached previously.

Details

This is the workhorse function in the SpaDES package. It runs simulations by implementing the rules outlined in the `simList`.

This function gives simple access to two sets of module parameters: `.plotInitialTime` and `.saveInitialTime`. The primary use of these arguments is to temporarily turn off plotting and saving. "Temporary" means that the `simList` is not changed, so it can be used again with the `simList` values reinstated. To turn off plotting and saving, use `.plotInitialTime = NA` or `.saveInitialTime = NA`. NOTE: if a module did not use `.plotInitialTime` or `.saveInitialTime`, then these arguments will not do anything.

Value

Invisibly returns the modified `simList` object.

Caching with SpaDES

There are numerous ways in which Caching can be used within SpaDES. Please see the vignette <https://spades-core.predictiveecology.org/articles/iii-cache.html> for many examples. Briefly, functions, events, modules, entire `spades` calls or experiment calls (see <https://github.com/PredictiveEcology/SpaDES.experiment>) can be cached and mixtures of all of these will work. For functions, simply wrap the call with `Cache`, moving the original function name into the first argument of `Cache`. For events or modules, set the module parameters, `.useCache`, e.g., `simInit(..., parameters = list(myModule = list(.useCache = "init")))`. This can be set to an event name, which will cache that event, or a logical, which will cache *every* event in that module. Event and module caching makes most sense when the event or module only runs once, such as an initialization or data preparation event/module. Caching an entire simulation is actually just a function call to `simInitAndSpades`, for example. So, simply writing `Cache(simInitAndSpades, modules = ...)` will effectively cache a whole simulation. Finally for experiments, it is just like a function call: `Cache(simInitandExperiment, ...)`. The final way Caching can be done is in `experiment` or `spades`, by setting the `cache` argument.

If `cache` is `TRUE`, this allows for a seamless way to "save" results of a simulation. The user does not have to intentionally do any saving manually. Instead, upon a call to `spades` in which the `simList` is identical, the function will simply return the result that would have come if it had been rerun. Use this with caution, as it will return exactly the result from a previous run, even if there is stochasticity internally. Caching is only based on the input `simList`. See also the vignette on caching for examples.

debug

The most powerful way to use debug is to invoke the logging R package. To invoke this, debug must be a list with up to 3 named elements: console, file, and debug. Each of these list elements must be a list (including empty list() for defaults) with the sub-list elements here:

console	level	The level, see below, of information shown
file	append	Logical. If TRUE, the default, then log entries are appended to file, if it exists
	file	A filename. Defaults to log.txt
	level	The level, see below, of information shown
debug	See possible values below	

level can be a number from 0 to 100 or a character string matching one of the values in logging::loglevels. These are hierarchical levels of information passed to the console. Set a lower number for more information and a higher number for less information. Errors in code will be shown if level is set to "ERROR" or 40 or above; warnings in code will be shown if level is set to "WARN" or 30 or above; normal messages in code will be shown if level is set to "INFO" or 20 or above. For consistency with base R messaging, if default level is used, then normal messaging via message will be shown; this means that suppressMessages will work to suppress messaging only when level is set to "INFO" or 20. Some functions in the SpaDES ecosystem may have information at the lower levels, but currently, there are few to none.

debug is specified as a non-list argument to spades or as list(debug = ...), then it can be a logical, a quoted call, a character vector or a numeric scalar (currently 1 or 2) or a list of any of these to get multiple outputs. This will be run at the start of every event. The following options for debug are available. Each of these can also be in a list to get multiple outputs:

TRUE	current(sim) will be printed at the start of each event
a function name (as character string)	If a function, then it will be run on the simList, e.g., 'current'
moduleName (as character string)	All calls to that module will be entered interactively
eventName (as character string)	All calls that have that event name (in any module) will be entered
c(<moduleName>, <eventName>)	Only the event in that specified module will be entered
Any other R expression expressed as a character string or quoted call	Will be evaluated with access to the simList as sim.
A numeric scalar, currently 1 or 2 (maybe others)	This will print out alternative forms of event information

If not specified in the function call, the package option spades.debug is used.

If options("spades.browserOnError" = TRUE) (experimental still) if there is an error, it will attempt to open a browser in the event where the error occurred. You can edit, and then press c to continue or Q to quit, plus all other normal interactive browser tools. c will trigger a reparse and events will continue as scheduled, starting with the one just edited. There may be some unexpected consequences if the simList objects had already been changed before the error occurred.

Note

The debug option is primarily intended to facilitate building simulation models by the user. Will print additional outputs informing the user of updates to the values of various simList slot components. See <https://github.com/PredictiveEcology/SpaDES/wiki/Debugging> for details.

Author(s)

Alex Chubaty and Eliot McIntire

References

Matloff, N. (2011). The Art of R Programming (ch. 7.8.3). San Francisco, CA: No Starch Press, Inc.. Retrieved from <https://nostarch.com/artofr.htm>

See Also

[SpaDES.core-package\(\)](#), [simInit\(\)](#), and the caching vignette (very important for reproducibility): <https://spades-core.predictiveecology.org/articles/iii-cache.html> which uses `reproducible::Cache()`.

vignettes

Examples

```
if (requireNamespace("SpaDES.tools", quietly = TRUE) &&
    packageVersion("SpaDES.tools") > "3.0.0") {
  # some options are not necessary when not interactive
  opts <- options("spades.moduleCodeChecks" = FALSE, "spades.useRequire" = FALSE)
  if (!interactive()) opts <- append(opts, options("spades.plots" = NA))
  mySim <- simInit(
    times = list(start = 0.0, end = 1.0, timeunit = "year"),
    params = list(
      randomLandscapes = list(nx = 10, ny = 10),
      .globals = list(stackName = "landscape", burnStats = "nPixelsBurned",
        .plots = NA) # plotting off --> not relevant for example
    ),
    modules = list("randomLandscapes", "fireSpread", "caribouMovement"),
    paths = list(modulePath = getSampleModules(tempdir()))
  )
  spades(mySim)

  options(opts) # reset options
}
```

 spadesClasses

Classes defined in SpaDES

Description

These S4 classes are defined within SpaDES. "dot" classes are not exported and are therefore intended for internal use only.

Simulation classes

<code>simList()</code>	The <code>simList</code> class
<code>.moduleDeps()</code>	Descriptor object for specifying SpaDES module dependencies
<code>.simDeps()</code>	Defines all simulation dependencies for all modules within a SpaDES simulation

Author(s)

Eliot McIntire and Alex Chubaty

See Also

`simInit()`

<code>spadesOptions</code>	<code>SpaDES.core options</code>
----------------------------	----------------------------------

Description

These provide top-level, powerful settings for a comprehensive SpaDES workflow. To see defaults, run `spadesOptions()`. See Details below.

Usage

`spadesOptions()`

Details

Below are options that can be set with `options("spades.xxx" = newValue)`, where `xxx` is one of the values below, and `newValue` is a new value to give the option. Sometimes these options can be placed in the user's `.Rprofile` file so they persist between sessions.

The following options are likely of interest to most users

<i>OPTION</i>	<i>DEFAULT</i>
<code>spades.allowInitDuringSimInit</code>	FALS
<code>spades.browserOnError</code>	FALS
<code>reproducible.cachePath</code>	<code>getOption('reproduc</code>
<code>spades.cacheChaining</code>	FALS
<code>spades.debug</code>	TRU
<code>spades.dotInputObjects</code>	TRU
<code>spades.DTthreads</code>	1L
<code>spades.evalPostEvent</code>	NUL

spades.futureEvents		FALSE
spades.logPath		Defaults to a subdirectory (logs/) of
spades.inputPath		Default is a temporary directory (typical
spades.loadReqdPkgs		Default is
spades.lowMemory		FALSE
spades.memoryUseInterval		FALSE
spades.messagingNumCharsModule		21
spades.moduleCodeChecks	list(suppressParamUnused = FALSE, suppressUndefined = TRUE, suppressP	
spades.moduleDocument		TRUE
spades.modulePath		file.path(tempdir(), "
spades.moduleRepo		"PredictiveEcology.
spades.nCompleted		1000
spades.outputPath		file.path(tempdir(), "
spades.plots	The value of this will passed to .plots within every module; it will thus override all r	
spades.recoveryMode		1L
spades.reqdPkgsDontLoad		"box
spades.saveFileExtensions		NUL
spades.scratchPath		file.path(tempdir(), "
spades.sessionInfo		TRUE
spades.switchPkgNamespaces		Defun
spades.testMemoryLeaks		TRUE
spades.tolerance		.Machine\$doub
spades.useragent		"https://github.com/Pred
spades.useBox		FALSE
spades.useRequire		!tolower(Sys.getenv("SPADES_L

Value

named list of the *default* package options.

suppliedElsewhere	<i>Assess whether an object has or will be supplied from elsewhere</i>
-------------------	--

Description

When loading objects into a `simList`, especially during the `simInit` call, and inside the `.inputObjects` functions of modules, it is often useful to know if an object in question will or has been by the user via the `inputs` or `objects` arguments, or by another module's `.inputObjects` while preparing its expected inputs (via `expectsInputs` in metadata), or if it will be supplied by another module during its "init" event. In all these cases, it may not be necessary for a given module to load any default value for its `expectsInputs`. This function can be used as a check to determine whether the module needs to proceed in getting and assigning its default value.

Usage

```
suppliedElsewhere(
  object,
  sim,
  where = c("sim", "user", "initEvent"),
  returnWhere = FALSE
)
```

Arguments

object	Character vector
sim	A simList in which to evaluated whether the object is supplied elsewhere
where	Character vector with one to three of "sim", "user", or "initEvent". Default is all three. Partial matching is used. See details.
returnWhere	Logical, default FALSE, whether the vector of length 3 logical should be returned, or a logical of length one

Details

where indicates which of three places to search, either "sim" i.e., the simList, which would be equivalent to `is.null(sim$objName)`, or "user" which would be supplied by the user in the `simInit` function call via outputs or inputs (equivalent to `!('defaultColor' %in% sim$.userSuppliedObjNames)`) or "initEvent", which would test whether a module that gets loaded **before** the present one **will** create it as part of its outputs (i.e., as indicated by `createsOutputs` in that module's metadata). There is a caveat to this test, however; if that other event also has the object as an `expectsInput`, then it would fail this test, as it *also* needs it as an input. This final one ("initEvent") does not explicitly test that the object will be created in the "init" event, only that it is in the outputs of that module, and that it is a module that is loaded prior to this one.

Value

logical

Examples

```
mySim <- simInit()
suppliedElsewhere("test", mySim) # FALSE

# supplied in the simList
mySim$test <- 1
suppliedElsewhere("test", mySim) # TRUE
test <- 1

# supplied from user at simInit time -- note, this object would eventually get into the simList
# but the user supplied values come after the module's .inputObjects, so
# a basic is.null(sim$test) would return TRUE even though the user supplied test
mySim <- simInit(objects = list("test" = test))
suppliedElsewhere("test", mySim) # TRUE
```

```
# Example with prepInputs
# Put chunks like this in your .inputObjects
if (!suppliedElsewhere("test", mySim))
  sim$test <- Cache(prepareInputs, "raster.tif", "downloadedArchive.zip",
                    destinationPath = dataPath(sim), studyArea = sim$studyArea,
                    rasterToMatch = sim$otherRasterTemplate, overwrite = TRUE)
```

times

Time usage in SpaDES

Description

Functions for the `simtimes` slot of a `simList` object and its elements. To maintain modularity, the behaviour of these functions depends on where they are used. In other words, different modules can have their own `timeunit`. SpaDES converts these to seconds when running a simulation, but shows the user time in the units of the model as shown with `timeunit(sim)`

Usage

```
times(x, ...)

## S4 method for signature 'simList'
times(x)

times(x) <- value

## S4 replacement method for signature 'simList'
times(x) <- value

## S3 method for class 'simList'
time(x, unit, ...)

time(x) <- value

## S4 replacement method for signature 'simList'
time(x) <- value

end(x, ...)

## S3 method for class 'simList'
end(x, unit, ...)

end(x) <- value

## S4 replacement method for signature 'simList'
end(x) <- value
```

```

start(x, ...)

## S3 method for class 'simList'
start(x, unit = NULL, ...)

start(x) <- value

## S4 replacement method for signature 'simList'
start(x) <- value

timeunit(x)

## S4 method for signature 'simList'
timeunit(x)

timeunit(x) <- value

## S4 replacement method for signature 'simList'
timeunit(x) <- value

timeunits(x)

## S4 method for signature 'simList'
timeunits(x)

elapsedTime(x, ...)

## S3 method for class 'simList'
elapsedTime(x, byEvent = TRUE, units = "auto", ...)

```

Arguments

x	A simList
...	Additional parameters.
value	A time, given as a numeric, optionally with a unit attribute, but this will be deduced from the model time units or module time units (if used within a module).
unit	Character. One of the time units used in Spades.
byEvent	Logical. If TRUE, the elapsed time will be by module and event; FALSE will report only by module. Default is TRUE.
units	character string. Units in which the results are desired. Can be abbreviated.

Details

timeunit will extract the current units of the time used in a simulation (i.e., within a spades call). If it is set within a simInit, e.g., times=list(start=0, end=52, timeunit = "week"), it will set the units for that simulation. By default, a simInit call will use the smallest unit contained within

the metadata for the modules being used. If there are parent modules, then the parent module `timeunit` will be used even if one of its children is a smaller `timeunit`. If all modules, including parents, are set to NA, `timeunit` defaults to seconds. If parents are set to NA, then the set of modules defined by that parent module will be given the smallest units of the children.

Currently, available units are "second", "hours", "day", "week", "month", and "year" can be used in the metadata of a module.

The user can also define a new unit. The unit name can be anything, but the function definition must be of the form `dunitName`, e.g., `dyear` or `dfortnight`. The unit name is the part without the `d` and the function name definition includes the `d`. This new function, e.g., `dfortnight <- function(x) lubridate::duration(dday(14))` can be placed anywhere in the search path or in a module.

`timeunits` will extract the current units of the time of all modules used in a simulation. This is different from `timeunit` because it is not necessarily associated with a `spades` call.

In many cases, the "simpler" use of each of these functions may be slower computationally. For instance, it is much faster to use `time(sim, "year")` than `time(sim)`. So as a module developer, it is advantageous to write out the longer one, minimizing the looking up that R must do.

Value

Returns or sets the value of the slot from the `simList` object.

Note

These have default behaviour that is based on the calling frame `timeunit`. When used inside a module, then the time is in the units of the module. If used in an interactive mode, then the time will be in the units of the simulation.

Additional methods are provided to access the current, start, and end times of the simulation:

<code>time</code>	Current simulation time.
<code>start</code>	Simulation start time.
<code>end</code>	Simulation end time.
<code>timeunit</code>	Simulation <code>timeunit</code> .
<code>timeunits</code>	Module <code>timeunits</code> .
<code>times</code>	List of all simulation times (current, start, end, <code>timeunit</code>).

Author(s)

Alex Chubaty and Eliot McIntire

See Also

[SpaDES.core-package](#), specifically the section 1.2.5 on Simulation times; `elapsedTime()`,

Other functions to access elements of a 'simList' object: `.addDepends()`, `checkpointFile()`, `envir()`, `events()`, `globals()`, `inputs()`, `modules()`, `objs()`, `packages()`, `params()`, `paths()`, `progressInterval()`

Examples

```
# Elapsed Time
s1 <- simInit()
s2 <- spades(s1)
elapsedTime(s2)
elapsedTime(s2, units = "mins")
```

updateList	<i>Update elements of a named list with elements of a second named list</i>
------------	---

Description

Defunct. Use `utils::modifyList()` (which can not handle NULL) or `Require::modifyList2()` for case with >2 lists and can handle NULL lists.

Usage

```
updateList(x, y)
```

Arguments

x, y a named list

Value

A named list, with elements sorted by name. The values of matching elements in list y replace the values in list x.

Author(s)

Alex Chubaty

use_gha	<i>Use GitHub actions for automated module checking</i>
---------	---

Description

See corresponding vignette for more information.

Usage

```
use_gha(name, path)
```

Arguments

name module name
path module path

Value

Invoked for its side effect of creating new GitHub Actions workflow files.

writeEventInfo	<i>Write simulation event info to file</i>
----------------	--

Description

Useful for debugging.

Usage

```
writeEventInfo(sim, file = "events.txt", append = FALSE)
```

Arguments

sim	A simList object.
file	Character specifying the file name (default "events.txt").
append	Logical indicating whether to append to the file (default FALSE).

Value

Nothing returned. Invoked for its side effect of writing to file.

Author(s)

Alex Chubaty

writeRNGInfo	<i>Write RNG state info to file</i>
--------------	-------------------------------------

Description

Useful for debugging and ensuring reproducibility.

Usage

```
writeRNGInfo(file = "seed.txt", append = FALSE)
```

Arguments

file	Character specifying the filename (default "seed.txt").
append	Logical indicating whether to append to the file (default FALSE).

Value

Nothing returned. Invoked for its side effect of writing to file.

Author(s)

Alex Chubaty

zipModule

Create a zip archive of a module subdirectory

Description

The most common use of this would be from a "modules" directory, rather than inside a given module.

Usage

```
zipModule(name, path, version, data = FALSE, ...)

## S4 method for signature 'character,character,character'
zipModule(name, path, version, data = FALSE, ...)

## S4 method for signature 'character,missing,character'
zipModule(name, path, version, data = FALSE, ...)

## S4 method for signature 'character,missing,missing'
zipModule(name, path, version, data = FALSE, ...)

## S4 method for signature 'character,character,missing'
zipModule(name, path, version, data = FALSE, ...)
```

Arguments

name	Character string giving the module name.
path	A file path to a directory containing the module subdirectory.
version	The module version.
data	Logical. If TRUE, then the data subdirectory will be included in the zip. Default is FALSE.
...	Additional arguments to <code>zip()</code> : e.g., add "-q" using <code>flags="-q -r9X"</code> (the default flags are "-r9X").

Value

NULL (invisibly). Invoked for its side effect of zipping module files.

Author(s)

Eliot McIntire and Alex Chubaty

zipSimList	<i>Zip a simList and various files</i>
------------	--

Description

zipSimList will save the simList and file-backed Raster* objects, plus, optionally, files identified in outputs(sim) and inputs(sim). This uses Copy under the hood, to not affect the original simList.

These functions have been moved to other packages.

Usage

```
zipSimList(sim, zipfile, ..., outputs = TRUE, inputs = TRUE, cache = FALSE)
```

```
experiment(...)
```

```
experiment2(...)
```

```
POM(...)
```

```
simInitAndExperiment(...)
```

```
loadPackages(...)
```

Arguments

sim	Either a simList or a character string of the name of a simList that can be found in envir. Using a character string will assign that object name to the saved simList, so when it is recovered it will be given that name.
zipfile	A character string indicating the filename for the zip file. Passed to zip.
...	Unused.
outputs	Logical. If TRUE, all files identified in outputs(sim) will be included in the zip.
inputs	Logical. If TRUE, all files identified in inputs(sim) will be included in the zip.
cache	Logical. Not yet implemented. If TRUE, all files in cachePath(sim) will be included in the archive. Defaults to FALSE as this could be large, and may include many out of date elements. See Details.

```
[,simList,character,ANY-method
```

Extract an intact simList but with subset of objects

Description

This is copies the non-object components of a `simList` (e.g., events, etc.) then selects only the objects listed in `i` using `Copy(mget(i, envir(sim)))` and adds them to the returned `simList`.

Usage

```
## S4 method for signature 'simList,character,ANY'  
x[i, j, ..., drop = TRUE]
```

Arguments

<code>x</code>	A <code>simList</code>
<code>i</code>	A character vector of objects to select.
<code>j</code>	Not used.
<code>...</code>	Not used.
<code>drop</code>	Not used.

Value

The `[` method returns a complete `simList` class with all the slots copied from the original, but only the named objects in `i` are returned.

Author(s)

Eliot McIntire

Examples

```
s <- simInit()  
s$a <- 1  
s$b <- 2  
s$d <- 3  
s[c("a", "d")] # a simList with only 2 objects
```

Index

- * **datasets**
 - .quickCheck, 21
 - inSeconds, 77
 - moduleDefaults, 84
- * **functions to access elements of a 'simList' object**
 - checkpointFile, 33
 - envir, 62
 - events, 64
 - globals, 71
 - inputs, 74
 - modules, 90
 - objs, 101
 - packages, 108
 - params, 111
 - paths, 113
 - progressInterval, 122
 - times, 157
- * **module creation helpers**
 - newModule, 92
 - newModuleTests, 95
- .Random.seed, 34
- .addChangedAttr, simList-method, 13
- .addDepends, 34, 63, 66, 71, 75, 91, 103, 109, 112, 116, 123, 159
- .addTagsToOutput, simList-method, 14
- .cacheMessage, simList-method, 15
- .checkCacheRepo, list-method, 16
- .checkpointSave (checkpointFile), 33
- .fileExtensions, 16
- .findSimList, 18
- .first (priority), 121
- .guessPkgFun, 19
- .highest (priority), 121
- .last (priority), 121
- .lowest (priority), 121
- .moduleDeps(), 147, 154
- .normal (priority), 121
- .parseElems, simList-method, 19
- .preDigestByClass, simList-method, 20
- .prepareOutput, simList-method, 20
- .quickCheck, 21
- .rndstr, 21
- .robustDigest, simList-method, 23
- .saveFileExtensions (.fileExtensions), 16
- .simDeps(), 154
- .spadesTimes (inSeconds), 77
- .tagsByClass, simList-method, 24
- .unwrap .moduleDeps (.wrap.simList), 25
- .unwrap .simDeps (.wrap.simList), 25
- .unwrap.simList (.wrap.simList), 25
- .wrap .moduleDeps (.wrap.simList), 25
- .wrap .simDeps (.wrap.simList), 25
- .wrap.simList, 25
- [, simList, character, ANY-method, 164
- all.equal.simList, 26
- anyPlotting, 27
- append_attr, 27
- append_attr, list, list-method (append_attr), 27
- base::all.equal(), 27
- bindrows, 28
- Cache (.robustDigest, simList-method), 23
- Cache(), 23
- cachePath (paths), 113
- cachePath(), 7
- cachePath, simList-method (paths), 113
- cachePath<- (paths), 113
- cachePath<-, simList-method (paths), 113
- checkModule, 29
- checkModule, character, character-method (checkModule), 29
- checkModule, character, missing-method (checkModule), 29
- checkModuleLocal, 29

- checkModuleLocal, character, ANY, ANY-method
(checkModuleLocal), 29
- checkModuleLocal, character, character, character-method
(checkModuleLocal), 29
- checkModulePath, 30
- checkObject, 31
- checkObject(), 10
- checkObject, missing, ANY, ANY-method
(checkObject), 31
- checkObject, simList, ANY, ANY-method
(checkObject), 31
- checkObject, simList, character, missing-method
(checkObject), 31
- checkParams, 32
- checkParams, simList, list-method
(checkParams), 32
- checkpointFile, 33, 63, 66, 71, 75, 91, 103,
109, 112, 116, 123, 159
- checkpointFile(), 8
- checkpointFile, simList-method
(checkpointFile), 33
- checkpointFile<- (checkpointFile), 33
- checkpointFile<-, simList-method
(checkpointFile), 33
- checkpointInterval (checkpointFile), 33
- checkpointInterval(), 8
- checkpointInterval, simList-method
(checkpointFile), 33
- checkpointInterval<- (checkpointFile),
33
- checkpointInterval<-, simList-method
(checkpointFile), 33
- checkpointLoad (checkpointFile), 33
- checksums, 34
- checksums(), 8, 60
- checkTimeunit (inSeconds), 77
- checkTimeunit, character, environment-method
(inSeconds), 77
- checkTimeunit, character, missing-method
(inSeconds), 77
- citation, 35
- citation(), 8
- citation, character-method (citation), 35
- citation, simList-method (citation), 35
- classFilter, 36
- classFilter, character, character, character, environment-method
(classFilter), 36
- classFilter, character, character, character, missing-method
(classFilter), 36
- classFilter, character, character, missing, environment-method
(classFilter), 36
- classFilter, character, character, missing, missing-method
(classFilter), 36
- clearCache, simList-method, 37
- clearCacheEventsOnly, 40
- completed (events), 64
- completed(), 7
- completed, simList, character-method
(events), 64
- completed, simList, missing-method
(events), 64
- completed<- (events), 64
- completed<-, simList-method (events), 64
- conditionalEvents (events), 64
- conditionalEvents(), 134
- conditionalEvents, simList, character-method
(events), 64
- conditionalEvents, simList, missing-method
(events), 64
- convertTimeunit (inSeconds), 77
- convertToPackage, 41
- Copy(), 7
- Copy, simList-method, 43
- copyModule, 44
- copyModule, character, character, character-method
(copyModule), 44
- copyModule, character, character, missing-method
(copyModule), 44
- createDESCRIPTIONandDocs, 45
- createsOutput, 48
- createsOutput(), 8
- createsOutput, ANY, ANY, ANY-method
(createsOutput), 48
- createsOutput, character, character, character-method
(createsOutput), 48
- current (events), 64
- current(), 7
- current, simList, character-method
(events), 64
- current, simList, missing-method
(events), 64
- current<- (events), 64
- current<-, simList-method (events), 64
- data.frame::copy(), 44
- data.table::copy(), 66, 147, 148

- dataPath (paths), 113
- dataPath, simList-method (paths), 113
- dday (dhour), 55
- defineEvent, 49
- defineEvent(), 51
- defineModule, 50
- defineModule(), 8, 49, 88, 142
- defineModule, simList, list-method (defineModule), 50
- defineParameter, 52
- defineParameter(), 8, 51
- depends (modules), 90
- depends(), 7, 90
- depends, simList-method (modules), 90
- depends<- (modules), 90
- depends<-, simList-method (modules), 90
- depsEdgeList, 54
- depsEdgeList(), 9
- depsEdgeList, simList, logical-method (depsEdgeList), 54
- depsEdgeList, simList, missing-method (depsEdgeList), 54
- depsGraph, 55
- depsGraph(), 9
- depsGraph, simList, logical-method (depsGraph), 55
- depsGraph, simList, missing-method (depsGraph), 55
- dhour, 55
- digest::digest(), 23
- dmin (dhour), 55
- dmonth (dhour), 55
- dmonths (dhour), 55
- dmonths, numeric-method (dhour), 55
- dNA (dhour), 55
- dNA, ANY-method (dhour), 55
- doCallSafe, 57
- documentation (inputObjects), 72
- documentation(), 8
- documentation, simList-method (inputObjects), 72
- doEvent.checkpoint (checkpointFile), 33
- downloadData, 57
- downloadData, character, character, logical-method (downloadData), 57
- downloadData, character, character, missing-method (downloadData), 57
- downloadData, character, missing, logical-method (downloadData), 57
- downloadData, character, missing, missing-method (downloadData), 57
- dsecond (dhour), 55
- dweek (dhour), 55
- dweeks (dhour), 55
- dweeks, numeric-method (dhour), 55
- dyear (dhour), 55
- dyears (dhour), 55
- dyears, numeric-method (dhour), 55
- elapsedTime (times), 157
- elapsedTime(), 7, 159
- end (times), 157
- end(), 7
- end<- (times), 157
- end<-, simList-method (times), 157
- envir, 34, 62, 66, 71, 75, 91, 103, 109, 112, 116, 123, 159
- envir(), 7
- envir, simList-method (envir), 62
- envir<- (envir), 62
- envir<-, simList-method (envir), 62
- eventDiagram, 63
- eventDiagram(), 11
- eventDiagram, simList, missing, character-method (eventDiagram), 63
- eventDiagram, simList, missing, missing-method (eventDiagram), 63
- eventDiagram, simList, numeric, character-method (eventDiagram), 63
- events, 34, 63, 64, 71, 75, 91, 103, 109, 112, 116, 123, 159
- events(), 7, 141
- events, simList, character-method (events), 64
- events, simList, missing-method (events), 64
- events<- (events), 64
- events<-, simList-method (events), 64
- expectsInput, 66

- expectsInput(), 8
- expectsInput, ANY, ANY, ANY, ANY-method
(expectsInput), 66
- expectsInput, character, character, character, character-method (expectsInput), 72
(expectsInput), 66
- expectsInput, character, character, character, missing-method (expectsInput), 66
(expectsInput), 66
- experiment (zipSimList), 163
- experiment2 (zipSimList), 163
- extractURL, 67
- extractURL, character, missing-method
(extractURL), 67
- extractURL, character, simList-method
(extractURL), 67

- figurePath (paths), 113
- figurePath, simList-method (paths), 113
- fileName, 68
- findObjects (objs), 101

- G (globals), 71
- G, simList-method (globals), 71
- G<- (globals), 71
- G<-, simList-method (globals), 71
- getMapPath, 69
- getModuleVersion, 69
- getModuleVersion(), 8
- getModuleVersion, character, character-method
(getModuleVersion), 69
- getModuleVersion, character, missing-method
(getModuleVersion), 69
- getSampleModules (getMapPath), 69
- globals, 34, 63, 66, 71, 75, 91, 103, 109, 112,
116, 123, 159
- globals(), 6
- globals, simList-method (globals), 71
- globals<- (globals), 71
- globals<-, simList-method (globals), 71
- gpar(), 117

- igraph::igraph, 85, 86
- inherits(), 37
- initialize, simList-method, 72
- initialize, simList_-method
(initialize, simList-method), 72
- inputArgs (inputs), 74
- inputArgs, simList-method (inputs), 74
- inputArgs<- (inputs), 74
- inputArgs<-, simList-method (inputs), 74
- inputObjects, 72
- inputObjects(), 8
- inputObjects, missing-method
(inputObjects), 72
- inputObjects, simList-method
(inputObjects), 72
- inputPath (paths), 113
- inputPath(), 7
- inputPath, simList-method (paths), 113
- inputPath<- (paths), 113
- inputPath<-, simList-method (paths), 113
- inputs, 34, 63, 66, 71, 74, 91, 103, 109, 112,
116, 123, 159
- inputs(), 6, 17, 90, 140, 142, 146
- inputs, simList-method (inputs), 74
- inputs<- (inputs), 74
- inputs<-, simList-method (inputs), 74
- inSeconds, 77

- keepCache, simList-method
(clearCache, simList-method), 37

- library(), 31
- loadFiles (.fileExtensions), 16
- loadFiles(), 12
- loadFiles, missing, ANY-method
(.fileExtensions), 16
- loadFiles, missing, missing-method
(.fileExtensions), 16
- loadFiles, simList, missing-method
(.fileExtensions), 16
- loadPackages (zipSimList), 163
- loadSimList, 78
- loadSimList(), 79, 133
- logPath (paths), 113
- logPath, simList-method (paths), 113
- ls(), 6
- ls.str(), 6

- makeMemoisable.simList, 80
- maxTimeunit, 80
- maxTimeunit, simList-method
(maxTimeunit), 80
- memoryUse (memoryUseThisSession), 81
- memoryUseThisSession, 81
- minTimeunit, 82
- minTimeunit, list-method (minTimeunit),
82

- minTimeunit, simList-method
 - (minTimeunit), 82
- moduleCodeFiles, 82
- moduleCoverage, 83
- moduleDefaults, 84
- moduleDefaults(), 51
- moduleDiagram, 84
- moduleDiagram(), 11, 87, 99
- moduleDiagram, simList, ANY, ANY-method
 - (moduleDiagram), 84
- moduleDiagram, simList, character, logical-method
 - (moduleDiagram), 84
- moduleGraph, 86
- moduleGraph(), 85
- moduleGraph, simList, logical-method
 - (moduleGraph), 86
- moduleGraph, simList, missing-method
 - (moduleGraph), 86
- moduleInputs (moduleParams), 88
- moduleInputs, character, character-method
 - (moduleParams), 88
- moduleMetadata, 87
- moduleMetadata(), 8, 89, 92
- moduleMetadata, ANY, ANY, ANY-method
 - (moduleMetadata), 87
- moduleMetadata, missing, character, character-method
 - (moduleMetadata), 87
- moduleMetadata, missing, character, missing-method
 - (moduleMetadata), 87
- moduleObjects (objs), 101
- moduleOutputs (moduleParams), 88
- moduleOutputs, character, character-method
 - (moduleParams), 88
- moduleParams, 88
- moduleParams, character, character-method
 - (moduleParams), 88
- modulePath (paths), 113
- modulePath(), 7
- modulePath, simList-method (paths), 113
- modulePath<- (paths), 113
- modulePath<- , simList-method (paths), 113
- modules, 34, 63, 66, 71, 75, 90, 103, 109, 112, 116, 123, 159
- modules(), 7, 90, 142
- modules, simList-method (modules), 90
- modules<- (modules), 90
- modules<- , simList-method (modules), 90
- moduleVersion, 91
- moduleVersion, character, character, missing-method
 - (moduleVersion), 91
- moduleVersion, character, missing, missing-method
 - (moduleVersion), 91
- moduleVersion, character, missing, simList-method
 - (moduleVersion), 91
- NA(), 53
- newModule, 92, 96
- newModule(), 8, 83, 84
- newModule, character, character-method
 - (newModule), 92
- newModule, character, missing-method
 - (newModule), 92
- newModuleCode (newModule), 92
- newModuleCode, character, character-method
 - (newModule), 92
- newModuleDocumentation (newModule), 92
- newModuleDocumentation(), 8
- newModuleDocumentation, character, character-method
 - (newModule), 92
- newModuleDocumentation, character, missing-method
 - (newModule), 92
- newModuleTests, 94, 95
- newModuleTests, character, character, logical, logical-method
 - (newModuleTests), 95
- newObjectsCreated, 96
- newProgressBar, 97
- newProject, 97
- newProject, character, character, logical-method
 - (newProject), 97
- newProject, character, character, missing-method
 - (newProject), 97
- newProjectCode, 98
- newProjectCode, character, character, logical-method
 - (newProjectCode), 98
- noEventWarning, 99
- numeric_version(), 51
- objectDiagram, 99
- objectDiagram(), 11, 84
- objectDiagram, simList-method
 - (objectDiagram), 99
- objects(), 6
- objectsCreated (newObjectsCreated), 96
- objectSynonyms, 100
- objs, 34, 63, 66, 71, 75, 91, 101, 109, 112, 116, 123, 159
- objs(), 7, 142

- objs, simList-method (objs), 101
- objs<- (objs), 101
- objs<-, simList-method (objs), 101
- objSize.simList, 103
- openModules, 104
- openModules(), 8
- openModules, character, character-method (openModules), 104
- openModules, character, missing-method (openModules), 104
- openModules, missing, character-method (openModules), 104
- openModules, missing, missing-method (openModules), 104
- openModules, simList, missing-method (openModules), 104
- options(), 12
- outputArgs (outputs), 105
- outputArgs, simList-method (outputs), 105
- outputArgs<- (outputs), 105
- outputArgs<-, simList-method (outputs), 105
- outputObjectNames (inputObjects), 72
- outputObjectNames, simList-method (inputObjects), 72
- outputObjects (inputObjects), 72
- outputObjects(), 8
- outputObjects, missing-method (inputObjects), 72
- outputObjects, simList-method (inputObjects), 72
- outputPath (paths), 113
- outputPath(), 7
- outputPath, simList-method (paths), 113
- outputPath<- (paths), 113
- outputPath<-, simList-method (paths), 113
- outputs, 105
- outputs(), 6, 107, 140, 142, 146
- outputs, simList-method (outputs), 105
- outputs<- (outputs), 105
- outputs<-, simList-method (outputs), 105

- P (params), 111
- P(), 6, 53
- P<- (params), 111
- packageDescription, 36
- packages, 34, 63, 66, 71, 75, 91, 103, 108, 112, 116, 123, 159
- packages(), 7
- packages, ANY-method (packages), 108
- paramCheckOtherMods, 109
- parameters (params), 111
- parameters, simList-method (params), 111
- params, 34, 63, 66, 71, 75, 91, 103, 109, 111, 116, 123, 159
- params(), 6, 53, 142
- params, simList-method (params), 111
- params<- (params), 111
- params<-, simList-method (params), 111
- paths, 34, 63, 66, 71, 75, 91, 103, 109, 112, 113, 123, 159
- paths(), 7, 142
- paths, simList-method (paths), 113
- paths<- (paths), 113
- paths<-, simList-method (paths), 113
- person(), 51
- Plot, simList-method, 116
- Plots, 118
- Plots(), 27, 107, 146, 150
- POM (zipSimList), 163
- priority, 121
- priority(), 134–136
- progressInterval, 34, 63, 66, 71, 75, 91, 103, 109, 112, 116, 122, 159
- progressInterval(), 8
- progressInterval, simList-method (progressInterval), 122
- progressInterval<- (progressInterval), 122
- progressInterval<-, simList-method (progressInterval), 122
- progressType (progressInterval), 122
- progressType(), 8
- progressType, simList-method (progressInterval), 122
- progressType<- (progressInterval), 122
- progressType<-, simList-method (progressInterval), 122

- quickPlot::.parseElems, 19
- quickPlot::.parseElems(), 19
- quickPlot::clearPlot(), 11
- quickPlot::clickCoordinates(), 11
- quickPlot::clickExtent(), 11
- quickPlot::clickValues(), 11
- quickPlot::dev(), 11
- quickPlot::divergentColors(), 10
- quickPlot::equalExtent(), 9

- quickPlot::getColors(), [10](#)
- quickPlot::layerNames(), [10](#)
- quickPlot::makeLines(), [9](#)
- quickPlot::newPlot(), [11](#)
- quickPlot::numLayers(), [10](#)
- quickPlot::Plot(), [11](#)
- quickPlot::rePlot(), [11](#)
- quickPlot::setColors(), [10](#)

- rasterCreate, [124](#)
- rasterPath(paths), [113](#)
- rasterPath(), [7](#)
- rasterPath, simList-method (paths), [113](#)
- rasterPath<- (paths), [113](#)
- rasterPath<-, simList-method (paths), [113](#)
- rasterToMemory, [124](#)
- rasterToMemory(), [12](#)
- rasterToMemory, ANY-method (rasterToMemory), [124](#)
- rasterToMemory, character-method (rasterToMemory), [124](#)
- rasterToMemory, list-method (rasterToMemory), [124](#)
- rasterToMemory, simList-method (rasterToMemory), [124](#)
- registerOutputs(outputs), [105](#)
- registerOutputs(), [107](#)
- remoteFileSize, [125](#)
- reproducible::.addChangedAttr, [14](#)
- reproducible::.addTagsToOutput(), [14](#)
- reproducible::.cacheMessage, [15](#)
- reproducible::.cacheMessage(), [15](#)
- reproducible::.checkCacheRepo, [16](#)
- reproducible::.checkCacheRepo(), [16](#)
- reproducible::.preDigestByClass, [20](#)
- reproducible::.preDigestByClass(), [20](#)
- reproducible::.prepareOutput, [21](#)
- reproducible::.prepareOutput(), [20](#)
- reproducible::.robustDigest(), [24](#)
- reproducible::.tagsByClass, [24](#)
- reproducible::.tagsByClass(), [24](#)
- reproducible::Cache(), [11](#), [153](#)
- reproducible::checkPath(), [10](#)
- reproducible::Checksums(), [34](#)
- reproducible::clearCache(), [11](#)
- reproducible::Copy(), [44](#)
- reproducible::keepCache(), [11](#)
- reproducible::makeMemoisable(), [80](#)
- reproducible::objSize(), [103](#)

- reproducible::paddedFloatToChar(), [10](#)
- reproducible::prepInputs(), [59](#), [60](#)
- reproducible::preProcess(), [59](#)
- reproducible::showCache(), [11](#)
- reqdPkgs(inputObjects), [72](#)
- reqdPkgs(), [8](#)
- reqdPkgs, missing-method (inputObjects), [72](#)
- reqdPkgs, simList-method (inputObjects), [72](#)

- Require::modifyList2(), [160](#)
- Require::Require(), [51](#)
- restartOrSimInitAndSpades (restartSpades), [127](#)
- restartR, [126](#)
- restartSpades, [127](#)
- rndstr(.rndstr), [21](#)
- rndstr, missing, missing, logical-method (.rndstr), [21](#)
- rndstr, missing, missing, missing-method (.rndstr), [21](#)
- rndstr, missing, numeric, logical-method (.rndstr), [21](#)
- rndstr, missing, numeric, missing-method (.rndstr), [21](#)
- rndstr, numeric, missing, logical-method (.rndstr), [21](#)
- rndstr, numeric, missing, missing-method (.rndstr), [21](#)
- rndstr, numeric, numeric, logical-method (.rndstr), [21](#)
- rndstr, numeric, numeric, missing-method (.rndstr), [21](#)

- savedSimEnv, [129](#)
- saveFiles, [130](#)
- saveFiles(), [12](#)
- saveRDS(), [106](#)
- saveSim(saveSimList), [131](#)
- saveSimList, [131](#)
- saveSimList(), [78](#), [80](#), [105](#), [107](#), [133](#)
- saveState(restartSpades), [127](#)
- scheduleConditionalEvent, [133](#)
- scheduleConditionalEvent(), [6](#), [136](#)
- scheduleEvent, [135](#)
- scheduleEvent(), [6](#), [49](#), [134](#)
- scratchPath(paths), [113](#)
- scratchPath, simList-method (paths), [113](#)
- scratchPath<- (paths), [113](#)

- scratchPath<- , simList-method (paths), 113
- sessInfo (inputObjects), 72
- sessInfo, simList-method (inputObjects), 72
- setPaths(), 45
- setProgressBar (newProgressBar), 97
- show, simList-method, 136
- showCache, simList-method (clearCache, simList-method), 37
- simFile, 137
- simInit, 137
- simInit(), 6, 49, 51, 109, 122, 130, 147, 153, 154
- simInit, ANY, ANY, ANY, ANY, ANY, ANY, ANY, ANY-method (simInit), 137
- simInit, ANY, ANY, ANY, character, ANY, ANY, ANY, ANY, ANY, ANY-method (simInit), 137
- simInit, ANY, ANY, character, ANY, ANY, ANY, ANY, ANY, ANY, ANY-method (simInit), 137
- simInit, list, list, list, list, list, data.frame, data.frame, character-method (simInit), 137
- simInit2 (simInit), 137
- simInitAndExperiment (zipSimList), 163
- simInitAndSpades (simInitAndSpades2), 144
- simInitAndSpades2, 144
- simInitDefaults (simInit), 137
- simList (simList-class), 147
- simList(), 6, 7, 31, 130, 154
- simList-accessors-envir (envir), 62
- simList-accessors-envir(), 148
- simList-accessors-events (events), 64
- simList-accessors-events(), 148
- simList-accessors-inout (inputs), 74
- simList-accessors-inout(), 148
- simList-accessors-metadata (inputObjects), 72
- simList-accessors-modules (modules), 90
- simList-accessors-modules(), 148
- simList-accessors-objects (objs), 101
- simList-accessors-objects(), 148
- simList-accessors-packages (packages), 108
- simList-accessors-params (params), 111
- simList-accessors-params(), 148
- simList-accessors-paths (paths), 113
- simList-accessors-paths(), 148
- simList-accessors-times (times), 157
- simList-accessors-times(), 148
- simList-class, 147
- simList_ (simList-class), 147
- simList_(), 148
- simList_-class (simList-class), 147
- spades (spades2), 149
- spades(), 6, 11, 115, 122, 142, 147
- spades, ANY, ANY, ANY, logical-method (spades2), 149
- spades, simList, ANY, ANY, missing-method (spades2), 149
- SpaDES.core (SpaDES.core-package), 5
- SpaDES.core-package, 5, 63, 66, 71, 75, 91, 102, 112, 116, 159
- SpaDES.tools::adj(), 9
- SpaDES.tools::agentLocation(), 10
- SpaDES.tools::cir(), 9
- SpaDES.tools::crw(), 9
- SpaDES.tools::directionFromEachPoint(), 9
- SpaDES.tools::distanceFromEachPoint(), 9
- SpaDES.tools::heading(), 9
- SpaDES.tools::initiateAgents(), 10
- SpaDES.tools::inRange(), 10
- SpaDES.tools::move(), 9
- SpaDES.tools::neutralLandscapeMap(), 10
- SpaDES.tools::numAgents(), 10
- SpaDES.tools::probInit(), 10
- SpaDES.tools::randomPolygons(), 10
- SpaDES.tools::rasterizeReduced(), 9
- SpaDES.tools::rings(), 9
- SpaDES.tools::specificNumPerPatch(), 9
- SpaDES.tools::spokes(), 9
- SpaDES.tools::spread(), 9
- SpaDES.tools::spread2(), 9
- SpaDES.tools::transitions(), 10
- SpaDES.tools::wrap(), 9
- spades2, 149
- spadesClasses, 153
- spadesOptions, 154
- spadesOptions(), 13
- spadesTimes (inSeconds), 77
- SpatialPoints*(), 9
- start (times), 157
- start(), 7

start<- (times), 157
start<-, simList-method (times), 157
suppliedElsewhere, 155

terra::adjacent(), 9
terra::rast(), 125
terraPath (paths), 113
terraPath, simList-method (paths), 113
terraPath<- (paths), 113
terraPath<-, simList-method (paths), 113
time(), 7
time.simList (times), 157
time<- (times), 157
time<-, simList-method (times), 157
times, 34, 63, 66, 71, 75, 91, 103, 109, 112, 116, 123, 157
times(), 7, 142
times, simList-method (times), 157
times<- (times), 157
times<-, simList-method (times), 157
timeunit (times), 157
timeunit(), 8
timeunit, simList-method (times), 157
timeunit<- (times), 157
timeunit<-, simList-method (times), 157
timeunits (times), 157
timeunits, simList-method (times), 157

unmakeMemoisable.simList_
 (makeMemoisable.simList), 80
unzipSimList (loadSimList), 78
unzipSimList(), 79
updateList, 160
use_gha, 160
utils::citation(), 35
utils::modifyList(), 160
utils::sessionInfo(), 155

writeEventInfo, 161
writeRNGInfo, 161

zip(), 132, 162
zipModule, 162
zipModule(), 8, 61, 62, 70
zipModule, character, character, character-method
 (zipModule), 162
zipModule, character, character, missing-method
 (zipModule), 162
zipModule, character, missing, character-method
 (zipModule), 162
zipModule, character, missing, missing-method
 (zipModule), 162
zipSimList, 78, 163
zipSimList(), 80