

# Package ‘SpoMAG’

May 7, 2026

**Type** Package

**Title** Probability of Sporulation Potential in MAGs

**Version** 0.1.0

**Description** Implements an ensemble machine learning approach to predict the sporulation potential of metagenome-assembled genomes (MAGs) from uncultivated Firmicutes based on the presence/absence of sporulation-associated genes.

**License** Artistic-2.0

**Encoding** UTF-8

**Imports** dplyr, tidyr, tibble, stats

**RoxygenNote** 7.3.2

**Suggests** testthat (>= 3.0.0), caret, kernlab, randomForest, readr

**Config/testthat/edition** 3

**NeedsCompilation** no

**Author** Douglas Terra Machado [aut, cre] (ORCID:  
<<https://orcid.org/0000-0002-6580-7628>>),  
Otávio José Bernardes Brustolini [ctb] (ORCID:  
<<https://orcid.org/0000-0001-8132-9753>>),  
Ellen dos Santos Corrêa [ctb],  
Ana Tereza Ribeiro Vasconcelos [ctb] (ORCID:  
<<https://orcid.org/0000-0002-4632-2086>>)

**Maintainer** Douglas Terra Machado <dougterra@gmail.com>

**Depends** R (>= 3.5.0)

**Repository** CRAN

**Date/Publication** 2025-05-29 18:20:09 UTC

## Contents

build_binary_matrix . . . . .	2
predict_sporulation . . . . .	3
sporulation_gene_name . . . . .	4

<b>Index</b>	<b>5</b>
--------------	----------

---

build\_binary\_matrix     *Build binary presence/absence matrix of sporulation genes*

---

### Description

Transforms the output of `sporulation_gene_name()` into a wide-format matrix indicating the presence (1) or absence (0) of each sporulation-associated gene per genome.

### Usage

```
build_binary_matrix(df)
```

### Arguments

`df`                    A data.frame from `sporulation_gene_name()` with columns `genome_ID` and `spo_gene_name`.

### Value

A wide-format binary matrix with genomes in rows and genes in columns.

### Examples

```
# Load package
library(SpoMAG)

# Load example annotation tables
file_spor <- system.file("extdata", "one_sporulating.csv.gz", package = "SpoMAG")
file_aspo <- system.file("extdata", "one_asporogenic.csv.gz", package = "SpoMAG")

# Read files
df_spor <- readr::read_csv(file_spor, show_col_types = FALSE)
df_aspo <- readr::read_csv(file_aspo, show_col_types = FALSE)

# Step 1: Extract sporulation-related genes
genes_spor <- sporulation_gene_name(df_spor)
genes_aspo <- sporulation_gene_name(df_aspo)

# Step 2: Convert to binary matrix
bin_spor <- build_binary_matrix(genes_spor)
bin_aspo <- build_binary_matrix(genes_aspo)
```

---

predict\_sporulation     *Predict Sporulation Potential*

---

### Description

This function predicts the sporulation potential of MAGs using an ensemble learning model. It uses probabilities from Random Forest and SVM classifiers as inputs to a meta-model.

### Usage

```
predict_sporulation(binary_matrix)
```

### Arguments

`binary_matrix`     A binary matrix (1/0) indicating gene presence/absence for each MAG. Must include a `genome_ID` column.

### Value

A tibble with predicted class and probability of sporulation for each genome.

### Examples

```
# Load package
library(SpoMAG)

# Load example annotation tables
file_spor <- system.file("extdata", "one_sporulating.csv.gz", package = "SpoMAG")
file_aspo <- system.file("extdata", "one_asporogenic.csv.gz", package = "SpoMAG")

# Read files
df_spor <- readr::read_csv(file_spor, show_col_types = FALSE)
df_aspo <- readr::read_csv(file_aspo, show_col_types = FALSE)

# Step 1: Extract sporulation-related genes
genes_spor <- sporulation_gene_name(df_spor)
genes_aspo <- sporulation_gene_name(df_aspo)

# Step 2: Convert to binary matrix
bin_spor <- build_binary_matrix(genes_spor)
bin_aspo <- build_binary_matrix(genes_aspo)

# Step 3: Predict using ensemble model (preloaded in package)

result_spor <- predict_sporulation(bin_spor)
result_aspo <- predict_sporulation(bin_aspo)
```

---

sporulation\_gene\_name *Identify Sporulation-Associated Genes*

---

### Description

This function identifies sporulation-associated genes in a genome annotation data frame. It searches for gene names and KEGG Orthology identifiers related to sporulation steps and returns a data frame with annotated sporulation genes and a consensus name.

### Usage

```
sporulation_gene_name(df)
```

### Arguments

df                    A data frame containing MAG annotation with the columns 'Preferred\_name', 'KEGG\_ko', and 'genome\_ID'.

### Value

A data frame of sporulation-associated genes with standardized names and spo\_process tags.

### Examples

```
# Load package
library(SpoMAG)
# Load example annotation tables
file_spor <- system.file("extdata", "one_sporulating.csv.gz", package = "SpoMAG")
file_aspo <- system.file("extdata", "one_asporogenic.csv.gz", package = "SpoMAG")

# Read files
df_spor <- readr::read_csv(file_spor, show_col_types = FALSE)
df_aspo <- readr::read_csv(file_aspo, show_col_types = FALSE)

# Step 1: Extract sporulation-related genes
genes_spor <- sporulation_gene_name(df_spor)
genes_aspo <- sporulation_gene_name(df_aspo)
```

# Index

`build_binary_matrix`, 2  
`predict_sporulation`, 3  
`sporulation_gene_name`, 4