

Package ‘SportMiner’

May 7, 2026

Type Package

Title Text Mining and Topic Modeling for Sport Science Literature

Version 0.1.0

Description A comprehensive toolkit for mining, analyzing, and visualizing scientific literature in sport science domains. Provides functions for retrieving abstracts from 'Scopus', preprocessing text data, performing advanced topic modeling using Latent Dirichlet Allocation ('LDA'), Structural Topic Models ('STM'), and Correlated Topic Models ('CTM'), and creating publication-ready visualizations including keyword co-occurrence networks and topic trends. For methodological details see Blei et al. (2003) <[doi:10.1162/jmlr.2003.3.4-5.993](https://doi.org/10.1162/jmlr.2003.3.4-5.993)> for 'LDA', Roberts et al. (2014) <[doi:10.1111/ajps.12103](https://doi.org/10.1111/ajps.12103)> for 'STM', and Blei and Lafferty (2007) <[doi:10.1214/07-AOAS114](https://doi.org/10.1214/07-AOAS114)> for 'CTM'.

License MIT + file LICENSE

URL <https://github.com/praveenmaths89/SportMiner>

BugReports <https://github.com/praveenmaths89/SportMiner/issues>

Encoding UTF-8

Depends R (>= 4.0.0)

Imports rscopus, dplyr, tidytext, topicmodels, stm, ggplot2, rlang, SnowballC, scales, textmineR, Matrix, tidyr, ggraph, igraph, widyr, magrittr, slam

Suggests testthat (>= 3.0.0), knitr, rmarkdown, withr

RoxygenNote 7.3.3

VignetteBuilder knitr

NeedsCompilation no

Author Praveen D Chougale [aut, cre],
Usha Ananthakumar [aut]

Maintainer Praveen D Chougale <praveenmaths89@gmail.com>

Repository CRAN

Date/Publication 2026-01-17 11:40:02 UTC

Contents

sm_compare_models	2
sm_create_dtm	3
sm_get_indexed_keywords	4
sm_keyword_network	5
sm_plot_topic_frequency	6
sm_plot_topic_terms	6
sm_plot_topic_trends	7
sm_preprocess_text	8
sm_search_scopus	9
sm_select_optimal_k	10
sm_set_api_key	11
sm_train_lda	12
theme_sportminer	13

Index	14
--------------	-----------

sm_compare_models	<i>Compare Multiple Topic Models</i>
-------------------	--------------------------------------

Description

Trains and compares three topic modeling approaches: LDA (Latent Dirichlet Allocation), STM (Structural Topic Model), and CTM (Correlated Topic Model). Calculates semantic coherence and exclusivity metrics for each model and suggests the optimal model.

Usage

```
sm_compare_models(
  dtm,
  k = 10,
  metadata = NULL,
  prevalence = NULL,
  seed = 1729,
  lda_method = "gibbs",
  verbose = TRUE
)
```

Arguments

dtm	A DocumentTermMatrix object.
k	Number of topics to extract. Default is 10.
metadata	Optional data frame with document-level covariates for STM. Must have the same number of rows as dtm. Default is NULL.
prevalence	Optional formula for STM prevalence specification. Default is NULL.
seed	Random seed for reproducibility. Default is 1729.

lda_method Method for LDA. Options: "gibbs" or "vem". Default is "gibbs".
 verbose Logical indicating whether to print progress messages. Default is TRUE.

Value

A list containing:

models List of fitted models (lda, stm, ctm)
 metrics Data frame comparing coherence and exclusivity
 recommendation Character string naming the optimal model

Examples

```
## Not run:
# Requires document-term matrix from sm_create_dtm()
dtm <- sm_create_dtm(processed_data)
comparison <- sm_compare_models(dtm, k = 10)
print(comparison$metrics)
print(comparison$recommendation)

## End(Not run)
```

sm_create_dtm *Create Document-Term Matrix*

Description

Converts preprocessed word counts into a document-term matrix suitable for topic modeling. Filters rare terms and empty documents.

Usage

```
sm_create_dtm(word_counts, min_term_freq = 3, max_term_freq = 0.5)
```

Arguments

word_counts A data.frame with columns doc_id, stem, and n, typically produced by sm_preprocess_text().
 min_term_freq Minimum number of documents a term must appear in to be retained. Default is 3.
 max_term_freq Maximum proportion of documents a term can appear in. Useful for removing ubiquitous terms. Default is 0.5 (50 percent).

Value

A DocumentTermMatrix object from the tm package.

Examples

```
## Not run:
processed <- sm_preprocess_text(papers)
dtm <- sm_create_dtm(processed)

## End(Not run)
```

sm_get_indexed_keywords

Get Indexed Keywords from Scopus

Description

Retrieves indexed keywords for a single paper using its DOI or EID. This function makes an additional API call per paper, so use judiciously.

Usage

```
sm_get_indexed_keywords(doi = NA, eid = NA, verbose = FALSE)
```

Arguments

doi	Character string containing the paper's DOI.
eid	Character string containing the paper's EID (Scopus identifier).
verbose	Logical indicating whether to print error messages. Default is FALSE.

Value

Character string of indexed keywords separated by " | ", or NA if not available.

Examples

```
## Not run:
# Requires Scopus API key
keywords <- sm_get_indexed_keywords(
  doi = "10.1016/j.jsams.2020.01.001"
)

## End(Not run)
```

sm_keyword_network *Create Keyword Co-occurrence Network*

Description

Generates and visualizes a keyword co-occurrence network from author-provided keywords. Shows which keywords frequently appear together in the same papers.

Usage

```
sm_keyword_network(  
  data,  
  keyword_col = "author_keywords",  
  separator = "; ",  
  min_cooccurrence = 2,  
  top_n = 30,  
  layout = "fr"  
)
```

Arguments

data	Data frame containing papers with keyword information.
keyword_col	Name of the column containing keywords. Default is "author_keywords".
separator	Character string separating keywords within a cell. Default is "; " (Scopus format).
min_cooccurrence	Minimum number of times keywords must co-occur to be included in the network. Default is 2.
top_n	Number of top keywords (by frequency) to include. If NULL, includes all keywords meeting min_cooccurrence. Default is 30.
layout	Network layout algorithm. Options include "fr" (Fruchterman-Reingold), "kk" (Kamada-Kawai), "circle". Default is "fr".

Value

A ggraph/ggplot object displaying the keyword network.

Examples

```
## Not run:  
# Requires API data from sm_search_scopus()  
papers <- sm_search_scopus(query, max_count = 100)  
network_plot <- sm_keyword_network(papers, top_n = 25)  
print(network_plot)  
  
## End(Not run)
```

sm_plot_topic_frequency

Plot Topic Frequency Distribution

Description

Creates a bar chart showing how many documents are assigned to each topic.

Usage

```
sm_plot_topic_frequency(model, dtm, threshold = 0.3)
```

Arguments

model	A fitted topic model (LDA, STM, or CTM).
dtm	The document-term matrix used to train the model.
threshold	Minimum gamma probability for topic assignment. Default is 0.3.

Value

A ggplot object.

Examples

```
## Not run:  
# Requires trained model from sm_train_lda()  
lda_model <- sm_train_lda(dtm, k = 10)  
sm_plot_topic_frequency(lda_model, dtm)  
  
## End(Not run)
```

sm_plot_topic_terms *Plot Topic Term Probabilities*

Description

Creates a bar chart showing the top terms for each topic, based on their beta (topic-word) probabilities.

Usage

```
sm_plot_topic_terms(model, n_terms = 10, topics = NULL)
```

Arguments

model	A fitted topic model (LDA, STM, or CTM).
n_terms	Number of top terms to display per topic. Default is 10.
topics	Vector of topic numbers to display. If NULL, shows all topics. Default is NULL.

Value

A ggplot object.

Examples

```
## Not run:  
# Requires trained model from sm_train_lda()  
lda_model <- sm_train_lda(dtm, k = 10)  
sm_plot_topic_terms(lda_model, n_terms = 15)  
  
## End(Not run)
```

sm_plot_topic_trends *Plot Topic Trends Over Time*

Description

Creates a stacked percentage bar chart showing how topic proportions change over publication years.

Usage

```
sm_plot_topic_trends(  
  model,  
  dtm,  
  metadata,  
  doc_id_col = "doc_id",  
  year_filter = NULL  
)
```

Arguments

model	A fitted topic model (LDA, STM, or CTM).
dtm	The document-term matrix used to train the model.
metadata	Data frame with a 'year' column and document identifiers.
doc_id_col	Name of the document ID column in metadata. Default is "doc_id".
year_filter	Optional vector of years to include. Default is NULL (includes all years).

Value

A ggplot object.

Examples

```
## Not run:  
# Requires trained model and metadata  
papers$doc_id <- paste0("doc_", seq_len(nrow(papers)))  
lda_model <- sm_train_lda(dtm, k = 10)  
sm_plot_topic_trends(lda_model, dtm, metadata = papers)  
  
## End(Not run)
```

sm_preprocess_text *Preprocess Text for Topic Modeling*

Description

Tokenizes, cleans, and stems text data in preparation for topic modeling. Removes stopwords, numbers, and performs stemming using the Porter algorithm.

Usage

```
sm_preprocess_text(  
  data,  
  text_col = "abstract",  
  id_col = NULL,  
  min_word_length = 3,  
  custom_stopwords = NULL  
)
```

Arguments

data	A data.frame containing text data.
text_col	Name of the column containing text to preprocess. Default is "abstract".
id_col	Name of the column containing document IDs. If NULL, a doc_id column will be created. Default is NULL.
min_word_length	Minimum word length to retain. Default is 3.
custom_stopwords	Additional stopwords to remove beyond the standard English stopwords. Default is NULL.

Value

A data.frame with columns: doc_id, stem, and n (word count).

Examples

```
## Not run:  
# Requires API data from sm_search_scopus()  
papers <- sm_search_scopus(query, max_count = 50)  
processed <- sm_preprocess_text(papers)  
  
## End(Not run)
```

sm_search_scopus	<i>Search Scopus Database</i>
------------------	-------------------------------

Description

Retrieves abstracts and metadata from the Scopus database based on a structured query. Handles pagination automatically and provides progress feedback.

Usage

```
sm_search_scopus(  
  query,  
  max_count = 200,  
  batch_size = 100,  
  view = "COMPLETE",  
  verbose = TRUE  
)
```

Arguments

query	Character string containing the Scopus search query. Should follow Scopus query syntax (e.g., 'TITLE-ABS-KEY("machine learning")').
max_count	Maximum number of papers to retrieve. Use Inf to retrieve all available papers. Default is 200.
batch_size	Number of records to retrieve per API call. Maximum is 100. Default is 100.
view	Level of detail in the response. Options are "STANDARD" or "COMPLETE". Default is "COMPLETE".
verbose	Logical indicating whether to print progress messages. Default is TRUE.

Value

A data.frame containing the retrieved papers with columns including title, abstract, author_keywords, year, DOI, and EID.

Examples

```
## Not run:
# Requires Scopus API key
sm_set_api_key()
query <- 'TITLE-ABS-KEY("sport science" AND "machine learning")'
papers <- sm_search_scopus(query, max_count = 50)

## End(Not run)
```

sm_select_optimal_k *Select Optimal Number of Topics*

Description

Tests multiple values of k (number of topics) and calculates topic coherence for each. Returns the optimal k based on maximum coherence score, along with a comparison plot.

Usage

```
sm_select_optimal_k(
  dtm,
  k_range = seq(2, 20, by = 2),
  method = "gibbs",
  seed = 1729,
  iter = 500,
  burnin = 100,
  plot = TRUE
)
```

Arguments

dtm	A DocumentTermMatrix object.
k_range	Vector of k values to test. Default is seq(2, 20, by = 2).
method	Topic modeling method. Options: "gibbs" or "vem". Default is "gibbs".
seed	Random seed for reproducibility. Default is 1729.
iter	Number of Gibbs iterations (if method = "gibbs"). Default is 500.
burnin	Number of burn-in iterations (if method = "gibbs"). Default is 100.
plot	Logical indicating whether to display the coherence plot. Default is TRUE.

Value

A list containing:

optimal_k	The k value with the highest coherence score
results	Data frame with k and coherence for each tested value
plot	A ggplot object showing coherence vs k

Examples

```
## Not run:  
# Requires document-term matrix from sm_create_dtm()  
dtm <- sm_create_dtm(processed_data)  
k_selection <- sm_select_optimal_k(dtm, k_range = c(5, 10, 15, 20))  
print(k_selection$optimal_k)  
  
## End(Not run)
```

sm_set_api_key	<i>Set Scopus API Key</i>
----------------	---------------------------

Description

Configures the Scopus API key for the current R session. The key can be provided directly or set via the SCOPUS_API_KEY environment variable.

Usage

```
sm_set_api_key(api_key = NULL)
```

Arguments

api_key	Character string containing your Scopus API key. If NULL, the function will attempt to read from the SCOPUS_API_KEY environment variable.
---------	---

Value

Invisible NULL. Called for side effects.

Examples

```
## Not run:  
# Requires Scopus API key  
sm_set_api_key("your_api_key_here")  
  
## End(Not run)
```

sm_train_lda

*Train LDA Topic Model***Description**

Fits a Latent Dirichlet Allocation (LDA) model to a document-term matrix.

Usage

```
sm_train_lda(
  dtm,
  k = NULL,
  method = "gibbs",
  seed = 1729,
  iter = 500,
  burnin = 100,
  alpha = NULL,
  beta = 0.1
)
```

Arguments

dtm	A DocumentTermMatrix object.
k	Number of topics. If NULL, will attempt to use sm_select_optimal_k first. Default is NULL.
method	Method for fitting. Options: "gibbs" or "vem". Default is "gibbs".
seed	Random seed for reproducibility. Default is 1729.
iter	Number of Gibbs iterations (if method = "gibbs"). Default is 500.
burnin	Number of burn-in iterations (if method = "gibbs"). Default is 100.
alpha	Hyperparameter for document-topic distributions. Default is 50/k (following Griffiths & Steyvers 2004).
beta	Hyperparameter for topic-word distributions. Default is 0.1.

Value

An LDA_Gibbs or LDA_VEM object from the topicmodels package.

Examples

```
## Not run:
# Requires document-term matrix from sm_create_dtm()
dtm <- sm_create_dtm(processed_data)
lda_model <- sm_train_lda(dtm, k = 10)

## End(Not run)
```

theme_sportminer	<i>SportMiner Custom ggplot2 Theme</i>
------------------	--

Description

A clean, professional, and colorblind-friendly ggplot2 theme designed for academic publications and presentations in sport science.

Usage

```
theme_sportminer(base_size = 11, base_family = "", grid = TRUE)
```

Arguments

base_size	Base font size in points. Default is 11.
base_family	Base font family. Default is "".
grid	Logical indicating whether to display grid lines. Default is TRUE.

Value

A ggplot2 theme object.

Examples

```
library(ggplot2)
ggplot(mtcars, aes(wt, mpg)) +
  geom_point() +
  theme_sportminer()
```

Index

[sm_compare_models](#), 2
[sm_create_dtm](#), 3
[sm_get_indexed_keywords](#), 4
[sm_keyword_network](#), 5
[sm_plot_topic_frequency](#), 6
[sm_plot_topic_terms](#), 6
[sm_plot_topic_trends](#), 7
[sm_preprocess_text](#), 8
[sm_search_scopus](#), 9
[sm_select_optimal_k](#), 10
[sm_set_api_key](#), 11
[sm_train_lda](#), 12

[theme_sportminer](#), 13