

Package ‘TestCor’

May 7, 2026

Title FWER and FDR Controlling Procedures for Multiple Correlation Tests

Version 0.0.2.2

Date 2020-09-18

Maintainer Gannaz Irene <irene.gannaz@insa-lyon.fr>

Description Different multiple testing procedures for correlation tests are implemented. These procedures were shown to theoretically control asymptotically the Family Wise Error Rate (Roux (2018) <<https://tel.archives-ouvertes.fr/tel-01971574v1>>) or the False Discovery Rate (Cai & Liu (2016) <[doi:10.1080/01621459.2014.999157](https://doi.org/10.1080/01621459.2014.999157)>). The package gather four test statistics used in correlation testing, four FWER procedures with either single step or stepdown versions, and four FDR procedures.

Depends R (>= 3.4)

Encoding UTF-8

License GPL (>= 2)

Imports Rcpp, MASS, stats

LinkingTo Rcpp, RcppArmadillo

RoxygenNote 7.1.1

NeedsCompilation yes

Author Gannaz Irene [aut, cre]

Repository CRAN

Date/Publication 2020-10-15 08:50:02 UTC

Contents

TestCor-package	2
ApplyFdrCor	4
ApplyFwerCor	6
ApplyFwerCor_oracle	8
BHBootCor	10
BHCor	11

BonferroniCor	12
BonferroniCor_SD	14
BootRWCOR	16
BootRWCOR_SD	17
covD2nd	19
covDcor	20
covDcorNorm	20
eval_stat	21
LCTboot	22
LCTnorm	23
maxTinfyCor	25
maxTinfyCor_SD	26
SidakCor	28
SidakCor_SD	30
SimuFdr	31
SimuFwer	33
SimuFwer_oracle	34
UncorrectedCor	36
unvectorize	37
vectorize	38
whichCor	38
Index	40

 TestCor-package

FWER and FDR controlling procedures for multiple correlation tests

Description

The package compiles some multiple testing procedures which theoretically control asymptotically the FWER in the framework of correlation testing. Four tests statistics can be considered: the empirical correlation, the Student statistics, the Fisher's z-transform and the usual Gaussian statistics considering random variables $(X_i - \text{mean}(X_i))(X_j - \text{mean}(X_j))$. Four methods are implemented: Bonferroni (1935)'s, Šidák (1967)'s, Romano & Wolf (2005)'s bootstrap and (Drton & Perlman (2007)'s procedure based on the asymptotic distributions of the test statistics, called Max-Tinfy. The package also includes some multiple testing procedures which are related to the control of the FDR : Cai & Liu (2016)'s procedures called LCT-N and LCT-B -which have been proven to control the FDR for correlation tests- and Benjamini & Hochberg (1995)'s -which has no theoretical results in correlation testing.

Details

Consider $\{\mathbf{X}_\ell = (X_{1\ell}, \dots, X_{p\ell}), \ell = 1, \dots, n\}$ a set of n independent and identically distributed R^p -valued random variables. Denote data the array containing $\{\mathbf{X}_\ell, \ell = 1, \dots, n\}$, with observation indexes l in row. The aim is to test simultaneously

$$(H_{0ij}) \text{Cor}(X_i, X_j) = 0 \text{ against } (H_{1ij}) \text{Cor}(X_i, X_j) \neq 0, \quad i, j = 1, \dots, p, \quad i < j.$$

Four tests statistics are implemented: the empirical correlation, the Student statistics, the Fisher's z-transform and the usual test statistics on expectancy considering the product of random variables. They are available in function `eval_stat`. Next, two main types of procedures are available:

Asymptotically FWER controlling procedures: Bonferroni (1935)'s method, Šidák (1967)'s procedure, Romano & Wolf (2005)'s bootstrap procedure and Drton & Perlman (2007)'s procedure. A description of these methods can be found in Chapter 5 of Roux (2018). To apply these procedures, function `ApplyFwerCor` can be used as follows:

`ApplyFwerCor(data, alpha, stat_test, method)`, with `alpha` the desired level of control for FDR and `stat_test`, `method` respectively the kind of test statistic and the FDR controlling method. The function returns the list of indexes $\{(i, j), i < j\}$ for which null hypothesis (H_{0ij}) is rejected.

Asymptotically FDR controlling procedures: Cai & Liu(2016)'s two procedures and Benjamini & Hochberg (1995)'s procedure (with no theoretical proof for the latest). To apply these procedures, use function `ApplyFdrCor` as follows: `ApplyFdrCor(data, alpha, stat_test, method)` with `alpha` the desired level of control for FWER and `stat_test`, `method` respectively the kind of test statistic and the FDR controlling method. The function returns the list of indexes $\{(i, j), i < j\}$ for which null hypothesis (H_{0ij}) is rejected.

Functions `SimuFwer` and `SimuFdr` provide simulations of Gaussian random variables for a given correlation matrix and return estimated FWER, FDR, Power and true discovery rate obtained applying one of the procedure above. Some example of results obtained can be found in Chapter 6 of Roux (2018).

Author(s)

Irene Gannaz

Maintainer: Irene Gannaz <irene.gannaz@insa-lyon.fr>

References

- Benjamini, Y., & Hochberg, Y. (1995). Controlling the false discovery rate: a practical and powerful approach to multiple testing. *Journal of the royal statistical society. Series B (Methodological)*, 289-300, <https://doi.org/10.1111/j.2517-6161.1995.tb02031.x>.
- Bonferroni, C. E. (1935). Il calcolo delle assicurazioni su gruppi di teste. *Studi in onore del professore salvatore ortu carboni*, 13-60.
- Cai, T. T., & Liu, W. (2016). Large-scale multiple testing of correlations. *Journal of the American Statistical Association*, 111(513), 229-240, <https://doi.org/10.1080/01621459.2014.999157>.
- Drton, M., & Perlman, M. D. (2007). Multiple testing and error control in Gaussian graphical model selection. *Statistical Science*, 22(3), 430-449, <https://doi.org/10.1214/088342307000000113>.
- Romano, J. P., & Wolf, M. (2005). Exact and approximate stepdown methods for multiple hypothesis testing. *Journal of the American Statistical Association*, 100(469), 94-108, <https://doi.org/10.1198/016214504000000539>.
- Roux, M. (2018). Graph inference by multiple testing with application to Neuroimaging, Ph.D., Université Grenoble Alpes, France, <https://tel.archives-ouvertes.fr/tel-01971574v1>.
- Šidák, Z. (1967). Rectangular confidence regions for the means of multivariate normal distributions. *Journal of the American Statistical Association*, 62(318), 626-633.

Examples

```

# Parameters for simulations
Nsimu <- 100 # number of Monte-Carlo simulations
seqn <- seq(100,400,100) # sample sizes
p <- 10 # number of random variables considered
rho <- 0.3 # value of non-zero correlations
seed <- 156724

corr_theo <- diag(1,p) # the correlation matrix
corr_theo[1,2:p] <- rho
corr_theo[2:p,1] <- rho

# Parameters for multiple testing procedure
stat_test <- 'empirical' # test statistics for correlation tests
method <- 'BootRW' # FWER controlling procedure
SD <- FALSE # logical determining if stepdown is applied
alpha <- 0.05 # FWER threshold
Nboot <- 100 # number of bootstrap or simulated samples

# Simulations and application of the chosen procedure
res <- matrix(0,nrow=length(seqn),ncol=5)
for(i in 1:length(seqn)){
  temp <- SimuFwer(corr_theo,n=seqn[i],Nsimu=Nsimu,alpha=alpha,stat_test=stat_test,
    method='BootRW',Nboot=Nboot,stepdown=SD,seed=seed)
  res[i,] <- temp
}
rownames(res) <- seqn
colnames(res) <- names(temp)

# Display results
par(mfrow=c(1,2))
plot(seqn,res[, 'fwer'],type='b',ylim=c(0,max(alpha*1.1,max(res[, 'fwer']))),
  main='FWER',ylab='fwer',xlab='number of observations')
plot(seqn,res[, 'sensitivity'],type='b',ylim=c(0,1.1),
  main='Power',ylab='sensitivity',xlab='number of observations')

```

ApplyFdrCor

Applies multiple testing procedures built to control (asymptotically) the FDR for correlation testing.

Description

Applies multiple testing procedures built to control (asymptotically) the FDR for correlation testing. Some have no theoretical proofs for tests on a correlation matrix.

Usage

ApplyFdrCor(

```

data,
alpha = 0.05,
stat_test = "empirical",
method = "LCTnorm",
Nboot = 1000,
vect = FALSE,
arr.ind = FALSE
)

```

Arguments

data	matrix of observations
alpha	level of multiple testing
stat_test	'empirical' $\sqrt{n} * abs(corr)$ 'fisher' $\sqrt{n-3} * 1/2 * \log((1+corr)/(1-corr))$ 'student' $\sqrt{n-2} * abs(corr) / \sqrt{1-corr^2}$ '2nd.order' $\sqrt{n} * mean(Y) / sd(Y)$ with $Y = (X_i - mean(X_i))(X_j - mean(X_j))$
method	choice between 'LCTnorm' and 'LCTboot' developed by Cai & Liu (2016), 'BH', traditional Benjamini-Hochberg's procedure Benjamini & Hochberg (1995)'s and 'BHboot', Benjamini-Hochberg (1995)'s procedure with bootstrap evaluation of p-values
Nboot	number of iterations for bootstrap p-values evaluation
vect	if TRUE returns a vector of TRUE/FALSE values, corresponding to <code>vectorize(cor(data))</code> ; if FALSE, returns an array containing rows and columns of significant correlations
arr.ind	if TRUE, returns the indexes of the significant correlations, with respect to level alpha

Value

Returns either

- logicals indicating if the corresponding correlation is significant, as a vector or a matrix depending on `vect`,
- an array containing indexes $\{(i, j), i < j\}$ for which correlation between variables i and j is significant, if `arr.ind=TRUE`.

References

- Benjamini, Y., & Hochberg, Y. (1995). Controlling the false discovery rate: a practical and powerful approach to multiple testing. *Journal of the royal statistical society. Series B (Methodological)*, 289-300.
- Cai, T. T., & Liu, W. (2016). Large-scale multiple testing of correlations. *Journal of the American Statistical Association*, 111(513), 229-240.
- Roux, M. (2018). Graph inference by multiple testing with application to Neuroimaging, Ph.D., Université Grenoble Alpes, France, <https://tel.archives-ouvertes.fr/tel-01971574v1>.

See Also

ApplyFwerCor
 LCTnorm, LCTboot, BHCOR, BHBootCor

Examples

```
n <- 100
p <- 10
corr_theo <- diag(1,p)
corr_theo[1,3] <- 0.5
corr_theo[3,1] <- 0.5
data <- MASS::mvrnorm(n,rep(0,p),corr_theo)
res <- ApplyFdrCor(data,stat_test='empirical',method='LCTnorm')
# significant correlations, level alpha:
alpha <- 0.05
whichCor(res<alpha)
```

ApplyFwerCor	<i>Applies multiple testing procedures controlling (asymptotically) the FWER for tests on a correlation matrix.</i>
--------------	---

Description

Applies multiple testing procedures controlling (asymptotically) the FWER for tests on a correlation matrix. Methods are described in Chapter 5 of *Roux (2018)*.

Usage

```
ApplyFwerCor(
  data,
  alpha = NULL,
  stat_test = "empirical",
  method = "Sidak",
  Nboot = 1000,
  stepdown = TRUE,
  vect = FALSE,
  logical = stepdown,
  arr.ind = FALSE
)
```

Arguments

data	matrix of observations
alpha	level of multiple testing (used if logical=TRUE)
stat_test	'empirical' $\sqrt{n} * abs(corr)$ 'fisher' $\sqrt{n-3} * 1/2 * \log((1+corr)/(1-corr))$

	'student' $\sqrt{n-2} * \text{abs}(\text{corr}) / \sqrt{1 - \text{corr}^2}$
	'2nd.order' $\sqrt{n} * \text{mean}(Y) / \text{sd}(Y)$ with $Y = (X_i - \text{mean}(X_i))(X_j - \text{mean}(X_j))$
method	choice between 'Bonferroni', 'Sidak', 'BootRW', 'MaxTinfy'
Nboot	number of iterations for Monte-Carlo of bootstrap quantile evaluation
stepdown	logical, if TRUE a stepdown procedure is applied
vect	if TRUE returns a vector of adjusted p-values, corresponding to <code>vectorize(cor(data))</code> ; if FALSE, returns an array containing the adjusted p-values for each entry of the correlation matrix
logical	if TRUE, returns either a vector or a matrix where each element is equal to TRUE if the corresponding null hypothesis is rejected, and to FALSE if it is not rejected if <code>stepdown=TRUE</code> and <code>logical=FALSE</code> , returns a list of successive p-values.
arr.ind	if TRUE, returns the indexes of the significant correlations, with respect to level alpha

Value

Returns either

- the adjusted p-values, as a vector or a matrix, depending on `vect`
- logicals indicating if the corresponding correlation is significant if `logical=TRUE`, as a vector or a matrix depending on `vect`,
- an array containing indexes $\{(i, j), i < j\}$ for which correlation between variables i and j is significant, if `arr.ind=TRUE`.

References

- Bonferroni, C. E. (1935). Il calcolo delle assicurazioni su gruppi di teste. Studi in onore del professore salvatore ortu carboni, 13-60.
- Drton, M., & Perlman, M. D. (2007). Multiple testing and error control in Gaussian graphical model selection. *Statistical Science*, 22(3), 430-449.
- Romano, J. P., & Wolf, M. (2005). Exact and approximate stepdown methods for multiple hypothesis testing. *Journal of the American Statistical Association*, 100(469), 94-108.
- Roux, M. (2018). Graph inference by multiple testing with application to Neuroimaging, Ph.D., Université Grenoble Alpes, France, <https://tel.archives-ouvertes.fr/tel-01971574v1>.
- Šidák, Z. (1967). Rectangular confidence regions for the means of multivariate normal distributions. *Journal of the American Statistical Association*, 62(318), 626-633.

See Also

ApplyFwerCor_SD, ApplyFdrCor
 BonferroniCor, SidakCor, BootRWCOR, maxTinfyCor
 BonferroniCor_SD, SidakCor_SD, BootRWCOR_SD, maxTinfyCor_SD

Examples

```
n <- 100
p <- 10
corr_theo <- diag(1,p)
corr_theo[1,3] <- 0.5
corr_theo[3,1] <- 0.5
data <- MASS::mvrnorm(n,rep(0,p),corr_theo)
# adjusted p-values
(res <- ApplyFwerCor(data,stat_test='empirical',method='Bonferroni',stepdown=FALSE))
# significant correlations, level alpha:
alpha <- 0.05
whichCor(res<alpha)
```

ApplyFwerCor_oracle *Applies an oracle version of MaxTinfy procedure described in Drton & Perlman (2007) for correlation testing.*

Description

Applies oracle MaxTinfy procedure described in Drton & Perlman (2007) which controls asymptotically the FWER for tests on a correlation matrix. It needs the true correlation matrix.

Usage

```
ApplyFwerCor_oracle(
  data,
  corr_theo,
  alpha = c(),
  stat_test = "empirical",
  method = "MaxTinfy",
  Nboot = 1000,
  stepdown = TRUE,
  vect = FALSE,
  logical = stepdown,
  arr.ind = FALSE
)
```

Arguments

data	matrix of observations
corr_theo	true matrix of correlations
alpha	level of multiple testing (used if logical=TRUE)
stat_test	'empirical' $\sqrt{n} * \text{abs}(corr)$ 'fisher' $\sqrt{n-3} * 1/2 * \log((1+corr)/(1-corr))$ 'student' $\sqrt{n-2} * \text{abs}(corr) / \sqrt{1-corr^2}$ '2nd.order' $\sqrt{n} * \text{mean}(Y) / \text{sd}(Y)$ with $Y = (X_i - \text{mean}(X_i))(X_j - \text{mean}(X_j))$

method	only 'MaxTinfy' implemented
Nboot	number of iterations for Monte-Carlo of bootstrap quantile evaluation
stepdown	logical, if TRUE a stepdown procedure is applied
vect	if TRUE returns a vector of adjusted p-values, corresponding to <code>vectorize(cor(data))</code> ; if FALSE, returns an array containing the adjusted p-values for each entry of the correlation matrix
logical	if TRUE, returns either a vector or a matrix where each element is equal to TRUE if the corresponding null hypothesis is rejected, and to FALSE if it is not rejected if <code>stepdown=TRUE</code> and <code>logical=FALSE</code> , returns a list of successive p-values.
arr.ind	if TRUE, returns the indexes of the significant correlations, with respect to level alpha

Value

Returns either

- the adjusted p-values, as a vector or a matrix, depending on `vect` (unavailable with `stepdown`)
- logicals indicating if the corresponding correlation is significant if `logical=TRUE`, as a vector or a matrix depending on `vect`,
- an array containing indexes $\{(i, j), i < j\}$ for which correlation between variables i and j is significant, if `arr.ind=TRUE`.

Oracle estimation of the quantile is used, based on the true correlation matrix

References

Drton, M., & Perlman, M. D. (2007). Multiple testing and error control in Gaussian graphical model selection. *Statistical Science*, 22(3), 430-449.

Roux, M. (2018). Graph inference by multiple testing with application to Neuroimaging, Ph.D., Université Grenoble Alpes, France, <https://tel.archives-ouvertes.fr/tel-01971574v1>.

See Also

ApplyFwerCor

maxTinfyCor, maxTinfyCor_SD

Examples

```
n <- 100
p <- 10
corr_theo <- diag(1,p)
corr_theo[1,3] <- 0.5
corr_theo[3,1] <- 0.5
data <- MASS::mvrnorm(n,rep(0,p),corr_theo)
# adjusted p-values:
(res <- ApplyFwerCor_oracle(data,corr_theo,stat_test='empirical',Nboot=1000,stepdown=FALSE))
# significant correlations, level alpha:
```

```
alpha <- 0.05
whichCor(res<alpha)
```

BHBootCor	<i>Benjamini & Hochberg (1995)'s procedure for correlation testing with bootstrap evaluation of p-values.</i>
-----------	---

Description

Benjamini & Hochberg (1995)'s procedure on the correlation matrix entries with bootstrap evaluation of p-values (no theoretical proof of control).

Usage

```
BHBootCor(
  data,
  alpha = 0.05,
  stat_test = "2nd.order",
  Nboot = 100,
  vect = FALSE,
  arr.ind = FALSE
)
```

Arguments

data	matrix of observations
alpha	level of multiple testing
stat_test	'empirical' $\sqrt{n} * \text{abs}(\text{corr})$ 'fisher' $\sqrt{n-3} * 1/2 * \log((1 + \text{corr})/(1 - \text{corr}))$ 'student' $\sqrt{n-2} * \text{abs}(\text{corr})/\sqrt{(1 - \text{corr}^2)}$ '2nd.order' $\sqrt{n} * \text{mean}(Y)/\text{sd}(Y)$ with $Y = (X_i - \text{mean}(X_i))(X_j - \text{mean}(X_j))$
Nboot	number of iterations for bootstrap quantile evaluation
vect	if TRUE returns a vector of TRUE/FALSE values, corresponding to <code>vectorize(cor(data))</code> ; if FALSE, returns an array containing TRUE/FALSE values for each entry of the correlation matrix
arr.ind	if TRUE, returns the indexes of the significant correlations, with respect to level alpha

Value

Returns

- a vector or a matrix of logicals, equal to TRUE if the corresponding element of the statistic vector is rejected, if `arr.ind=FALSE`,
- an array containing indexes $\{(i, j), i < j\}$ for which correlation between variables i and j is significant, if `arr.ind=TRUE`.

References

Benjamini, Y., & Hochberg, Y. (1995). Controlling the false discovery rate: a practical and powerful approach to multiple testing. *Journal of the royal statistical society. Series B (Methodological)*, 289-300.

See Also

ApplyFdrCor, BHCOR

Examples

```
n <- 100
p <- 10
corr_theo <- diag(1,p)
corr_theo[1,3] <- 0.5
corr_theo[3,1] <- 0.5
data <- MASS::mvrnorm(n,rep(0,p),corr_theo)
alpha <- 0.05
# significant correlations:
BHBootCor(data,alpha,stat_test='empirical',arr.ind=TRUE)
```

BHCOR

Benjamini & Hochberg (1995)'s procedure for correlation testing.

Description

Benjamini & Hochberg (1995)'s procedure on the correlation matrix entries (no theoretical proof of control).

Usage

```
BHCOR(
  data,
  alpha = 0.05,
  stat_test = "2nd.order",
  vect = FALSE,
  arr.ind = FALSE
)
```

Arguments

data	matrix of observations
alpha	level of multiple testing
stat_test	'empirical' $\sqrt{n} * abs(corr)$ 'fisher' $\sqrt{n-3} * 1/2 * \log((1+corr)/(1-corr))$ 'student' $\sqrt{n-2} * abs(corr) / \sqrt{1-corr^2}$ '2nd.order' $\sqrt{n} * mean(Y) / sd(Y)$ with $Y = (X_i - mean(X_i))(X_j - mean(X_j))$

vect	if TRUE returns a vector of TRUE/FALSE values, corresponding to vectorize(cor(data)) if FALSE, returns an array containing TRUE/FALSE values for each entry of the correlation matrix
arr.ind	if TRUE, returns the indexes of the significant correlations, with respect to level alpha

Value

Returns

- logicals, equal to TRUE if the corresponding element of the statistic vector is rejected, as a vector or a matrix depending of the value of vect,
- an array containing indexes $\{(i, j), i < j\}$ for which correlation between variables i and j is significant, if arr.ind=TRUE.

References

Benjamini, Y., & Hochberg, Y. (1995). Controlling the false discovery rate: a practical and powerful approach to multiple testing. *Journal of the royal statistical society. Series B (Methodological)*, 289-300.

See Also

ApplyFdrCor, BHBootCor

Examples

```
n <- 100
p <- 10
corr_theo <- diag(1,p)
corr_theo[1,3] <- 0.5
corr_theo[3,1] <- 0.5
data <- MASS::mvrnorm(n,rep(0,p),corr_theo)
alpha <- 0.05
# significant correlations:
BHCor(data,alpha,stat_test='empirical',arr.ind=TRUE)
```

BonferroniCor

Bonferroni multiple testing procedure for correlations.

Description

Bonferroni multiple testing procedure for correlations.

Usage

```

BonferroniCor(
  data,
  alpha = 0.05,
  stat_test = "empirical",
  vect = FALSE,
  logical = FALSE,
  arr.ind = FALSE
)

```

Arguments

data	matrix of observations
alpha	level of multiple testing (used if logical=TRUE)
stat_test	'empirical' $\sqrt{n} * \text{abs}(\text{corr})$ 'fisher' $\sqrt{n-3} * 1/2 * \log((1 + \text{corr})/(1 - \text{corr}))$ 'student' $\sqrt{n-2} * \text{abs}(\text{corr})/\sqrt{1 - \text{corr}^2}$ '2nd.order' $\sqrt{n} * \text{mean}(Y)/\text{sd}(Y)$ with $Y = (X_i - \text{mean}(X_i))(X_j - \text{mean}(X_j))$
vect	if TRUE returns a vector of adjusted p-values, corresponding to <code>vectorize(cor(data))</code> ; if FALSE, returns an array containing the adjusted p-values for each entry of the correlation matrix
logical	if TRUE, returns either a vector or a matrix where each element is equal to TRUE if the corresponding null hypothesis is rejected, and to FALSE if it is not rejected
arr.ind	if TRUE, returns the indexes of the significant correlations, with respect to level alpha

Value

Returns

- the adjusted p-values, as a vector or a matrix depending of the value of `vect`,
- an array containing indexes $\{(i, j), i < j\}$ for which correlation between variables i and j is significant, if `arr.ind=TRUE`.

References

Bonferroni, C. E. (1935). Il calcolo delle assicurazioni su gruppi di teste. Studi in onore del professore salvatore ortu carboni, 13-60.

Roux, M. (2018). Graph inference by multiple testing with application to Neuroimaging, Ph.D., Université Grenoble Alpes, France, <https://tel.archives-ouvertes.fr/tel-01971574v1>.

See Also

ApplyFwerCor, BonferroniCor_SD

Examples

```

n <- 100
p <- 10
corr_theo <- diag(1,p)
corr_theo[1,3] <- 0.5
corr_theo[3,1] <- 0.5
corr_theo <- diag(1,p)
data <- MASS::mvrnorm(n,rep(0,p),corr_theo)
# adjusted p-values
res <- BonferroniCor(data,stat_test='empirical')
round(res,2)
# significant correlations with level alpha:
alpha <- 0.05
whichCor(res<alpha)
# directly
BonferroniCor(data,alpha,stat_test='empirical',arr.ind=TRUE)

```

BonferroniCor_SD	<i>Bonferroni multiple testing method for correlations with stepdown procedure.</i>
------------------	---

Description

Bonferroni multiple testing method for correlations with stepdown procedure.

Usage

```

BonferroniCor_SD(
  data,
  alpha = 0.05,
  stat_test = "empirical",
  vect = FALSE,
  logical = TRUE,
  arr.ind = FALSE
)

```

Arguments

data	matrix of observations
alpha	level of multiple testing
stat_test	4 test statistics are available: 'empirical' $\sqrt{n} * \text{abs}(corr)$ 'fisher' $\sqrt{n-3} * 1/2 * \log((1+corr)/(1-corr))$ 'student' $\sqrt{n-2} * \text{abs}(corr) / \sqrt{(1-corr^2)}$ '2nd.order' $\sqrt{n} * \text{mean}(Y) / \text{sd}(Y)$ with $Y = (X_i - \text{mean}(X_i))(X_j - \text{mean}(X_j))$

vect	if TRUE returns a vector of TRUE/FALSE values, corresponding to <code>vectorize(cor(data))</code> ; if FALSE, returns an array containing TRUE/FALSE values for each entry of the correlation matrix
logical	if TRUE, returns either a vector or a matrix where each element is equal to TRUE if the corresponding null hypothesis is rejected, and to FALSE if it is not rejected if FALSE, returns a list of successive p-values : element <code>[[i+1]]</code> of the list giving the p-values evaluated on the non-rejected hypothesis at step <code>[[i]]</code> ; p-values are either as a vector or a list depending on <code>vect</code>
arr.ind	if TRUE, returns the indexes of the significant correlations, with respect to level alpha

Value

Returns

- logicals, equal to TRUE if the corresponding element of the statistic vector is rejected, as a vector or a matrix depending of the value of `vect`,
- an array containing indexes $\{(i, j), i < j\}$ for which correlation between variables i and j is significant, if `arr.ind=TRUE`.

References

Bonferroni, C. E. (1935). Il calcolo delle assicurazioni su gruppi di teste. Studi in onore del professore salvatore ortu carboni, 13-60.

Roux, M. (2018). Graph inference by multiple testing with application to Neuroimaging, Ph.D., Université Grenoble Alpes, France, <https://tel.archives-ouvertes.fr/tel-01971574v1>.

See Also

`ApplyFwerCor`, `BonferroniCor`

Examples

```
n <- 100
p <- 10
corr_theo <- diag(1,p)
corr_theo[1,3] <- 0.5
corr_theo[3,1] <- 0.5
data <- MASS::mvrnorm(n,rep(0,p),corr_theo)
alpha <- 0.05
# significant correlations:
BonferroniCor_SD(data,alpha,stat_test='empirical', arr.ind=TRUE)
# successive p-values
res <- BonferroniCor_SD(data,stat_test='empirical', logical=FALSE)
lapply(res,FUN=function(x){round(x,2)})
# successive rejections
lapply(res,FUN=function(x){whichCor(x<alpha)})
```

BootRWCOR	<i>Bootstrap multiple testing method of Romano & Wolf (2005) for correlations.</i>
-----------	--

Description

Multiple testing method based on the evaluation of quantile by bootstrap in the initial dataset (Romano & Wolf (2005)).

Usage

```
BootRWCOR(
  data,
  alpha = 0.05,
  stat_test = "empirical",
  Nboot = 1000,
  vect = FALSE,
  logical = FALSE,
  arr.ind = FALSE
)
```

Arguments

data	matrix of observations
alpha	level of multiple testing (used if logical=TRUE)
stat_test	'empirical' $\sqrt{n} * abs(corr)$ 'fisher' $\sqrt{n-3} * 1/2 * \log((1+corr)/(1-corr))$ 'student' $\sqrt{n-2} * abs(corr) / \sqrt{1-corr^2}$ '2nd.order' $\sqrt{n} * mean(Y) / sd(Y)$ with $Y = (X_i - mean(X_i))(X_j - mean(X_j))$
Nboot	number of iterations for Monte-Carlo quantile evaluation
vect	if TRUE returns a vector of adjusted p-values, corresponding to <code>vectorize(cor(data))</code> ; if FALSE, returns an array containing the adjusted p-values for each entry of the correlation matrix
logical	if TRUE, returns either a vector or a matrix where each element is equal to TRUE if the corresponding null hypothesis is rejected, and to FALSE if it is not rejected
arr.ind	if TRUE, returns the indexes of the significant correlations, with respect to level alpha

Value

Returns

- the adjusted p-values, as a vector or a matrix depending of the value of `vect`,
- an array containing indexes $\{(i, j), i < j\}$ for which correlation between variables i and j is significant, if `arr.ind=TRUE`.

References

- Romano, J. P., & Wolf, M. (2005). Exact and approximate stepdown methods for multiple hypothesis testing. *Journal of the American Statistical Association*, 100(469), 94-108.
- Roux, M. (2018). Graph inference by multiple testing with application to Neuroimaging, Ph.D., Université Grenoble Alpes, France, <https://tel.archives-ouvertes.fr/tel-01971574v1>.

See Also

ApplyFwerCor, BootRWCOR_SD

Examples

```
n <- 100
p <- 10
corr_theo <- diag(1,p)
corr_theo[1,3] <- 0.5
corr_theo[3,1] <- 0.5
data <- MASS::mvrnorm(n,rep(0,p),corr_theo)
# adjusted p-values
res <- BootRWCOR(data,stat_test='empirical',Nboot=1000)
round(res,2)
# significant correlations with level alpha:
alpha <- 0.05
whichCor(res<alpha)
# directly
BootRWCOR(data,alpha,stat_test='empirical',Nboot=1000,arr.ind=TRUE)
```

BootRWCOR_SD

Bootstrap multiple testing method of Romano & Wolf (2005) for correlations, with stepdown procedure.

Description

Multiple testing method based on the evaluation of quantile by bootstrap in the initial dataset (Romano & Wolf (2005)), with stepdown procedure.

Usage

```
BootRWCOR_SD(
  data,
  alpha = 0.05,
  stat_test = "empirical",
  Nboot = 1000,
  vect = FALSE,
  logical = TRUE,
  arr.ind = FALSE
)
```

Arguments

<code>data</code>	matrix of observations
<code>alpha</code>	level of multiple testing
<code>stat_test</code>	4 test statistics are available: 'empirical' $\sqrt{n} * \text{abs}(\text{corr})$ 'fisher' $\sqrt{n-3} * 1/2 * \log((1 + \text{corr})/(1 - \text{corr}))$ 'student' $\sqrt{n-2} * \text{abs}(\text{corr})/\sqrt{(1 - \text{corr}^2)}$ '2nd.order' $\sqrt{n} * \text{mean}(Y)/\text{sd}(Y)$ with $Y = (X_i - \text{mean}(X_i))(X_j - \text{mean}(X_j))$
<code>Nboot</code>	number of iterations for Bootstrap quantile evaluation
<code>vect</code>	if TRUE returns a vector of TRUE/FALSE values, corresponding to <code>vectorize(cor(data))</code> ; if FALSE, returns an array containing TRUE/FALSE values for each entry of the correlation matrix
<code>logical</code>	if TRUE, returns either a vector or a matrix where each element is equal to TRUE if the corresponding null hypothesis is rejected, and to FALSE if it is not rejected if FALSE, returns a list of successive p-values : element <code>[[i+1]]</code> of the list giving the p-values evaluated on the non-rejected hypothesis at step <code>[[i]]</code> ; p-values are either as a vector or a list depending on <code>vect</code>
<code>arr.ind</code>	if TRUE, returns the indexes of the significant correlations, with respect to level alpha

Value

Returns

- logicals, equal to TRUE if the corresponding element of the statistic vector is rejected, as a vector or a matrix depending of the value of `vect`,
- an array containing indexes $\{(i, j), i < j\}$ for which correlation between variables i and j is significant, if `arr.ind=TRUE`.

References

Romano, J. P., & Wolf, M. (2005). Exact and approximate stepdown methods for multiple hypothesis testing. *Journal of the American Statistical Association*, 100(469), 94-108.

Roux, M. (2018). Graph inference by multiple testing with application to Neuroimaging, Ph.D., Université Grenoble Alpes, France, <https://tel.archives-ouvertes.fr/tel-01971574v1>.

See Also

`ApplyFwerCor`, `BootRWCOR`

Examples

```
n <- 100
p <- 10
corr_theo <- diag(1,p)
corr_theo[1,3] <- 0.5
```

```

corr_theo[3,1] <- 0.5
data <- MASS::mvrnorm(n,rep(0,p),corr_theo)
alpha <- 0.05
# significant correlations:
BootRWCOR_SD(data,alpha,stat_test='empirical', arr.ind=TRUE)
# successive p-values
res <- BootRWCOR_SD(data,stat_test='empirical', logical=FALSE)
lapply(res,FUN=function(x){round(x,2)})
# successive rejections
lapply(res,FUN=function(x){whichCor(x<alpha)})

```

covD2nd

Returns the theoretical covariance of empirical correlations.

Description

Returns the theoretical covariance of empirical correlations.

Usage

```
covD2nd(r)
```

Arguments

r a correlation matrix

Value

Returns the theoretical covariance of 2nd order statistics, $\sqrt{n} * \text{mean}(Y) / \text{sd}(Y)$ with $Y = (X_i - \text{mean}(X_i))(X_j - \text{mean}(X_j))$.

See Also

covDcor

Examples

```

p <- 10
corr_theo <- diag(1,p)
corr_theo[2:p,] <- 0.3
corr_theo[,2:p] <- 0.3
covD2nd(corr_theo)

```

covDcor	<i>Returns the theoretical covariance of empirical correlations.</i>
---------	--

Description

Returns the theoretical covariance of empirical correlations.

Usage

```
covDcor(r)
```

Arguments

`r` a correlation matrix

Value

Returns the theoretical covariance of empirical correlations.

References

Aitkin, M. A. (1969). Some tests for correlation matrices. *Biometrika*, 443-446.

See Also

`covDcorNorm`

Examples

```
p <- 10
corr_theo <- diag(1,p)
corr_theo[2:p,] <- 0.3
corr_theo[,2:p] <- 0.3
covDcor(corr_theo)
```

covDcorNorm	<i>Returns the theoretical covariance of test statistics for correlation testing.</i>
-------------	---

Description

Returns the theoretical covariance of test statistics for correlation testing.

Usage

```
covDcorNorm(cor_mat, stat_test = "empirical")
```

Arguments

cor_mat A correlation matrix
stat_test **'empirical'** $\sqrt{n} * abs(corr)$
 'fisher' $\sqrt{n-3} * 1/2 * \log((1+corr)/(1-corr))$
 'student' $\sqrt{n-2} * abs(corr) / \sqrt{1-corr^2}$
 '2nd.order' $\sqrt{n} * mean(Y) / sd(Y)$ with $Y = (X_i - mean(X_i))(X_j - mean(X_j))$

Value

Returns the theoretical covariance of the test statistics.

See Also

covDcor, covD2nd, eval_stat

Examples

```
p <- 10
corr_theo <- diag(1,p)
corr_theo[2:p,] <- 0.3
corr_theo[,2:p] <- 0.3
covDcorNorm(corr_theo, stat_test='student')
```

eval_stat

Evaluates the test statistics for tests on correlation matrix entries.

Description

Evaluates the test statistics for tests on correlation matrix entries.

Usage

```
eval_stat(data, type = "empirical")
```

Arguments

data matrix of observations
type **'empirical'** $\sqrt{n} * abs(corr)$
 'fisher' $\sqrt{n-3} * 1/2 * \log((1+corr)/(1-corr))$
 'student' $\sqrt{n-2} * abs(corr) / \sqrt{1-corr^2}$
 '2nd.order' $\sqrt{n} * mean(Y) / sd(Y)$ with $Y = (X_i - mean(X_i))(X_j - mean(X_j))$

Value

Returns the test statistics for correlation testing.

Examples

```
n <- 100
p <- 10
corr_theo <- diag(1,p)
data <- MASS::mvrnorm(n,rep(0,p),corr_theo)
stat <- eval_stat(data,'fisher')
```

LCTboot	<i>Bootstrap procedure LCT-B proposed by Cai & Liu (2016) for correlation testing.</i>
---------	--

Description

Bootstrap procedure LCT-B proposed by Cai & Liu (2016) for correlation testing.

Usage

```
LCTboot(
  data,
  alpha = 0.05,
  stat_test = "2nd.order",
  Nboot = 100,
  vect = FALSE,
  arr.ind = FALSE
)
```

Arguments

data	matrix of observations
alpha	level of multiple testing
stat_test	'empirical' $\sqrt{n} * \text{abs}(\text{corr})$ 'fisher' $\sqrt{n-3} * 1/2 * \log((1 + \text{corr})/(1 - \text{corr}))$ 'student' $\sqrt{n-2} * \text{abs}(\text{corr})/\sqrt{1 - \text{corr}^2}$ '2nd.order' $\sqrt{n} * \text{mean}(Y)/\text{sd}(Y)$ with $Y = (X_i - \text{mean}(X_i))(X_j - \text{mean}(X_j))$
Nboot	number of iterations for bootstrap quantile evaluation
vect	if TRUE returns a vector of TRUE/FALSE values, corresponding to <code>vectorize(cor(data))</code> ; if FALSE, returns an array containing TRUE/FALSE values for each entry of the correlation matrix
arr.ind	if TRUE, returns the indexes of the significant correlations, with respect to level alpha

Value

Returns

- logicals, equal to TRUE if the corresponding element of the statistic vector is rejected, as a vector or a matrix depending of the value of vect,
- an array containing indexes $\{(i, j), i < j\}$ for which correlation between variables i and j is significant, if `arr.ind=TRUE`.

References

Cai, T. T., & Liu, W. (2016). Large-scale multiple testing of correlations. *Journal of the American Statistical Association*, 111(513), 229-240.

See Also

ApplyFdrCor, LCTNorm

Examples

```
n <- 100
p <- 10
corr_theo <- diag(1,p)
corr_theo[1,3] <- 0.5
corr_theo[3,1] <- 0.5
data <- MASS::mvrnorm(n,rep(0,p),corr_theo)
alpha <- 0.05
# significant correlations:
LCTboot(data,alpha,stat_test='empirical',Nboot=100,arr.ind=TRUE)
```

LCTnorm

Procedure LCT-N proposed by Cai & Liu (2016) for correlation testing.

Description

Procedure LCT-N proposed by Cai & Liu (2016) for correlation testing.

Usage

```
LCTnorm(
  data,
  alpha = 0.05,
  stat_test = "2nd.order",
  vect = FALSE,
  arr.ind = FALSE
)
```

Arguments

data	matrix of observations
alpha	level of multiple testing
stat_test	'empirical' $\sqrt{n} * abs(corr)$ 'fisher' $\sqrt{n-3} * 1/2 * \log((1+corr)/(1-corr))$ 'student' $\sqrt{n-2} * abs(corr) / \sqrt{1-corr^2}$ '2nd.order' $\sqrt{n} * mean(Y) / sd(Y)$ with $Y = (X_i - mean(X_i))(X_j - mean(X_j))$
vect	if TRUE returns a vector of TRUE/FALSE values, corresponding to <code>vectorize(cor(data))</code> ; if FALSE, returns an array containing TRUE/FALSE values for each entry of the correlation matrix
arr.ind	if TRUE, returns the indexes of the significant correlations, with respect to level alpha

Value

Returns

- logicals, equal to TRUE if the corresponding element of the statistic vector is rejected, as a vector or a matrix depending of the value of vect,
- an array containing indexes $\{(i, j), i < j\}$ for which correlation between variables i and j is significant, if `arr.ind=TRUE`.

References

Cai, T. T., & Liu, W. (2016). Large-scale multiple testing of correlations. *Journal of the American Statistical Association*, 111(513), 229-240.

See Also

ApplyFdrCor, LCTboot

Examples

```
n <- 100
p <- 10
corr_theo <- diag(1,p)
corr_theo[1,3] <- 0.5
corr_theo[3,1] <- 0.5
data <- MASS::mvrnorm(n,rep(0,p),corr_theo)
alpha <- 0.05
# significant correlations:
LCTnorm(data,alpha,stat_test='empirical',arr.ind=TRUE)
```

maxTinfyCor

Multiple testing method of Drton & Perlman (2007) for correlations.

Description

Multiple testing method based on the evaluation of quantile by simulation of observations from the asymptotic distribution (Drton & Perlman (2007)).

Usage

```
maxTinfyCor(
  data,
  alpha = 0.05,
  stat_test = "empirical",
  Nboot = 1000,
  OmegaChap = covDcorNorm(cor(data), stat_test),
  vect = FALSE,
  logical = FALSE,
  arr.ind = FALSE
)
```

Arguments

data	matrix of observations
alpha	level of multiple testing (used if logical=TRUE)
stat_test	'empirical' $\sqrt{n} * abs(corr)$ 'fisher' $\sqrt{n - 3} * 1/2 * \log((1 + corr)/(1 - corr))$ 'student' $\sqrt{n - 2} * abs(corr) / \sqrt{1 - corr^2}$ '2nd.order' $\sqrt{n} * mean(Y) / sd(Y)$ with $Y = (X_i - mean(X_i))(X_j - mean(X_j))$
Nboot	number of iterations for Monte-Carlo quantile evaluation
OmegaChap	matrix of covariance of empirical correlations used for quantile evaluation; optional, useful for oracle estimation and step-down
vect	if TRUE returns a vector of adjusted p-values, corresponding to <code>vectorize(cor(data))</code> ; if FALSE, returns an array containing the adjusted p-values for each entry of the correlation matrix
logical	if TRUE, returns either a vector or a matrix where each element is equal to TRUE if the corresponding null hypothesis is rejected, and to FALSE if it is not rejected
arr.ind	if TRUE, returns the indexes of the significant correlations, with respect to level alpha

Value

Returns

- the adjusted p-values, as a vector or a matrix depending of the value of vect,
- an array containing indexes $\{(i, j), i < j\}$ for which correlation between variables i and j is significant, if `arr.ind=TRUE`.

References

Drton, M., & Perlman, M. D. (2007). Multiple testing and error control in Gaussian graphical model selection. *Statistical Science*, 22(3), 430-449.

Roux, M. (2018). Graph inference by multiple testing with application to Neuroimaging, Ph.D., Université Grenoble Alpes, France, <https://tel.archives-ouvertes.fr/tel-01971574v1>.

See Also

ApplyFwerCor, maxTinfyCor_SD

Examples

```
n <- 100
p <- 10
corr_theo <- diag(1,p)
corr_theo[1,3] <- 0.5
corr_theo[3,1] <- 0.5
data <- MASS::mvrnorm(n,rep(0,p),corr_theo)
# adjusted p-values
res <- maxTinfyCor(data,stat_test='empirical',Nboot=1000)
round(res,2)
# significant correlations with level alpha:
alpha <- 0.05
whichCor(res<alpha)
# directly
res <- maxTinfyCor(data,alpha,stat_test='empirical',Nboot=1000,arr.ind=TRUE)
```

maxTinfyCor_SD

Multiple testing method of Drton & Perlman (2007) for correlations, with stepdown procedure.

Description

Multiple testing method based on the evaluation of quantile by simulation of observations from the asymptotic distribution (Drton & Perlman (2007)), with stepdown procedure.

Usage

```
maxTinfyCor_SD(
  data,
  alpha = 0.05,
  stat_test = "empirical",
  Nboot = 1000,
  OmegaChap = covDcorNorm(cor(data), stat_test),
  vect = FALSE,
  logical = TRUE,
  arr.ind = FALSE
)
```

Arguments

data	matrix of observations
alpha	level of multiple testing
stat_test	4 test statistics are available: 'empirical' $\sqrt{n} * abs(corr)$ 'fisher' $\sqrt{n-3} * 1/2 * \log((1+corr)/(1-corr))$ 'student' $\sqrt{n-2} * abs(corr) / \sqrt{1-corr^2}$ '2nd.order' $\sqrt{n} * mean(Y) / sd(Y)$ with $Y = (X_i - mean(X_i))(X_j - mean(X_j))$
Nboot	number of iterations for Monte-Carlo quantile evaluation
OmegaChap	matrix of covariance of test statistics; optional, useful for oracle estimation and step-down
vect	if TRUE returns a vector of TRUE/FALSE values, corresponding to <code>vectorize(cor(data))</code> ; if FALSE, returns an array containing TRUE/FALSE values for each entry of the correlation matrix
logical	if TRUE, returns either a vector or a matrix where each element is equal to TRUE if the corresponding null hypothesis is rejected, and to FALSE if it is not rejected if FALSE, returns a list of successive p-values : element <code>[[i+1]]</code> of the list giving the p-values evaluated on the non-rejected hypothesis at step <code>[[i]]</code> ; p-values are either as a vector or a list depending on vect
arr.ind	if TRUE, returns the indexes of the significant correlations, with respect to level alpha

Value**Returns**

- logicals, equal to TRUE if the corresponding element of the statistic vector is rejected, as a vector or a matrix depending of the value of vect,
- an array containing indexes $\{(i, j), i < j\}$ for which correlation between variables i and j is significant, if `arr.ind=TRUE`.

References

Drton, M., & Perlman, M. D. (2007). Multiple testing and error control in Gaussian graphical model selection. *Statistical Science*, 22(3), 430-449.

Roux, M. (2018). Graph inference by multiple testing with application to Neuroimaging, Ph.D., Université Grenoble Alpes, France, <https://tel.archives-ouvertes.fr/tel-01971574v1>.

See Also

ApplyFwerCor, maxTinfyCor

Examples

```
n <- 100
p <- 10
corr_theo <- diag(1,p)
corr_theo[1,3] <- 0.5
corr_theo[3,1] <- 0.5
data <- MASS::mvrnorm(n,rep(0,p),corr_theo)
alpha <- 0.05
# significant correlations:
maxTinfyCor_SD(data,alpha,stat_test='empirical', arr.ind=TRUE)
# successive p-values
res <- maxTinfyCor_SD(data,stat_test='empirical', logical=FALSE)
lapply(res,FUN=function(x){round(x,2)})
# successive rejections
lapply(res,FUN=function(x){whichCor(x<alpha)})
```

SidakCor

Sidak multiple testing procedure for correlations.

Description

Sidak multiple testing procedure for correlations.

Usage

```
SidakCor(
  data,
  alpha = 0.05,
  stat_test = "empirical",
  vect = FALSE,
  logical = FALSE,
  arr.ind = FALSE
)
```

Arguments

data	matrix of observations
alpha	level of multiple testing (used if logical=TRUE)
stat_test	'empirical' $\sqrt{n} * \text{abs}(\text{corr})$ 'fisher' $\sqrt{n-3} * 1/2 * \log((1 + \text{corr})/(1 - \text{corr}))$ 'student' $\sqrt{n-2} * \text{abs}(\text{corr})/\sqrt{1 - \text{corr}^2}$ '2nd.order' $\sqrt{n} * \text{mean}(Y)/\text{sd}(Y)$ with $Y = (X_i - \text{mean}(X_i))(X_j - \text{mean}(X_j))$
vect	if TRUE returns a vector of adjusted p-values, corresponding to <code>vectorize(cor(data))</code> ; if FALSE, returns an array containing the adjusted p-values for each entry of the correlation matrix
logical	if TRUE, returns either a vector or a matrix where each element is equal to TRUE if the corresponding null hypothesis is rejected, and to FALSE if it is not rejected
arr.ind	if TRUE, returns the indexes of the significant correlations, with respect to level alpha

Value

Returns

- the adjusted p-values, as a vector or a matrix depending of the value of `vect`,
- an array containing indexes $\{(i, j), i < j\}$ for which correlation between variables i and j is significant, if `arr.ind=TRUE`.

References

Roux, M. (2018). Graph inference by multiple testing with application to Neuroimaging, Ph.D., Université Grenoble Alpes, France, <https://tel.archives-ouvertes.fr/tel-01971574v1>.

Šidák, Z. (1967). Rectangular confidence regions for the means of multivariate normal distributions. *Journal of the American Statistical Association*, 62(318), 626-633.

See Also

`ApplyFwerCor`, `SidakCor_SD`

Examples

```
n <- 100
p <- 10
corr_theo <- diag(1,p)
corr_theo[1,3] <- 0.5
corr_theo[3,1] <- 0.5
data <- MASS::mvrnorm(n,rep(0,p),corr_theo)
# adjusted p-values
res <- SidakCor(data,stat_test='empirical')
round(res,2)
# significant correlations with level alpha:
```

```
alpha <- 0.05
whichCor(res<alpha)
# directly
SidakCor(data,alpha,stat_test='empirical',arr.ind=TRUE)
```

SidakCor_SD	<i>Sidak multiple testing method for correlations with stepdown procedure.</i>
-------------	--

Description

Sidak multiple testing method for correlations with stepdown procedure.

Usage

```
SidakCor_SD(
  data,
  alpha = 0.05,
  stat_test = "empirical",
  vect = FALSE,
  logical = TRUE,
  arr.ind = FALSE
)
```

Arguments

data	matrix of observations
alpha	level of multiple testing
stat_test	4 test statistics are available: 'empirical' $\sqrt{n} * \text{abs}(\text{corr})$ 'fisher' $\sqrt{n-3} * 1/2 * \log((1 + \text{corr})/(1 - \text{corr}))$ 'student' $\sqrt{n-2} * \text{abs}(\text{corr})/\sqrt{1 - \text{corr}^2}$ '2nd.order' $\sqrt{n} * \text{mean}(Y)/\text{sd}(Y)$ with $Y = (X_i - \text{mean}(X_i))(X_j - \text{mean}(X_j))$
vect	if TRUE returns a vector of TRUE/FALSE values, corresponding to <code>vectorize(cor(data))</code> ; if FALSE, returns an array containing TRUE/FALSE values for each entry of the correlation matrix
logical	if TRUE, returns either a vector or a matrix where each element is equal to TRUE if the corresponding null hypothesis is rejected, and to FALSE if it is not rejected if FALSE, returns a list of successive p-values : element <code>[[i+1]]</code> of the list giving the p-values evaluated on the non-rejected hypothesis at step <code>[[i]]</code> ; p-values are either as a vector or a list depending on <code>vect</code>
arr.ind	if TRUE, returns the indexes of the significant correlations, with respect to level alpha

Value

Returns

- logicals, equal to TRUE if the corresponding element of the statistic vector is rejected, as a vector or a matrix depending of the value of vect,
- an array containing indexes $\{(i, j), i < j\}$ for which correlation between variables i and j is significant, if `arr.ind=TRUE`.

References

Roux, M. (2018). Graph inference by multiple testing with application to Neuroimaging, Ph.D., Université Grenoble Alpes, France, <https://tel.archives-ouvertes.fr/tel-01971574v1>.

Šidák, Z. (1967). Rectangular confidence regions for the means of multivariate normal distributions. *Journal of the American Statistical Association*, 62(318), 626-633.

See Also

ApplyFwerCor, SidakCor

Examples

```
n <- 100
p <- 10
corr_theo <- diag(1,p)
corr_theo[1,3] <- 0.5
corr_theo[3,1] <- 0.5
data <- MASS::mvrnorm(n,rep(0,p),corr_theo)
alpha <- 0.05
# significant correlations:
SidakCor_SD(data,alpha,stat_test='empirical', arr.ind=TRUE)
# successive p-values
res <- SidakCor_SD(data,stat_test='empirical', logical=FALSE)
lapply(res,FUN=function(x){round(x,2)})
# successive rejections
lapply(res,FUN=function(x){whichCor(x<alpha)})
```

SimuFdr

Simulates Gaussian data with a given correlation matrix and applies a FDR controlling procedure on the correlations.

Description

Simulates Gaussian data with a given correlation matrix and applies a FDR controlling procedure on the correlations.

Usage

```

SimuFdr(
  corr_theo,
  n = 100,
  Nsimu = 1,
  alpha = 0.05,
  stat_test = "empirical",
  method = "LCTnorm",
  Nboot = 1000,
  seed = NULL
)

```

Arguments

corr_theo	the correlation matrix of Gaussian data simulated
n	sample size
Nsimu	number of simulations
alpha	level of multiple testing
stat_test	'empirical' $\sqrt{n} * abs(corr)$ 'fisher' $\sqrt{n-3} * 1/2 * \log((1+corr)/(1-corr))$ 'student' $\sqrt{n-2} * abs(corr) / \sqrt{1-corr^2}$ 'gaussian' $\sqrt{n} * mean(Y) / sd(Y)$ with $Y = (X_i - mean(X_i))(X_j - mean(X_j))$
method	choice between 'LCTnorm' and 'LCTboot', developed by Cai & Liu (2016), 'BH', traditional Benjamini-Hochberg (1995)'s procedure, and 'BHboot', Benjamini-Hochberg (1995)'s procedure with bootstrap evaluation of pvalues
Nboot	number of iterations for Monte-Carlo of bootstrap quantile evaluation
seed	seed for the Gaussian simulations

Value

Returns a line vector containing estimated values for fwer, fdr, sensitivity, specificity and accuracy.

References

- Benjamini, Y., & Hochberg, Y. (1995). Controlling the false discovery rate: a practical and powerful approach to multiple testing. *Journal of the royal statistical society. Series B (Methodological)*, 289-300.
- Cai, T. T., & Liu, W. (2016). Large-scale multiple testing of correlations. *Journal of the American Statistical Association*, 111(513), 229-240.
- Roux, M. (2018). Graph inference by multiple testing with application to Neuroimaging, Ph.D., Université Grenoble Alpes, France, <https://tel.archives-ouvertes.fr/tel-01971574v1>.

See Also

ApplyFdrCor, SimuFwer

Examples

```

Nsimu <- 1000
n <- 100
p <- 10
corr_theo <- diag(1,p)
corr_theo[1,3] <- 0.5
corr_theo[3,1] <- 0.5
alpha <- 0.05
SimuFdr(corr_theo,n,Nsimu,alpha,stat_test='empirical',method='LCTnorm')

```

SimuFwer	<i>Simulates Gaussian data with a given correlation matrix and applies a FWER controlling procedure on the correlations.</i>
----------	--

Description

Simulates Gaussian data with a given correlation matrix and applies a FWER controlling procedure on the correlations.

Usage

```

SimuFwer(
  corr_theo,
  n = 100,
  Nsimu = 1,
  alpha = 0.05,
  stat_test = "empirical",
  method = "Sidak",
  Nboot = 1000,
  stepdown = TRUE,
  seed = NULL
)

```

Arguments

corr_theo	the correlation matrix of Gaussian data simulated
n	sample size
Nsimu	number of simulations
alpha	level of multiple testing
stat_test	'empirical' $\sqrt{n} * abs(corr)$ 'fisher' $\sqrt{n-3} * 1/2 * \log((1+corr)/(1-corr))$ 'student' $\sqrt{n-2} * abs(corr) / \sqrt{1-corr^2}$ 'gaussian' $\sqrt{n} * mean(Y) / sd(Y)$ with $Y = (X_i - mean(X_i))(X_j - mean(X_j))$
method	choice between 'Bonferroni', 'Sidak', 'BootRW', 'MaxTinfy'
Nboot	number of iterations for Monte-Carlo of bootstrap quantile evaluation
stepdown	logical, if TRUE a stepdown procedure is applied
seed	seed for the Gaussian simulations

Value

Returns a line vector containing estimated values for fwer, fdr, sensitivity, specificity and accuracy.

References

Bonferroni, C. E. (1935). Il calcolo delle assicurazioni su gruppi di teste. Studi in onore del professore salvatore ortu carboni, 13-60.

Drton, M., & Perlman, M. D. (2007). Multiple testing and error control in Gaussian graphical model selection. *Statistical Science*, 22(3), 430-449.

Romano, J. P., & Wolf, M. (2005). Exact and approximate stepdown methods for multiple hypothesis testing. *Journal of the American Statistical Association*, 100(469), 94-108.

Roux, M. (2018). Graph inference by multiple testing with application to Neuroimaging, Ph.D., Université Grenoble Alpes, France, <https://tel.archives-ouvertes.fr/tel-01971574v1>.

Westfall, P.H. & Young, S. (1993) Resampling-based multiple testing: Examples and methods for p-value adjustment, John Wiley & Sons, vol. 279.

See Also

ApplyFwerCor, SimuFwer_oracle, SimuFdr

Examples

```
Nsimu <- 1000
n <- 100
p <- 10
corr_theo <- diag(1,p)
corr_theo[1,3] <- 0.5
corr_theo[3,1] <- 0.5
alpha <- 0.05
SimuFwer(corr_theo,n,Nsimu,alpha,stat_test='empirical',method='Bonferroni',stepdown=FALSE)
```

SimuFwer_oracle	<i>Simulates Gaussian data with a given correlation matrix and applies oracle MaxTinfy on the correlations.</i>
-----------------	---

Description

Simulates Gaussian data with a given correlation matrix and applies oracle MaxTinfy (i.e. Drton & Perlman (2007)'s procedure with the true correlation matrix) on the correlations.

Usage

```
SimuFwer_oracle(
  corr_theo,
  n = 100,
  Nsimu = 1,
```

```

alpha = 0.05,
stat_test = "empirical",
method = "MaxTinfy",
Nboot = 1000,
stepdown = TRUE,
seed = NULL
)

```

Arguments

corr_theo	the correlation matrix of Gaussian data simulated
n	sample size
Nsimu	number of simulations
alpha	level of multiple testing
stat_test	'empirical' $\sqrt{n} * abs(corr)$ 'fisher' $\sqrt{n-3} * 1/2 * \log((1+corr)/(1-corr))$ 'student' $\sqrt{n-2} * abs(corr) / \sqrt{1-corr^2}$ 'gaussian' $\sqrt{n} * mean(Y) / sd(Y)$ with $Y = (X_i - mean(X_i))(X_j - mean(X_j))$
method	only 'MaxTinfy' available
Nboot	number of iterations for Monte-Carlo of bootstrap quantile evaluation
stepdown	logical, if TRUE a stepdown procedure is applied
seed	seed for the Gaussian simulations

Value

Returns a line vector containing estimated values for fwer, fdr, sensitivity, specificity and accuracy.

References

Drton, M., & Perlman, M. D. (2007). Multiple testing and error control in Gaussian graphical model selection. *Statistical Science*, 22(3), 430-449.

Roux, M. (2018). Graph inference by multiple testing with application to Neuroimaging, Ph.D., Université Grenoble Alpes, France, <https://tel.archives-ouvertes.fr/tel-01971574v1>.

See Also

ApplyFwerCor_Oracle, SimuFwer

Examples

```

Nsimu <- 1000
n <- 50
p <- 10
corr_theo <- diag(1,p)
corr_theo[1,3] <- 0.5
corr_theo[3,1] <- 0.5
alpha <- 0.05
SimuFwer_oracle(corr_theo,n,Nsimu,alpha,stat_test='empirical',stepdown=FALSE,Nboot=100)

```

UncorrectedCor *Uncorrected testing procedure for correlations.*

Description

Uncorrected testing procedure for correlations.

Usage

```
UncorrectedCor(
  data,
  alpha = 0.05,
  stat_test = "empirical",
  vect = FALSE,
  logical = FALSE,
  arr.ind = FALSE
)
```

Arguments

data	matrix of observations
alpha	level of multiple testing (used if logical=TRUE)
stat_test	'empirical' $\sqrt{n} * abs(corr)$ 'fisher' $\sqrt{n-3} * 1/2 * \log((1+corr)/(1-corr))$ 'student' $\sqrt{n-2} * abs(corr) / \sqrt{1-corr^2}$ '2nd.order' $\sqrt{n} * mean(Y) / sd(Y)$ with $Y = (X_i - mean(X_i))(X_j - mean(X_j))$
vect	if TRUE returns a vector of adjusted p-values, corresponding to <code>vectorize(cor(data))</code> ; if FALSE, returns an array containing the adjusted p-values for each entry of the correlation matrix
logical	if TRUE, returns either a vector or a matrix where each element is equal to TRUE if the corresponding null hypothesis is rejected, and to FALSE if it is not rejected
arr.ind	if TRUE, returns the indexes of the significant correlations, with respect to level alpha

Value

Returns

- the non-adjusted p-values, as a vector or a matrix depending of the value of `vect`,
- an array containing indexes $\{(i, j), i < j\}$ for which correlation between variables i and j is significant, if `arr.ind=TRUE`.

Examples

```
n <- 100
p <- 10
corr_theo <- diag(1,p)
corr_theo[1,3] <- 0.5
corr_theo[3,1] <- 0.5
data <- MASS::mvrnorm(n,rep(0,p),corr_theo)
# p-values
res <- UncorrectedCor(data,stat_test='empirical')
round(res,2)
# significant correlations with level alpha:
alpha <- 0.05
whichCor(res<alpha)
# directly
UncorrectedCor(data,alpha,stat_test='empirical',arr.ind=TRUE)
```

unvectorize	<i>Returns an upper-triangle matrix, without the diagonal, containing the elements of a given vector.</i>
-------------	---

Description

Returns an upper-triangle matrix, without the diagonal, containing the elements of a given vector.

Usage

```
unvectorize(vect)
```

Arguments

vect A vector containing the upper triangle of a matrix, without the diagonal

Value

Returns an upper-triangle matrix where each entry is given by the vector containing the upper triangle of a matrix, without the diagonal.

See Also

vectorize

Examples

```
unvectorize(1:10)
```

vectorize	<i>Returns a vector containing the upper triangle of a matrix, without the diagonal.</i>
-----------	--

Description

Returns a vector containing the upper triangle of a matrix, without the diagonal.

Usage

```
vectorize(mat)
```

Arguments

mat	a square matrix
-----	-----------------

Value

Returns a vector containing the upper triangle of a matrix, without the diagonal.

See Also

unvectorize

Examples

```
vectorize(matrix(1:9,3,3))
```

whichCor	<i>Returns the indexes of an upper triangular matrix with logical entries.</i>
----------	--

Description

Returns the indexes of an upper triangular matrix with logical entries.

Usage

```
whichCor(mat)
```

Arguments

mat	A matrix with logical entries in the upper triangular part
-----	--

Value

Returns the indexes of the upper triangular part where the entries are TRUE

Examples

```
n <- 100
p <- 10
corr_theo <- diag(1,p)
corr_theo[1,3] <- 0.5
corr_theo[3,1] <- 0.5
data <- MASS::mvrnorm(n,rep(0,p),corr_theo)
res <- ApplyFwerCor(data,stat_test='empirical',method='Bonferroni',stepdown=FALSE)
# significant correlations, level alpha:
alpha <- 0.05
whichCor(res<alpha)
```

Index

- * **FDR**
 - TestCor-package, 2
- * **FWER**
 - TestCor-package, 2
- * **correlation testing**
 - TestCor-package, 2
- * **graph inference**
 - TestCor-package, 2
- * **multiple testing**
 - TestCor-package, 2

- ApplyFdrCor, 4
- ApplyFwerCor, 6
- ApplyFwerCor_oracle, 8

- BHBootCor, 10
- BHCor, 11
- BonferroniCor, 12
- BonferroniCor_SD, 14
- BootRWCOR, 16
- BootRWCOR_SD, 17

- covD2nd, 19
- covDcor, 20
- covDcorNorm, 20

- eval_stat, 21

- LCTboot, 22
- LCTnorm, 23

- maxTinfyCor, 25
- maxTinfyCor_SD, 26

- SidakCor, 28
- SidakCor_SD, 30
- SimuFdr, 31
- SimuFwer, 33
- SimuFwer_oracle, 34

- TestCor (TestCor-package), 2

- TestCor-package, 2
- UncorrectedCor, 36
- unvectorize, 37

- vectorize, 38

- whichCor, 38