

# Package ‘UniExactFunTest’

May 7, 2026

**Type** Package

**Title** Uniform Exact Functional Tests for Contingency Tables

**Version** 1.0.1

**Date** 2025-02-20

**Author** Yiyi Li [aut, cre] (ORCID: <<https://orcid.org/0000-0001-8859-3987>>),  
Joe Song [aut] (ORCID: <<https://orcid.org/0000-0002-6883-6547>>)

**Maintainer** Yiyi Li <gtarex@nmsu.edu>

**Description** Testing whether two discrete variables have a functional relationship under null distributions where the two variables are statistically independent with fixed marginal counts.

The fast enumeration algorithm was based on (Nguyen et al. 2020) <[doi:10.24963/ijcai.2020/372](https://doi.org/10.24963/ijcai.2020/372)>.

**License** LGPL (>= 3)

**Encoding** UTF-8

**Imports** Rcpp (>= 1.0.5)

**LinkingTo** Rcpp

**Depends** R (>= 3.5.0), stats

**Suggests** knitr, rmarkdown, testthat (>= 3.0.0)

**VignetteBuilder** knitr

**Config/testthat/edition** 3

**RoxygenNote** 7.3.2

**NeedsCompilation** yes

**Repository** CRAN

**Date/Publication** 2025-02-21 07:00:02 UTC

## Contents

UEFT . . . . .	2
<b>Index</b>	<b>3</b>

**Description**

Perform the uniform exact functional test on a contingency table to determine if the column variable is a function of the row variable.

**Usage**

```
UEFT(input, correct, log.p)
```

**Arguments**

input	A matrix of nonnegative integers representing a contingency table. Column is the casual and row is the effect.
correct	Logical; if implement the continuity correction. The description is at details. The default is TRUE.
log.p	Logical; if TRUE, the p-value is given as log(p). The default is FALSE. The default is FALSE.

**Details**

The uniform idea was implementated using uniform marginal distribution of a square table as null hypothesis.

**Value**

The exact p-value of the test.

**Note**

The functions provide a direct entry into the C++ implementations of the exact functional test.

**Author(s)**

Yiyi Li, Joe Song

**Examples**

```
# Initial a table
x = matrix(c(0,5,10,0,0,5), ncol=3)
# With continuity correction
UEFT(x)
# Without continuity correction
UEFT(x, FALSE)
```

# Index

- \* **exact**
  - UEFT, 2
- \* **functional**
  - UEFT, 2
- \* **nonparametric**
  - UEFT, 2
- \* **test**
  - UEFT, 2
- \* **uniform**
  - UEFT, 2

UEFT, 2