

Package ‘adepro’

May 7, 2026

Type Package

Title A 'shiny' Application for the (Audio-)Visualization of Adverse Event Profiles

Version 4.2.7

Description Contains a 'shiny' application called AdEPro (Animation of Adverse Event Profiles) which (audio-)visualizes adverse events occurring in clinical trials. As this data is usually considered sensitive, this tool is provided as a stand-alone application that can be launched from any local machine on which the data is stored.

Depends R (>= 3.5.0), shinyBS, seriation (>= 1.2.9)

License GPL-3

URL <https://github.com/Bayer-Group/BIC-AdEPro>

Encoding UTF-8

RoxygenNote 7.2.3

Imports graphics, MASS, V8, forcats, here, utils, shinyjs, shiny, audio, shape, Cairo, dplyr, readr, rlang, tidyr, haven, stats, shinyWidgets, DT

Suggests knitr, rmarkdown, testthat

VignetteBuilder knitr

NeedsCompilation no

Author Nicole Rethemeier [cre],
Christoph Tasto [aut],
Steffen Jeske [aut],
Bodo Kirsch [aut]

Maintainer Nicole Rethemeier <nicole.rethemeier@bayer.com>

Repository CRAN

Date/Publication 2025-03-25 09:30:11 UTC

Contents

launch_adepro 2

Index 4

launch_adepto	<i>launch_adepto - Launches the AdEPro application</i>
---------------	--

Description

Starts the AdEPro application in the client's browser.

Usage

```
launch_adepto(host = "127.0.0.1", port = NULL, browser = NULL)
```

Arguments

host	host link (defaults to the local machine "127.0.0.1")
port	port number (randomly chosen unless specified as a certain number)
browser	path to browser exe (defaults to standard browser)

Details

Further information on how to use this application can be found in the vignette of this package.

Value

A shiny app

Examples

```
## Not run:
## Launch application on localhost (127.0.0.1)
## -----
## By default launch_adepto starts the application on localhost
## and a randomly selected port (e.g. 9876), in which case you can connect
## to the running application by navigating your browser to
## http://localhost:9876.
launch_adepto()

## Launch application on a different host
## -----
## You can also run the application on a different host
## by specifying a hostname and port. Just make sure to
## use an open port on your machine. Here "open" means
## that the port should not be used by another service
## and the port is opened by your firewall.
launch_adepto(host="your-hostname", port=8888)

## Make the application available to your coworkers
## -----
## within your local area network even without a
```

```
## dedicated Shiny server. The value set through the
## host argument says to accept any connection (not just from localhost).
## Then take note of your local IP (if you are under linux,
## you can see it through ifconfig). Say your IP is 192.168.1.70.
## Your colleagues can use your app by inserting in the address
## bar of their browser 192.168.1.70:8888, i.e. your IP followed
## by : and the port number you selected.
launch_adepro(host="0.0.0.0", port=8888)

## Launch application on a different browser
## -----
## To run the shiny app on a different browser than your standard browser
## use the "browser" argument to set the path to the respective .exe file.
launch_adepro(browser = "C:/Program Files/Mozilla Firefox/firefox.exe")

## launching the application.

## End(Not run)
```

Index

* **adepro**

[launch_adepto](#), [2](#)

[launch_adepto](#), [2](#)