

Package ‘amen’

May 7, 2026

Title Additive and Multiplicative Effects Models for Networks and Relational Data

Version 1.4.5

Description Analysis of dyadic network and relational data using additive and multiplicative effects (AME) models. The basic model includes regression terms, the covariance structure of the social relations model (Warner, Kenny and Stoto (1979) <[DOI:10.1037/0022-3514.37.10.1742](https://doi.org/10.1037/0022-3514.37.10.1742)>, Wong (1982) <[DOI:10.2307/2287296](https://doi.org/10.2307/2287296)>), and multiplicative factor models (Hoff(2009) <[DOI:10.1007/s10588-008-9040-4](https://doi.org/10.1007/s10588-008-9040-4)>). Several different link functions accommodate different relational data structures, including binary/network data, normal relational data, zero-inflated positive outcomes using a tobit model, ordinal relational data and data from fixed-rank nomination schemes. Several of these link functions are discussed in Hoff, Fosdick, Volfovsky and Stovel (2013) <[DOI:10.1017/nws.2013.17](https://doi.org/10.1017/nws.2013.17)>. Development of this software was supported in part by NIH grant R01HD067509.

Maintainer Peter Hoff <peter.hoff@duke.edu>

URL <https://github.com/pdhoff/amen>

BugReports <https://github.com/pdhoff/amen/issues>

License GPL-3

Date 2024-02-20

LazyData true

Depends R (>= 3.5.0)

Suggests coda,network,knitr,rmarkdown

VignetteBuilder knitr

RoxygenNote 7.3.1

NeedsCompilation no

Author Peter Hoff [aut, cre],
Bailey Fosdick [aut],
Alex Volfovsky [aut],
Yanjun He [ctb]

Repository CRAN

Date/Publication 2024-02-20 23:20:07 UTC

Contents

| | |
|---------------------------|----|
| amen-package | 3 |
| addhealthc3 | 4 |
| addhealthc9 | 5 |
| addlines | 5 |
| ame | 6 |
| ame_rep | 8 |
| circplot | 10 |
| coldwar | 11 |
| comtrade | 12 |
| design_array | 12 |
| dutchcollege | 13 |
| e12sm | 13 |
| gofstats | 14 |
| IR90s | 15 |
| lazegalaw | 15 |
| ldZgbme | 16 |
| llsrmRho | 17 |
| mhalf | 18 |
| netplot | 18 |
| plot.ame | 19 |
| precomputeX | 20 |
| raSab_bin_fc | 20 |
| raSab_cbin_fc | 21 |
| raSab_frn_fc | 22 |
| rbeta_ab_fc | 23 |
| rbeta_ab_rep_fc | 24 |
| rmvnorm | 24 |
| rrho_fc | 25 |
| rrho_mh | 26 |
| rrho_mh_rep | 26 |
| rs2_fc | 27 |
| rs2_rep_fc | 28 |
| rSab_fc | 28 |
| rSuv_fc | 29 |
| rUV_fc | 29 |
| rUV_rep_fc | 30 |
| rUV_sym_fc | 31 |
| rwish | 32 |
| rZ_bin_fc | 33 |
| rZ_cbin_fc | 33 |
| rZ_frn_fc | 34 |
| rZ_nrm_fc | 35 |

| | |
|------------------------|----|
| rZ_ord_fc | 36 |
| rZ_rrl_fc | 36 |
| rZ_tob_fc | 37 |
| sampsonmonks | 38 |
| sheep | 38 |
| simY_bin | 39 |
| simY_frn | 39 |
| simY_nrm | 40 |
| simY_ord | 40 |
| simY_rrl | 41 |
| simY_tob | 42 |
| simZ | 42 |
| sm2el | 43 |
| summary.ame | 43 |
| Xbeta | 44 |
| xnet | 45 |
| YX_bin | 46 |
| YX_bin_long | 46 |
| YX_cbin | 47 |
| YX_frn | 47 |
| YX_nrm | 48 |
| YX_ord | 48 |
| YX_rrl | 49 |
| zscores | 49 |

Index 50

| | |
|--------------|--|
| amen-package | <i>Additive and Multiplicative Effects Models for Networks and Relational Data</i> |
|--------------|--|

Description

Analysis of network and relational data using additive and multiplicative effects (AME) models. The basic model includes regression terms, the covariance structure of the social relations model (Warner, Kenny and Stoto (1979), Wong (1982)), and multiplicative factor effects (Hoff(2009)). Four different link functions accommodate different relational data structures, including binary/network data (bin), normal relational data (nrm), ordinal relational data (ord) and data from fixed-rank nomination schemes (frn). Several of these link functions are discussed in Hoff, Fosdick, Volfovsky and Stovel (2013). Development of this software was supported in part by NICHD grant R01HD067509.

Details

| | |
|----------|------------|
| Package: | amen |
| Type: | Package |
| Version: | 1.4.4 |
| Date: | 2020-12-01 |

License: GPL-3

Author(s)

Peter Hoff, Bailey Fosdick, Alex Volfovsky, Yanjun He

Maintainer: Peter Hoff <peter.hoff@duke.edu>

See Also

Useful links:

- <https://github.com/pdhoff/amen>
- Report bugs at <https://github.com/pdhoff/amen/issues>

Examples

```
data(YX_frn)
fit<-ame(YX_frn$Y,YX_frn$X,burn=5,nscan=5,odens=1,family="frn")

summary(fit)

plot(fit)
```

addhealthc3

AddHealth community 3 data

Description

A valued sociomatrix (Y) and matrix of nodal attributes (X) for students in community 3 of the AddHealth study.

- Y: A sociomatrix in which the value of the edge corresponds to an ad-hoc measure of intensity of the relation. Note that students were only allowed to nominate up to 5 male friends and 5 female friends.
- X: Matrix of students attributes, including sex, race (1=white, 2=black, 3=hispanic, 4=asian, 5=mixed/other) and grade.

Usage

```
data(addhealthc3)
```

Format

list

| | |
|-------------|-----------------------------------|
| addhealthc9 | <i>AddHealth community 9 data</i> |
|-------------|-----------------------------------|

Description

A valued sociomatrix (Y) and matrix of nodal attributes (X) for students in community 9 of the AddHealth study.

- Y: A sociomatrix in which the value of the edge corresponds to an ad-hoc measure of intensity of the relation. Note that students were only allowed to nominate up to 5 male friends and 5 female friends.
- X: Matrix of students attributes, including sex, race (1=white, 2=black, 3=hispanic, 4=asian, 5=mixed/other) and grade.

Usage

```
data(addhealthc9)
```

Format

```
list
```

| | |
|----------|------------------|
| addlines | <i>Add lines</i> |
|----------|------------------|

Description

Add lines to a network plot

Usage

```
addlines(Y,X,col="lightblue",alength=0,...)
```

Arguments

| | |
|---------|--|
| Y | a sociomatrix |
| X | coordinates of nodes |
| col | color of lines. Can be a vector of length equal to the number of edges to be drawn |
| alength | length of arrows to be drawn |
| ... | additional plotting parameters |

Author(s)

Peter Hoff

Examples

```
data(addhealthc3)
Y<-addhealthc3$Y
X<-xnet(Y)
netplot(Y,X)
addlines(Y,X,col=Y[!=0])
```

ame

AME model fitting routine

Description

An MCMC routine providing a fit to an additive and multiplicative effects (AME) regression model to relational data of various types

Usage

```
ame(Y, Xdyad=NULL, Xrow=NULL, Xcol=NULL, family, R=0, rvar = !(family=="rrl") ,
cvar = TRUE, dcor = !symmetric, nvar=TRUE,
intercept=!is.element(family,c("rrl","ord")),
symmetric=FALSE,
odmax=rep(max(apply(Y>0,1,sum,na.rm=TRUE)),nrow(Y)), seed = 1, nscan =
10000, burn = 500, odens = 25, plot=TRUE, print = TRUE, gof=TRUE,
prior=list())
```

Arguments

| | |
|-----------|--|
| Y | an n x n square relational matrix of relations. See family below for various data types. |
| Xdyad | an n x n x pd array of covariates |
| Xrow | an n x pr matrix of nodal row covariates |
| Xcol | an n x pc matrix of nodal column covariates |
| family | character: one of "nrm","tob","bin","ord","cbin","frn","rrl" - see the details below |
| R | integer: dimension of the multiplicative effects (can be zero) |
| rvar | logical: fit row random effects (asymmetric case)? |
| cvar | logical: fit column random effects (asymmetric case)? |
| dcor | logical: fit a dyadic correlation (asymmetric case)? |
| nvar | logical: fit nodal random effects (symmetric case)? |
| intercept | logical: fit model with an intercept? |
| symmetric | logical: Is the sociomatrix symmetric by design? |
| odmax | a scalar integer or vector of length n giving the maximum number of nominations that each node may make - used for "frn" and "cbin" families |

| | |
|-------|--|
| seed | random seed |
| nscan | number of iterations of the Markov chain (beyond burn-in) |
| burn | burn in for the Markov chain |
| odens | output density for the Markov chain |
| plot | logical: plot results while running? |
| print | logical: print results while running? |
| gof | logical: calculate goodness of fit statistics? |
| prior | list: A list of hyperparameters for the prior distribution |

Details

This command provides posterior inference for parameters in AME models of relational data, assuming one of six possible data types/models:

"nrm": A normal AME model.

"tob": A tobit AME model.

"bin": A binary probit AME model.

"ord": An ordinal probit AME model. An intercept is not identifiable in this model.

"cbin": An AME model for censored binary data. The value of 'odmax' specifies the maximum number of links each row may have.

"frn": An AME model for fixed rank nomination networks. A higher value of the rank indicates a stronger relationship. The value of 'odmax' specifies the maximum number of links each row may have.

"rrl": An AME model based on the row ranks. This is appropriate if the relationships across rows are not directly comparable in terms of scale. An intercept, row random effects and row regression effects are not estimable for this model.

Value

| | |
|-------|--|
| BETA | posterior samples of regression coefficients |
| VC | posterior samples of the variance parameters |
| APM | posterior mean of additive row effects a |
| BPM | posterior mean of additive column effects b |
| U | posterior mean of multiplicative row effects u |
| V | posterior mean of multiplicative column effects v (asymmetric case) |
| UVPM | posterior mean of UV (asymmetric case) |
| ULUPM | posterior mean of ULU (symmetric case) |
| L | posterior mean of L (symmetric case) |
| EZ | estimate of expectation of Z matrix |
| YPM | posterior mean of Y (for imputing missing values) |
| GOF | observed (first row) and posterior predictive (remaining rows) values of four goodness-of-fit statistics |

Author(s)

Peter Hoff

Examples

```
data(YX_frn)
fit<-ame(YX_frn$Y,YX_frn$X,burn=5,nscan=5,odens=1,family="frn")
# you should run the Markov chain much longer than this
```

ame_rep

*AME model fitting routine for replicated relational data***Description**

An MCMC routine providing a fit to an additive and multiplicative effects (AME) regression model to replicated relational data of various types.

Usage

```
ame_rep(Y,Xdyad=NULL, Xrow=NULL, Xcol=NULL, family, R=0, rvar = !(family=="rrl"),
cvar = TRUE, dcor = !symmetric, nvar=TRUE,
intercept=!is.element(family,c("rrl","ord")),
symmetric=FALSE,
odmax=rep(max(apply(Y>0,c(1,3),sum,na.rm=TRUE)),nrow(Y[, ,1])), seed = 1,
nscan = 10000, burn = 500, odens = 25, plot=TRUE, print = TRUE, gof=TRUE)
```

Arguments

| | |
|-----------|---|
| Y | an n x n x T array of relational matrix, where the third dimension corresponds to replicates (over time, for example). See family below for various data types. |
| Xdyad | an n x n x pd x T array of covariates |
| Xrow | an n x pr x T array of nodal row covariates |
| Xcol | an n x pc x T array of nodal column covariates |
| family | character: one of "nrm","bin","ord","cbin","frn","rrl" - see the details below |
| R | integer: dimension of the multiplicative effects (can be zero) |
| rvar | logical: fit row random effects (asymmetric case)? |
| cvar | logical: fit column random effects (asymmetric case)? |
| dcor | logical: fit a dyadic correlation (asymmetric case)? |
| nvar | logical: fit nodal random effects (symmetric case)? |
| intercept | logical: fit model with an intercept? |
| symmetric | logical: Is the sociomatrix symmetric by design? |

| | |
|-------|--|
| odmax | a scalar integer or vector of length n giving the maximum number of nominations that each node may make - used for "frn" and "cbin" families |
| seed | random seed |
| nscan | number of iterations of the Markov chain (beyond burn-in) |
| burn | burn in for the Markov chain |
| odens | output density for the Markov chain |
| plot | logical: plot results while running? |
| print | logical: print results while running? |
| gof | logical: calculate goodness of fit statistics? |

Details

This command provides posterior inference for parameters in AME models of independent replicated relational data, assuming one of six possible data types/models:

"nrm": A normal AME model.

"bin": A binary probit AME model.

"ord": An ordinal probit AME model. An intercept is not identifiable in this model.

"cbin": An AME model for censored binary data. The value of 'odmax' specifies the maximum number of links each row may have.

"frn": An AME model for fixed rank nomination networks. A higher value of the rank indicates a stronger relationship. The value of 'odmax' specifies the maximum number of links each row may have.

"rrl": An AME model based on the row ranks. This is appropriate if the relationships across rows are not directly comparable in terms of scale. An intercept, row random effects and row regression effects are not estimable for this model.

Value

| | |
|-------|--|
| BETA | posterior samples of regression coefficients |
| VC | posterior samples of the variance parameters |
| APM | posterior mean of additive row effects a |
| BPM | posterior mean of additive column effects b |
| U | posterior mean of multiplicative row effects u |
| V | posterior mean of multiplicative column effects v (asymmetric case) |
| UVPM | posterior mean of UV |
| ULUPM | posterior mean of ULU (symmetric case) |
| L | posterior mean of L (symmetric case) |
| EZ | estimate of expectation of Z matrix |
| YPM | posterior mean of Y (for imputing missing values) |
| GOF | observed (first row) and posterior predictive (remaining rows) values of four goodness-of-fit statistics |

Author(s)

Peter Hoff, Yanjun He

Examples

```
data(YX_bin_long)
fit<-ame_rep(YX_bin_long$Y,YX_bin_long$X,burn=5,nscan=5,odens=1,family="bin")
# you should run the Markov chain much longer than this
```

cirplot

Circular network plot

Description

Produce a circular network plot.

Usage

```
cirplot(
  Y,
  U = NULL,
  V = NULL,
  row.names = rownames(Y),
  col.names = colnames(Y),
  plotnames = TRUE,
  vscale = 0.8,
  pscale = 1.75,
  mscale = 0.3,
  lcol = "gray",
  rcol = "brown",
  ccol = "blue",
  pch = 16,
  lty = 3,
  jitter = 0.1 * (nrow(Y)/(1 + nrow(Y))),
  bty = "n",
  add = FALSE
)
```

Arguments

| | |
|-----------|--|
| Y | (matrix) m by n relational matrix. |
| U | (matrix) m by 2 matrix of row factors of Y. |
| V | (matrix) n by 2 matrix of column factors of Y. |
| row.names | (character vector) names of the row objects. |
| col.names | (character vector) names of the columns objects. |

| | |
|-----------|---|
| plotnames | (logical) plot row and column names. |
| vscale | (scalar) scaling factor for V coordinates. |
| pscale | (scalar) scaling factor for plotting characters. |
| mscale | (scalar) scaling factor for plotting characters. |
| lcol | (scalar or vector) line color(s) for the nonzero elements of Y. |
| rcol | (scalar or vector) node color(s) for the rows. |
| ccol | (scalar or vector) node color(s) for the columns. |
| pch | (integer) plotting character. |
| lty | (integer) line type. |
| jitter | (scalar) a number to control jittering of nodes. |
| bty | (character) bounding box type. |
| add | (logical) add to existing plot |

Details

This function creates a circle plot of a relational matrix or social network. If not supplied via U and V, two-dimensional row factors and column factors are computed from the SVD of Y, scaled versions of which are used to plot positions on the outside edge (U) and inside edge (V) of the circle plot. The magnitudes of the plotting characters are determined by the magnitudes of the rows of U and V. Segments are drawn between each row object *i* and column object *j* for which $Y[i, j] \neq 0$.

Author(s)

Peter Hoff

Examples

```
data(IR90s)
circplot(IR90s$dyadvars[, , 1])
```

coldwar

Cold War data

Description

Positive and negative relations between countries during the cold war

Format

A list including the following dyadic and nodal variables:

- cc: a socioarray of ordinal levels of military cooperation (positive) and conflict (negative), every 5 years;
- distance: between-country distance (in thousands of kilometers);
- gdp: country gdp in dollars every 5 years;
- polity: country polity every 5 years.

Source

Xun Cao : <https://polisci.la.psu.edu/people/xuc11/>

comtrade

Comtrade data

Description

Eleven years of import and export data between 229 countries. The data use the SITC Rev. 1 commodity classification, aggregated at the first level (AG1).

Format

A list consisting of a socioarray Trade and a vector dollars2010 of inflation rates. The socioarray gives yearly trade volume (exports and imports) in dollars for 10 different commodity classes for eleven years between 229 countries. This gives a five-way array. The first index is the reporting country, so Trade[i, j, t, k, 1] is what i reports for exports to j, but in general this is not the same as Trade[j, i, t, k, 2], what j reports as importing from i.

Source

<https://comtrade.un.org>, <https://www.measuringworth.com>

design_array

Computes the design socioarray of covariate values

Description

Computes the design socioarray of covariate values for an AME fit

Usage

```
design_array(Xrow=NULL, Xcol=NULL, Xdyad=NULL, intercept=TRUE, n)
```

Arguments

| | |
|-----------|--|
| Xrow | an n x pr matrix of row covariates |
| Xcol | an n x pc matrix of column covariates |
| Xdyad | an n x n x pd array of dyadic covariates |
| intercept | logical |
| n | number of rows/columns |

Value

an n x n x (pr+pc+pd+intercept) 3-way array

Author(s)

Peter Hoff

dutchcollege

*Dutch college data***Description**

Longitudinal relational measurements and nodal characteristics of Dutch college students, described in van de Bunt, van Duijn, and Snijders (1999). The time interval between the first four measurements was three weeks, whereas the interval between the last three was six weeks.

Format

A list consisting of a socioarray Y and a matrix X of static nodal attributes. The relational measurements range from -1 to 4, indicating the following:

- -1 a troubled or negative relationship
- 0 don't know
- 1 neutral relationship
- 2 friendly
- 3 friendship
- 4 best friends

Source

Linton Freeman

el2sm

*Edgelist to sociomatrix***Description**

Construction of a sociomatrix from an edgelist

Usage

```
e12sm(e1,directed=TRUE,nadiag=all(e1[,1]!=e1[,2]))
```

Arguments

| | |
|----------|--|
| e1 | a matrix in which each row contains the indices of an edge and possibly the weight for the edge |
| directed | if FALSE, then a relation is placed in both entry ij and ji of the sociomatrix, for each edge ij (or ji) |
| nadiag | put NAs on the diagonal |

Value

a sociomatrix

Author(s)

Peter Hoff

Examples

```
Y<-matrix(rpois(10*10,.5),10,10) ; diag(Y)<-NA
E<-sm2el(Y)
e12sm(E) - Y
```

gofstats

Goodness of fit statistics

Description

Goodness of fit statistics evaluating second and third-order dependence patterns

Usage

```
gofstats(Y)
```

Arguments

Y a relational data matrix

Value

a vector of gof statistics

Author(s)

Peter Hoff

Examples

```
data(YX_nrm)
gofstats(YX_nrm$Y)
```

IR90s

International relations in the 90s

Description

A relational dataset recording a variety of nodal and dyadic variables on countries in the 1990s, including information on conflicts, trade and other variables. Except for the conflict variable, the variables are averages across the decade.

Format

A list consisting of a socioarray dyadvars of dyadic variables and matrix nodevars of nodal variables. The dyadic variables include

- total number of conflicts;
- exports (in billions of dollars);
- distance (in thousands of kilometers);
- number of shared IGOs (averages across the years);
- polity interaction.

The nodal variables include

- population (in millions);
- gdp (in billions of dollars);
- polity

Source

Michael Ward.

lazegalaw

Lazega's law firm data

Description

Several nodal and dyadic variables measured on 71 attorneys in a law firm.

Format

A list consisting of a socioarray Y and a nodal attribute matrix X .

The dyadic variables in Y include three binary networks: advice, friendship and co-worker status.

The categorical nodal attributes in X are coded as follows:

- status (1=partner, 2=associate)
- office (1=Boston, 2=Hartford, 3=Providence)
- practice (1=litigation, 2=corporate)
- law school (1=Harvard or Yale, 2=UConn, 3=other)

seniority and age are given in years, and female is a binary indicator.

Source

Linton Freeman

| | |
|---------|------------------------------------|
| ldZgbme | <i>log density for GBME models</i> |
|---------|------------------------------------|

Description

Calculation of the log conditional density of the latent AMEN matrix Z given observed data Y .

Usage

```
ldZgbme(Z, Y, l1YZ, EZ, rho, s2 = 1)
```

Arguments

| | |
|--------|---|
| Z | $n \times n$ latent relational matrix following an AMEN model |
| Y | $n \times n$ observed relational matrix |
| $l1YZ$ | a vectorizable function taking two arguments, y and z . See details below. |
| EZ | $n \times n$ mean matrix for Z based on AMEN model (including additive effects) |
| ρ | dyadic correlation in AMEN model for Z |
| $s2$ | residual variance in AMEN model for Z |

Details

This function is used for updating dyadic pairs of the latent variable matrix Z based on Y and an AMEN model for Z . The function $l1YZ$ specifies the log likelihood for each single $z[i, j]$ based on $y[i, j]$, that is, $l1YZ$ gives the log probability density (or mass function) of $y[i, j]$ given $z[i, j]$.

Value

a symmetric matrix where entry i, j is proportional to the log conditional bivariate density of $z[i, j], z[j, i]$.

Author(s)

Peter Hoff

Examples

```
## For (overdispersed) Poisson regression, use  
llYZ<-function(y,z){ dpois(y,z,log=TRUE) }
```

| | |
|----------|---|
| llsrmRho | <i>SRM log likelihood evaluated on a grid of rho-values</i> |
|----------|---|

Description

Calculation of the SRM log-likelihood over a grid of rho-values

Usage

```
llsrmRho(Y, Sab, rhos, s2 = 1)
```

Arguments

| | |
|------|---|
| Y | sociomatrix assumed to follow a mean-zero SRM distribution |
| Sab | covariance matrix of additive effects |
| rhos | vector of rho-values at which to calculate the log-likelihood |
| s2 | current value of s2 |

Value

a vector of log-likelihood values

Author(s)

Peter Hoff

| | |
|-------|--|
| mhalf | <i>Symmetric square root of a matrix</i> |
|-------|--|

Description

Computes the symmetric square root of a positive definite matrix

Usage

```
mhalf(M)
```

Arguments

M a positive definite matrix

Value

a matrix H such that H^2 equals M

Author(s)

Peter Hoff

| | |
|---------|-------------------------|
| netplot | <i>Network plotting</i> |
|---------|-------------------------|

Description

Plot the graph of a sociomatrix

Usage

```
netplot(Y,X=NULL,xaxt="n",yaxt="n",xlab="",ylab="",
  lcol="gray",ncol="black",lwd=1,lty=1,pch=16,bty="n",plotnames=FALSE,
  seed=1,
  plot.iso=TRUE,directed=NULL,add=FALSE,...)
```

Arguments

Y a sociomatrix
 X coordinates for plotting the nodes
 yaxt x-axis type
 yaxt y-axis type
 xlab x-axis label

| | |
|-----------|---|
| ylab | y-axis label |
| lcol | edge color |
| ncol | node color (can be node-specific) |
| lwd | line width |
| lty | line type |
| pch | plotting character for nodes (can be node-specific) |
| bty | bounding box type |
| plotnames | plot rownames of Y as node labels |
| seed | random seed |
| plot.iso | include isolates in plot |
| directed | draw arrows |
| add | add to an existing plot region |
| ... | additional plotting parameters |

Author(s)

Peter Hoff

Examples

```
data(addhealthc3)
Y<-addhealthc3$Y
X<-xnet(Y)
netplot(Y,X)
```

plot.ame

Plot results of an AME object

Description

A set of plots summarizing the MCMC routine for an AME fit, as well as some posterior predictive checks.

Usage

```
## S3 method for class 'ame'
plot(x, ...)
```

Arguments

| | |
|-----|------------------------------------|
| x | the result of fitting an AME model |
| ... | additional parameters (not used) |

Value

a series of plots

Author(s)

Peter Hoff

```
precomputeX
```

Precomputation of design matrix quantities.

Description

Computation of a variety of quantities from the design array to be used in MCMC model fitting algorithms.

Usage

```
precomputeX(X)
```

Arguments

X a three way array, the design array for an AME model

Value

the same three-way array but with derived quantities as attributes.

Author(s)

Peter Hoff

```
raSab_bin_fc
```

Simulate a and Sab from full conditional distributions under bin likelihood

Description

Simulate a and Sab from full conditional distributions under bin likelihood

Usage

```
raSab_bin_fc(Z, Y, a, b, Sab, Sab0=NULL, eta0=NULL, SS = round(sqrt(nrow(Z))))
```

Arguments

| | |
|------|---|
| Z | a square matrix, the current value of Z |
| Y | square binary relational matrix |
| a | current value of row effects |
| b | current value of column effects |
| Sab | current value of Cov(a,b) |
| Sab0 | prior (inverse) scale matrix for the prior distribution |
| eta0 | prior degrees of freedom for the prior distribution |
| SS | number of iterations |

Value

| | |
|-----|------------------|
| Z | new value of Z |
| Sab | new value of Sab |
| a | new value of a |

Author(s)

Peter Hoff

| | |
|---------------|---|
| raSab_cbin_fc | <i>Simulate a and Sab from full conditional distributions under the cbin likelihood</i> |
|---------------|---|

Description

Simulate a and Sab from full conditional distributions under the cbin likelihood

Usage

```
raSab_cbin_fc(Z, Y, a, b, Sab, odmax, odobs, Sab0=NULL, eta0=NULL, SS = round(sqrt(nrow(Z))))
```

Arguments

| | |
|-------|---|
| Z | a square matrix, the current value of Z |
| Y | square matrix of ranked nomination data |
| a | current value of row effects |
| b | current value of column effects |
| Sab | current value of Cov(a,b) |
| odmax | a scalar or vector giving the maximum number of nominations for each individual |
| odobs | observed outdegree |
| Sab0 | prior (inverse) scale matrix for the prior distribution |
| eta0 | prior degrees of freedom for the prior distribution |
| SS | number of iterations |

Value

| | |
|-----|------------------|
| Z | new value of Z |
| Sab | new value of Sab |
| a | new value of a |

Author(s)

Peter Hoff

| | |
|--------------|--|
| raSab_frn_fc | <i>Simulate a and Sab from full conditional distributions under frn likelihood</i> |
|--------------|--|

Description

Simulate a and Sab from full conditional distributions under frn likelihood

Usage

```
raSab_frn_fc(Z, Y, YL, a, b, Sab, odmax, odobs, Sab0=NULL, eta0=NULL,
SS=round(sqrt(nrow(Z))))
```

Arguments

| | |
|-------|---|
| Z | a square matrix, the current value of Z |
| Y | square matrix of ranked nomination data |
| YL | list of ranked individuals, from least to most preferred in each row |
| a | current value of row effects |
| b | current value of column effects |
| Sab | current value of Cov(a,b) |
| odmax | a scalar or vector giving the maximum number of nominations for each individual |
| odobs | observed outdegree |
| Sab0 | prior (inverse) scale matrix for the prior distribution |
| eta0 | prior degrees of freedom for the prior distribution |
| SS | number of iterations |

Value

| | |
|-----|------------------|
| Z | new value of Z |
| Sab | new value of Sab |
| a | new value of a |

Author(s)

Peter Hoff

 rbeta_ab_fc

Conditional simulation of additive effects and regression coefficients

Description

Simulates from the joint full conditional distribution of (beta,a,b) in a social relations regression model

Usage

```
rbeta_ab_fc(
  Z,
  Sab,
  rho,
  X = NULL,
  s2 = 1,
  offset = 0,
  iV0 = NULL,
  m0 = NULL,
  g = length(Z)
)
```

Arguments

| | |
|--------|--|
| Z | n X n normal relational matrix |
| Sab | row and column covariance |
| rho | dyadic correlation |
| X | n x n x p covariate array |
| s2 | dyadic variance |
| offset | a matrix of the same dimension as Z. It is assumed that Z-offset follows a SRRM, so the offset should contain any multiplicative effects (such as $U \otimes t(V)$) |
| iV0 | prior precision matrix for regression parameters |
| m0 | prior mean vector for regression parameters |
| g | prior variance scale for g-prior when iV0 is unspecified |

Value

| | |
|------|-------------------------|
| beta | regression coefficients |
| a | additive row effects |
| b | additive column effects |

Author(s)

Peter Hoff

| | |
|-----------------|--|
| rbeta_ab_rep_fc | <i>Gibbs sampling of additive row and column effects and regression coefficient with independent replicate relational data</i> |
|-----------------|--|

Description

Simulates from the joint full conditional distribution of (a,b,beta), assuming same additive row and column effects and regression coefficient across replicates.

Usage

```
rbeta_ab_rep_fc(Z.T, Sab, rho, X.T, s2=1)
```

Arguments

| | |
|-----|--|
| Z.T | n x n x T array, with the third dimension for replicates. Each slice of the array is a (latent) normal relational matrix, with multiplicative effects subtracted out |
| Sab | row and column covariance |
| rho | dyadic correlation |
| X.T | n x n x p x T covariate array |
| s2 | dyadic variance |

Value

| | |
|------|-------------------------|
| beta | regression coefficients |
| a | additive row effects |
| b | additive column effects |

Author(s)

Peter Hoff, Yanjun He

| | |
|---------|---|
| rmvnorm | <i>Simulation from a multivariate normal distribution</i> |
|---------|---|

Description

Simulates a matrix where the rows are i.i.d. samples from a multivariate normal distribution

Usage

```
rmvnorm(n, mu, Sigma, Sigma.chol = chol(Sigma))
```

Arguments

| | |
|------------|---------------------------------|
| n | sample size |
| mu | multivariate mean vector |
| Sigma | covariance matrix |
| Sigma.chol | Cholesky factorization of Sigma |

Value

a matrix with n rows

Author(s)

Peter Hoff

 rrho_fc

Griddy Gibbs update for dyadic correlation

Description

Simulation of dyadic correlation from its approximate full conditional distribution using griddy Gibbs sampling

Usage

```
rrho_fc(Z, Sab, s2 = 1, offset = 0, ngp = 100, asp = NULL)
```

Arguments

| | |
|--------|---|
| Z | n X n normal relational matrix |
| Sab | covariance of additive effects |
| s2 | residual variance |
| offset | matrix of the same dimension as Z. It is assumed that Z-offset follows an SRM distribution, so the offset should contain any regression terms and multiplicative effects (such as $X\beta + U * t(V)$) |
| ngp | the number of points for an unevenly-spaced grid on which to approximate the full conditional distribution |
| asp | use arc sine prior (TRUE) or uniform prior (FALSE) |

Value

a value of rho

Author(s)

Peter Hoff

| | |
|---------|---|
| rrho_mh | <i>Metropolis update for dyadic correlation</i> |
|---------|---|

Description

Metropolis update for dyadic correlation

Usage

```
rrho_mh(Z, rho, s2 = 1, offset=0, asp=NULL)
```

Arguments

| | |
|--------|--|
| Z | n X n normal relational matrix |
| rho | current value of rho |
| s2 | current value of s2 |
| offset | matrix of the same dimension as Z. It is assumed that Z-offset is equal to dyadic noise, so the offset should contain any additive and multiplicative effects (such as $X\beta + U\%*t(V) + \text{outer}(a, b, "+")$) |
| asp | use arc sine prior (TRUE) or uniform prior (FALSE) |

Value

a new value of rho

Author(s)

Peter Hoff

| | |
|-------------|---|
| rrho_mh_rep | <i>Metropolis update for dyadic correlation with independent replicate data</i> |
|-------------|---|

Description

Metropolis update for dyadic correlation with independent replicate data.

Usage

```
rrho_mh_rep(E.T, rho, s2 = 1)
```

Arguments

| | |
|-----|---|
| E.T | Array of square residual relational matrix series. The third dimension of the array is for different replicates. Each slice of the array according to the third dimension is a square residual relational matrix. |
| rho | current value of rho |
| s2 | current value of s2 |

Value

a new value of rho

Author(s)

Peter Hoff, Yanjun He

| | |
|--------|---|
| rs2_fc | <i>Gibbs update for dyadic variance</i> |
|--------|---|

Description

Gibbs update for dyadic variance

Usage

```
rs2_fc(Z, rho, offset=0, nu0=NULL, s20=NULL)
```

Arguments

| | |
|--------|--|
| Z | n X n normal relational matrix |
| rho | current value of rho |
| offset | matrix of the same dimension as Z. It is assumed that Z-offset is equal to dyadic noise, so the offset should contain any additive and multiplicative effects (such as $X\beta + U\%*t(V) + \text{outer}(a, b, "+")$) |
| nu0 | prior degrees of freedom |
| s20 | prior estimate of s2 |

Value

a new value of s2

Author(s)

Peter Hoff

| | |
|------------|--|
| rs2_rep_fc | <i>Gibbs update for dyadic variance with independent replicate relational data</i> |
|------------|--|

Description

Gibbs update for dyadic variance with independent replicate relational data

Usage

```
rs2_rep_fc(E.T, rho)
```

Arguments

| | |
|-----|--|
| E.T | Array of square residual relational matrix series. The third dimension of the array is for different replicates. Each slice of the array according to the third dimension is a square residual relational matrix |
| rho | current value of rho |

Value

a new value of s2

Author(s)

Peter Hoff, Yanjun He

| | |
|---------|---|
| rSab_fc | <i>Gibbs update for additive effects covariance</i> |
|---------|---|

Description

Gibbs update for additive effects covariance

Usage

```
rSab_fc(a, b, Sab0=NULL, eta0=NULL)
```

Arguments

| | |
|------|---|
| a | vector of row random effects |
| b | vector of row random effects |
| Sab0 | prior (inverse) scale matrix for the prior distribution |
| eta0 | prior degrees of freedom for the prior distribution |

Author(s)

Peter Hoff

| | |
|---------|---|
| rSuv_fc | <i>Gibbs update for multiplicative effects covariance</i> |
|---------|---|

Description

Gibbs update for multiplicative effects covariance

Usage

```
rSuv_fc(U,V, Suv0=NULL,kappa0=NULL)
```

Arguments

| | |
|--------|---|
| U | matrix of row random effects |
| V | matrix of row random effects |
| Suv0 | prior (inverse) scale matrix for the prior distribution |
| kappa0 | prior degrees of freedom for the prior distribution |

Author(s)

Peter Hoff

| | |
|--------|----------------------------------|
| rUV_fc | <i>Gibbs sampling of U and V</i> |
|--------|----------------------------------|

Description

A Gibbs sampler for updating the multiplicative effect matrices U and V

Usage

```
rUV_fc(Z, U, V, Suv, rho, s2 = 1, offset = 0)
```

Arguments

| | |
|--------|---|
| Z | n X n normal relational matrix |
| U | current value of U |
| V | current value of V |
| Suv | covariance of (U V) |
| rho | dyadic correlation |
| s2 | dyadic variance |
| offset | a matrix of the same dimension as Z. It is assumed that Z-offset is equal to the multiplicative effects plus dyadic noise, so the offset should contain any additive effects (such as $X\beta + \text{outer}(a,b, "+")$) |

Value

| | |
|---|------------------|
| U | a new value of U |
| V | a new value of V |

Author(s)

Peter Hoff

rUV_rep_fc

Gibbs sampling of U and V

Description

A Gibbs sampler for updating the multiplicative effect matrices U and V, assuming they are the same across replicates.

Usage

```
rUV_rep_fc(E.T,U,V,rho,s2=1,shrink=TRUE)
```

Arguments

| | |
|--------|---|
| E.T | Array of square residual relational matrix series with additive effects and covariates subtracted out. The third dimension of the array is for different replicates. Each slice of the array according to the third dimension is a square residual relational matrix. |
| U | current value of U |
| V | current value of V |
| rho | dyadic correlation |
| s2 | dyadic variance |
| shrink | adaptively shrink the factors with a hierarchical prior |

Value

| | |
|---|------------------|
| U | a new value of U |
| V | a new value of V |

Author(s)

Peter Hoff, Yanjun He

| | |
|------------|----------------------------------|
| rUV_sym_fc | <i>Gibbs sampling of U and V</i> |
|------------|----------------------------------|

Description

A Gibbs sampler for updating the multiplicative effect matrices U and V in the symmetric case. In this case $U\%*\%t(V)$ is symmetric, so this is parameterized as $V=U\%*\%L$ where L is the diagonal matrix of eigenvalues of $U\%*\%t(V)$.

Usage

```
rUV_sym_fc(E, U, V, s2 = 1, shrink=TRUE)
```

Arguments

| | |
|--------|---|
| E | square residual relational matrix |
| U | current value of U |
| V | current value of V |
| s2 | dyadic variance |
| shrink | adaptively shrink the factors with a hierarchical prior |

Value

| | |
|---|------------------|
| U | a new value of U |
| V | a new value of V |

Author(s)

Peter Hoff

Examples

```
U0<-matrix(rnorm(30,2),30,2) ; V0<-U0%*\%diag(c(3,-2))
E<- U0%*\%t(V0) + matrix(rnorm(30^2),30,30)
rUV_sym_fc
```

rwish

Simulation from a Wishart distribution

Description

Simulates a random Wishart-distributed matrix

Usage

```
rwish(S0, nu = dim(S0)[1] + 2)
```

Arguments

`S0` a positive definite matrix
`nu` a positive integer

Value

a positive definite matrix

Author(s)

Peter Hoff

Examples

```
## The expectation is S0*nu  
S0<-rwish(diag(3))  
  
SS<-matrix(0,3,3)  
for(s in 1:1000) { SS<-SS+rwish(S0,5) }  
  
SS/s  
  
S0*5
```

| | |
|-----------|---|
| rZ_bin_fc | <i>Simulate Z based on a probit model</i> |
|-----------|---|

Description

Simulates a random latent matrix Z given its expectation, dyadic correlation and a binary relational matrix Y

Usage

`rZ_bin_fc(Z, EZ, rho, Y)`

Arguments

| | |
|--------|---|
| Z | a square matrix, the current value of Z |
| EZ | expected value of Z |
| ρ | dyadic correlation |
| Y | square binary relational matrix |

Value

a square matrix , the new value of Z

Author(s)

Peter Hoff

| | |
|------------|--|
| rZ_cbin_fc | <i>Simulate Z given fixed rank nomination data</i> |
|------------|--|

Description

Simulates a random latent matrix Z given its expectation, dyadic correlation and censored binary nomination data

Usage

`rZ_cbin_fc(Z, EZ, rho, Y, odmax, odobs)`

Arguments

| | |
|-------|---|
| Z | a square matrix, the current value of Z |
| EZ | expected value of Z |
| rho | dyadic correlation |
| Y | square matrix of ranked nomination data |
| odmax | a scalar or vector giving the maximum number of nominations for each individual |
| odobs | observed outdegree |

Details

simulates Z under the constraints (1) $Y[i,j]=1, Y[i,k]=0 \Rightarrow Z[i,j]>Z[i,k]$, (2) $Y[i,j]=1 \Rightarrow Z[i,j]>0$, (3) $Y[i,j]=0 \ \& \ odobs[i]<odmax[i] \Rightarrow Z[i,j]<0$

Value

a square matrix, the new value of Z

Author(s)

Peter Hoff

rZ_frn_fc

Simulate Z given fixed rank nomination data

Description

Simulates a random latent matrix Z given its expectation, dyadic correlation and fixed rank nomination data

Usage

rZ_frn_fc(Z, EZ, rho, Y, YL, odmax, odobs)

Arguments

| | |
|-------|---|
| Z | a square matrix, the current value of Z |
| EZ | expected value of Z |
| rho | dyadic correlation |
| Y | square matrix of ranked nomination data |
| YL | list of ranked individuals, from least to most preferred in each row |
| odmax | a scalar or vector giving the maximum number of nominations for each individual |
| odobs | observed outdegree |

Details

simulates Z under the constraints (1) $Y[i,j] > Y[i,k] \Rightarrow Z[i,j] > Z[i,k]$, (2) $Y[i,j] > 0 \Rightarrow Z[i,j] > 0$, (3) $Y[i,j] = 0 \ \& \ odobs[i] < odmax[i] \Rightarrow Z[i,j] < 0$

Value

a square matrix, the new value of Z

Author(s)

Peter Hoff

rZ_nrm_fc

Simulate missing values in a normal AME model

Description

Simulates missing values of a sociomatrix under a normal AME model

Usage

```
rZ_nrm_fc(Z, EZ, rho, s2, Y)
```

Arguments

| | |
|-----|---|
| Z | a square matrix, the current value of Z |
| EZ | expected value of Z |
| rho | dyadic correlation |
| s2 | dyadic variance |
| Y | square relational matrix |

Value

a square matrix, equal to Y at non-missing values

Author(s)

Peter Hoff

rZ_ord_fc *Simulate Z given the partial ranks*

Description

Simulates a random latent matrix Z given its expectation, dyadic correlation and partial rank information provided by W

Usage

rZ_ord_fc(Z , EZ , ρ , Y)

Arguments

| | |
|--------|---|
| Z | a square matrix, the current value of Z |
| EZ | expected value of Z |
| ρ | dyadic correlation |
| Y | matrix of ordinal data |

Value

a square matrix, the new value of Z

Author(s)

Peter Hoff

rZ_rrl_fc *Simulate Z given relative rank nomination data*

Description

Simulates a random latent matrix Z given its expectation, dyadic correlation and relative rank nomination data

Usage

rZ_rrl_fc(Z , EZ , ρ , Y , YL)

Arguments

| | |
|--------|--|
| Z | a square matrix, the current value of Z |
| EZ | expected value of Z |
| ρ | dyadic correlation |
| Y | square matrix of ranked nomination data |
| YL | list of ranked individuals, from least to most preferred in each row |

Details

simulates Z under the constraints (1) $Y[i,j] > Y[i,k] \Rightarrow Z[i,j] > Z[i,k]$

Value

a square matrix, the new value of Z

Author(s)

Peter Hoff

rZ_tob_fc

Simulate Z based on a tobit model

Description

Simulates a random latent matrix Z given its expectation, dyadic correlation and a nonnegative relational matrix Y

Usage

`rZ_tob_fc(Z, EZ, rho, s2, Y)`

Arguments

| | |
|--------|---|
| Z | a square matrix, the current value of Z |
| EZ | expected value of Z |
| ρ | dyadic correlation |
| $s2$ | dyadic variance |
| Y | square relational matrix with nonnegative entries |

Value

a square matrix, the new value of Z

Author(s)

Peter Hoff

 sampsonmonks

Sampson's monastery data

Description

Several dyadic variables measured on 18 members of a monastery.

Format

A socioarray whose dimensions represent nominators, nominatees and relations. Each monk was asked to rank up to three other monks on a variety of positive and negative relations. A rank of three indicates the "highest" ranking for a particular relational variable. The relations like_m2 and like_m1 are evaluations of likeing at one and two timepoints previous to when the other relations were measured.

Source

Linton Freeman

 sheep

Sheep dominance data

Description

Number of dominance encounters between 28 female bighorn sheep. Cell (i,j) records the number of times sheep i dominated sheep j. From Hass (1991).

Format

A list consisting of the following:

- dom: a directed socioarray recording the number of dominance encounters.
- age: the age of each sheep in years.

Source

Linton Freeman

| | |
|----------|--|
| simY_bin | <i>Simulate a network, i.e. a binary relational matrix</i> |
|----------|--|

Description

Simulates a network, i.e. a binary relational matrix

Usage

```
simY_bin(EZ, rho)
```

Arguments

| | |
|-----|--|
| EZ | square matrix giving the expected value of the latent Z matrix |
| rho | dyadic correlation |

Value

a square binary matrix

Author(s)

Peter Hoff

| | |
|----------|--|
| simY_frn | <i>Simulate an relational matrix based on a fixed rank nomination scheme</i> |
|----------|--|

Description

Simulate an relational matrix based on a fixed rank nomination scheme

Usage

```
simY_frn(EZ, rho, odmax, Y0)
```

Arguments

| | |
|-------|---|
| EZ | a square matrix giving the expected value of the latent Z matrix |
| rho | dyadic correlation |
| odmax | a scalar or vector giving the maximum number of nominations for each node |
| Y0 | a square matrix identifying where missing values should be maintained |

Value

a square matrix, where higher values represent stronger relationships

Author(s)

Peter Hoff

`simY_nrm`*Simulate a normal relational matrix*

Description

Simulates a normal relational matrix

Usage`simY_nrm(EY, rho, s2)`**Arguments**

| | |
|------------------|--|
| <code>EY</code> | square matrix giving the expected value of the relational matrix |
| <code>rho</code> | dyadic correlation |
| <code>s2</code> | dyadic variance |

Value

a square matrix

Author(s)

Peter Hoff

`simY_ord`*Simulate an ordinal relational matrix*

Description

Simulates an ordinal relational matrix having a particular marginal distribution

Usage`simY_ord(EZ, rho, Y)`**Arguments**

| | |
|------------------|--|
| <code>EZ</code> | square matrix giving the expected value of the latent Z matrix |
| <code>rho</code> | scalar giving the within-dyad correlation |
| <code>Y</code> | ordinal relational data matrix |

Value

a square matrix

Author(s)

Peter Hoff

| | |
|----------|---|
| simY_rrl | <i>Simulate an relational matrix based on a relative rank nomination scheme</i> |
|----------|---|

Description

Simulate an relational matrix based on a relative rank nomination scheme

Usage

```
simY_rrl(EZ, rho, odobs, Y0)
```

Arguments

| | |
|-------|--|
| EZ | a square matrix giving the expected value of the latent Z matrix |
| rho | dyadic correlation |
| odobs | a scalar or vector giving the observed number of nominations for each node |
| Y0 | a square matrix identifying where missing values should be maintained |

Value

a square matrix, where higher values represent stronger relationships

Author(s)

Peter Hoff

simY_tob *Simulate a tobit relational matrix*

Description

Simulates a tobit relational matrix

Usage

```
simY_tob(EY, rho, s2)
```

Arguments

| | |
|-----|--|
| EY | square matrix giving the expected value of the relational matrix |
| rho | dyadic correlation |
| s2 | dyadic variance |

Value

a square matrix

Author(s)

Peter Hoff

simZ *Simulate Z given its expectation and covariance*

Description

Simulate Z given its expectation and covariance

Usage

```
simZ(EZ, rho, s2 = 1)
```

Arguments

| | |
|-----|---------------------|
| EZ | expected value of Z |
| rho | dyadic correlation |
| s2 | dyadic variance |

Value

a simulated value of Z

Author(s)

Peter Hoff

| | |
|-------|--------------------------------|
| sm2el | <i>Sociomatrix to edgelist</i> |
|-------|--------------------------------|

Description

Construction of an edgelist from a sociomatrix

Usage`sm2el(sm,directed=TRUE)`**Arguments**

| | |
|-----------------------|--|
| <code>sm</code> | a sociomatrix with possibly valued relations |
| <code>directed</code> | if TRUE, only use the upper triangular part of the matrix to enumerate edges |

Value

an edgelist

Author(s)

Peter Hoff

Examples

```
Y<-matrix(rpois(10*10,.5),10,10) ; diag(Y)<-NA
E<-sm2el(Y)
e12sm(E) - Y
```

| | |
|-------------|---------------------------------|
| summary.ame | <i>Summary of an AME object</i> |
|-------------|---------------------------------|

Description

Summary method for an AME object

Usage

```
## S3 method for class 'ame'
summary(object, ...)
```

Arguments

object the result of fitting an AME model
 ... additional parameters (not used)

Value

a summary of parameter estimates and confidence intervals for an AME fit

Author(s)

Peter Hoff

Xbeta

Linear combinations of submatrices of an array

Description

Computes a matrix of expected values based on an array X of predictors and a vector beta of regression coefficients.

Usage

Xbeta(X, beta)

Arguments

X an n by n by p array
 beta a p by 1 vector

Value

An n by n matrix

Author(s)

Peter Hoff

xnet

Network embedding

Description

Compute an embedding of a sociomatrix into a two-dimensional space.

Usage

```
xnet(  
  Y,  
  fm = try(requireNamespace("network", quietly = TRUE), silent = TRUE),  
  seed = 1  
)
```

Arguments

| | |
|------|--|
| Y | (square matrix) The sociomatrix. |
| fm | (logical scalar) If TRUE, the Fruchterman-Reingold layout will be used (requires the network package). |
| seed | (integer) The random seed (the FR layout is random). |

Details

Coordinates are obtained using the Fruchterman-Reingold layout if the package network is installed, and otherwise uses the first two eigenvectors the sociomatrix.

Value

(matrix) A matrix of two-dimensional coordinates.

Author(s)

Peter Hoff

Examples

```
data(addhealthc3)  
Y<-addhealthc3$Y  
X<-xnet(Y)  
netplot(Y,X)
```

| | |
|--------|--|
| YX_bin | <i>binary relational data and covariates</i> |
|--------|--|

Description

a synthetic dataset that includes binary relational data as well as information on eight covariates

Usage

```
data(YX_bin)
```

Format

The format is: List of 2 \$ Y: num [1:100, 1:100] NA 0 0 0 0 0 0 0 1 ... \$ X: num [1:100, 1:100, 1:8] 1 1 1 1 1 1 1 1 1 1- attr(*, "dimnames")=List of 3\$: NULL\$: NULL\$: chr [1:8] "intercept" "rgpa" "rsmoke" "cgpa" ...

Examples

```
data(YX_bin)
gofstats(YX_bin$Y)
```

| | |
|-------------|--|
| YX_bin_long | <i>binary relational data and covariates</i> |
|-------------|--|

Description

a synthetic dataset that includes longitudinal binary relational data as well as information on covariates

Usage

```
data(YX_bin_long)
```

Format

a list

Examples

```
data(YX_bin_long)
gofstats(YX_bin_long$Y[, , 1])
```

| | |
|---------|---|
| YX_cbin | <i>Censored binary nomination data and covariates</i> |
|---------|---|

Description

a synthetic dataset that includes relational data where the number of nominations per row is censored at 10, along with information on eight covariates

Usage

```
data(YX_cbin)
```

Format

The format is: List of 2 \$ Y: num [1:100, 1:100] NA 0 0 0 1 0 0 0 0 3 ... \$ X: num [1:100, 1:100, 1:8] 1 1 1 1 1 1 1 1 1 1- attr(*, "dimnames")=List of 3\$: NULL\$: NULL\$: chr [1:8] "intercept" "rgpa" "rsmoke" "cgpa" ...

Examples

```
data(YX_cbin)
gofstats(YX_cbin$Y)
```

| | |
|--------|--|
| YX_frn | <i>Fixed rank nomination data and covariates</i> |
|--------|--|

Description

a synthetic dataset that includes fixed rank nomination data as well as information on eight covariates

Usage

```
data(YX_frn)
```

Format

The format is: List of 2 \$ Y: num [1:100, 1:100] NA 0 0 0 1 0 0 0 0 3 ... \$ X: num [1:100, 1:100, 1:8] 1 1 1 1 1 1 1 1 1 1- attr(*, "dimnames")=List of 3\$: NULL\$: NULL\$: chr [1:8] "intercept" "rgpa" "rsmoke" "cgpa" ...

Examples

```
data(YX_frn)
gofstats(YX_frn$Y)
```

| | |
|--------|--|
| YX_nrm | <i>normal relational data and covariates</i> |
|--------|--|

Description

a synthetic dataset that includes continuous (normal) relational data as well as information on eight covariates

Usage

```
data(YX_nrm)
```

Format

The format is: List of 2 \$ Y: num [1:100, 1:100] NA -4.05 -0.181 -3.053 -1.579 ... \$ X: num [1:100, 1:100, 1:8] 1 1 1 1 1 1 1 1 1- attr(*, "dimnames")=List of 3\$: NULL\$: NULL\$: chr [1:8] "intercept" "rgpa" "rsmoke" "cgpa" ...

Examples

```
data(YX_nrm)
gofstats(YX_nrm$Y)
```

| | |
|--------|---|
| YX_ord | <i>ordinal relational data and covariates</i> |
|--------|---|

Description

a synthetic dataset that includes ordinal relational data as well as information on seven covariates

Usage

```
data(YX_ord)
```

Format

The format is: List of 2 \$ Y: num [1:100, 1:100] NA 0 3 0 3 1 0 1 1 0 ... \$ X: num [1:100, 1:100, 1:7] 1 1 1 1 1 1 1 1 1- attr(*, "dimnames")=List of 3\$: NULL\$: NULL\$: chr [1:7] "rgpa" "rsmoke" "cgpa" "csmoke" ...

Examples

```
data(YX_ord)
gofstats(YX_ord$Y)
```

| | |
|--------|--|
| YX_rr1 | <i>row-specific ordinal relational data and covariates</i> |
|--------|--|

Description

a synthetic dataset that includes row-specific ordinal relational data as well as information on five covariates

Usage

```
data(YX_rr1)
```

Format

The format is: List of 2 \$ Y: num [1:100, 1:100] NA 0 3 0 3 1 0 1 1 0 ... \$ X: num [1:100, 1:100, 1:5] 1 1 1 1 1 1 1 1 1 1- attr(*, "dimnames")=List of 3\$: NULL\$: NULL\$: chr [1:5] "cgpa" "csmoke" "igrade" "ismoke" ...

Examples

```
data(YX_rr1)
gofstats(YX_rr1$Y)
```

| | |
|---------|----------------------------|
| zscores | <i>rank-based z-scores</i> |
|---------|----------------------------|

Description

Computes the normal scores corresponding to the ranks of a data vector

Usage

```
zscores(y, ties.method="average")
```

Arguments

| | |
|-------------|------------------------------|
| y | a numeric vector |
| ties.method | method for dealing with ties |

Value

a numeric vector

Author(s)

Peter Hoff

Index

- * **datasets**
 - addhealthc3, 4
 - addhealthc9, 5
 - YX_bin, 46
 - YX_bin_long, 46
 - YX_cbin, 47
 - YX_frn, 47
 - YX_nrm, 48
 - YX_ord, 48
 - YX_rr1, 49
- * **package**
 - amen-package, 3
- addhealthc3, 4
- addhealthc9, 5
- addlines, 5
- ame, 6
- ame_rep, 8
- amen (amen-package), 3
- amen-package, 3
- circplot, 10
- coldwar, 11
- comtrade, 12
- design_array, 12
- dutchcollege, 13
- e12sm, 13
- gofstats, 14
- IR90s, 15
- lazegalaw, 15
- ldZgbme, 16
- llsrmRho, 17
- mhalf, 18
- netplot, 18
- plot.ame, 19
- precomputeX, 20
- raSab_bin_fc, 20
- raSab_cbin_fc, 21
- raSab_frn_fc, 22
- rbeta_ab_fc, 23
- rbeta_ab_rep_fc, 24
- rmvnorm, 24
- rrho_fc, 25
- rrho_mh, 26
- rrho_mh_rep, 26
- rs2_fc, 27
- rs2_rep_fc, 28
- rSab_fc, 28
- rSuv_fc, 29
- rUV_fc, 29
- rUV_rep_fc, 30
- rUV_sym_fc, 31
- rwish, 32
- rZ_bin_fc, 33
- rZ_cbin_fc, 33
- rZ_frn_fc, 34
- rZ_nrm_fc, 35
- rZ_ord_fc, 36
- rZ_rr1_fc, 36
- rZ_tob_fc, 37
- sampsonmonks, 38
- sheep, 38
- simY_bin, 39
- simY_frn, 39
- simY_nrm, 40
- simY_ord, 40
- simY_rr1, 41
- simY_tob, 42
- simZ, 42
- sm2e1, 43
- summary.ame, 43

Xbeta, [44](#)
xnet, [45](#)

YX_bin, [46](#)
YX_bin_long, [46](#)
YX_cbin, [47](#)
YX_frn, [47](#)
YX_nrm, [48](#)
YX_ord, [48](#)
YX_rr1, [49](#)

zscores, [49](#)