

Package ‘badger’

May 7, 2026

Title Badge for R Package

Version 0.2.5

Description Query information and generate badge for using in README and GitHub Pages.

Depends R (>= 3.3.0)

Imports dlstats, rvcheck, desc, usethis (>= 2.0.0)

Suggests testthat (>= 2.0.0)

License Artistic-2.0

ByteCompile true

URL <https://github.com/GuangchuangYu/badger>

BugReports <https://github.com/GuangchuangYu/badger/issues>

Encoding UTF-8

RoxygenNote 7.3.2

NeedsCompilation no

Author Guangchuang Yu [aut, cre] (ORCID:

<https://orcid.org/0000-0002-6485-8781>),

Gregor de Cillia [ctb],

Dirk Eddelbuettel [ctb],

Maëlle Salmon [ctb],

Robrecht Cannoodt [ctb] (ORCID:

<https://orcid.org/0000-0003-3641-729X>), github: rcannood),

Alexander Rossell Hayes [ctb] (ORCID:

<https://orcid.org/0000-0001-9412-0457>), github: rossellhayes),

Waldir Leoncio [ctb],

Matthew Schuelke [ctb] (ORCID: <https://orcid.org/0000-0001-5755-1725>),

github: the-mad-statter)

Maintainer Guangchuang Yu <guangchuangyu@gmail.com>

Repository CRAN

Date/Publication 2025-07-31 18:32:03 UTC

Contents

badge_altmetric	2
badge_bioc_download	3
badge_bioc_download_rank	4
badge_bioc_release	4
badge_codecov	5
badge_codefactor	6
badge_code_size	6
badge_coveralls	7
badge_cran_checks	7
badge_cran_download	8
badge_cran_release	9
badge_custom	9
badge_dependencies	10
badge_devel	10
badge_doi	11
badge_github_actions	12
badge_github_release	12
badge_github_version	13
badge_last_commit	13
badge_license	14
badge_lifecycle	15
badge_repostatus	15
badge_runiverse	16
badge_sci_citation	16
badge_travis	17
gitaward	18
ver_devel	18
Index	19

badge_altmetric	<i>badge_altmetric</i>
-----------------	------------------------

Description

altmetric badge

Usage

```
badge_altmetric(id, color, alt = NULL)
```

Arguments

id	altmetric id
color	color of badge
alt	Alternative text

Value

badge in markdown syntax

Author(s)

Guangchuang Yu

Examples

```
## Not run:  
badge_altmetric("2788597", "blue")  
  
## End(Not run)
```

`badge_bioc_download` *badge_bioc_download*

Description

badge of bioconductor download number

Usage

```
badge_bioc_download(pkg = NULL, by, color, type = "distinct", alt = NULL)
```

Arguments

<code>pkg</code>	package. If NULL (the default) the package is determined via the DESCRIPTION file.
<code>by</code>	one of total or month
<code>color</code>	badge color
<code>type</code>	one of distinct and total
<code>alt</code>	Alternative text

Value

badge in markdown syntax

Author(s)

Guangchuang Yu

badge_bioc_download_rank
badge_bioc_download_rank

Description

official Bioconductor download badge (download ranking)

Usage

```
badge_bioc_download_rank(pkg = NULL, alt = "download")
```

```
badge_download_bioc(pkg = NULL, alt = "download")
```

Arguments

pkg	package. If NULL (the default) the package is determined via the DESCRIPTION file.
alt	Alternative text

Value

bioc download ranking badge

Author(s)

Guangchuang Yu

badge_bioc_release *badge_bioc_release*

Description

badge of bioconductor release version

Usage

```
badge_bioc_release(pkg = NULL, color, alt = NULL)
```

Arguments

pkg	package. If NULL (the default) the package is determined via the DESCRIPTION file.
color	badge color
alt	Alternative text

Value

badge in markdown syntax

Author(s)

Guangchuang Yu

badge_codecov	<i>badge_codecov</i>
---------------	----------------------

Description

badge of codecov code coverage

Usage

badge_codecov(ref = NULL, token = NULL, branch = NULL, alt = NULL)

Arguments

- ref Reference for a GitHub repository. If NULL (the default), the reference is determined by the URL field in the DESCRIPTION file.
- token Codecov graphing token, needed for private repositories. It can be obtained at <https://codecov.io/gh/USER/REPO/branch/BRANCH/graph/>
- branch The GitHub branch. If NULL (the default), the default branch is automatically determined.
- alt Alternative text

Value

badge in markdown syntax

Author(s)

Gregor de Cillia

badge_codefactor	<i>CodeFactor badge</i>
------------------	-------------------------

Description

CodeFactor badge

Usage

```
badge_codefactor(ref = NULL, alt = "CodeFactor")
```

Arguments

ref	Reference for a GitHub repository. If NULL (the default), the reference is determined by the URL field in the DESCRIPTION file.
alt	Alternative text

Value

badge in markdown syntax

Author(s)

Alexander Rossell Hayes

badge_code_size	<i>badge_code_size</i>
-----------------	------------------------

Description

badge of GitHub code size

Usage

```
badge_code_size(ref = NULL, alt = NULL)
```

Arguments

ref	Reference for a GitHub repository. If NULL (the default), the reference is determined by the URL field in the DESCRIPTION file.
alt	Alternative text

Value

badge in markdown syntax

Author(s)

Gregor de Cillia

badge_coveralls *badge_coveralls*

Description

badge of coveralls code coverage

Usage

badge_coveralls(ref = NULL, branch = NULL, alt = NULL)

Arguments

- ref Reference for a GitHub repository. If NULL (the default), the reference is determined by the URL field in the DESCRIPTION file.
- branch The GitHub branch. If NULL (the default), the default branch is automatically determined.
- alt Alternative text

Value

badge in markdown syntax

Author(s)

Gregor de Cillia

badge_cran_checks *badge_cran_checks*

Description

CRAN checks badge

Usage

badge_cran_checks(pkg = NULL, worst = FALSE, alt = "CRAN checks")

Arguments

pkg	package. If NULL (the default) the package is determined via the DESCRIPTION file.
worst	logical; if FALSE (default) return "summary" badge. If TRUE, return "worst" badge.
alt	Alternative text

Value

badge in Markdown syntax

Author(s)

Scott Chamberlain (badges API), Maëlle Salmon (function)

badge_cran_download *badge_cran_download*

Description

badge of CRAN downloads

Usage

```
badge_cran_download(
  pkg = NULL,
  type = c("last-month", "last-week", "grand-total"),
  color = NULL,
  alt = NULL
)
```

Arguments

pkg	package. If NULL (the default) the package is determined via the DESCRIPTION file.
type	type of stats. last-month, last-week or "grand-total"
color	color of badge
alt	Alternative text

Value

badge in markdown syntax

Author(s)

Gregor de Cillia

badge_cran_release *badge_cran_release*

Description

badge of CRAN version

Usage

```
badge_cran_release(pkg = NULL, color = NULL, alt = NULL)
```

Arguments

pkg	package. If NULL (the default) the package is determined via the DESCRIPTION file.
color	color of badge
alt	Alternative text

Value

badge in markdown syntax

Author(s)

Gregor de Cillia

badge_custom *badge_custom*

Description

custom badge

Usage

```
badge_custom(x, y, color, url = NULL, alt = NULL)
```

Arguments

x	field 1
y	field 2
color	color
url	optional url
alt	Alternative text

Value

customize badge

Author(s)

Guangchuang Yu

badge_dependencies	<i>badge_depedencies</i>
--------------------	--------------------------

Description

dependency badge

Usage

```
badge_dependencies(pkg = NULL, alt = "Dependencies")
```

Arguments

pkg	package. If NULL (the default) the package is determined via the DESCRIPTION file.
alt	Alternative text

Value

badge in markdown syntax

Author(s)

Dirk Eddelbuettel

badge_devel	<i>badge_devel</i>
-------------	--------------------

Description

badge of devel version

Usage

```
badge_devel(pkg = NULL, color, alt = NULL)
```

Arguments

pkg	package. If NULL (the default) the package is determined via the DESCRIPTION file.
color	badge color
alt	Alternative text

Value

badge in markdown syntax

badge_doi	<i>badge_doi</i>
-----------	------------------

Description

doi badge

Usage

```
badge_doi(doi, color, alt = NULL)
```

Arguments

doi	doi
color	color
alt	Alternative text

Value

badge

Author(s)

Guangchuang Yu

Examples

```
badge_doi("10.1111/2041-210X.12628", "green")
```

badge_github_actions *GitHub Actions badge*

Description

GitHub Actions badge

Usage

```
badge_github_actions(  
  ref = NULL,  
  action = "R-CMD-check",  
  alt = "R build status"  
)
```

Arguments

ref	Reference for a GitHub repository. If NULL (the default), the reference is determined by the URL field in the DESCRIPTION file.
action	The name of the GitHub actions workflow. Defaults to "R-CMD-CHECK".
alt	Alternative text

Value

badge in markdown syntax

Author(s)

Alexander Rossell Hayes

badge_github_release *GitHub Release badge*

Description

GitHub Release badge

Usage

```
badge_github_release(ref = NULL, alt = NULL)
```

Arguments

ref	Reference for a GitHub repository. If NULL (the default), the reference is determined by the URL field in the DESCRIPTION file.
alt	Alternative text

Value

badge in markdown syntax

Author(s)

Matt Schuelke

badge_github_version *badge_github_version*

Description

badge of devel version

Usage

badge_github_version(pkg = NULL, color, alt = NULL)

Arguments

pkg	package. If NULL (the default) the package is determined via the DESCRIPTION file.
color	badge color
alt	Alternative text

Value

badge in markdown syntax

Author(s)

Guangchuang Yu

badge_last_commit *badge_last_commit*

Description

last commit badge

Usage

badge_last_commit(ref = NULL, branch = NULL, alt = NULL)

Arguments

ref	Reference for a GitHub repository. If NULL (the default), the reference is determined by the URL field in the DESCRIPTION file.
branch	The GitHub branch. If NULL (the default), the default branch is automatically determined.
alt	Alternative text

Value

badge in markdown syntax

Author(s)

Gregor de Cillia

badge_license	<i>License badge</i>
---------------	----------------------

Description

License badge

Usage

```
badge_license(
  license = NULL,
  color = "blue",
  url = NULL,
  alt = paste("License:", license)
)
```

Arguments

license	The license to use. If NULL (the default), the license is determined via the DESCRIPTION file.
color	badge color
url	The URL of the LICENSE text. If NULL (the default), links to the CRAN Package License page. This leads to a broken link if package uses a non-CRAN compatible license.
alt	Alternative text

Value

badge in markdown syntax

Author(s)

Alexander Rossell Hayes

badge_lifecycle	<i>badge_lifecycle</i>
-----------------	------------------------

Description

lifecycle badge

Usage

```
badge_lifecycle(stage = "experimental", color = NULL, alt = NULL)
```

Arguments

stage	lifecycle stage See https://lifecycle.r-lib.org/articles/stages.html
color	color of the badge. If missing, the color is determined by the stage.
alt	Alternative text

Value

badge in markdown syntax

Author(s)

Gregor de Cillia, Waldir Leoncio

badge_repostatus	<i>badge_repostatus</i>
------------------	-------------------------

Description

repostatus.org badge

Usage

```
badge_repostatus(status, alt = NULL)
```

Arguments

status	project status (Concept, WIP, Suspended, Abandoned, Active, Inactive, Unsupported, Moved). See https://www.repostatus.org/lifecycle for more details.
alt	Alternative text

Value

badge in markdown syntax

Author(s)

Waldir Leoncio

 badge_runiverse *r-universe badge*

Description

r-universe badge

Usage

```
badge_runiverse(pkg = NULL, user = NULL, alt = "r-universe status badge")
```

Arguments

pkg	Package name. If NULL (the default), the name is determined by the URL field in the DESCRIPTION file.
user	User name. If NULL (the default), the name is determined by the URL field in the DESCRIPTION file.
alt	Alternative text

Value

badge in markdown syntax

Author(s)

Alexander Rossell Hayes

 badge_sci_citation *badge_sci_citation*

Description

SCI citation badge

Usage

```
badge_sci_citation(url, color, alt = NULL)
```

Arguments

url	Web of Science url
color	color of badge
alt	Alternative text

Value

badge in markdown syntax

Author(s)

Guangchuang Yu

badge_travis	<i>badge_travis</i>
--------------	---------------------

Description

travis-ci badge

Usage

```
badge_travis(ref = NULL, is_commercial = FALSE, branch = NULL, alt = NULL)
```

Arguments

ref	Reference for a GitHub repository. If NULL (the default), the reference is determined by the URL field in the DESCRIPTION file.
is_commercial	Flag to indicate whether or not to use https://travis-ci.com
branch	The GitHub branch. If NULL (the default), the default branch is automatically determined.
alt	Alternative text

Value

badge in markdown syntax

Author(s)

Gregor de Cillia

gitaward	<i>gitaward</i>
----------	-----------------

Description

git award rank

Usage

```
gitaward(user = "guangchuangyu", lang)
```

Arguments

user	user
lang	language

Value

rank

Author(s)

Guangchuang Yu

ver_devel	<i>ver_devel</i>
-----------	------------------

Description

get devel version number of specific package

Usage

```
ver_devel(pkg = NULL)
```

Arguments

pkg	package. If NULL (the default) the package is determined via the DESCRIPTION file.
-----	--

Value

devel version

Author(s)

Guangchuang Yu

Index

badge_altmetric, 2
badge_bioc_download, 3
badge_bioc_download_rank, 4
badge_bioc_release, 4
badge_code_size, 6
badge_codecov, 5
badge_codefactor, 6
badge_coveralls, 7
badge_cran_checks, 7
badge_cran_download, 8
badge_cran_release, 9
badge_custom, 9
badge_dependencies, 10
badge_devel, 10
badge_doi, 11
badge_download_bioc
 (badge_bioc_download_rank), 4
badge_github_actions, 12
badge_github_release, 12
badge_github_version, 13
badge_last_commit, 13
badge_license, 14
badge_lifecycle, 15
badge_repostatus, 15
badge_runiverse, 16
badge_sci_citation, 16
badge_travis, 17

gitaward, 18

ver_devel, 18