

Package ‘birdring’

May 7, 2026

Type Package

Title Methods to Analyse Ring Re-Encounter Data

Version 1.6

Date 2023-10-02

Author Fraenzi Korner-Nievergelt, Rob Robinson

Maintainer Fraenzi Korner-Nievergelt <fraenzi.korner@vogelwarte.ch>

Depends R (>= 2.10.1), stats

Imports geosphere, ks, lazyData, raster, methods, graphics

Description R functions to read EURING data and analyse re-encounter data of birds marked by metal rings. For a tutorial, go to <[doi:10.1080/03078698.2014.933053](https://doi.org/10.1080/03078698.2014.933053)>.

License GPL-2

LazyLoad yes

LazyData TRUE

NeedsCompilation no

Repository CRAN

Date/Publication 2023-10-07 14:10:02 UTC

Contents

birdring-package	2
birdstate	3
circumstances	4
coastEU	5
coastpaleo	6
codes2names	7
conditions	8
critical.check.ringing.event	9
dayofyear	9
dc	10
decimal.coord	12

dmvnorm	12
draw.map	13
lancol	15
loxodrom	16
mdy.date	17
mercatorlat	18
orthodrom.dist	19
overlap	20
place2name	22
places	22
read.euring2000	23
read.euring2000plus	25
scheme2country	27
schemes	28
species	29

Index 30

birdring-package	<i>Methods to Analyse Bird Ring Reencounter data</i>
------------------	--

Description

This package is a collection of functions or methods used to analyse ring reencounter data. Its purpose is to read EURING ring reencounter data into R, and to help mapping and analysing reencounter data. For a tutorial, go to <http://www.tandfonline.com/doi/full/10.1080/03078698.2014.933053>

Details

Package:	birdring
Type:	Package
Version:	1.2
Date:	2014-09-24
License:	GPL 2
LazyLoad:	yes

Author(s)

Fraenzi Korner-Nievergelt and Robert Robinson

Maintainer: Fraenzi Korner-Nievergelt <fraenzi.korner@vogelwarte.ch>

References

Speek, G., Clark, J.A., Rhode, Z., Wassenaar, R.D. & van Noordwijk, A.J. (2001) The EURING exchange-code 2000. Dutch Ringing Scheme, Heteren.

`birdstate`*Transformation of condition into state*

Description

Transforms the numeric code of the variable condition into a factor defining the state of the bird (dead, alive, sick).

Usage

```
birdstate(x)
```

Arguments

`x` variable condition with numeric code for the condition of the bird as given in the original EURING data

Value

a factor with the levels "dead", "alive", "sick" and "unknown"

Author(s)

F. Korner-Nievergelt

References

du Feu et al. (2012) EURING Exchange Code 2000+. www.euring.org

See Also

[codes2names](#)

Examples

```
condition <- 0:9  
birdstate(condition)
```

circumstances

EURING-code for finding circumstances

Description

EURING-code for finding circumstances as given in Speek et al. (2001)

Usage

```
data(circumstances)
```

Format

A data frame with 92 observations on the following 4 variables.

Code a numeric vector containing the code given in column 78 and 79 in EURING data of the format 2000

Name a factor with the names of the finding circumstances

BTO a factor with the shorter names of the finding circumstances as defined by the BTO (, <http://www.bto.org/volunteer-surveys/ringing/publications/online-ringing-reports>))

Description a factor with the description of the finding circumstances

Date.Updated a numeric vector

Source

<http://www.euring.org>

References

Speek, G., Clark, J.A., Rhode, Z., Wassenaar, R.D. & van Noordwijk, A.J. (2001) The EURING exchange-code 2000. Dutch Ringing Scheme, Heteren.

Examples

```
data(circumstances)
circumstances
```

coastEU	<i>coordinates of the coastline of Europe</i>
---------	---

Description

coordinates of the coastline of Europe used by the function `draw.map`

Usage

```
data(coastEU)
```

Format

A data frame with 7528 observations on the following 4 variables.

x a numeric vector, longitude

y a numeric vector, latitude

name name of the island

abstract a numeric vector

Details

the data is used by the function `draw.map`

Source

<http://rimmer.ngdc.noaa.gov/mgg/coast/getcoast.html>

References

<http://rimmer.ngdc.noaa.gov/mgg/coast/getcoast.html>

Examples

```
data(coastEU)
head(coastEU)
```

coastpaleo	<i>coordinates of the palearctic coastline</i>
------------	--

Description

coordinates of the palearctic coastline used by the function draw.map. The coordinates were downloaded from the sources indicated below and then cleaned by hand from too small details

Usage

```
data(coastpaleo)
```

Format

A data frame with 25042 observations on the following 5 variables.

x a numeric vector of longitude

y a numeric vector of latitude

name name of the island

entry degree of detail to be entered in the map

kategorie a factor with levels i m s

Source

<http://rimmer.ngdc.noaa.gov/mgg/coast/getcoast.html>

References

<http://rimmer.ngdc.noaa.gov/mgg/coast/getcoast.html>

Examples

```
data(coastpaleo)
head(coastpaleo)
```

codes2names	<i>Transforms codes of circumstances, condition, species and sheme into string</i>
-------------	--

Description

The function gives for the numeric codes for circumstances, condition and species the interpretable string name as given in the EURING code. The alphabetic scheme code is transformed into the town and country name of the scheme.

Usage

```
codes2names(x, variable = "circumstances", type="euring")
```

Arguments

x	variable circumstances, condition, species or scheme from the output of read.EURING2000plus.
variable	character that declares the name of the variable x, should be one of c("circumstances" [default], "conditions", "schemes", "species").
type	character that declares which names should be used, the one defined in the EURING manual, "euring" (default), or the ones used in the BTO ringing reports, "bto", (http://www.bto.org/volunteer-surveys/ringing/publications/online-ringing-reports).

Value

a factor with levels corresponding to the names of the EURING code

Author(s)

F. Korner-Nievergelt

References

http://www.euring.org/data_and_codes/euring_code_list/index.html

See Also

[scheme2country](#)

Examples

```
# circumstances
examplecode <- c(20, 21, 35, 80)
codes2names(examplecode)

# conditions
examplecodes <- c(0:9)
codes2names(examplecodes, variable="conditions")

# schemes
codes2names("BGS", variable="schemes")
```

conditions	<i>EURING-code for finding conditions</i>
------------	---

Description

EURING-code for finding conditions as given in Speek et al. (2001)

Usage

```
data(conditions)
```

Format

A data frame with 10 observations on the following 2 variables.

Code a numeric vector containing the code given in column 77 in EURING data of the format 2000

Description a factor with the finding conditions

Source

<http://www.euring.org>

References

Speek, G., Clark, J.A., Rhode, Z., Wassenaar, R.D. & van Noordwijk, A.J. (2001) The EURING exchange-code 2000. Dutch Ringing Scheme, Heteren.

Examples

```
data(conditions)
conditions
```

`critical.check.ringing.event`*Checking whether Ringing Event Exists for each Individual Bird.*

Description

Adds a variable `ringing.event` which is TRUE if exactly one ringing event exists and FALSE otherwise.

Usage

```
critical.check.ringing.event(dat, id = "birdID")
```

Arguments

<code>dat</code>	a EURING data, read in using <code>read.euring2000plus</code> function
<code>id</code>	The name of the variable that contains the individual identifier, normally a combination of scheme and ring number

Value

A new variable called "ringing.event" is added to the data frame.

Author(s)

Kasper Thorup and Fraenzi Korner-Nievergelt

Examples

```
data(lancol)
lancol$birdID <- paste(lancol$scheme, lancol$ring)
critical.check.ringing.event(lancol)
```

`dayofyear`*The day of the year*

Description

Gives the day of the year, i.e. the number of days since the 31 December of the previous year.

Usage

```
dayofyear(m, d, y = 1960)
```

Arguments

m month (integer between 1 and 12)
d day (integer between 1 and 31)
y year (integer such as 2013)

Value

numeric value, day of the year

Author(s)

Fraenzi Korner-Nievergelt

References

no references

See Also

[mdy.date](#)

Examples

```
dayofyear(3, 1, 2013)  
dayofyear(3, 1, 2012)
```

dc *Division coefficient*

Description

The function `dc()` calculates from the number of ringed birds per group and the number of reencountered birds per group in each destination area the estimated division coefficients per group and the estimated re-encounter probabilities per destination area as described in Kania and Busse (1987). The function `bootci.dc()` gives the bootstrap confidence intervals for the division coefficients and the re-encounter probabilities estimated by `dc()`. For details see Korner-Nievergelt et al. (2010).

Usage

```
dc(N, recmatrix, group.names = NA, area.names = NA, start = NA)  
  
bootci.dc(N, recmatrix, interval = 0.95, R = 1000,  
          group.names = NA, area.names = NA)
```

Arguments

N	a vector containing the number of ringed birds per group
recmatrix	a matrix containing the number of re-encountered birds per group and area. The rows of the matrix represent the bird groups; the columns represent the destination areas.
interval	proportion of the confidence interval (default = 0.95)
R	number of bootstrap replicates (default = 1000)
group.names	facultative vector of group names
area.names	facultative vector of area names
start	facultative vector of starting values for the least-square iteration for estimating the inverse of the recovery probability per destination area. The vector has the length of the number of areas and contains approximate inverse values of the recovery probabilities (default = $N[1]/\text{recmatrix}[1,]/2$).

Value

rec.probs	estimated re-encounter probabilities per destination area
division.coef	estimated division coefficient per group and destination area
div.coef.lower	lower limits of the confidence intervals of the estimated division coefficients
div.coef.upper	upper limits of the confidence intervals of the estimated division coefficients

Author(s)

Fraenzi Korner-Nievergelt

References

Kania W, Busse P (1987) An analysis of the recovery distribution based on finding probabilities. *Acta Ornithologica* 23: 121-128. Korner-Nievergelt F, Schaub M, Thorup K, Vock M, Kania W (2010) Estimation of bird distribution based on ring re-encounters: precision and bias of the division coefficient and its relation to multi-state models. *Bird Study* 57: 56-68.

Example data are from: Bauthian I, Gossmann F, Ferrand Y, Julliard R. (2007) Quantifying the origin of Woodcock wintering in France. *Journal of Wildlife Management* 71: 701-705.

Examples

```
N<-c(7125, 9661, 5266, 3240, 3643, 3192, 3227)

recmatrix<-matrix(c(22,25, 6, 2, 4, 1, 0, 47, 78, 49, 28, 38,27, 34), ncol=2)
colnames(recmatrix) <- c("Scandinavian", "Eastern")
rownames(recmatrix) <- c("North", "West", "Southwest",
  "Central North", "Central South", "Northeast", "Southeast")

dc(N, recmatrix, group.names= c("North", "West", "Southwest",
  "Central North", "Central South", "Northeast", "Southeast"),
  area.names= c("Scandinavian", "Eastern"))
```

decimal.coord	<i>decimal coordinates</i>
---------------	----------------------------

Description

transforms degrees and minutes into decimal coordinates

Usage

```
decimal.coord(x)
```

Arguments

x scalar or vector containing degrees and minutes, e.g. for 45 degrees and 30 minutes = 45.3

Value

a scalar or a vector containing the decimal coordinates

Author(s)

Fraenzi Korner-Nievergelt

References

This function just multiplies the decimals by 5/3... (no reference)

Examples

```
decimal.coord(45.3)
```

dmvnorm	<i>Multivariate Normal Density and Random Deviates - this function is a copy of the function in the package mvtnorm</i>
---------	---

Description

These functions provide the density function and a random number generator for the multivariate normal distribution with mean equal to mean and covariance matrix sigma.

Usage

```
dmvnorm(x, mean, sigma, log = FALSE)
```

Arguments

x	Vector or matrix of quantiles. If x is a matrix, each row is taken to be a quantile.
mean	Mean vector, default is rep(0, length = ncol(x)).
sigma	Covariance matrix, default is diag(ncol(x)).
log	Logical; if TRUE, densities d are given as log(d).

Details

This function is copied to birdring from mvtnorm. If you use this function, please use and cite the original function from the package mvtnorm!

Author(s)

Friedrich Leisch and Fabian Scheipl

References

Alan Genz, Frank Bretz, Tetsuhisa Miwa, Xuefei Mi, Friedrich Leisch, Fabian Scheipl, Torsten Hothorn (2013). mvtnorm: Multivariate Normal and t Distributions. R package version 0.9-9995. URL <http://CRAN.R-project.org/package=mvtnorm>

Alan Genz, Frank Bretz (2009), Computation of Multivariate Normal and t Probabilities. Lecture Notes in Statistics, Vol. 195., Springer-Verlage, Heidelberg. ISBN 978-3-642-01688-2

See Also

see functions and documentations in the package mvtnorm

Examples

```
dmvnorm(x=c(0,0))
```

```
draw.map
```

Draws a map of the palearctic region

Description

Draws a map of the palearctic region that can be used as basis for showing ring reencounter data.

Usage

```
draw.map(a=-10, b=30, c=23, d=65, bbox=NULL, fill = TRUE, col.land = grey(0.5),
  col.water = "white", border = NA, detail = FALSE, box = TRUE, axes = FALSE,
  las = 1, cex.axis = 0.8, dist.axislab = 0.2, whichaxis = c(1:4), tck = -0.005,
  mercator = FALSE, mar = rep(0.5, 4), asp=NA)
```

Arguments

a	left edge of the map (longitude), can be used alternatively to the argument bbox
b	right edge of the map (longitude), can be used alternatively to the argument bbox
c	lower edge of the map (latitude), can be used alternatively to the argument bbox
d	upper edge of the map (latitude), can be used alternatively to the argument bbox
bbox	a numeric vector giving the map boundary in decimal degrees as c(long_min, long_max, lat_min, lat_max), can be used alternatively to the arguments a, b, c, and d.
fill	logical value, TRUE = land and water masses are filled with a color
col.land	color of the land
col.water	color of the water
border	color of the coastline, NA = no coastline is drawn
detail	if TRUE: an alternative way to draw coastlines
box	logical, TRUE = a box is drawn around the map
axes	logical, indicates whether axis should be drawn
las	see par
cex.axis	see par
dist.axislab	distance from the axis to the axis labels
whichaxis	vector of length 1 to 4 containing the axis that should be drawn, default is c(1,2,3,4), i.e. all axes
tck	see par
mercator	logical, if TRUE a mercator projection is plotted. see details below
mar	see par
asp	if set to 1 x and y axes are scaled equally (not recommended if mercator=TRUE), see par

Details

If a mercator projection is used, the values for a, b, c and d will be adjusted.

Value

this is a plotting function only

Note

some times it does not do what we expect....

Author(s)

Fraenzi Korner-Nievergelt

References

Rummler, H. 2002. Mercatorkarte und hyperbolische Geometrie. Elem. Math., 57, 168-173.

Examples

```
draw.map(-18, 50, -5, 56, col.land="white", col.water=grey(0.5),  
  detail=FALSE, axes=TRUE)
```

```
draw.map(a=0, b=30, c=35, d=60, col.land="white", col.water=grey(0.5),  
  detail=FALSE, axes=TRUE, mercator=TRUE)
```

lancol

Example data set of EURING2000 format

Description

Ringling and recovery data of the Red-backed Shrike in the EURING2000 format

Usage

```
data(lancol)
```

Format

A data frame with 2483 observations of the 40 variables of the EURING2000.

Source

<http://www.euring.org>

References

Speek, G., Clark, J.A., Rhode, Z., Wassenaar, R.D. & van Noordwijk, A.J. (2001) The EURING exchange-code 2000. Dutch Ringing Scheme, Heteren.

Examples

```
data(lancol)
```

loxodrom	<i>loxodromic distance and direction</i>
----------	--

Description

calculates the loxodromic distance and direction between two points on the earth

Usage

```
loxodrom.dir(x1, y1, x2, y2, epsilon = 1e-06)
```

```
loxodrom.dist(x1, y1, x2, y2, epsilon = 1e-04, package="geosphere")
```

Arguments

x1	x-coordinate/longitude of the first point (in decimal coordinates), can be a scalar or a vector
y1	y-coordinate/latitude of the first point (in decimal coordinates), can be a scalar or a vector
x2	x-coordinate/longitude of the second point (in decimal coordinates), can be a scalar or a vector
y2	y-coordinate/latitude of the second point (in decimal coordinates), can be a scalar or a vector
epsilon	a threshold value for considering a number as zero. See details.
package	if "geosphere" (default) the function is based on the geosphere package, if "birdring" the function written by F. Korner is used. The latter is less reliable.

Details

If you use the birdring package, please, check the results carefully, especially when vectors instead of scalars are given as arguments. If some distances or directions are obviously wrong (such cases occurred predominantly when the bird moved exactly into one of the four directions 0, 90, 180 or 270 degrees) then it might help to increase the value of epsilon.

Value

The function `loxodrom.dist()` gives back a number or a vector with the distances in km between the two points on earth. The function `loxodrom.dir()` gives back a number or a vector with the directions in degrees from North (clockwise) between the two points on earth.

Warning

see details

Author(s)

Fraenzi Korner-Nievergelt

References

Imboden, C., Imboden D. (1972) Orthodromic and loxodromic formula for the calculation of distance and direction between ringing and finding place. Vogelwarte 26: 336-346.

See Also

[decimal.coord](#)

Examples

```
ringingx<-7.30
ringingy<-47.41
findingx<-5.1
findingy<-32.01
rxdec<-decimal.coord(ringingx)
rydec<-decimal.coord(ringingy)
fxdec<-decimal.coord(findingx)
fydec<-decimal.coord(findingy)

loxodrom.dist(rxdec, rydec, fxdec, fydec)

loxodrom.dir(rxdec, rydec, fxdec, fydec)
```

mdy.date	<i>Convert to Julian Dates - this is a copy of the function mdy.date from the package date</i>
----------	--

Description

Given a month, day, and year, returns the number of days since January 1, 1960.

Usage

```
mdy.date(month, day, year, nineteen = TRUE, fillday = FALSE, fillmonth = FALSE)
```

Arguments

month	vector of months.
day	vector of days.
year	vector of years.
nineteen	if TRUE, year values between 0 and 99 are assumed to be in the 20th century A.D.; otherwise, if FALSE, they are assumed to be in the 1st century A.D.
fillday	if TRUE, then missing days are replaced with 15.
fillmonth	if TRUE, then a missing month causes the month and day to be set to 7/1.

Details

The date functions are particularly useful in computing time spans, such as number of days on test, and similar functions can be found in other statistical packages. The baseline date of Jan 1, 1960 is, of course, completely arbitrary (it is the same one used by SAS).

The fillday and fillmonth options are perhaps useful only to the author and a very few others: we sometimes deal with patients whose birth date was in the 1800's, and only the month or even only the year is known. When the interval is greater than 80 years, a filler seems defensible.

Value

a vector of Julian dates.

References

Press, W. H., Teukolsky, S. A., Vetterling, W. T., and Flannery, B. P. (1992). Numerical Recipes: The Art of Scientific Computing (Second Edition). Cambridge University Press.

Terry Therneau and Thomas Lumley and Kjetil Halvorsen and Kurt Hornik (2012). date: Functions for handling dates. R package version 1.2-33.

See Also

see documentation and other functions in the package date

Examples

```
mdy.date(3, 10, 53)
```

mercatorlat	<i>gives the stretching factor of the latitude to draw a mercator map</i>
-------------	---

Description

this function is only used internally by the function draw.map

Usage

```
mercatorlat(x)
```

Arguments

x latitude in decimal coordinates

Value

numeric: latitude to draw a mercator map

Author(s)

Fraenzi Korner-Nievergelt

References

Rummler, H. (2002) Mercatorkarte und hyperbolische Geometrie. Elem. Math., 57, 168-173.

Examples

```
mercatorlat(41.6)
```

orthodrom.dist	<i>orthodromic distance and direction</i>
----------------	---

Description

calculates the orthodromic (great circle, shortest distance) distance between two points on the earth

Usage

```
orthodrom.dist(x1, y1, x2, y2)
```

Arguments

x1	x-coordinate/longitude of the first point (in decimal coordinates), can be a scalar or a vector
y1	y-coordinate/latitude of the first point (in decimal coordinates), can be a scalar or a vector
x2	x-coordinate/longitude of the second point (in decimal coordinates), can be a scalar or a vector
y2	y-coordinate/latitude of the second point (in decimal coordinates), can be a scalar or a vector

Details

The function is a wrapper of the distMeeus function of the geosphere package.

Value

gives back a number or a vector with the distances in km between the two points on earth.

Warning

see details

Author(s)

Fraenzi Korner-Nievergelt

References

Imboden, C., Imboden D. (1972) Orthodromic and loxodromic formula for the calculation of distance and direction between ringing and finding place. *Vogelwarte* 26: 336-346.

See Also

[decimal.coord](#)

Examples

```
ringingx<-7.30
ringingy<-47.41
findingx<-5.1
findingy<-32.01
rxdec<-decimal.coord(ringingx)
rydec<-decimal.coord(ringingy)
fxdec<-decimal.coord(findingx)
fydec<-decimal.coord(findingy)

orthodrom.dist(rxdec, rydec, fxdec, fydec)
```

overlap

Overlap between the prior and posterior distribution

Description

Gives the overlap of two distributions (such as a prior and a posterior distribution) based on one sample of simulated values from each distribution

Usage

```
overlap(posterior, prior, from = 0, to = 1, nsim = 1e+05, edge.of.parameter.space=FALSE)
```

Arguments

posterior	A numeric vector, a sample of simulated random values from the posterior distribution
prior	A numeric vector, a sample of simulated random values from the prior distribution
from	Lower limit of the parameter space over which the posterior and prior distributions are compared.
to	Upper limit of the parameter space over which the posterior and prior distributions are compared.
nsim	Number of simulated values used for the Monte Carlo simulation to measure the overlap.

`edge.of.parameter.space`

logical value; Two different methods are implemented to calculate the overlap. First (`edge.of.parameter.space=FALSE`), smoothers are fitted to the histograms of the simulated values from the posterior and prior distributions, and the overlap is calculated based on this smoothed density functions. This has the advantage to be more exact when the number of simulated values from the posterior distribution is small. However, it can be unreliable when the mean of the posterior distribution is close to the edge of the parameter space. In such cases (`edge.of.parameter.space=TRUE`), it is more reliable to calculate the overlap directly from histograms of the simulated values from the posterior and prior distributions. See also details.

Details

If `edge.of.parameter.space=FALSE`, the function first uses the function density to obtain density functions of the prior and posterior distributions and then the overlap is measured by a Monte Carlo simulation. If `edge.of.parameter.space=TRUE`, two histograms of the simulated values from the posterior and prior distributions are drawn with 999 classes and breaks 1000 equally spaced values between from and to. The overlap is then calculated directly from these histograms.

Value

a numeric value which is an approximation of the proportion of the overlap of the posterior with the prior distribution.

Author(s)

Fraenzi Korner-Nievergelt

References

Gimenez, O., S. P. Brooks, et al. (2009). Weak identifiability in models for mark-recapture-recovery data. *Modelling Demographic Processes in Marked Populations*. Series: Environmental and Ecological Statistics. D. L. Thomson, E. G. Cooch and M. J. Conroy.

See Also

[density](#)

Examples

```
prior <- rbeta(2000, 1,1)
posterior <- rbeta(2000, 14, 35)
overlap(posterior, prior)
```

place2name

Decode Euring place codes

Description

Converts Euring country and region codes into their text names.

Usage

```
place2name(x)
```

Arguments

x a variable containing four character Euring place code.

Details

A warning is given if any place codes are not matched, these will be returned as NA.

Value

a dataframe with three columns: 'country.name', 'region.name', 'current', the last of which indicates whether the code is currently use or deprecated.

Author(s)

Rob Robinson

Examples

```
examplecodes <- c('BL20', 'GBTR')
place2name(examplecodes)
```

places*EURING-code for finding locations*

Description

EURING-code for places as given in Speek et al. (2001)

Usage

```
data(places)
```

Format

A data frame with 1852 rows of the following 5 variables.

country name of country. non-ASCII characters have been exchanged, please change back for Cote d Ivoire and Suqutra
 region name of region. non-ASCII characters have been exchanged, please check an change back!
 code the code used by EDB
 current
 date.updated date of update

Source

<http://www.euring.org>

References

Speek, G., Clark, J.A., Rhode, Z., Wassenaar, R.D. & van Noordwijk, A.J. (2001) The EURING exchange-code 2000. Dutch Ringing Scheme, Heteren.

Examples

```
data(places)
```

<code>read.euring2000</code>	<i>Reads EURING data into R</i>
------------------------------	---------------------------------

Description

Reads EURING data (format EURING exchange code 2000) into R and creates a data.frame

Usage

```
read.euring2000(filename, quote="", ...)
```

Arguments

filename	character string of the data file obtained from EURING (format: exchange code 2000)
quote	default is to ignore quotemarks as much as possible, see notes.
...	extra arguments to pass to read.table

Value

A data.frame containing the following variables from the EURING 2000 code:

scheme	Factor	ringing scheme (code)
id.method	Factor	identification method
ring	Factor	ring number
ring.verif	character	verification of the metal ring
metal.ring.info	character	metal ring information
marks.info	character	other marks information
spec.byringer	character	species + subsp., mentioned by person
spec.byscheme	character	species + subsp., concluded by scheme
manipulated	character	manipulated
moved	character	moved before the (re)capture/recovery
catching.method	character	catching method
catching.lures	character	catching lures
sex.byringer	character	sex, by the person who handled the bird
sex.byscheme	character	sex, as concluded by scheme
age.byringer	character	age, by the person who handled the bird
age.byscheme	character	age, as concluded by scheme
status	character	status
broodsize	character	broodsize
pullus.age	character	pullus age
pullus.age.acc	character	accuracy of pullus age
day	numeric	day of record, derived from date
month	numeric	month of record, derived from date
year	numeric	year of record, derived from date
date.acc	character	accuracy of date
time	character	time
place.code	character	place code
country	character	country derived from place code
region	character	region (county) derived from place code
lat	numeric	latitude in decimal coordinates
lon	numeric	longitude in decimal coordinates
coord.acc	character	accuracy of coordinates
condition	character	condition
circumstances	character	finding circumstances
circumstances.presumed	character	finding circumstances presumed
euring.codeid	character	EURING-code identifier
distance	numeric	distance to place of ringing (km)
direction	numeric	direction to place of ringing (km)
time.elapsed	numeric	time since ringing (days)

Note

Quotemarks, apostrophes and backticks can cause havoc when reading in files; if things do not work as you expect, check for their presence of these and consider removing!

Author(s)

Fraenzi Korner-Nievergelt

References

Speek et al. 2007: The EURING exchange-code 2000. www.euring.org

Examples

```
filename <- system.file("extdata", "RBSHrike2000.TXT", package = "birdring")
dat <- read.euring2000(filename)
str(dat)
```

read.euring2000plus *Reads EURING data of the format 2000\+ into R*

Description

Reads EURING data (format EURING exchange code 2000\+) into R and creates a data.frame

Usage

```
read.euring2000plus(filename, quote="", ...)
```

Arguments

filename	character string of the psv-file obtained from EURING (format: exchange code 2000\+)
quote	default is to ignore quotemarks as much as possible, see notes.
...	extra arguments to pass to read.table

Value

A data.frame containing the following variables from the EURING 2000\+ code:

scheme	Factor	ringing scheme (code)
id.method	Factor	identification method
ring	Factor	ring number
ring.verif	character	verification of the metal ring
metal.ring.info	character	metal ring information
marks.info	character	other marks information
spec.byringer	character	species + subsp., mentioned by person
spec.byscheme	character	species + subsp., concluded by scheme
manipulated	character	manipulated
moved	character	moved before the (re)capture/recovery
catching.method	character	catching method
catching.lures	character	catching lures
sex.byringer	character	sex, by the person who handled the bird
sex.byscheme	character	sex, as concluded by scheme
age.byringer	character	age, by the person who handled the bird

age.byscheme	character	age, as concluded by scheme
status	character	status
broodsize	character	broodsize
pullus.age	character	pullus age
pullus.age.acc	character	accuracy of pullus age
day	numeric	day of record, derived from date
month	numeric	month of record, derived from date
year	numeric	year of record, derived from date
date.acc	character	accuracy of date
time	character	time
place.code	character	place code
country	character	country extracted from place code
region	character	region (county) extracted from place code
lat	numeric	latitude in decimal coordinates
lon	numeric	longitude in decimal coordinates
coord.acc	character	accuracy of coordinates
condition	character	condition
circumstances	character	finding circumstances
circumstances.presumed	character	finding circumstances presumed
euring.codeid	character	EURING-code identifier
distance	numeric	distance to place of ringing (km)
direction	numeric	direction to place of ringing (km)
time.elapsed	numeric	time since ringing (days)
wing.length	numeric	maximum chord measurement in mm, Svensson (1992)
third.primary	numeric	Length of the third primary feather, in mm
state.of.wing.point	character	condition of the longest primary feather
mass	numeric	body, in grams, measured to a maximum precision of 0.1 g.
moult	character	code for main, clearly identifiable moult states
plumage.code	character	extra information to enhance age code
hind.claw	numeric	in mm, for details of method see Svensson (1992)
bill.length	numeric	in mm, see du Feu (2012).
bill.method	character	a single letter code, for details see Svensson (1992).
total.head.length	numeric	in mm, see du Feu (2012)
tarsus	numeric	in mm, see du Feu (2012)
tarsus.method	character	tarsus method used, see du Feu (2012)
tail.length	numeric	in mm, details of the method see Svensson (1992).
tail.difference	numeric	according to Svensson (1992)
fat.score	numeric	fat score, see du Feu (2012) for details.
fat.score.method	character	fat score method used, see du Feu (2012)
pectoral.muscle	numeric	state of pectoral muscle
brood.patch	character	state of the brood patch in the breeding season
primary.score	numeric	the sum of the primary moult scores
primary.moult	character	state of the 10 primary feathers
old.greater.coverts	numeric	the number of unmoulted greater coverts
alula	character	state of the three alula feathers
carpal.covert	numeric	state of moult of the carpal covert: 0=old, 1=new.
sexing.method	character	for code description see du Feu (2012).

For three additional optional variables, see du Feu (2012).

Note

Quotemarks, apostrophes and backticks can cause havoc when reading in files; if things do not work as you expect, check for their presence of these and consider removing!

Author(s)

Fraenzi Korner-Nievergelt

References

du Feu et al. 2012: EURING exchange-code 2000\+. www.euring.org

Examples

```
filename <- system.file("extdata", "REEWAExport_50.psv", package = "birdring")
dat <- read.euring2000plus(filename)
str(dat)
```

scheme2country	<i>Gives the country name from the scheme code</i>
----------------	--

Description

Transforms the scheme codes into country name.

Usage

```
scheme2country(x)
```

Arguments

x variable scheme from the data frame produced by read.EURING2000 or read.EURING2000plus

Value

a factor with levels corresponding to the country names

Author(s)

F. Korner-Nievergelt

References

www.euring.org

See Also[codes2names](#)**Examples**

```
schemecode <- "HES"  
scheme2country(schemecode)
```

schemes

EURING-code for ringing scheme

Description

EURING-code for ringing scheme as given in Speek et al. (2001)

Usage

```
data(schemes)
```

Format

A data frame with 39 observations on the following 7 variables.

Code a factor with the EURING code

Country a factor with the country of the scheme

Centre a factor with the city of the place of the scheme

EURING a factor with levels Y

Current a factor with levels Y

Date.Updated a factor

Notes a factor with additional remarks

Source

<http://www.euring.org>

References

Speek, G., Clark, J.A., Rhode, Z., Wassenaar, R.D. & van Noordwijk, A.J. (2001) The EURING exchange-code 2000. Dutch Ringing Scheme, Heteren.

Examples

```
data(schemes)
```

species

EURING-code for species

Description

EURING-code for species as given in Speek et al. (2001)

Usage

```
data(species)
```

Format

A data frame with 3311 observations on the following 3 variables.

Code a numeric vector with the EURING species code

Name a factor with the species names

Date.Updated a factor

Source

<http://www.euring.org>

References

Speek, G., Clark, J.A., Rhode, Z., Wassenaar, R.D. & van Noordwijk, A.J. (2001) The EURING exchange-code 2000. Dutch Ringing Scheme, Heteren.

Examples

```
data(species)
```

Index

- * **Bayesian data analysis**
 - overlap, [20](#)
 - * **codes**
 - codes2names, [7](#)
 - * **code**
 - birdstate, [3](#)
 - scheme2country, [27](#)
 - * **coordinates**
 - decimal.coord, [12](#)
 - * **datasets**
 - circumstances, [4](#)
 - coastEU, [5](#)
 - coastpaleo, [6](#)
 - conditions, [8](#)
 - lancol, [15](#)
 - places, [22](#)
 - schemes, [28](#)
 - species, [29](#)
 - * **data**
 - read.euring2000, [23](#)
 - read.euring2000plus, [25](#)
 - * **date**
 - dayofyear, [9](#)
 - * **distributions**
 - overlap, [20](#)
 - * **euring**
 - birdring-package, [2](#)
 - * **geographic location**
 - decimal.coord, [12](#)
 - * **graphics**
 - draw.map, [13](#)
 - * **manip**
 - read.euring2000, [23](#)
 - read.euring2000plus, [25](#)
 - * **math**
 - loxodrom, [16](#)
 - orthodrom.dist, [19](#)
 - * **migratory connectivity**
 - dc, [10](#)
 - * **misc**
 - critical.check.ringing.event, [9](#)
 - dmvnorm, [12](#)
 - draw.map, [13](#)
 - loxodrom, [16](#)
 - mercatorlat, [18](#)
 - orthodrom.dist, [19](#)
 - place2name, [22](#)
 - * **package**
 - birdring-package, [2](#)
 - * **ring recovery**
 - birdring-package, [2](#)
 - dc, [10](#)
 - * **ring reencounter data**
 - birdring-package, [2](#)
 - * **spatial**
 - loxodrom, [16](#)
 - orthodrom.dist, [19](#)
 - * **transformation**
 - birdstate, [3](#)
 - codes2names, [7](#)
 - mdy.date, [17](#)
 - place2name, [22](#)
 - scheme2country, [27](#)
- birdring-package, [2](#)
birdstate, [3](#)
bootci.dc (dc), [10](#)

circumstances, [4](#)
coastEU, [5](#)
coastpaleo, [6](#)
codes2names, [3](#), [7](#), [28](#)
conditions, [8](#)
critical.check.ringing.event, [9](#)

dayofyear, [9](#)
dc, [10](#)
decimal.coord, [12](#), [17](#), [20](#)
density, [21](#)

dmvnorm, [12](#)
draw.map, [13](#)

lancol, [15](#)
loxodrom, [16](#)

mdy.date, [10](#), [17](#)
mercatorlat, [18](#)

orthodrom.dist, [19](#)
overlap, [20](#)

place2name, [22](#)
places, [22](#)

read.euring2000, [23](#)
read.euring2000plus, [25](#)

scheme2country, [7](#), [27](#)
schemes, [28](#)
species, [29](#)