

Package ‘bp’

May 8, 2026

Type Package

Title Blood Pressure Analysis in R

Version 2.1.1

Maintainer John Schwenck <jschwenck12@gmail.com>

Description A comprehensive package to aid in the analysis of blood pressure data of all forms by providing both descriptive and visualization tools for researchers.

License GPL-3

URL <https://github.com/johenschwenck/bp>

BugReports <https://github.com/johenschwenck/bp/issues>

Encoding UTF-8

LazyData true

RoxygenNote 7.3.3

Imports dplyr, tidyr, magrittr, lubridate, ggplot2, gridExtra, cowplot, tibble, tidyselect, gtable

Depends R (>= 3.5.0)

Suggests knitr, rmarkdown, png

VignetteBuilder knitr

Language en-US

NeedsCompilation no

Author John Schwenck [aut, cre],
Irina Gaynanova [aut] (ORCID: <<https://orcid.org/0000-0002-4116-0268>>)

Repository CRAN

Date/Publication 2025-11-21 20:20:07 UTC

Contents

| | |
|---------------------|---|
| arv | 2 |
| bp_arv | 4 |
| bp_center | 6 |

| | |
|----------------------------|----|
| bp_children | 8 |
| bp_cv | 9 |
| bp_ghana | 11 |
| bp_hist | 14 |
| bp_hypos | 15 |
| bp_jhs | 16 |
| bp_mag | 17 |
| bp_preg | 18 |
| bp_range | 21 |
| bp_rats | 22 |
| bp_report | 23 |
| bp_scatter | 26 |
| bp_sleep_metrics | 30 |
| bp_stages | 32 |
| bp_stats | 36 |
| bp_sv | 38 |
| bp_tables | 40 |
| bp_ts_plots | 41 |
| cv | 43 |
| dip_calc | 45 |
| dip_class_plot | 48 |
| dow_tod_plots | 50 |
| process_data | 51 |
| sleep_int | 57 |
| sv | 58 |

| | |
|--------------|-----------|
| Index | 61 |
|--------------|-----------|

| | |
|-----|---------------------------------------|
| arv | <i>Average Real Variability (ARV)</i> |
|-----|---------------------------------------|

Description

THIS IS A DEPRECATED FUNCTION. USE bp_arv INSTEAD.

Usage

```
arv(
  data,
  inc_date = FALSE,
  subj = NULL,
  bp_type = 0,
  add_groups = NULL,
  inc_wake = TRUE
)
```

Arguments

| | |
|-------------------------|---|
| <code>data</code> | Required argument. Pre-processed dataframe containing SBP and DBP with optional ID, VISIT, WAKE, and DATE columns if available. Use <code>process_data</code> to properly format data. |
| <code>inc_date</code> | Optional argument. Default is FALSE. As ABPM data typically overlaps due to falling asleep on one date and waking up on another, the <code>inc_date</code> argument is typically kept as FALSE, but the function will work regardless. Setting <code>inc_date = TRUE</code> will include these dates as a grouping level. |
| <code>subj</code> | Optional argument. Allows the user to specify and subset specific subjects from the ID column of the supplied data set. The <code>subj</code> argument can be a single value or a vector of elements. The input type should be character, but the function will comply with integers so long as they are all present in the ID column of the data. |
| <code>bp_type</code> | Optional argument. Determines whether to calculate ARV for SBP values or DBP values. Default is 0 corresponding to output for both SBP & DBP. For both SBP and DBP ARV values use <code>bp_type = 0</code> , for SBP-only use <code>bp_type = 1</code> , and for DBP-only use <code>bp_type = 2</code> |
| <code>add_groups</code> | Optional argument. Allows the user to aggregate the data by an additional "group" to further refine the output. The supplied input must be a character vector with the strings corresponding to existing column names of the processed data input supplied. Capitalization of <code>add_groups</code> does not matter. Ex: <code>add_groups = c("Time_of_Day")</code> |
| <code>inc_wake</code> | Optional argument corresponding to whether or not to include WAKE in the grouping of the final output (if WAKE column is available). By default, <code>inc_wake = TRUE</code> which will include the WAKE column in the groups by which to calculate the respective metrics. |

Details

Calculate the Average Real Variability (ARV) at various levels of granularity based on what is supplied (ID, VISIT, WAKE, and / or DATE). ARV is a measure of dispersion that takes into account the temporal structure of the data and relies on the sum of absolute differences in successive observations, unlike the successive variation (SV) which relies on the sum of squared differences.

Value

A tibble object with a row corresponding to each subject, or alternatively a row corresponding to each date, if `inc_date = TRUE`. The resulting tibble consists of:

- ID: The unique identifier of the subject. For single-subject datasets, ID = 1
- VISIT: (If applicable) Corresponds to the visit # of the subject, if more than 1
- WAKE: (If applicable) Corresponds to the awake status of the subject (0 = asleep | 1 = awake)
- ARV_SBP / ARV_DBP: Calculates the average of the absolute differences between successive measurements. The resulting value averages across the granularity grouping for however many observations are present.

- N: The number of observations for that particular grouping. If `inc_date = TRUE`, N corresponds to the number of observations for that date. If `inc_date = FALSE`, N corresponds to the number of observations for the most granular grouping available (i.e. a combination of ID, VISIT, and WAKE)
- Any `add_groups` variables supplied to function argument will be present as a column in the resulting tibble.

References

Mena et al. (2005) A reliable index for the prognostic significance of blood pressure variability *Journal of Hypertension* **23(5)**.505-11, doi:[10.1097/01.hjh.0000160205.81652.5a](https://doi.org/10.1097/01.hjh.0000160205.81652.5a).

Examples

```
# Load data
data(bp_hypos)
data(bp_jhs)

# Process bp_hypos
hypos_proc <- process_data(bp_hypos, sbp = "SYST", dbp = "DIAST", date_time = "date.time",
id = "id", wake = "wake", visit = "visit", hr = "hr", pp = "pp", map = "map", rpp = "rpp")
# Process bp_jhs data
jhs_proc <- process_data(bp_jhs, sbp = "Sys.mmHg.", dbp = "Dias.mmHg.", date_time = "DateTime",
hr = "Pulse.bpm.")

## Not run:
# ARV Calculation
bp_arv(hypos_proc, add_groups = c("SBP_Category"))
bp_arv(jhs_proc, inc_date = TRUE)

## End(Not run)
```

bp_arv

Average Real Variability (ARV)

Description

Calculate the Average Real Variability (ARV) at various levels of granularity based on what is supplied (ID, VISIT, WAKE, and / or DATE). ARV is a measure of dispersion that takes into account the temporal structure of the data and relies on the sum of absolute differences in successive observations, unlike the successive variation (SV) which relies on the sum of squared differences.

Usage

```
bp_arv(
  data,
  inc_date = FALSE,
  subj = NULL,
```

```

  bp_type = c("both", "sbp", "dbp"),
  add_groups = NULL,
  inc_wake = TRUE
)

```

Arguments

| | |
|------------|---|
| data | Required argument. Pre-processed dataframe containing SBP and DBP with optional ID, VISIT, WAKE, and DATE columns if available. Use <code>process_data</code> to properly format data. |
| inc_date | Optional argument. Default is FALSE. As ABPM data typically overlaps due to falling asleep on one date and waking up on another, the <code>inc_date</code> argument is typically kept as FALSE, but the function will work regardless. Setting <code>inc_date = TRUE</code> will include these dates as a grouping level. |
| subj | Optional argument. Allows the user to specify and subset specific subjects from the ID column of the supplied data set. The <code>subj</code> argument can be a single value or a vector of elements. The input type should be character, but the function will comply with integers so long as they are all present in the ID column of the data. |
| bp_type | Optional argument. Determines whether to calculate ARV for SBP values or DBP values, or both. For both SBP and DBP ARV values use <code>bp_type = 'both'</code> , for SBP-only use <code>bp_type = 'sbp'</code> , and for DBP-only use <code>bp_type = 'dbp'</code> . If no type specified, default will be set to 'both' |
| add_groups | Optional argument. Allows the user to aggregate the data by an additional "group" to further refine the output. The supplied input must be a character vector with the strings corresponding to existing column names of the processed data input supplied. Capitalization of <code>add_groups</code> does not matter. Ex: <code>add_groups = c("Time_of_Day")</code> |
| inc_wake | Optional argument corresponding to whether or not to include WAKE in the grouping of the final output (if WAKE column is available). By default, <code>inc_wake = TRUE</code> which will include the WAKE column in the groups by which to calculate the respective metrics. |

Value

A tibble object with a row corresponding to each subject, or alternatively a row corresponding to each date, if `inc_date = TRUE`. The resulting tibble consists of:

- ID: The unique identifier of the subject. For single-subject datasets, `ID = 1`
- VISIT: (If applicable) Corresponds to the visit # of the subject, if more than 1
- WAKE: (If applicable) Corresponds to the awake status of the subject (0 = asleep | 1 = awake)
- ARV_SBP / ARV_DBP: Calculates the average of the absolute differences between successive measurements. The resulting value averages across the granularity grouping for however many observations are present.
- N: The number of observations for that particular grouping. If `inc_date = TRUE`, N corresponds to the number of observations for that date. If `inc_date = FALSE`, N corresponds to the number of observations for the most granular grouping available (i.e. a combination of ID, VISIT, and WAKE)

- Any `add_groups` variables supplied to function argument will be present as a column in the resulting tibble.

References

Mena et al. (2005) A reliable index for the prognostic significance of blood pressure variability *Journal of Hypertension* **23(5)**.505-11, doi:[10.1097/01.hjh.0000160205.81652.5a](https://doi.org/10.1097/01.hjh.0000160205.81652.5a).

Examples

```
# Load data
data(bp_hypos)
data(bp_jhs)

# Process bp_hypos
hyp_proc <- process_data(bp_hypos, sbp = "SYST", dbp = "DIAST", date_time = "date.time",
id = "id", wake = "wake", visit = "visit", hr = "hr", pp = "pp", map = "map", rpp = "rpp")
# Process bp_jhs data
jhs_proc <- process_data(bp_jhs, sbp = "Sys.mmHg.", dbp = "Dias.mmHg.", date_time = "DateTime",
hr = "Pulse.bpm.")

# ARV Calculation
bp_arv(hyp_proc, add_groups = c("SBP_Category"), bp_type = 'sbp')
bp_arv(jhs_proc, inc_date = TRUE)
```

bp_center

Measures of Center (bp_center)

Description

Calculate the mean and median at various levels of granularity based on what is supplied (ID, VISIT, WAKE, and / or DATE) for either SBP, DBP, or both.

Usage

```
bp_center(
  data,
  inc_date = FALSE,
  subj = NULL,
  bp_type = c("both", "sbp", "dbp"),
  add_groups = NULL,
  inc_wake = TRUE
)
```

Arguments

`data` Required argument. Pre-processed dataframe with SBP and DBP columns with optional ID, VISIT, WAKE, and DATE columns if available. Use `process_data` to properly format data.

| | |
|------------|---|
| inc_date | Optional argument. Default is FALSE. As ABPM data typically overlaps due to falling asleep on one date and waking up on another, the inc_date argument is typically kept as FALSE, but the function will work regardless. Setting inc_date = TRUE will include these dates as a grouping level. |
| subj | Optional argument. Allows the user to specify and subset specific subjects from the ID column of the supplied data set. The subj argument can be a single value or a vector of elements. The input type should be character, but the function will comply with integers so long as they are all present in the ID column of the data. |
| bp_type | Optional argument. Determines whether to calculate center for SBP values or DBP values, or both. For both SBP and DBP ARV values use bp_type = 'both', for SBP-only use bp_type = 'sbp', and for DBP-only use bp_type = 'dbp'. If no type specified, default will be set to 'both' |
| add_groups | Optional argument. Allows the user to aggregate the data by an additional "group" to further refine the output. The supplied input must be a character vector with the strings corresponding to existing column names of the processed data input supplied. Capitalization of add_groups does not matter. Ex: add_groups = c("Time_of_Day") |
| inc_wake | Optional argument corresponding to whether or not to include WAKE in the grouping of the final output (if WAKE column is available). By default, inc_wake = TRUE which will include the WAKE column in the groups by which to calculate the respective metrics. |

Value

A tibble object with a row corresponding to each subject, or alternatively a row corresponding to each date if inc_date = TRUE. The resulting tibble consists of:

- ID: The unique identifier of the subject. For single-subject datasets, ID = 1
- VISIT: (If applicable) Corresponds to the visit # of the subject, if more than 1
- WAKE: (If applicable) Corresponds to the awake status of the subject (0 = asleep | 1 = awake)
- SBP_mean / DBP_mean: Calculates the mean of systolic blood pressure readings for the specified time granularity.
- SBP_med / DBP_med: Calculates the median of systolic blood pressure readings for the specified time granularity.
- N: The number of observations for that particular grouping. If inc_date = TRUE, N corresponds to the number of observations for that date. If inc_date = FALSE, N corresponds to the number of observations for the most granular grouping available (i.e. a combination of ID, VISIT, and WAKE)
- Any add_groups variables supplied to function argument will be present as a column in the resulting tibble.

Examples

```
# Load data
data(bp_hypos)
data(bp_jhs)
```

```
# Process bp_hypnos
hyp_proc <- process_data(bp_hypnos, sbp = "SYST", dbp = "DIAST", date_time = "date.time",
id = "id", wake = "wake", visit = "visit", hr = "hr", pp = "pp", map = "map", rpp = "rpp")
# Process bp_jhs data
jhs_proc <- process_data(bp_jhs, sbp = "Sys.mmHg.", dbp = "Dias.mmHg.", date_time = "DateTime",
hr = "Pulse.bpm.")

# BP Center Calculation
bp_center(hyp_proc, subj = c(70417, 70435))
```

bp_children

B-Proact1v Children Data

Description

The bp_children data set contains information on 1,283 children from Bristol, UK, who each took three blood pressure readings per visit over the course of two observation periods (at ages 9 and 11) and had their body mass index (BMI), physical activity, and sedentary time information recorded. The study examined how sedentary behavior and physical activity affected children progressing through primary school to better understand the relationship between elevated blood pressure in children and its impact on the development of cardiovascular disease into adulthood

Usage

```
bp_children
```

Format

A data frame containing 15 variables pertaining to blood pressure and physical activity as follows:

id Child ID

reading Index of the blood pressure reading

sbp Systolic Blood Pressure (mmHg)

dbp Diastolic Blood Pressure (mmHg)

gender 1 = Male

2 = Female

hh_educ Household Highest Education:

1 = Up to GCSE/O level or equiv

2 = A level/NVQ or equiv

3 = Degree/HND or equiv

4 = Higher degree (MSc/PhD) or equiv

visit Visit #

age Age in Years

ht Height (ft)

wt Weight (lbs)

bmi Body Mass Index

N.valid.days.all Number of days of child accelerometer data overall

avg.mins.all Average minutes per day over all valid days

sed.avg.mins.all Average sedentary minutes per day over all valid days

mvpa.avg.mins.all Average minutes of Moderate to Vigorous Physical Activity (MVPA) per day over all valid days

Details

(Solomon-Moore E, Salway R, Emm-Collison L, Thompson JL, Sebire SJ, Lawlor DA, Jago R (PI). 2020).

Licensed under a CC-BY Creative Commons Attribution 4.0 International

Source

Original Paper: [doi:10.1371/journal.pone.0232333](https://doi.org/10.1371/journal.pone.0232333)

Data: [doi:10.5281/zenodo.1049587](https://doi.org/10.5281/zenodo.1049587)

Principal Investigator (PI): Russ Jago (University of Bristol)

bp_cv

Coefficient of Variation (CV)

Description

Calculate the coefficient of variation at various levels of granularity based on what is supplied (ID, VISIT, WAKE, and / or DATE) for either SBP, DBP, or both. CV is a measure of dispersion

Usage

```
bp_cv(
  data,
  inc_date = FALSE,
  subj = NULL,
  bp_type = c("both", "sbp", "dbp"),
  add_groups = NULL,
  inc_wake = TRUE
)
```

Arguments

| | |
|------------|---|
| data | Required argument. Pre-processed dataframe with SBP and DBP columns with optional ID, VISIT, WAKE, and DATE columns if available. Use <code>process_data</code> to properly format data. |
| inc_date | Optional argument. Default is FALSE. As ABPM data typically overlaps due to falling asleep on one date and waking up on another, the <code>inc_date</code> argument is typically kept as FALSE, but the function will work regardless. Setting <code>inc_date = TRUE</code> will include these dates as a grouping level. |
| subj | Optional argument. Allows the user to specify and subset specific subjects from the ID column of the supplied data set. The <code>subj</code> argument can be a single value or a vector of elements. The input type should be character, but the function will comply with integers so long as they are all present in the ID column of the data. |
| bp_type | Optional argument. Determines whether to calculate CV for SBP values or DBP values, or both. For both SBP and DBP ARV values use <code>bp_type = 'both'</code> , for SBP-only use <code>bp_type = 'sbp'</code> , and for DBP-only use <code>bp_type = 'dbp'</code> . If no type specified, default will be set to 'both' |
| add_groups | Optional argument. Allows the user to aggregate the data by an additional "group" to further refine the output. The supplied input must be a character vector with the strings corresponding to existing column names of the processed data input supplied. Capitalization of <code>add_groups</code> does not matter. Ex: <code>add_groups = c("Time_of_Day")</code> |
| inc_wake | Optional argument corresponding to whether or not to include WAKE in the grouping of the final output (if WAKE column is available). By default, <code>inc_wake = TRUE</code> which will include the WAKE column in the groups by which to calculate the respective metrics. |

Value

A tibble object with a row corresponding to each subject, or alternatively a row corresponding to each date if `inc_date = TRUE`. The resulting tibble consists of:

- ID: The unique identifier of the subject. For single-subject datasets, `ID = 1`
- VISIT: (If applicable) Corresponds to the visit # of the subject, if more than 1
- WAKE: (If applicable) Corresponds to the awake status of the subject (0 = asleep | 1 = awake)
- CV_SBP / CV_DBP: Calculates the ratio of standard deviation to the mean. CV_SBP or CV_DBP is useful for comparing the degree of variation from one data series to another.
- SD_SBP / SD_DBP: For completeness, the `cv` function also includes the standard deviation as a comparison metric to measure spread around the average.
- N: The number of observations for that particular grouping. If `inc_date = TRUE`, N corresponds to the number of observations for that date. If `inc_date = FALSE`, N corresponds to the number of observations for the most granular grouping available (i.e. a combination of ID, VISIT, and WAKE)
- Any `add_groups` variables supplied to function argument will be present as a column in the resulting tibble.

Examples

```
# Load data
data(bp_hypos)
data(bp_jhs)

# Process bp_hypos
hyp_proc <- process_data(bp_hypos, sbp = "SYST", dbp = "DIAST", date_time = "date.time",
id = "id", wake = "wake", visit = "visit", hr = "hr", pp = "pp", map = "map", rpp = "rpp")
# Process bp_jhs data
jhs_proc <- process_data(bp_jhs, sbp = "Sys.mmHg.", dbp = "Dias.mmHg.", date_time = "DateTime",
hr = "Pulse.bpm.")

# CV Calculation
bp_cv(hyp_proc, inc_date = TRUE, add_groups = "SBP_Category", bp_type = 'sbp')
bp_cv(jhs_proc, add_groups = c("meal_time"))
# Notice that meal_time is not a column from process_data, but it still works
```

bp_ghana

*Task Shifting and Blood Pressure Control in Ghana Data***Description**

The bp_ghana data set includes 757 subjects across 32 community health centers who were partitioned into intervention groups according to a pragmatic cluster-randomized trial with 389 in the health insurance coverage (HIC) group and 368 in another group consisting of a combination of HIC with a nurse-led task-shifting strategy for hypertension control (TASSH) (this group is denoted TASSH + HIC). This study was an effort to assess the comparative effectiveness of HIC alone versus the combination of TASSH + HIC on reducing systolic blood pressure among patients with uncontrolled hypertension in Ghana. Baseline blood pressure measurements and 12 month follow-up results were collected among subjects, 85% of whom had 12 month data present

Usage

bp_ghana

Format

A data frame containing 21 variables pertaining to blood pressure as follows:

ID Subject ID

Time_Elapsed How much time elapsed between readings: Baseline measurement, 6 month follow-up, 12 month follow-up

SBP Systolic Blood Pressure

DBP Diastolic Blood Pressure

Age Age in Years

Gender 0 = Male

1 = Female

EducationLevel Highest Degree Earned:

- 1 = No Schooling
- 2 = Primary Schooling (Grades 1 to 6)
- 3 = Junior Secondary Schooling (JSS) (Grades 7-8)
- 4 = Secondary School (Grades 9-11)
- 5 = Completed Secondary School
- 6 = Technical school certificate
- 7 = Some college but no degree
- 8 = Associate degree
- 9 = Graduate or Professional school (MD, JD, etc.)
- 999 = Not specified

EmploymentStatus 0 = Unemployed

- 1 = Employed

Literacy 0 = Illiterate

- 1 = Literate

Smoking 1 = Smoker

- 2 = Occasional
- 3 = Ex-Smoker
- 4 = Non-Smoker

Income Income level expressed in home currency - Ghanaian cedi (GhC)**SiteNumber** Site Location in Ghana:

- 1 = Suntreso
- 2 = Ananekrom
- 3 = Manhiya
- 4 = Apatrapa
- 5 = Nkawie
- 6 = Afrancho
- 7 = Kumsai South
- 8 = Mampongteneng
- 9 = Mampong
- 10 = Bomfa
- 11 = Ejura
- 12 = Kofiase
- 13 = Kokofu
- 14 = Asuofia
- 15 = Konongo
- 16 = Subirisu
- 17 = Effiduase
- 18 = Abuakwa
- 19 = Tafo
- 20 = KMA
- 21 = Methodist
- 22 = Kenyasi
- 23 = Asonamaso

24 = Juansa
25 = Juaso
26 = Sekyredumase
27 = Nkenkaasu
28 = Berekese
29 = Bekwai
30 = Dwease
31 = Kuntanese
32 = Foase

CVRisk Cardiovascular Risk Assessment (%) at Baseline:

1) <10%
2) 10-20%
3) 20-30%
4) 30 to 40%
999= Missing Data

BMI Body Mass Index

BMIClassification Classification of BMI:

1 = Underweight (<18.5 kg/m²)
2 = Normal (18.5 to 24.9 kg/m²)
3 = Overweight (25.0 to 29.9 kg/m²)
4 = Obese (>30 kg/m²)

PhysicalActivity All activity in weighted MET minutes (per week) at Baseline

TrtorCtrl 0 = Control

1 = Treatment

RuralUrban 0 = Rural

1 = Urban

DoctorsAvailable # of doctors on staff

NursesAvailable # of nurses on staff

Patientsannually # of patients seen annually

Details

(Ogedegbe G, Plange-Rhule J, Gyamfi J, Chaplin W, Ntim M, Apusiga K, Iwelunmor J, Awudzi KY, Quakyi KN, Mogavero JN, Khurshid K, Tayo B, Cooper R. 2019).

Licensed under a CC-0 1.0 (Creative Commons) Universal Public Domain Dedication License

Source

Original Paper: [doi:10.1371/journal.pmed.1002561](https://doi.org/10.1371/journal.pmed.1002561)

Data: [doi:10.5061/dryad.16c9m51](https://doi.org/10.5061/dryad.16c9m51)

bp_hist *Blood Pressure Histograms*

Description

The bp_hist function serves to display the frequencies of the SBP and DBP readings. These histograms are formatted to complement the bp_scatter function.

Usage

```
bp_hist(data, subj = NULL, bins = 30, na.rm = TRUE)
```

Arguments

| | |
|-------|---|
| data | A processed dataframe resulting from the process_data function that contains the SBP, DBP, SBP_CATEGORY, and DBP_CATEGORY columns. |
| subj | Optional argument. Allows the user to specify and subset specific subjects from the ID column of the supplied data set. The subj argument can be a single value or a vector of elements. The input type should be character, but the function will comply with integers so long as they are all present in the ID column of the data. |
| bins | An integer specifying how many bins to use for histogram plots. This is a ggplot parameter; default value set to 30 |
| na.rm | An logical value specifying whether or not to remove empty values from data frame. This is a ggplot parameter; default value set to TRUE. |

Value

A list containing four objects: three histogram visual graphics corresponding to the SBP / DBP totals, SBP frequency, and DBP frequency, and a fourth list element corresponding to a plot legend object for use in the bp_report function

Examples

```
data("bp_jhs")
data("bp_hypnos")
hyp_proc <- process_data(bp_hypnos,
  bp_type = 'ABPM',
  sbp = "syst",
  dbp = "DIAST",
  date_time = "date.time",
  id = "id",
  wake = "wake",
  visit = "visit",
  hr = "hr",
  map = "map",
  rpp = "rpp",
  pp = "pp",
  ToD_int = c(5, 13, 18, 23))
```

```

jhs_proc <- process_data(bp_jhs,
                        sbp = "Sys.mmHg.",
                        dbp = "Dias.mmHg.",
                        date_time = "DateTime",
                        hr = "pulse.bpm.")

rm(bp_hypos, bp_jhs)

bp_hist(hyp_proc)
bp_hist(jhs_proc)

```

bp_hypos

*HYPNOS Study - 5 Subject Sample***Description**

ABPM measurements for 5 subjects with Type II diabetes. These data are part of a larger study sample that consisted of patients with Type 2 diabetes recruited from the general community. To be eligible, patients with Type 2 diabetes, not using insulin therapy and with a glycosylated hemoglobin (HbA_{1c}) value at least 6.5

Usage

bp_hypos

Format

A data frame with the following columns:

NR. Integer. The index corresponding to the reading of a particular subject for a given visit.

DATE.TIME Character. The date-time value corresponding to the given reading.

SYST Integer. The systolic blood pressure reading.

MAP Integer. The mean arterial pressure value.

DIAST Integer. The diastolic blood pressure reading.

HR Integer. The heart rate value (measured in beats per minute – bpm).

PP Integer. The pulse pressure value calculated as the systolic value - the diastolic value.

RPP Integer. The rate pressure product calculated as the systolic reading multiplied by the heart rate value.

WAKE Integer. A logical indicator value corresponding to whether or not a subject is awake (WAKE = 1) or not.

ID Integer. A unique identifier for each subject.

VISIT Integer. A value associated with the visit number or a particular subject.

DATE Character. A date-valued column indicating the date of the given reading. Dates are specified according to their actual date (i.e. 01:00 corresponds to the next date, even if the subject is awake. Awake-state is indicated via WAKE).

bp_jhs

Blood Pressure - 1 Subject - John Schwenck

Description

Single-subject self-monitored blood pressure readings over 108 days (April 15, 2019 - August 01, 2019). This data set has been processed and uploaded to the Harvard Dataverse for public use. It contains variables pertaining to Date/Time, Systolic BP, Diastolic BP, and Heart Rate. The data assumes a threshold blood pressure of 135 / 85 which is used to calculate excess amounts.

Usage

bp_jhs

Format

A data frame with the following columns:

DateTime A POSIXct-formatted column corresponding to the date and time of the corresponding reading in local time.

Month Integer. The month corresponding to the Date column.

Day Integer. The day of the month corresponding to the Date column.

Year Integer. The year corresponding to the Date column.

DayofWk Character. The day of the week corresponding to the Date column.

Hour Integer. The hour corresponding to the DateTime column.

Meal_Time Character. The estimated meal time corresponding to the DateTime column.

Sys.mmHg. Integer. The systolic blood pressure reading.

Dias.mmHg. Integer. The diastolic blood pressure reading.

bpDelta Integer. The difference between the Sys.mmHg. and Dias.mmHg. column. This is also known as the Pulse Pressure.

Pulse.bpm. Integer. The heart rate value (measured in beats per minute – bpm).

Source

[doi:10.7910/DVN/EA1SAP](https://doi.org/10.7910/DVN/EA1SAP)

| | |
|--------|---|
| bp_mag | <i>Blood Pressure Magnitude (Peak and Trough)</i> |
|--------|---|

Description

Calculate the Peak and Trough defined as the max BP - average BP and average BP - min BP, respectively.

Usage

```
bp_mag(
  data,
  inc_date = FALSE,
  subj = NULL,
  bp_type = c("both", "sbp", "dbp"),
  add_groups = NULL,
  inc_wake = TRUE
)
```

Arguments

| | |
|------------|---|
| data | Required argument. Pre-processed dataframe with SBP and DBP columns with optional ID, VISIT, WAKE, and DATE columns if available. Use <code>process_data</code> to properly format data. |
| inc_date | Optional argument. Default is <code>FALSE</code> . As ABPM data typically overlaps due to falling asleep on one date and waking up on another, the <code>inc_date</code> argument is typically kept as <code>FALSE</code> , but the function will work regardless. Setting <code>inc_date = TRUE</code> will include these dates as a grouping level. |
| subj | Optional argument. Allows the user to specify and subset specific subjects from the ID column of the supplied data set. The <code>subj</code> argument can be a single value or a vector of elements. The input type should be character, but the function will comply with integers so long as they are all present in the ID column of the data. |
| bp_type | Optional argument. Determines whether to calculate magnitude for SBP values or DBP values, or both. For both SBP and DBP ARV values use <code>bp_type = 'both'</code> , for SBP-only use <code>bp_type = 'sbp'</code> , and for DBP-only use <code>bp_type = 'dbp'</code> . If no type specified, default will be set to <code>'both'</code> |
| add_groups | Optional argument. Allows the user to aggregate the data by an additional "group" to further refine the output. The supplied input must be a character vector with the strings corresponding to existing column names of the processed data input supplied. Capitalization of <code>add_groups</code> does not matter. Ex: <code>add_groups = c("Time_of_Day")</code> |
| inc_wake | Optional argument corresponding to whether or not to include WAKE in the grouping of the final output (if WAKE column is available). By default, <code>inc_wake = TRUE</code> which will include the WAKE column in the groups by which to calculate the respective metrics. |

Value

A tibble object with a row corresponding to each subject, or alternatively a row corresponding to each date if `inc_date = TRUE`. The resulting tibble consists of:

- `ID`: The unique identifier of the subject. For single-subject datasets, `ID = 1`
- `VISIT`: (If applicable) Corresponds to the visit # of the subject, if more than 1
- `WAKE`: (If applicable) Corresponds to the awake status of the subject (0 = asleep | 1 = awake)
- `Peak_SBP / Peak_DBP`: Measures the difference between the max value and the average
- `Trough_SBP / Trough_DBP`: Measures the difference between the average and the min value
- `N`: The number of observations for that particular grouping. If `inc_date = TRUE`, `N` corresponds to the number of observations for that date. If `inc_date = FALSE`, `N` corresponds to the number of observations for the most granular grouping available (i.e. a combination of `ID`, `VISIT`, and `WAKE`)
- Any `add_groups` variables supplied to function argument will be present as a column in the resulting tibble.

Examples

```
# Load data
data(bp_hypos)
data(bp_jhs)

# Process bp_hypos
hyp_proc <- process_data(bp_hypos, sbp = "SYST", dbp = "DIAST", date_time = "date.time",
id = "id", wake = "wake", visit = "visit", hr = "hr", pp = "pp", map = "map", rpp = "rpp")
# Process bp_jhs data
jhs_proc <- process_data(bp_jhs, sbp = "Sys.mmHg.", dbp = "Dias.mmHg.", date_time = "DateTime",
hr = "Pulse.bpm.")

# BP Magnitude Calculation
bp_mag(hyp_proc)
bp_mag(jhs_proc, inc_date = TRUE)
```

bp_preg

Pregnancy Day Assessment Clinic Data

Description

The `bp_preg` data set includes 209 women each with 30 minute recordings during the Pregnancy Day Assessment Clinic (PDAC) observation window for up to a maximum of 240 minutes (i.e. a maximum of 8 total readings per subject per observation window in addition to an initial "booking" reading before the PDAC assessment). This recent study in obstetrics and gynecology investigated pregnancy-induced hypertension (PIH) and pre-eclampsia (PE) prediction by analyzing cardiac and physiological information to determine whether the blood pressure assessment of the first observation window of 1 hour (60 minutes) was sufficient relative to the standard 4 hour (240 minute) window.

Usage

bp_preg

Format

A data frame containing 55 variables related to physiological assessment during pregnancy. The data variable dictionary is as follows:

Abdominal.pain Binary indicator for whether an individual exhibits abdominal pain (1 = yes) or not (0 = no)

Accelerations Fetal heart rate accelerations

Admission Admission from PDAC

Age Maternal age at estimated date of confinement

ALP Alkaline phosphatase u/L

ALT Alanine transaminase u/L

AN_PET Binary indicator for Antenatal diagnosis of pre-eclampsia 1 = yes, 0 = no

Antihypertensive.Meds Current antihypertensive medication

Asymptomatic Binary indicator for whether an individual is asymptomatic (1 = yes) or not (0 = no)

Baseline Baseline fetal heart rate (normal, bradycardia, tachycardia)

BMI Body Mass Index

Creatinine micromol/L

CTG Cardiotocogram

D_att_Dryad Date of attendance modified by adding a random number of days between -7 and +7

DBP Diastolic Blood Pressure

Decelerations Fetal heart rate decelerations

DOB_Dryad Maternal date of birth modified by adding a random number of days between -7 and +7

DrRV Medical review during PDAC

EDC_Dryad Estimated date of confinement modified by adding a random number of days between -7 and +7

EmCS Emergency Caesarean section

Final.Diagnosis. Final diagnosis: 0 = nil, 1 = pregnancy induced hypertension, 2 = pre-eclampsia

GA_att Gestational age (weeks) at attendance

GGT Gamma glutamyl transaminase u/L

Grav Gravidity: number of pregnancies including the current one

Headache Binary indicator for whether an individual has a headache (1 = yes) or not (0 = no)

Ht Maternal Height (cm)

Hyperreflexia Binary indicator for whether an individual exhibits Hyperreflexia (1 = yes) or not (0 = no)

IOL Induction of labour

ID Subject ID #

IP_PET Intrapartum diagnosis of pre-eclampsia 1 = yes, 0 = no

Nausea Binary indicator for whether an individual exhibits Nausea (1 = yes) or not (0 = no)

Oedema Binary indicator for whether an individual exhibits Oedema (1 = yes) or not (0 = no)

Para Parity: number of pregnancies proceeding to 20 or more weeks, not including the current one

PHx_ASA Prescribed aspirin in this pregnancy

PHx_Eclampsia Past history of eclampsia

PHx_EssBP Past history of essential hypertension

PHx_PET Past history of pre-eclampsia

PHx_Smoker Smoking history

PIERS Pre-eclampsia Integrated Estimate of Risk (%)

PN_PET Postnatal diagnosis of pre-eclampsia 1 = yes, 0 = no

Platelets 10^9 per mL

PrevPDAC Number of previous PDAC assessments this pregnancy

Privacy Generic privacy consent form permits participation in audit

SBP Systolic Blood Pressure

SOB Binary indicator for whether an individual exhibits Shortness of Breath (SOB) (1 = yes) or not (0 = no)

Safe.for.discharge.at.1.hour. Binary indicator for whether an individual is safe for discharge at 1 hour (1 = yes) or not (0 = no)

Safe.for.discharge.at.1.hour...Other.please.specify. Binary indicator for whether an individual is safe for discharge at 1 hour - other - comments

Self.discharge Self-discharge from PDAC

Time_Elapsed 30 minute recordings during the Pregnancy Day Assessment Clinic (PDAC) observation window for up to a maximum of 240 minutes including the "Booking" recording

Urate mmol/L

Urea micromol/L

UrinePCR Spot urine protein:creatinine ratio mg/mmol

Variability Fetal heart rate variability as judged visually

Visual.Disturbances Binary indicator for whether an individual exhibits Visual Disturbances (1 = yes) or not (0 = no)

Wt Pre-pregnancy or early pregnancy weight (kg)

Details

(McCarthy EA, Carins TA, Hannigan Y, Bardien N, Shub A, Walker S. 2015)

Licensed under a CC-0 1.0 (Creative Commons) Universal Public Domain Dedication License

Source

[doi:10.5061/dryad.0bq15](https://doi.org/10.5061/dryad.0bq15)

| | |
|----------|-----------------------------|
| bp_range | <i>Blood Pressure Range</i> |
|----------|-----------------------------|

Description

Calculates the range (max - min) of both SBP and DBP values in addition to max and min values for reference with the option to specify date as an additional level of granularity

Usage

```
bp_range(
  data,
  inc_date = FALSE,
  subj = NULL,
  add_groups = NULL,
  inc_wake = TRUE
)
```

Arguments

| | |
|------------|---|
| data | Required dataframe with SBP and DBP columns corresponding to Systolic and Diastolic BP. This dataframe should come from data_process |
| inc_date | Optional argument. Default is FALSE. As ABPM data typically overlaps due to falling asleep on one date and waking up on another, the inc_date argument is typically kept as FALSE, but the function will work regardless. Setting inc_date = TRUE will include these dates as a grouping level. |
| subj | Optional argument. Allows the user to specify and subset specific subjects from the ID column of the supplied data set. The subj argument can be a single value or a vector of elements. The input type should be character, but the function will comply with integers so long as they are all present in the ID column of the data. |
| add_groups | Optional argument. Allows the user to aggregate the data by an additional "group" to further refine the output. The supplied input must be a character vector with the strings corresponding to existing column names of the processed data input supplied. Capitalization of add_groups does not matter. Ex: add_groups = c("Time_of_Day") |
| inc_wake | Optional argument corresponding to whether or not to include WAKE in the grouping of the final output (if WAKE column is available). By default, inc_wake = TRUE which will include the WAKE column in the groups by which to calculate the respective metrics. |

Value

A tibble with SBP_max, SBP_min, SBP_range, DBP_max, DBP_min, DBP_range and any additional optional columns included in data such as ID, VISIT, WAKE, and DATE. If inc_date = TRUE, each row will correspond to a date. The resulting tibble consists of:

- ID: The unique identifier of the subject. For single-subject datasets, ID = 1
- VISIT: (If applicable) Corresponds to the visit # of the subject, if more than 1
- WAKE: (If applicable) Corresponds to the awake status of the subject (0 = asleep | 1 = awake)
- SBP_max / DBP_max: Finds the maximum value for the given grouping granularity
- SBP_min / DBP_min: Finds the minimum value for the given grouping granularity
- SBP_range / DBP_range: Calculates the range between the max and min values
- N: The number of observations for that particular grouping. If inc_date = TRUE, N corresponds to the number of observations for that date. If inc_date = FALSE, N corresponds to the number of observations for the most granular grouping available (i.e. a combination of ID, VISIT, and WAKE)
- Any add_groups variables supplied to function argument will be present as a column in the resulting tibble.

Examples

```
# Load bp_hypnos
data(bp_hypnos)
data(bp_jhs)

# Process bp_hypnos
hypnos_proc <- process_data(bp_hypnos, sbp = "SYST", dbp = "DIAST", date_time = "date.time",
id = "id", wake = "wake", visit = "visit", hr = "hr", pp = "pp", map = "map", rpp = "rpp")
# Process bp_jhs data
jhs_proc <- process_data(bp_jhs, sbp = "Sys.mmHg.", dbp = "Dias.mmHg.", date_time = "DateTime",
hr = "Pulse.bpm.")

# Calculate BP range
bp_range(hypnos_proc)
bp_range(jhs_proc, inc_date = TRUE, add_groups = c("meal_time"))
# Notice that meal_time is not a column from process_data, but it still works
```

bp_rats

Blood Pressure in Salt-Sensitive Dahl Rats Data

Description

The bp_rats data set includes arterial blood pressure waveform time series data of the SS(n = 9) and SS.13 (n = 6) genetic strains of Dahl rats sampled at 100 Hz who were each administered a low and high salt diet. It is taken from the study of Bugenhagen et al.(2010) which sought to investigate the origins of the baroreflex dysfunction in salt-sensitive Dahl rats on Hypertension.

Usage

bp_rats

Format

A data frame containing 5 variables pertaining to arterial continuous waveform blood pressure as follows:

rat_type The type of a particular Dahl Rat (either SS or SSBN13) corresponding to the sodium intake administered:

ss_hs = SS rat given the high sodium diet
ss_ls = SS rat given the low sodium diet
ssbn13_hs = SSBN13 rat given the high sodium diet
ssbn13_ls = SSBN13 rat given the low sodium diet

rat_ID ID # corresponding to a particular rat. There are 9 SS rats and 6 SSBN13 rats.

ABP Continuous waveform data of each rat's arterial (blood) pressure sampled at 100 Hz.

time_sec Amount of time elapsed, expressed in seconds

time_min Amount of time elapsed, expressed in minutes

Details

(Goldberger A., Amaral L., Glass L., Hausdorff J., Ivanov P. C., Mark R., Bugenhagen S.M., Cowley A.W. Jr, Beard D.A., ... & Stanley H. E. 2000).

Licensed under a ODC-BY (Creative Commons) Open Data Commons Attribution License 1.0

Source

Original Paper: [doi:10.1152/physiolgenomics.00027.2010](https://doi.org/10.1152/physiolgenomics.00027.2010)

Data: [doi:10.13026/C20597](https://doi.org/10.13026/C20597)

bp_report

Blood Pressure Report

Description

The bp_report function serves to aggregate various data visuals and metrics pertaining to the supplied data set into a clean formatted report.

Usage

```
bp_report(  
  data,  
  subj = NULL,  
  inc_low = TRUE,  
  inc_crisis = TRUE,  
  group_var = NULL,  
  save_report = TRUE,
```

```

path = NULL,
filename = "bp_report",
width = 11,
height = 8.5,
filetype = "pdf",
units = "in",
scale = 1.25,
plot = TRUE,
hist_bins = 30
)

```

Arguments

| | |
|-------------|---|
| data | <p>Required argument. A processed dataframe resulting from the <code>process_data</code> function to properly format data set. In order for the <code>bp_report</code> function to work properly, the following variables must be present and properly formatted:</p> <ul style="list-style-type: none"> • SBP • DBP • DATE_TIME - Used in the <code>process_data</code> function to create additional columns that are needed for the <code>bp_report</code> function (SBP_Category, DBP_Category, Weekday, and Time_of_Day.) • SBP_CATEGORY - Automatically calculated in the <code>process_data</code> function • DBP_CATEGORY - Automatically calculated in the <code>process_data</code> function • DAY_OF_WEEK - Automatically calculated in the <code>process_data</code> function • TIME_OF_DAY - Automatically calculated in the <code>process_data</code> function • ID - (If applicable) Used for separating out different individuals, if more than one • VISIT - (If applicable) Used for separating out an individuals' different visits, if more than one |
| subj | Optional argument. Allows the user to specify and subset specific subjects from the ID column of the supplied data set. The <code>subj</code> argument can be a single value or a vector of elements. The input type should be character, but the function will comply with integers so long as they are all present in the ID column of the data. |
| inc_low | Optional logical argument dictating whether or not to include the "Low" category for BP classification column (and the supplementary SBP/DBP Category columns). Default set to TRUE. |
| inc_crisis | Optional logical argument dictating whether or not to include the "Crisis" category for BP classification column (and the supplementary SBP/DBP Category columns). Default set to TRUE. |
| group_var | A categorical column of the input data set that the individual points are to be grouped / separated by for a given plot. Cannot contain more than 10 levels (to avoid overcrowding the plot). This is different from the <code>wrap_var</code> argument which segments plots by category and cannot be used with the <code>process_data</code> function. |
| save_report | A logical value indicating whether to save the BP report output as a separate file. The default is TRUE indicating that the report will be saved. |

| | |
|-----------|--|
| path | Optional argument. A string corresponding to the respective file path by which the report is to be saved. Do not include trailing slashes (i.e. ~/loc/) or the file name (i.e. ~/loc/testfile.pdf). By default, if not path argument specified, will save at the current working directory. |
| filename | Optional argument. A string corresponding to the name of the report. The default is "bp_report". The string cannot begin with a number or non-alphabetical character. Note: DO NOT include the file type extension (such as ".pdf" or ".png") at the end of the string; the bp_report function will automatically join the name with the file type. |
| width | Optional argument. An numeric value corresponding to the width of the output document. The default is set to 12 inches. |
| height | Optional argument. An numeric value corresponding to the height of the output document. The default is set to 8.53 inches. |
| filetype | A string corresponding to the particular type of file that the report is to be saved as. Although PDF is the default possible options include: <ul style="list-style-type: none"> • pdf (default) • png • jpeg • tiff • bmp • eps • ps |
| units | A character string corresponding to the unit of measurement that the width and height correspond to in the exported output. The default is inches ("in"), but centimeters ("cm") and millimeters ("mm") are also available. |
| scale | A multiplicative scaling factor for the report output. |
| plot | A logical value indicating whether to automatically produce the plot of bp_report, or suppress the output. The default value is TRUE. If false, the returned object is a grob that can be plotted using grid.arrange |
| hist_bins | An integer specifying how many bins to use for histogram plots. This is a ggplot parameter; default value set to 30 |

Value

If `plot = TRUE`, the function produces a plot of BP report that contains scatterplot of BP values by stages (see [bp_scatter](#)), histograms of BP values by stages (see [bp_hist](#)) and frequency tables of BP values by stages and day of the week/time of the day (see [dow_tod_plots](#)). If `plot = FALSE`, the function returns the grob object that can be plotted later using [grid.arrange](#). If `save_report = TRUE`, the report will be automatically saved at the current working directory (can be checked using `getwd()`) or at specified file path.

Examples

```

data("bp_jhs")
data("bp_hypos")
hyp_proc <- process_data(bp_hypos,
  sbp = "syst",
  dbp = "DIAST",
  date_time = "date.time",
  id = "id",
  wake = "wake",
  visit = "visit",
  hr = "hr",
  map = "map",
  rpp = "rpp",
  pp = "pp",
  ToD_int = c(5, 13, 18, 23))

jhs_proc <- process_data(bp_jhs,
  sbp = "Sys.mmHg.",
  dbp = "Dias.mmHg.",
  date_time = "DateTime",
  hr = "pulse.bpm.")

rm(bp_hypos, bp_jhs)

## Not run:
# Single-subject Report
# save_report = FALSE for illustrative purposes
# plot = TRUE will automatically generate a plot
bp_report(jhs_proc, save_report = FALSE, plot = TRUE)

# Multi-subject Report
# save_report = FALSE for illustrative purposes
# plot = FALSE will suppress the plot output and return a grob object
out = bp_report(hyp_proc, group_var = 'VISIT', save_report = FALSE, plot = FALSE)
gridExtra::grid.arrange(out)

## End(Not run)

```

bp_scatter

Blood Pressure Stage Scatter Plot

Description

Display all SBP and DBP readings on a scatterplot with deliniation of BP according to the 8 mutually exclusive levels of Hypertension as in Lee et al (2020) (the default), or the levels set by the American Heart Association (AHA).

Usage

```
bp_scatter(
```

```

data,
plot_type = c("stages2020", "AHA"),
subj = NULL,
group_var = NULL,
wrap_var = NULL,
inc_crisis = TRUE,
inc_low = TRUE,
bp_cutoffs = list(c(100, 120, 130, 140, 180), c(60, 80, 80, 90, 120)),
bp_type = c("hbpm", "abpm", "ap")
)

```

Arguments

| | |
|------------|---|
| data | A processed dataframe resulting from the <code>process_data</code> function that contains the SBP, and DBP columns, as well as (potentially) other information that can be used for grouping. |
| plot_type | String corresponding to the particular type of plot to be displayed. Default plot ("stages2020") sets the BP stages according to Lee et al (2020) with 8 mutually exclusive categories. Two additional categories, "Low" or "Crisis", can be determined through the <code>inc_low</code> or <code>inc_crisis</code> function arguments, respectively. Setting <code>plot_type = "AHA"</code> will use the stages according to the guidelines set forth by the American Heart Association (reference: https://www.heart.org/en/health-topics/high-blood-pressure/understanding-blood-pressure-reading). |
| subj | Optional argument. Allows the user to specify and subset specific subjects from the ID column of the supplied data set. The <code>subj</code> argument can be a single value or a vector of elements. The input type should be character, but the function will comply with integers so long as they are all present in the ID column of the data. |
| group_var | A categorical column of the input data set that the individual points are to be grouped / separated by for a given plot. Cannot contain more than 10 levels (to avoid overcrowding the plot). This is different from the <code>wrap_var</code> argument which segments plots by category. The default value is NULL (no grouping). |
| wrap_var | A categorical column of the input data set that the plots are to be segmented by. If there are multiple levels such as time of day, or visit number, the output will include a matrix with each plot corresponding to an individual level. This differs from the <code>group_var</code> argument which separates data within the same plot. The default value is NULL (no wrapping). |
| inc_crisis | A TRUE / FALSE indicator of whether or not to include the "Crisis" (Hypertensive) category to the scatter plot. This is only activated in conjunction with "stages2020" plot type, and if TRUE is defined as SBP > 180 or DBP > 120. If FALSE, those values are displayed as either "ISH - S2", "S2" or "IDH - S2" stages (see details). This argument is ignored with plot type "AHA", where the "Crisis" stage (SBP > 180 or DBP > 120) is always displayed. |
| inc_low | A TRUE / FALSE indicator of whether or not to include the "Low" (Hypotension) category to the scatter plot. This is only activated in conjunction with "stages2020" plot type, and if TRUE is defined as SBP < 100 and DBP > 60. If FALSE, those values are displayed as "Normal". This argument is ignored with plot type "AHA", where the "Low" stage (SBP < 100 and DBP < 60) is always displayed. |

| | |
|------------|--|
| bp_cutoffs | <p>A list containing two vectors corresponding to SBP and DBP cutoffs, respectively. Each vector contains 5 values.</p> <p>The SBP vector (100, 120, 130, 140, 180) corresponds to the upper limits for the following stages: Low (0-100), Normal (100-120), Elevated (120-130), Stage 1 Hypertension (130-140), Stage 2 Hypertension (140-180). When utilizing Lee et al (2020) guidelines, additional stages are included: Isolated Systolic Hypertension for Stage 1 (ISH - S1) (130-140), Isolated Diastolic Hypertension for Stage 1 (IDH - S1) (0-130), ISH - S2 (140-180), and IDH - S2 (0-140).</p> <p>The DBP vector (60, 80, 80, 90, 120) corresponds to the upper limits for the following stages: Low (0-60), Normal (60-80), Elevated (0-80), Stage 1 Hypertension (80-90), Stage 2 Hypertension (90-120). The upper limit of the "Elevated" category repeats in the DBP vector and matches that of Normal. This because according to most guidelines, there is no distinction between DBP cutoffs for Normal and Elevated - these stages are discerned by SBP, not DBP. When utilizing Lee et al (2020) guidelines, additional stages are included: Isolated Diastolic Hypertension for Stage 1 (ISH - S1) (0-80), Isolated Diastolic Hypertension for Stage 1 (IDH - S1) (80-90), ISH - S2 (0-90), and IDH - S2 (90-120).</p> <p>Any SBP reading below 100 or DBP reading below 60 is considered Hypotension ("Low"). Any SBP reading above 180 or DBP reading above 120 is considered a Crisis.</p> <p>When guidelines = "AHA", the cutoffs are automatically adjusted to match BP type without user input, For bp_type = "hbpm", SBP = (100, 120, 130, 135, 160), DBP = (60, 80, 80, 85, 110). Forbp_type = "abpm", SBP = (100, 115, 125, 130, 160), DBP = (60, 75, 75, 80, 105). An adjustment of default cutoffs by the user These choices can be overwritten by directly changing bp_cutoffs, in which case the guidelines are ignored and automatically treated as "Custom".</p> <p>If inc_low = FALSE, although an upper limit value is still required in the SBP vector, the "Low" stage will be omitted in the final output. Similarly, if inc_crisis = FALSE, then the "Crisis" category will be omitted from the final output.</p> |
| bp_type | <p>Required argument specifying which of the three BP data types ("HBPM", "ABPM", or "AP") the input data is. Default bp_type set to "HBPM". This argument determines which processing steps are necessary to yield sensible output.</p> <p>HBPM - Home Blood Pressure Monitor ABPM - Ambulatory Blood Pressure AP - Arterial Pressure</p> <p>NOTE: bp_type impacts blood pressure staging in bp_stages if guidelines = "AHA", for which the cutoffs for each blood pressure stage are automatically adjusted according to bp_type.</p> |

Details

There are eight total stages according to Lee et al (2020) with the options to include two additional categories for "Low" (Hypotension) and Hypertensive "Crisis". The categories are as follows:

- Low - (Optional) Legacy category for consistency with AHA stages. According to the AHA, low blood pressure is any reading with SBP < 100 and DBP < 60, and is depicted in light blue in the scatter plot. This is always displayed in "AHA" plot, and can be displayed in "stages2020" plot by setting inc_low = TRUE.

- Normal - SBP readings less than 120 and DBP readings less than 80. Reading within this range that either have SBP > 100 or DBP > 60 are also considered Normal by AHA. Normal BP is depicted in green in the scatter plot.
- Elevated - SBP readings between 120 - 129 and DBP readings less than 80. Coincides with Elevated stage as defined by AHA. Without intervention to control the condition, individuals are likely to develop Hypertension. Elevated BP is depicted in yellow in the scatter plot.
- Stage 1 - All (SDH) - SBP readings between 130 - 139 and DBP readings between 80 - 89. Stage 1 Hypertension will typically result in doctors prescribing medication or lifestyle changes. Stage 1 BP is depicted in dark orange in the scatter plot. These readings correspond to Stage 1 as defined by AHA.
- Stage 1 - Isolated Diastolic Hypertension (IDH) - SBP readings less than 130, but DBP readings between 80 - 89. This alternative stage 1 level accounts for unusually high diastolic readings, but fairly normal systolic readings and is depicted in orange in the plot. These readings correspond to Stage 1 as defined by AHA.
- Stage 1 - Isolated Systolic Hypertension (ISH) - SBP readings between 130 - 139, but DBP readings less than 80. This alternative stage 1 level accounts for unusually high systolic readings, but fairly normal diastolic readings and is depicted in orange in the plot. These readings correspond to Stage 1 as defined by AHA.
- Stage 2 - All (SDH) - SBP readings between 140 - 180 and DBP readings between 90 - 120. Stage 2 Hypertension will typically result in doctors prescribing both medication and lifestyle changes. Stage 2 BP is depicted in bright red in the scatter plot. These readings correspond to Stage 2 as defined by AHA.
- Stage 2 - Isolated Diastolic Hypertension (IDH) - SBP readings less than or equal to 140, but DBP readings greater than or equal to 90. This alternative stage 2 level accounts for unusually high diastolic readings, but fairly normal systolic readings and is depicted in red. These readings correspond to Stage 2 as defined by AHA.
- Stage 2 - Isolated Systolic Hypertension (IDH) - SBP readings greater than or equal to 140, but DBP readings less or equal to 90. This alternative stage 2 level accounts for unusually high systolic readings, but fairly normal diastolic readings and is depicted in red. These readings correspond to Stage 2 as defined by AHA.
- Crisis - (Optional) Legacy category for consistency with AHA stages. According to the AHA, hypertensive crisis is defined as a SBP reading exceeding 180 or a DBP reading exceeding 120. This stage requires medical attention immediately. Crisis is depicted in red in the scatter plot. This is always displayed in "AHA" plot, and can be displayed in "stages2020" plot by setting `inc_crisis = TRUE`.

Value

A scatter plot graphic using the `ggplot2` package overlaying each reading (represented as points) onto a background that contains each stage

References

Lee H, Yano Y, Cho SMJ, Park JH, Park S, Lloyd-Jones DM, Kim HC. Cardiovascular risk of isolated systolic or diastolic hypertension in young adults. *Circulation*. 2020; 141:1778-1786. doi:10.1161/CIRCULATIONAHA.119.044838

Unger, T., Borghi, C., Charchar, F., Khan, N. A., Poulter, N. R., Prabhakaran, D., ... & Schutte, A. E. (2020). 2020 International Society of Hypertension global hypertension practice guidelines. *Hypertension*, 75(6), 1334-1357. doi:10.1161/HYPERTENSIONAHA.120.15026

Examples

```
data("bp_jhs")
data("bp_hypnos")
data("bp_ghana")
hypnos_proc <- process_data(bp_hypnos,
                           bp_type = 'abpm',
                           sbp = "syst",
                           dbp = "DIAST",
                           date_time = "date.time",
                           id = "id",
                           wake = "wake",
                           visit = "visit",
                           hr = "hr",
                           map = "map",
                           rpp = "rpp",
                           pp = "pp",
                           ToD_int = c(5, 13, 18, 23))

jhs_proc <- process_data(bp_jhs,
                       sbp = "Sys.mmHg.",
                       dbp = "Dias.mmHg.",
                       date_time = "DateTime",
                       hr = "pulse.bpm.")

rm(bp_hypnos, bp_jhs)

# HYPNOS Data
bp_scatter(hypnos_proc,
           inc_crisis = TRUE,
           inc_low = TRUE,
           group_var = "wake",
           wrap_var = "day_of_week")

# JHS Data
bp_scatter(jhs_proc,
           plot_type = "AHA",
           group_var = "time_of_day")

# Ghana Data Set
#(Note that column names are of proper naming convention so no processing needed)
bp_scatter(bp::bp_ghana, inc_crisis = TRUE, inc_low = FALSE, group_var = "TIME_ELAPSED")
```

Description

The `bp_sleep_metrics` function serves to calculate nocturnal metrics from relevant medical literature.

Usage

```
bp_sleep_metrics(data, subj = NULL)
```

Arguments

| | |
|-------------------|--|
| <code>data</code> | User-supplied data set containing blood pressure data. Must contain a Systolic blood pressure (SBP), Diastolic blood pressure (DBP) as well as ID, WAKE, and DATE_TIME columns. |
| <code>subj</code> | Optional argument. Allows the user to specify and subset specific subjects from the ID column of the supplied data set. The <code>subj</code> argument can be a single value or a vector of elements. The input type should be character, but the function will comply with integers so long as they are all present in the ID column of the data. |

Details

NOTE: Any reference to "sleep" in the `bp` package refers to an individual's nocturnal period; "sleep" is used in an informal sense for intuitive purposes. Technically, from a clinical perspective, indication of sleep is currently obtained through means of EEG or other highly specialized equipment. For all intents and purposes, sleep in the context of this package refers to actigraphy-inferred nocturnal periods of rest.

The calculation of BP metrics related to sleep is based on averages of BP readings from four periods as identified in Kairo et al. (2003): presleep or evening (2 hours before sleep start), prewake (2 hours before wake), postwake or morning (2 hours after wake), lowest (3 measurements centered at the minimal BP reading over sleep). The function uses WAKE column to automatically allocate BP measurements to various periods. The following metrics are defined as a function of the period averages (separately for SBP and DBP)

`dip_calc` = $1 - \text{mean_sleep_BP} / \text{mean_wake_BP}$ (dip proportion)

`noct_fall` = $\text{mean_presleep_BP} - \text{mean_lowest_BP}$ (nocturnal fall)

`ST_mbps` = $\text{mean_postwake_BP} - \text{mean_lowest_BP}$ (sleep through morning blood pressure surge)

`PW_mbps` = $\text{mean_postwake_BP} - \text{mean_prewake_BP}$ (prewake morning blood pressure surge)

`ME_avg` = $(\text{mean_presleep_BP} + \text{mean_postwake_BP}) / 2$ (morning-evening average)

`ME_diff` = $\text{mean_postwake_BP} - \text{mean_presleep_BP}$ (morning-evening difference)

`wSD` = $((\text{wake_SD} \times \text{HRS_wake}) + (\text{sleep_SD} \times \text{HRS_sleep})) / (\text{HRS_wake} + \text{HRS_sleep})$ (weighted standard deviation)

Value

The function outputs a list containing 4 tibble objects corresponding to the following tables:

- [[1]] Counts of how many BP measurements were observed overall (N_total), total number of readings during sleep (N_sleep), total number of readings during wake (N_wake), number of unique hours recorded during the sleep period (HRS_sleep), and number of unique hours recorded during the wake period (HRS_wake) for each subject ID and grouping variable
- [[2]] Summary statistics for systolic BP measurements (SBP): mean SBP value over Sleep and Wake, sd SBP value over Sleep and Wake, mean SBP value over presleep period (evening in Kario et al. (2003)), mean SBP value over prewake period, mean SBP value over postwake period (morning in Kario et al. (2003)), mean SBP value over 3 reading centered at the lowest SBP value during sleep
- [[3]] Summary statistics for diastolic BP measurements (DBP), same as for SBP
- [[4]] BP metrics associated with sleep as defined above, separately for SBP and DBP

References

Kario, K., Pickering, T. G., Umeda, Y., Hoshide, S., Hoshide, Y., Morinari, M., ... & Shimada, K. (2003). Morning surge in blood pressure as a predictor of silent and clinical cerebrovascular disease in elderly hypertensives: a prospective study. *Circulation*, 107(10), 1401-1406.

Examples

```
hypnos_proc <- process_data(bp_hypos,
  sbp = "syst",
  dbp = "DIAST",
  date_time = "date.time",
  id = "id",
  wake = "wake",
  visit = "visit",
  hr = "hr",
  map = "map",
  rpp = "rpp",
  pp = "pp",
  bp_type = "ABPM")

bp_sleep_metrics(hypos_proc)
```

bp_stages

Blood Pressure Stage Classification

Description

Adds BP_CLASS, SBP_Category, and DBP_Category columns to supplied dataframe.

Usage

```

bp_stages(
  data,
  sbp,
  dbp,
  bp_type = c("hbpm", "abpm", "ap"),
  inc_low = TRUE,
  inc_crisis = TRUE,
  data_screen = TRUE,
  SUL = 240,
  SLL = 50,
  DUL = 140,
  DLL = 40,
  adj_sbp_dbp = TRUE,
  guidelines = c("Lee_2020", "AHA", "Custom"),
  bp_cutoffs = list(c(100, 120, 130, 140, 180), c(60, 80, 80, 90, 120))
)

```

Arguments

| | |
|-------------|--|
| data | User-supplied dataset containing blood pressure data. Must contain data for Systolic blood pressure and Diastolic blood pressure at a minimum. |
| sbp | Required column name (character string) corresponding to Systolic Blood Pressure (mmHg) |
| dbp | Required column name (character string) corresponding to Diastolic Blood Pressure (mmHg) |
| bp_type | Required argument specifying which of the three BP data types ("HBPM", "ABPM", or "AP") the input data is. Default bp_type set to "HBPM". This argument determines which processing steps are necessary to yield sensible output. HBPM - Home Blood Pressure Monitor ABPM - Ambulatory Blood Pressure AP - Arterial Pressure NOTE: bp_type impacts blood pressure staging in bp_stages if guidelines = "AHA", for which the cutoffs for each blood pressure stage are automatically adjusted according to bp_type. |
| inc_low | Optional logical argument dictating whether or not to include the "Low" category for BP classification column (and the supplementary SBP/DBP Category columns). Default set to TRUE. |
| inc_crisis | Optional logical argument dictating whether or not to include the "Crisis" category for BP classification column (and the supplementary SBP/DBP Category columns). Default set to TRUE. |
| data_screen | Optional logical argument; default set to TRUE. Screens for extreme values in the data for both SBP and DBP according to Omboni, et al (1995) paper - Calculation of Trough:Peak Ratio of Antihypertensive Treatment from Ambulatory Blood Pressure: Methodological Aspects |
| SUL | Systolic Upper Limit (SUL). If data_screen = TRUE, then SUL sets the upper limit by which to exclude any SBP values that exceed this threshold. The default |

is set to 240 per Omboni, et al (1995) paper - Calculation of Trough:Peak Ratio of Antihypertensive Treatment from Ambulatory Blood Pressure: Methodological Aspects

| | |
|-------------|---|
| SLL | Systolic Lower Limit (SLL). If <code>data_screen = TRUE</code> , then SLL sets the lower limit by which to exclude any SBP values that fall below this threshold. The default is set to 50 per Omboni, et al (1995) paper - Calculation of Trough:Peak Ratio of Antihypertensive Treatment from Ambulatory Blood Pressure: Methodological Aspects |
| DUL | Diastolic Upper Limit (DUL). If <code>data_screen = TRUE</code> , then DUL sets the upper limit by which to exclude any DBP values that exceed this threshold. The default is set to 140 per Omboni, et al (1995) paper - Calculation of Trough:Peak Ratio of Antihypertensive Treatment from Ambulatory Blood Pressure: Methodological Aspects |
| DLL | Diastolic Lower Limit (DLL). If <code>data_screen = TRUE</code> , then DLL sets the lower limit by which to exclude any DBP values that fall below this threshold. The default is set to 40 per Omboni, et al (1995) paper - Calculation of Trough:Peak Ratio of Antihypertensive Treatment from Ambulatory Blood Pressure: Methodological Aspects |
| adj_sbp_dbp | Logical indicator to dictate whether or not to run helper functions that adjust / process SBP & DBP columns in supplied data set. Default set to: <code>adj_sbp_dbp = TRUE</code> |
| guidelines | A string designation for the guidelines to follow when mapping BP readings to a respective BP stage. <code>guidelines</code> can take on either "Lee_2020" corresponding to staging in Lee et al (2020), "AHA" corresponding to guidelines by the American Heart Association, see e.g. Muntner et al (2019), or "Custom" based on user-defined cutoffs in <code>bp_cutoffs</code> . By default, AHA guidelines adjust <code>bp_cutoffs</code> depending on the BP type. |
| bp_cutoffs | <p>A list containing two vectors corresponding to SBP and DBP cutoffs, respectively. Each vector contains 5 values.</p> <p>The SBP vector (100, 120, 130, 140, 180) corresponds to the upper limits for the following stages: Low (0-100), Normal (100-120), Elevated (120-130), Stage 1 Hypertension (130-140), Stage 2 Hypertension (140-180). When utilizing Lee et al (2020) guidelines, additional stages are included: Isolated Systolic Hypertension for Stage 1 (ISH - S1) (130-140), Isolated Diastolic Hypertension for Stage 1 (IDH - S1) (0-130), ISH - S2 (140-180), and IDH - S2 (0-140).</p> <p>The DBP vector (60, 80, 80, 90, 120) corresponds to the upper limits for the following stages: Low (0-60), Normal (60-80), Elevated (0-80), Stage 1 Hypertension (80-90), Stage 2 Hypertension (90-120). The upper limit of the "Elevated" category repeats in the DBP vector and matches that of Normal. This because according to most guidelines, there is no distinction between DBP cutoffs for Normal and Elevated - these stages are discerned by SBP, not DBP. When utilizing Lee et al (2020) guidelines, additional stages are included: Isolated Diastolic Hypertension for Stage 1 (ISH - S1) (0-80), Isolated Diastolic Hypertension for Stage 1 (IDH - S1) (80-90), ISH - S2 (0-90), and IDH - S2 (90-120).</p> <p>Any SBP reading below 100 or DBP reading below 60 is considered Hypotension ("Low"). Any SBP reading above 180 or DBP reading above 120 is considered a Crisis.</p> |

When `guidelines = "AHA"`, the cutoffs are automatically adjusted to match BP type without user input. For `bp_type = "hbpm"`, SBP = (100, 120, 130, 135, 160), DBP = (60, 80, 80, 85, 110). For `bp_type = "abpm"`, SBP = (100, 115, 125, 130, 160), DBP = (60, 75, 75, 80, 105). An adjustment of default cutoffs by the user. These choices can be overwritten by directly changing `bp_cutoffs`, in which case the guidelines are ignored and automatically treated as "Custom".

If `inc_low = FALSE`, although an upper limit value is still required in the SBP vector, the "Low" stage will be omitted in the final output. Similarly, if `inc_crisis = FALSE`, then the "Crisis" category will be omitted from the final output.

Details

Supplied dataframe must adhere to the unified format using the `process_data` function.

Value

A dataframe with additional columns corresponding to the stages of blood pressure and the supplementary SBP / DBP categories

References

Lee H, Yano Y, Cho SMJ, Park JH, Park S, Lloyd-Jones DM, et al. Cardiovascular risk of isolated systolic or diastolic hypertension in young adults. *Circulation*. 2020;141(22):1778-1786. doi:10.1161/CIRCULATIONAHA.119.044838

Muntner, P., Carey, R. M., Jamerson, K., Wright Jr, J. T., & Whelton, P. K. (2019). Rationale for ambulatory and home blood pressure monitoring thresholds in the 2017 American College of Cardiology/American Heart Association Guideline. *Hypertension*, 73(1), 33-38. doi:10.1161/HYPERTENSIONAHA.118.11946

Examples

```
# Load bp_hypos
data(bp_hypos)

bp_stages(bp_hypos, sbp = "syst", dbp = "diast")

# Load bp_jhs data
data(bp_jhs)

bp_stages(bp_jhs, sbp = "sys.mmhg.", dbp = "dias.mmhg.")
```

bp_stats

*Aggregated BP Summary Statistics***Description**

Combines the output from the following functions:

- bp_center
- bp_cv
- bp_arv
- bp_sv
- bp_mag
- bp_range

Usage

```
bp_stats(
  data,
  inc_date = FALSE,
  subj = NULL,
  bp_type = c("both", "sbp", "dbp"),
  add_groups = NULL,
  inc_wake = TRUE
)
```

Arguments

| | |
|----------|---|
| data | Required argument. Pre-processed dataframe containing SBP and DBP with optional ID, VISIT, WAKE, and DATE columns if available. Use process_data to properly format data. |
| inc_date | Optional argument. Default is FALSE. As ABPM data typically overlaps due to falling asleep on one date and waking up on another, the inc_date argument is typically kept as FALSE, but the function will work regardless. Setting inc_date = TRUE will include these dates as a grouping level. |
| subj | Optional argument. Allows the user to specify and subset specific subjects from the ID column of the supplied data set. The subj argument can be a single value or a vector of elements. The input type should be character, but the function will comply with integers so long as they are all present in the ID column of the data. |
| bp_type | Optional argument. Determines whether to calculate magnitude for SBP values or DBP values, or both. For both SBP and DBP ARV values use bp_type = 'both', for SBP-only use bp_type = 'sbp', and for DBP-only use bp_type = 'dbp'. If no type specified, default will be set to 'both' |

| | |
|------------|---|
| add_groups | Optional argument. Allows the user to aggregate the data by an additional "group" to further refine the output. The supplied input must be a character vector with the strings corresponding to existing column names of the processed data input supplied. Capitalization of add_groups does not matter. Ex: add_groups = c("Time_of_Day") |
| inc_wake | Optional argument corresponding to whether or not to include WAKE in the grouping of the final output (if WAKE column is available). By default, inc_wake = TRUE which will include the WAKE column in the groups by which to calculate the respective metrics. |

Value

A tibble object with a row corresponding to each subject, or alternatively a row corresponding to each date, if inc_date = TRUE. The resulting tibble consists of:

- ID: The unique identifier of the subject. For single-subject datasets, ID = 1
- N: The number of observations for that particular grouping. If inc_date = TRUE, N corresponds to the number of observations for that date. If inc_date = FALSE, N corresponds to the number of observations for the most granular grouping available (i.e. a combination of ID, VISIT, and WAKE)
- VISIT: (If applicable) Corresponds to the visit # of the subject, if more than 1
- WAKE: (If applicable) Corresponds to the awake status of the subject (0 = asleep | 1 = awake)
- Output from the following functions: bp_center, bp_cv, bp_arv, bp_sv, bp_mag, bp_range
- Any add_groups variables supplied to function argument will be present as a column in the resulting tibble.

Examples

```
# Load data
data(bp_hypos)
data(bp_jhs)

# Process bp_hypos
hyp_proc <- process_data(bp_hypos, sbp = "SYST", dbp = "DIAST", date_time = "date.time",
id = "id", wake = "wake", visit = "visit", hr = "hr", pp = "pp", map = "map", rpp = "rpp")
# Process bp_jhs data
jhs_proc <- process_data(bp_jhs, sbp = "Sys.mmHg.", dbp = "Dias.mmHg.", date_time = "DateTime",
hr = "Pulse.bpm.")

# BP Stats Aggregated Table
bp_stats(hyp_proc, subj = c(70417, 70435), add_groups = c("SBP_Category"), bp_type = 'sbp')
bp_stats(jhs_proc, add_groups = c("SBP_Category"))
```

bp_sv

*Successive Variation (SV)***Description**

Calculate the successive variation (SV) at various levels of granularity based on what is supplied (ID, VISIT, WAKE, and / or DATE) for either SBP, DBP, or both. SV is a measure of dispersion that takes into account the temporal structure of the data and relies on the sum of squared differences in successive observations, unlike the average real variability (ARV) which relies on the sum of absolute differences.

$$SV = \sqrt{\frac{\sum (x_{i+1} - x_i)^2}{n - 1}}$$

Usage

```
bp_sv(
  data,
  inc_date = FALSE,
  subj = NULL,
  bp_type = c("both", "sbp", "dbp"),
  add_groups = NULL,
  inc_wake = TRUE
)
```

Arguments

| | |
|------------|---|
| data | Required argument. Pre-processed dataframe with SBP and DBP columns with optional ID, VISIT, WAKE, and DATE columns if available. Use process_data to properly format data. |
| inc_date | Optional argument. Default is FALSE. As ABPM data typically overlaps due to falling asleep on one date and waking up on another, the inc_date argument is typically kept as FALSE, but the function will work regardless. Setting inc_date = TRUE will include these dates as a grouping level. |
| subj | Optional argument. Allows the user to specify and subset specific subjects from the ID column of the supplied data set. The subj argument can be a single value or a vector of elements. The input type should be character, but the function will comply with integers so long as they are all present in the ID column of the data. |
| bp_type | Optional argument. Determines whether to calculate SV for SBP values or DBP values, or both. For both SBP and DBP ARV values use bp_type = 'both', for SBP-only use bp_type = 'sbp', and for DBP-only use bp_type = 'dbp'. If no type specified, default will be set to 'both' |
| add_groups | Optional argument. Allows the user to aggregate the data by an additional "group" to further refine the output. The supplied input must be a character vector with the strings corresponding to existing column names of the processed data input supplied. Capitalization of add_groups does not matter. Ex: add_groups = c("Time_of_Day") |

`inc_wake` Optional argument corresponding to whether or not to include WAKE in the grouping of the final output (if WAKE column is available). By default, `inc_wake = TRUE` which will include the WAKE column in the groups by which to calculate the respective metrics.

Details

NOTE: The canonical standard deviation, independent of the temporal structure using the sample average, is added for comparison:

$$SD = \sqrt{\frac{\sum (x_{i+1} - \bar{x})^2}{n - 1}}$$

Value

A tibble object with a row corresponding to each subject, or alternatively a row corresponding to each date if `inc_date = TRUE`. The resulting tibble consists of:

- `ID`: The unique identifier of the subject. For single-subject datasets, `ID = 1`
- `VISIT`: (If applicable) Corresponds to the visit # of the subject, if more than 1
- `WAKE`: (If applicable) Corresponds to the awake status of the subject (0 = asleep | 1 = awake)
- `SV_SBP / SV_DBP`: Calculates the square root of the average squared differences between successive measurements. The resulting value averages across the granularity grouping for however many observations are present.
- `N`: The number of observations for that particular grouping. If `inc_date = TRUE`, `N` corresponds to the number of observations for that date. If `inc_date = FALSE`, `N` corresponds to the number of observations for the most granular grouping available (i.e. a combination of `ID`, `VISIT`, and `WAKE`)
- Any `add_groups` variables supplied to function argument will be present as a column in the resulting tibble.

Examples

```
# Load data
data(bp_hypos)
data(bp_jhs)

# Process bp_hypos
hypos_proc <- process_data(bp_hypos, sbp = "SYST", dbp = "DIAST", date_time = "date.time",
id = "id", wake = "wake", visit = "visit", hr = "hr", pp = "pp", map = "map", rpp = "rpp")
# Process bp_jhs data
jhs_proc <- process_data(bp_jhs, sbp = "Sys.mmHg.", dbp = "Dias.mmHg.", date_time = "DateTime",
hr = "Pulse.bpm.")

# SV Calculation
bp_sv(hypos_proc)
bp_sv(jhs_proc, add_groups = c("meal_time"))
# Notice that meal_time is not a column from process_data, but it still works
```

 bp_tables

Blood Pressure Tables

Description

Generate a list of pertinent table outputs that detail various information specific to blood pressure.

Usage

```
bp_tables(
  data,
  bp_type = c("both", "sbp", "dbp"),
  bp_perc_margin = NULL,
  wake_perc_margin = 2,
  subj = NULL
)
```

Arguments

| | |
|------------------|---|
| data | A processed dataframe resulting from the process_data function that contains the SBP, DBP, DAY_OF_WEEK, Time_of_Day, SBP_CATEGORY, and DBP_CATEGORY columns. |
| bp_type | Optional argument. Determines whether to calculate tables for SBP values or DBP values, or both. For both SBP and DBP ARV values use bp_type = 'both', for SBP-only use bp_type = 'sbp', and for DBP-only use bp_type = 'dbp'. If no type specified, default will be set to 'both' |
| bp_perc_margin | An optional argument that determines which of the marginal totals to include in the raw count tables expressed as percentages. The argument can take on values either NULL (default, both SBP and DBP), 1 (SBP only), or 2 (DBP only). |
| wake_perc_margin | An optional argument that determines which of the marginal totals to include in the tables pertaining to the percentages of awake / asleep readings if applicable (i.e. if the WAKE column is present). The argument can take on values either NULL (both SBP and DBP), 1 (SBP only), or 2 (DBP only). |
| subj | Optional argument. Allows the user to specify and subset specific subjects from the ID column of the supplied data set. The subj argument can be a single value or a vector of elements. The input type should be character, but the function will comply with integers so long as they are all present in the ID column of the data. |

Value

A list of table outputs for various subsets of the data based on which bp_type is selected

Examples

```

data("bp_jhs")
data("bp_hypnos")
hyp_proc <- process_data(bp_hypnos,
                        bp_type = 'ABPM',
                        sbp = "syst",
                        dbp = "DIAST",
                        date_time = "date.time",
                        id = "id",
                        wake = "wake",
                        visit = "visit",
                        hr = "hr",
                        map = "map",
                        rpp = "rpp",
                        pp = "pp",
                        ToD_int = c(5, 13, 18, 23))

jhs_proc <- process_data(bp_jhs,
                        sbp = "Sys.mmHg.",
                        dbp = "Dias.mmHg.",
                        date_time = "DateTime",
                        hr = "pulse.bpm.")

rm(bp_hypnos, bp_jhs)

bp_tables(jhs_proc)
bp_tables(hyp_proc)

```

bp_ts_plots

Blood Pressure Time Series Plots

Description

Blood Pressure Time Series Plots

Usage

```

bp_ts_plots(
  data,
  index = NULL,
  subj = NULL,
  first_hour = 0,
  rotate_xlab = FALSE,
  wrap_var = NULL,
  wrap_row = NULL,
  wrap_col = NULL,
  method = NULL,
  formula = NULL
)

```

Arguments

| | |
|-------------|--|
| data | User-supplied data set containing blood pressure data. Must contain a Systolic blood pressure (SBP), Diastolic blood pressure (DBP) and an ID column. Data must also have either a DATE_TIME or DATE column, unless an index column is specified for the x axis. An index column trumps DATE_TIME and DATE if specified. |
| index | An optional user-specified column denoting x-axis values (other than DATE_TIME or DATE columns). index argument must be a character denoting a column in the supplied data. This argument is useful in the event the data has no corresponding date/time value, but rather an index of values such as (reading #1, #2, #3, etc. or office visit #1, #2, etc. as examples) If NULL, the function will look for DATE_TIME or DATE columns to reference. If index is character, it will be coerced to factor. |
| subj | Optional argument. Allows the user to specify and subset specific subjects from the ID column of the supplied data set. The subj argument can be a single value or a vector of elements. The input type should be character, but the function will comply with integers so long as they are all present in the ID column of the data. |
| first_hour | Optional argument denoting a value corresponding to the first hour of the x-axis for the hour plots. Only applicable to data sets that contain a DATE_TIME column. It is often easier to visualize a BP time series not from 0 - 23 hours but rather an order that begins or ends with waking up such as first_hour = 6 which will sequence the hours from 6am (6, 7, ..., 23, 0, ..., 4, 5). The default value for first_hour is set at 0 |
| rotate_xlab | An optional logical argument to rotate the x axis labels 90 degrees. The default value is set to FALSE. |
| wrap_var | An optional character argument indicating a column by which to "wrap" the data. This function utilizes ggplot2's facet_wrap function to split plots according to some extraneous variable (such as gender, smoking status, awake/asleep, etc.). |
| wrap_row | An optional argument specifying how many rows to wrap the plots if wrap_var is specified. |
| wrap_col | An optional argument specifying how many columns to wrap the plots if wrap_var is specified. |
| method | (ggplot2 plotting arguments) Smoothing method (function) to use. Default is NULL, but also accepts a character vector "lm", "glm", "gam", "loess". NULL implies that the smoothing method will be chosen automatically based on the size of the largest group. See https://ggplot2.tidyverse.org/reference/geom_smooth.html for more details. |
| formula | (ggplot2 plotting arguments) Formula to use in smoothing function. Default is NULL implying $y \sim x$ for fewer than 1,000 observations and $y \sim x(x, bs = "cs")$ otherwise. See https://ggplot2.tidyverse.org/reference/geom_smooth.html for more details. |

Value

If the data does not contain a `DATE_TIME` column, a single list will be returned with the time-dependent plots for each subject ID. If the data does contain a `DATE_TIME` column (and index is not specified), a list of two lists will be returned for each subject ID: one corresponding to the time-dependent plots (according to the `DATE_TIME` values), and another plot corresponding to the `HOUR` plots which show repeated measurements of BP values throughout a 24-hour period. The index of the output therefore corresponds to whether there is only the time-dependent plot type (the former situation) or there are both time-dependent and hourly plot types (the latter situation).

Examples

```
# Pregnancy Data Set

# bp_preg requires the use of the index argument since there are no DATE or
# DATE_TIME columns available
data_preg <- bp::bp_preg
data_preg$Time_Elapsed <- factor(data_preg$Time_Elapsed,
  levels = c("Booking", "0", "30", "60", "90", "120", "150", "180", "210", "240"))

bp::bp_ts_plots(data_preg, index = 'time_elapsed', subj = 1:3)

# JHS Data Set

# bp_jhs returns two lists since there is a DATE_TIME column: one for
# DATE_TIME and one for HOUR
data_jhs <- bp::process_data(bp::bp_jhs,
  sbp = 'sys.mmhg.',
  dbp = 'dias.mmhg.',
  hr = 'pulse.bpm.',
  date_time = 'datetime')

bp::bp_ts_plots(data_jhs)

# HYPNOS Data Set

# bp_hypnos wraps the plots by the visit # since each subject was recorded over
# the course of two office visits
data_hypnos <- bp::process_data(bp::bp_hypnos,
  sbp = 'syst',
  dbp = 'diast',
  date_time = 'date.time')

bp::bp_ts_plots(data_hypnos, wrap_var = 'visit', subj = '70435')
```

Description

THIS IS A DEPRECATED FUNCTION. USE `bp_cv` INSTEAD.

Usage

```
cv(
  data,
  inc_date = FALSE,
  subj = NULL,
  bp_type = 0,
  add_groups = NULL,
  inc_wake = TRUE
)
```

Arguments

| | |
|-------------------------|---|
| <code>data</code> | Required argument. Pre-processed dataframe with SBP and DBP columns with optional ID, VISIT, WAKE, and DATE columns if available. Use <code>process_data</code> to properly format data. |
| <code>inc_date</code> | Optional argument. Default is <code>FALSE</code> . As ABPM data typically overlaps due to falling asleep on one date and waking up on another, the <code>inc_date</code> argument is typically kept as <code>FALSE</code> , but the function will work regardless. Setting <code>inc_date = TRUE</code> will include these dates as a grouping level. |
| <code>subj</code> | Optional argument. Allows the user to specify and subset specific subjects from the ID column of the supplied data set. The <code>subj</code> argument can be a single value or a vector of elements. The input type should be character, but the function will comply with integers so long as they are all present in the ID column of the data. |
| <code>bp_type</code> | Optional argument. Determines whether to calculate ARV for SBP values or DBP values. Default is 0 corresponding to output for both SBP & DBP. For both SBP and DBP ARV values use <code>bp_type = 0</code> , for SBP-only use <code>bp_type = 1</code> , and for DBP-only use <code>bp_type = 2</code> |
| <code>add_groups</code> | Optional argument. Allows the user to aggregate the data by an additional "group" to further refine the output. The supplied input must be a character vector with the strings corresponding to existing column names of the processed data input supplied. Capitalization of <code>add_groups</code> does not matter. Ex: <code>add_groups = c("Time_of_Day")</code> |
| <code>inc_wake</code> | Optional argument corresponding to whether or not to include WAKE in the grouping of the final output (if WAKE column is available). By default, <code>inc_wake = TRUE</code> which will include the WAKE column in the groups by which to calculate the respective metrics. |

Details

Calculate the coefficient of variation at various levels of granularity based on what is supplied (ID, VISIT, WAKE, and / or DATE) for either SBP, DBP, or both. CV is a measure of dispersion

Value

A tibble object with a row corresponding to each subject, or alternatively a row corresponding to each date if `inc_date = TRUE`. The resulting tibble consists of:

- **ID:** The unique identifier of the subject. For single-subject datasets, `ID = 1`
- **VISIT:** (If applicable) Corresponds to the visit # of the subject, if more than 1
- **WAKE:** (If applicable) Corresponds to the awake status of the subject (0 = asleep | 1 = awake)
- **CV_SBP / CV_DBP:** Calculates the ratio of standard deviation to the mean. `CV_SBP` or `CV_DBP` is useful for comparing the degree of variation from one data series to another.
- **SD_SBP / SD_DBP:** For completeness, the `cv` function also includes the standard deviation as a comparison metric to measure spread around the average.
- **N:** The number of observations for that particular grouping. If `inc_date = TRUE`, `N` corresponds to the number of observations for that date. If `inc_date = FALSE`, `N` corresponds to the number of observations for the most granular grouping available (i.e. a combination of `ID`, `VISIT`, and `WAKE`)
- Any `add_groups` variables supplied to function argument will be present as a column in the resulting tibble.

Examples

```
# Load data
data(bp_hypos)
data(bp_jhs)

# Process bp_hypos
hypos_proc <- process_data(bp_hypos, sbp = "SYST", dbp = "DIAST", date_time = "date.time",
id = "id", wake = "wake", visit = "visit", hr = "hr", pp = "pp", map = "map", rpp = "rpp")
# Process bp_jhs data
jhs_proc <- process_data(bp_jhs, sbp = "Sys.mmHg.", dbp = "Dias.mmHg.", date_time = "DateTime",
hr = "Pulse.bpm.")

## Not run:
# CV Calculation
bp_cv(hypos_proc, inc_date = TRUE, add_groups = "SBP_Category")
bp_cv(jhs_proc, add_groups = c("meal_time"))
# Notice that meal_time is not a column from process_data, but it still works

## End(Not run)
```

Description

Calculate the percent and average decline (or potentially reverse) in nocturnal blood pressure. This function is typically used with ABPM data, or at minimum, data with a corresponding a WAKE column available to indicate awake vs asleep.

Nocturnal blood pressure decline is an indicator of an individual's natural circadian rhythm. Studies have shown that individuals with diminished circadian rhythms are more likely to exhibit target organ damage. There is a "U-shaped" relationship that exists among the magnitude of nocturnal blood pressure decline; the extreme dippers and the non-dippers (including reverse dippers) are both more prone to mortality risk than normal dippers.

NOTE: Any reference to "sleep" in the bp package refers to an individual's nocturnal period; "sleep" is used in an informal sense for intuitive purposes. Technically, from a clinical perspective, indication of sleep is currently obtained through means of EEG or other highly specialized equipment. For all intents and purposes, sleep in the context of this package refers to actigraphy-inferred nocturnal periods of rest.

Usage

```
dip_calc(
  data,
  sleep_start_end = NULL,
  dip_thresh = 0.1,
  extreme_thresh = 0.2,
  inc_date = FALSE,
  subj = NULL
)
```

Arguments

- | | |
|-----------------|--|
| data | User-supplied data set that must contain SBP, DBP, and either DATE_TIME or WAKE columns in order to distinguish between sleep and awake In the event of non-ABPM data (i.e. a data set without a corresponding WAKE column), then a DATE_TIME column must be present in order to denote which times correspond to sleep and which times correspond to awake. |
| sleep_start_end | (optional) User-supplied manual override to adjust sleep interval indicating indicate start and end time corresponding to the sleep interval of interest. Must only contain 2 values and must be 24-hour denoted integers Example: sleep_start_end = c(22, 5) indicates a sleep period from 10pm - 5am. NOTE: If the sleep_start_end function argument is specified, and no WAKE column exists, then awake/asleep indicators will be assigned according the the DATE_TIME column (which must exist). Otherwise, if sleep_int is not supplied, then the WAKE column will default to a sleep period between 11PM - 6AM as specified in the literature (see reference). Furthermore, the sleep_int argument will override the WAKE column, which may cause unintended consequences in the event that the data set already contains a WAKE column. |

| | |
|----------------|---|
| dip_thresh | Default threshold for normal "Dipping" set to 0.10 (i.e. 10%). This value represents the maximum percentage that BP can fall during sleep and be characterized as "Normal" nocturnal decline (dipping). Specifically, this category includes all dips between 0% and this value. |
| extreme_thresh | Default threshold for "Extreme Dipping" set to 0.20 (i.e. 20%). This value represents the maximum percentage that BP can fall during sleep and be characterized as "Extreme" nocturnal decline (dipping). Specifically, this category includes all dips between the Normal dipping threshold and this value. NOTE: dip_thresh cannot exceed extreme_thresh. |
| inc_date | Default to FALSE. Indicates whether or not to include the date in the grouping of the final output |
| subj | Optional argument. Allows the user to specify and subset specific subjects from the ID column of the supplied data set. The subj argument can be a single value or a vector of elements. The input type should be character, but the function will comply with integers so long as they are all present in the ID column of the data. |

Value

A list containing 2 tibble objects. The first tibble object lists grouped average values for SBP and DBP for awake and asleep periods. The second dip_pct tibble object lists the dipping percentage and classification according to the results from the first dip tibble. If inc_date = TRUE these two tibbles will be broken down further by date. There are 4 classifications a subject can have (assuming a default dipping threshold of 10% and extreme dipping threshold of 20% according to the original source):

- Reverse Dipper - no nocturnal decline (greater or equal to 0%)
- Non-Dipper - a nocturnal decline between 0 - 10%
- Dipper - a nocturnal decline between 10% and the extreme dipping % (20%)
- Extreme Dipper - a nocturnal decline exceeding 20%

References

Okhubo, T., Imai, Y., Tsuji, K., Nagai, K., Watanabe, N., Minami, J., Kato, J., Kikuchi, N., Nishiyama, A., Aihara, A., Sekino, M., Satoh, H., and Hisamichi, S. (1997). Relation Between Nocturnal Decline in Blood Pressure and Mortality: The Ohasama Study, *American Journal of Hypertension* **10(11)**, 1201–1207, doi:10.1016/S08957061(97)002744.

Examples

```
## Load bp_hypos
data(bp_hypos)

## Process bp_hypos
hypos_proc <- process_data(bp_hypos,
  sbp = 'syst',
  dbp = 'diast',
  date_time = 'date.time',
  hr = 'hr',
```

```

        pp = 'PP',
        map = 'MaP',
        rpp = 'Rpp',
        id = 'id',
        visit = 'Visit',
        wake = 'wake')

dip_calc(hypos_proc)

```

dip_class_plot

Plot of Dipping Classifications

Description

Graphical visualization of the dip_calc output for categories of dipping percentages.

NOTE: Any reference to "sleep" in the bp package refers to an individual's nocturnal period; "sleep" is used in an informal sense for intuitive purposes. Technically, from a clinical perspective, indication of sleep is currently obtained through means of EEG or other highly specialized equipment. For all intents and purposes, sleep in the context of this package refers to actigraphy-inferred nocturnal periods of rest.

Usage

```

dip_class_plot(
  data,
  subj = NULL,
  dip_thresh = 0.1,
  extreme_thresh = 0.2,
  thresh_mult = 2,
  sleep_start_end = NULL
)

```

Arguments

| | |
|------------|--|
| data | User-supplied data set that must contain SBP, DBP, and either DATE_TIME or WAKE columns in order to distinguish between sleep and awake In the event of non-ABPM data (i.e. a data set without a corresponding WAKE column), then a DATE_TIME column must be present in order to denote which times correspond to sleep and which times correspond to awake. |
| subj | Optional argument. Allows the user to specify and subset specific subjects from the ID column of the supplied data set. The subj argument can be a single value or a vector of elements. The input type should be character, but the function will comply with integers so long as they are all present in the ID column of the data. |
| dip_thresh | Default threshold for normal "Dipping" set to 0.10 (i.e. 10%). This value represents the maximum percentage that BP can fall during sleep and be characterized as "Normal" nocturnal decline (dipping). Specifically, this category includes all dips between 0% and this value. |

- `extreme_thresh` Default threshold for "Extreme Dipping" set to 0.20 (i.e. 20%). This value represents the maximum percentage that BP can fall during sleep and be characterized as "Extreme" nocturnal decline (dipping). Specifically, this category includes all dips between the Normal dipping threshold and this value.
NOTE: `dip_thresh` cannot exceed `extreme_thresh`.
- `thresh_mult` Optional argument that serves as a multiplier by which to expand plot sizing for X and Y axis. Default set to 2.
- `sleep_start_end` Optional User-supplied manual override to adjust sleep interval indicating indicate start and end time corresponding to the sleep interval of interest. Must only contain 2 values and must be 24-hour denoted integers
Example: `sleep_start_end = c(22,5)` indicates a sleep period from 10pm - 5am.

Value

A scatter plot of all dipping percentage values layered on top of the category plot outlined in Okhubo et al. (1995). `dip_thresh` and `extreme_thresh` denote the cutoffs for the Normal and Extreme dipping categories. Any dips below zero are denoted as Inverted (or Reverse) dipping.

The default plot categories are as follows:

- *INV*: Inverted (Reverse) Dipper - no nocturnal decline (greater or equal to 0%)
- *ND*: Non-Dipper - a nocturnal decline between 0 - 10%
- *DIP*: Dipper - a nocturnal decline between 10% and the extreme dipping % (20%)
- *ED*: Extreme Dipper - a nocturnal decline exceeding 20%

References

Okhubo, T., Imai, Y., Tsuji, K., Nagai, K., Watanabe, N., Minami, J., Kato, J., Kikuchi, N., Nishiyama, A., Aihara, A., Sekino, M., Satoh, H., and Hisamichi, S. (1997). Relation Between Nocturnal Decline in Blood Pressure and Mortality: The Ohasama Study, *American Journal of Hypertension* **10(11)**, 1201–1207, [doi:10.1016/S08957061\(97\)002744](https://doi.org/10.1016/S08957061(97)002744).

Examples

```
hypnos_proc <- process_data(bp::bp_hypnos,
  sbp = "syst",
  dbp = "DIAST",
  date_time = "date.time",
  id = "id",
  wake = "wake",
  visit = "visit")

dip_class_plot(hypnos_proc)
```

dow_tod_plots

Blood Pressure Tables in Graphical Format

Description

Blood Pressure Tables in Graphical Format

Usage

```
dow_tod_plots(data, subj = NULL)
```

Arguments

| | |
|------|---|
| data | A processed dataframe resulting from the process_data function that contains the SBP, DBP, DAY_OF_WEEK, Time_of_Day, SBP_Category, and DBP_Category columns. |
| subj | Optional argument. Allows the user to specify and subset specific subjects from the ID column of the supplied data set. The subj argument can be a single value or a vector of elements. The input type should be character, but the function will comply with integers so long as they are all present in the ID column of the data. |

Value

A list of four ‘gtables’ that correspond to the tables for Day of Week and Time of Day broken down by both SBP and DBP.

Examples

```
data("bp_hypos")
hyp_proc <- process_data(bp_hypos,
  bp_type = 'ABPM',
  sbp = "syst",
  dbp = "DIAST",
  date_time = "date.time",
  id = "id",
  wake = "wake",
  visit = "visit",
  hr = "hr",
  map = "map",
  rpp = "rpp",
  pp = "pp",
  ToD_int = c(5, 13, 18, 23))

rm(bp_hypos)

dow_tod_plots_out <- dow_tod_plots(hyp_proc)
grid::grid.draw(
  gridExtra::grid.arrange(dow_tod_plots_out[[1]], dow_tod_plots_out[[2]], ncol = 2)
)
```

| | |
|--------------|---------------------------|
| process_data | <i>Data Pre-Processor</i> |
|--------------|---------------------------|

Description

A helper function to assist in pre-processing the user-supplied input data in a standardized format for use with other functions in the bp package. See Vignette for further details.

Usage

```
process_data(  
  data,  
  bp_type = c("hbpm", "abpm", "ap"),  
  guidelines = c("Lee_2020", "AHA", "Custom"),  
  bp_cutoffs = list(c(100, 120, 130, 140, 180), c(60, 80, 80, 90, 120)),  
  ap = NULL,  
  time_elap = NULL,  
  sbp = NULL,  
  dbp = NULL,  
  date_time = NULL,  
  id = NULL,  
  group = NULL,  
  wake = NULL,  
  visit = NULL,  
  hr = NULL,  
  pp = NULL,  
  map = NULL,  
  rpp = NULL,  
  DoW = NULL,  
  ToD_int = NULL,  
  eod = NULL,  
  data_screen = TRUE,  
  SUL = 240,  
  SLL = 50,  
  DUL = 140,  
  DLL = 40,  
  HRUL = 220,  
  HRLL = 27,  
  inc_low = TRUE,  
  inc_crisis = TRUE,  
  agg = FALSE,  
  agg_thresh = 3,  
  collapse_df = FALSE,  
  dt_fmt = "ymd HMS",  
  chron_order = FALSE,  
  tz = "UTC"  
)
```

Arguments

| | |
|------------|--|
| data | User-supplied dataset containing blood pressure data. Must contain data for Systolic blood pressure and Diastolic blood pressure at a minimum. |
| bp_type | <p>Required argument specifying which of the three BP data types ("HBPM", "ABPM", or "AP") the input data is. Default bp_type set to "HBPM". This argument determines which processing steps are necessary to yield sensible output.</p> <p>HBPM - Home Blood Pressure Monitor ABPM - Ambulatory Blood Pressure AP - Arterial Pressure</p> <p>NOTE: bp_type impacts blood pressure staging in bp_stages if guidelines = "AHA", for which the cutoffs for each blood pressure stage are automatically adjusted according to bp_type.</p> |
| guidelines | A string designation for the guidelines to follow when mapping BP readings to a respective BP stage. guidelines can take on either "Lee_2020" corresponding to staging in Lee et al (2020), "AHA" corresponding to guidelines by the American Heart Association, see e.g. Muntner et al (2019), or "Custom" based on user-defined cutoffs in bp_cutoffs. By default, AHA guidelines adjust bp_cutoffs depending on the BP type. |
| bp_cutoffs | <p>A list containing two vectors corresponding to SBP and DBP cutoffs, respectively. Each vector contains 5 values.</p> <p>The SBP vector (100, 120, 130, 140, 180) corresponds to the upper limits for the following stages: Low (0-100), Normal (100-120), Elevated (120-130), Stage 1 Hypertension (130-140), Stage 2 Hypertension (140-180). When utilizing Lee et al (2020) guidelines, additional stages are included: Isolated Systolic Hypertension for Stage 1 (ISH - S1) (130-140), Isolated Diastolic Hypertension for Stage 1 (IDH - S1) (0-130), ISH - S2 (140-180), and IDH - S2 (0-140).</p> <p>The DBP vector (60, 80, 80, 90, 120) corresponds to the upper limits for the following stages: Low (0-60), Normal (60-80), Elevated (0-80), Stage 1 Hypertension (80-90), Stage 2 Hypertension (90-120). The upper limit of the "Elevated" category repeats in the DBP vector and matches that of Normal. This because according to most guidelines, there is no distinction between DBP cutoffs for Normal and Elevated - these stages are discerned by SBP, not DBP. When utilizing Lee et al (2020) guidelines, additional stages are included: Isolated Diastolic Hypertension for Stage 1 (ISH - S1) (0-80), Isolated Diastolic Hypertension for Stage 1 (IDH - S1) (80-90), ISH - S2 (0-90), and IDH - S2 (90-120).</p> <p>Any SBP reading below 100 or DBP reading below 60 is considered Hypotension ("Low"). Any SBP reading above 180 or DBP reading above 120 is considered a Crisis.</p> <p>When guidelines = "AHA", the cutoffs are automatically adjusted to match BP type without user input, For bp_type = "hbpm", SBP = (100, 120, 130, 135, 160), DBP = (60, 80, 80, 85, 110). Forbp_type = "abpm", SBP = (100, 115, 125, 130, 160), DBP = (60, 75, 75, 80, 105). An adjustment of default cutoffs by the user These choices can be overwritten by directly changing bp_cutoffs, in which case the guidelines are ignored and automatically treated as "Custom".</p> <p>If inc_low = FALSE, although an upper limit value is still required in the SBP vector, the "Low" stage will be omitted in the final output. Similarly, if inc_crisis = FALSE, then the "Crisis" category will be omitted from the final output.</p> |

| | |
|-----------|--|
| ap | (For AP data only) Required column name (character string) corresponding to continuous Arterial Pressure (AP) (mmHg). Note that this is a required argument so long as bp_type = "AP". Ensure that bp_type is set accordingly. |
| time_elap | (For AP data only) Column name corresponding to the time elapsed for the given AP waveform data. |
| sbp | Required column name (character string) corresponding to Systolic Blood Pressure (mmHg) |
| dbp | Required column name (character string) corresponding to Diastolic Blood Pressure (mmHg) |
| date_time | Optional column name (character string) corresponding to Date/Time, but HIGHLY recommended to supply if available. For DATE-only columns (with no associated time), leave date_time = NULL. DATE-only adjustments are automatic. Dates can be automatically calculated off DATE_TIME column provided that it is called "DATE_TIME" exactly. |
| id | Optional column name (character string) corresponding to subject ID. Typically needed for data corresponding to more than one subject. For one-subject datasets, ID will default to 1 (if ID column not found in dataset) |
| group | Optional column name (character string) corresponding to an additional grouping variable that can be used to further break down data. NOTE that this simply sets the column as "GROUP" so that other functions recognize which column to use as the grouping variable. |
| wake | Optional column name (character string) corresponding to sleep status. A WAKE value of 1 indicates that the subject is awake and 0 implies asleep. |
| visit | Optional column name (character string) corresponding to Visit number |
| hr | Optional column name (character string) corresponding to Heart Rate (bpm) |
| pp | Optional column name (character string) corresponding to Pulse Pressure (SBP - DBP). If not supplied, it will be calculated automatically. |
| map | Optional column name (character string) corresponding to Mean Arterial Pressure |
| rpp | Optional column name (character string) corresponding to Rate Pulse Pressure (SBP * HR). If not supplied, but HR column available, then RPP will be calculated automatically. |
| DoW | Optional column name (character string) corresponding to the Day of the Week. If not supplied, but DATE or DATE_TIME columns available, then DoW will be created automatically. DoW values must be abbreviated as such c("Sun", "Mon", "Tue", "Wed", "Thu", "Fri", "Sat") |
| ToD_int | Optional vector of length 4, acceptable values are from 0 to 23 in a an order corresponding to hour for Morning, Afternoon, Evening, Night). This vector allows to override the default interval for the Time-of-Day periods: if NULL, the Morning, Afternoon, Evening, and Night periods are set at 6, 12, 18, 0 respectively, where 0 corresponds to the 24th hour of the day (i.e. Midnight). For example, ToD_int = c(5, 13, 18, 23) would correspond to a period for Morning starting at 5:00 (until 13:00), Afternoon starting at 13:00 (until 18:00), Evening starting at 18:00 (until 23:00), and Night starting at 23:00 (until 5:00) |

| | |
|-------------|---|
| eod | Optional argument to adjust the delineation for the end of day (eod). The supplied value should be a character string with 4 characters representing the digits of 24-hour time, e.g. "1310" corresponds to 1:10pm. For individuals who do not go to bed early or work night-shifts, this argument adjusts the DATE column so that the days change at specified time. eod = "0000" means no change. eod = "1130" will adjust the date of the readings up to 11:30am to the previous date. eod = "1230" will adjust the date of the readings after 12:30pm to the next date. |
| data_screen | Optional logical argument; default set to TRUE. Screens for extreme values in the data for both SBP and DBP according to Omboni, et al (1995) paper - Calculation of Trough:Peak Ratio of Antihypertensive Treatment from Ambulatory Blood Pressure: Methodological Aspects |
| SUL | Systolic Upper Limit (SUL). If data_screen = TRUE, then SUL sets the upper limit by which to exclude any SBP values that exceed this threshold. The default is set to 240 per Omboni, et al (1995) paper - Calculation of Trough:Peak Ratio of Antihypertensive Treatment from Ambulatory Blood Pressure: Methodological Aspects |
| SLL | Systolic Lower Limit (SLL). If data_screen = TRUE, then SLL sets the lower limit by which to exclude any SBP values that fall below this threshold. The default is set to 50 per Omboni, et al (1995) paper - Calculation of Trough:Peak Ratio of Antihypertensive Treatment from Ambulatory Blood Pressure: Methodological Aspects |
| DUL | Diastolic Upper Limit (DUL). If data_screen = TRUE, then DUL sets the upper limit by which to exclude any DBP values that exceed this threshold. The default is set to 140 per Omboni, et al (1995) paper - Calculation of Trough:Peak Ratio of Antihypertensive Treatment from Ambulatory Blood Pressure: Methodological Aspects |
| DLL | Diastolic Lower Limit (DLL). If data_screen = TRUE, then DLL sets the lower limit by which to exclude any DBP values that fall below this threshold. The default is set to 40 per Omboni, et al (1995) paper - Calculation of Trough:Peak Ratio of Antihypertensive Treatment from Ambulatory Blood Pressure: Methodological Aspects |
| HRUL | Heart Rate Upper Limit (HRUL). If data_screen = TRUE, then HRUL sets the upper limit by which to exclude any HR values that exceed this threshold. The default is set to 220 per the upper limit of the common max heart rate formula: 220 - age see https://www.cdc.gov/physicalactivity/basics/measuring/hearttrate.htm |
| HRLL | Heart Rate Upper Limit (HRUL). If data_screen = TRUE, then HRUL sets the upper limit by which to exclude any HR values that exceed this threshold. The default is set to 27 per Guinness World Records - lowest heart rate (https://www.guinnessworldrecords.com/records/lowest-heart-rate) |
| inc_low | Optional logical argument dictating whether or not to include the "Low" category for BP classification column (and the supplementary SBP/DBP Category columns). Default set to TRUE. |
| inc_crisis | Optional logical argument dictating whether or not to include the "Crisis" category for BP classification column (and the supplementary SBP/DBP Category columns). Default set to TRUE. |

| | |
|-------------|---|
| agg | Optional argument specifying whether or not to aggregate the data based on the amount of time between observations. If agg = TRUE then any two (or more) observations within the amount of time allotted by the agg_thresh argument will be averaged together. |
| agg_thresh | Optional argument specifying the threshold of how many minutes can pass between readings (observations) and still be considered part of the same sitting. The default is set to 3 minutes. This implies that if two or more readings are within 3 minutes of each other, they will be averaged together (if agg is set to TRUE). |
| collapse_df | Optional argument that collapses the dataframe to eliminate repeating rows after aggregation. |
| dt_fmt | Optional argument that specifies the input date/time format (dt_fmt). Default set to "ymd HMS" but can take on any format specified by the lubridate package. |
| chron_order | Optional argument that specifies whether to order the data in chronological (Oldest dates & times at the top / first) or reverse chronological order (Most recent dates & times at the top / first). TRUE refers to chronological order; FALSE refers to reverse chronological order. The default is set to FALSE (i.e. most recent observations listed first in the dataframe). See https://lubridate.tidyverse.org/reference/parse_date_time.html for more details. |
| tz | Optional argument denoting the respective time zone. Default time zone set to "UTC". See <code>UseOlsonNames()</code> for a complete listing of all available time zones that can be used in this argument. |

Value

A processed dataframe object with standardized column names and formats to use with the rest of bp package functions. The following standardized column names are used throughout

| | |
|--------------|--|
| BP_TYPE | One of AP, HBPM or ABPM |
| ID | Subject ID |
| SBP | Systolic Blood Pressure |
| DBP | Diastolic Blood Pressure |
| SBP_CATEGORY | Ordinal, SBP characterization into "Low" < "Normal"<"Elevated"<"Stage 1"<"Stage 2" < "Crisis". "Low" is not included if inc_low = FALSE. "Crisis" is not included if inc_crisis = FALSE. |
| DBP_CATEGORY | Ordinal, DBP characterization into "Low" < "Normal"<"Elevated"<"Stage 1"<"Stage 2" < "Crisis". "Low" is not included if inc_low = FALSE. "Crisis" is not included if inc_crisis = FALSE. |
| BP_CLASS | Blood pressure categorization based on paired values (SBP, DBP) into one of the 8 stages according to Lee et al. 2020. See bp_scatter |
| HR | Heart Rate |
| MAP | Mean Arterial Pressure |
| PP | Pulse Pressure, SBP-DBP |


```

# Load bp_jhs data
data("bp_jhs")

# Process data for bp_jhs
# Note that bp_type defaults to "hbpm" and is therefore not specified
jhs_proc <- process_data(bp_jhs,
  sbp = "Sys.mmHg.",
  dbp = "Dias.mmHg.",
  date_time = "DateTime",
  hr = "Pulse.bpm.")

jhs_proc

```

sleep_int

Sleep Interval Manual Override

Description

Adjusts WAKE column to reflect start and end of user-defined sleep period. If sleep_start_end is NULL and WAKE column is included in input data, this function will not alter data.

Usage

```
sleep_int(data, sleep_start_end = NULL, adj = TRUE)
```

Arguments

| | |
|-----------------|--|
| data | Supplied data from function |
| sleep_start_end | User-supplied sleep interval to indicate start and end time of the sleep interval of interest. Must only contain 2 values and must be 24-hour denoted integers |
| adj | Logical indicating whether or not to perform necessary adjustments / additions to data for WAKE column (i.e. set the default sleep time from 11PM - 6 AM if no interval specified and a DATE_TIME column is available). Default set to TRUE. adj == FALSE essentially acts as a pass statement |

Value

Dataframe with added / adjusted WAKE column moved after DATE_TIME column containing binary 1 (awake) and 0 (asleep)

sv

*Successive Variation (SV)***Description**

THIS IS A DEPRECATED FUNCTION. USE `bp_sv` INSTEAD.

Usage

```
sv(
  data,
  inc_date = FALSE,
  subj = NULL,
  bp_type = 0,
  add_groups = NULL,
  inc_wake = TRUE
)
```

Arguments

| | |
|-------------------------|---|
| <code>data</code> | Required argument. Pre-processed dataframe with SBP and DBP columns with optional ID, VISIT, WAKE, and DATE columns if available. Use <code>process_data</code> to properly format data. |
| <code>inc_date</code> | Optional argument. Default is FALSE. As ABPM data typically overlaps due to falling asleep on one date and waking up on another, the <code>inc_date</code> argument is typically kept as FALSE, but the function will work regardless. Setting <code>inc_date = TRUE</code> will include these dates as a grouping level. |
| <code>subj</code> | Optional argument. Allows the user to specify and subset specific subjects from the ID column of the supplied data set. The <code>subj</code> argument can be a single value or a vector of elements. The input type should be character, but the function will comply with integers so long as they are all present in the ID column of the data. |
| <code>bp_type</code> | Optional argument. Determines whether to calculate ARV for SBP values or DBP values. Default is 0 corresponding to output for both SBP & DBP. For both SBP and DBP ARV values use <code>bp_type = 0</code> , for SBP-only use <code>bp_type = 1</code> , and for DBP-only use <code>bp_type = 2</code> |
| <code>add_groups</code> | Optional argument. Allows the user to aggregate the data by an additional "group" to further refine the output. The supplied input must be a character vector with the strings corresponding to existing column names of the processed data input supplied. Capitalization of <code>add_groups</code> does not matter. Ex: <code>add_groups = c("Time_of_Day")</code> |
| <code>inc_wake</code> | Optional argument corresponding to whether or not to include WAKE in the grouping of the final output (if WAKE column is available). By default, <code>inc_wake = TRUE</code> which will include the WAKE column in the groups by which to calculate the respective metrics. |

Details

Calculate the successive variation (SV) at various levels of granularity based on what is supplied (ID, VISIT, WAKE, and / or DATE) for either SBP, DBP, or both. SV is a measure of dispersion that takes into account the temporal structure of the data and relies on the sum of squared differences in successive observations, unlike the average real variability (ARV) which relies on the sum of absolute differences.

$$SV = \sqrt{\frac{\sum (x_{i+1} - x_i)^2}{n - 1}}$$

NOTE: The canonical standard deviation, independent of the temporal structure using the sample average, is added for comparison:

$$SD = \sqrt{\frac{\sum (x_{i+1} - \bar{x})^2}{n - 1}}$$

Value

A tibble object with a row corresponding to each subject, or alternatively a row corresponding to each date if `inc_date = TRUE`. The resulting tibble consists of:

- ID: The unique identifier of the subject. For single-subject datasets, ID = 1
- VISIT: (If applicable) Corresponds to the visit # of the subject, if more than 1
- WAKE: (If applicable) Corresponds to the awake status of the subject (0 = asleep | 1 = awake)
- SV_SBP / SV_DBP: Calculates the square root of the average squared differences between successive measurements. The resulting value averages across the granularity grouping for however many observations are present.
- N: The number of observations for that particular grouping. If `inc_date = TRUE`, N corresponds to the number of observations for that date. If `inc_date = FALSE`, N corresponds to the number of observations for the most granular grouping available (i.e. a combination of ID, VISIT, and WAKE)
- Any `add_groups` variables supplied to function argument will be present as a column in the resulting tibble.

Examples

```
# Load data
data(bp_hypos)
data(bp_jhs)

# Process bp_hypos
hypos_proc <- process_data(bp_hypos, sbp = "SYST", dbp = "DIAST", date_time = "date.time",
id = "id", wake = "wake", visit = "visit", hr = "hr", pp = "pp", map = "map", rpp = "rpp")
# Process bp_jhs data
jhs_proc <- process_data(bp_jhs, sbp = "Sys.mmHg.", dbp = "Dias.mmHg.", date_time = "DateTime",
hr = "Pulse.bpm.")

# SV Calculation
## Not run:
bp_sv(hypos_proc)
```

```
bp_sv(jhs_proc, add_groups = c("meal_time"))  
# Notice that meal_time is not a column from process_data, but it still works  
  
## End(Not run)
```

Index

* datasets

- bp_children, 8
- bp_ghana, 11
- bp_hypnos, 15
- bp_jhs, 16
- bp_preg, 18
- bp_rats, 22

- sleep_int, 57
- sv, 58

arv, 2

- bp_arv, 4
- bp_center, 6
- bp_children, 8
- bp_cv, 9
- bp_ghana, 11
- bp_hist, 14, 25
- bp_hypnos, 15
- bp_jhs, 16
- bp_mag, 17
- bp_preg, 18
- bp_range, 21
- bp_rats, 22
- bp_report, 23
- bp_scatter, 25, 26, 55
- bp_sleep_metrics, 30
- bp_stages, 32
- bp_stats, 36
- bp_sv, 38
- bp_tables, 40
- bp_ts_plots, 41

cv, 43

- dip_calc, 45
- dip_class_plot, 48
- dow_tod_plots, 25, 50

grid.arrange, 25

process_data, 51