Package ‘catcont’

May 8, 2026

Title Test, Identify, Select and Mutate Categorical or Continuous Values

Version 0.5.0

Date 2018-06-23

Description Methods and utilities for testing, identifying, selecting and mutating objects as categorical or continous types. These functions work on both atomic vectors as well as recursive objects: data.frames, data.tables, tibbles, lists, etc..

URL https://github.com/decisionpatterns/catcont
http://www.decisionpatterns.com

BugReports https://github.com/decisionpatterns/catcont/issues

Depends R (>= 3.3.0)

Suggests testthat, data.table(>= 1.10.0)

Imports dplyr (>= 0.7.0)

License GPL-2 | file LICENSE

Encoding UTF-8

LazyData true

RoxygenNote 6.0.1.9000

Repository CRAN

NeedsCompilation no

Author Christopher Brown [aut, cre], Decision Patterns [cph]

Maintainer Christopher Brown <chris.brown@decisionpatterns.com>

Date/Publication 2018-06-25 07:43:03 UTC

Contents

cat_cont 2
mutate_if_cat 4
select_cat 5

Index 7

`cat_cont` *categorical or continuous variables*

Description

These functions facilitate working with variables as categorical or continous rather than logical, integer, numeric, factor, character, ..

Usage

```
cat_cont(x)

is_cat(x)

## Default S3 method:
is_cat(x)

## S3 method for class 'ordered'
is_cat(x)

## S3 method for class 'factor'
is_cat(x)

## S3 method for class 'logical'
is_cat(x)

is_cont(x)

## Default S3 method:
is_cont(x)

## S3 method for class 'logical'
is_cont(x)

## S3 method for class 'factor'
is_cont(x)

## S3 method for class 'ordered'
is_cont(x)

which_cat(x, ..., names = FALSE)

which_cont(x, ..., names = FALSE)
```

Arguments

`x`	object
`...`	arguments passed to other functions.
`names`	logical; whether to return the names of the variables instead of their index?

Details

These functions are used to test and identify which/if a variable or variables are categorical or continuos. `is_cat` and `is_cont` take single variable arguments.

Mostly, the categorical and continuos assessment is straight- forward. Continuous variables are respresented by `integer`, `double` or `complex` types. All other types are categorical. There are a few opinionated exceptions:

- **factors** are categorical (though typed 'integer')
- **ordered** factors are (though typed 'integer')
- **logical** are categorical

For simplicity, it is assumed that a vector cannot be simultaneous categorical and continous, though in some cases (e.g. ordered factors) this may be the case.

Value

`cat_cont` returns a named character with values either `"cat"` or `"cont"`. If `x` is a atomic vector, a single string is given. If `x` is recursive, a `"cat"`/`"cont"` value is given for each element. Names correspond to the names of the element.

`is_cat` and `is_cont` return `logical`.

`which_cat` and `which.cont` report which variables in an object are categorical and continuous. By default, interger indices are return. If `names=TRUE`, the names of the variables are returned instead.

See Also

- `base::typeof()`
- `base::is.numeric()` `methods::is()`
- `base::which()`

Examples

```
data(iris)
cat_cont(iris)


is_cat(letters)          # TRUE
is_cat(factor(letters))  # TRUE
is_cat(TRUE)             # TRUE
is_cat(FALSE)            # TRUE
is_cat(1:10)             # FALSE
is_cat(rnorm(10))        # FALSE
is_cat( Sys.Date() )     # FALSE
```

```
is_cat( complex(1,2) )   # FALSE

is_cont(letters)         # FALSE
is_cont(factor(letters)) # FALSE
is_cont(TRUE)            # FALSE
is_cont(FALSE)           # FALSE
is_cont(1:10)            # TRUE
is_cont(rnorm(10))       # TRUE
is_cont( Sys.Date() )    # TRUE
is_cont( complex(1,2) )  # TRUE

which_cat(iris)
which_cat( iris, names=TRUE )

which_cont(iris)
which_cont( iris, names=TRUE )
```

`mutate_if_cat` *mutate_if_cat, mutate_if_cont*

Description

mutates only categoricall|continuous columns

Usage

```
mutate_if_cat(.tbl, .funs, ...)

## Default S3 method:
mutate_if_cat(.tbl, .funs, ...)

## S3 method for class 'data.table'
mutate_if_cat(.tbl, .funs, ...)

mutate_if_cont(.tbl, .funs, ...)

## Default S3 method:
mutate_if_cont(.tbl, .funs, ...)

## S3 method for class 'data.table'
mutate_if_cont(.tbl, .funs, ...)
```

Arguments

`.tbl`	table
`.funs`	functions see `dplyr::mutate_if()`
`...`	additional parameters

Details

Mutates categorical or continuous columns.

The data.table variants do this as

Value

An object of class `.tbl` in with columns mutated according to `.funs`

See Also

Similar to `dplyr::mutate_if()`

Examples

```
 data(iris)

## Not run:
  iris %>% mutate_if_cat( as.character )

  library(data.table)
  setDT(iris)
  class(iris$Species)
  iris %>% mutate_if_cat( as.character )
  class(iris1$Species)  # character
  class(iris2)

  iris %>% mutate_if_cont( add, 2 )

## End(Not run)
```

---

select_cat *select_cat, select_cont*

Description

Select columns by type

Usage

```
select_cat(.data)

## Default S3 method:
select_cat(.data)

## S3 method for class 'data.table'
select_cat(.data)
```

```
select_cont(.data)

## Default S3 method:
select_cont(.data)

## S3 method for class 'data.table'
select_cont(.data)
```

Arguments

`.data`	table

Details

select_cat() and select_cont() return only the categorical and continuous types respectively. This is closely mirrors the dplyr function select but works with non-table values as well.

Value

Returns a table-like object of the same class as data unless there are no columns in which case ‘NULL‘ is returned

Examples

```
  data(iris)
  select_cat(iris)
  select_cont(iris)

## Not run:
  setDT(iris)
  select_cat(iris)
  select_cont(iris)

## End(Not run)
```

Index

base::is.numeric(), *3*
base::typeof(), *3*
base::which(), *3*

cat_cont, 2

dplyr::mutate_if(), *4*, *5*

is_cat *(*cat_cont*)*, 2
is_cont *(*cat_cont*)*, 2

methods::is(), *3*
mutate_if_cat, 4
mutate_if_cont *(*mutate_if_cat*)*, 4

select_cat, 5
select_cont *(*select_cat*)*, 5

which_cat *(*cat_cont*)*, 2
which_cont *(*cat_cont*)*, 2