

Package ‘connectcreds’

May 8, 2026

Title Manage 'OAuth' Credentials from 'Posit Connect'

Version 0.2.0

Description A toolkit for making use of credentials mediated by 'Posit Connect'. It handles the details of communicating with the Connect API correctly, 'OAuth' token caching, and refresh behaviour.

License MIT + file LICENSE

Imports cli, httr2 (>= 1.1.0), rlang (>= 1.1.0)

Suggests testthat (>= 3.0.0), withr

Encoding UTF-8

RoxygenNote 7.3.2

Config/testthat/edition 3

URL <https://github.com/posit-dev/connectcreds>

BugReports <https://github.com/posit-dev/connectcreds/issues>

NeedsCompilation no

Author Aaron Jacobs [aut, cre],
Posit Software, PBC [cph, fnd]

Maintainer Aaron Jacobs <aaron.jacobs@posit.co>

Repository CRAN

Date/Publication 2026-03-02 22:40:02 UTC

Contents

connect_service_account_token	2
connect_viewer_token	3
connect_workload_token	4
with_mocked_connect_responses	5

Index	7
--------------	----------

connect_service_account_token

Service account credentials on Posit Connect

Description

Request an OAuth access token for a third-party resource from Posit Connect. The OAuth token will belong to the client (usually a "service principal" or "service account") managed by Connect, not the publisher.

Usage

```
connect_service_account_token(
  resource = NULL,
  scope = NULL,
  content_token = Sys.getenv("CONNECT_CONTENT_SESSION_TOKEN"),
  server_url = Sys.getenv("CONNECT_SERVER"),
  api_key = Sys.getenv("CONNECT_API_KEY")
)

has_service_account_token(...)
```

Arguments

resource	The URI that identifies the resource that the client is trying to access, if applicable.
scope	Scopes to be requested from the resource owner.
content_token	A token that uniquely identifies this content session. Defaults to the value of the CONNECT_CONTENT_SESSION_TOKEN environment variable, which is set automatically when running on Connect.
server_url	The Connect server to exchange credentials with. Defaults to the value of the CONNECT_SERVER environment variable, which is set automatically when running on Connect.
api_key	An API key for the Connect server. Defaults to the value of the CONNECT_API_KEY environment variable, which is set automatically when running on Connect.
...	Further arguments passed on to connect_service_account_token() .

Details

`connect_service_account_token()` handles caching automatically.

Value

`connect_service_account_token()` returns an `httr2::oauth_token`.

`has_service_account_token()` returns TRUE if there is a Connect-managed service account available and FALSE otherwise.

Examples

```
token <- "default-token"
if (has_service_account_token()) {
  token <- connect_service_account_token()
}
```

connect_viewer_token *Viewer-based credentials on Posit Connect*

Description

Request an OAuth access token for a third-party resource belonging to the user associated with a given Shiny session. This works by exchanging a short-lived session credential for OAuth tokens issued to the client managed by the Connect server, without the Shiny app in question having to manage the user's authentication flow (or the associated client credentials) itself.

Usage

```
connect_viewer_token(
  resource = NULL,
  scope = NULL,
  session = get_connect_session(),
  server_url = Sys.getenv("CONNECT_SERVER"),
  api_key = Sys.getenv("CONNECT_API_KEY")
)

has_viewer_token(..., session = get_connect_session())
```

Arguments

resource	The URI that identifies the resource that the client is trying to access, if applicable.
scope	Scopes to be requested from the resource owner.
session	A Shiny session object. By default, this grabs the Shiny session of the parent environment (if any), provided we are also running on Connect.
server_url	The Connect server to exchange credentials with. Defaults to the value of the CONNECT_SERVER environment variable, which is set automatically when running on Connect.
api_key	An API key for the Connect server. Defaults to the value of the CONNECT_API_KEY environment variable, which is set automatically when running on Connect.
...	Further arguments passed on to connect_viewer_token() .

Details

connect_viewer_token() handles caching automatically.

Value

`connect_viewer_token()` returns an `httr2::oauth_token`.

`has_viewer_token()` returns TRUE if the session has a viewer token and FALSE otherwise.

Examples

```
token <- "default-token"
if (has_viewer_token()) {
  token <- connect_viewer_token()
}
```

connect_workload_token

Workload identity tokens on Posit Connect

Description

Request an OpenID Connect identity token suitable for workload identity federation with a third-party service.

Usage

```
connect_workload_token(
  ...,
  content_token = Sys.getenv("CONNECT_CONTENT_SESSION_TOKEN"),
  server_url = Sys.getenv("CONNECT_SERVER"),
  api_key = Sys.getenv("CONNECT_API_KEY")
)

has_workload_token(...)
```

Arguments

<code>...</code>	Further arguments passed on to <code>connect_workload_token()</code> .
<code>content_token</code>	A token that uniquely identifies this content session. Defaults to the value of the <code>CONNECT_CONTENT_SESSION_TOKEN</code> environment variable, which is set automatically when running on Connect.
<code>server_url</code>	The Connect server to exchange credentials with. Defaults to the value of the <code>CONNECT_SERVER</code> environment variable, which is set automatically when running on Connect.
<code>api_key</code>	An API key for the Connect server. Defaults to the value of the <code>CONNECT_API_KEY</code> environment variable, which is set automatically when running on Connect.

Details

`connect_workload_token()` handles caching automatically.

Value

`connect_workload_token()` returns an `httr2::oauth_token`.

`has_workload_token()` returns TRUE if a workload identity token is available and FALSE otherwise.

Examples

```
integration_guid <- "891db041-22d6-4f5f-9fee-fc715a33929e"
token <- "default-token"
if (has_workload_token(audience = integration_guid)) {
  token <- connect_workload_token(audience = integration_guid)
}
```

with_mocked_connect_responses

Mock responses from the Posit Connect server

Description

These functions can be used to temporarily mock responses from the Connect server, which is useful for writing tests that verify the behaviour of viewer-based or service account credentials.

Usage

```
with_mocked_connect_responses(
  code,
  mock = NULL,
  token = NULL,
  error = FALSE,
  env = caller_env()
)

local_mocked_connect_responses(
  mock = NULL,
  token = NULL,
  error = FALSE,
  env = caller_env()
)
```

Arguments

<code>code</code>	Code to execute in the temporary environment.
<code>mock</code>	A function, a list, or NULL. <ul style="list-style-type: none"> • NULL disables mocking and returns <code>httr2</code> to regular operation. • A list of responses will be returned in sequence. After all responses have been used up, will return 503 server errors.

- For maximum flexibility, you can supply a function that takes a single argument, req, and returns either NULL (if it doesn't want to handle the request) or a [response](#) (if it does).

token	When not NULL, return this token from the Connect server.
error	When TRUE, return an error from the Connect server.
env	Environment to use for scoping changes.

Value

[with_mocked_connect_responses\(\)](#) returns the result of evaluating code.

Examples

```
with_mocked_connect_responses(  
  connect_viewer_token(),  
  token = "test"  
)  
  
with_mocked_connect_responses(  
  connect_service_account_token(),  
  token = "test"  
)
```

Index

connect_service_account_token, 2
connect_service_account_token(), 2
connect_viewer_token, 3
connect_viewer_token(), 3, 4
connect_workload_token, 4
connect_workload_token(), 4, 5

has_service_account_token
 (connect_service_account_token),
 2
has_service_account_token(), 2
has_viewer_token
 (connect_viewer_token), 3
has_viewer_token(), 4
has_workload_token
 (connect_workload_token), 4
has_workload_token(), 5
httr2::oauth_token, 2, 4, 5

local_mocked_connect_responses
 (with_mocked_connect_responses),
 5

response, 6

with_mocked_connect_responses, 5
with_mocked_connect_responses(), 6