

Package ‘crrSC’

May 8, 2026

Title Competing Risks Regression for Stratified and Clustered Data

Version 1.1.2

Author Bingqing Zhou and Aurelien Latouche

Description Extension of 'cmprsk' to Stratified and Clustered data.

A goodness of fit test for Fine-Gray model is also provided.

Methods are detailed in the following articles: Zhou et al. (2011) <[doi:10.1111/j.1541-0420.2010.01493.x](https://doi.org/10.1111/j.1541-0420.2010.01493.x)>,

Zhou et al. (2012) <[doi:10.1093/biostatistics/kxr032](https://doi.org/10.1093/biostatistics/kxr032)>,

Zhou et al. (2013) <[doi:10.1002/sim.5815](https://doi.org/10.1002/sim.5815)>.

Depends survival

Maintainer Aurelien Latouche <aurelien.latouche@cnam.fr>

License GPL-2

NeedsCompilation yes

Repository CRAN

Date/Publication 2022-06-10 21:20:20 UTC

Contents

bce	2
cdata	2
center	3
crrc	3
crrs	5
crrvvs	8
print.crrs	8
psh.test	9

Index	11
--------------	-----------

bce

Breast Cancer Data

Description

Data Randomly Generated According To E1178 clinical trial

Usage

data(bce)

Format

A data frame with 200 observations and the following 6 variables.

trt Treatment: 0=Placebo, 1=Tamoxifen

time Event time

type Event type. 0=censored, 1=Breast Cancer recurrence , 2=Death without recurrence

nnodes Number of positive nodes

tsize Tumor size

age Age

Examples

data(bce)

cdata

Clustered competing risks simulated data

Description

sample of 200 observations

Usage

data(cdata)

Format

A data frame with 200 observations and the following 4 variables. Simulation is detailed on the paper Competing Risk Regression for clustered data. Zhou, Fine, Latouche, Labopin. 2011. In Press. Biostatistics.

ID Id of cluster, each cluster is of size 2

ftime Event time

fstatus Event type. 0=censored, 1 , 2

z a binary covariate with $P(z=1)=0.5$

Examples

```
data(cdata)
```

```
center
```

```
Multicenter Bone Marrow transplantation data
```

Description

Random sub sample of 400 patients

Usage

```
data(center)
```

Format

A data frame with 400 observations and the following 5 variables.

id Id of transplantation center

ftime Event time

fstatus Event type. 0=censored, 1=Acute or Chronic GvHD , 2=Death free of GvHD

cells source of stem cells: peripheral blood vs bone marrow

fm female donor to male recipient match

Examples

```
data(center)
```

```
crrc
```

```
Competing Risks Regression for Clustered Data
```

Description

Regression modeling of subdistribution hazards for clustered right censored data. Failure times within the same cluster are dependent.

Usage

```
crrc(ftime, fstatus, cov1, cov2, tf, cluster,
      cengroup, failcode=1,
      cencode=0, subset,
      na.action=na.omit,
      gtol=1e-6, maxiter=10, init)
```

Arguments

<code>cluster</code>	Clustering covariate
<code>ftime</code>	vector of failure/censoring times
<code>fstatus</code>	vector with a unique code for each failure type and a separate code for censored observations
<code>cov1</code>	matrix (nobs x ncovs) of fixed covariates (either <code>cov1</code> , <code>cov2</code> , or both are required)
<code>cov2</code>	matrix of covariates that will be multiplied by functions of time; if used, often these covariates would also appear in <code>cov1</code> to give a prop hazards effect plus a time interaction
<code>tf</code>	functions of time. A function that takes a vector of times as an argument and returns a matrix whose <i>j</i> th column is the value of the time function corresponding to the <i>j</i> th column of <code>cov2</code> evaluated at the input time vector. At time <i>tk</i> , the model includes the term <code>cov2[, j]*tf(tk)[, j]</code> as a covariate.
<code>cengroup</code>	vector with different values for each group with a distinct censoring distribution (the censoring distribution is estimated separately within these groups). All data in one group, if missing.
<code>failcode</code>	code of <code>fstatus</code> that denotes the failure type of interest
<code>cencode</code>	code of <code>fstatus</code> that denotes censored observations
<code>subset</code>	a logical vector specifying a subset of cases to include in the analysis
<code>na.action</code>	a function specifying the action to take for any cases missing any of <code>ftime</code> , <code>fstatus</code> , <code>cov1</code> , <code>cov2</code> , <code>cengroup</code> , or <code>subset</code> .
<code>gtol</code>	iteration stops when a function of the gradient is < <code>gtol</code>
<code>maxiter</code>	maximum number of iterations in Newton algorithm (0 computes scores and var at <code>init</code> , but performs no iterations)
<code>init</code>	initial values of regression parameters (default=all 0)

Details

This method extends Fine-Gray proportional hazards model for subdistribution (1999) to accommodate situations where the failure times within a cluster might be correlated since the study subjects from the same cluster share common factors This model directly assesses the effect of covariates on the subdistribution of a particular type of failure in a competing risks setting.

Value

Returns a list of class `crr`, with components

<code>\$coef</code>	the estimated regression coefficients
<code>\$loglik</code>	log pseudo-likelihood evaluated at <code>coef</code>
<code>\$score</code>	derivatives of the log pseudo-likelihood evaluated at <code>coef</code>
<code>\$inf</code>	-second derivatives of the log pseudo-likelihood
<code>\$var</code>	estimated variance covariance matrix of <code>coef</code>
<code>\$res</code>	matrix of residuals

\$uftime	vector of unique failure times
\$bfitj	jumps in the Breslow-type estimate of the underlying sub-distribution cumulative hazard (used by predict.crr())
\$tfs	the tfs matrix (output of tf(), if used)
\$converged	TRUE if the iterative algorithm converged
\$call	The call to crr
\$n	The number of observations used in fitting the model
\$n.missing	The number of observations removed from the input data due to missing values
\$loglik.null	The value of the log pseudo-likelihood when all the coefficients are 0

Author(s)

Bingqing Zhou, <bingqing.zhou@yale.edu>

References

Zhou B, Fine J, Latouche A, Labopin M.(2012). Competing Risks Regression for Clustered data. *Biostatistics*. 13 (3): 371-383.

See Also

cmprsk

Examples

```
#library(cmprsk)
#crr(ftime=cdata$ftime, fstatus=cdata$fstatus, cov1=cdata$z)
# Simulated clustered data set
data(cdata)
crrc(ftime=cdata[,1], fstatus=cdata[,2],
cov1=cdata[,3],
cluster=cdata[,4])
```

crrs

Competing Risks Regression for Stratified Data

Description

Regression modeling of subdistribution hazards for stratified right censored data

Two types of stratification are addressed : Regularly stratified: small number of large groups (strata) of subjects Highly stratified: large number of small groups (strata) of subjects

Usage

```
crrs(ftime, fstatus, cov1, cov2, strata,
     tf, failcode=1, cencode=0,
     ctype=1,
     subsets, na.action=na.omit,
     gtol=1e-6, maxiter=10, init)
```

Arguments

<code>strata</code>	stratification covariate
<code>ctype</code>	1 if estimating censoring dist within strata (regular stratification), 2 if estimating censoring dist across strata (highly stratification)
<code>ftime</code>	vector of failure/censoring times
<code>fstatus</code>	vector with a unique code for each failure type and a separate code for censored observations
<code>cov1</code>	matrix (nobs x ncovs) of fixed covariates (either <code>cov1</code> , <code>cov2</code> , or both are required)
<code>cov2</code>	matrix of covariates that will be multiplied by functions of time; if used, often these covariates would also appear in <code>cov1</code> to give a prop hazards effect plus a time interaction
<code>tf</code>	functions of time. A function that takes a vector of times as an argument and returns a matrix whose <i>j</i> th column is the value of the time function corresponding to the <i>j</i> th column of <code>cov2</code> evaluated at the input time vector. At time <code>tk</code> , the model includes the term <code>cov2[, j]*tf(tk)[, j]</code> as a covariate.
<code>failcode</code>	code of <code>fstatus</code> that denotes the failure type of interest
<code>cencode</code>	code of <code>fstatus</code> that denotes censored observations
<code>subsets</code>	a logical vector specifying a subset of cases to include in the analysis
<code>na.action</code>	a function specifying the action to take for any cases missing any of <code>ftime</code> , <code>fstatus</code> , <code>cov1</code> , <code>cov2</code> , <code>cengroup</code> , or <code>subset</code> .
<code>gtol</code>	iteration stops when a function of the gradient is < <code>gtol</code>
<code>maxiter</code>	maximum number of iterations in Newton algorithm (0 computes scores and var at <code>init</code> , but performs no iterations)
<code>init</code>	initial values of regression parameters (default=all 0)

Details

Fits the stratified extension of the Fine and Gray model (2011). This model directly assesses the effect of covariates on the subdistribution of a particular type of failure in a competing risks setting.

Value

Returns a list of class `crr`, with components (see `crr` for details)

<code>\$coef</code>	the estimated regression coefficients
<code>\$loglik</code>	log pseudo-likelihood evaluated at <code>coef</code>

<code>\$score</code>	derivitives of the log pseudo-likelihood evaluated at coef
<code>\$inf</code>	-second derivatives of the log pseudo-likelihood
<code>\$var</code>	estimated variance covariance matrix of coef
<code>\$res</code>	matrix of residuals
<code>\$uftime</code>	vector of unique failure times
<code>\$bfitj</code>	jumps in the Breslow-type estimate of the underlying sub-distribution cumulative hazard (used by <code>predict.crr()</code>)
<code>\$tfs</code>	the tfs matrix (output of <code>tf()</code> , if used)
<code>\$converged</code>	TRUE if the iterative algorithm converged
<code>\$call</code>	The call to <code>crr</code>
<code>\$n</code>	The number of observations used in fitting the model
<code>\$n.missing</code>	The number of observations removed from the input data due to missing values
<code>\$loglik.null</code>	The value of the log pseudo-likelihood when all the coefficients are 0

Author(s)

Bingqing Zhou, <bingqing.zhou@yale.edu>

References

Zhou B, Latouche A, Rocha V, Fine J. (2011). Competing Risks Regression for Stratified Data. *Biometrics*. 67(2):661-70.

See Also

`cmprsk`

Examples

```
##
#using fine and gray model
#crr(ftime=center$ftime, fstatus=center$fstatus,
#cov1=cbind(center$fm,center$cells))
#
# High Stratification: ctype=2
# Random sub-sample
data(center)
cov.test<-cbind(center$fm,center$cells)
crrs(ftime=center[,1],fstatus=center[,2],
cov1=cov.test,
strata=center$id,ctype=2)
```

crrvvs	<i>For internal use</i>
--------	-------------------------

Description

for internal use

Author(s)

Bingqing Zhou

print.crrs	<i>Print method for crrs output</i>
------------	-------------------------------------

Description

Prints call for crrs object

Usage

```
## S3 method for class 'crrs'  
print(x, ...)
```

Arguments

x	crr object (output from crrs())
...	additional arguments to print()

Author(s)

B. Zhou

psh.test	<i>Goodness-of-fit test for proportional subdistribution hazards model</i>
----------	--

Description

This Goodness-of-fit test proposed a modified weighted Schoenfeld residuals to test the proportionality of subdistribution hazards for the Fine and Gray model

Usage

```
psh.test(time, fstatus, z, D=c(1,1), tf=function(x) cbind(x,x^2), init)
```

Arguments

time	vector of failure times
fstatus	failure status =0 if censored
z	covariates
D	components of z that are tested for time-varying effect
tf	functions of t for z being tested on the same location
init	initial values of regression parameters (default=all 0)

Details

The proposed score test employs Schoenfeld residuals adapted to competing risks data. The form of the test is established assuming that the non-proportionality arises via time-dependent coefficients in the Fine-Gray model, similar to the test of Grambsch and Therneau.

Value

Returns a data.frame with percentage of censored, cause 1, Test Statistic, d.f., p-value

Author(s)

Bingqing Zhou, <bingqing.zhou@yale.edu>

References

Zhou B, Fine JP, Laird, G. (2013). Goodness-of-fit test for proportional subdistribution hazards mode. *Statistics in Medicine*. In Press.

Examples

```
data(bce)
attach(bce)
lognodes <- log(nnodes)
Z1 <- cbind(lognodes, tsize/10, age, trt)
# trt = 0 if placebo, = 1 treatment
# testing for linear time varying effect of trt
psh.test(time=time, fstatus=type, z=Z1, D=c(0,0,0,1), tf=function(x) x)
# testing for quadratic time varying effect of trt
psh.test(time=time, fstatus=type, z=Z1, D=c(0,0,0,1), tf=function(x) x^2)
# testing for log time varying effect of trt
psh.test(time=time, fstatus=type, z=Z1, D=c(0,0,0,1),
tf=function(x) log(x))
# testing for both linear and quadratic time varying effect of trt
psh.test(time=time, fstatus=type, z=Z1,
D=matrix(c(0,0,0,1,0,0,0,1), 4,2), tf=function(x) cbind(x,x^2))
```

Index

- * **crrSC**
 - bce, 2
 - cdata, 2
 - center, 3
- * **datasets**
 - bce, 2
 - cdata, 2
 - center, 3
- * **survival**
 - crrc, 3
 - crrs, 5

bce, 2

cdata, 2

center, 3

crrc, 3

crrfs (crrvvs), 8

crrfsvs (crrvvs), 8

crrs, 5

crrvvs, 8

print.crrs, 8

psh.test, 9