

Package ‘dadjokeapi’

May 8, 2026

Type Package

Title Return a Random Dad Joke

Version 1.0.2

URL <https://github.com/jhollister/dadjokeapi/>

BugReports <https://github.com/jhollister/dadjokeapi/issues/>

Maintainer Jeffrey Hollister <jhollister.jeff@epa.gov>

Description What is funnier than a dad joke? A dad joke in R! This package utilizes the API for <<https://icanhazdadjoke.com>> and returns dad jokes from several API endpoints.

License MIT + file LICENSE

Depends R (>= 3.5.0)

Imports httr, beepr, curl, dplyr, png

LazyData true

RoxygenNote 7.1.1

Suggests testthat, mockery

NeedsCompilation no

Author Jeffrey Hollister [aut, cre],
Antoine Bichat [ctb],
Brett Langdon [cph]

Repository CRAN

Date/Publication 2021-03-01 09:20:09 UTC

Contents

groan	2
groan_id	2
groan_image	3
groan_search	3
Index	5

groan	<i>Function to return random dad joke</i>
-------	---

Description

This function returns a random dad joke(s) from <https://icanhazdadjoke.com>. as a message and invisibly as a character.

Usage

```
groan(sting = TRUE)
```

Arguments

sting	Plays a joke sting after the joke. Sound from https://archive.org/details/Rimshot_254
-------	---

Value

Invisibly returns a two item list with the first item holding the joke as a character and the second item containing the joke id as a character.

Examples

```
groan(sting = FALSE)
```

groan_id	<i>Function to return a specific dad joke</i>
----------	---

Description

This function returns a specific dad joke from <https://icanhazdadjoke.com> using its dad joke ID.

Usage

```
groan_id(joke_id)
```

Arguments

joke_id	A specific dad joke ID to return
---------	----------------------------------

Value

Returns a two item list with the first item holding the joke as a character and the second item containing the joke id as a character.

Examples

```
groan_id("G1GBIY0wAAAd")
```

groan_image	<i>Function to return a specific dad joke as an image</i>
-------------	---

Description

This function returns a specific dad joke as a png from <https://icanhazdadjoke.com> using its dad joke ID.

Usage

```
groan_image(joke_id)
```

Arguments

joke_id A specific dad joke ID to return

Value

Returns a png array from readPNG.

Examples

```
joke_png <- groan_image("G1GBIY0wAAAd")
```

groan_search	<i>Function to search and return dad jokes with specific terms</i>
--------------	--

Description

This function returns a specific dad joke as a png from <https://icanhazdadjoke.com> using its dad joke ID.

Usage

```
groan_search(term)
```

Arguments

term A term to search <https://icanhazdadjoke.com>

Value

Returns a tibble of joke and joke id for jokes that contain the search term.

Examples

```
groan_search(term = "cat")
```

Index

groan, [2](#)
groan_id, [2](#)
groan_image, [3](#)
groan_search, [3](#)