

# Package ‘datasets.load’

May 8, 2026

**Title** Graphical Interface for Loading Datasets

**Version** 2.3.0

**Description** Graphical interface for loading datasets in RStudio from all installed (including un-loaded) packages, also includes command line interfaces.

**Depends** R (>= 3.0.0)

**Imports** shiny, miniUI, DT

**License** GPL-3

**Encoding** UTF-8

**RoxygenNote** 7.2.3

**Suggests** testthat (>= 3.0.0), covr

**Config/testthat/edition** 3

**NeedsCompilation** no

**Author** Bastiaan quast [aut, cre] (ORCID:  
<<https://orcid.org/0000-0002-2951-3577>>)

**Maintainer** Bastiaan quast <bquast@gmail.com>

**Repository** CRAN

**Date/Publication** 2023-11-10 00:30:02 UTC

## Contents

datasets.load-package . . . . .	2
alldata . . . . .	2
browseDatasets . . . . .	2
datasets . . . . .	3
datasets.load . . . . .	3
getDatasetInfo . . . . .	4
print.browseDatasets . . . . .	4
print.datasets . . . . .	5
printDatasets . . . . .	5
promptDatasets . . . . .	6
<b>Index</b>	<b>7</b>

---

datasets.load-package *Interface for loading Datasets*

---

### Description

Interface for loading Datasets

---

alldata *List all datasets*

---

### Description

List all datasets

### Usage

```
alldata(package = NULL, lib.loc = NULL, all = TRUE, drop.defaults = FALSE)
```

### Arguments

package	a character vector with the names of packages to search through, or NULL in which "all" packages (as defined by argument all) are searched.
lib.loc	a character vector of directory names of R libraries, or NULL. The default value of NULL corresponds to all libraries currently known.
all	logical; if TRUE search all available packages in the library trees specified by lib.loc, and if FALSE, search only attached packages.
drop.defaults	logical; if TRUE, do not include the datasets from the datasets package.

---

browseDatasets *List datasets in an HTML Browser*

---

### Description

List datasets in an HTML Browser

### Usage

```
browseDatasets(  
  package = NULL,  
  lib.loc = NULL,  
  all = TRUE,  
  drop.defaults = FALSE  
)
```

**Arguments**

package	a character vector with the names of packages to search through, or NULL in which "all" packages (as defined by argument all) are searched.
lib.loc	a character vector of directory names of R libraries, or NULL. The default value of NULL corresponds to all libraries currently known.
all	logical; if TRUE search all available packages in the library trees specified by lib.loc, and if FALSE, search only attached packages.
drop.defaults	logical; if TRUE, do not include the datasets from the datasets package.

---

datasets	<i>View datasets from all installed packages</i>
----------	--

---

**Description**

View datasets from all installed packages

**Usage**

```
datasets(package = NULL, lib.loc = NULL, all = TRUE, drop.defaults = FALSE)
```

**Arguments**

package	a character vector with the names of packages to search through, or NULL in which "all" packages (as defined by argument all) are searched.
lib.loc	a character vector of directory names of R libraries, or NULL. The default value of NULL corresponds to all libraries currently known.
all	logical; if TRUE search all available packages in the library trees specified by lib.loc, and if FALSE, search only attached packages.
drop.defaults	logical; if TRUE, do not include the datasets from the datasets package.

---

datasets.load	<i>Load Datasets from a Menu</i>
---------------	----------------------------------

---

**Description**

Load Datasets from a Menu

**Usage**

```
datasets.load()
```

---

getDatasetInfo      *Get information on installed datasets.*

---

### Description

Get information on installed datasets.

### Usage

```
getDatasetInfo(
  package = NULL,
  lib.loc = NULL,
  all = TRUE,
  drop.defaults = FALSE
)
```

### Arguments

package	a character vector with the names of packages to search through, or NULL in which "all" packages (as defined by argument all) are searched.
lib.loc	a character vector of directory names of R libraries, or NULL. The default value of NULL corresponds to all libraries currently known.
all	logical; if TRUE search all available packages in the library trees specified by lib.loc, and if FALSE, search only attached packages.
drop.defaults	logical; if TRUE, do not include the datasets from the datasets package.

---

print.browseDatasets      *Print function for browseDatasets objects*

---

### Description

Print function for browseDatasets objects

### Usage

```
## S3 method for class 'browseDatasets'
print(x, ...)
```

### Arguments

x	Object of class datasets
...	Further arguments, ignored by the print method.

---

print.datasets	<i>Print function for datasets class objects</i>
----------------	--

---

**Description**

Print function for datasets class objects

**Usage**

```
## S3 method for class 'datasets'  
print(x, ...)
```

**Arguments**

x	an object used to select a method.
...	further arguments passed to or from other methods.

---

printDatasets	<i>Print datasets in the console</i>
---------------	--------------------------------------

---

**Description**

Print datasets in the console

**Usage**

```
printDatasets(  
  package = NULL,  
  lib.loc = NULL,  
  all = TRUE,  
  drop.defaults = FALSE  
)
```

**Arguments**

package	a character vector with the names of packages to search through, or NULL in which "all" packages (as defined by argument all) are searched.
lib.loc	a character vector of directory names of R libraries, or NULL. The default value of NULL corresponds to all libraries currently known.
all	logical; if TRUE search all available packages in the library trees specified by lib.loc, and if FALSE, search only attached packages.
drop.defaults	logical; if TRUE, do not include the datasets from the datasets package.

---

promptDatasets      *Prompt for dataset in the console*

---

**Description**

Prompt for dataset in the console

**Usage**

```
promptDatasets(  
  package = NULL,  
  lib.loc = NULL,  
  all = TRUE,  
  drop.defaults = FALSE  
)
```

**Arguments**

package	a character vector with the names of packages to search through, or NULL in which "all" packages (as defined by argument all) are searched.
lib.loc	a character vector of directory names of R libraries, or NULL. The default value of NULL corresponds to all libraries currently known.
all	logical; if TRUE search all available packages in the library trees specified by lib.loc, and if FALSE, search only attached packages.
drop.defaults	logical; if TRUE, do not include the datasets from the datasets package.

# Index

`alldata`, [2](#)

`browseDatasets`, [2](#)

`datasets`, [3](#)

`datasets.load`, [3](#)

`datasets.load-package`, [2](#)

`getDatasetInfo`, [4](#)

`print.browseDatasets`, [4](#)

`print.datasets`, [5](#)

`printDatasets`, [5](#)

`promptDatasets`, [6](#)