

Package ‘depth.plot’

May 8, 2026

Type Package

Title Multivariate Analogy of Quantiles

Version 0.1

Date 2015-12-19

Maintainer Somedip Karmakar <somedip@yahoo.co.in>

Description

Could be used to obtain spatial depths, spatial ranks and outliers of multivariate random variables. Could also be used to visualize DD-plots (a multivariate generalization of QQ-plots).

Imports mvtnorm , stats , graphics

License GPL-2

RoxygenNote 5.0.1

NeedsCompilation no

Author Omker Mahalanobish [aut],
Somedip Karmakar [cre, aut]

Repository CRAN

Date/Publication 2015-12-20 15:33:19

Contents

dd.plot	2
multi.quant	3
spatial.depth	4
spatial.outlier	4
spatial.rank	5

Index	7
--------------	----------

`dd.plot`*Depth-Depth Plots*

Description

`dd.plot` is a multivariate generalization of a normal QQ-plot. It produces a DD-plot of two datasets.

Usage

```
dd.plot(data1, data2 = rmvnorm(nrow(data1), array(0, ncol(data1)), diag(1,
  ncol(data1), ncol(data1))), main = "Normal DD-plot",
  xlab = "Sample Depths", ylab = "Normal Depths", col = "black",
  pch = 20)
```

Arguments

<code>data1</code>	A matrix or a data.frame with each row as a p-variate observation.
<code>data2</code>	A matrix or a data.frame (defaults to a standard independent p-variate normal).
<code>main</code>	Plot labels. The title of the plot.
<code>xlab</code>	Plot labels. The x-axis label of the plot.
<code>ylab</code>	Plot labels. The y-axis label of the plot.
<code>col</code>	The color of the points
<code>pch</code>	character string or vector of 1-characters or integers for plotting characters.

Value

A DD-plot of the input data

Author(s)

Somedip Karmakar <somedip@yahoo.co.in>

Omker Mahalanobish <omker.scorpio@gmail.com>

See Also

[spatial.depth](#)

Examples

```
u<-matrix(rnorm(300,1,4),ncol=3)
dd.plot(u)
```

multi.quant	<i>Multivariate Quantile</i>
-------------	------------------------------

Description

Used to compute the p-variate quantile of a p-variate observation with respect to a p-variate data cloud.

Usage

```
multi.quant(x, data)
```

Arguments

x	A numeric p-variate spatial rank. Elements must lie within -1 and +1, with a 0-vector denoting the median.
data	A matrix or a data.frame with each row as a p-variate observation.

Value

The xth multivariate quantile with respect to data.

Author(s)

Somedip Karmakar <somedip@yahoo.co.in>
Omker Mahalanobish <omker.scorpio@gmail.com>

See Also

[spatial.rank](#)

Examples

```
u<-matrix(rnorm(90,0,1),ncol=3)
u0<-runif(3,0,1)
multi.quant(spatial.rank(u0,u),u)
```

spatial.depth *Spatial Depth*

Description

spatial.depth is used to find the spatial depth of one or more p-variate observation(s) in a data cloud of numerous p-variate observations.

Usage

```
spatial.depth(x, data)
```

Arguments

x	A matrix or a data.frame of objects (numerical vector as one object) whose depth is to be found; each row consists a p-variate observation.
data	A matrix or a data.frame of objects which acts as the data cloud. Each row consists of a p-variate observation.

Value

Numerical vector of depths, one for each row in x; or one depth value if x is numerical.

Author(s)

Somedip Karmakar <somedip@yahoo.co.in>
Omker Mahalanobish <omker.scorpio@gmail.com>

Examples

```
u<-matrix(rnorm(90,0,1),ncol=3)
u0<-matrix(runif(9,0,1),ncol=3)
spatial.depth(u0,u)
```

spatial.outlier *Multivariate Spatial Outlier*

Description

spatial.outlier is used to find the multivariate spatial outlier within a p-variate data cloud or to identify if any p-variate observation is an outlier with respect to a p-variate data cloud.

Usage

```
spatial.outlier(data, x = data, threshold = 0.05)
```

Arguments

data	A matrix or a data.frame of p-variate observations which works as the data cloud.
x	A matrix or a data.frame p-variate to test whether is an outlier with respect to the data. Defaults to data, to find outliers (if exists) within the data.
threshold	A decimal threshold between 0 and 1 on the <code>spatial.depth</code> . Spatial depth values less than which will be considered as outlier. Defaults to 0.05. Usually taken as 0.1 or 0.05 or 0.01.

Value

FALSE :: If there doesnot exist any outlier
 A list with objects (If outliers exist)
 index :: Returns the indices of the outliers
 observation :: Returns the p-variate outliers

Author(s)

Somedip Karmakar <somedip@yahoo.co.in>
 Omker Mahalanobish <omker.scorpio@gmail.com>

Examples

```
u<-matrix(rnorm(60,0,1),ncol=3)
u0<-matrix(runif(9,3,4),ncol=3)
spatial.outlier(u,rbind(u,u0))
```

 spatial.rank

Spatial Rank

Description

Used to compute the Spatial Rank of a p-variate observation with respect to a p-variate data cloud.

Usage

```
spatial.rank(x, data)
```

Arguments

x	A numeric p-variate vector whose spatial rank is to be calculated.
data	A matrix or a data.frame with each row as a p-variate observation.

Value

The spatial rank of x with respect to data.

Author(s)

Somedip Karmakar <somedip@yahoo.co.in>

Omker Mahalanobish <omker.scorpio@gmail.com>

Examples

```
u<-matrix(rnorm(90,0,1),ncol=3)
```

```
u0<-runif(3,0,1)
```

```
spatial.rank(u0,u)
```

Index

`dd.plot`, 2

`multi.quant`, 3

`spatial.depth`, 2, 4, 5

`spatial.outlier`, 4

`spatial.rank`, 3, 5