

Package ‘detectXOR’

May 8, 2026

Title XOR Pattern Detection and Visualization

Version 0.1.0

Description Provides tools for detecting XOR-like patterns in variable pairs in two-class data sets. Includes visualizations for pattern exploration and reporting capabilities with both text and HTML output formats.

License GPL-3

Encoding UTF-8

LazyData true

Imports dplyr (>= 1.1.0), ggplot2 (>= 3.4.0), ggh4x (>= 0.2.3), tibble (>= 3.1.8), reshape2 (>= 1.4.4), glue (>= 1.6.0), magrittr (>= 2.0.0), stats, ggthemes, DescTools (>= 0.99.50), utils, methods, grDevices, knitr, kableExtra, htmltools, base64enc

Suggests testthat (>= 3.0.0), rmarkdown, doParallel, foreach, parallel (>= 4.2.0), future (>= 1.28.0), future.apply (>= 1.10.0), pbmcapply (>= 1.5.0)

RoxygenNote 7.2.3

SystemRequirements GNU make

Depends R (>= 3.5.0)

URL <https://github.com/JornLotsch/detectXOR>

BugReports <https://github.com/JornLotsch/detectXOR/issues>

NeedsCompilation no

Author Jorn Lotsch [aut, cre] (ORCID: <<https://orcid.org/0000-0002-5818-6958>>), Alfred Ultsch [aut]

Maintainer Jorn Lotsch <j.lotsch@em.uni-frankfurt.de>

Repository CRAN

Date/Publication 2025-06-27 13:00:06 UTC

Contents

detectXOR-package	2
detect_xor	3
generate_spaghetti_plot_from_results	6
generate_xor_reportConsole	7
generate_xor_reportHTML	8
generate_xy_plot_from_results	9
XOR_data	11
Index	12

detectXOR-package	<i>XOR Pattern Detection and Visualization</i>
-------------------	--

Description

Provides tools for detecting XOR-like patterns in variable pairs in two-class data sets. Includes visualizations for pattern exploration and reporting capabilities with both text and HTML output formats.

Details

Core Features:

1. Statistical detection using chi-square tests and Kendall's tau
2. Spaghetti plots and xy plot for pattern visualization

Main Functions:

- [detect_xor](#): Core detection algorithm
- [generate_spaghetti_plot_from_results](#): Line plots
- [generate_xy_plot_from_results](#): Plot for pattern visualization

Author(s)

Jorn Lotsch <j.lotsch@em.uni-frankfurt.de>

References

Methodological foundations:

- Pattern detection in machine learning
- Statistical dependency measures (Kendall's tau)

See Also

Useful links:

- <https://github.com/JornLotsch/detectXOR>
- Report bugs at <https://github.com/JornLotsch/detectXOR/issues>

Related packages:

- [DescTools](#) for statistical tests
- [ggh4x](#) for advanced plotting
- [future](#) for parallel processing

Examples

```
# Basic workflow with included dataset
data(XOR_data)

# Detect XOR patterns
results <- detect_xor(XOR_data, class_col = "class")

# Generate visualizations
generate_spaghetti_plot_from_results(
  results$results_df,
  XOR_data,
  class_col = "class"
)

generate_xy_plot_from_results(
  results$results_df,
  XOR_data,
  class_col = "class"
)
```

detect_xor

Detect XOR Patterns in Variable Pairs

Description

Identifies XOR-shaped relationships between variables using statistical tests and pattern detection.

Usage

```
detect_xor(
  data,
  class_col = "class",
  check_tau = TRUE,
  compute_axes_parallel_significance = TRUE,
```

```

p_threshold = 0.05,
tau_threshold = 0.3,
abs_diff_threshold = 20,
split_method = "quantile",
max_cores = 1,
extreme_handling = "winsorize",
winsor_limits = c(0.05, 0.95),
scale_data = TRUE,
use_complete = TRUE
)

```

Arguments

<code>data</code>	Data frame containing features and class column
<code>class_col</code>	Name of class column (default: "class")
<code>check_tau</code>	Logical - compute classwise tau coefficients (default: TRUE)
<code>compute_axes_parallel_significance</code>	Logical - compute Wilcoxon tests (default: TRUE)
<code>p_threshold</code>	Significance threshold (default: 0.05)
<code>tau_threshold</code>	Tau coefficient threshold (default: 0.3)
<code>abs_diff_threshold</code>	Absolute difference threshold for patterns (default: 20)
<code>split_method</code>	Method for splitting data ("quantile" or "range") (default: "quantile")
<code>max_cores</code>	Maximum cores for parallel processing (default: NULL = automatic)
<code>extreme_handling</code>	Method for handling extreme values; options include "winsorize" or "none" (default: "winsorize")
<code>winsor_limits</code>	Numeric vector of length 2 specifying lower and upper quantiles for winsorization (default: c(0.05, 0.95))
<code>scale_data</code>	Logical; whether to scale/standardize the data before analysis (default: TRUE)
<code>use_complete</code>	Logical; whether to use only complete cases (default: TRUE)

Details

This function performs an analysis to detect XOR-like patterns in pairwise variable relationships within two-class data sets. The analysis pipeline includes:

1. Data preprocessing (winsorization, scaling, complete cases)
2. Tile pattern analysis using chi-squared tests
3. Classwise Kendall tau correlation analysis
4. Group-wise Wilcoxon significance tests

The function automatically handles parallel processing when multiple cores are available and returns both a summary data frame and detailed results for further analysis.

Value

List containing:

results_df	Data frame with detection results for all variable pairs
pair_list	Detailed analysis results for each variable pair

See Also

[generate_spaghetti_plot_from_results](#) for spaghetti plot visualization, [generate_xy_plot_from_results](#) for scatter plot visualization, [generate_xor_reportConsole](#) for console reporting, [generate_xor_reportHTML](#) for HTML report generation, [XOR_data](#) for example dataset

Examples

```
# Load example data
data(XOR_data)

# Run XOR detection
results <- detect_xor(data = XOR_data, class_col = "class")

# View summary of detected patterns
print(results$results_df["xor_shape_detected"])

# Generate visualizations
spaghetti_plot <- generate_spaghetti_plot_from_results(
  results = results,
  data = XOR_data,
  class_col = "class"
)

print(spaghetti_plot)

xy_plot <- generate_xy_plot_from_results(
  results = results,
  data = XOR_data,
  class_col = "class"
)

print(xy_plot)

# Generate console report (doesn't write files)
generate_xor_reportConsole(results, XOR_data, "class", show_plots = FALSE)

# View detailed results for detected pairs
detected_pairs <- results$results_df[results$results_df$xor_shape_detected == TRUE, ]
print(detected_pairs)
```

generate_spaghetti_plot_from_results
Generate XOR Spaghetti Plots

Description

Creates connected line plots for variable pairs showing XOR patterns.

Usage

```
generate_spaghetti_plot_from_results(  
  results,  
  data,  
  class_col,  
  scale_data = TRUE  
)
```

Arguments

results	Either a data frame from <code>detect_xor()</code> \$results_df or the full list object returned by <code>detect_xor()</code>
data	Original dataset containing variables and classes
class_col	Character string specifying the name of the class column
scale_data	Logical indicating whether to scale variables before plotting (default: TRUE)

Details

This function creates spaghetti plots (connected line plots) for variable pairs that have been flagged as showing XOR patterns by `detect_xor()`. The function automatically handles both original and rotated XOR patterns, applying the appropriate coordinate transformation when necessary.

The function accepts either the full results object returned by `detect_xor()` or just the `results_df` component extracted from it. Variable pairs are separated using "|" as the delimiter in plot labels.

If no XOR patterns are detected, an empty plot with an appropriate message is returned.

To save the plot, use `ggplot2::ggsave()` or other standard R plotting save methods.

Value

Returns a ggplot object. No files are saved automatically.

See Also

[detect_xor](#) for XOR pattern detection, [generate_xy_plot_from_results](#) for scatter plots

Examples

```
# Using full results object (recommended)
data(XOR_data)
results <- detect_xor(data = XOR_data, class_col = "class")
spaghetti_plot <- generate_spaghetti_plot_from_results(
  results = results,
  data = XOR_data,
  class_col = "class"
)

# Display the plot
print(spaghetti_plot)

# Save the plot if needed
# ggplot2::ggsave("my_spaghetti_plot.png", spaghetti_plot)

# Using extracted results_df (also works)
xy_plot <- generate_spaghetti_plot_from_results(
  results = results$results_df,
  data = XOR_data,
  class_col = "class"
)
```

generate_xor_reportConsole

Generate XOR Detection Report (Console-friendly)

Description

Creates a report with formatted table and plots for XOR pattern detection results.

Usage

```
generate_xor_reportConsole(
  results,
  data,
  class_col,
  scale_data = TRUE,
  show_plots = TRUE,
  quantile_lines = c(1/3, 2/3),
  line_method = "quantile"
)
```

Arguments

results Either a data frame from `detect_xor$results_df` or the full list returned by `detect_xor`.

<code>data</code>	Original dataset containing variables and classes.
<code>class_col</code>	Character specifying the class column name.
<code>scale_data</code>	Logical indicating whether to scale variables in plots. Default: TRUE.
<code>show_plots</code>	Logical indicating whether to display plots. Default: TRUE.
<code>quantile_lines</code>	Numeric vector of quantiles for reference lines in XY plots. Default: <code>c(1/3, 2/3)</code> .
<code>line_method</code>	Method for boundary calculation ("quantile" or "range"). Default: "quantile".

Value

Invisibly returns a list containing the formatted table and plots (if generated).

See Also

[detect_xor](#) for XOR pattern detection, [generate_xor_reportHTML](#) for HTML report generation

`generate_xor_reportHTML`

Generate XOR Detection HTML Report

Description

Creates an HTML report with formatted table and plots for XOR pattern detection results.

Usage

```
generate_xor_reportHTML(
  results,
  data,
  class_col,
  output_file = "xor_detection_report.html",
  open_browser = TRUE,
  scale_data = TRUE,
  quantile_lines = c(1/3, 2/3),
  line_method = "quantile"
)
```

Arguments

<code>results</code>	Either a data frame from <code>detect_xor\$results_df</code> or the full list returned by <code>detect_xor</code> .
<code>data</code>	Original dataset containing variables and classes.
<code>class_col</code>	Character specifying the class column name.
<code>output_file</code>	Character specifying the output HTML file name. Default: "xor_detection_report.html".
<code>open_browser</code>	Logical indicating whether to open the report in browser automatically. Default: TRUE.

scale_data	Logical indicating whether to scale variables in plots. Default: TRUE.
quantile_lines	Numeric vector of quantiles for reference lines in XY plots. Default: c(1/3, 2/3).
line_method	Method for boundary calculation ("quantile" or "range"). Default: "quantile".

Value

Invisibly returns the file path of the generated HTML report.

See Also

[detect_xor](#) for XOR pattern detection, [generate_xor_reportConsole](#) for text-based report generation

generate_xy_plot_from_results

Generate XOR Scatter Plots

Description

Creates scatterplots with decision boundaries for variable pairs showing XOR patterns.

Usage

```
generate_xy_plot_from_results(
  results,
  data,
  class_col,
  scale_data = TRUE,
  quantile_lines = c(1/3, 2/3),
  line_method = "quantile"
)
```

Arguments

results	Either a data frame from <code>detect_xor()\$results_df</code> or the full list object returned by <code>detect_xor()</code>
data	Original dataset containing variables and classes
class_col	Character string specifying the name of the class column
scale_data	Logical indicating whether to scale variables before plotting (default: TRUE)
quantile_lines	Numeric vector of length 2 specifying quantiles for reference lines (default: c(1/3, 2/3))
line_method	Character string specifying the boundary calculation method, either "quantile" or "range" (default: "quantile")

Details

This function creates scatter plots for variable pairs that have been flagged as showing XOR patterns by `detect_xor()`. The plots include dashed reference lines that help visualize the decision boundaries used in XOR pattern detection.

The function automatically handles both original and rotated XOR patterns, applying the appropriate coordinate transformation when necessary. Variable pairs are separated using "||" as the delimiter in plot labels.

The `line_method` parameter controls how reference lines are calculated:

- "quantile": Lines are placed at the specified quantiles of the data distribution
- "range": Lines divide the data range into three equal parts

If no XOR patterns are detected, an empty plot with an appropriate message is returned.

To save the plot, use `ggplot2::ggsave()` or other standard R plotting save methods.

Value

Returns a ggplot object. No files are saved automatically.

See Also

[detect_xor](#) for XOR pattern detection, [generate_spaghetti_plot_from_results](#) for spaghetti plots

Examples

```
# Using full results object (recommended)
data(XOR_data)
results <- detect_xor(data = XOR_data, class_col = "class")
xy_plot <- generate_xy_plot_from_results(
  results = results,
  data = XOR_data,
  class_col = "class"
)

# Display the plot
print(xy_plot)

# Using different boundary method
xy_plot_range <- generate_xy_plot_from_results(
  results = results,
  data = XOR_data,
  class_col = "class",
  line_method = "range"
)

# Save the plot if needed
# ggplot2::ggsave("my_xy_plot.png", xy_plot)

# Using extracted results_df (also works)
```

```
xy_plot_df <- generate_xy_plot_from_results(  
  results = results$results_df,  
  data = XOR_data,  
  class_col = "class"  
)
```

XOR_data

Synthetic XOR Pattern Dataset

Description

Simulated classification dataset containing 400 observations with 5 features demonstrating XOR patterns, linear class differences, and random noise.

Usage

```
data("XOR_data")
```

Format

A data frame with 400 rows and 6 variables:

class Binary class labels (1 or 2)

Variable_A Normally distributed with subtle class difference ($\Delta \mu = 0.25$)

Variable_B High-variance normal distribution ($\sigma = 3$) with moderate class separation ($\Delta \mu = -0.7$)

Variable_C XOR pattern component 1 ($\mu = 3$ vs 10 between classes)

Variable_D XOR pattern component 2 ($\mu = 3$ vs 10 between classes)

Variable_E Uniform noise (1-10)

Source

Synthetic data generated with `rnorm()` and `runif()`

Examples

```
data(XOR_data)  
str(XOR_data)  
summary(XOR_data)
```

Index

- * **XOR**
 - detect_xor, 3
 - detectXOR-package, 2
 - generate_spaghetti_plot_from_results,
6
 - generate_xy_plot_from_results, 9
 - * **datasets**
 - XOR_data, 11
 - * **detection**
 - detect_xor, 3
 - * **machine learning**
 - detectXOR-package, 2
 - * **package**
 - detectXOR-package, 2
 - * **pattern detection**
 - detectXOR-package, 2
 - * **pattern**
 - detect_xor, 3
 - * **scatter**
 - generate_xy_plot_from_results, 9
 - * **spaghetti**
 - generate_spaghetti_plot_from_results,
6
 - * **visualization**
 - generate_spaghetti_plot_from_results,
6
 - generate_xy_plot_from_results, 9
- DescTools, 3
- detect_xor, 2, 3, 6, 8–10
- detectXOR-package, 2
- future, 3
- generate_spaghetti_plot_from_results,
2, 5, 6, 10
- generate_xor_reportConsole, 5, 7, 9
- generate_xor_reportHTML, 5, 8, 8
- generate_xy_plot_from_results, 2, 5, 6, 9
- ggh4x, 3