

# Package ‘dimensio’

May 8, 2026

**Title** Multivariate Data Analysis

**Version** 0.14.1

**Maintainer** Nicolas Frerebeau <nicolas.frerebeau@u-bordeaux-montaigne.fr>

**Description** Simple Principal Components Analysis (PCA) and (Multiple) Correspondence Analysis (CA) based on the Singular Value Decomposition (SVD). This package provides S4 classes and methods to compute, extract, summarize and visualize results of multivariate data analysis. It also includes methods for partial bootstrap validation described in Greenacre (1984, ISBN: 978-0-12-299050-2) and Lebart et al. (2006, ISBN: 978-2-10-049616-7).

**License** GPL (>= 3)

**URL** <https://codeberg.org/tesselle/dimensio>,  
<https://packages.tesselle.org/dimensio/>,  
<https://tesselle.r-universe.dev/dimensio>

**BugReports** <https://codeberg.org/tesselle/dimensio/issues>

**Depends** R (>= 3.5)

**Imports** arkhe (>= 1.10.0), graphics, grDevices, khroma (>= 1.16.0), methods, utils

**Suggests** fontquiver, knitr, markdown, rsvg, svglite, tinysnapshot, tinytest

**VignetteBuilder** knitr

**Encoding** UTF-8

**LazyData** true

**RoxygenNote** 7.3.2

**X-schema.org-isPartOf** <https://www.tesselle.org>

**X-schema.org-keywords** data-analysis, multivariate-analysis, r-package

**Collate** 'AllClasses.R' 'AllGenerics.R' 'annotations.R' 'augment.R'  
'biplot.R' 'bootstrap.R' 'ca.R' 'coerce.R' 'data.R'  
'dimensio-defunct.R' 'dimensio-deprecated.R'  
'dimensio-internal.R' 'dimensio-package.R' 'export.R'

'get\_contributions.R' 'get\_coordinates.R' 'get\_correlations.R'  
 'get\_cos2.R' 'get\_data.R' 'get\_distances.R' 'get\_eigenvalues.R'  
 'get\_inertia.R' 'get\_variance.R' 'mca.R' 'mutators.R' 'pca.R'  
 'pcoa.R' 'plot.R' 'predict.R' 'reexport.R' 'screeplot.R'  
 'show.R' 'subset.R' 'summary.R' 'svd.R' 'tidy.R' 'tools.R'  
 'viz\_contributions.R' 'viz\_coordinates.R' 'viz\_cos2.R'  
 'viz\_ellipse.R' 'viz\_hull.R' 'wrap\_ellipses.R' 'wrap\_hull.R'  
 'zzz.R'

**NeedsCompilation** no

**Author** Nicolas Frerebeau [aut, cre] (ORCID:

<<https://orcid.org/0000-0001-5759-4944>>),

Jean-Baptiste Fourvel [ctb] (ORCID:

<<https://orcid.org/0000-0002-1061-4642>>),

Camille Thabard [ctb] (ORCID: <<https://orcid.org/0000-0002-3196-7658>>),

Brice Lebrun [art] (ORCID: <<https://orcid.org/0000-0001-7503-8685>>),

Logo designer),

Université Bordeaux Montaigne [fnd] (ROR: <<https://ror.org/03pbgwk21>>),

CNRS [fnd] (ROR: <<https://ror.org/02feahw73>>)

**Repository** CRAN

**Date/Publication** 2025-09-03 16:00:02 UTC

## Contents

benthos	3
biplot	3
bootstrap	7
burt	9
ca	10
cdt	11
colours	13
countries	13
describe	14
dimnames	15
export	15
get_contributions	16
get_coordinates	18
get_data	19
get_eigenvalues	20
mca	21
pca	22
pcoa	24
plot	26
predict	28
screeplot	29
subset	30
summary	32

<i>benthos</i>	3
tidy . . . . .	33
viz_confidence . . . . .	35
viz_contributions . . . . .	38
viz_ellipses . . . . .	40
viz_hull . . . . .	42
viz_individuals . . . . .	43
viz_tolerance . . . . .	47
viz_variables . . . . .	50
<b>Index</b>	<b>55</b>

---

benthos	<i>Benthos</i>
---------	----------------

---

**Description**

Abundances of Marine Species in Sea-Bed Samples

**Usage**

benthos

**Format**

A `data.frame` with 13 columns (sites) and 92 rows (species).

**Source**

<http://www.carme-n.org/?sec=data7>

**See Also**

Other datasets: [colours](#), [countries](#)

---

biplot	<i>Biplot</i>
--------	---------------

---

**Description**

Biplot

**Usage**

```
## S4 method for signature 'CA'
biplot(
  x,
  ...,
  axes = c(1, 2),
  type = c("symetric", "rows", "columns", "contributions"),
  active = TRUE,
  sup = TRUE,
  labels = NULL,
  col.rows = c("#E69F00", "#E69F00"),
  col.columns = c("#56B4E9", "#56B4E9"),
  pch.rows = c(16, 1),
  pch.columns = c(17, 2),
  size = c(1, 3),
  xlim = NULL,
  ylim = NULL,
  main = NULL,
  sub = NULL,
  legend = list(x = "topleft")
)
```

```
## S4 method for signature 'PCA'
biplot(
  x,
  ...,
  axes = c(1, 2),
  type = c("form", "covariance"),
  active = TRUE,
  sup = TRUE,
  labels = "variables",
  col.rows = c("#E69F00", "#E69F00"),
  col.columns = c("#56B4E9", "#56B4E9"),
  pch.rows = c(16, 1),
  lty.columns = c(1, 3),
  xlim = NULL,
  ylim = NULL,
  main = NULL,
  sub = NULL,
  legend = list(x = "topleft")
)
```

**Arguments**

<code>x</code>	A <i>CA</i> , <i>MCA</i> or <i>PCA</i> object.
<code>...</code>	Currently not used.
<code>axes</code>	A length-two <i>numeric</i> vector giving the dimensions to be plotted.

type	A <a href="#">character</a> string specifying the biplot to be plotted (see below). It must be one of "rows", "columns", "contribution" (CA), "form" or "covariance" (PCA). Any unambiguous substring can be given.
active	A <a href="#">logical</a> scalar: should the active observations be plotted?
sup	A <a href="#">logical</a> scalar: should the supplementary observations be plotted?
labels	A <a href="#">character</a> vector specifying whether "rows"/"individuals" and/or "columns"/"variables" names must be drawn. Any unambiguous substring can be given.
col.rows, col.columns	A length-two vector of color specification for the active and supplementary rows/columns.
pch.rows, pch.columns	A length-two vector of symbol specification for the active and supplementary rows/columns.
size	A length-two <a href="#">numeric</a> vector giving range of possible sizes (greater than 0). Only used if type is "contribution" (CA).
xlim	A length-two <a href="#">numeric</a> vector giving the x limits of the plot. The default value, NULL, indicates that the range of the <a href="#">finite</a> values to be plotted should be used.
ylim	A length-two <a href="#">numeric</a> vector giving the y limits of the plot. The default value, NULL, indicates that the range of the <a href="#">finite</a> values to be plotted should be used.
main	A <a href="#">character</a> string giving a main title for the plot.
sub	A <a href="#">character</a> string giving a subtitle for the plot.
legend	A <a href="#">list</a> of additional arguments to be passed to <a href="#">graphics::legend()</a> ; names of the list are used as argument names. If NULL, no legend is displayed.
lty.columns	A length-two vector of line type specification for the active and supplementary columns.

## Details

A biplot is the simultaneous representation of rows and columns of a rectangular dataset. It is the generalization of a scatterplot to the case of multivariate data: it allows to visualize as much information as possible in a single graph (Greenacre 2010).

Biplots have the drawbacks of their advantages: they can quickly become difficult to read as they display a lot of information at once. It may then be preferable to visualize the results for individuals and variables separately.

## Value

biplot() is called for its side-effects: it results in a graphic being displayed. Invisibly returns x.

## PCA Biplots

form (**row-metric-preserving**) The form biplot favors the representation of the individuals: the distance between the individuals approximates the Euclidean distance between rows. In the form biplot the length of a vector approximates the quality of the representation of the variable.

covariance (**column-metric-preserving**) The covariance biplot favors the representation of the variables: the length of a vector approximates the standard deviation of the variable and the cosine of the angle formed by two vectors approximates the correlation between the two variables. In the covariance biplot the distance between the individuals approximates the Mahalanobis distance between rows.

### CA Biplots

symetric (**symetric biplot**) Represents the row and column profiles simultaneously in a common space: rows and columns are in standard coordinates. Note that the the inter-distance between any row and column items is not meaningful (i.e. the proximity between rows and columns cannot be directly interpreted).

rows (**asymetric biplot**) Row principal biplot (row-metric-preserving) with rows in principal coordinates and columns in standard coordinates.

columns (**asymetric biplot**) Column principal biplot (column-metric-preserving) with rows in standard coordinates and columns in principal coordinates.

contribution (**asymetric biplot**) Contribution biplot with rows in principal coordinates and columns in standard coordinates multiplied by the square roots of their masses.

### Author(s)

N. Frerebeau

### References

Aitchison, J. and Greenacre, M. J. (2002). Biplots of Compositional Data. *Journal of the Royal Statistical Society: Series C (Applied Statistics)*, 51(4): 375-92. doi:10.1111/14679876.00275.

Greenacre, M. J. (2010). *Biplots in Practice*. Bilbao: Fundación BBVA.

### See Also

Other plot methods: [plot\(\)](#), [screeplot\(\)](#), [viz\\_contributions\(\)](#), [viz\\_individuals\(\)](#), [viz\\_variables\(\)](#)

### Examples

```
## Replicate examples from Greenacre 2007, p. 59-68
data("iris")

## Compute principal components analysis
## All rows and all columns obtain the same weight
row_w <- rep(1 / nrow(countries), nrow(countries)) # 1/13
col_w <- rep(1 / ncol(countries), ncol(countries)) # 1/6
Y <- pca(iris, scale = FALSE, sup_quali = "Species")

## Row-metric-preserving biplot (form biplot)
biplot(Y, type = "form")

## Column-metric-preserving biplot (covariance biplot)
biplot(Y, type = "covariance", legend = list(x = "bottomright"))
```

```
## Replicate examples from Greenacre 2007, p. 79-88
data("benthos")

## Compute correspondence analysis
X <- ca(benthos)

## Symetric CA biplot
biplot(X, labels = "columns", legend = list(x = "bottomright"))

## Row principal CA biplot
biplot(X, type = "row", labels = "columns", legend = list(x = "bottomright"))

## Column principal CA biplot
biplot(X, type = "column", labels = "columns", legend = list(x = "bottomright"))

## Contribution CA biplot
biplot(X, type = "contrib", labels = NULL, legend = list(x = "bottomright"))
```

---

bootstrap

*Partial Bootstrap Analysis*

---

## Description

Checks analysis with partial bootstrap resampling.

## Usage

```
## S4 method for signature 'CA'
bootstrap(object, n = 30)

## S4 method for signature 'PCA'
bootstrap(object, n = 30)
```

## Arguments

object            A [CA](#) or [PCA](#) object.

n                 A non-negative [integer](#) giving the number of bootstrap replications.

## Value

Returns a [BootstrapCA](#) or a [BootstrapPCA](#) object.

## Author(s)

N. Frerebeau

## References

- Greenacre, Michael J. *Theory and Applications of Correspondence Analysis*. London: Academic Press, 1984.
- Lebart, L., Piron, M. and Morineau, A. *Statistique exploratoire multidimensionnelle: visualisation et inférence en fouille de données*. Paris: Dunod, 2006.
- Lockyear, K. (2013). Applying Bootstrapped Correspondence Analysis to Archaeological Data. *Journal of Archaeological Science*, 40(12): 4744-4753. doi:10.1016/j.jas.2012.08.035.
- Ringrose, T. J. (1992). Bootstrapping and Correspondence Analysis in Archaeology. *Journal of Archaeological Science*, 19(6): 615-629. doi:10.1016/03054403(92)90032X.

## Examples

```
## Bootstrap on CA
## Data from Lebart et al. 2006, p. 170-172
data("colours")

## Compute correspondence analysis
X <- ca(colours)

## Bootstrap (30 replicates)
Y <- bootstrap(X, n = 30)

## Not run:
## Get replicated coordinates
get_replications(Y, margin = 1)
get_replications(Y, margin = 2)

## End(Not run)

## Plot with ellipses
viz_rows(Y)
viz_tolerance(Y, level = c(0.68, 0.95))

viz_columns(Y)
viz_tolerance(Y, level = c(0.68, 0.95))

## Plot with convex hulls
viz_columns(Y)
viz_hull(Y)

## Bootstrap on PCA
## Compute principal components analysis
data("iris")
X <- pca(iris, sup_quali = "Species")

## Bootstrap (30 replicates)
Y <- bootstrap(X, n = 30)

## Plot with ellipses
viz_variables(Y)
viz_tolerance(Y, level = c(0.68, 0.95))
```

---

burt	<i>Burt Table</i>
------	-------------------

---

## Description

Computes the burt table of a factor table.

## Usage

```
burt(object, ...)
```

```
## S4 method for signature 'data.frame'  
burt(object, exclude = NULL, abbrev = TRUE)
```

## Arguments

object	A <a href="#">data.frame</a> .
...	Currently not used.
exclude	A vector of values to be excluded when forming the set of levels (see <a href="#">factor()</a> ). If NULL (the default), will make NA an extra level.
abbrev	A <a href="#">logical</a> scalar: should the column names be abbreviated? If FALSE, these are of the form 'factor_level' but if abbrev = TRUE they are just 'level' which will suffice if the factors have distinct levels.

## Value

A symmetric [matrix](#).

## Author(s)

N. Frerebeau

## See Also

Other tools: [cdt\(\)](#)

## Examples

```
## Create a factor table  
x <- data.frame(  
  A = c("a", "b", "a"),  
  B = c("x", "y", "z")  
)  
  
## Complete disjunctive table  
cdt(x)  
  
## Burt table  
burt(x)
```

---

ca *Correspondence Analysis*

---

### Description

Computes a simple correspondence analysis based on the singular value decomposition.

### Usage

```
ca(object, ...)  
  
## S4 method for signature 'data.frame'  
ca(  
  object,  
  rank = NULL,  
  sup_row = NULL,  
  sup_col = NULL,  
  sup_quali = NULL,  
  autodetect = FALSE  
)  
  
## S4 method for signature 'matrix'  
ca(object, rank = NULL, sup_row = NULL, sup_col = NULL)
```

### Arguments

object	A $m \times p$ numeric <a href="#">matrix</a> or a <a href="#">data.frame</a> .
...	Currently not used.
rank	An <a href="#">integer</a> value specifying the maximal number of components to be kept in the results. If NULL (the default), $\min(m, p) - 1$ components will be returned.
sup_row	A vector specifying the indices of the supplementary rows.
sup_col	A vector specifying the indices of the supplementary columns.
sup_quali	A vector specifying the indices of the supplementary qualitative columns.
autodetect	A <a href="#">logical</a> scalar: should non-numeric variables be automatically removed?

### Value

A [CA](#) object.

### Author(s)

N. Frerebeau

## References

Greenacre, M. J. *Theory and Applications of Correspondence Analysis*. London: Academic Press, 1984.

Greenacre, M. J. *Correspondence Analysis in Practice*. Seconde edition. Interdisciplinary Statistics Series. Boca Raton: Chapman & Hall/CRC, 2007.

Lebart, L., Piron, M. and Morineau, A. *Statistique exploratoire multidimensionnelle: visualisation et inférence en fouille de données*. Paris: Dunod, 2006.

## See Also

[svd\(\)](#)

Other multivariate analysis: [mca\(\)](#), [pca\(\)](#), [pcoa\(\)](#), [predict\(\)](#)

## Examples

```
## Data from Lebart et al. 2006, p. 170-172
data("colours")

## The chi square of independence between the two variables
stats::chisq.test(colours)

## Compute correspondence analysis
X <- ca(colours)

## Plot rows
viz_rows(X, labels = TRUE)

## Plot columns
viz_columns(X, labels = TRUE)

## Get row coordinates
get_coordinates(X, margin = 1)

## Get column coordinates
get_coordinates(X, margin = 2)

## Get total inertia
sum(get_inertia(X))

## Get row contributions
get_contributions(X, margin = 1)
```

---

cdt

*Complete Disjunctive Table*

---

## Description

Computes the complete disjunctive table of a factor table.

## Usage

```
cdt(object, ...)  
  
## S4 method for signature 'matrix'  
cdt(object, exclude = NULL, abbrev = TRUE)  
  
## S4 method for signature 'data.frame'  
cdt(object, exclude = NULL, abbrev = TRUE)
```

## Arguments

object	A <a href="#">data.frame</a> .
...	Currently not used.
exclude	A vector of values to be excluded when forming the set of levels (see <a href="#">factor()</a> ). If NULL (the default), will make NA an extra level.
abbrev	A <a href="#">logical</a> scalar: should the column names be abbreviated? If FALSE, these are of the form 'factor_level' but if abbrev = TRUE they are just 'level' which will suffice if the factors have distinct levels.

## Value

A [data.frame](#).

## Author(s)

N. Frerebeau

## See Also

Other tools: [burt\(\)](#)

## Examples

```
## Create a factor table  
x <- data.frame(  
  A = c("a", "b", "a"),  
  B = c("x", "y", "z")  
)  
  
## Complete disjunctive table  
cdt(x)  
  
## Burt table  
burt(x)
```

---

colours

*Colours*

---

**Description**

Contingency table of eye and hair colours of different individuals.

**Usage**

colours

**Format**

A [data.frame](#) with 4 columns (hair colours) and 4 rows (eye colours).

**Source**

Lebart, L., Piron, M. and Morineau, A. *Statistique exploratoire multidimensionnelle: visualisation et inférence en fouille de données*. Paris: Dunod, 2006, p. 170-172

**See Also**

Other datasets: [benthos](#), [countries](#)

---

countries

*Countries*

---

**Description**

Student ratings of 13 countries on six attributes.

**Usage**

countries

**Format**

A [data.frame](#) with 6 columns (attributes) and 13 rows (countries).

**Source**

Greenacre, M. J. *Biplots in Practice*. Bilbao: Fundación BBVA, 2010.

**See Also**

Other datasets: [benthos](#), [colours](#)

---

describe	<i>Object Description</i>
----------	---------------------------

---

**Description**

Object Description

**Usage**

```
## S4 method for signature 'CA'
```

```
describe(x, ...)
```

```
## S4 method for signature 'PCA'
```

```
describe(x, ...)
```

**Arguments**

x                    A CA, MCA or PCA object.

...                  Further parameters to be passed to `cat()`.

**Value**

`describe()` is called for its side-effects. Invisibly returns x.

**Author(s)**

N. Frerebeau

**See Also**

Other summary: `summary()`, `tidy()`

**Examples**

```
## Data from Lebart et al. 2006, p. 170-172  
data("colours")
```

```
## Compute correspondence analysis  
X <- ca(colours)
```

```
## Rows summary  
summary(X, margin = 1)
```

```
## Columns summary  
summary(X, margin = 2)
```

---

dimnames	<i>Dimnames of an Object</i>
----------	------------------------------

---

**Description**

Retrieve or set the dimnames of an object.

**Usage**

```
## S4 method for signature 'MultivariateAnalysis'  
dim(x)  
  
## S4 method for signature 'MultivariateAnalysis'  
rownames(x, do.NULL = TRUE, prefix = "row")  
  
## S4 method for signature 'MultivariateAnalysis'  
colnames(x, do.NULL = TRUE, prefix = "col")  
  
## S4 method for signature 'MultivariateAnalysis'  
dimnames(x)
```

**Arguments**

x	An object from which to retrieve the row or column names (a <a href="#">CA</a> or <a href="#">PCA</a> object).
do.NULL	A <a href="#">logical</a> scalar. If FALSE and names are NULL, names are created.
prefix	A <a href="#">character</a> string specifying the prefix for created names.

**Author(s)**

N. Frerebeau

**See Also**

Other mutators: [subset\(\)](#)

---

export	<i>Export Results</i>
--------	-----------------------

---

**Description**

Creates a Zip archive of all results in CSV format.

**Usage**

```
export(object, ...)

## S4 method for signature 'MultivariateAnalysis'
export(object, file, flags = "-r9Xj", ...)

## S4 method for signature 'PCOA'
export(object, file, flags = "-r9Xj", ...)
```

**Arguments**

object	A <a href="#">CA</a> , <a href="#">MCA</a> or <a href="#">PCA</a> object.
...	Currently not used.
file	A <a href="#">character</a> string specifying the pathname of the zip file.
flags	A <a href="#">character</a> string of flags (see <a href="#">utils::zip()</a> ).

**Author(s)**

N. Frerebeau

**See Also**

[utils::write.csv\(\)](#), [utils::zip\(\)](#)

Other getters: [get\\_contributions\(\)](#), [get\\_coordinates\(\)](#), [get\\_data\(\)](#), [get\\_eigenvalues\(\)](#)

**Examples**

```
## Not run:
## Load data
data("iris")

## Compute principal components analysis
X <- pca(iris, sup_quali = "Species")

## Export results
export(X, file = "results.zip")

## End(Not run)
```

---

get\_contributions

*Get Contributions*

---

**Description**

Get Contributions

**Usage**

```

get_contributions(x, ...)

get_correlations(x, ...)

get_cos2(x, ...)

## S4 method for signature 'MultivariateAnalysis'
get_contributions(x, margin = 1)

## S4 method for signature 'PCA'
get_correlations(x, sup_name = ".sup")

## S4 method for signature 'MultivariateAnalysis'
get_cos2(x, margin = 1, sup_name = ".sup")

```

**Arguments**

x	An object from which to get element(s) (a <a href="#">CA</a> , <a href="#">MCA</a> or <a href="#">PCA</a> object).
...	Currently not used.
margin	A length-one <a href="#">numeric</a> vector giving the subscript which the data will be returned: 1 indicates individuals/rows (the default), 2 indicates variables/columns.
sup_name	A <a href="#">character</a> string specifying the name of the column to create for supplementary points attribution (see below).

**Value**

- `get_contributions()` returns a [data.frame](#) of contributions to the definition of the principal dimensions.
- `get_correlations()` returns a [data.frame](#) of correlations between variables and dimensions. An extra column (named after `sup_name`) is added specifying whether an observation is a supplementary point or not.
- `get_cos2()` returns a [data.frame](#) of  $\cos^2$  values (i.e. quality of the representation of the points on the factor map). An extra column (named after `sup_name`) is added specifying whether an observation is a supplementary point or not.

**Author(s)**

N. Frerebeau

**See Also**

Other getters: [export\(\)](#), [get\\_coordinates\(\)](#), [get\\_data\(\)](#), [get\\_eigenvalues\(\)](#)

---

get\_coordinates      *Get Coordinates*

---

## Description

Get Coordinates

## Usage

```
get_coordinates(x, ...)
```

```
get_replications(x, ...)
```

```
## S4 method for signature 'MultivariateAnalysis'
get_coordinates(x, margin = 1, principal = TRUE, sup_name = ".sup")
```

```
## S4 method for signature 'PCOA'
get_coordinates(x)
```

```
## S4 method for signature 'MultivariateBootstrap'
get_replications(x, margin = 1)
```

```
## S4 method for signature 'BootstrapPCA'
get_replications(x)
```

## Arguments

x	An object from which to get element(s) (a <a href="#">CA</a> , <a href="#">MCA</a> or <a href="#">PCA</a> object).
...	Currently not used.
margin	A length-one <a href="#">numeric</a> vector giving the subscript which the data will be returned: 1 indicates individuals/rows (the default), 2 indicates variables/columns.
principal	A <a href="#">logical</a> scalar: should principal coordinates be returned? If FALSE, standard coordinates are returned.
sup_name	A <a href="#">character</a> string specifying the name of the column to create for supplementary points attribution (see below).

## Value

- `get_coordinates()` returns a [data.frame](#) of coordinates. An extra column (named after `sup_name`) is added specifying whether an observation is a supplementary point or not.
- `get_replications()` returns an [array](#) of coordinates.

## Author(s)

N. Frerebeau

**See Also**

Other getters: [export\(\)](#), [get\\_contributions\(\)](#), [get\\_data\(\)](#), [get\\_eigenvalues\(\)](#)

**Examples**

```
## Load data
data("iris")

## Compute principal components analysis
X <- pca(iris, scale = TRUE, sup_row = 5:10, sup_quali = "Species")

## Get row principal coordinates
head(get_coordinates(X, margin = 1, principal = TRUE))

## Get row standard coordinates
head(get_coordinates(X, margin = 1, principal = FALSE))

## Tidy principal coordinates
head(tidy(X, margin = 1))
head(tidy(X, margin = 2))

head(augment(X, margin = 1, axes = c(1, 2)))
head(augment(X, margin = 2, axes = c(1, 2)))
```

---

get\_data

*Get Original Data*

---

**Description**

Get Original Data

**Usage**

```
get_data(x, ...)
```

## S4 method for signature 'MultivariateAnalysis'  
get\_data(x)

**Arguments**

x                    An object from which to get element(s) (a [CA](#), [MCA](#) or [PCA](#) object).  
...                   Currently not used.

**Value**

Returns a [data.frame](#) of original data.

**Author(s)**

N. Frerebeau

**See Also**Other getters: [export\(\)](#), [get\\_contributions\(\)](#), [get\\_coordinates\(\)](#), [get\\_eigenvalues\(\)](#)


---

get_eigenvalues	<i>Get Eigenvalues</i>
-----------------	------------------------

---

**Description**

Get Eigenvalues

**Usage**`get_eigenvalues(x)``get_variance(x, ...)``get_distances(x, ...)``get_inertia(x, ...)`

```
## S4 method for signature 'MultivariateAnalysis'
get_distances(x, margin = 1)
```

```
## S4 method for signature 'MultivariateAnalysis'
get_eigenvalues(x)
```

```
## S4 method for signature 'PCOA'
get_eigenvalues(x)
```

```
## S4 method for signature 'MultivariateAnalysis'
get_inertia(x, margin = 1)
```

```
## S4 method for signature 'MultivariateAnalysis'
get_variance(x, digits = 2)
```

**Arguments**

<code>x</code>	An object from which to get element(s) (a <a href="#">CA</a> , <a href="#">MCA</a> or <a href="#">PCA</a> object).
<code>...</code>	Currently not used.
<code>margin</code>	A length-one <a href="#">numeric</a> vector giving the subscript which the data will be returned: 1 indicates individuals/rows (the default), 2 indicates variables/columns.
<code>digits</code>	An <a href="#">integer</a> indicating the number of decimal places to be used.

**Value**

- `get_eigenvalues()` returns a `data.frame` with the following columns: eigenvalues, variance (percentage of variance) and cumulative (cumulative percentage of variance).
- `get_variance()` returns a `numeric` vector giving the amount of variance explained by each (principal) component.
- `get_distance()` returns a `numeric` vector of squared distance to the centroid.
- `get_inertia()` returns a `numeric` vector giving the inertia (weighted squared distance to the centroid).

**Author(s)**

N. Frerebeau

**See Also**

Other getters: `export()`, `get_contributions()`, `get_coordinates()`, `get_data()`

---

mca

*Multiple Correspondence Analysis*

---

**Description**

Computes a multiple correspondence analysis.

**Usage**

```
mca(object, ...)  
  
## S4 method for signature 'data.frame'  
mca(  
  object,  
  rank = NULL,  
  sup_row = NULL,  
  sup_col = NULL,  
  sup_quanti = NULL,  
  autodetect = FALSE  
)  
  
## S4 method for signature 'matrix'  
mca(object, rank = NULL, sup_row = NULL, sup_col = NULL)
```

**Arguments**

object	A $m \times p$ numeric <a href="#">matrix</a> or a <a href="#">data.frame</a> .
...	Currently not used.
rank	An <a href="#">integer</a> value specifying the maximal number of components to be kept in the results. If NULL (the default), $\min(m, p) - 1$ components will be returned.
sup_row	A vector specifying the indices of the supplementary rows.
sup_col	A vector specifying the indices of the supplementary categorical columns.
sup_quanti	A vector specifying the indices of the supplementary quantitative columns.
autodetect	A <a href="#">logical</a> scalar: should numeric variables be automatically removed (except sup_quanti)?

**Value**

A [MCA](#) object.

**Author(s)**

N. Frerebeau

**References**

Lebart, L., Piron, M. and Morineau, A. *Statistique exploratoire multidimensionnelle: visualisation et inférence en fouille de données*. Paris: Dunod, 2006.

**See Also**

[svd\(\)](#), [cdt\(\)](#)

Other multivariate analysis: [ca\(\)](#), [pca\(\)](#), [pcoa\(\)](#), [predict\(\)](#)

---

pca

*Principal Components Analysis*

---

**Description**

Computes a principal components analysis based on the singular value decomposition.

**Usage**

```
pca(object, ...)  
  
## S4 method for signature 'data.frame'  
pca(  
  object,  
  center = TRUE,  
  scale = TRUE,
```

```

rank = NULL,
sup_row = NULL,
sup_col = NULL,
sup_quali = NULL,
weight_row = NULL,
weight_col = NULL,
autodetect = FALSE
)

## S4 method for signature 'matrix'
pca(
  object,
  center = TRUE,
  scale = TRUE,
  rank = NULL,
  sup_row = NULL,
  sup_col = NULL,
  weight_row = NULL,
  weight_col = NULL
)

```

### Arguments

object	A $m \times p$ numeric <a href="#">matrix</a> or a <a href="#">data.frame</a> .
...	Currently not used.
center	A <a href="#">logical</a> scalar: should the variables be shifted to be zero centered?
scale	A <a href="#">logical</a> scalar: should the variables be scaled to unit variance?
rank	An <a href="#">integer</a> value specifying the maximal number of components to be kept in the results. If NULL (the default), $p - 1$ components will be returned.
sup_row	A vector specifying the indices of the supplementary rows.
sup_col	A vector specifying the indices of the supplementary columns.
sup_quali	A vector specifying the indices of the supplementary qualitative columns.
weight_row	A <a href="#">numeric</a> vector specifying the active row (individual) weights. If NULL (the default), uniform weights are used. Row weights are internally normalized to sum 1
weight_col	A <a href="#">numeric</a> vector specifying the active column (variable) weights. If NULL (the default), uniform weights (1) are used.
autodetect	A <a href="#">logical</a> scalar: should non-numeric variables be automatically removed (except <code>sup_quali</code> )?

### Value

A [PCA](#) object.

### Author(s)

N. Frerebeau

## References

Lebart, L., Piron, M. and Morineau, A. *Statistique exploratoire multidimensionnelle: visualisation et inférence en fouille de données*. Paris: Dunod, 2006.

## See Also

[svd\(\)](#)

Other multivariate analysis: [ca\(\)](#), [mca\(\)](#), [pcoa\(\)](#), [predict\(\)](#)

## Examples

```
## Load data
data("iris")

## Compute principal components analysis
X <- pca(iris, sup_quali = "Species")

## Get eigenvalues
get_eigenvalues(X)

## Get individual cos2
head(get_cos2(X, margin = 1))

## Get variable contributions
get_contributions(X, margin = 2)

## Get correlations between variables and dimensions
get_correlations(X)
```

---

pcoa

*Principal Coordinates Analysis*

---

## Description

Computes classical (metric) multidimensional scaling.

## Usage

```
pcoa(object, ...)
```

## S4 method for signature 'dist'

```
pcoa(object, rank = 2)
```

## Arguments

object	A <a href="#">distance structure</a> .
...	Currently not used.
rank	An <a href="#">integer</a> value specifying the maximal number dimension of the space which the data are to be represented in.

**Value**

A [PCOA](#) object.

**Author(s)**

N. Frerebeau

**References**

Gower, J. C. (1966). Some Distance Properties of Latent Root and Vector Methods Used in Multivariate Analysis. *Biometrika*, 53(3-4): 325-338. doi:[10.1093/biomet/53.34.325](https://doi.org/10.1093/biomet/53.34.325).

**See Also**

[stats::cmdscale\(\)](#)

Other multivariate analysis: [ca\(\)](#), [mca\(\)](#), [pca\(\)](#), [predict\(\)](#)

**Examples**

```
## Load data
data("iris")

## Compute euclidean distances
d <- dist(iris[, 1:4], method = "euclidean")

## Compute principal coordinates analysis
X <- pcoa(d)

## Screeplot
screeplot(X)

## Plot results
plot(X, extra_quali = iris$Species)

## Add convex hulls
plot(
  x = X,
  extra_quali = iris$Species,
  hull = TRUE
)

## Add tolerance ellipses
plot(
  x = X,
  extra_quali = iris$Species,
  ellipse = list(type = "tolerance", level = 0.95)
)
```

plot

*Plot Coordinates***Description**

Plot Coordinates

**Usage**

```
## S4 method for signature 'PCOA,missing'
plot(
  x,
  ...,
  axes = c(1, 2),
  labels = FALSE,
  extra_quali = NULL,
  extra_quant = NULL,
  ellipse = NULL,
  hull = FALSE,
  color = NULL,
  fill = FALSE,
  symbol = FALSE,
  size = c(1, 6),
  xlim = NULL,
  ylim = NULL,
  main = NULL,
  sub = NULL,
  ann = graphics::par("ann"),
  frame.plot = TRUE,
  panel.first = NULL,
  panel.last = NULL,
  legend = list(x = "topleft")
)
```

**Arguments**

x	An R object.
...	Further <a href="#">graphical parameters</a> .
axes	A length-two <a href="#">numeric</a> vector giving the dimensions to be plotted.
labels	A <a href="#">logical</a> scalar: should labels be drawn? Labeling a large number of points can be computationally expensive and make the graph difficult to read. A selection of points to label can be provided using a <code>list</code> of two named elements, <code>filter</code> (a string specifying how to filter the labels to be drawn) and <code>n</code> (an integer specifying the number of labels to be drawn). See examples below.
extra_quali	An optional vector of qualitative data for aesthetics mapping.

extra_quant	An optional vector of quantitative data for aesthetics mapping. If a single <a href="#">character</a> string is passed, it must be one of "observation", "mass", "sum", "contribution" or "cos2" (see <a href="#">augment()</a> ).
ellipse	A <a href="#">list</a> of additional arguments to be passed to <a href="#">viz_ellipses()</a> ; names of the list are used as argument names. If NULL, no ellipse are displayed.
hull	A <a href="#">logical</a> scalar: should convex hulls be displayed?
color	The colors for lines and points (will be mapped to extra_quant or extra_qual; if both are set, the latter has priority). Ignored if set to FALSE. If NULL, the default color scheme will be used.
fill	The background colors for points (will be mapped to extra_quant or extra_qual; if both are set, the latter has priority). Ignored if set to FALSE.
symbol	A vector of plotting characters or symbols (will be mapped to extra_qual). This can either be a single character or an integer code for one of a set of graphics symbols. If symbol is a named vector, then the symbols will be associated with their name within extra_qual. Ignored if set to FALSE.
size	A length-two <a href="#">numeric</a> vector giving range of possible sizes (greater than 0; will be mapped to extra_quant). Ignored if set to FALSE.
xlim	A length-two <a href="#">numeric</a> vector giving the x limits of the plot. The default value, NULL, indicates that the range of the <a href="#">finite</a> values to be plotted should be used.
ylim	A length-two <a href="#">numeric</a> vector giving the y limits of the plot. The default value, NULL, indicates that the range of the <a href="#">finite</a> values to be plotted should be used.
main	A <a href="#">character</a> string giving a main title for the plot.
sub	A <a href="#">character</a> string giving a subtitle for the plot.
ann	A <a href="#">logical</a> scalar: should the default annotation (title and x and y axis labels) appear on the plot?
frame.plot	A <a href="#">logical</a> scalar: should a box be drawn around the plot?
panel.first	An expression to be evaluated after the plot axes are set up but before any plotting takes place. This can be useful for drawing background grids.
panel.last	An expression to be evaluated after plotting has taken place but before the axes, title and box are added.
legend	A <a href="#">list</a> of additional arguments to be passed to <a href="#">graphics::legend()</a> ; names of the list are used as argument names. If NULL, no legend is displayed.

**Author(s)**

N. Frerebeau

**See Also**

Other plot methods: [biplot\(\)](#), [screplot\(\)](#), [viz\\_contributions\(\)](#), [viz\\_individuals\(\)](#), [viz\\_variables\(\)](#)

---

predict	<i>Predict New Coordinates</i>
---------	--------------------------------

---

### Description

Predict the projection of new individuals/rows or variables/columns.

### Usage

```
## S4 method for signature 'CA'  
predict(object, newdata, margin = 1)  
  
## S4 method for signature 'MCA'  
predict(object, newdata, margin = 1)  
  
## S4 method for signature 'PCA'  
predict(object, newdata, margin = 1)
```

### Arguments

object	A <a href="#">CA</a> or <a href="#">PCA</a> object.
newdata	An object of supplementary points coercible to a <a href="#">matrix</a> for which to compute principal coordinates.
margin	A length-one <a href="#">numeric</a> vector giving the subscript which the data will be predicted: 1 indicates individuals/rows (the default), 2 indicates variables/columns.

### Value

A [data.frame](#) of coordinates.

### Author(s)

N. Frerebeau

### See Also

Other multivariate analysis: [ca\(\)](#), [mca\(\)](#), [pca\(\)](#), [pcoa\(\)](#)

### Examples

```
## Create a matrix  
A <- matrix(data = sample(1:10, 100, TRUE), nrow = 10, ncol = 10)  
  
## Compute correspondence analysis  
X <- ca(A, sup_row = 8:10, sup_col = 7:10)  
  
## Predict new row coordinates  
Y <- matrix(data = sample(1:10, 120, TRUE), nrow = 20, ncol = 6)
```

```

predict(X, Y, margin = 1)

## Predict new column coordinates
Z <- matrix(data = sample(1:10, 140, TRUE), nrow = 7, ncol = 20)
predict(X, Z, margin = 2)

```

screepLOT

*Scree Plot***Description**

Plot eigenvalues (scree plot) or variances histogram.

**Usage**

```

## S4 method for signature 'MultivariateAnalysis'
screepLOT(
  x,
  ...,
  eigenvalues = FALSE,
  cumulative = FALSE,
  labels = TRUE,
  limit = 10,
  col = "grey90",
  border = "grey10",
  col.cumulative = "red",
  lty.cumulative = "solid",
  lwd.cumulative = 2
)

## S4 method for signature 'PCOA'
screepLOT(
  x,
  ...,
  labels = FALSE,
  limit = NULL,
  col = "grey90",
  border = "grey10"
)

```

**Arguments**

x	A <a href="#">CA</a> , <a href="#">MCA</a> or <a href="#">PCA</a> object.
...	Extra parameters to be passed to <a href="#">graphics::barplot()</a> .
eigenvalues	A <a href="#">logical</a> scalar: should the eigenvalues be plotted instead of variance/inertia?
cumulative	A <a href="#">logical</a> scalar: should the cumulative percentages of variance be plotted?

**labels** A [logical](#) scalar: should text labels be drawn on top of bars?  
**limit** An [integer](#) specifying the number of top elements to be displayed.  
**col, border** A [character](#) string specifying the bars infilling and border colors.  
**col.cumulative** A specification for the line color.  
**lty.cumulative** A specification for the line type.  
**lwd.cumulative** A specification for the line width.

### Value

screepplot() is called for its side-effects: it results in a graphic being displayed. Invisibly returns x.

### Author(s)

N. Frerebeau

### See Also

Other plot methods: [biplot\(\)](#), [plot\(\)](#), [viz\\_contributions\(\)](#), [viz\\_individuals\(\)](#), [viz\\_variables\(\)](#)

### Examples

```
## Load data
data("iris")

## Compute principal components analysis
X <- pca(iris, scale = TRUE, sup_quali = "Species")

## Screeplot
screepplot(X)
screepplot(X, cumulative = TRUE)
```

---

subset

*Extract Parts of an Object*

---

### Description

Operators acting on objects to extract parts.

### Usage

```
## S4 method for signature 'CA,ANY,missing'
x[[i]]

## S4 method for signature 'PCA,ANY,missing'
x[[i]]
```

**Arguments**

- x An object from which to extract element(s) or in which to replace element(s).
- i A [character](#) string specifying elements to extract. Any unambiguous substring can be given (see details).

**Details**

If *i* is "data", returns a list with the following elements:

data A [numeric](#) matrix of raw data.

mean A [numeric](#) vector giving the variables means (PCA).

sd A [numeric](#) vector giving the variables standard deviations (PCA).

If *i* is "rows", returns a list with the following elements:

coord A [numeric](#) matrix of rows/individuals coordinates.

cos2 A [numeric](#) matrix of rows/individuals squared cosine.

masses A [numeric](#) vector giving the rows masses/individual weights.

sup A [logical](#) vector specifying whether a point is a supplementary observation or not.

If *i* is "columns", returns a list with the following elements:

coord A [numeric](#) matrix of columns/variables coordinates.

cor A [numeric](#) matrix of correlation between variables and the dimensions (PCA).

cos2 A [numeric](#) matrix of columns/variables squared cosine.

masses A [numeric](#) vector giving the columns masses/variable weights.

sup A [logical](#) vector specifying whether a point is a supplementary observation or not.

If *i* is "eigenvalues", returns a [numeric](#) vector of eigenvalues.

**Value**

A [list](#).

**Author(s)**

N. Frerebeau

**See Also**

Other mutators: [dimnames\(\)](#)

**Examples**

```
## Load data
data("iris")

## Compute principal components analysis
X <- pca(iris, scale = TRUE, sup_row = 8:10, sup_col = 1, sup_quali = "Species")

## Get results for the individuals
X[["rows"]]
```

---

summary

*Object Summaries*


---

**Description**

Provides a summary of the results of a multivariate data analysis.

**Usage**

```
## S4 method for signature 'MultivariateSummary'
as.data.frame(x, row.names = NULL, optional = FALSE, ...)
```

```
## S4 method for signature 'CA'
summary(
  object,
  ...,
  axes = c(1, 2),
  margin = 1,
  active = TRUE,
  sup = TRUE,
  rank = NULL
)
```

```
## S4 method for signature 'PCA'
summary(
  object,
  ...,
  axes = c(1, 2),
  margin = 1,
  active = TRUE,
  sup = TRUE,
  rank = NULL
)
```

**Arguments**

x                    A [MultivariateSummary](#) object.

row.names	A <a href="#">character</a> vector giving the row names for the data frame, or NULL.
optional	A <a href="#">logical</a> scalar: should the names of the variables in the data frame be checked? If FALSE then the names of the variables in the data frame are checked to ensure that they are syntactically valid variable names and are not duplicated.
...	Currently not used.
object	A <a href="#">CA</a> , <a href="#">MCA</a> or <a href="#">PCA</a> object.
axes	A length-two <a href="#">numeric</a> vector giving the dimensions to be summarized.
margin	A length-one <a href="#">numeric</a> vector giving the subscript which the data will be summarized: 1 indicates individuals/rows (the default), 2 indicates variables/columns.
active	A <a href="#">logical</a> scalar: should the active observations be summarized?
sup	A <a href="#">logical</a> scalar: should the supplementary observations be summarized?
rank	An <a href="#">integer</a> value specifying the maximal number of components to be kept in the results. Deprecated, use axes instead.

**Author(s)**

N. Frerebeau

**See Also**

Other summary: [describe\(\)](#), [tidy\(\)](#)

**Examples**

```
## Data from Lebart et al. 2006, p. 170-172
data("colours")

## Compute correspondence analysis
X <- ca(colours)

## Rows summary
summary(X, margin = 1)

## Columns summary
summary(X, margin = 2)
```

---

tidy

*Tidy Coordinates*


---

**Description**

Tidy Coordinates

**Usage**

```

tidy(x, ...)

augment(x, ...)

## S4 method for signature 'MultivariateAnalysis'
augment(x, ..., margin = 1, axes = c(1, 2), principal = TRUE)

## S4 method for signature 'MultivariateAnalysis'
tidy(x, ..., margin = 1, principal = TRUE)

```

**Arguments**

x	A <a href="#">CA</a> , <a href="#">MCA</a> or <a href="#">PCA</a> object.
...	Currently not used.
margin	A length-one <a href="#">numeric</a> vector giving the subscript which the data will be returned: 1 indicates individuals/rows (the default), 2 indicates variables/columns.
axes	A length-two <a href="#">numeric</a> vector giving the dimensions for which to compute results.
principal	A <a href="#">logical</a> scalar: should principal coordinates be returned? If FALSE, standard coordinates are returned.

**Value**

tidy() returns a long [data.frame](#) with the following columns:

label Row/column names of the original data.  
 component Component.  
 supplementary Whether an observation is active or supplementary.  
 coordinate Coordinates.  
 contribution Contributions to the definition of the components.  
 cos2  $\cos^2$ .

augment() returns a wide [data.frame](#) of the row/column coordinates along axes and the following columns:

label Row/column names of the original data.  
 supplementary Whether an observation is active or supplementary.  
 mass Weight/mass of each observation.  
 sum Sum of squared coordinates along axes.  
 contribution Joint contributions to the definition of axes.  
 cos2 Joint  $\cos^2$  along axes.

**Author(s)**

N. Frerebeau

**See Also**

Other summary: [describe\(\)](#), [summary\(\)](#)

**Examples**

```
## Load data
data("iris")

## Compute principal components analysis
X <- pca(iris, scale = TRUE, sup_row = 5:10, sup_quali = "Species")

## Get row principal coordinates
head(get_coordinates(X, margin = 1, principal = TRUE))

## Get row standard coordinates
head(get_coordinates(X, margin = 1, principal = FALSE))

## Tidy principal coordinates
head(tidy(X, margin = 1))
head(tidy(X, margin = 2))

head(augment(X, margin = 1, axes = c(1, 2)))
head(augment(X, margin = 2, axes = c(1, 2)))
```

---

viz\_confidence

*Confidence Ellipses*

---

**Description**

Plots confidence ellipses.

**Usage**

```
viz_confidence(x, y, ...)

wrap_confidence(x, y, ...)

## S4 method for signature 'numeric,numeric'
viz_confidence(
  x,
  y,
  ...,
  group = NULL,
  level = 0.95,
  color = NULL,
  fill = FALSE,
  symbol = FALSE
)
```

```
## S4 method for signature 'MultivariateAnalysis,missing'
viz_confidence(
  x,
  ...,
  group = NULL,
  level = 0.95,
  color = NULL,
  fill = FALSE,
  symbol = FALSE
)

## S4 method for signature 'MultivariateBootstrap,missing'
viz_confidence(
  x,
  ...,
  level = 0.95,
  color = FALSE,
  fill = FALSE,
  symbol = FALSE
)

## S4 method for signature 'PCOA,missing'
viz_confidence(
  x,
  ...,
  axes = c(1, 2),
  group = NULL,
  level = 0.95,
  color = NULL,
  fill = FALSE,
  symbol = FALSE
)

## S4 method for signature 'numeric,numeric'
wrap_confidence(x, y, group = NULL, level = 0.95)

## S4 method for signature 'MultivariateAnalysis,missing'
wrap_confidence(
  x,
  margin = 1,
  axes = c(1, 2),
  group = NULL,
  level = 0.95,
  principal = TRUE
)

## S4 method for signature 'PCOA,missing'
```

```
wrap_confidence(x, axes = c(1, 2), group = NULL, level = 0.95)
```

### Arguments

x, y	A <b>numeric</b> vector. If y is missing, x must be an object from which to wrap observations (a <b>CA</b> , <b>MCA</b> or <b>PCA</b> object).
...	Further <b>graphical parameters</b> to be passed to <code>graphics::polygon()</code> .
group	A vector specifying the group an observation belongs to.
level	A <b>numeric</b> vector specifying the confidence/tolerance level.
color	The colors for borders (will be mapped to group). Ignored if set to FALSE. If NULL, the default color scheme will be used.
fill	The background colors (will be mapped to group). Ignored if set to FALSE.
symbol	A vector of symbols (will be mapped to group). Ignored if set to FALSE.
axes	A length-two <b>numeric</b> vector giving the dimensions for which to compute results.
margin	A length-one <b>numeric</b> vector giving the subscript which the data will be returned: 1 indicates individuals/rows (the default), 2 indicates variables/columns.
principal	A <b>logical</b> scalar: should principal coordinates be used? If FALSE, standard coordinates are returned.

### Value

`wrap_confidence()` returns a **data.frame** of envelope x and y coordinates. An extra column named `group` is added specifying the group an observation belongs to.

`viz_confidence()` is called for its side-effects: it results in a graphic being displayed. Invisibly returns `x`.

### Author(s)

N. Frerebeau

### See Also

Other envelopes: `viz_ellipses()`, `viz_hull()`, `viz_tolerance()`

### Examples

```
## Load data
data("iris")

## Compute principal components analysis
X <- pca(iris, scale = TRUE, sup_quali = "Species")

## Compute confidence ellipse coordinates
conf <- wrap_confidence(X, margin = 1, group = "Species", level = 0.95)

## Plot confidence ellipses
```

```
col <- c("#004488", "#DDAA33", "#BB5566")
viz_rows(X, extra_quali = iris$Species, color = col)
viz_confidence(X, group = iris$Species, color = col, level = 0.95)
```

---

viz\_contributions      *Visualize Contributions and cos<sup>2</sup>*

---

## Description

Plots contributions histogram and  $\cos^2$  scatterplot.

## Usage

```
viz_contributions(x, ...)

viz_cos2(x, ...)

## S4 method for signature 'MultivariateAnalysis'
viz_contributions(
  x,
  ...,
  margin = 2,
  axes = 1,
  sort = TRUE,
  decreasing = TRUE,
  limit = 10,
  horiz = FALSE,
  col = "grey90",
  border = "grey10"
)

## S4 method for signature 'MultivariateAnalysis'
viz_cos2(
  x,
  ...,
  margin = 2,
  axes = 1,
  active = TRUE,
  sup = TRUE,
  sort = TRUE,
  decreasing = TRUE,
  limit = 10,
  horiz = FALSE,
  col = "grey90",
  border = "grey10"
)
```

**Arguments**

x	A CA, MCA or PCA object.
...	Extra parameters to be passed to <code>graphics::barplot()</code> .
margin	A length-one <b>numeric</b> vector giving the subscript which the data will be returned: 1 indicates individuals/rows (the default), 2 indicates variables/columns.
axes	A <b>numeric</b> vector giving the dimensions to be plotted.
sort	A <b>logical</b> scalar: should the data be sorted?
decreasing	A <b>logical</b> scalar: should the sort order be decreasing? Only used if sort is TRUE.
limit	An <b>integer</b> specifying the number of top elements to be displayed.
horiz	A <b>logical</b> scalar: should the bars be drawn horizontally with the first at the bottom?
col, border	A <b>character</b> string specifying the bars infilling and border colors.
active	A <b>logical</b> scalar: should the active observations be plotted?
sup	A <b>logical</b> scalar: should the supplementary observations be plotted?

**Details**

The red dashed line indicates the expected average contribution (variables with a contribution larger than this cutoff can be considered as important in contributing to the component).

**Value**

`viz_contributions()` and `viz_cos2()` are called for their side-effects: they result in a graphic being displayed. Invisibly return x.

**Author(s)**

N. Frerebeau

**See Also**

Other plot methods: `biplot()`, `plot()`, `screeplot()`, `viz_individuals()`, `viz_variables()`

**Examples**

```
## Load data
data("iris")

## Compute principal components analysis
X <- pca(iris, scale = TRUE, sup_quali = "Species")

## Get row contributions
head(get_contributions(X, margin = 1))

## Plot contributions
viz_contributions(X, axes = 1)
```

```
## Plot cos2
viz_cos2(X, axes = 1)
```

---

viz\_ellipses

*Ellipses*

---

## Description

Plots ellipses.

## Usage

```
viz_ellipses(x, y, ...)
```

```
## S4 method for signature 'numeric,numeric'
```

```
viz_ellipses(
  x,
  y,
  ...,
  group = NULL,
  type = c("tolerance", "confidence"),
  level = 0.95,
  color = NULL,
  fill = FALSE,
  symbol = FALSE
)
```

```
## S4 method for signature 'MultivariateAnalysis,missing'
```

```
viz_ellipses(
  x,
  ...,
  group = NULL,
  type = c("tolerance", "confidence"),
  level = 0.95,
  color = NULL,
  fill = FALSE,
  symbol = FALSE
)
```

```
## S4 method for signature 'PCOA,missing'
```

```
viz_ellipses(
  x,
  ...,
  group = NULL,
  type = c("tolerance", "confidence"),
  level = 0.95,
```

```

    color = NULL,
    fill = FALSE,
    symbol = FALSE
  )

```

### Arguments

x, y	A <b>numeric</b> vector. If y is missing, x must be an object from which to wrap observations (a <b>CA</b> , <b>MCA</b> or <b>PCA</b> object).
...	Further <b>graphical parameters</b> to be passed to <code>graphics::polygon()</code> .
group	A vector specifying the group an observation belongs to.
type	A <b>character</b> string specifying the ellipse to draw. It must be one of "tolerance" or "confidence". Any unambiguous substring can be given.
level	A <b>numeric</b> vector specifying the confidence/tolerance level.
color	The colors for borders (will be mapped to group). Ignored if set to FALSE. If NULL, the default color scheme will be used.
fill	The background colors (will be mapped to group). Ignored if set to FALSE.
symbol	A vector of symbols (will be mapped to group). Ignored if set to FALSE.

### Value

`viz_ellipses()` is called for its side-effects: it results in a graphic being displayed. Invisibly returns x.

### Author(s)

N. Frerebeau

### See Also

Other envelopes: `viz_confidence()`, `viz_hull()`, `viz_tolerance()`

### Examples

```

## Load data
data("iris")

## Compute principal components analysis
X <- pca(iris, scale = TRUE, sup_quali = "Species")

## Plot with tolerance ellipses
col <- c("#004488", "#DDAA33", "#BB5566")
viz_rows(X, extra_quali = iris$Species, color = col)
viz_ellipses(
  x = X,
  type = "tolerance",
  level = c(0.68, 0.95),
  group = iris$Species,
  color = col
)

```

viz\_hull

*Convex Hulls***Description**

Plots convex hull of a set of observations.

**Usage**

```
viz_hull(x, y, ...)
```

```
wrap_hull(x, y, ...)
```

```
## S4 method for signature 'numeric,numeric'
```

```
viz_hull(x, y, ..., group = NULL, color = NULL, fill = FALSE, symbol = FALSE)
```

```
## S4 method for signature 'MultivariateAnalysis,missing'
```

```
viz_hull(x, ..., group = NULL, color = NULL, fill = FALSE, symbol = FALSE)
```

```
## S4 method for signature 'MultivariateBootstrap,missing'
```

```
viz_hull(x, ..., color = FALSE, fill = FALSE, symbol = FALSE)
```

```
## S4 method for signature 'PCOA,missing'
```

```
viz_hull(x, ..., group = NULL, color = FALSE, fill = FALSE, symbol = FALSE)
```

```
## S4 method for signature 'numeric,numeric'
```

```
wrap_hull(x, y, group = NULL)
```

```
## S4 method for signature 'MultivariateAnalysis,missing'
```

```
wrap_hull(x, margin = 1, axes = c(1, 2), group = NULL, principal = TRUE)
```

```
## S4 method for signature 'PCOA,missing'
```

```
wrap_hull(x, axes = c(1, 2), group = NULL)
```

**Arguments**

`x, y` A [numeric](#) vector. If `y` is missing, `x` must be an object from which to wrap observations (a [CA](#), [MCA](#) or [PCA](#) object).

`...` Further [graphical parameters](#) to be passed to [graphics::polygon\(\)](#).

`group` A vector specifying the group an observation belongs to.

`color` The colors for borders (will be mapped to `group`). Ignored if set to `FALSE`. If `NULL`, the default color scheme will be used.

`fill` The background colors (will be mapped to `group`). Ignored if set to `FALSE`.

`symbol` A vector of symbols (will be mapped to `group`). Ignored if set to `FALSE`.

`margin` A length-one [numeric](#) vector giving the subscript which the data will be returned: 1 indicates individuals/rows (the default), 2 indicates variables/columns.

axes	A length-two <a href="#">numeric</a> vector giving the dimensions for which to compute results.
principal	A <a href="#">logical</a> scalar: should principal coordinates be used? If FALSE, standard coordinates are returned.

### Value

`wrap_hull()` returns a [data.frame](#) of envelope x and y coordinates. An extra column named `group` is added specifying the group an observation belongs to.

`viz_hull()` is called for its side-effects: it results in a graphic being displayed. Invisibly returns `x`.

### Author(s)

N. Frerebeau

### See Also

Other envelopes: [viz\\_confidence\(\)](#), [viz\\_ellipses\(\)](#), [viz\\_tolerance\(\)](#)

### Examples

```
## Load data
data("iris")

## Compute principal components analysis
X <- pca(iris, scale = TRUE, sup_quali = "Species")

## Compute convex hull coordinates
hulls <- wrap_hull(X, margin = 1, group = "Species")

## Plot convex hulls
col <- c("#004488", "#DDAA33", "#BB5566")
viz_rows(X, extra_quali = iris$Species, color = col)
viz_hull(X, group = iris$Species, color = col)
```

---

viz\_individuals

*Visualize Individuals Factor Map*

---

### Description

Plots row/individual principal coordinates.

**Usage**

```
viz_individuals(x, ...)  
  
viz_rows(x, ...)  
  
## S4 method for signature 'MultivariateAnalysis'  
viz_rows(  
  x,  
  ...,  
  axes = c(1, 2),  
  active = TRUE,  
  sup = TRUE,  
  labels = FALSE,  
  extra_quali = NULL,  
  extra_quanti = NULL,  
  ellipse = NULL,  
  hull = NULL,  
  color = NULL,  
  fill = FALSE,  
  symbol = FALSE,  
  size = c(1, 6),  
  xlim = NULL,  
  ylim = NULL,  
  main = NULL,  
  sub = NULL,  
  panel.first = NULL,  
  panel.last = NULL,  
  legend = list(x = "topleft")  
)  
  
## S4 method for signature 'BootstrapCA'  
viz_rows(  
  x,  
  ...,  
  axes = c(1, 2),  
  color = FALSE,  
  fill = FALSE,  
  symbol = FALSE,  
  legend = NULL  
)  
  
## S4 method for signature 'PCA'  
viz_individuals(  
  x,  
  ...,  
  axes = c(1, 2),  
  active = TRUE,  
  sup = TRUE,
```

```

labels = FALSE,
extra_quali = NULL,
extra_quant_i = NULL,
ellipse = NULL,
hull = NULL,
color = NULL,
fill = FALSE,
symbol = FALSE,
size = c(1, 6),
xlim = NULL,
ylim = NULL,
main = NULL,
sub = NULL,
panel.first = NULL,
panel.last = NULL,
legend = list(x = "topleft")
)

```

### Arguments

x	A <a href="#">CA</a> , <a href="#">MCA</a> or <a href="#">PCA</a> object.
...	Further <a href="#">graphical parameters</a> .
axes	A length-two <a href="#">numeric</a> vector giving the dimensions to be plotted.
active	A <a href="#">logical</a> scalar: should the active observations be plotted?
sup	A <a href="#">logical</a> scalar: should the supplementary observations be plotted?
labels	A <a href="#">logical</a> scalar: should labels be drawn? Labeling a large number of points can be computationally expensive and make the graph difficult to read. A selection of points to label can be provided using a <code>list</code> of two named elements, <code>filter</code> (a string specifying how to filter the labels to be drawn) and <code>n</code> (an integer specifying the number of labels to be drawn). See examples below.
extra_quali	An optional vector of qualitative data for aesthetics mapping.
extra_quant_i	An optional vector of quantitative data for aesthetics mapping. If a single <a href="#">character</a> string is passed, it must be one of "observation", "mass", "sum", "contribution" or "cos2" (see <a href="#">augment()</a> ).
ellipse	A <a href="#">list</a> of additional arguments to be passed to <a href="#">viz_ellipses()</a> ; names of the list are used as argument names. If <code>NULL</code> , no ellipse are displayed.
hull	A <a href="#">logical</a> scalar: should convex hulls be displayed?
color	The colors for lines and points (will be mapped to <code>extra_quant_i</code> or <code>extra_quali</code> ; if both are set, the latter has priority). Ignored if set to <code>FALSE</code> . If <code>NULL</code> , the default color scheme will be used.
fill	The background colors for points (will be mapped to <code>extra_quant_i</code> or <code>extra_quali</code> ; if both are set, the latter has priority). Ignored if set to <code>FALSE</code> .
symbol	A vector of plotting characters or symbols (will be mapped to <code>extra_quali</code> ). This can either be a single character or an integer code for one of a set of graphics symbols. If <code>symbol</code> is a named vector, then the symbols will be associated with their name within <code>extra_quali</code> . Ignored if set to <code>FALSE</code> .

size	A length-two <b>numeric</b> vector giving range of possible sizes (greater than 0; will be mapped to <code>extra_quanti</code> ). Ignored if set to <code>FALSE</code> .
xlim	A length-two <b>numeric</b> vector giving the x limits of the plot. The default value, <code>NULL</code> , indicates that the range of the <b>finite</b> values to be plotted should be used.
ylim	A length-two <b>numeric</b> vector giving the y limits of the plot. The default value, <code>NULL</code> , indicates that the range of the <b>finite</b> values to be plotted should be used.
main	A <b>character</b> string giving a main title for the plot.
sub	A <b>character</b> string giving a subtitle for the plot.
panel.first	An expression to be evaluated after the plot axes are set up but before any plotting takes place. This can be useful for drawing background grids.
panel.last	An expression to be evaluated after plotting has taken place but before the axes, title and box are added.
legend	A <b>list</b> of additional arguments to be passed to <code>graphics::legend()</code> ; names of the list are used as argument names. If <code>NULL</code> , no legend is displayed.

**Value**

`viz_*`() is called for its side-effects: it results in a graphic being displayed. Invisibly returns `x`.

**Author(s)**

N. Frerebeau

**See Also**

Other plot methods: `biplot()`, `plot()`, `screepplot()`, `viz_contributions()`, `viz_variables()`

**Examples**

```
## Load data
data("iris")

## Compute principal components analysis
X <- pca(iris, scale = TRUE, sup_quali = "Species")

## Plot individuals
viz_individuals(X, panel.last = graphics::grid())

## Labels of the 10 individuals with highest cos2
viz_individuals(X, labels = list(filter = "cos2", n = 10))

## Plot variables
viz_variables(X, panel.last = graphics::grid())

## Graphical parameters
## Continuous values
viz_individuals(X, extra_quanti = iris$Petal.Length, symbol = 16, size = c(1, 2))
viz_individuals(X, extra_quanti = iris$Petal.Length, symbol = 16, size = c(1, 2),
                color = grDevices::hcl.colors(12, "RdPu"))
```

```

viz_variables(X, extra_quanti = "contribution",
             color = grDevices::hcl.colors(12, "BluGrn", rev = TRUE),
             size = c(0, 1))

## Discrete values
viz_individuals(X, extra_quali = iris$Species, symbol = 21:23)
viz_individuals(X, extra_quali = iris$Species, symbol = 21:23,
              fill = c("#004488", "#DDAA33", "#BB5566"),
              color = "black")

viz_variables(X, extra_quali = c("Petal", "Petal", "Sepal", "Sepal"),
             color = c("#EE7733", "#0077BB"),
             symbol = c(1, 3))

```

---

viz_tolerance	<i>Tolerance Ellipses</i>
---------------	---------------------------

---

## Description

Plots tolerance ellipses.

## Usage

```
viz_tolerance(x, y, ...)
```

```
wrap_tolerance(x, y, ...)
```

```
## S4 method for signature 'numeric,numeric'
```

```

viz_tolerance(
  x,
  y,
  ...,
  group = NULL,
  level = 0.95,
  color = NULL,
  fill = FALSE,
  symbol = FALSE
)

```

```
## S4 method for signature 'MultivariateAnalysis,missing'
```

```

viz_tolerance(
  x,
  ...,
  group = NULL,
  level = 0.95,
  color = NULL,
  fill = FALSE,

```

```

    symbol = FALSE
  )

## S4 method for signature 'MultivariateBootstrap,missing'
viz_tolerance(
  x,
  ...,
  level = 0.95,
  color = FALSE,
  fill = FALSE,
  symbol = FALSE
)

## S4 method for signature 'PCOA,missing'
viz_tolerance(
  x,
  ...,
  group = NULL,
  level = 0.95,
  color = NULL,
  fill = FALSE,
  symbol = FALSE
)

## S4 method for signature 'numeric,numeric'
wrap_tolerance(x, y, group = NULL, level = 0.95)

## S4 method for signature 'MultivariateAnalysis,missing'
wrap_tolerance(
  x,
  margin = 1,
  axes = c(1, 2),
  group = NULL,
  level = 0.95,
  principal = TRUE
)

## S4 method for signature 'PCOA,missing'
wrap_tolerance(x, axes = c(1, 2), group = NULL, level = 0.95)

```

### Arguments

x, y	A <a href="#">numeric</a> vector. If y is missing, x must be an object from which to wrap observations (a <a href="#">CA</a> , <a href="#">MCA</a> or <a href="#">PCA</a> object).
...	Further <a href="#">graphical parameters</a> to be passed to <a href="#">graphics::polygon()</a> .
group	A vector specifying the group an observation belongs to.
level	A <a href="#">numeric</a> vector specifying the confidence/tolerance level.

color	The colors for borders (will be mapped to group). Ignored if set to FALSE. If NULL, the default color scheme will be used.
fill	The background colors (will be mapped to group). Ignored if set to FALSE.
symbol	A vector of symbols (will be mapped to group). Ignored if set to FALSE.
margin	A length-one <b>numeric</b> vector giving the subscript which the data will be returned: 1 indicates individuals/rows (the default), 2 indicates variables/columns.
axes	A length-two <b>numeric</b> vector giving the dimensions for which to compute results.
principal	A <b>logical</b> scalar: should principal coordinates be used? If FALSE, standard coordinates are returned.

### Value

wrap\_tolerance() returns a **data.frame** of envelope x and y coordinates. An extra column named group is added specifying the group an observation belongs to.

viz\_tolerance() is called for its side-effects: it results in a graphic being displayed. Invisibly returns x.

### Author(s)

N. Frerebeau

### See Also

Other envelopes: [viz\\_confidence\(\)](#), [viz\\_ellipses\(\)](#), [viz\\_hull\(\)](#)

### Examples

```
## Load data
data("iris")

## Compute principal components analysis
X <- pca(iris, scale = TRUE, sup_quali = "Species")

## Compute tolerance ellipse coordinates
conf <- wrap_confidence(X, margin = 1, group = "Species", level = 0.95)

## Plot tolerance ellipses
col <- c("#004488", "#DDAA33", "#BB5566")
viz_rows(X, extra_quali = iris$Species, color = col)
viz_tolerance(X, group = iris$Species, color = col, level = 0.95)
```

---

`viz_variables`*Visualize Variables Factor Map*

---

**Description**

Plots column/variable principal coordinates.

**Usage**

```
viz_variables(x, ...)
```

```
viz_columns(x, ...)
```

```
## S4 method for signature 'MultivariateAnalysis'
```

```
viz_columns(  
  x,  
  ...,  
  axes = c(1, 2),  
  active = TRUE,  
  sup = TRUE,  
  labels = FALSE,  
  extra_quali = NULL,  
  extra_quanti = NULL,  
  color = NULL,  
  fill = FALSE,  
  symbol = FALSE,  
  size = c(1, 6),  
  xlim = NULL,  
  ylim = NULL,  
  main = NULL,  
  sub = NULL,  
  panel.first = NULL,  
  panel.last = NULL,  
  legend = list(x = "topleft")  
)
```

```
## S4 method for signature 'MultivariateBootstrap'
```

```
viz_columns(  
  x,  
  ...,  
  axes = c(1, 2),  
  color = FALSE,  
  fill = FALSE,  
  symbol = FALSE,  
  legend = NULL  
)
```

```
## S4 method for signature 'PCA'  
viz_variables(  
  x,  
  ...,  
  axes = c(1, 2),  
  active = TRUE,  
  sup = TRUE,  
  labels = list(filter = "contribution", n = 10),  
  extra_quali = NULL,  
  extra_quanti = NULL,  
  color = NULL,  
  symbol = NULL,  
  size = 1,  
  xlim = NULL,  
  ylim = NULL,  
  main = NULL,  
  sub = NULL,  
  panel.first = NULL,  
  panel.last = NULL,  
  legend = list(x = "topleft")  
)
```

```
## S4 method for signature 'CA'  
viz_variables(  
  x,  
  ...,  
  axes = c(1, 2),  
  active = TRUE,  
  sup = TRUE,  
  labels = FALSE,  
  extra_quali = NULL,  
  extra_quanti = NULL,  
  color = NULL,  
  fill = FALSE,  
  symbol = FALSE,  
  size = c(1, 6),  
  xlim = NULL,  
  ylim = NULL,  
  main = NULL,  
  sub = NULL,  
  panel.first = NULL,  
  panel.last = NULL,  
  legend = list(x = "topleft")  
)
```

```
## S4 method for signature 'BootstrapPCA'  
viz_variables(  
  x,
```

```

...,
axes = c(1, 2),
color = FALSE,
fill = FALSE,
symbol = FALSE,
legend = NULL
)

```

## Arguments

x	A <a href="#">CA</a> , <a href="#">MCA</a> or <a href="#">PCA</a> object.
...	Further <a href="#">graphical parameters</a> .
axes	A length-two <a href="#">numeric</a> vector giving the dimensions to be plotted.
active	A <a href="#">logical</a> scalar: should the active observations be plotted?
sup	A <a href="#">logical</a> scalar: should the supplementary observations be plotted?
labels	A <a href="#">logical</a> scalar: should labels be drawn? Labeling a large number of points can be computationally expensive and make the graph difficult to read. A selection of points to label can be provided using a <code>list</code> of two named elements, <code>filter</code> (a string specifying how to filter the labels to be drawn) and <code>n</code> (an integer specifying the number of labels to be drawn). See examples below.
extra_quali	An optional vector of qualitative data for aesthetics mapping.
extra_quant	An optional vector of quantitative data for aesthetics mapping. If a single <a href="#">character</a> string is passed, it must be one of "observation", "mass", "sum", "contribution" or "cos2" (see <a href="#">augment()</a> ).
color	The colors for lines and points (will be mapped to <code>extra_quant</code> or <code>extra_quali</code> ; if both are set, the latter has priority). Ignored if set to <code>FALSE</code> . If <code>NULL</code> , the default color scheme will be used.
fill	The background colors for points (will be mapped to <code>extra_quant</code> or <code>extra_quali</code> ; if both are set, the latter has priority). Ignored if set to <code>FALSE</code> .
symbol	A vector of plotting characters or symbols (will be mapped to <code>extra_quali</code> ). This can either be a single character or an integer code for one of a set of graphics symbols. If <code>symbol</code> is a named vector, then the symbols will be associated with their name within <code>extra_quali</code> . Ignored if set to <code>FALSE</code> .
size	A length-two <a href="#">numeric</a> vector giving range of possible sizes (greater than 0; will be mapped to <code>extra_quant</code> ). Ignored if set to <code>FALSE</code> .
xlim	A length-two <a href="#">numeric</a> vector giving the x limits of the plot. The default value, <code>NULL</code> , indicates that the range of the <a href="#">finite</a> values to be plotted should be used.
ylim	A length-two <a href="#">numeric</a> vector giving the y limits of the plot. The default value, <code>NULL</code> , indicates that the range of the <a href="#">finite</a> values to be plotted should be used.
main	A <a href="#">character</a> string giving a main title for the plot.
sub	A <a href="#">character</a> string giving a subtitle for the plot.
panel.first	An expression to be evaluated after the plot axes are set up but before any plotting takes place. This can be useful for drawing background grids.

panel.last	An expression to be evaluated after plotting has taken place but before the axes, title and box are added.
legend	A <a href="#">list</a> of additional arguments to be passed to <code>graphics::legend()</code> ; names of the list are used as argument names. If NULL, no legend is displayed.

**Value**

`viz_*()` is called for its side-effects: it results in a graphic being displayed. Invisibly returns `x`.

**Author(s)**

N. Frerebeau

**See Also**

Other plot methods: [biplot\(\)](#), [plot\(\)](#), [screplot\(\)](#), [viz\\_contributions\(\)](#), [viz\\_individuals\(\)](#)

**Examples**

```
## Load data
data("iris")

## Compute principal components analysis
X <- pca(iris, scale = TRUE, sup_quali = "Species")

## Plot individuals
viz_individuals(X, panel.last = graphics::grid())

## Labels of the 10 individuals with highest cos2
viz_individuals(X, labels = list(filter = "cos2", n = 10))

## Plot variables
viz_variables(X, panel.last = graphics::grid())

## Graphical parameters
## Continuous values
viz_individuals(X, extra_quanti = iris$Petal.Length, symbol = 16, size = c(1, 2))
viz_individuals(X, extra_quanti = iris$Petal.Length, symbol = 16, size = c(1, 2),
  color = grDevices::hcl.colors(12, "RdPu"))

viz_variables(X, extra_quanti = "contribution",
  color = grDevices::hcl.colors(12, "BluGrn", rev = TRUE),
  size = c(0, 1))

## Discrete values
viz_individuals(X, extra_quali = iris$Species, symbol = 21:23)
viz_individuals(X, extra_quali = iris$Species, symbol = 21:23,
  fill = c("#004488", "#DDAA33", "#BB5566"),
  color = "black")

viz_variables(X, extra_quali = c("Petal", "Petal", "Sepal", "Sepal"),
  color = c("#EE7733", "#0077BB"),
```

```
symbol = c(1, 3))
```

# Index

- \* **datasets**
  - benthos, 3
  - colours, 13
  - countries, 13
- \* **envelopes**
  - viz\_confidence, 35
  - viz\_ellipses, 40
  - viz\_hull, 42
  - viz\_tolerance, 47
- \* **getters**
  - export, 15
  - get\_contributions, 16
  - get\_coordinates, 18
  - get\_data, 19
  - get\_eigenvalues, 20
- \* **multivariate analysis**
  - ca, 10
  - mca, 21
  - pca, 22
  - pcoa, 24
  - predict, 28
- \* **mutators**
  - dimnames, 15
  - subset, 30
- \* **plot methods**
  - biplot, 3
  - plot, 26
  - screeplot, 29
  - viz\_contributions, 38
  - viz\_individuals, 43
  - viz\_variables, 50
- \* **resampling methods**
  - bootstrap, 7
- \* **summary**
  - describe, 14
  - summary, 32
  - tidy, 33
- \* **tools**
  - burt, 9
  - cdt, 11
  - [[, CA, ANY, missing-method (subset), 30
  - [[, PCA, ANY, missing-method (subset), 30
  - array, 18
  - as.data.frame, MultivariateSummary-method (summary), 32
  - augment (tidy), 33
  - augment(), 27, 45, 52
  - augment, MultivariateAnalysis-method (tidy), 33
  - augment-method (tidy), 33
  - benthos, 3, 13
  - biplot, 3, 27, 30, 39, 46, 53
  - biplot, CA-method (biplot), 3
  - biplot, PCA-method (biplot), 3
  - bootstrap, 7
  - bootstrap, CA-method (bootstrap), 7
  - bootstrap, PCA-method (bootstrap), 7
  - BootstrapCA, 7
  - BootstrapPCA, 7
  - burt, 9, 12
  - burt, data.frame-method (burt), 9
  - burt-method (burt), 9
  - CA, 4, 7, 10, 14–20, 28, 29, 33, 34, 37, 39, 41, 42, 45, 48, 52
  - ca, 10, 22, 24, 25, 28
  - ca, data.frame-method (ca), 10
  - ca, matrix-method (ca), 10
  - ca-method (ca), 10
  - cat(), 14
  - cdt, 9, 11
  - cdt(), 22
  - cdt, data.frame-method (cdt), 11
  - cdt, matrix-method (cdt), 11
  - cdt-method (cdt), 11
  - character, 5, 15–18, 27, 30, 31, 33, 39, 41, 45, 46, 52

- colnames, MultivariateAnalysis-method (dimnames), 15
- colours, 3, 13, 13
- countries, 3, 13, 13
- data.frame, 3, 9, 10, 12, 13, 17–19, 21–23, 28, 34, 37, 43, 49
- describe, 14, 33, 35
- describe, CA-method (describe), 14
- describe, PCA-method (describe), 14
- dim, MultivariateAnalysis-method (dimnames), 15
- dimnames, 15, 31
- dimnames, MultivariateAnalysis-method (dimnames), 15
- distance structure, 24
- export, 15, 17, 19–21
- export, MultivariateAnalysis-method (export), 15
- export, PCA-method (export), 15
- export-method (export), 15
- factor(), 9, 12
- finite, 5, 27, 46, 52
- get\_contributions, 16, 16, 19–21
- get\_contributions, MultivariateAnalysis-method (get\_contributions), 16
- get\_contributions-method (get\_contributions), 16
- get\_coordinates, 16, 17, 18, 20, 21
- get\_coordinates, MultivariateAnalysis-method (get\_coordinates), 18
- get\_coordinates, PCA-method (get\_coordinates), 18
- get\_coordinates-method (get\_coordinates), 18
- get\_correlations (get\_contributions), 16
- get\_correlations, PCA-method (get\_contributions), 16
- get\_correlations-method (get\_contributions), 16
- get\_cos2 (get\_contributions), 16
- get\_cos2, MultivariateAnalysis-method (get\_contributions), 16
- get\_cos2-method (get\_contributions), 16
- get\_data, 16, 17, 19, 19, 21
- get\_data, MultivariateAnalysis-method (get\_data), 19
- get\_data-method (get\_data), 19
- get\_distances (get\_eigenvalues), 20
- get\_distances, MultivariateAnalysis-method (get\_eigenvalues), 20
- get\_distances-method (get\_eigenvalues), 20
- get\_eigenvalues, 16, 17, 19, 20, 20
- get\_eigenvalues, MultivariateAnalysis-method (get\_eigenvalues), 20
- get\_eigenvalues, PCA-method (get\_eigenvalues), 20
- get\_eigenvalues-method (get\_eigenvalues), 20
- get\_inertia (get\_eigenvalues), 20
- get\_inertia, MultivariateAnalysis-method (get\_eigenvalues), 20
- get\_inertia-method (get\_eigenvalues), 20
- get\_replications (get\_coordinates), 18
- get\_replications, BootstrapPCA-method (get\_coordinates), 18
- get\_replications, MultivariateBootstrap-method (get\_coordinates), 18
- get\_replications-method (get\_coordinates), 18
- get\_variance (get\_eigenvalues), 20
- get\_variance, MultivariateAnalysis-method (get\_eigenvalues), 20
- get\_variance-method (get\_eigenvalues), 20
- graphical parameters, 26, 37, 41, 42, 45, 48, 52
- graphics::barplot(), 29, 39
- graphics::legend(), 5, 27, 46, 53
- graphics::polygon(), 37, 41, 42, 48
- integer, 7, 10, 20, 22–24, 30, 33, 39
- list, 5, 27, 31, 45, 46, 53
- logical, 5, 9, 10, 12, 15, 18, 22, 23, 26, 27, 29–31, 33, 34, 37, 39, 43, 45, 49, 52
- matrix, 9, 10, 22, 23, 28
- MCA, 4, 14, 16–20, 22, 29, 33, 34, 37, 39, 41, 42, 45, 48, 52
- mca, 11, 21, 24, 25, 28
- mca, data.frame-method (mca), 21
- mca, matrix-method (mca), 21
- mca-method (mca), 21
- MultivariateSummary, 32

- numeric, [4](#), [5](#), [17](#), [18](#), [20](#), [21](#), [23](#), [26–28](#), [31](#), [33](#), [34](#), [37](#), [39](#), [41–43](#), [45](#), [46](#), [48](#), [49](#), [52](#)
- PCA, [4](#), [7](#), [14–20](#), [23](#), [28](#), [29](#), [33](#), [34](#), [37](#), [39](#), [41](#), [42](#), [45](#), [48](#), [52](#)
- pca, [11](#), [22](#), [22](#), [25](#), [28](#)
- pca, data.frame-method (pca), [22](#)
- pca, matrix-method (pca), [22](#)
- pca-method (pca), [22](#)
- PCOA, [25](#)
- pcoa, [11](#), [22](#), [24](#), [24](#), [28](#)
- pcoa, dist-method (pcoa), [24](#)
- pcoa-method (pcoa), [24](#)
- plot, [6](#), [26](#), [30](#), [39](#), [46](#), [53](#)
- plot, PCOA, missing-method (plot), [26](#)
- predict, [11](#), [22](#), [24](#), [25](#), [28](#)
- predict, CA-method (predict), [28](#)
- predict, MCA-method (predict), [28](#)
- predict, PCA-method (predict), [28](#)
- rownames, MultivariateAnalysis-method (dimnames), [15](#)
- screepLOT, [6](#), [27](#), [29](#), [39](#), [46](#), [53](#)
- screepLOT, MultivariateAnalysis-method (screepLOT), [29](#)
- screepLOT, PCOA-method (screepLOT), [29](#)
- screepLOT-method (screepLOT), [29](#)
- stats::cmdscale(), [25](#)
- subset, [15](#), [30](#)
- summary, [14](#), [32](#), [35](#)
- summary, CA-method (summary), [32](#)
- summary, PCA-method (summary), [32](#)
- svd(), [11](#), [22](#), [24](#)
- tidy, [14](#), [33](#), [33](#)
- tidy, MultivariateAnalysis-method (tidy), [33](#)
- tidy-method (tidy), [33](#)
- utils::write.csv(), [16](#)
- utils::zip(), [16](#)
- viz\_columns (viz\_variables), [50](#)
- viz\_columns, MultivariateAnalysis-method (viz\_variables), [50](#)
- viz\_columns, MultivariateBootstrap-method (viz\_variables), [50](#)
- viz\_columns-method (viz\_variables), [50](#)
- viz\_confidence, [35](#), [41](#), [43](#), [49](#)
- viz\_confidence, MultivariateAnalysis, missing-method (viz\_confidence), [35](#)
- viz\_confidence, MultivariateBootstrap, missing-method (viz\_confidence), [35](#)
- viz\_confidence, numeric, numeric-method (viz\_confidence), [35](#)
- viz\_confidence, PCOA, missing-method (viz\_confidence), [35](#)
- viz\_confidence-method (viz\_confidence), [35](#)
- viz\_contributions, [6](#), [27](#), [30](#), [38](#), [46](#), [53](#)
- viz\_contributions, MultivariateAnalysis-method (viz\_contributions), [38](#)
- viz\_contributions-method (viz\_contributions), [38](#)
- viz\_cos2 (viz\_contributions), [38](#)
- viz\_cos2, MultivariateAnalysis-method (viz\_contributions), [38](#)
- viz\_cos2-method (viz\_contributions), [38](#)
- viz\_ellipses, [37](#), [40](#), [43](#), [49](#)
- viz\_ellipses(), [27](#), [45](#)
- viz\_ellipses, MultivariateAnalysis, missing-method (viz\_ellipses), [40](#)
- viz\_ellipses, numeric, numeric-method (viz\_ellipses), [40](#)
- viz\_ellipses, PCOA, missing-method (viz\_ellipses), [40](#)
- viz\_ellipses-method (viz\_ellipses), [40](#)
- viz\_hull, [37](#), [41](#), [42](#), [49](#)
- viz\_hull, MultivariateAnalysis, missing-method (viz\_hull), [42](#)
- viz\_hull, MultivariateBootstrap, missing-method (viz\_hull), [42](#)
- viz\_hull, numeric, numeric-method (viz\_hull), [42](#)
- viz\_hull, PCOA, missing-method (viz\_hull), [42](#)
- viz\_hull-method (viz\_hull), [42](#)
- viz\_individuals, [6](#), [27](#), [30](#), [39](#), [43](#), [53](#)
- viz\_individuals, PCA-method (viz\_individuals), [43](#)
- viz\_individuals-method (viz\_individuals), [43](#)
- viz\_rows (viz\_individuals), [43](#)
- viz\_rows, BootstrapCA-method (viz\_individuals), [43](#)
- viz\_rows, MultivariateAnalysis-method

- (viz\_individuals), 43
- viz\_rows-method (viz\_individuals), 43
- viz\_tolerance, 37, 41, 43, 47
- viz\_tolerance, MultivariateAnalysis, missing-method (viz\_tolerance), 47
- viz\_tolerance, MultivariateBootstrap, missing-method (viz\_tolerance), 47
- viz\_tolerance, numeric, numeric-method (viz\_tolerance), 47
- viz\_tolerance, PCOA, missing-method (viz\_tolerance), 47
- viz\_tolerance-method (viz\_tolerance), 47
- viz\_variables, 6, 27, 30, 39, 46, 50
- viz\_variables, BootstrapPCA-method (viz\_variables), 50
- viz\_variables, CA-method (viz\_variables), 50
- viz\_variables, PCA-method (viz\_variables), 50
- viz\_variables-method (viz\_variables), 50
  
- wrap\_confidence (viz\_confidence), 35
- wrap\_confidence, MultivariateAnalysis, missing-method (viz\_confidence), 35
- wrap\_confidence, numeric, numeric-method (viz\_confidence), 35
- wrap\_confidence, PCOA, missing-method (viz\_confidence), 35
- wrap\_confidence-method (viz\_confidence), 35
- wrap\_hull (viz\_hull), 42
- wrap\_hull, MultivariateAnalysis, missing-method (viz\_hull), 42
- wrap\_hull, numeric, numeric-method (viz\_hull), 42
- wrap\_hull, PCOA, missing-method (viz\_hull), 42
- wrap\_hull-method (viz\_hull), 42
- wrap\_tolerance (viz\_tolerance), 47
- wrap\_tolerance, MultivariateAnalysis, missing-method (viz\_tolerance), 47
- wrap\_tolerance, numeric, numeric-method (viz\_tolerance), 47
- wrap\_tolerance, PCOA, missing-method (viz\_tolerance), 47
- wrap\_tolerance-method (viz\_tolerance), 47