

Package ‘distinctiveness’

May 8, 2026

Type Package

Title Distinctiveness Centrality

Version 1.0.1

Description Calculates Distinctiveness Centrality in social networks.
For formulas and descriptions, see Fronzetti Colladon and Naldi (2020) <[doi:10.1371/journal.pone.0233276](https://doi.org/10.1371/journal.pone.0233276)>.

License MIT + file LICENSE

URL <https://github.com/iandrea/c/distinctiveness-R>,
<https://journals.plos.org/plosone/article?id=10.1371/journal.pone.0233276>

Depends R (>= 3.5.0)

Imports igraph

Encoding UTF-8

RoxygenNote 7.2.3

NeedsCompilation no

Author Andrea Fronzetti Colladon [aut, cre],
Luis Maas [aut]

Maintainer Andrea Fronzetti Colladon <andrea.fronzeticolladon@unipg.it>

Repository CRAN

Date/Publication 2023-10-15 15:10:02 UTC

Contents

distinctiveness	2
Index	3

distinctiveness	<i>The main function; oversees the calculations of Distinctiveness Centrality</i>
-----------------	---

Description

The main function; oversees the calculations of Distinctiveness Centrality

Usage

```
distinctiveness(
  G,
  alpha = 1,
  normalize = FALSE,
  measures = c("D1", "D2", "D3", "D4", "D5")
)
```

Arguments

G	the given graph
alpha	the given exponent for penalizing connections to highly connected nodes
normalize	when TRUE, the function normalizes output metrics to allow for comparison with other graphs. Defaults to FALSE
measures	the measures of Distinctiveness Centrality to be computed

Value

a data frame containing the specified calculated measures of Distinctiveness Centrality for the given graph

Examples

```
g <- igraph::erdos.renyi.game(20, 50, type = "gnm", directed = FALSE)
plot(g)
distinctiveness(g)
distinctiveness(g, alpha = list(2, 1, 3, 2, 4), measures = c("D1", "D3", "D4"))

g_dir <- igraph::erdos.renyi.game(20, 50, type = "gnm", directed = TRUE)
plot(g_dir)
distinctiveness(g_dir)
distinctiveness(g_dir, alpha = 2, normalize = TRUE, measures = c("D2", "D5"))
```

Index

distinctiveness, [2](#)