

# Package ‘effectsizescr’

May 8, 2026

**Type** Package

**Title** Indices for Single-Case Research

**Version** 0.1.0

**Author** Isabella Giammusso

**Maintainer** Isabella Giammusso <isabella.giammusso@unipa.it>

**Description** Parametric and nonparametric statistics for single-case design. Regarding nonparametric statistics, the index suggested by Parker, Vannest, Davis and Sauber (2011) <[doi:10.1016/j.beth.2010.08.006](https://doi.org/10.1016/j.beth.2010.08.006)> was included. It combines both nonoverlap and trend to estimate the effect size of a treatment in a single case design.

**Depends** R (>= 2.15)

**Imports** Kendall

**License** MIT + file LICENSE

**Encoding** UTF-8

**LazyData** true

**NeedsCompilation** no

**Repository** CRAN

**Date/Publication** 2018-04-16 14:04:35 UTC

## Contents

TAU . . . . .	2
<b>Index</b>	<b>3</b>

---

TAU

*Parker's TAU-U*

---

### Description

Nonoverlap and trend for single case research: the TAU-U function of Parker et al. (2011).

### Usage

```
TAU(data1, nameTime = "TIME", namePhase = "DUMMYPHASE",  
nameDV = "DV", Aphase = 0, Bphase = 1)
```

### Arguments

data1	a matrix or a dataframe with time,outcome and phases columns
nameTime	the name of the time column
namePhase	the name of the phase column
nameDV	the name of the dependent variable
Aphase	how phase A was coded in the phases column
Bphase	how phase B was coded in the phases column

### Value

A list including partition matrix, full matrix and TAU-U analysis

### References

Parker, R. I., Vannest, K. J., Davis, J. L., & Sauber, S. B. (2011). Combining nonoverlap and trend for single-case research: Tau-U. *Behavior Therapy*, 42(2), 284-299, doi: 10.1016/j.beth.2010.08.006

### Examples

```
data=cbind(rnorm(16),1:16,c(rep(0,8),rep(1,8)))  
colnames(data)=c("DV","TIME","PHASE")  
TAU(data1=data,nameTime = "TIME",namePhase = "PHASE",  
nameDV = "DV")
```

# Index

TAU, [2](#)