

Package ‘energymethod’

May 8, 2026

Type Package

Title Two-Sample Test of many Functional Means using the Energy Method

Version 1.1

Date 2025-04-09

Maintainer David Colin Decker <d.colin.decker@gmail.com>

Description Given two samples of size n_1 and n_2 from a data set where each sample consists of K functional observations (channels), each recorded on T grid points, the function `energy_method` implements a hypothesis test of equality of channel-wise mean at each channel using the bootstrapped distribution of maximum energy to control family wise error. The function `energy_method_complex` accomodates complex valued functional observations.

License GPL-3

Imports Rcpp ($\geq 1.0.14$)

LinkingTo Rcpp, RcppArmadillo

RoxygenNote 7.3.2

NeedsCompilation yes

Author David Colin Decker [aut, cre]

Repository CRAN

Date/Publication 2025-04-20 01:22:10 UTC

Contents

<code>energymethod</code>	2
<code>energy_method</code>	2
<code>energy_method_complex</code>	3

Index	5
--------------	----------

 energymethod

Energy Method

Description

Given two samples from a multi-channel functional distribution, this package implements the energy method to perform a test of equality of mean. It returns channel-wise p-values and the global p-value.

Author(s)

David Colin Decker <d.colin.decker@gmail.com>

 energy_method

Implements the two sample paired or independent energy method

Description

This function takes two samples of high-dimensional functional data, implements the energy method, and returns a p-value for the global test of equality of mean and a channel-wise p-value for each functional coordinate.

Usage

```
energy_method(sample_1, sample_2, num_bootstrap_reps, seed, type)
```

Arguments

sample_1	A three dimensional array with dimension attribute (K,T,n_1) where K is the number of channels, T is the number of functional recordings, and n_1 is the sample size.
sample_2	A three dimensional array with dimension attribute (K,T,n_1) where K is the number of channels, T is the number of functional recordings, and n_2 is the sample size.
num_bootstrap_reps	A number. The number of bootstrap resamples to use when implementing the test
seed	A number. The seed used for randomness in bootstrap procedure
type	A sting. Either "paired" or "independent"

Value

A list containing the p-values of the test for the global hypothesis and channel-wise hypotheses, as well as summary information about the samples.

Author(s)

David Colin Decker

References

Article on energy method forthcoming

Examples

```
K=10
T=100
n_1=10
n_2=20
sample_1 = array(rnorm (K*T*n_1), dim=c(K, T, n_1))
sample_2 = array(rnorm (K*T*n_2), dim=c(K, T, n_2))
energy_method(sample_1, sample_2, num_bootstrap_reps=1000, seed=123, type="independent")
```

energy_method_complex *Implements the two sample paired or independent energy method*

Description

This function takes two samples of complex-valued high-dimensional functional data, implements the energy method, and returns a p-value for the global test of equality of mean and a channel-wise p-value for each functional coordinate.

Usage

```
energy_method_complex(sample_1, sample_2, num_bootstrap_reps, seed, type)
```

Arguments

sample_1	A three dimensional complex array with dimension attribute (K,T,n_1) where K is the number of channels, T is the number of functional recordings, and n_1 is the sample size.
sample_2	A three dimensional complex array with dimension attribute (K,T,n_1) where K is the number of channels, T is the number of functional recordings, and n_2 is the sample size.
num_bootstrap_reps	A number. The number of bootstrap resamples to use when implementing the test
seed	A number. The seed used for randomness in bootstrap procedure
type	A sting. Either "paired" or "independent"

Value

A list containing the p-values of the test for the global hypothesis and channel-wise hypotheses, as well as summary information about the samples.

Author(s)

David Colin Decker

References

Article on energy method forthcoming

Examples

```
K=10
T=100
n_1=10
n_2=20
sample_1_real=array(rnorm(K*T*n_1), dim=c(K,T,n_1))
sample_1_complex=array(rnorm(K*T*n_1), dim=c(K,T,n_1))

sample_1<-array(complex(real=sample_1_real, imaginary=sample_1_complex), dim=c(K,T,n_1))

sample_2_real=array(rnorm(K*T*n_2), dim=c(K,T,n_2))
sample_2_complex=array(rnorm(K*T*n_2), dim=c(K,T,n_2))

sample_2<-array(complex(real=sample_2_real, imaginary=sample_2_complex), dim=c(K,T,n_2))
energy_method_complex(sample_1, sample_2, num_bootstrap_reps=1000, seed=123, type="independent")
```

Index

[energy_method](#), 2
[energy_method_complex](#), 3
[energymethod](#), 2