

Package ‘envDocument’

May 8, 2026

Type Package

Title Document the R Working Environment

Version 2.4.2

Date 2025-09-09

Description Prints out information about the R working environment (system, R version,loaded and attached packages and versions) from a single function ``env_doc()". Optionally adds information on git repository, tags, commits and remotes (if available).

License GPL (>= 3.0)

Repository CRAN

URL <https://github.com/dgJacks0n/envDocument>

Suggests knitr(>= 1.13), git2r(>= 0.22.1), stringr(>= 1.2.0), testthat(>= 1.0.2), rmarkdown

RoxygenNote 7.3.3

Encoding UTF-8

VignetteBuilder knitr

Imports utils, renv(>= 1.1.4), here

NeedsCompilation no

Author Donald Jackson [aut, cre]

Maintainer Donald Jackson <djackson2641@gmail.com>

Date/Publication 2025-09-11 05:50:02 UTC

Contents

envDocument-package	2
collapseInfo	3
env_doc	3
getDominoInfo	4
getGitInfo	5
getPackageInfo	5

getRenvStatus	6
getRepo	6
getScriptInfo	7
getScriptPath	7
getSysInfo	8
get_Rversion	8
infoNotFound	8
prettyPrintInfo	9
remoteInfo	9

Index	10
--------------	-----------

envDocument-package *Document the environment under which an analysis was performed*

Description

Provides a function `env_doc` that collects information on the script, environment and system that performed an analysis.

Details

Returns a data frame with information on:

- R version
- Attached packages and version
- OS, version and user
- Path and modification time of the calling script
- Git commit and tag info (optional, requires `git2r`)

Results are collected in a standardized data frame that can be queried or pretty-printed using `kable` or similar methods.

Author(s)

Maintainer: Donald Jackson <14615921+dgJacks0n@users.noreply.github.com>

See Also

Useful links:

- <https://github.com/dgJacks0n/envDocument>

collapseInfo	<i>Collapse list of environment information into a single data frame</i>
--------------	--

Description

Collapse list of environment information into a single data frame

Usage

```
collapseInfo(info_list = list())
```

Arguments

info_list	List with environment information
-----------	-----------------------------------

env_doc	<i>Report the working environment in which an analysis was performed.</i>
---------	---

Description

env_doc prints or returns a data frame with the following information: - System version (OS, version, user, working directory)

Usage

```
env_doc(
  output = c("return", "print", "table"),
  system = TRUE,
  version = TRUE,
  packages = TRUE,
  script = TRUE,
  git = TRUE,
  renv = TRUE,
  domino = c("auto", "on", "off")
)
```

Arguments

output	How should output be handled? Character, values: return - return as a data frame (default); print - print to stdout; table - pretty-print using knitr::kable (requires package knitr)
system	Include OS info from getSysInfo? Boolean, default TRUE
version	Include R version from getRversion? Boolean, default TRUE
packages	Include attached packages with repository and version from getPackageInfo? Boolean, default TRUE

script	Include script path and modification time from getScriptInfo? Boolean, default TRUE
git	Include git repository information from getGitInfo (note: requires git2r)? Boolean, default TRUE
renv	Include renv status information from getRenvStatus? Boolean, default TRUE
domino	Include Domino Datalab run information from getDominoInfo? Character, values: auto - include if available; on - include with warning if not available; off - do not include evn if available

Details

- R version
- Package names and versions
- Top-level script name and modification time
- Git hash, status and tag (if any; requires package git2r)

Value

If output = return (default): A data frame with columns for information type, variable name and value. NULL for output = print or output = table

Examples

```
## Not run:
# Note that these only work when called in a script or markdown document
env_doc("print") # print information to stdout
info <- env_doc() # return information as a consolidated data frame

## End(Not run)
```

getDominoInfo	<i>Get information about a Domino Datalab run from environment variables in the run environment</i>
---------------	---

Description

Get information about a Domino Datalab run from environment variables in the run environment

Usage

```
getDominoInfo(
  drop_vars = c("DOMINO_API_HOST", "DOMINO_EXECUTOR_HOSTNAME", "DOMINO_USER_API_KEY")
)
```

Arguments

drop_vars Variables that will not be included in results. Character vector; see <https://support.dominodatalab.com/hc/en-us/articles/205536355-Domino-environment-variables> for a list of variables.

Value

data frame of Domino environment variables (renamed) and their values

getGitInfo *Get git repository information for a script*

Description

getGitInfo locates the git repository for the calling script (if any) and retrieves relevant information such as last commit, status (e.g. modified since last commit) and tag (if any).

Usage

```
getGitInfo(scriptpath = NA)
```

Arguments

scriptpath Path to script (optional, defaults to calling script from get_scriptPath())

Details

Requires that git2r be installed.

Examples

```
git_info <- getGitInfo()
```

getPackageInfo *Get information on attached packages*

Description

getPackageInfo returns information on attached packages including name, version and source.

Usage

```
getPackageInfo()
```

Examples

```
packages <- getPackageInfo()
```

getRenvStatus	<i>Check whether renv is in use for this project. If it is, get project status. Requires that renv be installed and active.</i>
---------------	---

Description

Check whether renv is in use for this project. If it is, get project status. Requires that renv be installed and active.

Usage

```
getRenvStatus(project_root = NA)
```

Arguments

project_root Project root directory (optional); defaults to value from here: `here()`

getRepo	<i>Locate the git repository where a file is tracked</i>
---------	--

Description

getRepo looks the up the repository for a file and makes sure path is tracked in repo. Repositories are searched from the file directory up using [discover_repository](#)

Usage

```
getRepo(testPath = NA)
```

Arguments

testPath Path to a file to find/check repo

getScriptInfo	<i>Get information about the calling script</i>
---------------	---

Description

getScriptInfo retrieves the file path and modification time for the calling script.

Usage

```
getScriptInfo()
```

Details

Note: Currently this works if the script was called via source(), knitr::spin(), Rstudio's _compile notebook_ (ctrl-shift-K), Rscript or R -f.

Examples

```
script_info <- getScriptInfo()
```

getScriptPath	<i>Get the path of the calling script</i>
---------------	---

Description

getScriptPath returns the full path of the script that called this function (if any) or NULL if path is not available

Usage

```
getScriptPath(absolute = TRUE)
```

Arguments

absolute	Return absolute path (absolute = TRUE, default) or path relative to working directory (FALSE)
----------	---

Examples

```
## Not run:  
mypath <- getScriptPath()  
  
## End(Not run)
```

getSysInfo *Get system information.*

Description

getSysInfo returns the OS, hostname, userid and working directory for the current analysis as a data frame

Usage

```
getSysInfo()
```

Examples

```
getSysInfo()
```

get_Rversion *Get information on R version*

Description

Get information on R version

Usage

```
get_Rversion()
```

Examples

```
Rversion <- getRversion()
```

infoNotFound *Return a consistent failure result when something is not available*

Description

Return a consistent failure result when something is not available

Usage

```
infoNotFound()
```

prettyPrintInfo	<i>Output environment information as individual tables per section</i>
-----------------	--

Description

Uses `knitr::kable` to pretty-print separate tables for each 'section' (list element) in the environment information.

Usage

```
prettyPrintInfo(info_list = list())
```

Arguments

info_list	R list with environment information
-----------	-------------------------------------

remoteInfo	<i>Look up remotes for repository</i>
------------	---------------------------------------

Description

Look up remotes for repository

Usage

```
remoteInfo(repo)
```

Arguments

repo	A git2r repository object
------	---------------------------

Index

`collapseInfo`, 3

`discover_repository`, 6

`env_doc`, 2, 3

`envDocument (envDocument-package)`, 2

`envDocument-package`, 2

`get_Rversion`, 8

`get_scriptpath (getScriptPath)`, 7

`getDominoInfo`, 4, 4

`getGitInfo`, 4, 5

`getPackageInfo`, 3, 5

`getRenvStatus`, 4, 6

`getRepo`, 6

`getRversion`, 3

`getScriptInfo`, 4, 7

`getScriptPath`, 7

`getSysInfo`, 3, 8

`infoNotFound`, 8

`kable`, 2

`prettyPrintInfo`, 9

`remoteInfo`, 9