

# Package 'eq5d'

May 8, 2026

**Type** Package

**Title** Methods for Analysing 'EQ-5D' Data and Calculating 'EQ-5D' Index Scores

**Version** 0.16.3

**Description** EQ-5D is a popular health related quality of life instrument used in the clinical and economic evaluation of health care. Developed by the EuroQol group <<https://euroqol.org/>>, the instrument consists of two components: health state description and evaluation. For the description component a subject self-rates their health in terms of five dimensions; mobility, self-care, usual activities, pain/discomfort, and anxiety/depression using either a three-level (EQ-5D-3L, <<https://euroqol.org/information-and-support/euroqol-instruments/eq-5d-3l/>>) or a five-level (EQ-5D-5L, <<https://euroqol.org/information-and-support/euroqol-instruments/eq-5d-5l/>>) scale. Frequently the scores on these five dimensions are converted to a single utility index using country specific value sets, which can be used in the clinical and economic evaluation of health care as well as in population health surveys. The eq5d package provides methods to calculate index scores from a subject's dimension scores. 33 TTO and 11 VAS EQ-5D-3L value sets including those for countries in Szende et al (2007) <[doi:10.1007/1-4020-5511-0](https://doi.org/10.1007/1-4020-5511-0)> and Szende et al (2014) <[doi:10.1007/978-94-007-7596-1](https://doi.org/10.1007/978-94-007-7596-1)>, 49 EQ-5D-5L EQ-VT value sets, the EQ-5D-5L crosswalk value sets developed by van Hout et al. (2012) <[doi:10.1016/j.jval.2012.02.008](https://doi.org/10.1016/j.jval.2012.02.008)>, the crosswalk value sets for Bermuda, Jordan and Russia and the van Hout (2021) reverse crosswalk value sets. 13 EQ-5D-Y-3L value sets are also included as are the NICE 'DSU' age-sex based EQ-5D-3L to EQ-5D-5L and EQ-5D-5L to EQ-5D-3L mappings. Methods are also included for the analysis of EQ-5D profiles, including those from the book ``Methods for Analyzing and Reporting EQ-5D data" by Devlin et al. (2020) <[doi:10.1007/978-3-030-47622-9](https://doi.org/10.1007/978-3-030-47622-9)>. Additionally a shiny web tool is included to enable the calculation, visualisation and automated statistical analysis of EQ-5D data via a web browser using EQ-5D dimension scores stored in CSV or Excel files.

**License** MIT + file LICENSE

**Encoding** UTF-8

**Depends** R (>= 3.5.0), lifecycle, rlang

**Suggests** testthat, shiny, DT, mime, readxl, ggplot2, ggiraph,  
ggiraphExtra, shinycssloaders, shinyWidgets, FSA, PMCMRplus,  
knitr, rmarkdown, covr

**URL** <https://github.com/fragla/eq5d>

**BugReports** <https://github.com/fragla/eq5d/issues>

**RoxygenNote** 7.3.3

**VignetteBuilder** knitr

**Language** en-GB

**NeedsCompilation** no

**Author** Fraser Morton [aut, cre],  
Jagtar Singh Nijjar [aut]

**Maintainer** Fraser Morton <fraser.morton@glasgow.ac.uk>

**Repository** CRAN

**Date/Publication** 2026-03-30 17:20:02 UTC

## Contents

CW	3
DSU3L	4
DSU5L	4
eq5d	5
eq5d3l	7
eq5d5l	7
eq5dcf	8
eq5dcw	9
eq5dds	10
eq5dmap	11
eq5drcw	12
eq5dy	12
eq5dy3l	13
get_all_health_states	14
get_dimensions_from_health_states	14
get_health_states_from_dimensions	15
hpg	16
hsdi	17
lfs	18
lss	18
pche	19
ps	20
RCW	22

CW	3
RCWVH	22
shannon	23
shiny_eq5d	24
TTO	24
valuesets	27
VAS	28
VT	30
Y3L	34
<b>Index</b>	<b>36</b>

---

CW	<i>EQ-5D-5L Crosswalk data</i>
----	--------------------------------

---

### Description

Crosswalk index value calculation table to calculate EQ-5D-3L indices from EQ-5D-5L data for Denmark, France, Germany, Japan, Netherlands, Russia, Spain, Thailand, UK, USA and Zimbabwe.

### Usage

CW

### Format

An object of class `data.frame` with 3125 rows and 13 columns.

### Source

van Hout B, Janssen MF, et al. Interim scoring for the EQ-5D-5L: Mapping the EQ-5D-5L to EQ-5D-3L value sets. *Value in Health* 2012 Jul-Aug;15(5):708-15. doi:10.1016/j.jval.2012.02.008. PMID: 22867780.

Bailey H, Roudijk B, Brathwaite R. The EQ-5D-3L valuation study for Bermuda: using an on-line EQ-VT protocol. *Eur J Health Econ.* 2024 Jul 9. doi:10.1007/s10198024017012. Epub ahead of print. PMID: 38982011.

Al Rabayah A, Roudijk B, Purba FD, Rencz F, Jaddoua S, Siebert U. Valuation of the EQ-5D-3L in Jordan. *Eur J Health Econ.* 2024 Sep 3. doi:10.1007/s1019802401712z. Epub ahead of print. PMID: 39225720.

Omelyanovskiy V, Musina N, Ratushnyak S, Bezdenezhnykh T, Fediaeva V, Roudijk B, Purba FD. Valuation of the EQ-5D-3L in Russia. *Qual Life Res.* 2021 Mar 13. doi:10.1007/s1113602102804-6. Epub ahead of print. PMID: 33713323.

[EQ-5D-5L Crosswalk Index Value Sets](#)

---

DSU3L

*DSU mapping from EQ-5D-3L to EQ-5D-5L*

---

**Description**

Data for age and sex based mapping from EQ-5D-3L dimensions or utility index score to EQ-5D-5L for China, Germany, Japan, Netherlands, South Korea, Spain and UK.

**Usage**

DSU3L

**Format**

An object of class data.frame with 2430 rows and 22 columns.

**Source**

Hernández Alava M, Pudney S, Wailoo A. Estimating the Relationship Between EQ-5D-5L and EQ-5D-3L: Results from a UK Population Study. *Pharmacoeconomics*. 2023 Feb;41(2):199-207. doi:10.1007/s40273022012187. Epub 2022 Nov 30. PMID: 36449173.

Hernández-Alava M, Pudney S. Econometric modelling of multiple self-reports of health states: The switch from EQ-5D-3L to EQ-5D-5L in evaluating drug therapies for rheumatoid arthritis. *J Health Econ*. 2017 Sep;55:139-152. doi:10.1016/j.jhealeco.2017.06.013. Epub 2017 Jul 4. PMID: 28778350.

[NICE DSU mapping website.](#)

---

DSU5L

*DSU mapping from EQ-5D-5L to EQ-5D-3L*

---

**Description**

Data for age and sex based mapping from EQ-5D-5L dimensions or utility index score to EQ-5D-3L for China, Germany, Japan, Netherlands, South Korea, Spain and UK.

**Usage**

DSU5L

**Format**

An object of class data.frame with 31250 rows and 22 columns.

## Source

Hernández Alava M, Pudney S, Wailoo A. Estimating the Relationship Between EQ-5D-5L and EQ-5D-3L: Results from a UK Population Study. *Pharmacoeconomics*. 2023 Feb;41(2):199-207. doi:10.1007/s40273022012187. Epub 2022 Nov 30. PMID: 36449173.

Hernández-Alava M, Pudney S. Econometric modelling of multiple self-reports of health states: The switch from EQ-5D-3L to EQ-5D-5L in evaluating drug therapies for rheumatoid arthritis. *J Health Econ*. 2017 Sep;55:139-152. doi:10.1016/j.jhealeco.2017.06.013. Epub 2017 Jul 4. PMID: 28778350.

[NICE DSU mapping website.](#)

---

 eq5d

*Calculate EQ-5D index scores*


---

## Description

Wrapper for eq5d3l, eq5d5l and eq5dy3l. Calculate EQ-5D index scores for EQ-5D-3L, EQ-5D-5L and EQ-5D-Y-3L. Available value sets can be viewed using the function valuesets.

## Usage

```
eq5d(scores, version, type, country, ignore.invalid, ...)
```

## Arguments

scores	numeric or data.frame with names/colnames MO, SC, UA, PD and AD representing Mobility, Self-care, Usual activities, Pain/discomfort and Anxiety/depression. Alternatively EQ-5D scores can be provided in five digit format e.g. 12321. If five digit scores are used in a data.frame the default column name look for by the function is "State".
version	string of value "3L", "5L" or "Y3L" to indicate instrument version.
type	string specifying method type used in deriving value set scores. Options are TTO or VAS for EQ-5D-3L, VT for EQ-5D-5L, CW for EQ-5D-5L crosswalk conversion valuesets, RCW for EQ-5D-3L reverse crosswalk conversion valuesets and DSU for the NICE Decision Support Unit's EEPRU age-sex based EQ-5D-3L to EQ-5D-5L and EQ-5D-5L to EQ-5D-3L mappings. Not required for EQ-5D-Y-3L.
country	string of value set country name used.
ignore.invalid	logical to indicate whether to ignore dimension data with invalid, incomplete or missing data.
...	character vectors for column names when using a data.frame. Use "dimensions" (default c("MO", "SC", "UA", "PD" and "AD")), "five.digit" (default "State") or "utility", "age", "sex" and "bwidth" (defaults "Utility", "Age", "Sex" and "bwidth") for NICE DSU mapping. bwidth can also be a number which is applied to the whole dataset. When a single NICE DSU score is being calculated "age", "sex" and "bwidth" are also used. See <a href="#">eq5dmap</a> for valid options. "digits" can also be used to return scores with more precision.

**Value**

a numeric vector of utility index scores.

**Examples**

```
#EQ-5D-5L single utility score by dimension
eq5d(scores=c(M0=1,SC=2,UA=3,PD=4,AD=5), type="VT",
      country="Indonesia", version="5L")

#EQ-5D-3L single utility score by dimension
eq5d(scores=c(M0=3,SC=2,UA=3,PD=2,AD=3),
      type="TTO", version="3L", country="Germany")

#Mapping an EQ-5D-5L utility score to EQ-5D-3L using NICE DSU method
eq5d(0.922, country="UK", version="5L", type="DSU",
     age=18, sex="male")

#Calculation of multiple EQ-5D-5L utility scores from a data.frame of dimensions
scores.df <- data.frame(
  M0=c(1,2,3,4,5), SC=c(1,5,4,3,2),
  UA=c(1,5,2,3,1), PD=c(1,3,4,3,4), AD=c(1,2,NA,2,1)
)

eq5d(scores.df, country="Canada", version="5L", type="VT", ignore.invalid=TRUE)

#Calculation of a utility score using five digit state
eq5d(scores=12321, type="TTO", version="3L", country="UK")

scores.df2 <- data.frame(
  state=c(11111,12121,23232,33333)
)

#Calculation of utility scores using a data.frame with five digit states
eq5d(scores=scores.df2, type="TTO", version="3L", country="UK", five.digit="state")

#Calculation of utility scores from a vector of five digit states
eq5d(scores=scores.df2$state, type="TTO", version="3L", country="UK")

#Mapping multiple utility scores from EQ-5D-5L to EQ-5D-3L using NICE DSU method
scores.df3 <- data.frame(
  Utility=c(0.715,0.435,0.95),
  Age=c(50,30,70),
  Sex=c("m","f","m"),
  bwidth=c(0.2,0.2,0.1)
)

#using bwidth column values (one per observation)
eq5d(scores.df3, type="DSU", version="5L", country="UK")

#using single bwidth value for whole dataset
eq5d(scores.df3, type="DSU", version="5L", country="UK", bwidth=0.1)
```

---

eq5d3l                      *Calculate EQ-5D-3L index scores*

---

**Description**

Calculate indices for EQ-5D-3L value sets. Available value sets can be viewed using the function `valuesets`.

**Usage**

```
eq5d3l(scores, type = "TTO", country = "UK", digits = 3)
```

**Arguments**

<code>scores</code>	numeric with names MO, SC, UA, PD and AD representing Mobility, Self-care, Usual activities, Pain/discomfort and Anxiety/depression.
<code>type</code>	3L values set type. Either TTO or VAS.
<code>country</code>	value set country.
<code>digits</code>	number of decimal places to return.

**Value**

calculated utility index score.

**Examples**

```
eq5d3l(scores=c(MO=1,SC=2,UA=3,PD=1,AD=3), type="VAS", country="UK")  
eq5d3l(scores=c(MO=3,SC=2,UA=3,PD=2,AD=3), type="TTO", country="Germany")
```

---

eq5d5l                      *Calculate EQ-5D-5L index scores*

---

**Description**

Calculate indices for EQ-5D-5L value sets. Available value sets can be viewed using the function `valuesets`.

**Usage**

```
eq5d5l(scores, country = "England", digits = 3)
```

**Arguments**

scores	numeric with names MO, SC, UA, PD and AD representing Mobility, Self-care, Usual activities, Pain/discomfort and Anxiety/depression.
country	value set country.
digits	number of decimal places to return.

**Value**

calculated utility index score.

**Examples**

```
eq5d5l(scores=c(M0=1,SC=2,UA=3,PD=4,AD=5), country="England")
eq5d5l(scores=c(M0=3,SC=2,UA=5,PD=2,AD=3), country="Netherlands")
```

---

 eq5dcf

---

*Calculate the cumulative frequency profile of an EQ-5D dataset*


---

**Description**

Calculate the frequency, percentage, cumulative frequency and cumulative percentage for each profile in an EQ-5D dataset.

**Usage**

```
eq5dcf(data, version, ignore.invalid, proportions, digits, ...)
```

**Arguments**

data	A data.frame with columns MO, SC, UA, PD and AD representing Mobility, Self-care, Usual activities, Pain/discomfort and Anxiety/depression or a "State" column containing five digit scores. Alternatively a vector of five digit scores can also be used.
version	string of value "3L" or "5L" to indicate instrument version.
ignore.invalid	boolean whether to ignore invalid scores. TRUE returns NA, FALSE throws an error.
proportions	boolean whether to include proportion data columns Proportions and CumulativeProp. Default is FALSE.
digits	numeric specifying the number of decimal places for percentages. Defaults to 1.
...	character vector, specifying "dimensions" column names. Defaults are "MO", "SC", "UA", "PD" and "AD".

**Value**

a data.frame or list of data.frames of counts/percentages. Columns contain dimensions names and rows the EQ-5D score.

**Examples**

```
dat <- read.csv(system.file("extdata", "eq5d3l_example.csv", package="eq5d"))
eq5dcf(dat, "3L")
```

---

eq5dcw

*Calculate EQ-5D-5L crosswalk index scores*

---

**Description**

Calculate indices for EQ-5D-5L indices by mapping them onto EQ-5D-3L value sets. Available value sets can be viewed using the function `valuesets`.

**Usage**

```
eq5dcw(scores, country = "UK")
```

**Arguments**

scores	numeric with names MO, SC, UA, PD and AD representing Mobility, Self-care, Usual activities, Pain/discomfort and Anxiety/depression.
country	value set country.

**Value**

calculated utility index score.

**Examples**

```
eq5dcw(scores=c(MO=1,SC=2,UA=5,PD=1,AD=3), country="UK")
eq5dcw(scores=c(MO=3,SC=5,UA=5,PD=2,AD=3), country="Germany")
```

eq5dds

*Analyse the descriptive system of an EQ-5D dataset***Description**

Analyses the descriptive components of an EQ-5D dataset producing summary information either as counts or as percentages.

**Usage**

```
eq5dds(data, version, counts = FALSE, by = NULL, ignore.invalid = TRUE, ...)
```

**Arguments**

<code>data</code>	numeric or data.frame with names/colnames MO, SC, UA, PD and AD representing Mobility, Self-care, Usual activities, Pain/discomfort and Anxiety/depression. Alternatively an EQ-5D score can be provided in five digit format e.g. 12321.
<code>version</code>	string of value "3L" or "5L" to indicate instrument version.
<code>counts</code>	logical show absolute counts in the summary table. Default is FALSE, which shows percentages for each EQ-5D dimension.
<code>by</code>	character specifying the column in the data.frame by which to group the results.
<code>ignore.invalid</code>	boolean whether to ignore invalid scores. TRUE returns NA, FALSE throws an error.
<code>...</code>	character vector, specifying "dimensions" column names. Defaults are "MO", "SC", "UA", "PD" and "AD".

**Value**

a data.frame or list of data.frames of counts/percentages. Columns contain dimensions names and rows the EQ-5D score.

**Examples**

```
dat <- data.frame(
  matrix(
    sample(1:3,5*12, replace=TRUE),12,5,
    dimnames=list(1:12,c("MO", "SC", "UA", "PD", "AD"))
  ),
  Sex=rep(c("Male", "Female"))
)

eq5dds(dat, version="3L")
eq5dds(dat, version="3L", counts=TRUE)

eq5dds(dat, version="3L", by="Sex")
```

---

eq5dmap	<i>Calculate utility index scores by mapping between EQ-5D-3L and EQ-5D-5L</i>
---------	--

---

### Description

Conditional prediction of the utility values of 5L scores onto 3L value sets and 3L scores onto 5L value sets from observed or specified values conditional on age and gender using the NICE Decision Support Unit's EEPRU funded models (see [NICE DSU's website](#) for more information).

### Usage

```
eq5dmap(scores, country, version, age, sex, bwidth = 0, digits = 3)
```

### Arguments

scores	numeric with names MO, SC, UA, PD and AD representing Mobility, Self-care, Usual activities, Pain/discomfort and Anxiety/depression. or a utility index score
country	value set country
version	string of value "3L" or "5L" to indicate starting instrument version.
age	age in years (18-100), or age category (1: 18-34, 2: 35-44, 3: 45-54, 4: 55-64, 5: 65-100)
sex	Male or Female
bwidth	bandwidth score for approximate scores (< 0.8: 0.2, 0.8-0.951: 0.1, 0.951-1: small, but large enough to include 1)
digits	number of decimal places to return

### Details

Available value sets can be viewed using the function `valuesets`.

### Value

calculated utility index score.

### Examples

```
eq5dmap(c(MO=1,SC=2,UA=3,PD=4,AD=5), "UK", "5L", 30, "female")
eq5dmap(0.922, "UK", "5L", 18, "male")
eq5dmap(0.715, "UK", "5L", 50, "male", bwidth = 0.0001)
eq5dmap(0.715, "UK", "5L", 50, "male", bwidth = 0.0001, digits = 8)
```

---

 eq5drcw

*Calculate EQ-5D-3L reverse crosswalk index scores*


---

### Description

Calculate indices for EQ-5D-3L indices by mapping them onto EQ-5D-5L value sets. Available value sets can be viewed using the function `valuesets`.

### Usage

```
eq5drcw(scores, country = "UK", method = "VH", digits = 3)
```

### Arguments

<code>scores</code>	numeric with names MO, SC, UA, PD and AD representing Mobility, Self-care, Usual activities, Pain/discomfort and Anxiety/depression.
<code>country</code>	value set country.
<code>method</code>	crosswalk values to use. Either "VH" (Van Hout, 2021) or "EQ" (EuroQol 2019 values). The van Hout method is recommended.
<code>digits</code>	number of decimal places to return.

### Value

calculated utility index score.

### Examples

```
eq5drcw(scores=c(MO=1,SC=2,UA=3,PD=2,AD=1), country="Netherlands")
eq5drcw(scores=c(MO=3,SC=3,UA=3,PD=3,AD=3), country="Germany")
```

---

 eq5dy

*Calculate EQ-5D-Y index scores*


---

### Description

`'r lifecycle::badge("deprecated")`

`'eq5dy'` was renamed to `'eq5dy3l'` to be consistent with the new EuroQol naming convention.

### Usage

```
eq5dy(scores, country = NULL)
```

**Arguments**

scores	numeric with names MO, SC, UA, PD and AD representing Mobility, Self-care, Usual activities, Pain/discomfort and Anxiety/depression.
country	value set country.

**Value**

calculated utility index score.

---

eq5dy3l	<i>Calculate EQ-5D-Y-3L index scores</i>
---------	--

---

**Description**

Calculate indices for EQ-5D-Y-3L value sets. Available value sets can be viewed using the function `valuesets`.

**Usage**

```
eq5dy3l(scores, country = NULL, digits = 3)
```

**Arguments**

scores	numeric with names MO, SC, UA, PD and AD representing Mobility, Self-care, Usual activities, Pain/discomfort and Anxiety/depression.
country	value set country.
digits	number of decimal places to return.

**Value**

calculated utility index score.

**Examples**

```
eq5dy3l(scores=c(MO=3,SC=3,UA=3,PD=3,AD=3), country="Slovenia")
```

---

get\_all\_health\_states *Get all five digit health state scores*

---

### Description

Get all five digit health state scores for either EQ-5D-3L, EQ-5D-5L or EQ-5D-Y3L

### Usage

```
get_all_health_states(version)
```

### Arguments

version            the EQ-5D version. Either 3L or 5L.

### Value

A character vector of five digit health states.

### Examples

```
get_all_health_states("3L")
get_all_health_states("5L")
get_all_health_states("Y3L")
```

---

get\_dimensions\_from\_health\_states  
*Get individual dimension scores from their five digit health states*

---

### Description

Get a data.frame of individual dimension scores from their five digit health states.

### Usage

```
get_dimensions_from_health_states(
  scores,
  ignore.invalid = TRUE,
  version = "5L"
)
```

### Arguments

scores            a vector of five digit scores  
ignore.invalid   whether to ignore invalid scores. TRUE returns NA, FALSE throws an error.  
version            3L, 5L or Y. Used for validating scores when ignore.invalid is FALSE.

**Value**

A data.frame of individual dimension scores.

**Examples**

```
get_dimensions_from_health_states(c("12345", "54321"), version="5L")
```

---

```
get_health_states_from_dimensions
```

*Get five digit health states from dimension scores*

---

**Description**

Merge MO, SC, UA, PD and AD dimension scores to get five digit health states.

**Usage**

```
get_health_states_from_dimensions(  
  scores,  
  version = "5L",  
  ignore.invalid = TRUE,  
  dimensions = .get_dimension_names()  
)
```

**Arguments**

scores	a data.frame containing each dimension in a column
version	3L, 5L or Y. Used for validating scores when ignore.invalid is FALSE.
ignore.invalid	whether to ignore invalid scores. TRUE returns NA, FALSE throws an error.
dimensions	character vector specifying "dimensions" column names. Defaults are "MO", "SC", "UA", "PD" and "AD".

**Value**

A character vector of individual dimension scores.

**Examples**

```
scores <- data.frame(MO=c(1,1,1,1,1), SC=c(1,2,1,2,1),  
                    UA=c(1,2,3,2,1), PD=c(3,2,1,2,3), AD=c(3,3,3,3,3))  
get_health_states_from_dimensions(scores, version="5L")
```

---

hpg *Calculate the Health Profile Grid*

---

**Description**

Calculate the Health Profile Grid (HPG) for two EQ-5D datasets.

**Usage**

```
hpg(
  pre,
  post,
  country = NULL,
  version = NULL,
  type = NULL,
  ignore.invalid = TRUE,
  dimensions = .get_dimension_names(),
  no.problems = TRUE
)
```

**Arguments**

pre	data.frame, numeric or character. For data.frame default column names should be MO, SC, UA, PD and AD representing Mobility, Self-care, Usual activities, Pain/discomfort and Anxiety/depression. Vector using five digit format can also be used.
post	data.frame, numeric or character. For data.frame default column names should be MO, SC, UA, PD and AD representing Mobility, Self-care, Usual activities, Pain/discomfort and Anxiety/depression. Vector using five digit format can also be used.
country	string of value set country name used.
version	string of value "3L" or "5L" to indicate instrument version.
type	string specifying method type used in deriving value set scores. Options are TTO or VAS for EQ-5D-3L, VT for EQ-5D-5L, CW for EQ-5D-5L crosswalk conversion valuesets, RCW for EQ-5D-3L reverse crosswalk conversion valuesets.
ignore.invalid	boolean whether to ignore invalid scores. TRUE returns NA, FALSE throws an error.
dimensions	character vector, specifying "dimension" column names. Defaults are "MO", "SC", "UA", "PD" and "AD".
no.problems	boolean. Summarise 11111 "No change" subjects in a "No problems" group.

**Value**

a data.frame or list of data.frames containing the columns Pre, Post and PCHC. Pre and Post contain the severity rankings and PCHC the PCHC category.

**Examples**

```
dat <- read.csv(system.file("extdata", "eq5d3l_example.csv", package="eq5d"))

pre <- dat[dat$Group=="Group1",][1:50,]
post <- dat[dat$Group=="Group2",][1:50,]
res <- hpg(pre, post, country="UK", version="3L", type="TT0")
head(res)
```

---

hsdi

*Calculate the Health State Density Index*


---

**Description**

Calculate the Health State Density Index (HSDI) for an EQ-5D dataset.

**Usage**

```
hsdi(scores, version = NULL, ignore.invalid = TRUE, digits = 2, ...)
```

**Arguments**

scores	scores data.frame, numeric or character. For data.frame default column names should be MO, SC, UA, PD and AD representing Mobility, Self-care, Usual activities, Pain/discomfort and Anxiety/depression. Vector using five digit format can also be used.
version	string of value "3L" or "5L" to indicate instrument version.
ignore.invalid	boolean whether to ignore invalid scores. TRUE returns NA, FALSE throws an error.
digits	numeric specifying the number of decimal places for percentages. Defaults to 1, use NULL to skip rounding.
...	character vector, specifying "dimensions" column names. Defaults are "MO", "SC", "UA", "PD" and "AD".

**Value**

numeric containing the HSDI value.

**Examples**

```
dat <- read.csv(system.file("extdata", "eq5d3l_example.csv", package="eq5d"))
hsdi(dat, version="3L")
```

---

lfs

---

*Calculate the Level Frequency Score for an EQ-5D profile*


---

**Description**

Calculate the Levels Frequency Score for a single or number of EQ-5D profiles

**Usage**

```
lfs(scores, version, ignore.invalid, ...)
```

**Arguments**

scores	data.frame with names MO, SC, UA, PD and AD representing Mobility, Self-care, Usual activities, Pain/discomfort and Anxiety/depression.
version	string of value "3L", "5L" or "Y3L" to indicate instrument version.
ignore.invalid	whether to ignore invalid scores. TRUE returns NA, FALSE throws an error.
...	character vector, specifying "dimensions" column names. Defaults are "MO", "SC", "UA", "PD" and "AD".

**Value**

a data.frame or list of data.frames of counts/percentages. Columns contain dimensions names and rows the EQ-5D score.

**Examples**

```
lfs(c(MO=1,SC=2,UA=3,PD=2,AD=1), version="3L")
lfs(55555, version="5L")
lfs(c(11111, 12345, 55555), version="5L")
```

---

lss

---

*Calculate the Level Sum Score for an EQ-5D profile*


---

**Description**

Calculate the Levels Sum Score for a single or number of EQ-5D profiles

**Usage**

```
lss(scores, version, ignore.invalid, ...)
```

**Arguments**

scores	data.frame with names MO, SC, UA, PD and AD representing Mobility, Self-care, Usual activities, Pain/discomfort and Anxiety/depression.
version	string of value "3L" or "5L" to indicate instrument version.
ignore.invalid	whether to ignore invalid scores. TRUE returns NA, FALSE throws an error.
...	character vector, specifying "dimensions" column names. Defaults are "MO", "SC", "UA", "PD" and "AD".

**Value**

a data.frame or list of data.frames of counts/percentages. Columns contain dimensions names and rows the EQ-5D score.

**Examples**

```
lss(c(MO=1,SC=2,UA=3,PD=2,AD=1), version="3L")
lss(55555, version="5L")
lss(c(11111, 12345, 55555), version="5L")
```

---

pchc

---

*Calculate the Paretian Classification of Health Change*


---

**Description**

Calculate the Paretian Classification of Health Change (PCHC) for two EQ-5D datasets.

**Usage**

```
pchc(
  pre,
  post,
  version = NULL,
  no.problems = TRUE,
  totals = TRUE,
  by.dimension = FALSE,
  ignore.invalid = TRUE,
  dimensions = .get_dimension_names(),
  summary = TRUE
)
```

**Arguments**

pre	data.frame, numeric or character. For data.frame default column names should be MO, SC, UA, PD and AD representing Mobility, Self-care, Usual activities, Pain/discomfort and Anxiety/depression. Vector using five digit format can also be used.
post	data.frame, numeric or character. For data.frame default column names should be MO, SC, UA, PD and AD representing Mobility, Self-care, Usual activities, Pain/discomfort and Anxiety/depression. Vector using five digit format can also be used.
version	string of value "3L" or "5L" to indicate instrument version.
no.problems	boolean. Summarise 11111 "No change" subjects in a "No problems" group.
totals	boolean. Include a summary total.
by.dimension	boolean. Summarise results by each EQ-5D dimension rather than by the whole dataset.
ignore.invalid	boolean whether to ignore invalid scores. TRUE returns NA, FALSE throws an error.
dimensions	character vector, specifying "dimension" column names. Defaults are "MO", "SC", "UA", "PD" and "AD".
summary	boolean. Summarise results or return all classifications.

**Value**

a data.frame or list of data.frames of changes according to PCHC. contain dimensions names and rows the EQ-5D score or, if summary=FALSE, a vector or list of vectors of changes.

**Examples**

```
dat <- read.csv(system.file("extdata", "eq5d3l_example.csv", package="eq5d"))

pre <- dat[dat$Group=="Group1",][1:50,]
post <- dat[dat$Group=="Group2",][1:50,]

pchc(pre, post, version="3L", no.problems=FALSE, totals=FALSE)
```

---

ps

---

*Calculate the Probability of Superiority*


---

**Description**

Calculate the Probability of Superiority (PS) for the dimensions of two EQ-5D datasets. Score is less than 0.5 if more patients deteriorate than improve, 0.5 if the same number of patients improve and deteriorate or do not change and greater than 0.5 if more patients improve than deteriorate.

**Usage**

```
ps(
  pre,
  post,
  version = NULL,
  ignore.invalid = TRUE,
  dimensions = .get_dimension_names(),
  digits = 2
)
```

**Arguments**

pre	data.frame, numeric or character. For data.frame default column names should be MO, SC, UA, PD and AD representing Mobility, Self-care, Usual activities, Pain/discomfort and Anxiety/depression. Vector using five digit format can also be used.
post	data.frame, numeric or character. For data.frame default column names should be MO, SC, UA, PD and AD representing Mobility, Self-care, Usual activities, Pain/discomfort and Anxiety/depression. Vector using five digit format can also be used.
version	string of value "3L" or "5L" to indicate instrument version.
ignore.invalid	boolean whether to ignore invalid scores. TRUE returns NA, FALSE throws an error.
dimensions	character vector, specifying "dimension" column names. Defaults are "MO", "SC", "UA", "PD" and "AD".
digits	numeric specifying the number of decimal places. Defaults to 2.

**Value**

a list of Probability of Superiority scores by dimension.

**Examples**

```
dat <- read.csv(system.file("extdata", "eq5d3l_example.csv", package="eq5d"))

pre <- dat[dat$Group=="Group1",][1:50,]
post <- dat[dat$Group=="Group2",][1:50,]

ps(pre, post, version="3L")
```

---

RCW

*EQ-5D-3L Reverse Crosswalk data (deprecated)*

---

**Description**

Reverse Crosswalk index value table to calculate EQ-5D-5L indices from EQ-5D-3L data for England, Germany, Netherlands and USA. Table uses the values published on the EuroQol analysis tools webpage based on reverse engineering of van Hout et al (2012)

**Usage**

RCW

**Format**

An object of class `data.frame` with 243 rows and 4 columns.

**Source**

[Reverse crosswalk datasets](#)

---

RCWVH

*EQ-5D-3L Reverse Crosswalk data*

---

**Description**

Reverse Crosswalk index value table to calculate EQ-5D-5L indices from EQ-5D-3L data using the van Hout et al (2021) method.

**Usage**

RCWVH

**Format**

An object of class `matrix` (inherits from `array`) with 243 rows and 49 columns.

**Source**

[doi:10.1016/j.jval.2021.03.009](https://doi.org/10.1016/j.jval.2021.03.009)

---

`shannon`*Calculate Shannon's Index*

---

### Description

Calculate Shannon's H' (diversity) index, H' max and Shannon's J' (evenness) index for an EQ-5D data set. This can be calculated both by dimension and for health states as a whole.

### Usage

```
shannon(  
  scores,  
  version = NULL,  
  by.dimension = TRUE,  
  ignore.invalid = TRUE,  
  dimensions = .get_dimension_names(),  
  base = 2,  
  digits = 2,  
  permutations = TRUE  
)
```

### Arguments

<code>scores</code>	data.frame, numeric or character. For data.frame default column names should be MO, SC, UA, PD and AD representing Mobility, Self-care, Usual activities, Pain/discomfort and Anxiety/depression. Vector using five digit format can also be used.
<code>version</code>	string of value "3L" or "5L" to indicate instrument version.
<code>by.dimension</code>	boolean whether to calculate scores by EQ-5D dimensions or for the whole dataset. Defaults to TRUE.
<code>ignore.invalid</code>	boolean whether to ignore invalid scores. TRUE returns NA, FALSE throws an error.
<code>dimensions</code>	character vector, specifying "dimension" column names. Defaults are "MO", "SC", "UA", "PD" and "AD".
<code>base</code>	numeric base of logarithm to use. Defaults to base 2.
<code>digits</code>	numeric specifying the number of decimal places. Defaults to 2.
<code>permutations</code>	boolean whether to use maximum number of permutations for H' max or the number of observed unique profiles. Default is TRUE.

### Value

a single list or list of dimensions containing H' H' max and J' scores.

**Examples**

```
dat <- read.csv(system.file("extdata", "eq5d3l_example.csv", package="eq5d"))

shannon(dat, version="3L", by.dimension=FALSE)
shannon(dat, version="3L", by.dimension=TRUE)
```

---

shiny_eq5d	<i>Launch shiny EQ-5D interface</i>
------------	-------------------------------------

---

**Description**

shiny\_eq5d launches a shiny interface for browser based EQ-5D calculations.

**Usage**

```
shiny_eq5d(display.mode = "normal")
```

**Arguments**

display.mode    The display mode to be passed to [runApp](#)

**Examples**

```
## Not run:
shiny_eq5d()
shiny_eq5d(display.mode="normal")

## End(Not run)
```

---

TTO	<i>EQ-5D-3L TTO value set data</i>
-----	------------------------------------

---

**Description**

Coefficients for the estimation of the EQ-5D-3L index values based on TTO valuation studies for Argentina, Australia, Brazil, Canada, Chile, China, Denmark, Ecuador, France, Germany, Hungary, Italy, Japan, Netherlands (2006), Netherlands (2026), Pakistan, Poland, Portugal, Russia, Singapore, SouthKorea, Spain, SriLanka, Sweden, Taiwan, Thailand, Trinidad and Tobago, Tunisia, UK, USA and Zimbabwe.

**Usage**

```
TTO
```

**Format**

An object of class `data.frame` with 63 rows and 33 columns.

**Source**

Szende, A., Oppe, M., & de Charro, F. (2007), Comparative review of Time Trade-Off value sets. In Szende, A., Oppe, M., & Devlin, N. (Ed.), *EQ-5D Value Sets: Inventory, Comparative Review and User Guide* (pp. 27-28). Dordrecht, The Netherlands: Springer.

Janssen, B., Szende, A., & Ramos-Goñi JM. (2014), Data and Methods. Szende, A., Janssen, B., & Cabasés, J. (Ed.), *In Self-Reported Population Health: An International Perspective based on EQ-5D* (p 13). Dordrecht, The Netherlands: Springer.

- **Argentina:** Augustovski FA, Irazola VE, Velazquez AP, Gibbons L, Craig BM. Argentine valuation of the EQ-5D health states. *Value Health*. 2009 Jun;12(4):587-96. doi:10.1111/j.15244733.2008.00468.x. Epub 2008 Nov 12. PMID: 19900257.
- **Australia:** Viney R, Norman R, King MT, Cronin P, Street DJ, Knox S, Ratcliffe J. Time trade-off derived EQ-5D weights for Australia. *Value Health*. 2011 Sep-Oct;14(6):928-36. doi:10.1016/j.jval.2011.04.009. PMID: 21914515.
- **Bermuda:** Bailey H, Roudijk B, Brathwaite R. The EQ-5D-3L valuation study for Bermuda: using an on-line EQ-VT protocol. *Eur J Health Econ*. 2024 Jul 9. doi:10.1007/s10198024-017012. Epub ahead of print. PMID: 38982011.
- **Brazil:** Viegas Andrade M, Noronha K, Kind P, Maia AC, Miranda de Menezes R, De Barros Reis C, Nepomuceno Souza M, Martins D, Gomes L, Nichele D, Calazans J, Mascarenhas T, Carvalho L, Lins C. Societal Preferences for EQ-5D Health States from a Brazilian Population Survey. *Value Health Reg Issues*. 2013 Dec;2(3):405-412. doi: 10.1016/j.vhri.2013.01.009. Epub 2013 Mar 13. Erratum in: *Value Health Reg Issues*. 2016 Dec;11:85-87. doi:10.1016/j.vhri.2016.12.001. PMID: 29702778.
- **Canada:** Bansback N, Tsuchiya A, Brazier J, Anis A. Canadian valuation of EQ-5D health states: preliminary value set and considerations for future valuation studies. *PLoS One*. 2012;7(2):e31115. doi:10.1371/journal.pone.0031115. Epub 2012 Feb 6. PMID: 22328929.
- **Chile:** Zarate V, Kind P, Valenzuela P, Vignau A, Olivares-Tirado P, Munoz A. Social valuation of EQ-5D health states: the Chilean case. *Value Health*. 2011 Dec;14(8):1135-41. doi:10.1016/j.jval.2011.09.002. Epub 2011 Nov 6. PMID: 22152184.
- **China:** Liu GG, Wu H, Li M, Gao C, Luo N. Chinese time trade-off values for EQ-5D health states. *Value Health*. 2014 Jul;17(5):597-604. doi:10.1016/j.jval.2014.05.007. Epub 2014 Jul 23. PMID: 25128053.
- **Denmark:** Wittrup-Jensen KU, Lauridsen J, Gudex C, Pedersen KM. Generation of a Danish TTO value set for EQ-5D health states. *Scand J Public Health*. 2009 Jul;37(5):459-66. doi:10.1177/1403494809105287. Epub 2009 May 1. PMID: 19411320.
- **Ecuador:** Lucio R, Flores V, Granja M, Mata G. Resultados de la encuesta de valoración social de los estados de salud de IAños de vida ajustados por calidad (QALY'S). 2019. [Link](#)
- **France:** Chevalier J, de Pouvourville G. Valuing EQ-5D using time trade-off in France. *Eur J Health Econ*. 2013 Feb;14(1):57-66. doi:10.1007/s101980110351x. Epub 2011 Sep 21. PMID: 21935715.

- **Germany:** Greiner W, Claes C, Busschbach JJ, von der Schulenburg JM. Validating the EQ-5D with time trade off for the German population. *Eur J Health Econ.* 2005 Jun;6(2):124-30. doi:10.1007/s101980040264z. PMID: 19787848.
- **Hungary:** Rencz F, Brodszky V, Gulácsi L, Golicki D, Ruzsa G, Pickard AS, Law EH, Péntek M. Parallel Valuation of the EQ-5D-3L and EQ-5D-5L by Time Trade-Off in Hungary. *Value Health.* 2020 Sep;23(9):1235-1245. doi:10.1016/j.jval.2020.03.019. Epub 2020 Aug 12. PMID: 32940242.
- **Italy:** Scalone L, Cortesi PA, Ciampichini R, Belisari A, D'Angiolella LS, Cesana G, Mantovani LG. Italian population-based values of EQ-5D health states. *Value Health.* 2013 Jul-Aug;16(5):814-22. doi:10.1016/j.jval.2013.04.008. Epub 2013 Jun 19. PMID: 23947975.
- **Japan:** Tsuchiya A, Ikeda S, Ikegami N, Nishimura S, Sakai I, Fukuda T, Hamashima C, Hisashige A, Tamura M. Estimating an EQ-5D population value set: the case of Japan. *Health Econ.* 2002 Jun;11(4):341-53. doi:10.1002/hec.673. PMID: 12007165.
- **Jordan:** Al Rabayah A, Roudijk B, Purba FD, Rencz F, Jaddoua S, Siebert U. Valuation of the EQ-5D-3L in Jordan. *Eur J Health Econ.* 2024 Sep 3. doi:10.1007/s1019802401712z. Epub ahead of print. PMID: 39225720.
- **Netherlands (2006):** Lamers LM, McDonnell J, Stalmeier PF, Krabbe PF, Busschbach JJ. The Dutch tariff: results and arguments for an effective design for national EQ-5D valuation studies. *Health Econ.* 2006 Oct;15(10):1121-32. doi:10.1002/hec.1124. PMID: 16786549.
- **Netherlands (2026):** Roudijk B, Jonker MF. Revisiting health state preferences after 20 years: A new EQ-5D-3L value set for the Netherlands. *Eur J Health Econ.* 2026 Jan 12. doi:10.1007/s10198025018922. PMID: 41525009.
- **Pakistan:** Malik M, Gu NY, Hussain A, Roudijk B, Purba FD. The EQ-5D-3L Valuation Study in Pakistan. *Pharmacoecon Open.* 2023 Sep 13. doi:10.1007/s41669023004378. Epub ahead of print. PMID: 37702988.
- **Poland:** Golicki D, Jakubczyk M, Niewada M, Wrona W, Busschbach JJ. Valuation of EQ-5D health states in Poland: first TTO-based social value set in Central and Eastern Europe. *Value Health.* 2010 Mar-Apr;13(2):289-97. doi:10.1111/j.15244733.2009.00596.x. Epub 2009 Sep 10. PMID: 19744296.
- **Portugal:** Ferreira LN, Ferreira PL, Pereira LN, Oppe M. The valuation of the EQ-5D in Portugal. *Qual Life Res.* 2014 Mar;23(2):413-23. doi:10.1007/s111360130448z. Epub 2013 Jun 8. PMID: 23748906.
- **Russia:** Omelyanovskiy V, Musina N, Ratushnyak S, Bezdenezhnykh T, Fediaeva V, Roudijk B, Purba FD. Valuation of the EQ-5D-3L in Russia. *Qual Life Res.* 2021 Mar 13. doi:10.1007/s11136021028046. Epub ahead of print. PMID: 33713323.
- **Singapore:** Luo N, Wang P, Thumboo J, Lim YW, Vrijhoef HJ. Valuation of EQ-5D-3L health states in Singapore: modeling of time trade-off values for 80 empirically observed health states. *Pharmacoeconomics.* 2014 May;32(5):495-507. doi:10.1007/s4027301401421. PMID: 24519603.
- **Spain:** Badia X, Roset M, Herdman M, Kind P. A comparison of United Kingdom and Spanish general population time trade-off values for EQ-5D health states. *Med Decis Making.* 2001 Jan-Feb;21(1):7-16. doi:10.1177/0272989X0102100102. PMID: 11206949.
- **South Korea:** Lee YK, Nam HS, Chuang LH, Kim KY, Yang HK, Kwon IS, Kind P, Kweon SS, Kim YT. South Korean time trade-off values for EQ-5D health states: modeling with observed values for 101 health states. *Value Health.* 2009 Nov-Dec;12(8):1187-93. doi:10.1111/j.15244733.2009.00579.x. Epub 2009 Jul 29. PMID: 19659703.

- **Sri Lanka:** Kularatna S, Whitty JA, Johnson NW, Jayasinghe R, Scuffham PA. Valuing EQ-5D health states for Sri Lanka. *Qual Life Res.* 2015 Jul;24(7):1785-93. doi:10.1007/s11136-01409062. Epub 2014 Dec 28. PubMed PMID: PMID: 25543271.
- **Sweden:** Burström K, Sun S, Gerdtham UG, Henriksson M, Johannesson M, Levin LÅ, Zethraeus N. Swedish experience-based value sets for EQ-5D health states. *Qual Life Res.* 2014 Mar;23(2):431-42. doi:10.1007/s1113601304964. PMID: 23975375.
- **Taiwan:** Lee HY, Hung MC, Hu FC, Chang YY, Hsieh CL, Wang JD. Estimating quality weights for EQ-5D (EuroQol-5 dimensions) health states with the time trade-off method in Taiwan. *J Formos Med Assoc.* 2013 Nov;112(11):699-706. doi:10.1016/j.jfma.2012.12.015. Epub 2013 Feb 12. PMID: 24183199.
- **Thailand:** Tongsiri S, Cairns J. Estimating population-based values for EQ-5D health states in Thailand. *Value Health.* 2011 Dec;14(8):1142-5. doi:10.1016/j.jval.2011.06.005. PMID: 22152185.
- **Trinidad and Tobago:** Bailey H, Stolk E, Kind P. Toward Explicit Prioritization for the Caribbean: An EQ-5D Value Set for Trinidad and Tobago. *Value Health Reg Issues.* 2016 Dec;11:60-67. doi:10.1016/j.vhri.2016.07.010. PMID: 27986200.
- **Tunisia:** Chemli J, Drira C, Felfel H, Roudijk B, Al Sayah F, Kouki M, Kooli A, Razgallah Khrouf M. Valuing health-related quality of life using a hybrid approach: Tunisian value set for the EQ-5D-3L. *Qual Life Res.* 2021 Jan 14. doi:10.1007/s1113602002730z. Epub ahead of print. PMID: 33447958.
- **UK:** Dolan P. Modeling valuations for EuroQol health states. *Med Care.* 1997 Nov;35(11):1095-108. doi:10.1097/0000565019971100000002. PMID: 9366889.
- **USA:** Shaw JW, Johnson JA, Coons SJ. US valuation of the EQ-5D health states: development and testing of the D1 valuation model. *Med Care.* 2005 Mar;43(3):203-20. doi:10.1097/0000565020050300000003. PMID: 15725977.
- **Zimbabwe:** Jelsma J, Hansen K, De Weerd W, De Cock P, Kind P. How do Zimbabweans value health states? *Popul Health Metr.* 2003 Dec 16;1(1):11. doi:10.1186/14787954111. PMID: 14678566.

---

valuesets

*Get the available EQ-5D value sets.*

---

## Description

valuesets returns a data.frame of the available EQ-5D value sets in the eq5d package.

## Usage

```
valuesets(
  type = NULL,
  version = NULL,
  country = NULL,
  references = c("PubMed", "DOI", "ISBN", "ExternalURL")
)
```

**Arguments**

type	string EQ-5D value set type. TTO or VAS for EQ-5D-3L, VT for EQ-5D-5L, IVP (International Valuation Protocol of Ramos-Goñi et al (2020)) for EQ-5D-Y-3L, CW for EQ-5D-5L crosswalk conversion dataset, or DSU for NICE Decision Support Unit's EQ-5D-5L to EQ-5D-3L and EQ-5D-3L to EQ-5D-5L mappings.
version	string either 3L, 5L or Y3L.
country	string one of the countries for which there is a value set.
references	character vector of reference columns. One or more of PubMed, DOI, ISBN or ExternalURL. Default is all. Reference columns can be removed by setting argument to NULL.

**Value**

A data.frame containing the EQ-5D version, the value set type and country, along with PubMed IDs, DOIs, ISBNs and external URLs where available.

**Examples**

```
valuesets()
valuesets(type="TTO")
valuesets(version="5L")
valuesets(country="UK")
valuesets(version="Y3L", references=c("DOI", "PubMed"))
```

---

VAS

*EQ-5D-3L VAS value set data*

---

**Description**

Coefficients for the estimation of the EQ-5D-3L index values based on VAS valuation studies for Belgium, Denmark, Europe, Finland, Germany, Iran, Malaysia, New Zealand, Slovenia, Spain and UK.

**Usage**

VAS

**Format**

An object of class data.frame with 21 rows and 11 columns.

## Source

Oppe, M., Szende, A., & de Charro, F. (2007), Comparative review of Visual Analogue Scale value sets. In Szende, A., Oppe, M., & Devlin, N. (Ed.), *EQ-5D Value Sets: Inventory, Comparative Review and User Guide* (pp. 37-38). Dordrecht, The Netherlands: Springer.

- **Belgium:** Cleemput I. A social preference valuations set for EQ-5D health states in Flanders, Belgium. *Eur J Health Econ.* 2010 Apr;11(2):205-13. doi:10.1007/s1019800901670. Epub 2009 Jul 7. PMID: 19582490.
- **Denmark:** Wittrup-Jensen KU, Lauridsen JT, Gudex C, Brooks R, Pedersen KM. Estimating Danish EQ-5D tariffs using TTO and VAS. In: Norinder A, Pedersen K, Roos P, editors. *Proceedings of the 18th Plenary Meeting of the EuroQol Group.* 2001. Copenhagen, Denmark. IHE, The Swedish Institute for Health Economics, 2002: 257-292.
- **Europe:** Greiner W, Weijnen T, Nieuwenhuizen M, et al. A single European currency for EQ-5D health states. Results from a six country study. *Eur J Health Econ* 2003; 4(3):222-231.
- **Finland:** Ohinmaa, A., & Sintonen, H. (1998, October). Inconsistencies and modelling of the Finnish EuroQol (EQ-5D) preference values. In *EuroQol Plenary Meeting* (pp. 1-2). Health Economics and Health System Research, University of Hannover.
- **Germany:** Claes, C., Greiner, W., Uber, A., & Graf von der Schulenburg, J. M. (1999). An interview-based comparison of the TTO and VAS values given to EuroQol states of health by the general German population. In *Proceedings of the 15th Plenary Meeting of the EuroQol Group.* Hannover, Germany: Centre for Health Economics and Health Systems Research, University of Hannover (pp. 13-38).
- **Iran:** Goudarzi R, Zeraati H, Akbari Sari A, Rashidian A, Mohammad K. Population-Based Preference Weights for the EQ-5D Health States Using the Visual Analogue Scale (VAS) in Iran. *Iran Red Crescent Med J.* 2016 Feb 13;18(2):e21584. doi:10.5812/ircmj.21584. PMID: 27186384.
- **Malaysia:** Yusof FA, Goh A, Azmi S. Estimating an EQ-5D value set for Malaysia using time trade-off and visual analogue scale methods. *Value Health.* 2012 Jan-Feb;15(1 Suppl):S85-90. doi:10.1016/j.jval.2011.11.024. PMID: 22265073.
- **New Zealand:** Devlin NJ, Hansen P, Kind P, Williams A. Logical inconsistencies in survey respondents' health state valuations – a methodological challenge for estimating social tariffs. *Health Econ.* 2003 Jul;12(7):529-44. doi:10.1002/hec.741. PMID: 12825206.
- **Slovenia:** Prevolnik Rupel V, Rebolj M. The Slovenian VAS Tariff based on valuations of EQ-5D health states from the general population. In: Cabasés JM, Gaminde I, editors. *Proceedings of the 17th Plenary Meeting of the EuroQol Group.* Universidad Pública de Navarra 2001; 23-47.
- **Spain** Badia X, Roset M, Monserrat S, Herdman M. The Spanish VAS tariff based on valuation of EQ-5D health states from the general population. In: Rabin RE et al, editors. *EuroQol Plenary meeting Rotterdam 1997, 2-3 October. Discussion papers.* Centre for Health Policy & Law, Erasmus University, Rotterdam, 1998; 93-114
- **UK** MVH Group. *The Measurement and Valuation of Health. Final report on the modeling of valuation tariffs.* York Centre for Health Economics, 1995.

VT

*EQ-5D-5L VT value set data***Description**

EQ-5D-5L VT value set calculation data for Australia, Belgium, Canada, China, Denmark, Egypt, England, Ethiopia, France, Germany, Ghana, HongKong, Hungary, India, Indonesia, Iran, Ireland, Italy, Japan, Malaysia, Mexico, Morocco, Netherlands, NewZealand, Norway, Peru, Philippines, Poland, Portugal, Romania, SaudiArabia, Slovenia, SouthKorea, Spain, Sweden, Taiwan, Thailand, Uganda, UAE, Uruguay, USA, Vietnam and Western Preference Pattern (WePP).

**Usage**

VT

**Format**

An object of class `data.frame` with 37 rows and 49 columns.

**Source**

- **Australia:** Norman R, Mulhern B, Lancsar E, Lorgelly P, Ratcliffe J, Street D, Viney R. The Use of a Discrete Choice Experiment Including Both Duration and Dead for the Development of an EQ-5D-5L Value Set for Australia. *Pharmacoeconomics*. 2023 Jan 31. doi:10.1007/s40273023012430. Epub ahead of print. PMID: 36720793.
- **Belgium:** Bouckaert N, Cleemput I, Devriese S, Gerkens S. An EQ-5D-5L Value Set for Belgium. *Pharmacoecon Open*. 2022 Aug 4. doi:10.1007/s41669022003533. Epub ahead of print. PMID: 35927410.
- **Canada:** Xie F, Pullenayegum E, Gaebel K, Bansback N, Bryan S, Ohinmaa A, Poissant L, Johnson JA; Canadian EQ-5D-5L Valuation Study Group. A Time Trade-off-derived Value Set of the EQ-5D-5L for Canada. *Med Care*. 2016 Jan;54(1):98-105. doi:10.1097/MLR.000000000000447. PMID: 26492214.
- **China:** Luo N, Liu G, Li M, Guan H, Jin X, Rand-Hendriksen K. Estimating an EQ-5D-5L Value Set for China. *Value Health*. 2017 Apr;20(4):662-669. doi:10.1016/j.jval.2016.11.016. Epub 2017 Feb 9. PMID: 28408009.
- **Denmark:** Jensen CE, Sørensen SS, Gudex C, Jensen MB, Pedersen KM, Ehlers LH. The Danish EQ-5D-5L Value Set: A Hybrid Model Using cTTO and DCE Data. *Appl Health Econ Health Policy*. 2021 Feb 2. doi:10.1007/s40258021006393. Epub ahead of print. PMID: 33527304.
- **Egypt:** Al Shabasy S, Abbassi M, Finch A, Roudijk B, Baines D, Farid S. The EQ-5D-5L Valuation Study in Egypt. *Pharmacoeconomics*. 2021 Nov 17:1–15. doi:10.1007/s40273021-01100y. Epub ahead of print. PMID: 34786590.
- **England:** Devlin NJ, Shah KK, Feng Y, Mulhern B, van Hout B. Valuing health-related quality of life: An EQ-5D-5L value set for England. *Health Econ*. 2018 Jan;27(1):7-22. doi:10.1002/hec.3564. Epub 2017 Aug 22. PMID: 28833869.

- **Ethiopia:** Welie AG, Gebretekle GB, Stolk E, Mukuria C, Krahn MD, Enquoselassie F, Fenta TG. Valuing Health State: An EQ-5D-5L Value Set for Ethiopians. *Value Health Reg Issues*. 2019 Nov 1;22:7-14. doi:10.1016/j.vhri.2019.08.475. PMID: 31683254.
- **France:** Andrade LF, Ludwig K, Goni JMR, Oppe M, de Pouvourville G. A French Value Set for the EQ-5D-5L. *Pharmacoeconomics*. 2020 Jan 8. doi:10.1007/s40273019008764. PMID: 31912325.
- **Germany:** Ludwig K, Graf von der Schulenburg JM, Greiner W. German Value Set for the EQ-5D-5L. *Pharmacoeconomics*. 2018 Feb;36(6):663-674. doi:10.1007/s4027301806158. PMID: 29460066.
- **Ghana:** Addo R, Mulhern B, Norman R, Owusu R, Viney R, Nonvignon J. An EQ-5D-5L Value Set for Ghana Using an Adapted EuroQol Valuation Technology Protocol. *Value Health Reg Issues*. 2024 Sep 4;45:101045. doi:10.1016/j.vhri.2024.101045. Epub ahead of print. PMID: 39236574.
- **HongKong:** Wong ELY, Ramos-Goñi JM, Cheung AWL, Wong AYK, Rivero-Arias O. Assessing the Use of a Feedback Module to Model EQ-5D-5L Health States Values in Hong Kong. *Patient*. 2018 Apr;11(2):235-247. doi:10.1007/s4027101702780. PMID: 29019161.
- **Hungary:** Rencz F, Brodszky V, Gulácsi L, Golicki D, Ruzsa G, Pickard AS, Law EH, Péntek M. Parallel Valuation of the EQ-5D-3L and EQ-5D-5L by Time Trade-Off in Hungary. *Value Health*. 2020 Sep;23(9):1235-1245. doi:10.1016/j.jval.2020.03.019. Epub 2020 Aug 12. PMID: 32940242.
- **India:** Jyani G, Sharma A, Prinja S, Kar SS, Trivedi M, Patro BK, Goyal A, Purba FD, Finch AP, Rajsekar K, Raman S, Stolk E, Kaur M. Development of an EQ-5D Value Set for India Using an Extended Design (DEVINE) Study: The Indian 5-Level Version EQ-5D Value Set. *Value Health*. 2022 Jul;25(7):1218-1226. doi:10.1016/j.jval.2021.11.1370. Epub 2022 Jan 5. PMID: 35779943.
- **Indonesia:** Purba FD, Hunfeld JAM, Iskandarsyah A, Fitriana TS, Sadarjoen SS, Ramos-Goñi JM, Passchier J, Busschbach JJ. The Indonesian EQ-5D-5L Value Set. *Pharmacoeconomics*. 2017 Nov;35(11):1153-1165. doi:10.1007/s4027301705389. PMID: 28695543.
- **Iran:** Afshari S, Daroudi R, Goudarzi R, Mahboub-Ahari A, Yaseri M, Sari AA, Ameri H, Bahariniya S, Oliaei-Manesh A, Kalavani K, Zare Z, Hasannezhad E, Mirzaei M, Amiri Z. A national survey of Iranian general population to estimate a value set for the EQ-5D-5L. *Qual Life Res*. 2023 Mar 10. doi:10.1007/s11136023033781. Epub ahead of print. PMID: 36897530.
- **Ireland:** Hobbins A, Barry L, Kelleher D, Shah K, Devlin N, Ramos Goñi JM, O'Neill C. Utility Values for Health States in Ireland: A Value Set for the EQ-5D-5L. *Pharmacoeconomics*. 2018 Nov;36(11):1345-1353. doi:10.1007/s402730180690x. PMID: 30051267.
- **Italy:** Finch AP, Mereaglia M, Ciani O, Roudijk B, Jommi C. An EQ-5D-5L value set for Italy using videoconferencing interviews and feasibility of a new mode of administration. *Soc Sci Med*. 2022 Jan;292:114519. doi:10.1016/j.socscimed.2021.114519. Epub 2021 Oct 28. PMID: 34736804.
- **Japan:** Shiroywa T, Ikeda S, Noto S, Igarashi A, Fukuda T, Saito S, Shimoizuma K. Comparison of Value Set Based on DCE and/or TTO Data: Scoring for EQ-5D-5L Health States in Japan. *Value Health*. 2016 Jul-Aug;19(5):648-54. doi:10.1016/j.jval.2016.03.1834. Epub 2016 Apr 26. PMID: 27565282.

- **Malaysia:** Shafie AA; Vasan Thakumar A; Lim CJ; Luo N; Rand-Hendriksen K; Yusof FA. EQ-5D-5L Valuation for the Malaysian Population. *Pharmacoeconomics*. 2019 May;37(5):715-725. doi:10.1007/s4027301807587. PMID: 30535779.
- **Mexico:** Gutierrez-Delgado C, Galindo-Suárez RM, Cruz-Santiago C, Shah K, Papadimitropoulos M, Feng Y, Zamora B, Devlin N. EQ-5D-5L Health-State Values for the Mexican Population. *Appl Health Econ Health Policy*. 2021 Nov;19(6):905-914. doi:10.1007/s40258-021006580. Epub 2021 Jun 26. PMID: 34173957.
- **Morocco:** Azizi A, Boutib A, Achak D, Purba FD, Rencz F, Saad E, Hilali A, Ahid S, Nejjari C, Stolk EA, Roudijk B, Youlyouz-Marfak I, Marfak A. Valuing health-related quality of life: an EQ-5D-5L value set for Morocco. *Qual Life Res*. 2025 Feb 28. doi:10.1007/s11136025-039301. Online ahead of print. PMID: 40019677.
- **Netherlands:** Versteegh MM, Vermeulen KM, Evers SM, de Wit GA, Prenger R, Stolk EA. Dutch Tariff for the Five-Level Version of EQ-5D. *Value in Health*. 2016 Jun;19(4):343-52. doi:10.1016/j.jval.2016.01.003. PMID: 27325326.
- **New Zealand:** Sullivan T, Hansen P, Ombler F, Derrett S, Devlin N. A new tool for creating personal and social EQ-5D-5L value sets, including valuing 'dead'. *Soc Sci Med*. 2020 Feb;246:112707. doi:10.1016/j.socscimed.2019.112707. Epub 2019 Nov 30. PMID: 31945596.
- **Norway:** Garratt AM, Stavem K, Shaw JW, Rand K. EQ-5D-5L value set for Norway: a hybrid model using cTTO and DCE data. *Qual Life Res*. 2024 Nov 20. doi:10.1007/s11136-024038373. Epub ahead of print. PMID: 39565555.
- **Peru** Augustovski F, Belizán M, Gibbons L, Reyes N, Stolk E, Craig BM, Tejada RA. Peruvian Valuation of the EQ-5D-5L: A Direct Comparison of Time Trade-Off and Discrete Choice Experiments. *Value Health*. 2020;23(7):880-888. doi:10.1016/j.jval.2020.05.004. PMID: 32762989.
- **Philippines** Miguel RTD, Rivera AS, Cheng KJG, Rand K, Purba FD, Luo N, Zarsuelo MA, Genuino-Marfori AJ, Florentino-Fariñas I, Guerrero AM, Lam HY. Estimating the EQ-5D-5L value set for the Philippines. *Qual Life Res*. 2022 May 9. doi:10.1007/s1113602203143w. PMID: 35532835.
- **Poland** Golicki D, Jakubczyk M, Niewada M, Wrona W, Busschbach JJ. Valuation of EQ-5D health states in Poland: first TTO-based social value set in Central and Eastern Europe. *Value Health*. 2010 Mar-Apr;13(2):289-97. doi:10.1111/j.15244733.2009.00596.x. PMID: 19744296.
- **Portugal** Ferreira PL, Antunes P, Ferreira LN, Pereira LN, Ramos-Goñi JM. A hybrid modelling approach for eliciting health state preferences: the Portuguese EQ-5D-5L value set. *Qual Life Res*. 2019 Jun 14. doi:10.1007/s11136019022265. PMID: 31201730.
- **Romania** Olariu E, Mohammed W, Oluboyede Y, Caplescu R, Niculescu-Aron IG, Paveliu MS, Vale L. EQ-5D-5L: a value set for Romania. *Eur J Health Econ*. 2022 Jun 10. doi:10.1007/s10198022014817. Epub ahead of print. PMID: 35688994.
- **Saudi Arabia** Al-Jedai A, Almudaiheem H, Al-Salamah T, Aldosari M, Almutairi AR, Al-mogbel Y, AlRuthia Y, Althemery AU, Alluhidan M, Roudijk B, Purba FD, Awad N, O'jeil R. Valuation of EQ-5D-5L in the Kingdom of Saudi Arabia: A national representative study. *Value Health*. 2024 Feb 9:S1098-3015(24)00047-0. doi:10.1016/j.jval.2024.01.017. PMID: 38342365.

- **Singapore** Luo N, Vasan Thakumar A, Cheng LJ, Yang Z, Rand K, Cheung YB, Thumboo J. Developing an EQ-5D-5L Value Set for Singapore. *Pharmacoeconomics*. 2025 Aug 29. doi:10.1007/s40273025015197. Epub ahead of print. PMID: 40880001.
- **Slovenia** Prevolnik Rupel V, Ogorevc M. EQ-5D-5L Value Set for Slovenia. *Pharmacoeconomics*. 2023 Jun 21. doi:10.1007/s40273023012809. Epub ahead of print. PMID: 37341959.
- **South Korea** Kim SH, Ahn J, Ock M, Shin S, Park J, Luo N, Jo MW. The EQ-5D-5L valuation study in Korea. *Qual Life Res*. 2016 Jul;25(7):1845-52. doi:10.1007/s1113601512052. PMID: 26961008.
- **Spain:** Ramos-Goñi JM, Craig B, Oppe M, Ramallo-Fariña Y, Pinto-Prades JL, Luo N, Rivero-Arias O. Handling data quality issues to estimate the Spanish EQ-5D-5L Value Set using a hybrid interval regression approach. *Value in Health* 2018 May;21(5):596-604. doi:10.1016/j.jval.2017.10.023. PMID: 29753358.
- **Sweden (2020):** Burström K, Teni FS, Gerdtham UG, Leidl R, Helgesson G, Rolfson O, Henriksson M. Experience-Based Swedish TTO and VAS Value Sets for EQ-5D-5L Health States. *Pharmacoeconomics*. 2020 Apr 20. doi:10.1007/s40273020009057. PMID: 32307663.
- **Sweden (2022):** Sun S, Chuang LH, Sahlén KG, Lindholm L, Norström F. Estimating a social value set for EQ-5D-5L in Sweden. *Health Qual Life Outcomes*. 2022 Dec 23;20(1):167. doi:10.1186/s1295502202083w. PMID: 36564844.
- **Taiwan:** Lin HW, Li CI, Lin FJ, Chang JY, Gau CS, Luo N, Pickard AS, Ramos Goñi JM, Tang CH, Hsu CN. Valuation of the EQ-5D-5L in Taiwan. *PLoS One*. 2018; 13(12):: e0209344. doi:10.1371/journal.pone.0209344. PMID: 30586400.
- **Thailand** Pattanaphesaj J, Thavorncharoensap M, Ramos-Goñi JM, Tongsiri S, Ingsrisawang L, Teerawattananon Y. The EQ-5D-5L Valuation study in Thailand. *Expert Review of Pharmacoeconomics & Outcomes Research*. 2018 Oct;18(5):551-558. doi:10.1080/14737167.2018.1494574. PMID: 29958008.
- **Trinidad\_and\_Tobago** Bailey H, Jonker MF, Pullenayegum E, Rencz F, Roudijk B. The EQ-5D-5L valuation study for Trinidad and Tobago. *Health Qual Life Outcomes*. 2024 Jul 2;22(1):51. doi:10.1186/s12955024022667. PMID: 38956543.
- **UAE** Al Sayah F, Roudijk B, El Sadig M, Al Mannaei A, Farghaly MN, Dallal S, Kaddoura R, Metni M, Elbarazi I, Kharroubi SA. A Value Set for the EQ-5D-5L for United Arab Emirates. *Value Health*. 2025 Jan 27:S1098-3015(25)00021-X. doi:10.1016/j.jval.2025.01.003. Epub ahead of print. PMID: 39880198.
- **Uganda** Yang F, Katumba KR, Roudijk B, Yang Z, Reville P, Griffin S, Ochanda PN, Lamorde M, Greco G, Seeley J, Sculpher M. Developing the EQ-5D-5L Value Set for Uganda Using the 'Lite' Protocol. *Pharmacoeconomics*. 2021 Nov 29:1–13. doi:10.1007/s4027302101101x. PMID: 34841471.
- **UK** Rowen D, Mukuria C, Bray N, Carlton J, Longworth L, Meads D, Oluboyede Y, O'Neill C, Yang Y. A UK value set for the EQ-5D-5L. *Value Health*. 2026 Mar 24:S1098-3015(26)00110-5. doi:10.1016/j.jval.2026.03.008. Epub ahead of print. PMID: 41887403.
- **Uruguay:** Augustovski F, Rey-Ares L, Irazola V, Garay OU, Gianneo O, Fernández G, Morales M, Gibbons L, Ramos-Goñi JM. An EQ-5D-5L value set based on Uruguayan population preferences. *Qual Life Res*. 2016 Feb;25(2):323-33. doi:10.1007/s1113601510864. PMID: 26242249.
- **USA:** Pickard AS, Law EH, Jiang R, Pullenayegum E, Shaw JW, Xie F, Oppe M, Boye KS, Chapman RH, Gong CL, Balch A, Busschbach JJV. United States Valuation of EQ-5D-5L

Health States Using an International Protocol. *Value in Health*. 2019 Aug;22(8):931-941. doi:10.1016/j.jval.2019.02.009. PMID: 31426935.

- **Vietnam:** Mai VQ, Sun S, Minh HV, Luo N, Giang KB, Lindholm L, Sahlen KG. An EQ-5D-5L Value Set for Vietnam. *Qual Life Res*. 2020;29(7):1923-1933. doi:10.1007/s11136020-024697. PMID: 32221805.
- **WePP:** Olsen JA, Lamu AN, Cairns J. In search of a common currency: A comparison of seven EQ-5D-5L value sets. *Health Econ*. 2018 Jan;27(1):39-49. doi:10.1002/hec.3606. Epub 2017 Oct 24. PMID: 29063633.

Y3L

*EQ-5D-Y-3L value set data*

### Description

EQ-5D-Y-3L value set calculation data for Australia, Belgium, Brazil, China, Germany, Hungary, Indonesia, Japan, Netherlands, Slovenia and Spain.

### Usage

Y3L

### Format

An object of class `data.frame` with 14 rows and 13 columns.

### Source

- **Australia:** Pan T, Roudijk B, Devlin N, Mulhern B, Norman R. An Australian Value Set for the EQ-5D-Y-3L. *Health Qual Life Outcomes*. 2025 Jul 15;23(1):72. doi:10.1186/s12955-02502402x. PMID: 40660259.
- **Belgium:** Dewilde S, Roudijk B, Tollenaar NH, Ramos-Goñi JM. An EQ-5D-Y-3L Value Set for Belgium. *Pharmacoeconomics*. 2022 Nov 1:1–12. doi:10.1007/s4027302201187x. Epub ahead of print. PMID: 36316544.
- **Brazil:** Espirito Santo CM, Miyamoto GC, Santos VS, Ben ÂJ, Finch AP, Roudijk B, de Jesus-Moraleida FR, Stein AT, Santos M, Yamato TP. Estimating an EQ-5D-Y-3L Value Set for Brazil. *Pharmacoeconomics*. 2024 Jul 2. doi:10.1007/s40273024014049. Epub ahead of print. PMID: 38954389.
- **China:** Yang Z, Jiang J, Wang P, Jin X, Wu J, Fang Y, Feng D, Xi X, Li S, Jing M, Zheng B, Huang W, Luo N. Estimating an EQ-5D-Y-3L Value Set for China. *Pharmacoeconomics*. 2022 Nov 18. doi:10.1007/s40273022012169. Epub ahead of print. PMID: 36396878.
- **Germany:** Kreimeier S, Mott D, Ludwig K, Greiner W; IMPACT HTA HRQoL Group. EQ-5D-Y Value Set for Germany. *Pharmacoeconomics*. 2022 May 23:1–13. doi:10.1007/s40273-022011439. Epub ahead of print. PMID: 35604633.
- **HongKong:** Wong EL, Wang K, Wong AY, Cheung AW, Wong CKH, Luo N, Rivero-Arias O, Yeoh EK. Value set of EQ-5D-Y-3L for Hong Kong. *Health Qual Life Outcomes*. 2026 Mar 23. doi:10.1186/s1295502602522y. Epub ahead of print. PMID: 41872908.

- **Hungary:** Rencz F, Ruzsa G, Bató A, Yang Z, Finch AP, Brodszky V. Value Set for the EQ-5D-Y-3L in Hungary. *Pharmacoeconomics*. 2022 Sep 20:1–11. doi:10.1007/s40273022-011902. Epub ahead of print. PMID: 36123448.
- **Indonesia:** Fitriana TS, Roudijk B, Purba FD, Busschbach JJV, Stolk E. Estimating an EQ-5D-Y-3L Value Set for Indonesia by Mapping the DCE onto TTO Values. *Pharmacoeconomics*. 2022 Nov 9. doi:10.1007/s40273022012101. Epub ahead of print. PMID: 36348155.
- **Japan:** Shiroiwa T, Ikeda S, Noto S, Fukuda T, Stolk E. Valuation Survey of EQ-5D-Y Based on the International Common Protocol: Development of a Value Set in Japan. *Med Decis Making*. 2021 Mar 23:272989X211001859. doi:10.1177/0272989X211001859. Epub ahead of print. PMID: 33754886.
- **Netherlands:** Roudijk B, Sajjad A, Essers B, Lipman S, Stalmeier P, Finch AP. A Value Set for the EQ-5D-Y-3L in the Netherlands. *Pharmacoeconomics*. 2022 Oct 10:1–11. doi:10.1007/s40273022011920. Epub ahead of print. PMID: 36216977.
- **Slovenia:** Prevolnik Rupel V, Ogorevc M; IMPACT HTA HRQoL Group. EQ-5D-Y Value Set for Slovenia. *Pharmacoeconomics*. 2021 Feb 10. doi:10.1007/s40273020009944. Epub ahead of print. PMID: 33565048.
- **Spain:** Ramos-Goñi JM, Oppe M, Estévez-Carrillo A, Rivero-Arias O; IMPACT HTA HRQoL Group. Accounting for Unobservable Preference Heterogeneity and Evaluating Alternative Anchoring Approaches to Estimate Country-Specific EQ-5D-Y Value Sets: A Case Study Using Spanish Preference Data. *Value Health*. 2022 May;25(5):835-843. doi:10.1016/j.jval.2021.10.013. Epub 2021 Dec 6. PMID: 35500952.
- **USA:** Pickard AS, Nazari JL, Ramos-Goñi JM, Gu NY. Valuing child health: an EQ-5D-Y-3L value set for the United States. *Value Health*. 2025 Nov 26:S1098-3015(25)05689-X. doi:10.1016/j.jval.2025.11.003. Epub ahead of print. PMID: 41314415.

# Index

## \* datasets

- CW, [3](#)
  - DSU3L, [4](#)
  - DSU5L, [4](#)
  - RCW, [22](#)
  - RCWVH, [22](#)
  - TTO, [24](#)
  - VAS, [28](#)
  - VT, [30](#)
  - Y3L, [34](#)
- CW, [3](#)
- DSU3L, [4](#)
- DSU5L, [4](#)
- eq5d, [5](#)
- eq5d3l, [7](#)
- eq5d5l, [7](#)
- eq5dcf, [8](#)
- eq5dcw, [9](#)
- eq5dds, [10](#)
- eq5dmap, [5](#), [11](#)
- eq5drcw, [12](#)
- eq5dy, [12](#)
- eq5dy3l, [13](#)
- get\_all\_health\_states, [14](#)
- get\_dimensions\_from\_health\_states, [14](#)
- get\_health\_states\_from\_dimensions, [15](#)
- getDimensionsFromHealthStates  
(get\_dimensions\_from\_health\_states),  
[14](#)
- getHealthStates  
(get\_all\_health\_states), [14](#)
- getHealthStatesFromDimensions  
(get\_health\_states\_from\_dimensions),  
[15](#)
- hpg, [16](#)
- hsdi, [17](#)
- lfs, [18](#)
- lss, [18](#)
- pchc, [19](#)
- ps, [20](#)
- RCW, [22](#)
- RCWVH, [22](#)
- runApp, [24](#)
- shannon, [23](#)
- shiny\_eq5d, [24](#)
- splitHealthStates  
(get\_dimensions\_from\_health\_states),  
[14](#)
- TTO, [24](#)
- valuesets, [27](#)
- VAS, [28](#)
- VT, [30](#)
- Y3L, [34](#)