

# Package ‘evidenceratio’

May 8, 2026

**Type** Package

**Title** Likelihood-Based Evidence Ratios for Classical Statistical Tests

**Version** 0.1.0

**License** MIT + file LICENSE

**Language** en-GB

**Description** Implements likelihood-based evidence ratios for unified reporting in classical statistical testing. The package reports effect estimates, uncertainty intervals, and likelihood ratios on the log 10 scale derived from a single statistical model. It applies to standard normal mean tests, contingency tables, and regression coefficients, and provides a direct evidential measure while retaining classical error guarantees. For the Evidence Ratio Reporting Standard see Lawless (2026)  [<doi:10.5281/zenodo.18261076>](https://doi.org/10.5281/zenodo.18261076).

**Encoding** UTF-8

**Depends** R (>= 4.0)

**Imports** stats

**Suggests** testthat (>= 3.1.0), waldo (>= 0.5.0), knitr, rmarkdown, ggplot2

**VignetteBuilder** knitr

**RoxygenNote** 7.3.2

**NeedsCompilation** no

**Author** Dylan Lawless [aut, cre, cph] (ORCID:  [<https://orcid.org/0000-0001-8496-3725>](https://orcid.org/0000-0001-8496-3725))

**Maintainer** Dylan Lawless <admin@switzerlandomics.ch>

**Repository** CRAN

**Date/Publication** 2026-01-21 20:00:08 UTC

## Contents

evidence\_test . . . . . 2

**Index** . . . . . 3

---

evidence_test	<i>Likelihood-based evidence ratio test</i>
---------------	---

---

**Description**

Computes an effect estimate, a Wald-style uncertainty interval, and a likelihood-based evidence ratio (log10 scale) from a single statistical model.

**Usage**

```
evidence_test(...)
```

**Arguments**

... Arguments defining the data and model.

**Value**

An object of class `evidence_result`.

**Examples**

```
x <- sleep$extra[sleep$group == 1]
evidence_test(x)

tbl <- matrix(c(30, 70, 20, 80), nrow = 2)
evidence_test(tbl)

evidence_test(mpg ~ wt, data = mtcars, coef = "wt")
```

# Index

evidence\_test, [2](#)