

# Package ‘exvatools’

May 8, 2026

**Type** Package

**Title** Value Added in Exports and Other Input-Output Table Analysis  
Tools

**Version** 1.0.0

**Description** Analysis of trade in value added with international input-output tables. Includes commands for easy data extraction, matrix manipulation, decomposition of value added in gross exports and calculation of value added indicators, with full geographical and sector customization. Decomposition methods include Borin and Mancini (2023) <[doi:10.1080/09535314.2022.2153221](https://doi.org/10.1080/09535314.2022.2153221)>, Miroudot and Ye (2021) <[doi:10.1080/09535314.2020.1730308](https://doi.org/10.1080/09535314.2020.1730308)>, Wang et al. (2013) <<https://econpapers.repec.org/paper/nbrnberwo/19677.htm>> and Koopman et al. (2014) <[doi:10.1257/aer.104.2.459](https://doi.org/10.1257/aer.104.2.459)>.

**License** GPL-3

**Depends** R (>= 3.5)

**Imports** cli, data.table, methods, openxlsx, reshape2, utils

**Suggests** knitr, rmarkdown, testthat (>= 3.0.0)

**VignetteBuilder** knitr

**Config/testthat/edition** 3

**Encoding** UTF-8

**Language** en-US

**LazyData** true

**RoxygenNote** 7.3.2

**NeedsCompilation** no

**Author** Enrique Feas [aut, cre] (ORCID:  
<<https://orcid.org/0000-0002-9431-6051>>)

**Maintainer** Enrique Feas <efeas@runbox.com>

**Repository** CRAN

**Date/Publication** 2026-01-16 16:30:07 UTC

## Contents

bkd	3
bkdiag	3
bkoffd	4
bkt	4
bktt	5
csums	6
diagcs	7
diagrs	7
dmult	8
get_data	9
get_exvadec_bkdown	10
get_geo_codes	11
get_sec_codes	12
get_va_exgr	12
get_va_exgry	14
get_va_fd	15
get_xmatrix	16
hmult	17
iciotest_data	17
info_geo	18
info_sec	19
make_custom_wio	19
make_exvadec	20
make_exvadir	23
make_wio	24
meld	26
multd	27
print.exvadec	28
print.exvadir	28
print.wio	29
rsums	29
set_zero	30
sumgcols	31
sumgrows	31
summary.exvadec	32
summary.exvadir	32
summary.wio	33
sumncol	33
sumnrow	34
txt_from_ids	34
wiodtest_data	35

## Index

36

---

bkd	<i>Get block diagonal matrix</i>
-----	----------------------------------

---

**Description**

Produces a block diagonal matrix version of block matrix, i.e., a matrix in which the diagonal blocks are non-zero and the off-diagonal blocks are zero

**Usage**

```
bkd(df)
```

**Arguments**

df                    A block matrix with named rows and columns. Names of countries and sectors are automatically identified.

**Value**

Block diagonal version of the original matrix.

**Examples**

```
wio <- make_wio("wiodtest", quiet = TRUE)
# Block diagonal version of Y (coincides with Yd)
bkd(wio$Y)
```

---

bkdiag	<i>Diagonalize blocks of a block matrix</i>
--------	---

---

**Description**

Diagonalize each block of a block matrix, so sectors of origin become also sectors of destination. Blocks of dimension NxN will remain NxN, but diagonalized, and blocks of dimensions Nx1 will be expanded to NxN and then diagonalized.

**Usage**

```
bkdiag(df)
```

**Arguments**

df                    A block matrix with named rows and columns.

**Value**

Matrix df with blocks of dimension NxN diagonalized.

**Examples**

```
wio <- make_wio("wiodtest", quiet = TRUE)
# Normal version of matrix Y
wio$Y
# Diagonal version (show first columns only)
bkdiag(wio$Y)[, 1:6]
```

---

bkoffd	<i>Get block off-diagonal matrix</i>
--------	--------------------------------------

---

**Description**

Produces a block off-diagonal matrix version of block matrix, i.e., a matrix in which the diagonal blocks are zero and the off-diagonal blocks are non-zero.

**Usage**

```
bkoffd(df)
```

**Arguments**

`df` A block matrix with named rows and columns. Names of countries and sectors are automatically identified.

**Value**

Block off-diagonal version of the original matrix.

**Examples**

```
wio <- make_wio("wiodtest", quiet = TRUE)
# Block off-diagonal version of Y (coincides with Ym)
bkoffd(wio$Y)
```

---

bkt	<i>Block transpose matrix</i>
-----	-------------------------------

---

**Description**

Transpose a matrix by blocks, so  $\text{block}(s, r)$  becomes  $\text{block}(r, s)$ , but elements within each block are not transposed.

**Usage**

```
bkt(df)
```

**Arguments**

`df` A block matrix with named rows and columns. Names of countries and sectors are automatically identified.

**Details**

`bkt()` takes a matrix of  $c1 \times c2$  blocks where each block has a dimension  $s1 \times s2$  and transposes its blocks. Block B21 becomes B12, B31 becomes B13, etc., but blocks are not altered internally. For instance, a matrix with rows 5 exporting countries of 4 sectors each and columns with 3 importing countries with 2 aggregated sectors, i.e., a  $(5 \times 4) \times (3 \times 2)$ , matrix will become a  $(3 \times 4) \times (5 \times 2)$  matrix. The rows will now show the importing countries and the sectors they import from, and the columns will show the the exporting countries and the sectors they export from.

**Value**

Block transposed version of `df`.

**See Also**

[bktt\(\)](#).

**Examples**

```
wio <- make_wio("wiodtest", quiet = TRUE)
# Matrix Ym (exports of final products)
wio$Ym
# Block transposed version of Ym (imports of final products)
bkt(wio$Ym)
```

---

**bktt**

*Block transpose matrix with transposed blocks*

---

**Description**

Block transpose matrix and then transpose each block. `block(s, r)` is transformed into `block(r, s)` and then internally transposed. This is not equivalent to directly transpose the matrix.

**Usage**

```
bktt(df)
```

**Arguments**

`df` A square block matrix with named rows and columns. Names of countries and sectors are automatically identified. Unlike `bkt()`, `bktt()` can only be used with square block matrices with  $N \times N$  blocks (with row and column names in the form AUS\_01T02, AUS\_05, etc.)

**Value**

Block transposed version of `df` with elements transposed.

**See Also**

[bkt\(\)](#).

**Examples**

```
wio <- make_wio("wiodtest", quiet = TRUE)
# Block-transpose Z and transpose blocks (show first elements only)
bktt(wio$Z)[1:6, 1:6]
# Note that directly transposing Z produces a different result:
t(wio$Z)[1:6, 1:6]
```

---

csums

*Sum matrix columns and assign name to resulting row*

---

**Description**

Improved version of `colSums()` for matrix output. The sum of columns is kept as a row vector with column names and the resulting row can be named in the same command.

**Usage**

```
csums(df, row_name = NULL)
```

**Arguments**

<code>df</code>	A matrix with named rows and columns.
<code>row_name</code>	String, name to assign to resulting row.

**Value**

A row matrix (with rows and column names)

**Examples**

```
wio <- make_wio("wiodtest", quiet = TRUE)
csums(wio$Y, "TOTAL_Y")
```

---

diagcs	<i>Diagonalize the sums of columns of a matrix</i>
--------	--

---

**Description**

Makes a diagonal matrix with the sums of columns of a matrix.

Diagonalizes the sums of each column of a matrix.

**Usage**

```
diagcs(df)
```

```
diagcs(df)
```

**Arguments**

df                    A matrix with named rows and columns.

**Value**

A diagonal matrix with the sums of columns in the diagonal.

A diagonal matrix with the sums of columns in the diagonal.

**Examples**

```
wio <- make_wio("wiodtest")
diagcs(wio$W %*% wio$Bd)
wio <- make_wio("wiodtest")
diagcs(wio$W %*% wio$Bd)
```

---

diagrs	<i>Diagonalize the sums of each row of a matrix</i>
--------	---

---

**Description**

Diagonalizes the sums of each row of a matrix.

**Usage**

```
diagrs(df)
```

**Arguments**

df                    A matrix with named rows and columns.

**Value**

A diagonal matrix with the sums of rows in the diagonal.

**Examples**

```
wio <- make_wio("wiodtest")
diagrs(wio$Y)
```

---

dmult

*Multiply a diagonal matrix by another matrix*

---

**Description**

Fast multiplication of a diagonal matrix by another matrix, taking taking advantage of the properties of diagonal matrices.

**Usage**

```
dmult(matrix1, matrix2)
```

**Arguments**

matrix1	A diagonal matrix.
matrix2	An ordinary matrix.

**Details**

dmult() will turn matrix1 into a vector and multiply it horizontally by every rows in matrix2. This saves precious computing time.\ The number of rows and columns of the diagonal matrix1 must be equal to the number of rows of matrix1.

**Value**

Product of matrix1 and matrix2.

**See Also**

[multd\(\)](#).

**Examples**

```
wio <- make_wio("wiodtest")
dmult(wio$W, wio$Bd)
```

get\_data

*Get data from different exvatoools objects***Description**

Extracts exporting country and sector and destination data from a specific variable in an exvatoools object.

**Usage**

```
get_data(
  exvatoools_object,
  var,
  exporter,
  sector = "TOTAL",
  importer = "WLD",
  imp_sector = "TOTAL",
  demand_comp = "TOTAL",
  as_num = FALSE
)
```

**Arguments**

exvatoools_object	An exvatoools object (wio, exvadece or exvadir). If it is an ICIO wio, it will be previously melded (i.e., China and Mexico will be grouped).
var	String for the selected variable included in the exvatoools object: "VA", "X", "EXGR", "VAX", "DC", "DVA", etc.
exporter	String vector with codes of the exporting countries.\ If the exvadece object includes only one country or country group, exporter is not required (data can only be extracted for that country).\ If exporter is not specified and it is an exvadir object, the exporter will be considered the world ("WLD"), as by definition exporters in exvadir objects are the countries of origin of value added. \ To include a vector with several exporters (e.g., c("ESP", "FRA")) the exvadece object must have been created with the option exporter = "all" in the command <code>make_exvadece()</code> . <code>get_data()</code> will then produce matrices horizontally bound.
sector	A character vector with sector codes, e.g. TOTAL, AGF, MANUF, c("TOTAL", "AGF", "MANUF", "SERVS"). Available codes can be checked with <code>info_sec()</code> .
importer	String vector with importing country or country group codes, e.g. "WLD", "ESP", "EU27", c("WLD", "EU27", "NONEU27"). Available codes can be checked with <code>info_geo()</code> .\ Please note that country groups will not show the strict values of "DVA", "VAX" etc. but an average value of the countries included in that group. To obtain the specific "DVA", "VAX", etc. for a group, an exvadece object must be specifically created for that country group.\ Of course, variables that do not require to exclude double-counting, like "EXGR", "DC" or "FC" will be the same in both cases, so no specific exvadece object will be required.

imp_sector	A character vector with sector codes, e.g. TOTAL, AGF, MANUF, c("TOTAL", "AGF", "MANUF", "SERVS"). Available codes can be checked with <code>info_sec()</code> .
demand_comp	A character vector of demand components, e.g., "HFCE", c("HFCE", "GCFC"). Only valid for wio objects.
as_num	Boolean specifying whether to present the data with names of rows and columns or just as a numeric vector or matrix. This option is useful when creating data frames composed of several <code>get_data()</code> commands, as in that case dimensions need to be controlled.

**Value**

A two-dimensional matrix with sector and geographical data of a variable.

**Examples**

```
wio <- make_wio("wiodtest")
get_data(wio, "EXGR", exporter = "ESP", sector = "MANUF")
get_data(wio, "EXGR", exporter = "ESP", sector = c("TOTAL", "MANUF", "SRVWC"),
         importer = c("USA", "FRA"))
```

---

get\_exvadec\_bkdown      *Get a summary decomposition of value added in exports*

---

**Description**

Detail from an exvadec decomposition of a country by sector and by destination

**Usage**

```
get_exvadec_bkdown(
  exvadec_object,
  exporter = "WLD",
  sector = "TOTAL",
  importer = "WLD"
)
```

**Arguments**

exvadec_object	An exvadec object created by <code>make_exvadec()</code> .
exporter	A character string with the code for the exporting country
sector	Character code of sector
importer	Character code of importer

**Value**

Print result to console

## Examples

```
wio <- make_wio("wiodtest", quiet = TRUE)
exvadec <- make_exvadec(wio, quiet = TRUE)
get_exvadec_bkdown(exvadec, "ESP", "MANUF")
```

---

get_geo_codes	<i>Get the ISO3 codes of standard country groups</i>
---------------	--

---

## Description

Gets the ISO3 codes of standard country groups available for the different input-output tables. The resulting format can be used to extract elements of a matrix using `grep`.

## Usage

```
get_geo_codes(geo_id, wiotype = "icio2025", icio_extend = FALSE)
```

## Arguments

geo_id	String, country group id. Available geo_ids for a specific input-output table can be obtained with the command <code>info_geo()</code> .
wiotype	String, type of input-output table.
icio_extend	Boolean. If TRUE and the input-output table is of type icio extended, codes will also include the extended elements for China (CN1, CN2) and Mexico (MX1, MX2).

## Value

Codes of country/countries ready to `grep`, e.g. AUS|ARG|BEL

## Examples

```
# Get the codes of EU27 countries
get_geo_codes("EU27", "icio2025")
# Gets the codes for NAFTA and extends MEX to MX1|MX2
get_geo_codes("NAFTA", "icio2025", icio_extend = TRUE)
```

---

get\_sec\_codes                      *Get the ISO3 codes of standard sector groups*

---

### Description

Gets the ISO3 codes of standard sector groups available for the different input-output tables. The resulting format can be used to extract elements of a matrix using `grep`.

### Usage

```
get_sec_codes(sector_id, wiotype = "icio2025", remove_letter = FALSE)
```

### Arguments

sector_id	String, sector or sector group code. Available sector_ids can be obtained with the command <code>info_sec()</code> .
wiotype	String, type of input-output database.
remove_letter	Boolean. If TRUE, the initial letter from the sector code will be removed: D20 or C20 will become _20. This is needed to <code>grep</code> rows and columns, as country-sector naming follows the pattern AUS_01T02, i.e., without the initial letter D or C.

### Value

Codes of sector ready to `grep`, e.g. `_01|_02|_03`.

### Examples

```
# Get sector codes for manufactures in the icio2025 database.
get_sec_codes("MANUF", "icio2025")
# Get sector codes for services (including construction)
get_sec_codes("SRVWC", "icio2025")
# Get sector codes for manufacturing, removing the first letter so
# the result can be used with `grep` to select specific sectors from
# a matrix
get_sec_codes("MANUF", "icio2025", remove_letter = TRUE)
```

---

get\_va\_exgr                      *Detailed origin and destination of value added in gross exports*

---

### Description

Origin of value added in gross exports. It combines a `make_exvadir()` command and a `get_data()` command to obtain a result equivalent to the OECD's Origin of Value added in Gross Exports EXGR\_BSCI, but with much more flexible geographical and sector options.

## Usage

```
get_va_exgr(  
  wio_object,  
  va_type = "FC",  
  geo_orig = "WLD",  
  sec_orig = "TOTAL",  
  geo_export,  
  sec_export = "TOTAL",  
  as_numeric = TRUE  
)
```

## Arguments

wio_object	An object of class wio.
va_type	Character string specifying the output as domestic content ("DC"), foreign content ("FC") or total content ("TC") from the perspective of the exporter. As origin of value added is specified, this is normally redundant, but in the case of exporter "WLD", the domestic and foreign content is considered as the sum of domestic/foreign contents of all individual countries. For groups (such as "EU27") domestic/foreign means value added from within/outside the group.
geo_orig	Character string with code of country or country group of origin of value added
sec_orig	Character string with code of sector or sector group of origin of value added. Combinations (with " ") and exceptions (with "x") are allowed.
geo_export	Character string with code of exporting country or country group.
sec_export	Character string with code of exporting sector or sector group. Combinations (with " ") and exceptions (with "x") are allowed.
as_numeric	Boolean specifying whether to return a numeric value or matrix (TRUE, default) or a data frame (default for <a href="#">get_data()</a> ).

## Value

A matrix, vector or data frame with export value added data.

## Examples

```
wio <- make_wio("iciotest")  
# Exports of manufactures of Spain using foreign VA from France  
get_va_exgr(wio, "FC", "FRA", "TOTAL", "ESP", "MANUF")
```

get\_va\_exgry

*Detailed origin and final absorption of value added in gross exports***Description**

Get exports in terms of final absorption by origin of value added and final destination. It combines a `make_exvadir()` command and a `get_data()` command to obtain a result equivalent to that of the OECD's Gross Exports by Origin of Value Added and Final destination (FD\_EXGR\_VA, FD\_EXGRFNL\_VA and FD\_EXGRINT\_VA), but with much more flexible geographical and sector options.

**Usage**

```
get_va_exgry(
  wio_object,
  va_type = "TC",
  flow_type = "EXGRY",
  geo_orig = "WLD",
  geo_export,
  sec_export = "TOTAL",
  geo_fd = "WLD",
  as_numeric = TRUE
)
```

**Arguments**

wio_object	An object of class wio.
va_type	String for domestic content ("DC"), foreign content ("FC") or total content ("TC") from the perspective of the exporter. As origin of value added is specified, this is normally redundant, but in the case of exporter "WLD", the domestic and foreign content is considered as the sum of domestic/foreign contents of all individual countries. For groups (such as "EU27") domestic/foreign means value added from within/outside the group.
flow_type	String specifying the type of flow in terms of absorption. It can be total gross exports ("EXGRY"), exports of final products ("EXGRY_FIN") or exports of intermediates ("EXGRY_INT").
geo_orig	Character string with code of country or country group of origin of value added.
geo_export	Character string with code of exporting country or country group.
sec_export	Character string with code of exporting sector or sector group. Combinations (with " ") and exceptions (with "x") are allowed.
geo_fd	String character with code of country or country group of final destination of exports
as_numeric	Boolean. If TRUE (default), returns a numeric value, vector or matrix instead of a data frame (default for <code>get_data()</code> ).

**Value**

A matrix, vector or data frame with data of exports

**Examples**

```
# What part of French value added exported as US final intermediate
# manufactures ends up absorbed by Spain?
wio <- make_wio("iciotest")
get_va_exgry(wio, flow_type = "EXGRY_INT", geo_orig = "FRA",
             geo_export = "USA", sec_export = "MANUF", geo_fd = "ESP")
```

---

get\_va\_fd

*Value added induced by final demand*


---

**Description**

Details of both geographical and sector origin of the VA induced by final demand. Equivalent to the OECD's Origin of Value added in Final Demand (FDVA\_BSCI), but with much more flexible geographical and sector options.

**Usage**

```
get_va_fd(
  wio_object,
  va_type = "TOTAL",
  geo_orig = "WLD",
  sec_orig = "TOTAL",
  geo_fd = "WLD",
  sec_fd = "TOTAL",
  intra = FALSE
)
```

**Arguments**

wio_object	A wio object
va_type	String character with the type of VA induced (VA domestically absorbed "VAD" or exported "VAX") or the equivalent inducing VA (domestic final demand "DFD" or foreign final demand "FFD"). That is, "VAD" and "DFD" will produce the same result, and so will "VAX" and "FFD". Default is both, i.e. "TOTAL" VA o total demand.
geo_orig	String character with code of country or country group generating value added, i.e., exporter. Default is "all")
sec_orig	String character with code of sector or sector group generating value added. Default: "all")
geo_fd	String character with code of country (or country group) of final demand (inducing the generation of VA)

sec_fd	String character with code of sector (or sector group) of final demand (including the generation of VA)
intra	Boolean for inclusion of intra-regional exports (default: FALSE)

**Value**

Matrix with source and destination of value added.

**Examples**

```
wio <- make_wio("iciotest")
# Get USA's total VA in services induced by China's manufacturing
get_va_fd(wio, geo_orig = "USA", sec_orig = "SRVWC",
          geo_fd = "CHN", sec_fd = "MANUF")
# Get world VA exported (VAX), i.e., world VA induced by the rest of
# the world not domestically absorbed
get_va_fd(wio, "VAX", "WLD", "TOTAL", "WLD", "TOTAL")
```

---

get_xmatrix	<i>Get extraction matrix.</i>
-------------	-------------------------------

---

**Description**

Creates a global extraction matrix Anots of an exporter and its inverse Bnots.

**Usage**

```
get_xmatrix(
  wio,
  exporter,
  perim = "country",
  partner = "WLD",
  sector = "TOTAL",
  inverse = TRUE
)
```

**Arguments**

wio	A class wio object
exporter	String, code of country or country group
perim	String: "country" for country perspective and "WLD" for world perspective.
partner	String: code of country or country group for bilateral perspectives (only with country).
sector	Character string: code of sector or sector group for sector perspectives (only with country).
inverse	Boolean, if TRUE returns the global inverse extraction matrix Bnots, if FALSE just the global extraction matrix Anots.

**Value**

The global (inverse) extraction matrix of the specified exporter.

---

hmult	<i>Hadamard product of matrices</i>
-------	-------------------------------------

---

**Description**

Hadamard product, i.e., element by element product of matrix df1 and matrix df2 (by blocks). Both matrices must be block matrices, and the number and dimension of blocks in matrix df1 and df2 must be compatible.

**Usage**

```
hmult(df1, df2)
```

**Arguments**

df1	A block matrix with named rows and columns (country/sector)
df2	A block matrix with named rows and columns (country/sector)

**Details**

In a Hadamard product, matrices are multiplied block by block, i.e., `block(s, r) %** block(s, r)`.

**Value**

Hadamard product of the two matrices.

---

iciotest_data	<i>ICIO-type input-output table example data</i>
---------------	--

---

**Description**

An example of an ICIO-type input-output table, with rows for MEX and CHN disaggregated into MX1 and MX2 and CN1 and CN2, respectively.

**Usage**

```
iciotest_data
```

**Format**

A matrix of 30 by 42, composed of two sub-matrices:

- Sub-matrix Z, intermediate inputs: 30 by 30 (10 countries with 3 sectors each). 4 of those 10 are the extensions of CHN and MEX).
- Sub-matrix Yfd, final demand: 30 by 12 (10 countries with 3 sectors each in rows, 6 countries by 2 demand components each in columns).

**Source**

Data were randomly generated with an uniform distribution.

---

info_geo	<i>Show available countries and country groups in a specific Input-Output table</i>
----------	---

---

**Description**

Show available countries and country groups in a specific Input-Output table

**Usage**

```
info_geo(wiotype = "icio2025", lang = "en")
```

**Arguments**

wiotype	Character string specifying the world input-output database.
lang	Character string for the language of the descriptive text: "eng" for English (default) and "es" for Spanish.

**Value**

Prints country codes and descriptive text in the console.

**Examples**

```
info_geo("icio2025")
```

---

info_sec	<i>Show available sectors and sector groups included in a specific Input-Output table</i>
----------	---

---

**Description**

Show available sectors and sector groups included in a specific Input-Output table

**Usage**

```
info_sec(wiotype = "icio2025", lang = "en")
```

**Arguments**

wiotype	Character string specifying the world input-output database
lang	Character string for the language of the descriptive text: eng for English (default) and es for Spanish.

**Value**

Prints ids, sector codes and descriptive text

**Examples**

```
info_sec("icio2025")
```

---

make_custom_wio	<i>Make standard world input-output matrices from custom data</i>
-----------------	---

---

**Description**

Creates a list object of class wio containing the typical international input-output matrices in a standardized format, as well as a list of code names (countries, sectors and demand components) and a list of dimensions (number of countries, sectors and demand components), using custom data.

**Usage**

```
make_custom_wio(
  df,
  g_names,
  n_names = NULL,
  fd_names = NULL,
  year = NULL,
  quiet = FALSE
)
```

**Arguments**

df	A data frame or matrix containing data for intermediate inputs and final demand.
g_names	A string vector with names of countries.
n_names	A string vector with names of sectors. If missing, sectors will be S01, S02, etc. If just one sector, it will be named TOTAL.
fd_names	A string vector with names of final demand components. If missing, demand components will be FD1, FD2, etc. If just one, it will be named FD.
year	Integer. If missing, the current year will be used.
quiet	Boolean, if TRUE, the function will produce a silent output.

**Details**

make\_custom\_wio() creates a wio from custom input-output data provided as a single matrix of dimension  $G \times N \times G \times FD$ , i.e., the matrix  $Z$  of intermediate inputs (dimension  $G \times N \times G \times N$ ) bound with the matrix  $Y_{fd}$  of final demand (dimension  $G \times N \times G \times FD$ ). The matrices of total output  $X$  and value added  $VA$  will be automatically generated, so should not be included. Data must be exclusively numeric.

A string vector with the names of countries is required. Number of countries will be calculated from this vector. Names for sectors and final demand components can be provided or will otherwise be automatically generated. All names must be composed of alphabetic characters (no special characters are allowed).

**Value**

A wioobject of wiotype = "custom".

**Examples**

```
df <- as.data.frame(matrix(c(19:36), nrow = 3))
wio <- make_custom_wio(df, g_names = c("C01", "C02", "C03"))
```

---

make_exvadec	<i>Decomposition of value added in exports using different methodologies</i>
--------------	--

---

**Description**

Calculates the decomposition of value added in exports of a country or a group of countries according to different methodologies.

**Usage**

```

make_exvadec(
  wio_object,
  exporter = "all",
  method = "bm_src",
  output = "standard",
  quiet = FALSE,
  ...
)

```

**Arguments**

wio_object	An object of class wio (standardized world input-output table) obtained using <code>make_wio()</code> .
exporter	String with a country or a country group code (e.g., "USA", "NAFTA", etc.). The default "all" produces the decomposition of value added in exports for all available individual countries.
method	A string specifying the export VA decomposition method: <ul style="list-style-type: none"> <li>• "bm_src": Borin and Mancini, source-based (2023) (default).</li> <li>• "bm_snk": Borin and Mancini, sink-based (2023).</li> <li>• "wwz": Wang et al. (2013).</li> <li>• "kww": Koopman et al. (2014).</li> <li>• "my": Miroudot and Ye (2021)</li> <li>• "oecd": OECD (not properly a decomposition).</li> </ul>
output	Type of matrices in output: <ul style="list-style-type: none"> <li>• "standard" (default): Shows the domestic content (DC), domestic value added (DVA), the domestic double counting (DDC), the foreign content (FC), the foreign value added (FVA) and the foreign double counting (DDC). The value added exported (VAX) is also produced in most cases, and additional indicators in some cases.</li> <li>• "terms": Shows the basic decomposition terms, whose sum gives the value of gross exports. The number and specification of terms follows the standard in the economic literature: 12 in the Borin and Mancini (2019) decompositions (source and sink), 16 in the Wang et al. (2013) decomposition, 9 in the Koopman et al. (2014) decomposition and just 4 in the Miroudot and Ye (2021) decomposition (as the latter does not expand value added in terms of final absorption). \ Additional outputs: <ul style="list-style-type: none"> <li>• For the "bm_src" (Borin and Mancini, 2023, source-based) method there is an additional "basic" output, without GVC indicators. This output will replace "standard" if targeted perspectives (sector, bilateral or sector-bilateral) are selected.</li> <li>• For the Miroudot and Ye (2021) method there is an additional "terms2" output, when world perspective is selected.</li> <li>• For the "wwz" (Wang et al. ,2013) decomposition there is an additional "terms2" option with an alternative arrangement of the 16 terms.</li> </ul> </li> </ul>

- For the "oecd" decomposition there is an additional "tiva" output with several indicators of the OECD TiVA database.
- quiet Boolean, if TRUE, suppresses all status messages. Default is FALSE, i.e., messages are shown.
- ... Additional parameters for targeted value-added perspectives and for sector breakdown. Targeted value-added perspectives are only available for the "bm\_src" (Borin and Mancini, 2023, source-based) and the "my" (Miroudot and Ye, 2021) decomposition methods. Specific perimeters can be partner, sector and general perimeter. Sector breakdown is only available for the "bm\_src" (Borin and Mancini, 2023, source-based) method, and can be exporting sector and sector of origin of value added.
- partner String, for bilateral perspective. Default is "WLD", but any country or country group code (e.g. "USA" or "EU27") can be specified. In that case, all flows that cross the bilateral geographic perimeter more than once will be considered as double counting.
  - sector String, for sector perspective. Default is "TOTAL", but any sector or sector group code (e.g. "MANUF") can be specified. In that case, all flows that cross the sector perimeter more than once will be considered as double counting. \ The bilateral and sector perspectives can be combined in a bilateral-sector perspective.
  - perim (only for "my", and incompatible with sector or partner specifications). String, for general perimeter of value added. If perim = "WLD" (world) is specified (default is exporting country), then all flows that cross the border of *any* country more than once will be considered as double counting (unlike in the country perspective, where flows are considered as double counting only when they *exit* the border of *the exporting country* more than once). Please note that, when using the world perspective (perim = "WLD") and the terms output (output = "terms", the foreign double counting will be automatically divided into two elements ("terms2").
  - bkdown Sector breakdown (only for "bm\_src"). The default value "exporting" will present a breakdown of value added by exporting sector. The matrix product VB is diagonalized, and the total content of value added (domestic and foreign) will coincide with total gross exports. The alternative value "origin" will show a breakdown by sector of origin of value added. In this case, only matrix V will be diagonalized and the total content of value added will not coincide with total gross exports.

## Value

A list object of class exvadec with several matrices plus metadata.

## References

- Borin, A., & Mancini, M. (2023). Measuring What Matters in Value-Added Trade. *Economic Systems Research*, 1-25.
- Koopman, R., Wang, Z., & Wei, S.-J. (2014). Tracing Value-Added and Double Counting in Gross Exports. *American Economic Review*, 104(2), 459–494.

- Miroudot, S., & Ye, M. (2021). Decomposing Value Added in Gross Exports. *Economic Systems Research*, 33(1), 67–87.
- Wang, Z., Wei, S.-J., & Zhu, K. (2013). Quantifying International Production Sharing at the Bilateral and Sector Levels (NBER Working Paper No. 19677). National Bureau of Economic Research, Inc.

## Examples

```
# Create a test wio
wio <- make_wio("iciotest")
# Make Borin and Mancini (2023) source decomposition for Spain
exvadec <- make_exvadec(wio, exporter = "ESP", method = "bm_src")
# Make Wang et al. (2013) decomposition for all countries
# expressed in the traditional 16 terms
exvadec <- make_exvadec(wio, method = "wwz", output = "terms")
```

---

make_exvadir	<i>Direction (detailed origin and destination) of value added in exports</i>
--------------	--

---

## Description

Direction of value added in exports, i.e., details of both geographical and sector origin of the VA incorporated in exports and of the final destination (in gross terms or in terms of final absorption).

## Usage

```
make_exvadir(
  wio_object,
  exporter,
  va_type = "TC",
  flow_type = "EXGR",
  orig_geo = "all",
  sec_orig = "all",
  via = "any",
  perspective = "exporting",
  intra = FALSE
)
```

## Arguments

wio_object	A wio object
exporter	Country code (or country group code) of exporting country
va_type	Value-added total content ("TC"), domestic content ("DC") or foreign content ("FC") or these indicators excluding double counting ("TVA", "DVA" and "FVA", plus "GVCB").
flow_type	Gross exports ("EXGR") or in terms of final demand: "EXGRY", "EXGRY_FIN", "EXGRY_INT".

orig_geo	Geographical origin of value added (default: "all")
sec_orig	Code of sector of origin of value added (default: "all")
via	Code of intermediate importing country (default: "any")
perspective	Sector breakdown perspective, "exporting" (exporting sector, default) or "origin" (sector of origin). In the former the matrix VB will be diagonalized.
intra	Boolean for inclusion of intra-regional exports (default: FALSE)

### Value

Matrix with source and destination of value added in exports

### Examples

```
wio <- make_wio("wiodtest", quiet = TRUE)
# Foreign services content of value added incorporated in exports of Spain,
# by country of origin and final destination, expressed in gross terms
# (equivalent to OECD TiVA's indicator EXGR_SERV_FVA).
exvadir <- make_exvadir(wio, va = "FC", flow="EXGR", exp="ESP",
                      sec_orig="SRVWC")
summary(exvadir)
```

---

make\_wio

*Make standard world input-output matrices from source files*

---

### Description

Creates a list object of class `wio` containing the typical international input-output matrices in a standardized format, as well as a list of code names (countries, sectors and demand components) and a list of dimensions (number of countries, sectors and demand components). It can use source files from well-known databases or internal data (test data).

### Usage

```
make_wio(wiotype = "icio2025", year = NULL, src_dir = NULL, quiet = FALSE)
```

### Arguments

wiotype	String specifying the name and edition of the input-output tables to be used: * "icio2025" for the 2025 edition of the OECD ICIO tables (1995-2022) and "icio2025s" for the small format of the same edition. The deprecated editions "icio2023" and "icio2023s" (1995-2020), "icio2021" (1995-2018), "icio2018" (1995-2011) and "icio2016" (2005-2015) remain available for literature replication purposes. * "wiod2016" for the 2016 edition of the WIOD tables (2000-2014). The deprecated edition "wiod2013" (1995-2011) remains available for literature replication purposes. * "lrwiod2022" for the 2022 edition of the long-run WIOD (1965-2000), useful for historical analysis. * "figaro2025i" for the 2025 edition of the FIGARO EU Input-Output Tables, industry-by-industry
---------	--

(2010-2023), and "figaro2025p" for the product-by-product version of the same database. The deprecated editions of 2022, 2023 and 2024 remain available for literature replication purposes. \* "mrio2025" for the 2025 edition of the 62-country ADB MRIO tables in current prices (2000, 2007-2023). The deprecated editions of 2024 and 2023 remain available for replication purposes. \* "mrio2025k" for the 2024 edition of the 62-country tables in 2010 constant prices (2000, 2007-2009, 2011-2023). The deprecated versions for 2024 and 2023 remain available. \* "mrio2025x" for the 72-country edition, current prices (2017-2023). The deprecated versions for 2024 and 2023 remain available. \* "mrio2025xx" for the 74-country edition, current prices (2022-2023). \* "iciotest" for an example of an ICIO-type international input-output table (disaggregated for MEX into MX1 and MX2 and for CHN into CN1 and CN2) and "wiodtest" for an example of a WIOD-type international input-output table (not disaggregated). Data for these tables is not real, but these small input-output tables are useful for didactic purposes and to check the functionality of the program.

year	Integer specifying reference year. If NULL (default), the last available year of the specified database will be used.
src_dir	String specifying the source directory where the source file of the international input-output tables is saved, normally as a zip file (containing .csv files, .RData or .xlsx files, see Details). In order for make_wio() to work, these zip files should not be renamed. If src_dir is not specified, make_wio() will look in the working directory.
quiet	Boolean, if TRUE suppress all status messages. Default is FALSE, i.e., messages are shown.

## Details

make\_wio() directly unzips and processes the original source files for the different international input-output tables and returns a list with the traditional matrices, including the coefficient matrix A, the Leontief global inverse matrix B, the Leontief matrix of local inverse matrices Ld and others.

Original source files can be obtained from the OECD's [ICIO web page](#), the University of Groningen's [WIOD web page](#), the [Eurostat web page](#) or the [Asian Development Bank MRIO web page](#)

If source files are used, they must be previously downloaded and placed in an accessible folder in disk, without renaming them. The following name pattern is expected:

- XXXX-XXXX.zip for "icio2025" and "icio2023" (.csv files)
- XXXX-XXXX\_SML.zip for "icio2025s" and "icio2023s" (.csv files)
- ICIO\_XXXX-XXXX.zip for "icio2021" (.csv files)
- ICIO2018\_XXXX.zip for "icio2018" (.csv files)
- ICIO2016\_XXXX.zip for "icio2016" (.csv files)
- WIOTS\_in\_R.zip for "wiod2016" (.RData files)
- WIOTS\_in\_EXCEL.zip for "wiod2013" (.xlsx files). Requires package openxlsx.
- lr\_wiod\_wiot\_final\_filled.csv for "lrwiod2022". Requires packages data.table and reshape2.
- matrix\_eu-ic-io\_ind-by-ind\_2Xed\_XXXX.csv for "figaro202Xi" and matrix\_eu-ic-io\_prod-by-prod\_2Xed\_XX for "figaro202Xp" (.csv files).

- ADB-MRIO[XX]-XXXX\_xxx202X.xlsx for the "mrio202X", "mrio202Xx" and ADB MRIO XXXX, at constant 2010 prices for the "mrio62-202Xk" tables (with some exceptions and updates).

The input-output framework follows the traditional demand model of Leontief (1936), which makes assumptions about the stability of inputs (and therefore value-added) as a proportion of production. This allows production and value-added to be expressed as the result of variations in final demand.

Details about the content of the world input-output object (wio) produced by `make_wio()` can be obtained with the command `summary(wio_object)`.

### Value

A list object of class `wio` including input-output matrices, dimensions, and names.

### See Also

[make\\_custom\\_wio\(\)](#)

### Examples

```
wio <- make_wio("iciotest")
summary(wio)
## Not run:
# The following examples require the previous download of the source
# files in the working directory or in a directory specified by `src_dir`.
wio <- make_wio("icio2025", 2022)
wio <- make_wio("wiod2023", 2020)
wio <- make_wio("wiod2023", 2020, src_dir = "C:/Users/John/R/")

## End(Not run)
```

---

meld	<i>Meld ICIO-type matrix (consolidating China and Mexico sub-components)</i>
------	--

---

### Description

Meld ICIO matrix with extended countries. Melds countries CHN and MEX from their extended versions e.g., CN1 and CN2 are melded into CHN.

### Usage

```
meld(df, meld_rows = TRUE, meld_cols = TRUE)
```

### Arguments

df	A block matrix.
meld_rows	Boolean, true to meld rows.
meld_cols	Boolean, true to meld cols.

**Value**

Melded version of ICIO matrix.

---

multd

*Multiply a matrix by a diagonal matrix*

---

**Description**

Fast multiplication of a matrix by a diagonal matrix, taking advantage of the properties of diagonal matrices.

**Usage**

```
multd(matrix1, matrix2)
```

**Arguments**

matrix1	An ordinary matrix.
matrix2	A diagonal matrix.

**Details**

multd() will turn matrix2 into a vector and multiply it horizontally by every row in matrix1. This saves precious computing time. The number of columns of matrix1 must be equal to the rows and columns of diagonal matrix2.

**Value**

The product of matrix1 and matrix2.

**See Also**

[dmult\(\)](#).

**Examples**

```
wio <- make_wio("wiodtest")
multd(wio$B, wio$E)
```

---

print.exvadec	<i>Print method for exvadec class</i>
---------------	---------------------------------------

---

**Description**

Print method for exvadec class

**Usage**

```
## S3 method for class 'exvadec'  
print(x, ...)
```

**Arguments**

x	An object of class exvadec
...	Additional arguments

**Value**

Printout to console

---

print.exvadir	<i>Print method for exvadir class</i>
---------------	---------------------------------------

---

**Description**

Print method for exvadir class

**Usage**

```
## S3 method for class 'exvadir'  
print(x, ...)
```

**Arguments**

x	An object of class exvadir
...	Additional arguments

**Value**

Printout to console

---

print.wio	<i>Print method for wio class</i>
-----------	-----------------------------------

---

**Description**

Print method for wio class

**Usage**

```
## S3 method for class 'wio'
print(x, ...)
```

**Arguments**

x	An object of class wio
...	Additional arguments

**Value**

Printout to console

---

rsums	<i>Sum matrix rows and assign name to resulting column</i>
-------	--

---

**Description**

Improved version of rowSums() for matrix output. The sum of rows is kept as a column vector with rows names and the resulting column can be named in the same command.

**Usage**

```
rsums(df, col_name = NULL)
```

**Arguments**

df	A matrix with named rows and columns.
col_name	String, name to assign to resulting column.

**Value**

A column matrix (with rows and column names)

**Examples**

```
wio <- make_wio("wiodtest", quiet = TRUE)
rsums(wio$Y, "Y")
```

---

set_zero	<i>Set to zero specific rows and columns of a matrix</i>
----------	--

---

### Description

Sets to zero specific rows and columns of a matrix, to include and exclude specific geographical and sector effects.

### Usage

```
set_zero(df, orig = NULL, dest = NULL, wioType = NULL, invert = FALSE)
```

### Arguments

df	A matrix with named rows and columns.
orig	A vector of integers with position of rows or a list of strings with codes of country and sector of origin.
dest	A vector of integers with position of columns or a list of strings with codes of country and sector of destination.
wioType	String, type of wio. Required if origin or destination is specified with lists of codes.
invert	Boolean: FALSE (default) to set to zero the specified countries and sectors, or TRUE to set to zero the non-specified countries and sectors.

### Value

The same matrix with specific rows and columns set to zero.

### Examples

```
wio <- make_wio("wiodtest")
# Set to zero Spanish exports of intermediates of manufacturing to
# non EU27 countries (for any sector of destination) in the coefficient
# matrix A
set_zero(wio$A, list("ESP", "MANUF"), list("NONEU27", "TOTAL"), "wiodtest")
# Set to zero Spanish exports of intermediates (extraction matrix of Spain)
set_zero(wio$A, list("ESP", "TOTAL"), list("WLDxESP", "TOTAL"), "wiodtest")
```

---

sumgcols	<i>Sum groups of columns of a matrix and name the resulting columns</i>
----------	---

---

**Description**

Groups a matrix by columns, by summing blocks of columns of size n each. Matrix columns should be multiple of n.

**Usage**

```
sumgcols(df, n, col_names = NULL)
```

**Arguments**

df	A matrix with named rows and columns.
n	Integer, specifying the size of each group.
col_names	String vector of length n, with names to assign to the resulting columns.

**Value**

A matrix where each column is the sum of groups of n columns of the original matrix.

**Examples**

```
wio <- make_wio("wiodtest", quiet = TRUE)
sumgcols(wio$Yfd, wio$dims$FD, wio$names$g_names)
```

---

sumgrows	<i>Sum groups of rows of a matrix and name the resulting rows</i>
----------	---

---

**Description**

Groups a matrix by rows, summing blocks of rows of size n each. Matrix rows should be multiple of n.

**Usage**

```
sumgrows(df, n, row_names = NULL)
```

**Arguments**

df	A matrix with named rows and columns.
n	Integer, specifying the size of each group.
row_names	String vector of length n, with names to assign to the resulting rows.

**Value**

A matrix where each row is the sum of groups of n rows of the original matrix.

**Examples**

```
wio <- make_wio("wiodtest", quiet = TRUE)
sumgrows(wio$Y, wio$dims$N, wio$names$g_names)
```

---

summary.exvadec	<i>Summary method for exvadec class</i>
-----------------	---

---

**Description**

Summary method for exvadec class

**Usage**

```
## S3 method for class 'exvadec'
summary(object, ...)
```

**Arguments**

object	An object of class exvadec.
...	Additional arguments.

**Value**

Printout to console

---

summary.exvadir	<i>Summary method for exvadir class</i>
-----------------	---

---

**Description**

Summary method for exvadir class

**Usage**

```
## S3 method for class 'exvadir'
summary(object, ...)
```

**Arguments**

object	An object of class exvadir.
...	Additional arguments.

**Value**

Printout to console

---

summary.wio	<i>Summary method for wio class</i>
-------------	-------------------------------------

---

**Description**

Summary method for wio class

**Usage**

```
## S3 method for class 'wio'
summary(object, ...)
```

**Arguments**

object	An object of class wio
...	Additional arguments

**Value**

Printout to console

---

sumncol	<i>Sum every nth column of a matrix and name the resulting columns</i>
---------	--

---

**Description**

Groups a matrix by columns, summing every Nth column. Matrix should be multiple of N.

**Usage**

```
sumncol(df, N, col_names = NULL)
```

**Arguments**

df	A matrix with named rows and columns.
N	Integer, specifying the resulting number of columns.
col_names	String vector of length N, with names to assign to the resulting columns.

**Value**

A matrix with N columns, where each columns is the sum of every Nth column of the original matrix.

**Examples**

```
wio <- make_wio("wiodtest", quiet = TRUE)
sumncol(wio$Yfd, wio$dims$FD, paste0("WLD", "_", wio$names$fd_names))
```

---

sumnrow	<i>Sum every nth row of a matrix and name the resulting rows</i>
---------	--

---

**Description**

Groups a matrix by rows, summing every Nth row. Matrix should be multiple of N.

**Usage**

```
sumnrow(df, N, row_names = NULL)
```

**Arguments**

df	A matrix with named rows and columns.
N	Integer, specifying the resulting number of rows.
row_names	String vector of length N, with names to assign to the resulting rows.

**Value**

A matrix with N rows, where each row is the sum of every Nth row of the original matrix.

**Examples**

```
wio <- make_wio("wiodtest", quiet = TRUE)
sumnrow(wio$Y, wio$dims$N, paste0("WLD", "_",
  gsub("^D", "", wio$names$n_names)))
```

---

txt_from_ids	<i>Get a descriptive text from a series of id codes</i>
--------------	---

---

**Description**

Gives a descriptive text of id codes from a vector of id codes, like those in rows or columns of exvatools objects.

**Usage**

```
txt_from_ids(
  id_list,
  type = "sec",
  lang = "en",
  ver = "short",
  wiotype = "icio2023"
)
```

**Arguments**

id_list	String or string vector of ids (in rows, columns, etc)
type	Type of id: "sec" for sector ids, "geo" for country or country group ids, "va" for value-added component ids.
lang	Character string for the language of the descriptive text: "eng" for English (default) and "es" for Spanish.
ver	Version: "short" (default) or "long".
wiotype	Type of wio (which determines the codes and text)

**Value**

A string vector with text

**Examples**

```
txt_from_ids("MANUF")
txt_from_ids("MANUF", lang = "es")
```

---

wiodtest_data	<i>WIOD-type input-output table example data</i>
---------------	--

---

**Description**

An example of a WIOD-type input-output table.

**Usage**

```
wiodtest_data
```

**Format**

A matrix of 18 by 30, composed of two sub-matrices:

- Sub-matrix Z, intermediate inputs: 18 by 18 (10 countries with 3 sectors each).
- Sub-matrix Yfd, final demand: 18 by 12 (6 countries with 3 sectors each in rows, 6 countries by 2 demand components each in columns).

**Source**

Data were randomly generated with an uniform distribution.

# Index

## \* datasets

- iciotest\_data, [17](#)
  - wiodtest\_data, [35](#)
- bkd, [3](#)  
bkdiag, [3](#)  
bkoffd, [4](#)  
bkt, [4](#)  
bkt(), [5](#), [6](#)  
bktt, [5](#)  
bktt(), [5](#)
- csums, [6](#)
- diagcs, [7](#)  
diagrs, [7](#)  
dmult, [8](#)  
dmult(), [27](#)
- get\_data, [9](#)  
get\_data(), [12–14](#)  
get\_exvadec\_bkdown, [10](#)  
get\_geo\_codes, [11](#)  
get\_sec\_codes, [12](#)  
get\_va\_exgr, [12](#)  
get\_va\_exgry, [14](#)  
get\_va\_fd, [15](#)  
get\_xmatrix, [16](#)
- hmult, [17](#)
- iciotest\_data, [17](#)  
info\_geo, [18](#)  
info\_geo(), [9](#), [11](#)  
info\_sec, [19](#)  
info\_sec(), [9](#), [10](#), [12](#)
- make\_custom\_wio, [19](#)  
make\_custom\_wio(), [26](#)  
make\_exvadec, [20](#)  
make\_exvadec(), [9](#), [10](#)
- make\_exvadir, [23](#)  
make\_exvadir(), [12](#), [14](#)  
make\_wio, [24](#)  
make\_wio(), [21](#)  
meld, [26](#)  
multd, [27](#)  
multd(), [8](#)
- print.exvadec, [28](#)  
print.exvadir, [28](#)  
print.wio, [29](#)
- rsums, [29](#)
- set\_zero, [30](#)  
sumgcols, [31](#)  
sumgrows, [31](#)  
summary.exvadec, [32](#)  
summary.exvadir, [32](#)  
summary.wio, [33](#)  
sumncol, [33](#)  
sumnrow, [34](#)
- txt\_from\_ids, [34](#)
- wiodtest\_data, [35](#)